

## RF EXPOSURE EVALUATION

FCC ID : 2AFWN-EL022G2

### Standard Requirement

The following FCC Rule Parts and procedures are applicable :

*Part 1.1310 Radiofrequency radiation exposure limits*

*Part 2.1091 Radiofrequency radiation exposure evaluation : Mobile device*

*KDB447498 D01 v06 Mobile and Portable Devices RF Exposure Procedures and Equipment*

*Authorization Policies*

Table 1 below sets forth limits for Maximum Permissible Exposure (MPE) to radiofrequency electromagnetic fields.

*Table 1—Limits for Maximum Permissible Exposure (MPE)*

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
<b>(A) Limits for Occupational/Controlled Exposure</b>				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f <sup>2</sup>	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
<b>(B) Limits for General Population/Uncontrolled Exposure</b>				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f <sup>2</sup>	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			<b>1.0</b>	30

*f = frequency in MHz*

*\* = Plane-wave equivalent power density*



CTK Co., Ltd.  
The First Leader of Global Regulatory Compliance

## CTK Co., Ltd.

(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea  
Tel: +82-31-339-9970 Fax: +82-31-624-9501  
www.e-ctk.com

---

### MPE calculation

$$S = \text{EIRP} / (4\pi R^2)$$

Where      S : Power density  
              EIRP :  $P \times G$   
              P : Maximum transmitter power  
              G : Antenna gain  
              R : distance to the centre of radiation of the antenna

### EUT RF Exposure

P : 1.72 dBm (1.486 mW)  
G : 3.09 (x 2.037)  
R : 20 cm

$$S = 0.0006 \text{ mW/cm}^2$$

### Conclusion

This confirms compliance to the required Radio frequency radiation exposure limit.