

FCC Part 22H & 24E

Measurement and Test Report

For

FACTORYTECH S.A.

Km 16 Via Daule, Guayaquil- Ecuador

FCC ID: 2AFWX-Z5

FCC Rules: FCC Part 22H, FCC Part 24E

Product Description: Mobile phone

Tested Model: Infineum Z5

Report No.: STR15118240I-1

Tested Date: 2015-11-18 to 2015-12-16

Issued Date: 2015-12-17

Tested By: Silin Chen / EMC Manager

Silin Chen

Reviewed By: Suan Su / Engineer

Suan Su

Approved & Authorized By: Jandy So / PSQ Manager

Jandy So

Prepared By:

Shenzhen SEM.Test Technology Co., Ltd.

1/F, Building A, Hongwei Industrial Park, Liuxian 2nd Road,
Bao'an District, Shenzhen, P.R.C. (518101)

Tel.: +86-755-33663308 Fax.: +86-755-33663309 Website: www.semtest.com.cn

Note: This test report is limited to the above client company and the product model only. It may not be duplicated without prior permitted by Shenzhen SEM. Test Technology Co., Ltd.

TABLE OF CONTENTS

1. GENERAL INFORMATION.....	3
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	3
1.2 TEST STANDARDS.....	5
1.3 TEST METHODOLOGY.....	5
1.4 TEST FACILITY.....	5
1.5 EUT SETUP AND TEST MODE.....	6
1.6 TEST EQUIPMENT LIST AND DETAILS.....	7
2. SUMMARY OF TEST RESULTS.....	8
3. RF EXPOSURE.....	9
3.1 STANDARD APPLICABLE.....	9
3.2 TEST RESULT.....	9
4. RF OUTPUT POWER.....	10
4.1 STANDARD APPLICABLE.....	10
4.2 TEST PROCEDURE.....	10
4.3 ENVIRONMENTAL CONDITIONS.....	10
4.4 SUMMARY OF TEST RESULTS/PLOTS.....	11
5. PEAK-TO-AVERAGE RADIO (PAR) OF TRANSMITTER.....	19
5.1 STANDARD APPLICABLE.....	19
5.2 TEST PROCEDURE.....	19
5.3 ENVIRONMENTAL CONDITIONS.....	19
5.4 SUMMARY OF TEST RESULTS.....	20
6. EMISSION BANDWIDTH.....	21
6.1 STANDARD APPLICABLE.....	21
6.2 TEST PROCEDURE.....	21
6.3 ENVIRONMENTAL CONDITIONS.....	21
6.4 SUMMARY OF TEST RESULTS/PLOTS.....	22
7. OUT OF BAND EMISSIONS AT ANTENNA TERMINAL.....	42
7.1 STANDARD APPLICABLE.....	42
7.2 TEST PROCEDURE.....	42
7.3 ENVIRONMENTAL CONDITIONS.....	42
7.4 SUMMARY OF TEST RESULTS/PLOTS.....	43
8. SPURIOUS RADIATED EMISSIONS.....	84
8.1 MEASUREMENT UNCERTAINTY.....	84
8.2 STANDARD APPLICABLE.....	84
8.3 TEST PROCEDURE.....	84
8.4 ENVIRONMENTAL CONDITIONS.....	84
8.5 SUMMARY OF TEST RESULTS/PLOTS.....	84
9. FREQUENCY STABILITY.....	95
9.1 STANDARD APPLICABLE.....	95
9.2 TEST PROCEDURE.....	95
9.3 ENVIRONMENTAL CONDITIONS.....	95
9.4 SUMMARY OF TEST RESULTS/PLOTS.....	96

1. GENERAL INFORMATION

1.1 Product Description for Equipment Under Test (EUT)

Client Information

Applicant: FACTORYTECH S.A.
Address of applicant: Km 16 Via Daule, Guayaquil- Ecuador

Manufacturer: FACTORYTECH S.A.
Address of manufacturer: Km 16 Via Daule, Guayaquil- Ecuador

General Description of EUT:	
Product Name:	Mobile phone
Brand Name:	PIXELA
Model No.:	Infineum Z5
Rated Voltage:	DC 3.8V Li-ion Battery
Battery Capacity:	2100mAh
Device Category:	Portable Device
<i>The EUT Main board support GSM850/PCS1900, WCDMA Band 2/5, LTE Band 2/4/7 function. It is intended for speech, Multimedia Message Service (MMS) transmission. It is equipped with GPRS/EDGE class 12 for GSM850/PCS1900, GPS, Bluetooth and Wi-Fi functions. For more information see the following datasheet</i>	
<i>Note: The test data is gathered from a production sample provided by the manufacturer.</i>	

Technical Characteristics of EUT:	
2G	
Support Networks:	GSM, GPRS, EDGE
Support Band:	GSM850/PCS1900
Uplink Frequency:	GSM/GPRS/EDGE 850: 824~849MHz GSM/GPRS/EDGE 1900: 1850~1910MHz
Downlink Frequency:	GSM/GPRS/EDGE 850: 869~894MHz GSM/GPRS/EDGE 1900: 1930~1990MHz
Max RF Output Power:	GSM850: 32.23dBm, GSM1900: 28.87dBm EDGE850: 26.28dBm, EDGE1900: 24.97dBm
Type of Emission:	GSM850: 255KGXW, GSM1900: 261KGXW EDGE850: 278KG7W, EDGE1900: 254KG7W
Type of Modulation:	GMSK, 8PSK
Type of Antenna:	Integral Antenna
Antenna Gain:	GSM850: -1dBi, GSM1900: 0dBi
GPRS/EDGE Class:	Class 12
3G	
Support Networks:	WCDMA, HSDPA, HSUPA
Support Band:	WCDMA Band 2, WCDMA Band 5
Uplink Frequency:	WCDMA Band 2: 1850~1910MHz WCDMA Band 5: 824~849MHz
Downlink Frequency:	WCDMA Band 2: 1930~1990MHz WCDMA Band 5: 869~894MHz
RF Output Power:	WCDMA Band 2: 22.26dBm, WCDMA Band 5: 23.22dBm
Type of Emission:	WCDMA Band 2: 4M22F9W WCDMA Band 5: 4M20F9W
Type of Modulation:	BPSK
Antenna Type:	Integral Antenna
Antenna Gain:	WCDMA Band 2: 0dBi, WCDMA Band 5: 0dBi

1.2 Test Standards

The following report is prepared on behalf of the FACTORYTECH S.A. in accordance with FCC Part 2 subpart J, FCC Part 22 subpart H and FCC Part 24 subpart E and FCC Part 27 of the Federal Communication Commissions rules.

The objective is to determine compliance with FCC Part 2 subpart J, FCC Part 22 subpart H and FCC Part 24 subpart E and FCC Part 27 of the Federal Communication Commissions rules.

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product, which result in lowering the emission, should be checked to ensure compliance has been maintained.

1.3 Test Methodology

All measurements contained in this report were conducted with ANSI/TIA-603-D: 2010 and ANSI C63.4-2014, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

1.4 Test Facility

- **FCC – Registration No.: 934118**

Shenzhen SEM.Test Technology Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files and the Registration is 934118.

- **Industry Canada (IC) Registration No.: 11464A**

The 3m Semi-anechoic chamber of Shenzhen SEM.Test Technology Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 11464A.

- **CNAS Registration No.: L4062**

Shenzhen SEM.Test Technology Co., Ltd. is a testing organization accredited by China National Accreditation Service for Conformity Assessment (CNAS) according to ISO/IEC 17025. The accreditation certificate number is L4062. All measurement facilities used to collect the measurement data are located at 1/F, Building A, Hongwei Industrial Park, Liuxian 2nd Road, Bao'an District, Shenzhen, P.R.C (518101)

1.5 EUT Setup and Test Mode

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. All testing shall be performed under maximum output power condition, and to measure its highest possible emissions level, more detailed description as follows:

Test Mode List		
Test Mode	Description	Remark
TM1	GSM 850	Low, Middle, High Channels
TM2	GPRS 850	Low, Middle, High Channels
TM3	EDGE 850	Low, Middle, High Channels
TM4	GSM 1900	Low, Middle, High Channels
TM5	GPRS 1900	Low, Middle, High Channels
TM6	EDGE 1900	Low, Middle, High Channels
TM7	WCDMA Band 5	Low, Middle, High Channels
TM8	HSDPA Band 5	Low, Middle, High Channels
TM9	HSUPA Band 5	Low, Middle, High Channels
TM10	WCDMA Band 2	Low, Middle, High Channels
TM11	HSDPA Band 2	Low, Middle, High Channels
TM12	HSUPA Band 2	Low, Middle, High Channels

Testing Configure			
Support Band	Support Standard	Channel Frequency	Channel Number
GSM 850	GSM/GPRS/EDGE	824.2 MHz	128
		836.6 MHz	190
		848.8 MHz	251
PCS 1900	GSM/GPRS/EDGE	1850.2 MHz	512
		1880.0 MHz	661
		1909.8 MHz	810
WCDMA Band 5	WCDMA/HSDPA/HSUPA	826.4 MHz	4132
		836.6 MHz	4183
		846.6 MHz	4233
WCDMA Band 2	WCDMA/HSDPA/HSUPA	1852.4 MHz	9262
		1880.0 MHz	9400
		1907.6 MHz	9538

Note: the transmitter has been tested on the communications mode of GSM, GPRS, EDGE, WCDMA, HSDPA, HSUPA compliance test and record the worst case.

EUT Cable List and Details

Cable Description	Length (M)	Shielded/Unshielded	With Core/Without Core
USB Cable	1.0	Shielded	Without Ferrite
Earphone Cable	1.2	Unshielded	Without Ferrite

Auxiliary Equipment List and Details

Description	Manufacturer	Model	Serial Number
Notebook	Lenovo	E10	LR-63C8R

Special Cable List and Details

Cable Description	Length (M)	Shielded/Unshielded	With Core/Without Core
/	/	/	/

1.6 Test Equipment List and Details

Kind of Equipment	Manufacturer	Type	S/N	Cal Date	Due Date
Equipment list of < Shenzhen SEM.Test Technology Co., Ltd.>					
Test SIM card	-		-	N/A	
GSM Tester	Rohde & Schwarz	CMU200	104036	2015-06-17	2016-06-16
Spectrum Analyzer	Agilent	E4407B	MY41440400	2015-06-17	2016-06-16
Spectrum Analyzer	Agilent	N9020A	US47140102	2015-06-17	2016-06-16
Signal Generator	Agilent	83752A	3610A01453	2015-06-17	2016-06-16
Vector Signal Generator	Agilent	N5182A	MY47070202	2015-06-17	2016-06-16
Power Divider	Weinschel	1506A	PM204	2015-06-17	2016-06-16
Power Divider	RF-Lambda	RFLT4W5M18G	14110400027	2015-06-17	2016-06-16
Spectrum Analyzer	Rohde & Schwarz	FSP	836079/035	2015-06-17	2016-06-16
EMI Test Receiver	Rohde & Schwarz	ESVB	825471/005	2015-06-17	2016-06-16
Amplifier	Agilent	8447F	3113A06717	2015-06-17	2016-06-16
Amplifier	C&D	PAP-1G18	2002	2015-06-17	2016-06-16
Broadband Antenna	Schwarz beck	VULB9163	9163-333	2015-06-17	2016-06-16
Horn Antenna	ETS	3117	00086197	2015-06-17	2016-06-16
Horn Antenna	ETS	3116B	00088203	2015-06-17	2016-06-16

2. SUMMARY OF TEST RESULTS

FCC Rules	Description of Test Item	Result
§ 1.1307, § 2.1093	RF Exposure	Compliant
§ 22.913 (a), § 24.232 (c)	RF Output Power	Compliant
§ 24.51	Peak-to-average Radio (PAR) of Transmitter	Compliant
§ 22.917 (b), § 24.238 (b)	Emission Bandwidth	Compliant
§ 22.917 (a), § 24.238 (a)	Spurious Emissions at Antenna Terminal	Compliant
§ 22.917 (a), § 24.238 (a)	Spurious Radiation Emissions	Compliant
§ 22.917 (a), § 24.238 (a)	Out of Band Emissions	Compliant
§ 22.355, § 24.235	Frequency Stability	Compliant

3. RF Exposure

3.1 Standard Applicable

According to § 1.1307 and § 2.1093, the portable transmitter must comply the RF exposure requirements.

3.2 Test Result

This product complied with the requirement of the RF exposure, please see the SAR report.

4. RF Output Power


4.1 Standard Applicable

According to §22.913(a)(2), The ERP of mobile and portable stations transmitters and auxiliary test transmitters must not exceed 7 Watts.

According to §24.232 (c), Mobile and portable stations are limited to 2 watts EIRP and the equipment must employ a means for limiting power to the minimum necessary for successful communications.

4.2 Test Procedure

Conducted output power test method:



Radiated power test method:

1. The setup of EUT is according with per ANSI/TIA-603-D: 2010 and ANSI C63.4-2014 measurement procedure.
2. The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.
3. The frequency range up to tenth harmonic of the fundamental frequency was investigated.
4. Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution.

4.3 Environmental Conditions

Temperature:	24 °C
Relative Humidity:	54%
ATM Pressure:	1011 mbar

4.4 Summary of Test Results/Plots

Max. Radiated Power

ERP For GSM Mode GSM850

Frequency	Substitute SG	Height	Table	Polar	Cable loss	Antenna Gain	Result	FCC Part 22H Limit
MHz	dBm	Meter	Degree	H / V	dB	dB	dBm	dBm
Low Channel								
824.2	30.69	1.5	0	H	1.5	0	29.19	38.45
824.2	32.17	1.5	0	V	1.5	0	30.67	38.45
Middle Channel								
836.4	30.46	1.5	0	H	1.5	0	28.96	38.45
836.4	32.36	1.5	0	V	1.5	0	30.86	38.45
High Channel								
848.8	30.5	1.5	0	H	1.5	0	29.00	38.45
848.8	31.78	1.5	0	V	1.5	0	30.28	38.45

EIRP For GSM Mode PCS1900

Frequency	Substitute SG	Height	Table	Polar	Cable loss	Antenna Gain	Result	FCC Part 24E Limit
MHz	dBm	Meter	Degree	H / V	dB	dB	DBm	dBm
Low Channel								
1850.2	21.17	1.5	0	H	1.9	7.7	26.97	33.00
1850.2	23.17	1.5	0	V	1.9	7.7	28.97	33.00
Middle Channel								
1880.0	21.05	1.5	0	H	1.9	7.7	26.85	33.00
1880.0	22.54	1.5	0	V	1.9	7.7	28.34	33.00
High Channel								
1909.8	20.83	1.5	0	H	1.9	7.7	26.63	33.00
1909.8	22.48	1.5	0	V	1.9	7.7	28.28	33.00

ERP For GPRS Mode GSM850

Frequency	Substitute SG	Height	Table	Polar	Cable loss	Antenna Gain	Result	FCC Part 22H Limit
MHz	dBm	Meter	Degree	H / V	dB	dB	dBm	dBm
Low Channel								
824.2	30.29	1.5	0	H	1.5	0	28.79	38.45
824.2	31.51	1.5	0	V	1.5	0	30.01	38.45
Middle Channel								
836.6	30.17	1.5	0	H	1.5	0	28.67	38.45
836.6	31.37	1.5	0	V	1.5	0	29.87	38.45
High Channel								
848.8	29.85	1.5	0	H	1.5	0	28.35	38.45
848.8	30.84	1.5	0	V	1.5	0	29.34	38.45

EIRP For GPRS Mode PCS1900

Frequency	Substitute SG	Height	Table	Polar	Cable loss	Antenna Gain	Result	FCC Part 24E Limit
MHz	dBm	Meter	Degree	H / V	dB	dB	DBm	dBm
Low Channel								
1850.2	18.51	1.5	0	H	1.9	7.7	24.31	33.00
1850.2	19.68	1.5	0	V	1.9	7.7	25.48	33.00
Middle Channel								
1880.0	17.96	1.5	0	H	1.9	7.7	23.76	33.00
1880.0	19.52	1.5	0	V	1.9	7.7	25.32	33.00
High Channel								
1909.8	17.73	1.5	0	H	1.9	7.7	23.53	33.00
1909.8	19.49	1.5	0	V	1.9	7.7	25.29	33.00

ERP For EDGE Mode GSM850

Frequency	Substitute SG	Height	Table	Polar	Cable loss	Antenna Gain	Result	FCC Part 22H Limit
MHz	dBm	Meter	Degree	H / V	dB	dB	dBm	dBm
Low Channel								
824.2	24.48	1.5	0	H	1.5	0	22.98	38.45
824.2	26.74	1.5	0	V	1.5	0	25.24	38.45
Middle Channel								
836.6	24.28	1.5	0	H	1.5	0	22.78	38.45
836.6	26.82	1.5	0	V	1.5	0	25.32	38.45
High Channel								
848.8	23.98	1.5	0	H	1.5	0	22.48	38.45
848.8	26.73	1.5	0	V	1.5	0	25.23	38.45

EIRP For EDGE Mode PCS1900

Frequency	Substitute SG	Height	Table	Polar	Cable loss	Antenna Gain	Result	FCC Part 24E Limit
MHz	dBm	Meter	Degree	H / V	dB	dB	DBm	dBm
Low Channel								
1850.2	15.59	1.5	0	H	1.9	7.7	21.39	33.00
1850.2	17.62	1.5	0	V	1.9	7.7	23.42	33.00
Middle Channel								
1880.0	15.43	1.5	0	H	1.9	7.7	21.23	33.00
1880.0	17.49	1.5	0	V	1.9	7.7	23.29	33.00
High Channel								
1909.8	15.42	1.5	0	H	1.9	7.7	21.22	33.00
1909.8	17.39	1.5	0	V	1.9	7.7	23.19	33.00

ERP For WCDMA Mode Band 5

Frequency	Substitute SG	Height	Table	Polar	Cable loss	Antenna Gain	Result	FCC Part 22H Limit
MHz	dBm	Meter	Degree	H / V	dB	dBd	dBm	dBm
Low Channel								
826.4	20.22	1.5	0	H	1.5	0	18.72	38.45
826.4	21.71	1.5	0	V	1.5	0	20.21	38.45
Middle Channel								
836.6	19.47	1.5	0	H	1.5	0	17.97	38.45
836.6	20.77	1.5	0	V	1.5	0	19.27	38.45
High Channel								
846.6	19.7	1.5	0	H	1.5	0	18.20	38.45
846.6	21.18	1.5	0	V	1.5	0	19.68	38.45

ERP For HSDPA Mode Band 5

Frequency	Substitute SG	Height	Table	Polar	Cable loss	Antenna Gain	Result	FCC Part 22H Limit
MHz	dBm	Meter	Degree	H / V	dB	dBd	dBm	dBm
Low Channel								
826.4	19.78	1.5	0	H	1.5	0	18.28	38.45
826.4	20.85	1.5	0	V	1.5	0	19.35	38.45
Middle Channel								
836.6	19.61	1.5	0	H	1.5	0	18.11	38.45
836.6	21.03	1.5	0	V	1.5	0	19.53	38.45
High Channel								
846.6	19.45	1.5	0	H	1.5	0	17.95	38.45
846.6	21.39	1.5	0	V	1.5	0	19.89	38.45

ERP For HSUPA Mode Band 5

Frequency	Substitute SG	Height	Table	Polar	Cable loss	Antenna Gain	Result	FCC Part 22H Limit
MHz	dBm	Meter	Degree	H / V	dB	dBd	dBm	dBm
Low Channel								
826.4	20.06	1.5	0	H	1.5	0	18.56	38.45
826.4	20.92	1.5	0	V	1.5	0	19.42	38.45
Middle Channel								
836.6	19.78	1.5	0	H	1.5	0	18.28	38.45
836.6	21.26	1.5	0	V	1.5	0	19.76	38.45
High Channel								
846.6	19.61	1.5	0	H	1.5	0	18.11	38.45
846.6	20.74	1.5	0	V	1.5	0	19.24	38.45

EIRP For WCDMA Mode Band 2

Frequency	Substitute SG	Height	Table	Polar	Cable loss	Antenna Gain	Result	FCC Part 24E Limit
MHz	dBm	Meter	Degree	H / V	dB	dB	DBm	dBm
Low Channel								
1852.4	13.47	1.5	0	H	1.9	7.7	19.27	33
1852.4	14.31	1.5	0	V	1.9	7.7	20.11	33
Middle Channel								
1880.0	12.47	1.5	0	H	1.9	7.7	18.27	33
1880.0	14.09	1.5	0	V	1.9	7.7	19.89	33
High Channel								
1907.6	12.57	1.5	0	H	1.9	7.7	18.37	33
1907.6	13.58	1.5	0	V	1.9	7.7	19.38	33

EIRP For HSDPA Mode Band 2

Frequency	Substitute SG	Height	Table	Polar	Cable loss	Antenna Gain	Result	FCC Part 24E Limit
MHz	dBm	Meter	Degree	H / V	dB	dB	DBm	dBm
Low Channel								
1852.4	12.57	1.5	0	H	1.9	7.7	18.37	33
1852.4	13.58	1.5	0	V	1.9	7.7	19.38	33
Middle Channel								
1880.0	12.07	1.5	0	H	1.9	7.7	17.87	33
1880.0	13.12	1.5	0	V	1.9	7.7	18.92	33
High Channel								
1907.6	12.48	1.5	0	H	1.9	7.7	18.28	33
1907.6	12.99	1.5	0	V	1.9	7.7	18.79	33

EIRP For HSUPA Mode Band 2

Frequency	Substitute SG	Height	Table	Polar	Cable loss	Antenna Gain	Result	FCC Part 24E Limit
MHz	dBm	Meter	Degree	H / V	dB	dB	DBm	dBm
Low Channel								
1852.4	11.69	1.5	0	H	1.9	7.7	17.49	33
1852.4	13.68	1.5	0	V	1.9	7.7	19.48	33
Middle Channel								
1880.0	11.57	1.5	0	H	1.9	7.7	17.37	33
1880.0	13.57	1.5	0	V	1.9	7.7	19.37	33
High Channel								
1907.6	11.69	1.5	0	H	1.9	7.7	17.49	33
1907.6	13.58	1.5	0	V	1.9	7.7	19.38	33

Note: Result = Substitute - Cable loss + Antenna Gain

Max. Conducted Output Power

For Cellular Band (GSM850)

Test Mode	Channel	Frequency (MHz)	Average Power (dBm)	FCC Part 22.913 Limit (dBm)
GSM	Low Channel	824.2	32.14	38.45
	Middle Channel	836.6	32.23	38.45
	High Channel	848.8	32.03	38.45
GPRS(1 Slot)	Low Channel	824.2	32.10	38.45
	Middle Channel	836.6	32.18	38.45
	High Channel	848.8	32.05	38.45
EDGE(1 Slot)	Low Channel	824.2	26.28	38.45
	Middle Channel	836.6	26.12	38.45
	High Channel	848.8	26.20	38.45

For PCS Band (GSM1900)

Test Mode	Channel	Frequency (MHz)	Average Power (dBm)	FCC Part 24.232 Limit (dBm)
GSM	Low Channel	1850.2	28.87	33.0
	Middle Channel	1880.0	28.63	33.0
	High Channel	1909.8	28.46	33.0
GPRS(1 Slot)	Low Channel	1850.2	28.47	33.0
	Middle Channel	1880.0	28.12	33.0
	High Channel	1909.8	28.23	33.0
EDGE(1 Slot)	Low Channel	1850.2	24.97	33.0
	Middle Channel	1880.0	24.76	33.0
	High Channel	1909.8	24.59	33.0

For WCDMA Band 5

Test Mode	Channel	Frequency (MHz)	Average Power (dBm)	FCC Part 22.913 Limit (dBm)
WCDMA	Low Channel	826.4	22.02	38.45
	Middle Channel	836.6	21.86	38.45
	High Channel	846.6	21.89	38.45
HSDPA	Low Channel	826.4	21.34	38.45
	Middle Channel	836.6	21.63	38.45
	High Channel	846.6	21.42	38.45
HSUPA	Low Channel	826.4	21.57	38.45
	Middle Channel	836.6	21.37	38.45
	High Channel	846.6	21.46	38.45

For WCDMA Band 2

Test Mode	Channel	Frequency (MHz)	Average Power (dBm)	FCC Part 24.232 Limit (dBm)
WCDMA	Low Channel	1852.4	21.78	33.00
	Middle Channel	1880.0	21.53	33.00
	High Channel	1907.6	21.63	33.00
HSDPA	Low Channel	1852.4	21.66	33.00
	Middle Channel	1880.0	21.24	33.00
	High Channel	1907.6	21.29	33.00
HSUPA	Low Channel	1852.4	21.22	33.00
	Middle Channel	1880.0	21.02	33.00
	High Channel	1907.6	20.86	33.00

5. Peak-to-average Radio (PAR) of Transmitter


5.1 Standard Applicable

According to §24.232(d), Power measurements for transmissions by stations authorized under this section may be made either in accordance with a Commission-approved average power technique or in compliance with paragraph (e) of this section. In both instances, equipment employed must be authorized in accordance with the provisions of §24.51. In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

5.2 Test Procedure

The RF output terminal of the transmitter was connected to the input of the spectrum analyzer via a suitable attenuation. The RBW of the spectrum analyzer was set to 30kHz and the peak-to-average ratio (PAR) of the transmission was recorded.

Test Configuration for the emission bandwidth testing:



5.3 Environmental Conditions

Temperature:	25 °C
Relative Humidity:	54%
ATM Pressure:	1011 mbar

5.4 Summary of Test Results

For PCS Band

Test Mode	Channel	Frequency (MHz)	Peak Power (dBm)	Average Power (dBm)	PAR (dB)	Limit (dB)
GSM	512	1850.2	31.82	28.87	2.95	13
	661	1880.0	31.34	28.63	2.71	13
	810	1909.8	31.26	28.46	2.8	13
GPRS (1 Slot)	512	1850.2	30.93	28.47	2.46	13
	661	1880.0	30.31	28.12	2.19	13
	810	1909.8	30.64	28.23	2.41	13
EDGE (1 Slot)	512	1850.2	26.93	24.97	1.96	13
	661	1880.0	26.43	24.76	1.67	13
	810	1909.8	26.18	24.59	1.59	13

For WCDMA Band 2

Test Mode	Channel	Frequency (MHz)	Peak Power (dBm)	Average Power (dBm)	PAR (dB)	Limit (dB)
WCDMA	9262	1852.4	24.28	21.78	2.5	13
	9400	1880.0	24.11	21.53	2.58	13
	9538	1907.6	24.07	21.63	2.44	13
HSDPA	9262	1852.4	24.12	21.66	2.46	13
	9400	1880.0	24.08	21.24	2.84	13
	9538	1907.6	23.97	21.29	2.68	13
HSUPA	9262	1852.4	23.91	21.22	2.69	13
	9400	1880.0	23.68	21.02	2.66	13
	9538	1907.6	23.10	20.86	2.24	13

6. Emission Bandwidth

6.1 Standard Applicable

According to §22.917(b), The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.


According to §24.238(b), The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

According to §27.53, The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

6.2 Test Procedure

The RF output terminal of the transmitter was connected to the input of the spectrum analyzer via a suitable attenuation. The RBW of the spectrum analyzer was set to 30kHz and the 26dB bandwidth was recorded.

Test Configuration for the emission bandwidth testing:



6.3 Environmental Conditions

Temperature:	25 °C
Relative Humidity:	54%
ATM Pressure:	1011 mbar

6.4 Summary of Test Results/Plots

For Cellular Band

Test Mode	Channel	Frequency (MHz)	99% Emission Bandwidth (kHz)	26 dB Emission Bandwidth (kHz)
GSM	128	824.2	253.2198	342.836
	190	836.6	254.8637	335.682
	251	848.8	252.5707	339.698
GPRS	128	824.2	253.2198	342.836
	190	836.6	254.9711	341.339
	251	848.8	254.1249	339.718
EDGE	128	824.2	274.0538	369.994
	190	836.6	277.9887	366.744
	251	848.8	273.3312	369.176

For PCS Band

Test Mode	Channel	Frequency (MHz)	99% Emission Bandwidth (kHz)	26 dB Emission Bandwidth (kHz)
GSM	512	1850.2	258.3169	343.884
	661	1880.0	257.4629	339.327
	810	1909.8	254.4829	339.644
GPRS	512	1850.2	256.3138	345.099
	661	1880.0	261.3718	340.390
	810	1909.8	254.4829	339.644
EDGE	512	1850.2	254.2272	310.709
	661	1880.0	252.1871	319.584
	810	1909.8	251.3004	342.579

Please refer to the following test plots:


For Band 5

Test Mode	Channel	Frequency (MHz)	99% Emission Bandwidth (MHz)	26 dB Emission Bandwidth (MHz)
WCDMA	4132	826.4	4.1635	4.744
	4183	836.6	4.1549	4.703
	4233	846.6	4.1913	4.803
HSDPA	4132	826.4	4.1671	4.727
	4183	836.6	4.1711	4.740
	4233	846.6	4.1885	4.720
HSUPA	4132	826.4	4.1541	4.722
	4183	836.6	4.1648	4.723
	4233	846.6	4.2018	5.665


For Band 2

Test Mode	Channel	Frequency (MHz)	99% Emission Bandwidth (MHz)	26 dB Emission Bandwidth (MHz)
WCDMA	9262	1852.4	4.1720	4.714
	9400	1880.0	4.2009	4.758
	9538	1907.6	4.2226	4.795
HSDPA	9262	1852.4	4.1704	4.743
	9400	1880.0	4.1739	4.750
	9538	1907.6	4.1948	4.732
HSUPA	9262	1852.4	4.1706	4.715
	9400	1880.0	4.1766	4.743
	9538	1907.6	4.1791	4.741


For Cellular Band
GSM Low Channel




GSM Middle Channel




GSM High channel




GPRS Low Channel




GPRS Middle Channel




GPRS High Channel




EDGE Low Channel




EDGE Middle Channel




EDGE High channel




For PCS Band GSM Low Channel




GSM Middle Channel




GSM High channel




GPRS Low Channel




GPRS Middle Channel




GPRS High Channel




EDGE Low Channel



EDGE Middle Channel




EDGE High channel




For Band 5


WCDMA Low Channel




WCDMA Middle Channel




WCDMA High Channel




HSDPA Low Channel




HSDPA Middle Channel




HSDPA High Channel




HSUPA Low Channel



HSUPA Middle Channel




HSUPA High Channel




For Band 2


WCDMA Low Channel




WCDMA Middle Channel




WCDMA High Channel




HSDPA Low Channel




HSDPA Middle Channel




HSDPA High Channel




HSUPA Low Channel



HSUPA Middle Channel



HSUPA High Channel



7. Out of Band Emissions at Antenna Terminal

7.1 Standard Applicable

According to §22.917(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.


According to §24.238(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

According to §27.53 (h), the power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) in watts by at least $43 + 10 \log_{10}(P)$ dB.

7.2 Test Procedure

The RF output terminal of the transmitter was connected to the input of the spectrum analyzer via a suitable attenuation. The RBW of the spectrum analyzer was set to 100kHz and 1MHz for the scan frequency from 30MHz to 1GHz and the scan frequency from 1GHz to up to 10th harmonic.

Test Configuration for the out of band emissions testing:




7.3 Environmental Conditions

Temperature:	25 °C
Relative Humidity:	53%
ATM Pressure:	1018 mbar


7.4 Summary of Test Results/Plots

Please refer to the following test plots For Cellular Band


Please refer to the following test plots For Cellular Band
GSM Low Channel 30MHz to 1GHz




Above 1GHz




GSM Middle Channel
30MHz to 1GHz




Above 1GHz




GSM High Channel 30MHz to 1GHz




Above 1GHz




GSM Low Band Emission




GSM High Band Emission




GPRS Low Channel 30MHz to 1GHz




Above 1GHz




GPRS Middle Channel 30MHz to 1GHz




Above 1GHz




GPRS High Channel 30MHz to 1GHz




Above 1GHz




GPRS Low Band Emission




GPRS High Band Emission




For PCS Band
GSM Low Channel
30MHz to 1GHz




Above 1GHz




GSM Middle Channel 30MHz to 1GHz




Above 1GHz




GSM High Channel 30MHz to 1GHz




Above 1GHz




GSM Low Band Emission




GSM High Band Emission




GPRS Low Channel
30MHz to 1GHz




Above 1GHz




GPRS Middle Channel 30MHz to 1GHz




Above 1GHz




GPRS High Channel 30MHz to 1GHz




Above 1GHz



GPRS Low Band Emission




GPRS High Band Emission




For Band 5

WCDMA Low Channel


30MHz to 1GHz




Above 1GHz




WCDMA Middle Channel 30MHz to 1GHz




Above 1GHz




WCDMA High Channel 30MHz to 1GHz




Above 1GHz




WCDMA Low Band Spurious Emission




WCDMA High Band Spurious Emission




HSDPA Low Channel 30MHz to 1GHz




Above 1GHz




HSDPA Middle Channel 30MHz to 1GHz




Above 1GHz




HSDPA High Channel 30MHz to 1GHz




Above 1GHz




HSDPA Low Band Spurious Emission




HSDPA High Band Spurious Emission




HSUPA Low Channel 30MHz to 1GHz




Above 1GHz




HSUPA Middle Channel
30MHz to 1GHz




Above 1GHz




HSUPA High Channel 30MHz to 1GHz




Above 1GHz



HSUPA Low Band Spurious Emission




HSUPA High Band Spurious Emission




For Band 2

WCDMA Low Channel


30MHz to 1GHz




Above 1GHz




WCDMA Middle Channel 30MHz to 1GHz




Above 1GHz




WCDMA High Channel 30MHz to 1GHz




Above 1GHz




WCDMA Low Band Spurious Emission




WCDMA High Band Spurious Emission




HSDPA Low Channel 30MHz to 1GHz




Above 1GHz




HSDPA Middle Channel 30MHz to 1GHz




Above 1GHz




HSDPA High Channel 30MHz to 1GHz




Above 1GHz




HSDPA Low Band Spurious Emission




HSDPA High Band Spurious Emission




HSUPA Low Channel 30MHz to 1GHz




Above 1GHz




HSUPA Middle Channel 30MHz to 1GHz




Above 1GHz




HSUPA High Channel 30MHz to 1GHz




Above 1GHz



HSUPA Low Band Spurious Emission



HSUPA High Band Spurious Emission



8. Spurious Radiated Emissions

8.1 Measurement Uncertainty

Based on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of a radiation emissions measurement is ± 5.20 dB.

8.2 Standard Applicable

According to §22.917(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

According to §24.238(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

According to §27.53 (h), the power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) in watts by at least $43 + 10 \log_{10}(P)$ dB.

8.3 Test Procedure

1. The setup of EUT is according with per ANSI/TIA-603-D: 2010 and ANSI C63.4-2014 measurement procedure.
2. The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.
3. The frequency range up to tenth harmonic of the fundamental frequency was investigated.
4. Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution.

$$\text{Spurious attenuation limit in dB} = 43 + 10 \log_{10}(\text{power out in Watts})$$

8.4 Environmental Conditions

Temperature:	25 °C
Relative Humidity:	52%
ATM Pressure:	1012 mbar


8.5 Summary of Test Results/Plots

According to the data below, the FCC Part 22.917 and 24.238 standards, and had the worst margin of:

Note: this EUT was tested in 3 orthogonal positions and the worst case position (Vertical) data was reported.


Spurious Emission From 30MHz to 1GHz

Horizontal:



No.	Frequency (MHz)	Reading (dBm)	Correct dB	Result (dBm)	Limit (dBm)	Margin (dB)	Remark
1	40.5591	-70.51	20.41	-50.10	-13.00	-37.10	ERP
2	100.2286	-70.61	17.60	-53.01	-13.00	-40.01	ERP
3	321.0608	-69.77	20.80	-48.97	-13.00	-35.97	ERP
4	739.6605	-69.98	27.51	-42.47	-13.00	-29.47	ERP


Vertical:



No.	Frequency (MHz)	Reading (dBm)	Correct dB	Result (dBm)	Limit (dBm)	Margin (dB)	Remark
1	39.9942	-70.32	20.66	-49.66	-13.00	-36.66	ERP
2	100.2286	-69.95	17.92	-52.03	-13.00	-39.03	ERP
3	293.0842	-69.95	20.66	-49.29	-13.00	-36.29	ERP
4	744.8661	-69.34	27.10	-42.24	-13.00	-29.24	ERP
5	1000.0000	-69.49	29.05	-40.44	-13.00	-27.44	ERP


For Cellular Band_ GSM1900 Mode

Horizontal:



No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBm)	dB	(dBm)	(dBm)	(dB)	
1	39.4372	-69.57	20.50	-49.07	-13.00	-36.07	ERP
2	130.8369	-68.02	14.67	-53.35	-13.00	-40.35	ERP
3	279.0436	-68.83	19.80	-49.03	-13.00	-36.03	ERP
4	739.6605	-70.07	27.51	-42.56	-13.00	-29.56	ERP


Vertical:



No.	Frequency (MHz)	Reading (dBm)	Correct Factor(dB)	Result (dBm)	Limit (dBm)	Margin (dB)	Remark
1	45.6948	-69.97	2.82	-67.15	-13.00	-54.15	ERP
2	244.2321	-68.52	5.48	-63.04	-13.00	-50.04	ERP
3	968.9338	-69.30	17.93	-51.37	-13.00	-38.37	ERP


For band 5 Mode

Horizontal:



No.	Frequency (MHz)	Reading (dBm)	Correct Factor(dB)	Result (dBm)	Limit (dBm)	Margin (dB)	Remark
1	52.5753	-69.74	2.91	-66.83	-13.00	-53.83	ERP
2	244.2321	-69.59	5.48	-64.11	-13.00	-51.11	ERP
3	945.4399	-69.35	17.71	-51.64	-13.00	-38.64	ERP


Vertical:



No.	Frequency (MHz)	Reading (dBm)	Correct dB	Result (dBm)	Limit (dBm)	Margin (dB)	Remark
1	48.5016	-69.33	3.22	-66.11	-13.00	-53.11	ERP
2	256.5211	-69.07	5.69	-63.38	-13.00	-50.38	ERP
3	912.8620	-68.84	17.53	-51.31	-13.00	-38.31	ERP


For band 2 Mode

Horizontal:



No.	Frequency (MHz)	Reading (dBm)	Correct dB	Result (dBm)	Limit (dBm)	Margin (dB)	Remark
1	49.1866	-69.42	3.33	-66.09	-13.00	-53.09	ERP
2	305.6800	-69.07	6.93	-62.14	-13.00	-49.14	ERP
3	958.7943	-69.24	17.82	-51.42	-13.00	-38.42	ERP

Vertical:



No.	Frequency (MHz)	Reading (dBm)	Correct Factor(dB)	Result (dBm)	Limit (dBm)	Margin (dB)	Remark
1	43.2017	-69.32	2.44	-66.88	-13.00	-53.88	ERP
2	419.1081	-69.05	9.94	-59.11	-13.00	-46.11	ERP
3	955.4381	-69.51	17.80	-51.71	-13.00	-38.71	ERP

Note: $\text{Margin} = (\text{Reading} + \text{Correct}) - \text{Limit}$

Spurious Emissions Above 1GHz
For Cellular Band_GSM850 Mode

Frequency	Reading	Correct	Result	Limit	Margin	Polar
(MHz)	(dBm)	dB	(dBm)	(dBm)	(dB)	H/V
Low Channel (824.2MHz)						
1648.4	-49.46	4.94	-44.52	-13.00	-31.52	H
2472.6	-51.46	8.46	-43.00	-13.00	-30.00	H
1648.4	-50.06	4.94	-45.12	-13.00	-32.12	V
2472.6	-53.71	8.46	-45.25	-13.00	-32.25	V
Middle Channel (836.6MHz)						
1673.2	-48.47	5.11	-43.36	-13.00	-30.36	H
2509.8	-50.79	8.54	-42.25	-13.00	-29.25	H
1673.2	-48.36	5.11	-43.25	-13.00	-30.25	V
2509.8	-50.69	8.54	-42.15	-13.00	-29.15	V
High Channel (848.8MHz)						
1697.6	-50.43	5.29	-45.14	-13.00	-32.14	H
2546.4	-52.80	8.59	-44.21	-13.00	-31.21	H
1697.6	-50.30	5.29	-45.01	-13.00	-32.01	V
2546.4	-52.73	8.59	-44.14	-13.00	-31.14	V

For PCS Band_GSM1900 Mode

Frequency	Reading	Correct	Result	Limit	Margin	Polar
(MHz)	(dBm)	dB	(dBm)	(dBm)	(dB)	H/V
Low Channel (1850.2MHz)						
3700.4	-54.90	10.54	-44.36	-13.00	-31.36	H
5550.6	-57.62	13.37	-44.25	-13.00	-31.25	H
3700.4	-53.90	10.54	-43.36	-13.00	-30.36	V
5550.6	-57.62	13.37	-44.25	-13.00	-31.25	V
Middle Channel (1880MHz)						
3760.0	-53.00	10.64	-42.36	-13.00	-29.36	H
5640.0	-57.79	13.54	-44.25	-13.00	-31.25	H
3760.0	-53.00	10.64	-42.36	-13.00	-29.36	V
5640.0	-57.79	13.54	-44.25	-13.00	-31.25	V
High Channel (1909.8MHz)						
3819.6	-54.43	10.74	-43.69	-13.00	-30.69	H
5729.4	-57.96	13.71	-44.25	-13.00	-31.25	H
3819.6	-55.13	10.74	-44.39	-13.00	-31.39	V
5729.4	-57.46	13.71	-43.75	-13.00	-30.75	V

For Band 5 Mode

Frequency	Reading	Correct	Result	Limit	Margin	Polar
(MHz)	(dBm)	dB	(dBm)	(dBm)	(dB)	H/V
Low Channel (826.4MHz)						
1652.8	-58.19	4.94	-53.25	-13	-40.25	H
2479.2	-58.71	8.46	-50.25	-13	-37.25	H
1652.8	-57.16	4.94	-52.22	-13	-39.22	V
2479.2	-58.39	8.46	-49.93	-13	-36.93	V
Middle Channel (836.6MHz)						
1672.8	-58.27	5.11	-53.16	-13	-40.16	H
2509.2	-58.76	8.54	-50.22	-13	-37.22	H
1672.8	-59.22	5.11	-54.11	-13	-41.11	V
2509.2	-60.25	8.54	-51.71	-13	-38.71	V
High Channel (846.6MHz)						
1693.2	-57.57	5.29	-52.28	-13	-39.28	H
2539.8	-60.59	8.59	-52	-13	-39	H
1693.2	-58.07	5.29	-52.78	-13	-39.78	V
2539.8	-59.51	8.59	-50.92	-13	-37.92	V

For Band 2 Mode

Frequency	Reading	Correct	Result	Limit	Margin	Polar
(MHz)	(dBm)	dB	(dBm)	(dBm)	(dB)	H/V
Low Channel (1852.4MHz)						
3704.8	-57.55	10.17	-47.38	-13	-34.38	H
5557.2	-58.11	14.69	-43.42	-13	-30.42	H
3704.8	-58.61	10.17	-48.44	-13	-35.44	V
5557.2	-58.84	14.69	-44.15	-13	-31.15	V
Middle Channel (1880MHz)						
3760.8	-58.88	10.26	-48.62	-13	-35.62	H
5640.0	-58.73	14.78	-43.95	-13	-30.95	H
3760.8	-58.45	10.26	-48.19	-13	-35.19	V
5640.0	-59	14.78	-44.22	-13	-31.22	V
High Channel (1907.6MHz)						
3815.2	-59.11	10.59	-48.52	-13	-35.52	H
5722.8	-59.15	15.03	-44.12	-13	-31.12	H
3815.2	-59.41	10.59	-48.82	-13	-35.82	V
5722.8	-58.74	15.03	-43.71	-13	-30.71	H

Note: Result=Reading+ Correct, Margin= Result- Limit

Testing is carried out with frequency rang 9kHz to 20GHz, which above 3th Harmonics are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

The measurements greater than 20dB below the limit from, 9kHz to 30MHz,so the data is not display.

9. Frequency Stability

9.1 Standard Applicable

According to §22.355, the carrier frequency of each transmitter in the Public Mobile Services must be maintained within the tolerances given in Table below:

Frequency Tolerance for Cellular Band

Frequency range (MHz)	Base, fixed (ppm)	Mobile ≤3 watts (ppm)	Mobile ≤3 watts (ppm)
25 to 50	20.0	20.0	50.0
50 to 450	5.0	5.0	50.0
450 to 512	2.5	5.0	5.0
821 to 896	1.5	2.5	2.5
928 to 929	5.0	N/A	N/A
929 to 960	1.5	N/A	N/A
2110 to 2220	10.0	N/A	N/A

According to §24.235, the frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.

According to §27.54 The frequency stability shall be sufficient to ensure that the fundamental emissions stay within the authorized bands of operation.

9.2 Test Procedure

According to §2.1055, the following test procedure was performed.

The Frequency Stability is measured directly with a Frequency Domain Analyzer. Frequency Deviation in ppm is calculated from the measured peak to peak value.

The Carrier Frequency Stability over Power Supply Voltage and over Temperature is measured with a Frequency Domain Analyzer in histogram mode

Temperature:	Supply Voltage
20°C	85-115% of declared nominal voltage
-30°C to +50°C	Normal

9.3 Environmental Conditions

Temperature:	20°C
Relative Humidity:	54%
ATM Pressure:	1011 mbar

9.4 Summary of Test Results/Plots

For Cellular Band GSM Mode

Reference Frequency(Middle Channel): 836.6 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		MCF (Hz)	Error (ppm)
50	3.8	58	0.0693
40	3.8	54	0.0645
30	3.8	49	0.0586
20	3.8	47	0.0562
10	3.8	52	0.0622
0	3.8	46	0.0550
-10	3.8	31	0.0371
-20	3.8	42	0.0502
-30	3.8	39	0.0466

For PCS Band GSM Mode

Reference Frequency(Middle Channel): 1880 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		MCF (Hz)	Error (ppm)
50	3.8	53	0.0282
40	3.8	40	0.0213
30	3.8	36	0.0191
20	3.8	45	0.0239
10	3.8	31	0.0165
0	3.8	20	0.0106
-10	3.8	66	0.0351
-20	3.8	49	0.0261
-30	3.8	36	0.0191

For Cellular Band GPRS Mode

Reference Frequency(Middle Channel): 836.6MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		MCF (Hz)	Error (ppm)
50	3.8	49	0.0586
40	3.8	45	0.0538
30	3.8	40	0.0478
20	3.8	38	0.0454
10	3.8	43	0.0514
0	3.8	37	0.0442
-10	3.8	22	0.0263
-20	3.8	33	0.0394
-30	3.8	30	0.0359

For PCS Band GPRS Mode

Reference Frequency(Middle Channel): 1880 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		MCF (Hz)	Error (ppm)
50	3.8	64	0.0340
40	3.8	51	0.0271
30	3.8	47	0.0250
20	3.8	56	0.0298
10	3.8	42	0.0223
0	3.8	31	0.0165
-10	3.8	77	0.0410
-20	3.8	60	0.0319
-30	3.8	47	0.0250

For Cellular Band EDGE Mode

Reference Frequency(Middle Channel): 836.6MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		MCF (Hz)	Error (ppm)
50	3.8	62	0.0741
40	3.8	58	0.0693
30	3.8	53	0.0634
20	3.8	51	0.0610
10	3.8	56	0.0669
0	3.8	50	0.0598
-10	3.8	35	0.0418
-20	3.8	46	0.0550
-30	3.8	43	0.0514

For PCS Band EDGE Mode

Reference Frequency(Middle Channel): 1880 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		MCF (Hz)	Error (ppm)
50	3.8	67	0.0356
40	3.8	54	0.0287
30	3.8	50	0.0266
20	3.8	59	0.0314
10	3.8	45	0.0239
0	3.8	34	0.0181
-10	3.8	80	0.0426
-20	3.8	63	0.0335
-30	3.8	50	0.0266

For WCDMA Band 5 Mode

Reference Frequency(Middle Channel): 836.6 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		MCF (Hz)	Error (ppm)
50	3.8	57	0.0681
40	3.8	64	0.0765
30	3.8	67	0.0801
20	3.8	53	0.0634
10	3.8	72	0.0861
0	3.8	77	0.0920
-10	3.8	66	0.0789
-20	3.8	62	0.0741
-30	3.8	83	0.0992

For WCDMA Band 2 Mode

Reference Frequency(Middle Channel): 1880 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		MCF (Hz)	Error (ppm)
50	3.8	52	0.0277
40	3.8	39	0.0207
30	3.8	35	0.0186
20	3.8	44	0.0234
10	3.8	30	0.0160
0	3.8	19	0.0101
-10	3.8	65	0.0346
-20	3.8	48	0.0255
-30	3.8	35	0.0186

For HSDPA Band 5 Mode

Reference Frequency(Middle Channel): 836.6 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		MCF (Hz)	Error (ppm)
50	3.8	61	0.0729
40	3.8	68	0.0813
30	3.8	71	0.0849
20	3.8	57	0.0681
10	3.8	76	0.0908
0	3.8	81	0.0968
-10	3.8	70	0.0837
-20	3.8	66	0.0789
-30	3.8	87	0.1040

For HSDPA Band 2 Mode

Reference Frequency(Middle Channel): 1880 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		MCF (Hz)	Error (ppm)
50	3.8	60	0.0319
40	3.8	47	0.0250
30	3.8	43	0.0229
20	3.8	52	0.0277
10	3.8	38	0.0202
0	3.8	27	0.0144
-10	3.8	73	0.0388
-20	3.8	56	0.0298
-30	3.8	43	0.0229

For HSUPA Band 5 Mode

Reference Frequency(Middle Channel): 836.6 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		MCF (Hz)	Error (ppm)
50	3.8	53	0.0634
40	3.8	60	0.0717
30	3.8	63	0.0753
20	3.8	49	0.0586
10	3.8	68	0.0813
0	3.8	73	0.0873
-10	3.8	62	0.0741
-20	3.8	58	0.0693
-30	3.8	79	0.0944

For HSUPA Band 2 Mode

Reference Frequency(Middle Channel): 1880 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		MCF (Hz)	Error (ppm)
50	3.8	48	0.0255
40	3.8	35	0.0186
30	3.8	31	0.0165
20	3.8	40	0.0213
10	3.8	26	0.0138
0	3.8	15	0.0080
-10	3.8	61	0.0324
-20	3.8	44	0.0234
-30	3.8	31	0.0165

So, Frequency Stability Versus Input Voltage is:

Reference Frequency(Middle Channel): GSM 836.6MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		Frequency (Hz)	Error (ppm)
20	3.23	44	0.0526
	3.80	63	0.0753
	4.37	68	0.0813
Reference Frequency(Middle Channel): GSM 1880 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		Frequency (Hz)	Error (ppm)
20	3.23	41	0.0218
	3.80	27	0.0144
	4.37	16	0.0085
Reference Frequency(Middle Channel): GPRS 836.6MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		Frequency (Hz)	Error (ppm)
20	3.23	57	0.0681
	3.80	53	0.0634
	4.37	74	0.0885
Reference Frequency(Middle Channel): GPRS 1880 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		Frequency (Hz)	Error (ppm)
20	3.23	62	0.0330
	3.80	45	0.0239
	4.37	32	0.0170

Reference Frequency(Middle Channel): EDGE 836.6MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		Frequency (Hz)	Error (ppm)
20	3.3	48	0.0574
	3.8	55	0.0657
	4.2	58	0.0693
Reference Frequency(Middle Channel): EDGE 1880 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		Frequency (Hz)	Error (ppm)
20	3.3	49	0.0261
	3.8	36	0.0191
	4.2	32	0.0170
Reference Frequency(Middle Channel): WCDMA 836.6MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		Frequency (Hz)	Error (ppm)
20	3.3	61	0.0729
	3.8	70	0.0837
	4.2	91	0.1088
Reference Frequency(Middle Channel): WCDMA 1880 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		Frequency (Hz)	Error (ppm)
20	3.3	48	0.0255
	3.8	34	0.0181
	4.2	23	0.0122
Reference Frequency(Middle Channel): HSDPA 836.6MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		Frequency (Hz)	Error (ppm)
20	3.3	80	0.0956
	3.8	85	0.1016
	4.2	74	0.0885

Reference Frequency(Middle Channel): HSUPA1880 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		Frequency (Hz)	Error (ppm)
20	3.3	51	0.0271
	3.8	47	0.0250
	4.2	51	0.0271
Reference Frequency(Middle Channel): HSDPA 836.6MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		Frequency (Hz)	Error (ppm)
20	3.3	-59	-0.0705
	3.8	-40	-0.0478
	4.2	-35	-0.0418
Reference Frequency(Middle Channel): HSDPA 1880 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		Frequency (Hz)	Error (ppm)
20	3.42	62	0.0330
	3.8	57	0.0303
	4.56	64	0.0340

***** END OF REPORT *****