

FCC - TEST REPORT

Report Number : **68.950.15.174.01** Date of Issue: November 5, 2015

Model : **JioPay 2800**

Product Type : **POS**

Applicant : **KanhaTech Solutions Pvt Ltd**

Address : **No 74, Prestige Feroze Building, 4th Floor, Cunningham road,**
Bangalore

Production Facility : **KanhaTech Solutions Pvt Ltd**

Address : **No 74, Prestige Feroze Building, 4th Floor, Cunningham road,**
Bangalore

Test Result : ☒ **Positive** ☐ **Negative**

Total pages : **37**

TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch is a subcontractor to TÜV SÜD Product Service GmbH according to the principles outlined in ISO 17025.

TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch reports apply only to the specific samples tested under stated test conditions. Construction of the actual test samples has been documented. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical components. The manufacturer/importer is responsible to the Competent Authorities in Europe for any modifications made to the production units which result in non-compliance to the relevant regulations. TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch shall have no liability for any deductions, inferences or generalizations drawn by the client or others from TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch issued reports.

This report is the confidential property of the client. As a mutual protection to our clients, the public and ourselves, extracts from the test report shall not be reproduced except in full without our written approval

1 Table of Contents

1	Table of Contents.....	2
2	Details about the Test Laboratory	3
3	Description of the Equipment Under Test.....	4
4	Summary of Test Standards.....	5
5	Summary of Test Results	6
6	General Remarks.....	7
7	Test Setups.....	8
8	Systems test configuration	9
9	Technical Requirement	10
9.1	Conducted peak output power	10
9.2	20 dB bandwidth and 99% Occupied Bandwidth	15
9.3	Carrier Frequency Separation	17
9.4	Number of hopping frequencies	19
9.5	Dwell Time	21
9.6	Spurious RF conducted emissions	25
9.7	Band edge testing	29
9.8	Spurious radiated emissions for transmitter and receiver	34
10	Test Equipment List	36
11	System Measurement Uncertainty	37



2 Details about the Test Laboratory

Details about the Test Laboratory

Test Site 1

Company name: TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch
Building 12&13, Zhiheng Wisdomland Business Park,
Nantou Checkpoint Road 2, Nanshan District,
Shenzhen City, 518052,
P. R. China

FCC Registration No.: 502708

IC Registration No: 10320A-1

Telephone: 86 755 8828 6998
Fax: 86 755 8828 5299

3 Description of the Equipment Under Test

Product:	POS
Model no.:	JioPay 2800
Brand Name:	JioPay
FCC ID:	2AFXJ-JIOPAY2800
Options and accessories:	NIL
Rating:	DC 3.7V by Li-ion Battery or 5VDC,2.0A (Charged by an external power adapter Adapter input:100-240VAC, 50/60Hz, 0.5A Adapter output:5.0V, 2.0A)
RF Transmission Frequency:	2402-2480MHz
No. of Operated Channel:	79
Modulation:	GFSK, $\pi/4$ -DQPSK, 8DPSK
Antenna Type:	Integral Antenna
Antenna Gain:	1.6dBi
Description of the EUT:	The Equipment Under Test (EUT) is a POS with Bluetooth function operated at 2.4GHz

4 Summary of Test Standards

Test Standards	
FCC Part 15 Subpart C 10-1-2014 Edition	PART 15 - RADIO FREQUENCY DEVICES Subpart C - Intentional Radiators

All the test methods were according to Public Notice DA 00-705 -Frequency Hopper Spread Spectrum Test Procedure released by FCC on March 30, 2000 and C63.10 (2014).

5 Summary of Test Results

Technical Requirements				
FCC Part 15 Subpart C				
Test Condition		Pages	Test Site	Test Result
§15.207	Conducted emission AC power port	---	---	N/A
§15.247 (b) (1)	Conducted peak output power	10	Site 1	Pass
§15.247(a)(1)	20dB bandwidth	---	---	N/A
§15.247(a)(1)	Carrier frequency separation	12	Site 1	Pass
§15.247(a)(1)(iii)	Number of hopping frequencies	18	Site 1	Pass
§15.247(a)(1)(iii)	Dwell Time	21	Site 1	Pass
§15.247(a)(2)	6dB bandwidth	---	---	Pass
§15.247(e)	Power spectral density	---	---	N/A
§15.247(d)	Spurious RF conducted emissions	26	Site 1	Pass
§15.247(d)	Band edge	30	Site 1	Pass
§15.247(d) & §15.209	Spurious radiated emissions for transmitter	35	Site 1	Pass
§15.203	Antenna requirement	See note 2		Pass

Note 1: N/A=Not Applicable.

Note 2: The EUT uses an integral antenna, which gain is 1.6dBi. In accordance to §15.203, It is considered sufficiently to comply with the provisions of this section.

6 General Remarks

Remarks

This submittal(s) (test report) is intended for FCC ID: 2AFXJ-JIOPAY2800 complies with Section 15.207, 15.209, 15.247 of the FCC Part 15, Subpart C Rules.

SUMMARY:

All tests according to the regulations cited on page 5 were

■ - Performed

□ - **Not** Performed

The Equipment Under Test

■ - **Fulfills** the general approval requirements.

□ - **Does not** fulfill the general approval requirements.

Sample Received Date: August 11, 2015

Testing Start Date: August 12, 2015

Testing End Date: August 25, 2015


TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch

Reviewed by:

Prepared by:




John Zhi
EMC Project Manager




Alan Xiong
EMC Project Engineer

7 Test Setups


7.1 AC Power Line Conducted Emission test setups



7.2 Radiated test setups



7.3 Conducted RF test setups



8 Systems test configuration

Auxiliary Equipment Used during Test:

DESCRIPTION	MANUFACTURER	MODEL NO.(SHIELD)	S/N(LENGTH)
Notebook	Lenovo	X220	---

Test software: Bluetooth 3, which used to control the EUT in continues transmitting mode

The system was configured to hopping mode and non-hopping mode.

Hopping mode: typical working mode (normal hopping status)

Non-hopping mode: The system was configured to operate at a signal channel transmitting. The test software allows the configuration and operation at the worst-case duty and the highest transmit power

9 Technical Requirement

9.1 Conducted Emission on AC power port

Test Method

1. The EUT was placed on a table, which is 0.8m above ground plane
2. The power line of the EUT is connected to the AC mains through a Artificial Mains Network (A.M.N.).
3. Maximum procedure was performed to ensure EUT compliance
4. A EMI test receiver is used to test the emissions from both sides of AC line

Limit


According to §15.207, conducted emissions limit as below:

Frequency MHz	QP Limit dB μ V	AV Limit dB μ V
0.150-0.500	66-56*	56-46*
0.500-5	56	46
5-30	60	50

Decreasing linearly with logarithm of the frequency

Conducted Emission


Product Type : POS
 M/N : JioPay 2800
 Operating Condition : Charging and Transmitting
 Test Specification : Line
 Comment : AC 120V/60Hz



Frequency (MHz)	QuasiPeak (dBμV)	Average (dBμV)	Limit (dBμV)	Margin (dB)	Line	Corr. (dB)
0.157500	---	26.20	55.59	29.39	L1	9.6
0.157500	40.30	---	65.59	25.29	L1	9.6
0.578500	---	38.10	46.00	7.90	L1	10.0
0.578500	43.74	---	56.00	12.26	L1	10.0
0.669500	---	25.01	46.00	20.99	L1	10.0
0.669500	31.22	---	56.00	24.78	L1	10.0
1.145500	---	22.22	46.00	23.78	L1	9.8
1.145500	29.69	---	56.00	26.31	L1	9.8
1.657500	---	22.61	46.00	23.39	L1	9.8
1.657500	30.28	---	56.00	25.72	L1	9.8
17.713500	---	20.18	50.00	29.82	L1	10.1
17.713500	25.75	---	60.00	34.25	L1	10.1

Conducted Emission

Product Type : POS
 M/N : JioPay 2800
 Operating Condition : Charging and Transmitting
 Test Specification : Neutral
 Comment : AC 120V/60Hz



Frequency (MHz)	QuasiPeak (dBµV)	Average (dBµV)	Limit (dBµV)	Margin (dB)	Line	Corr. (dB)
0.157500	---	25.13	55.59	30.46	N	9.6
0.157500	41.82	---	65.59	23.77	N	9.6
0.201500	---	22.62	53.55	30.93	N	9.8
0.201500	38.07	---	63.55	25.48	N	9.8
0.577500	---	27.59	46.00	18.41	N	10.0
0.577500	37.73	---	56.00	18.27	N	10.0
1.145500	---	16.25	46.00	29.75	N	9.8
1.145500	28.67	---	56.00	27.33	N	9.8
2.201500	---	14.85	46.00	31.15	N	9.8
2.201500	25.62	---	56.00	30.38	N	9.8
17.370500	---	19.80	50.00	30.20	N	10.1
17.370500	26.82	---	60.00	33.18	N	10.1

9.2 Conducted peak output power

Test Method

1. Use the following spectrum analyzer settings:
Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel
RBW > the 20 dB bandwidth of the emission being measured, VBW ≥ RBW,
Sweep = auto, Detector function = peak, Trace = max hold
2. Add a correction factor to the display.
3. Allow the trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. The indicated level is the peak output power

Limits

According to §15.247 (b) (1), conducted peak output power limit as below:

Frequency Range MHz	Limit W	Limit dBm
2400-2483.5	≤1	≤30

Conducted peak output power**Bluetooth Mode GFSK modulation Test Result**

Frequency MHz	Conducted Peak Output Power dBm	Result
Low channel 2402MHz	4.38	Pass
Middle channel 2441MHz	4.64	Pass
High channel 2480MHz	4.61	Pass

Bluetooth Mode 8DPSK modulation Test Result

Frequency MHz	Conducted Peak Output Power dBm	Result
Low channel 2402MHz	4.73	Pass
Middle channel 2441MHz	4.99	Pass
High channel 2480MHz	4.94	Pass

9.3 20 dB bandwidth

Test Method

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.

Limit

Limit [kHz]

N/A

20 dB bandwidth

Bluetooth Mode GFSK Modulation test result

Frequency MHz	20 dB Bandwidth kHz	Limit kHz	Result
2402	946.5	--	Pass
2441	943.6	--	Pass
2480	943.6	--	Pass

Bluetooth Mode 8DPSK Modulation test result

Frequency MHz	20 dB Bandwidth kHz	Limit kHz	Result
2402	1253.3	--	Pass
2441	1253.3	--	Pass
2480	1250.4	--	Pass

9.4 Carrier Frequency Separation

Test Method

1. Use the following spectrum analyzer settings:
Span = wide enough to capture the peaks of two adjacent channels, $RBW \geq 1\%$ of the span, $VBW \geq RBW$, Sweep = auto, Detector function = peak
2. By using the Max-Hold function record the separation of two adjacent channels.
3. Measure the frequency difference of these two adjacent channels by spectrum analyzer marker function.
4. Repeat above procedures until all frequencies measured were complete.

Limit

Limit kHz
$\geq 25\text{kHz}$ or $2/3$ of the 20 dB bandwidth which is greater

GFSK Modulation Limit


Frequency MHz	2/3 of 20 dB Bandwidth kHz
2402	631.0
2441	629.1
2480	629.1

Carrier Frequency Separation

Test result: The measurement was performed with the typical configuration (normal hopping status), here GFSK modulation mode was used to show compliance.

GFSK Modulation test result

Frequency MHz	Carrier Frequency Separation kHz	Result
2441	1002.9	Pass



9.5 Number of hopping frequencies

Test Method

1. Use the following spectrum analyzer settings:
Span = wide enough to capture the peaks of two adjacent channels, $RBW \geq 1\%$ of the span, $VBW \geq RBW$, Sweep = auto, Detector function = peak
2. Set the spectrum analyzer on Max-Hold Mode, and then keep the EUT in hopping mode.
3. Record all the signals from each channel until each one has been recorded.
4. Repeat above procedures until all frequencies measured were complete.

Limit

Limit
number


≥ 15



Number of hopping frequencies

Test result: The measurement was performed with the typical configuration (normal hopping status), and the total hopping channels is constant for the all modulation mode according with the Bluetooth Core Specification. Here GFSK modulation mode was used to show compliance.

Number of hopping frequencies	Result
79	Pass



9.6 Dwell Time

Test Method

1. Connect EUT antenna terminal to the spectrum analyzer with a low loss cable.
Equipment mode: Spectrum analyzer
2. RBW: 1MHz; VBW: 1MHz; SPAN: Zero Span
3. Adjust the center frequency of spectrum analyzer on any frequency be measured.
4. Measure the Dwell Time by spectrum analyzer Marker function.
5. Repeat above procedures until all frequencies measured were complete.

Limit

According to §15.247(a)(1)(iii) The average time of occupancy on any frequency shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

Dwell time

The maximum dwell time shall be 0,4 s.

According to the Bluetooth Core Specification, the worse result (DH5 mode) was reported to show compliance.

The Dwell Time = Burst Width * Total Hops. The detailed calculations are showed as follows:

The duration for dwell time calculation: $0.4 \text{ [s]} * \text{hopping number} = 0.4 \text{ [s]} * 79 \text{ [ch]} = 31.6 \text{ [s*ch]}$;



The burst width, which is directly measured, refers to the duration on one channel hop.

The maximum number of hopping channels in 31.6s for DH5= $1600 / 6 / 79 * 31.6 = 106.67$



Test Result

Modulation	Mode	Reading (μs)	Total Hops	Test Result (ms)	Limit (ms)	Result
GFSK	DH5	2971	107.44	319.20	< 400	Pass
π/4-DQPSK	2DH5	2957	107.44	317.70	< 400	Pass
8-DPSK	3DH5	2971	107.44	319.20	< 400	Pass



GFSK Modulation



DH5

$\pi/4$ -DQPSK Modulation

8-DPSK Modulation



9.7 Spurious RF conducted emissions

Test Method

1. Use the following spectrum analyzer settings:
Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic. Typically, several plots are required to cover this entire span.
RBW = 100 kHz, VBW ≥ RBW, Sweep = auto, Detector function = peak, Trace = max hold
2. Allow the trace to stabilize. Set the marker on the peak of any spurious emission recorded.
3. The level displayed must comply with the limit specified in this Section. Submit these plots.
4. Repeat above procedures until all frequencies measured were complete.



Limit

Frequency Range MHz	Limit (dBc)
30-25000	-20

Spurious RF conducted emissions



Only the worse case (which is subject to the maximum EIRP, GFSK mode) test result is listed in the report.

2402MHz





Spurious RF conducted emissions

2441MHz



Spurious RF conducted emissions

2480MHz



9.8 Band edge testing

Test Method



- 1 Use the following spectrum analyzer settings:
Span = wide enough to capture the peak level of the in-band emission and all spurious
RBW = 100 kHz, VBW \geq RBW, Sweep = auto, Detector function = peak, Trace = max hold
- 2 Allow the trace to stabilize, use the peak and delta measurement to record the result.
- 3 The level displayed must comply with the limit specified in this Section. .
- 4 Repeat the test at the hopping off and hopping on mode, submit all the plots.

Limit:

According to §15.247(d), in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a) and RSS-Gen7.2.2, must also comply with the radiated emission limits specified in 15.209(a) (see Section 15.205(c)) and RSS-Gen.



Band edge testing

GFSK Modulation Test Result:
Hopping on mode:





Band edge testing

Hopping off mode:





Band edge testing

8DPSK Modulation Test Result:
Hopping on mode:



Band edge testing

Hopping off mode:



9.9 Spurious radiated emissions for transmitter

Test Method

1. The EUT is placed on a turntable, which is 0.8m above ground plane.
2. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
3. Use the following spectrum analyzer settings:
Span = wide enough to fully capture the emission being measured, RBW = 1 MHz for $f \geq 1\text{GHz}$, 100 kHz for $f < 1\text{GHz}$, VBW \geq RBW, Sweep = auto, Detector function = peak, Trace = max hold
4. Follow the guidelines in ANSI C63.4-2009 with respect to maximizing the emission by rotating the EUT, adjusting the measurement antenna height and polarization, etc.
The peak reading of the emission, after being corrected by the antenna factor, cable loss, pre-amp gain, etc., is the peak field strength, submit this data. Each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
5. Set the VBW to 10 Hz, while maintaining all of the other instrument settings. This peak level, once corrected, must comply with the limit specified in Section 15.209. If the duty cycle per channel of the hopping signal is less than 100 ms, then the reading obtained with the 10 Hz VBW may be further adjusted by a "duty cycle correction factor", derived from $20\log(\text{duty cycle}/100\text{ ms})$, in an effort to demonstrate compliance with the 15.209 limit. Submit this data.

Limit

According to part 15.247(d), the radio emission outside the operating frequency band shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power. Radiated emissions which fall in the restricted bands, as defined in section 15.205, must comply with the radiated emission limits specified in section 15.209.

Frequency MHz	Field Strength uV/m	Field Strength dB μ V/m	Detector
30-88	100	40	QP
88-216	150	43.5	QP
216-960	200	46	QP
960-1000	500	54	QP
Above 1000	500	54	AV
Above 1000	5000	74	PK

Spurious radiated emissions for transmitter

According to C63.10, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement, so AV emission value did not show in below table if the peak value complies with average limit.

The only worse case (which is subject to the maximum EIRP, GFSK mode) test result is listed in the report.

Transmitting spurious emission test result as below:

Bluetooth Mode GFSK Modulation 2402MHz Test Result

Frequency	Emission Level	Polarization	Limit	Detector	Margin	Result
MHz	dBuV/m		dBuV/m		dBuV/m	
79.71	18.32	Horizontal	40.00	QP	21.68	Pass
97.42	18.99	Horizontal	43.50	QP	24.51	Pass
362.16	24.38	Horizontal	46.00	QP	21.62	Pass
49.89	24.97	Vertical	40.00	QP	15.03	Pass
80.44	25.19	Vertical	40.00	QP	14.81	Pass
96.93	24.46	Vertical	43.50	QP	19.04	Pass
137.49	24.05	Vertical	43.50	QP	19.45	Pass
*4804	51.02	Horizontal	74	PK	22.98	Pass
*4804	49.79	Vertical	74	PK	24.21	Pass

Bluetooth Mode GFSK Modulation 2441MHz Test Result

Frequency	Emission Level	Polarization	Limit	Detector	Margin	Result
MHz	dBuV/m		dBuV/m		dBuV/m	
*4882	51.32	Horizontal	74	PK	22.68	Pass
*4882	55.81	Vertical	74	PK	18.19	Pass
*4882	47.51	Vertical	54	AV	6.49	Pass

Bluetooth Mode GFSK Modulation 2480MHz Test Result

Frequency	Emission Level	Polarization	Limit	Detector	Margin	Result
MHz	dBuV/m		dBuV/m		dBuV/m	
*4960	47.66	Horizontal	74	PK	26.34	Pass
*4960	54.16	Vertical	74	PK	19.84	Pass
*4960	48.61	Vertical	54	AV	5.39	Pass

Remark:

- (1) AV Emission Level= PK Emission Level+20log(dutycycle)
- (2) Data of measurement within this frequency range shown “-” in the table above means the reading of emissions are attenuated more than 20db below the permissible limits or the field strength is too small to be measured.
- (3) “*” means the emission(s) appear within the restrict bands shall follow the requirement of section 15.205.

10 Test Equipment List

List of Test Instruments

	DESCRIPTION	MANUFACTURER	MODEL NO.	SERIAL NO.	CAL. DUE DATE
CE	EMI Test Receiver	Rohde & Schwarz	ESR 3	101782	2016-7-24
	LISN	Rohde & Schwarz	ENV4200	100249	2016-7-24
	LISN	Rohde & Schwarz	ENV216	100326	2016-7-24
	ISN	Rohde & Schwarz	ENY81	100177	2016-7-24
	ISN	Rohde & Schwarz	ENY81-CA6	101664	2016-7-24
	High Voltage Probe	Rohde & Schwarz	TK9420(VT9420)	9420-58	2016-7-24
	RF Current Probe	Rohde & Schwarz	EZ-17	100816	2016-7-24
RE	Signal Analyzer	Rohde & Schwarz	FSV40	101031	2016-7-24
	Trilog Super Broadband Test Antenna	Schwarzbeck	VULB 9163	708	2016-7-31
	Horn Antenna	Rohde & Schwarz	HF907	102295	2016-7-24
	Wideband Horn Antenna	Q-PAR	QWH-SL-18-40-K-SG	12827	2017-10-21
	Pre-amplifier	Rohde & Schwarz	SCU 18	102230	2016-7-24
	Pre-amplifier	Rohde & Schwarz	SCU 40A	100432	2016-7-24
	Fully Anechoic Chamber	TDK	8X4X4	--	2019-5-29
Conducted	Signal Analyzer	Rohde & Schwarz	FSV40	101030	2016-7-24

11 System Measurement Uncertainty

For a 95% confidence level, the measurement expanded uncertainties for defined systems, in accordance with the recommendations of ISO 17025 were:

System Measurement Uncertainty	
Test Items	Extended Uncertainty
Uncertainty for Conducted Emission 150kHz-30MHz (for test using AMN ENV216 or ENV4200)	3.50dB
Uncertainty for Radiated Spurious Emission 25MHz-3000MHz	Horizontal: 4.95dB; Vertical: 5.02dB;
Uncertainty for Radiated Spurious Emission 3000MHz-18000MHz	Horizontal: 4.89dB; Vertical: 4.88dB;
Uncertainty for Radiated Spurious Emission 18000MHz-40000MHz	Horizontal: 4.93dB; Vertical: 4.92dB;
Uncertainty for Conducted RF test with TS 8997	Power level test involved: 2.04dB Frequency test involved: 1.1×10^{-7}