

FCC SAR Measurement and Test Report

For

High Quality Electronics Corp

2665 south park lane, Pembroke park FL 33009, United States

FCC ID: 2AFYQ-HQNEPTUNE70

FCC Rules:	FCC Part 2.1093 ANSI / IEEE C95.1 :2005 ANSI / IEEE C95.3 :2002 <u>IEEE 1528 :2013</u>
Product Description:	<u>TABLET PC</u>
Tested Model:	<u>HQ Neptune 7.0</u>
Report No.:	<u>STR15118128H</u>
Tested Date:	<u>2015-12-01 to 2015-12-04</u>
Issued Date:	<u>2015-12-07</u>
Tested By:	<u>Lucy Wei / Engineer</u> <i>Lucy Wei</i>
Reviewed By:	<u>Silin Chen / EMC Manager</u> <i>Silin Chen</i>
Approved & Authorized By:	<u>Jandy So / PSQ Manager</u> <i>Jandy So</i>
Prepared By:	

Shenzhen SEM.Test Technology Co., Ltd.
1/F, Building A, Hongwei Industrial Park, Liuxian 2nd Road,
Bao'an District, Shenzhen, P.R.C. (518101)
Tel.: +86-755-33663308 Fax.: +86-755-33663309 Website: www.semtest.com.cn

Note: This test report is limited to the above client company and the product model only. It may not be duplicated without prior permitted by Shenzhen SEM. Test Technology Co., Ltd.

TABLE OF CONTENTS

1. General Information	3
1.1 Product Description for Equipment Under Test (EUT).....	3
1.2 Test Standards	5
1.3 Test Methodology	5
1.4 Test Facility	5
2. Summary of Test Results	6
3. Specific Absorption Rate (SAR).....	7
3.1 Introduction.....	7
3.2 SAR Definition	7
4. SAR Measurement System.....	8
4.1 The Measurement System	8
4.2 Probe	8
4.3 Probe Calibration Process.....	10
4.4 Phantom	11
4.5 Device Holder	11
4.6 Test Equipment List.....	12
5. Tissue Simulating Liquids.....	13
5.1 Composition of Tissue Simulating Liquid.....	13
5.2 Tissue Dielectric Parameters for Head and Body Phantoms	14
5.3 Tissue Calibration Result.....	15
6. SAR Measurement Evaluation	16
6.1 Purpose of System Performance Check.....	16
6.2 System Setup	16
6.3 Validation Results.....	17
7. EUT Testing Position	18
7.1 Define Two Imaginary Lines on The Handset.....	18
7.2 Cheek Position	19
7.3 Tilted Position.....	19
7.4 Body Position	20
7.5 EUT Antenna Position	20
7.6 EUT Testing Position.....	21
8. SAR Measurement Procedures	22
8.1 Measurement Procedures	22
8.2 Spatial Peak SAR Evaluation	22
8.3 Area & Zoom Scan Procedures	23
8.4 Volume Scan Procedures.....	23
8.5 SAR Averaged Methods	23
8.6 Power Drift Monitoring	23
9. SAR Test Result	24
9.1 Conducted RF Output Power	24
9.2 Test Results for Standalone SAR Test.....	28
9.3 Simultaneous Multi-band Transmission SAR Analysis	33
10. Measurement Uncertainty	38
10.1 Uncertainty for EUT SAR Test.....	38
10.2 Uncertainty for System Performance Check.....	39
Annex A. Plots of System Performance Check	41
Annex B. Plots of SAR Measurement	53
Annex C. EUT Photos	156
Annex D. Test Setup Photos	158
Annex E. Calibration Certificate.....	163

1. General Information

1.1 Product Description for Equipment Under Test (EUT)

Client Information

Applicant: High Quality Electronics Corp
Address of applicant: 2665 south park lane, Pembroke park FL 33009, United States

Manufacturer: SHENZHEN HONESTY ELECTRONIC TECHNOLOGY CO., LTD
Address of manufacturer: Room 2802, Dyamic World Building, ZhongHang Road, Futian District, Shenzhen City, China

General Description of EUT	
Product Name:	TABLET PC
Brand Name:	HQ
Model No.:	HQ Neptune 7.0
Adding Model:	F733
Rated Voltage:	DC 3.7V Li-ion Battery
Battery Capacity:	2500mAh
<i>The EUT Main board support GSM850/900/DCS1800/PCS1900, WCDMA Band 2/5 TABLET PC, It is intended for speech, Multimedia Message Service (MMS) transmission. It is equipped with GPRS/EDGE class 12 for GSM850/900/DCS1800/PCS1900, GPS, FM, Bluetooth and Wi-Fi functions. For more information see the following datasheet</i>	
<i>Note: The test data is gathered from a production sample, provided by the manufacturer. The appearance of others models listed in the report is different from main-test model HQ Neptune 7.0, but the circuit and the electronic construction do not change, declared by the manufacturer.</i>	

Technical Characteristics of EUT	
2G	
Support Networks:	GSM, GPRS,EDGE
Support Band:	GSM850/PCS1900
Uplink Frequency:	GSM/GPRS 850: 824~849MHz GSM/GPRS 1900: 1850~1910MHz
Downlink Frequency:	GSM/GPRS 850: 869~894MHz GSM/GPRS 1900: 1930~1990MHz
RF Output Power:	GSM850: 32.45dBm, GSM1900: 29.13dBm
Type of Modulation:	GMSK,8PSK
Antenna Type:	Internal Antenna
Antenna Gain:	GSM850: 0.81dBi: GSM1900: 1.01dBi
GPRS/EDGE Class:	Class 12
3G	

Support Networks:	WCDMA, HSDPA, HSUPA
Support Band:	WCDMA Band II, WCDMA Band V
Uplink Frequency:	WCDMA Band II: 1850~1910MHz WCDMA Band V: 824~849MHz
Downlink Frequency:	WCDMA Band II: 1930~1990MHz WCDMA Band V: 869~894MHz
RF Output Power:	WCDMA850: 22.09dBm, WCDMA1900: 22.50dBm
Type of Modulation:	BPSK, QPSK, 16QAM
Antenna Type:	Integral Antenna
Antenna Gain:	Band V: 0.81dBi: Band II: 1.01dBi
WIFI	
Support Standards:	802.11b, 802.11g, 802.11n
Frequency Range:	2412-2462MHz for 802.11b/g/n(HT20) 2422-2452MHz for 802.11n(HT40)
AV Output Power:	16.95dBm (Conducted)
Type of Modulation:	CCK, OFDM, QPSK, BPSK, 16QAM, 64QAM
Data Rate:	1-11Mbps, 6-54Mbps, up to 150Mbps
Quantity of Channels:	11 for 802.11b/b/n(HT20), 7 for 802.11n(HT40)
Channel Separation:	5MHz
Antenna Type:	Integral Antenna
Antenna Gain:	2.23dBi
Bluetooth	
Bluetooth Version:	V4.0
Frequency Range:	2402-2480MHz
AV Output Power:	6.67dBm (Conducted)
Data Rate:	1Mbps, 2Mbps, 3Mbps
Modulation:	GFSK, Pi/4 QDPSK, 8DPSK
Quantity of Channels:	79/40
Channel Separation:	1MHz/2MHz
Antenna Type:	Integral Antenna
Antenna Gain:	2.23dBi

1.2 Test Standards

The following report is prepared on behalf of the High Quality Electronics Corp in accordance with FCC 47 CFR Part 2.1093, ANSI/IEEE C95.1-2005, IEEE 1528-2013 and KDB 865664 D01 v01r04 and KDB 865664 D02 v01r02 and KDB 941225 D06 Hotspot mode v02r01.

The objective is to determine compliance with FCC Part 2.1093 of the Federal Communication Commissions rules.

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product, which result in lowering the emission, should be checked to ensure compliance has been maintained.

1.3 Test Methodology

All measurements contained in this report were conducted with KDB 865664 D01 v01r04 and KDB 865664 D02 v01r02. The public notice KDB 447498 D01 v06 for Mobile and Portable Devices RF Exposure Procedure also.

1.4 Test Facility

- **FCC – Registration No.: 934118**

Shenzhen SEM.Test Technology Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files and the Registration is 934118.

- **Industry Canada (IC) Registration No.: 11464A**

The 3m Semi-anechoic chamber of Shenzhen SEM.Test Technology Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 11464A.

- **CNAS Registration No.: L4062**

Shenzhen SEM.Test Technology Co., Ltd. is a testing organization accredited by China National Accreditation Service for Conformity Assessment (CNAS) according to ISO/IEC 17025. The accreditation certificate number is L4062. All measurement facilities used to collect the measurement data are located at 1/F, Building A, Hongwei Industrial Park, Liuxian 2nd Road, Bao'an District, Shenzhen, P.R.C (518101)

2. Summary of Test Results

The maximum results of Specific Absorption Rate (SAR) have found during testing are as follows:

Frequency Band	Head SAR	Body-worn (0mm Gap)	Hotspot (0mm Gap)	SAR _{lg} Limit (W/kg)
	Maximum SAR _{lg} (W/kg)	Maximum SAR _{lg} (W/kg)	Maximum SAR _{lg} (W/kg)	
GSM850	0.226	0.348	1.261	1.6
GSM1900	0.275	0.351	0.553	1.6
WCDMA Band V	0.189	0.315	0.315	1.6
WCDMA Band II	0.331	0.301	0.301	1.6
WLAN 2.4GHz	0.027	0.014	0.014	1.6
Simultaneous Transmission	0.358	0.362	1.275	1.6

*The highest reported SAR values for head, body-worn accessory, wireless router(hotspot) , and simultaneous transmission conditions are **0.331W/kg**, **0.351W/kg** , **1.261W/kg**, and **1.275W/kg** respectively*

The device is in compliance with Specific Absorption Rate (SAR) for general population/uncontrolled exposure limits (1.6 W/kg) specified in FCC 47 CFR Part 2.1093 and ANSI/IEEE C95.1-2005, and had been tested in accordance with the measurement methods and procedure specified in IEEE 1528-2013 and KDB 865664 D01 v01r04 and KDB 865664 D02 v01r02

3. Specific Absorption Rate (SAR)

3.1 Introduction

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

3.2 SAR Definition

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (ρ). The equation description is as below:

$$SAR = \frac{d}{dt} \left(\frac{dW}{dm} \right) = \frac{d}{dt} \left(\frac{dW}{\rho dv} \right)$$

SAR is expressed in units of Watts per kilogram (W/kg)

SAR measurement can be either related to the temperature elevation in tissue by

$$SAR = C \left(\frac{\delta T}{\delta t} \right)$$

Where: C is the specific heat capacity, δT is the temperature rise and δt is the exposure duration, or related to the electrical field in the tissue by

$$SAR = \frac{\sigma |E|^2}{\rho}$$

Where: σ is the conductivity of the tissue, ρ is the mass density of the tissue and E is the RMS electrical field strength.

However for evaluating SAR of low power transmitter, electrical field measurement is typically applied.

4. SAR Measurement System

4.1 The Measurement System

Comosar is a system that is able to determine the SAR distribution inside a phantom of human being according to different standards. The Comosar system consists of the following items:

- Main computer to control all the system
- 6 axis robot
- Data acquisition system
- Miniature E-field probe
- Phone holder
- Head simulating tissue

The following figure shows the system.



The EUT under test operating at the maximum power level is placed in the phone holder, under the phantom, which is filled with head simulating liquid. The E-Field probe measures the electric field inside the phantom. The OpenSAR software computes the results to give a SAR value in a 1g or 10g mass.

4.2 Probe

For the measurements the Specific Dosimetric E-Field Probe SSE5 SN 09/13 EP168 with following specifications is used

- Dynamic range: 0.01-100 W/kg
- Probe Length: 330 mm
- Length of Individual Dipoles: 4.5 mm
- Maximum external diameter: 8 mm
- Probe Tip External Diameter : 5 mm
- Distance between dipoles / probe extremity: 2.7mm

- Probe linearity: <0.25 dB
 - Axial Isotropy: <0.25 dB
 - Spherical Isotropy: <0.50 dB
 - Calibration range: 700 to 3000MHz for head & body simulating liquid.
- Angle between probe axis (evaluation axis) and surface normal line: less than 30°

Probe calibration is realized, in compliance with EN 62209-1 and IEEE 1528 STD, with CALISAR, Antennessa proprietary calibration system. The calibration is performed with the EN 62209-1 annexe technique using reference guide at the five frequencies.



$$SAR = \frac{4(P_{fw} - P_{bw})}{ab\delta} \cos^2\left(\pi \frac{y}{a}\right) e^{-(2z/\delta)}$$

Where :

P_{fw} = Forward Power

P_{bw} = Backward Power

a and b = Waveguide dimensions

δ = Skin depth

Keithley configuration:

Rate = Medium; Filter = ON; RDGS = 10; Filter type = Moving Average; Range auto after each calibration, a SAR measurement is performed on a validation dipole and compared with a NPL calibrated probe, to verify it.

The calibration factors, CF(N), for the 3 sensors corresponding to dipole 1, dipole 2 and dipole 3 are:

$$CF(N)=SAR(N)/V_{lin}(N) \quad (N=1,2,3)$$

The linearised output voltage $V_{lin}(N)$ is obtained from the displayed output voltage $V(N)$ using

$$V_{lin}(N)=V(N)*(1+V(N)/DCP(N)) \quad (N=1,2,3)$$

where DCP is the diode compression point in mV.

4.3 Probe Calibration Process

Dosimetric Assessment Procedure

Each E-Probe/Probe Amplifier combination has unique calibration parameters. SATIMO Probe calibration procedure is conducted to determine the proper amplifier settings to enter in the probe parameters. The amplifier settings are determined for a given frequency by subjecting the probe to a known E-field density (1 mW/cm²) using an with CALISAR, Antenna proprietary calibration system.

Free Space Assessment Procedure

The free space E-field from amplified probe outputs is determined in a test chamber. This calibration can be performed in a TEM cell if the frequency is below 1 GHz and in a waveguide or other methodologies above 1 GHz for free space. For the free space calibration, the probe is placed in the volumetric center of the cavity and at the proper orientation with the field. The probe is rotated 360 degrees until the three channels show the maximum reading. The power density readings equates to 1mW/cm².

Temperature Assessment Procedure

E-field temperature correlation calibration is performed in a flat phantom filled with the appropriate simulated head tissue. The E-field in the medium correlates with the temperature rise in the dielectric medium. For temperature correlation calibration a RF transparent thermistor-based temperature probe is used in conjunction with the E-field probe.

Where:

$$SAR = C \frac{\Delta T}{\Delta t}$$

Δt = exposure time (30 seconds),

C = heat capacity of tissue (brain or muscle),

ΔT = temperature increase due to RF exposure.

SAR is proportional to $\Delta T / \Delta t$, the initial rate of tissue heating, before thermal diffusion takes place. The electric field in the simulated tissue can be used to estimate SAR by equating the thermally derived SAR to that with the E- field component.

$$SAR = \frac{|E|^2 \cdot \sigma}{\rho}$$

Where:

σ = simulated tissue conductivity,


ρ = Tissue density (1.25 g/cm³ for brain tissue)

4.4 Phantom

For the measurements the Specific Anthropomorphic Mannequin (SAM) defined by the IEEE SCC-34/SC2 group is used. The phantom is a polyurethane shell integrated in a wooden table. The thickness of the phantom amounts to 2mm +/- 0.2mm. It enables the dosimetric evaluation of left and right phone usage and includes an additional flat phantom part for the simplified performance check. The phantom set-up includes a cover, which prevents the evaporation of the liquid.

4.5 Device Holder

The positioning system allows obtaining cheek and tilting position with a very good accuracy. In compliance with CENELEC, the tilt angle uncertainty is lower than 1°.



System Material	Permittivity	Loss Tangent
Delrin	3.7	0.005


4.6 Test Equipment List

Description	Manufacturer	Model	Serial Number	Cal. Date	Due. Date
E-Field Probe	SATIMO	SSE5	SN 09/13 EP168	2015-06-03	2016-06-02
835MHz Dipole	SATIMO	SID835	SN 47/12 DIP 0G835-204	2015-03-16	2016-03-15
1900MHz Dipole	SATIMO	SID1900	SN 47/12 DIP 1G900-207	2015-03-16	2016-03-15
2450MHz Dipole	SATIMO	SID2450	SN 13/15 DIP 2G450-364	2015-04-13	2016-04-12
Dielectric Probe Kit	SATIMO	SCLMP	SN 47/12 OCPG49	2015-03-16	2016-03-15
SAM Phantom	SATIMO	SAM	SN/ 47/12 SAM95	N/A	N/A
MULTIMETER	KEITHLEY	Keithley 2000	4006367	2015-06-17	2016-06-16
Signal Generator	Rohde & Schwarz	SMR20	100047	2015-06-17	2016-06-16
Universal Tester	Rohde & Schwarz	CMU200	112012	2015-06-17	2016-06-16
Network Analyzer	HP	8753C	2901A00831	2015-06-17	2016-06-16
Data Acquisition Electronics	SATIMO	DAE4	915	2015-06-17	2016-06-16
Directional Couplers	Agilent	778D	20160	2015-06-17	2016-06-16

5. Tissue Simulating Liquids

5.1 Composition of Tissue Simulating Liquid

For the measurement of the field distribution inside the SAM phantom with SMTIMO, the phantom must be filled with around 25 liters of homogeneous body tissue simulating liquid. For head SAR testing, the liquid height from the ear reference point (ERP) of the phantom to the liquid top surface is larger than 15 cm. For body SAR testing, the liquid height from the center of the flat phantom to the liquid top surface is larger than 15 cm. Please see the following photos for the liquid height.



Liquid Height for Head SAR



Liquid Height for Body SAR

The Composition of Tissue Simulating Liquid

Frequency (MHz)	Water (%)	Salt (%)	Triton (%)	HEC (%)	Preventol (%)	DGBE (%)
Head						
835	35.34	0.98	0.00	0.00	63.68	0.00
1900	55.26	0.52	30.40	0.00	0.00	13.82
2450	55.44	0.32	30.50	0.00	0.00	13.74
Body						
835	52.87	1.07	0.00	0.00	46.10	0.00
1900	69.99	0.41	20.66	0.00	0.00	8.93
2450	70.56	0.35	20.88	0.00	0.00	8.21

5.2 Tissue Dielectric Parameters for Head and Body Phantoms

The head tissue dielectric parameters recommended by the IEEE SCC-34/SC-2 in P1528 have been incorporated in the following table. These head parameters are derived from planar layer models simulating the highest expected SAR for the dielectric properties and tissue thickness variations in a human head. Other head and body tissue parameters that have not been specified in P1528 are derived from the tissue dielectric parameters computed from the 4-Cole-Cole equations described in Reference [12] and extrapolated according to the head parameters specified in P1528.

Target Frequency (MHz)	Head		Body	
	Conductivity (σ)	Permittivity (ϵ_r)	Conductivity (σ)	Permittivity (ϵ_r)
150	0.76	52.3	0.80	61.9
300	0.87	45.3	0.92	58.2
450	0.87	43.5	0.94	56.7
835	0.90	41.5	0.97	55.2
900	0.97	41.5	1.05	55.0
915	0.98	41.5	1.06	55.0
1450	1.20	40.5	1.30	54.0
1610	1.29	40.3	1.40	53.8
1800-2000	1.40	40.0	1.52	53.3
2450	1.80	39.2	1.95	52.7
3000	2.40	38.5	2.73	52.0
5800	5.27	35.3	6.00	48.2

5.3 Tissue Calibration Result

The dielectric parameters of the liquids were verified prior to the SAR evaluation using COMOSAR Dielectric Probe Kit and an Agilent Network Analyzer.

Calibration Result for Dielectric Parameters of Tissue Simulating Liquid

Head Tissue Simulating Liquid									
Freq. MHz.	Temp. (°C)	Conductivity			Permittivity			Limit (%)	Date
		Reading (σ)	Target (σ)	Delta (%)	Reading (ϵ_r)	Target (ϵ_r)	Delta (%)		
835	21.2	0.87	0.90	-3.33	41.11	41.50	-0.94	± 5	2015-12-01
1900	21.3	1.38	1.40	-1.43	38.56	40.00	-3.60	± 5	2015-12-01
2450	21.3	1.76	1.80	-2.22	38.6	39.2	-1.53	± 5	2015-12-01

Body Tissue Simulating Liquid									
Freq. MHz.	Temp. (°C)	Conductivity			Permittivity			Limit (%)	Date
		Reading (σ)	Target (σ)	Delta (%)	Reading (ϵ_r)	Target (ϵ_r)	Delta (%)		
835	21.2	0.95	0.97	-2.06	54.85	55.20	-0.63	± 5	2015-12-01
1900	21.3	1.50	1.52	-1.32	52.42	53.30	-1.65	± 5	2015-12-01
2450	21.3	2.00	1.95	2.56	52.3	52.7	-0.76	± 5	2015-12-01

6.1 Purpose of System Performance Check

6.2 System Setup

[illegible]

System Verification Setup Block Diagram



Setup Photo of Dipole Antenna

The output power on dipole port must be calibrated to 24 dBm (250 mW) before dipole is connected.

6.3 Validation Results

Comparing to the original SAR value provided by SATIMO, the validation data should be within its specification of 10 %. Table 6.1 shows the target SAR and measured SAR after normalized to 1W input power. The table below indicates the system performance check can meet the variation criterion.

Frequency	Targeted SAR _{1g}	Measured SAR _{1g}	Normalized SAR _{1g}	Tolerance
MHz	(W/kg)	(W/kg)	(W/kg)	(%)
Head				
835	9.65	2.39	9.56	-0.93
1900	39.59	9.91	39.64	0.13
2450	53.76	13.46	53.84	0.15
Body				
835	9.36	2.36	9.44	0.85
1900	39.01	9.80	39.2	0.49
2450	50.33	12.60	50.4	0.14

Targeted and Measurement SAR

Please refer to Annex A for the plots of system performance check.

7. EUT Testing Position

7.1 Define Two Imaginary Lines on The Handset

- (a) The vertical centerline passes through two points on the front side of the handset - the midpoint of the width w_t of the handset at the level of the acoustic output, and the midpoint of the width w_b of the bottom of the handset.
- (b) The horizontal line is perpendicular to the vertical centerline and passes through the center of the acoustic output. The horizontal line is also tangential to the face of the handset at point A.
- (c) The two lines intersect at point A. Note that for many handsets, point A coincides with the center of the acoustic output; however, the acoustic output may be located elsewhere on the horizontal line. Also note that the vertical centerline is not necessarily parallel to the front face of the handset, especially for clamshell handsets, handsets with flip covers, and other irregularly shaped handsets.



Illustration for Handset Vertical and Horizontal Reference Lines

7.2 Cheek Position

(a) To position the device with the vertical center line of the body of the device and the horizontal line crossing the center piece in a plane parallel to the sagittal plane of the phantom. While maintaining the device in this plane, align the vertical center line with the reference plane containing the three ear and mouth reference point (M: Mouth, RE: Right Ear, and LE: Left Ear) and align the center of the ear piece with the line RE-LE.

(b) To move the device towards the phantom with the ear piece aligned with the line LE-RE until the phone touched the ear. While maintaining the device in the reference plane and maintaining the phone contact with the ear, move the bottom of the phone until any point on the front side is in contact with the cheek of the phantom or until contact with the ear is lost (see Fig. 7.2).




Illustration for Cheek Position

7.3 Tilted Position

(a) To position the device in the “cheek” position described above.

(b) While maintaining the device the reference plane described above and pivoting against the ear, moves it outward away from the mouth by an angle of 15 degrees or until contact with the ear is lost (see Fig. 7.3).




Illustration for Tilted Position

7.4 Body Position

- To position the device parallel to the phantom surface with either keypad up or down.
- To adjust the device parallel to the flat phantom.
- To adjust the distance between the device surface and the flat phantom to 0mm.





Illustration for Body Position

7.5 EUT Antenna Position



Block Diagram for EUT Antenna Position

7.6 EUT Testing Position

Exclusion Distance Calculation				
Frequency Bands	Service	Maximum Tune-up Power	Average Power	Exclusion Distance
GSM850	GSM	32.5dBm	23.5dBm	70mm
GPRS850	GPRS(3slots)	29.5dBm	25.25dBm	90mm
GSM1900	GSM	29.5dBm	20.5dBm	60mm
GPRS1900	GPRS(3slots)	26.5dBm	22.25dBm	60mm
WCDMA Band V	RMC 12.2k	22.5dBm	22.5dBm	60mm
WCDMA Band II	RMC 12.2k	23.0dBm	23.0dBm	60mm
WLAN	802.11b	17dBm	17dBm	30mm
Note: Refer to Chapter 9.1 Conducted RF Output Power				

Remark:

- Referring to KDB 447498 D01v06 and KDB616217 D04 v01r02, the distance of the antennas to all adjacent edges SAR test exclusion for adjacent edges.

Head/Body-worn/Hotspot mode SAR assessments are required for this device. This EUT was tested in different positions for different SAR test modes, more information as below:

Head SAR tests				
Antennas	Right Cheek	Left Cheek	Right Tilted	Left Tilted
WWAN	Yes	Yes	Yes	Yes
WLAN	Yes	Yes	Yes	Yes

Hotspot SAR tests, Test distance: 0mm						
Antennas	Front	Back	Right Side	Left Side	Top Side	Bottom Side
WWAN	Yes	Yes	Yes	Yes	No	Yes
WLAN	Yes	Yes	No	Yes	Yes	No

Body-worn SAR tests, Test distance: 0mm		
Antennas	Front	Back
WWAN	Yes	Yes
WLAN	Yes	Yes

Remark:

- Referring to KDB 616217 D04 v01r02, KDB 248227 D01 v02r01 and KDB 447498 D01 v06, this device is overall diagonal dimension(>20cm) tablet, tested in direct contact (no gap) with flat phantom.

Please refer to Annex D for the EUT test setup photos.

8. SAR Measurement Procedures

8.1 Measurement Procedures

The measurement procedures are as follows:

- (a) Use base station simulator (if applicable) or engineering software to transmit RF power continuously (continuous Tx) in the highest power channel.
- (b) Keep EUT to radiate maximum output power or 100% factor (if applicable)
- (c) Measure output power through RF cable and power meter.
- (d) Place the EUT in the positions as Annex E demonstrates.
- (e) Set scan area, grid size and other setting on the SATIMO software.
- (f) Measure SAR results for the highest power channel on each testing position.
- (g) Find out the largest SAR result on these testing positions of each band
- (h) Measure SAR results for other channels in worst SAR testing position if the SAR of highest power channel is larger than 0.8 W/kg

According to the test standard, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

- (a) Power reference measurement
- (b) Area scan
- (c) Zoom scan
- (d) Power drift measurement

8.2 Spatial Peak SAR Evaluation

The procedure for spatial peak SAR evaluation has been implemented according to the test standard. It can be conducted for 1g and 10g, as well as for user-specific masses. The SATIMO software includes all numerical procedures necessary to evaluate the spatial peak SAR value.

The base for the evaluation is a "cube" measurement. The measured volume must include the 1g and 10g cubes with the highest averaged SAR values. For that purpose, the center of the measured volume is aligned to the interpolated peak SAR value of a previously performed area scan.

The entire evaluation of the spatial peak values is performed within the post-processing engine. The system always gives the maximum values for the 1g and 10g cubes. The algorithm to find the cube with highest averaged SAR is divided into the following stages:

- (a) Extraction of the measured data (grid and values) from the Zoom Scan
- (b) Calculation of the SAR value at every measurement point based on all stored data
- (c) Generation of a high-resolution mesh within the measured volume
- (d) Interpolation of all measured values from the measurement grid to the high-resolution grid
- (e) Extrapolation of the entire 3D field distribution to the phantom surface over the distance from sensor to surface
- (f) Calculation of the averaged SAR within masses of 1g and 10g

8.3 Area & Zoom Scan Procedures

First Area Scan is used to locate the approximate location(s) of the local peak SAR value(s). The measurement grid within an Area Scan is defined by the grid extent, grid step size and grid offset. Next, in order to determine the EM field distribution in a three-dimensional spatial extension, Zoom Scan is required. The Zoom Scan measures 5x5x7 points with step size 8, 8 and 5 mm for 300 MHz to 3 GHz, and 8x8x8 points with step size 4, 4 and 2.5 mm for 3 GHz to 6 GHz. The Zoom Scan is performed around the highest E-field value to determine the averaged SAR-distribution over 10 g.

8.4 Volume Scan Procedures

The volume scan is used for assess overlapping SAR distributions for antennas transmitting in different frequency bands. It is equivalent to an oversized zoom scan used in standalone measurements. The measurement volume will be used to enclose all the simultaneous transmitting antennas. For antennas transmitting simultaneously in different frequency bands, the volume scan is measured separately in each frequency band. In order to sum correctly to compute the 1g aggregate SAR, the EUT remain in the same test position for all measurements and all volume scan use the same spatial resolution and grid spacing (step-size is 4, 4 and 2.5 mm). When all volume scan were completed, the software can combine and subsequently superpose these measurement data to calculating the multiband SAR.

8.5 SAR Averaged Methods

The local SAR inside the phantom is measured using small dipole sensing elements inside a probe body. The probe tip must not be in contact with the phantom surface in order to minimize measurements errors, but the highest local SAR will occur at the surface of the phantom.

An extrapolation is using to determinate this highest local SAR values. The extrapolation is based on a fourth-order least-square polynomial fit of measured data. The local SAR value is then extrapolated from the liquid surface with a 1mm step.

The measurements have to be performed over a limited time (due to the duration of the battery) so the step of measurement is high. It could vary between 5 and 8 mm. To obtain an accurate assessment of the maximum SAR averaged over 10g and 1 g requires a very fine resolution in the three dimensional scanned data array.

8.6 Power Drift Monitoring

All SAR testing is under the EUT install full charged battery and transmit maximum output power. In SATIMO measurement software, the power reference measurement and power drift measurement procedures are used for monitoring the power drift of EUT during SAR test. Both these procedures measure the field at a specified reference position before and after the SAR testing. The software will calculate the field difference in dB. If the power drift more than 5%, the SAR will be retested.

9. SAR Test Result

9.1 Conducted RF Output Power

GSM - Burst Average Power (dBm)						
Band	GSM850			PCS1900		
Channel	128	190	251	512	661	810
Frequency (MHz)	824.2	836.4	848.8	1850.2	1880	1909.8
GSM	32.45	32.34	32.28	29.13	29.09	29.07
GPRS (1 slot)	32.33	32.26	32.21	29.04	28.04	28.05
GPRS (2 slots)	30.70	30.63	30.59	27.43	26.76	26.74
GPRS (3 slots)	29.28	29.19	29.15	26.02	25.99	25.94
GPRS (4 slots)	27.45	27.36	27.34	24.22	24.19	24.12
EDGE (1 slot)	26.76	26.54	26.48	25.42	25.38	25.29
EDGE (2 slot)	24.87	24.71	24.67	23.76	23.70	23.61
EDGE (3 slot)	23.42	23.36	23.35	21.82	21.76	21.67
EDGE (4 slot)	21.09	21.05	21.04	20.43	20.35	20.25

GSM - Source-Based Time-Average Power (dBm)						
Band	GSM850			PCS1900		
Channel	128	190	251	512	661	810
Frequency (MHz)	824.2	836.4	848.8	1850.2	1880	1909.8
GSM	23.45	23.34	23.28	20.13	20.09	20.07
GPRS (1 slot)	23.33	23.26	23.21	20.04	19.04	19.05
GPRS (2 slots)	24.70	24.63	24.59	21.43	20.76	20.74
GPRS (3 slots)	25.03	24.94	24.90	21.77	21.74	21.69
GPRS (4 slots)	24.45	24.36	24.34	21.22	21.19	21.12
EDGE (1 slot)	17.76	17.54	17.48	16.42	16.38	16.29
EDGE (2 slot)	18.87	18.71	18.67	17.76	17.70	17.61
EDGE (3 slot)	19.17	19.11	19.10	17.57	17.51	17.42
EDGE (4 slot)	18.09	18.05	18.04	17.43	17.35	17.25

Note: The source-based time-averaged power is linearly scaled the maximum burst averaged power based on time slots. The calculated method are shown as below:

Source based time-average power = Burst averaged power - Duty cycle factor in dB

Remark:

1. For Head SAR testing, GSM should be evaluated, therefore the EUT was set in GSM for GSM850 and GSM1900 due to its highest source-based time-average power.
2. For Body SAR testing, GPRS should be evaluated, therefore the EUT was set in GPRS (3Tx slots) for GSM850 and GSM1900 due to its highest source-based time-average power.
3. Per KDB 447498 D01 v06, the maximum output power channel is used for SAR testing and for further SAR test reduction.
4. The DUT do not support DTM function.

WCDMA - Average Power (dBm)						
Band	WCDMA Band II			WCDMA Band V		
Channel	9262	9400	9538	4132	4183	4233
Frequency (MHz)	1852.4	1880.0	1907.6	826.4	836.6	846.6
RMC 12.2k	21.81	22.50	21.70	21.95	22.09	21.87
HSDPA Subtest-1	21.65	21.87	21.56	21.89	22.04	21.72
HSDPA Subtest-2	21.61	21.54	21.42	21.65	21.94	21.53
HSDPA Subtest-3	21.58	21.32	24.35	21.48	21.71	21.38
HSDPA Subtest-4	21.42	21.27	21.24	21.27	21.50	21.25
HSUPA Subtest-1	21.67	21.78	21.64	21.78	21.98	21.67
HSUPA Subtest-2	21.59	21.48	21.41	21.54	21.72	21.57
HSUPA Subtest-3	21.55	21.34	21.38	21.36	21.58	21.43
HSUPA Subtest-4	21.63	21.25	21.35	21.18	21.43	21.42
HSUPA Subtest-5	21.57	21.37	21.45	21.10	21.30	21.38

Remark:

1. For Head SAR, per KDB 941225 D01 v03, RMC 12.2kbps setting is used to evaluate SAR. If AMR 12.2kbps power is < 1/4 dB higher than RMC, SAR tests with AMR 12.2kbps can be excluded.
2. For Body SAR, per KDB 941225 D01 v03, RMC 12.2kbps setting is used to evaluate SAR. If HSDPA subset-1 output power is < 1/4 dB higher than RMC, and SAR with RMC 12.2kbps setting is $\leq 1.2\text{W/kg}$, HSDPA SAR evaluation can be excluded.

WLAN - Maximum Average Power				
Test Mode	Data Rate	Channel	Frequency (MHz)	Average Power (dBm)
802.11b	1Mbps	CH 01	2412	16.83
		CH 06	2437	16.95
		CH 11	2462	16.35
802.11g	54Mbps	CH 01	2412	12.83
		CH 06	2437	12.94
		CH 11	2462	12.88
802.11n (20MHz)	MCS7	CH 01	2412	12.71
		CH 06	2437	12.78
		CH 11	2462	12.7
802.11n (40MHz)	MCS7	CH 03	2422	12.75
		CH 06	2437	12.57
		CH 09	2452	12.43

Remark:

1. Per KDB 248227 D01 v02r01, choose the highest output power channel to test SAR and determine further SAR exclusion
2. Per KDB 248227 D01 v02r01, if 11g and 11n average output power is higher than 1/4 dB higher than 11b mode, SAR will be verified.
3. For each frequency band, testing at higher data rates and higher order modulations is not required when the maximum average output power for each of these configurations is less than 1/4 dB higher than those measured at the lowest data rate. For 802.11n mode, SAR test according to the highest power channel with correspondence data rates.

Bluetooth - Maximum Average Power				
Test Mode	Data Rate	Channel	Frequency (MHz)	Average Power (dBm)
GFSK	1Mbps	CH 00	2402	6.56
		CH 39	2441	6.45
		CH 78	2480	6.67
Pi/4 DQPSK	2Mbps	CH 00	2402	5.12
		CH 39	2441	5.24
		CH 78	2480	5.33
8DPSK	3Mbps	CH 00	2402	4.27
		CH 39	2441	4.36
		CH 78	2480	4.37
BLE	1Mbps	CH 00	2402	-1.232
		CH 19	2440	-1.257
		CH 39	2480	-2.145

Remark:

Bluetooth maximum output power is 6.67dBm, and Tune-Up output power is 7.0dBm. Per KDB 648474 D01, the 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR,¹⁶ where

- f(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation¹⁷
- The result is rounded to one decimal place for comparison

Tune-Up Power (dBm)	Max. Power (mW)	Distance (mm)	Frequency (GHz)	Result	Limit
7.0	5.01	5	2.480	1.58	3

The exclusion thresholds is $1.58 < 3$, therefore, the RF exposure evaluation is not required.

9.2 Test Results for Standalone SAR Test

Head SAR

GSM850 – Head SAR Test									
Plot No.	Mode	Test Position Head	Frequency		Output Power (dBm)	Rated Limit (dBm)	Scaling Factor	SAR1g (W/kg)	Scaled SAR1g (W/kg)
			CH.	MHz					
1	GSM	Right Cheek	128	824.2	32.45	32.5	1.0116	0.1943	0.1965
2	GSM	Right Tilted	128	824.2	32.45	32.5	1.0116	0.0984	0.0995
3	GSM	Left Cheek	128	824.2	32.45	32.5	1.0116	0.2235	0.2261
4	GSM	Left Tilted	128	824.2	32.45	32.5	1.0116	0.0839	0.0849

GSM1900 – Head SAR Test									
Plot No.	Mode	Test Position Head	Frequency		Output Power (dBm)	Rated Limit (dBm)	Scaling Factor	SAR1g (W/kg)	Scaled SAR1g (W/kg)
			CH.	M Hz					
14	GSM	Right Cheek	512	1850.2	29.13	29.5	1.0889	0.2525	0.2750
15	GSM	Right Tilted	512	1850.2	29.13	29.5	1.0889	0.0228	0.0248
16	GSM	Left Cheek	512	1850.2	29.13	29.5	1.0889	0.0969	0.1055
17	GSM	Left Tilted	512	1850.2	29.13	29.5	1.0889	0.0235	0.0256

WCDMA Band V – Head SAR Test									
Plot No.	Mode	Test Position Head	Frequency		Output Power (dBm)	Rated Limit (dBm)	Scaling Factor	SAR1g (W/kg)	Scaled SAR1g (W/kg)
			CH.	MHz					
25	RMC	Right Cheek	4183	836.6	22.09	22.5	1.0990	0.1465	0.1610
26	RMC	Right Tilted	4183	836.6	22.09	22.5	1.0990	0.0671	0.0737
27	RMC	Left Cheek	4183	836.6	22.09	22.5	1.0990	0.1721	0.1891
28	RMC	Left Tilted	4183	836.6	22.09	22.5	1.0990	0.0598	0.0657

WCDMA Band II – Head SAR Test									
Plot No.	Mode	Test Position Head	Frequency		Output Power (dBm)	Rated Limit (dBm)	Scaling Factor	SAR1g (W/kg)	Scaled SAR1g (W/kg)
			CH.	MHz					
34	RMC	Right Cheek	9400	1880.0	22.50	23.0	1.1220	0.2954	0.3314
35	RMC	Right Tilted	9400	1880.0	22.50	23.0	1.1220	0.0267	0.0300
36	RMC	Left Cheek	9400	1880.0	22.50	23.0	1.1220	0.1156	0.1297
37	RMC	Left Tilted	9400	1880.0	22.50	23.0	1.1220	0.0256	0.0287

WLAN 2.4GHz – Head SAR Test									
Plot No.	Mode	Test Position Head	Frequency		Output Power (dBm)	Rated Limit (dBm)	Scaling Factor	SAR1g (W/kg)	Scaled SAR1g (W/kg)
			CH.	MHz					
43	802.11b	Right Cheek	06	2437	16.95	17.0	1.0116	0.0266	0.0269
44	802.11b	Right Tilted	06	2437	16.95	17.0	1.0116	0.0115	0.0116
45	802.11b	Left Cheek	06	2437	16.95	17.0	1.0116	0.0104	0.0105
46	802.11b	Left Tilted	06	2437	16.95	17.0	1.0116	0.0056	0.0057

Remark: Per KDB447498 D01 v06, if the highest output channel SAR for each exposure position ≤ 0.8 W/kg other channels SAR tests are not necessary.

Body-worn SAR

GSM850 – Body SAR Test (Gap: 0mm)									
Plot No.	Mode	Test Position Body	Frequency		Output Power (dBm)	Rated Limit (dBm)	Scaling Factor	SAR1g (W/kg)	Scaled SAR1g (W/kg)
			CH.	MHz					
5	GSM	Back	128	824.2	32.45	32.5	1.0116	0.3440	0.3480
6	GSM	Front	128	824.2	32.45	32.5	1.0116	0.2331	0.2358

GSM1900 – Body SAR Test (Gap: 0mm)									
Plot No.	Mode	Test Position Body	Frequency		Output Power (dBm)	Rated Limit (dBm)	Scaling Factor	SAR1g (W/kg)	Scaled SAR1g (W/kg)
			CH.	MHz					
18	GSM	Back	512	1850.2	29.13	29.5	1.0889	0.2301	0.2506
19	GSM	Front	512	1850.2	29.13	29.5	1.0889	0.3227	0.3514

WCDMA Band V – Body SAR Test (Gap: 0mm)									
Plot No.	Mode	Test Position Body	Frequency		Output Power (dBm)	Rated Limit (dBm)	Scaling Factor	SAR1g (W/kg)	Scaled SAR1g (W/kg)
			CH.	MHz					
29	RMC 12.2k	Back Side	4183	836.6	22.09	22.5	1.0990	0.2864	0.3148
30	RMC 12.2k	Front Side	4183	836.6	22.09	22.5	1.0990	0.1982	0.2178

WCDMA Band II – Body SAR Test (Gap: 0mm)									
Plot No.	Mode	Test Position Body	Frequency		Output Power (dBm)	Rated Limit (dBm)	Scaling Factor	SAR1g (W/kg)	Scaled SAR1g (W/kg)
			CH.	MHz					
38	RMC 12.2k	Back Side	9400	1880.0	22.50	23.0	1.1220	0.2042	0.2291
39	RMC 12.2k	Front Side	9400	1880.0	22.50	23.0	1.1220	0.2680	0.3007

WLAN 2.4GHz –Body SAR Test									
Plot No.	Mode	Test Position Body	Frequency		Output Power (dBm)	Rated Limit (dBm)	Scaling Factor	SAR1g (W/kg)	Scaled SAR1g (W/kg)
			CH.	MHz					
47	802.11b	Back Side	06	2437	16.95	17.0	1.0116	0.0141	0.0143
48	802.11b	Front Side	06	2437	16.95	17.0	1.0116	0.0061	0.0062

Remark: Per KDB447498 D01 v06, if the highest output channel SAR for each exposure position ≤ 0.8 W/kg other channels SAR tests are not necessary.

Hotspot SAR

GSM850 – Body SAR Test (Gap: 0mm)									
Plot No.	Mode	Test Position Body	Frequency		Output Power (dBm)	Rated Limit (dBm)	Scaling Factor	SAR1g (W/kg)	Scaled SAR1g (W/kg)
			CH.	MHz					
7	GPRS_3TX	Back Side	128	824.2	29.28	29.5	1.0520	1.1988	1.2611
8	GPRS_3TX	Back Side	190	836.4	29.19	29.5	1.0740	1.0522	1.1301
9	GPRS_3TX	Back Side	251	848.8	29.15	29.5	1.0839	0.9144	0.9911
10	GPRS_3TX	Front Side	128	824.2	29.28	29.5	1.0520	0.5797	0.6098
11	GPRS_3TX	Bottom side	128	824.2	29.28	29.5	1.0520	0.1519	0.1598
12	GPRS_3TX	Right side	128	824.2	29.28	29.5	1.0520	0.5030	0.5291
13	GPRS_3TX	Left side	128	824.2	29.28	29.5	1.0520	0.0692	0.0728

GSM1900 – Body SAR Test (Gap: 0mm)									
Plot No.	Mode	Test Position Body	Frequency		Output Power (dBm)	Rated Limit (dBm)	Scaling Factor	SAR1g (W/kg)	Scaled SAR1g (W/kg)
			CH.	MHz					
20	GPRS_3TX	Back Side	512	1850.2	26.02	26.5	1.1169	0.3387	0.3783
21	GPRS_3TX	Front Side	512	1850.2	26.02	26.5	1.1169	0.4534	0.5064
22	GPRS_3TX	Bottom side	512	1850.2	26.02	26.5	1.1169	0.4952	0.5531
23	GPRS_3TX	Right side	512	1850.2	26.02	26.5	1.1169	0.1245	0.1390
24	GPRS_3TX	Left side	512	1850.2	26.02	26.5	1.1169	0.0348	0.0389

WCDMA Band V – Body SAR Test (Gap: 0mm)									
Plot No.	Mode	Test Position Body	Frequency		Output Power (dBm)	Rated Limit (dBm)	Scaling Factor	SAR1g (W/kg)	Scaled SAR1g (W/kg)
			CH.	MHz					
29	RMC 12.2k	Back Side	4183	836.6	22.09	22.5	1.0990	0.2864	0.3148
30	RMC 12.2k	Front Side	4183	836.6	22.09	22.5	1.0990	0.1982	0.2178
31	RMC 12.2k	Bottom side	4183	836.6	22.09	22.5	1.0990	0.0516	0.0567
32	RMC 12.2k	Right side	4183	836.6	22.09	22.5	1.0990	0.1674	0.1840
33	RMC 12.2k	Left side	4183	836.6	22.09	22.5	1.0990	0.1465	0.1610

WCDMA Band II – Body SAR Test (Gap: 0mm)									
Plot No.	Mode	Test Position Body	Frequency		Output Power (dBm)	Rated Limit (dBm)	Scaling Factor	SAR1g (W/kg)	Scaled SAR1g (W/kg)
			CH.	MHz					
38	RMC 12.2k	Back Side	9400	1880.0	22.50	23.0	1.1220	0.2042	0.2291
39	RMC 12.2k	Front Side	9400	1880.0	22.50	23.0	1.1220	0.2680	0.3007
40	RMC 12.2k	Bottom side	9400	1880.0	22.50	23.0	1.1220	0.2646	0.2969
41	RMC 12.2k	Right side	9400	1880.0	22.50	23.0	1.1220	0.0843	0.0946
42	RMC 12.2k	Left side	9400	1880.0	22.50	23.0	1.1220	0.0464	0.0521

WLAN 2.4GHz –Body SAR Test									
Plot No.	Mode	Test Position Body	Frequency		Output Power (dBm)	Rated Limit (dBm)	Scaling Factor	SAR1g (W/kg)	Scaled SAR1g (W/kg)
			CH.	MHz					
47	802.11b	Back Side	06	2437	16.95	17.0	1.0116	0.0141	0.0143
48	802.11b	Front Side	06	2437	16.95	17.0	1.0116	0.0061	0.0062
49	802.11b	Left side	06	2437	16.95	17.0	1.0116	0.0105	0.0106
50	802.11b	Top Side	06	2437	16.95	17.0	1.0116	0.0052	0.0053

Remark: Per KDB447498 D01 v06, if the highest output channel SAR for each exposure position ≤ 0.8 W/kg other channels SAR tests are not necessary.

9.3 Simultaneous Multi-band Transmission SAR Analysis

List of Mode for Simultaneous Multi-band Transmission

No.	Configurations	Head SAR	Body-worn SAR	Hotspot SAR
1	GSM(Voice) + WLAN(Data)	Yes	Yes	-
2	GPRS/EDGE (Data) + WLAN(Data)	-	-	Yes
3	WCDMA (Voice)+ WLAN(Data)	Yes	Yes	-
4	HSDPA(Data) + WLAN(Data)	-	-	Yes
5	HSUPA(Data) + WLAN(Data)	-	-	Yes
6	GSM(Voice) + Bluetooth(Data)	Yes	Yes	-
7	GPRS/EDGE (Data) + Bluetooth(Data)	-	-	Yes
8	WCDMA(Voice) + Bluetooth(Data)	Yes	Yes	-
9	HSDPA(Data)+ Bluetooth(Data)	-	-	Yes
10	HSUPA(Data) + Bluetooth(Data)	-	-	Yes

Remark:

1. GSM and WCDMA share the same antenna, and cannot transmit simultaneously.
2. WLAN and Bluetooth share the same antenna, and cannot transmit simultaneously.
3. According to the KDB 447498 D01 v06, when standalone SAR test exclusion applies to an antenna that transmits simultaneously with other antennas, the standalone SAR must be estimated according to following to determine simultaneous transmission SAR test exclusion:

$(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm}) \cdot [\sqrt{f(\text{GHz})} / x] \text{ W/kg}$ for test separation distances $\leq 50 \text{ mm}$;

where $x = 7.5$ for 1-g SAR, and $x = 18.75$ for 10-g SAR.

For simultaneous transmission analysis, Bluetooth SAR is estimated per KDB 447498 D01 v06 as below:

Bluetooth:

Tune-Up Power (dBm)	Max. Power (mW)	Distance (mm)	Frequency (GHz)	X	SAR(1g) 5mm	SAR(1g) 0mm
7.0	5.01	5/10	2.480	7.5	0.2104	0.1052

4. The maximum SAR summation is calculated based on the same configuration and test position.

Head SAR

WWAN and WLAN

	WWAN		WLAN	Summed SAR (W/kg)
Position	Band	Scaled SAR (W/kg)	Scaled SAR (W/kg)	
Right Cheek	GSM850	0.1965	0.0269	0.2234
Right Tilted	GSM850	0.0995	0.0116	0.1111
Left Cheek	GSM850	0.2261	0.0105	0.2366
Left Tilted	GSM850	0.0849	0.0057	0.0906
Right Cheek	GSM1900	0.2750	0.0269	0.3019
Right Tilted	GSM1900	0.0248	0.0116	0.0364
Left Cheek	GSM1900	0.1055	0.0105	0.116
Left Tilted	GSM1900	0.0256	0.0057	0.0313
Right Cheek	WCDMA Band V	0.1610	0.0269	0.1879
Right Tilted	WCDMA Band V	0.0737	0.0116	0.0853
Left Cheek	WCDMA Band V	0.1891	0.0105	0.1996
Left Tilted	WCDMA Band V	0.0657	0.0057	0.0714
Right Cheek	WCDMA Band II	0.3314	0.0269	0.3583
Right Tilted	WCDMA Band II	0.0300	0.0116	0.0416
Left Cheek	WCDMA Band II	0.1297	0.0105	0.1402
Left Tilted	WCDMA Band II	0.0287	0.0057	0.0344

WWAN and Bluetooth

	WWAN		Bluetooth	Summed SAR (W/kg)
Position	Band	Scaled SAR (W/kg)	Scaled SAR (W/kg)	
Right Cheek	GSM850	0.1965	0.2104	0.4069
Right Tilted	GSM850	0.0995	0.2104	0.3099
Left Cheek	GSM850	0.2261	0.2104	0.4365
Left Tilted	GSM850	0.0849	0.2104	0.2953
Right Cheek	GSM1900	0.2750	0.2104	0.4854
Right Tilted	GSM1900	0.0248	0.2104	0.2352
Left Cheek	GSM1900	0.1055	0.2104	0.3159
Left Tilted	GSM1900	0.0256	0.2104	0.236
Right Cheek	WCDMA Band V	0.1610	0.2104	0.3714
Right Tilted	WCDMA Band V	0.0737	0.2104	0.2841
Left Cheek	WCDMA Band V	0.1891	0.2104	0.3995
Left Tilted	WCDMA Band V	0.0657	0.2104	0.2761
Right Cheek	WCDMA Band II	0.3314	0.2104	0.5418
Right Tilted	WCDMA Band II	0.0300	0.2104	0.2404
Left Cheek	WCDMA Band II	0.1297	0.2104	0.3401
Left Tilted	WCDMA Band II	0.0287	0.2104	0.2391

Body-worn SAR

WWAN and WLAN

	WWAN		WLAN	Summed SAR (W/kg)
Position	Band	Scaled SAR (W/kg)	Scaled SAR (W/kg)	
Back	GSM850	0.3480	0.0143	0.3623
Front	GSM850	0.2358	0.0062	0.242
Back	GSM1900	0.2506	0.0143	0.2649
Front	GSM1900	0.3514	0.0062	0.3576
Back	WCDMA Band V	0.3148	0.0143	0.3291
Front	WCDMA Band V	0.2178	0.0062	0.224
Back	WCDMA Band II	0.2291	0.0143	0.2434
Front	WCDMA Band II	0.3007	0.0062	0.3069

WWAN and Bluetooth

	WWAN		Bluetooth	Summed SAR (W/kg)
Position	Band	Scaled SAR (W/kg)	Scaled SAR (W/kg)	
Back	GSM850	0.3480	0.1052	0.4532
Front	GSM850	0.2358	0.1052	0.341
Back	GSM1900	0.2506	0.1052	0.3558
Front	GSM1900	0.3514	0.1052	0.4566
Back	WCDMA Band V	0.3148	0.1052	0.42
Front	WCDMA Band V	0.2178	0.1052	0.323
Back	WCDMA Band II	0.2291	0.1052	0.3343
Front	WCDMA Band II	0.3007	0.1052	0.4059

Remark: BT the 1g SAR value is not being captured by the measurement system, the 1g-SAR value is conservatively used for simultaneous transmission analysis.

Hotspot SAR

WWAN and WLAN

	WWAN		WLAN	Summed SAR (W/kg)
Position	Band	Scaled SAR (W/kg)	Scaled SAR (W/kg)	
Back	GSM850	1.2611	0.0143	1.2754
Front	GSM850	0.6098	0.0062	0.616
Top side	GSM850	--	0.0053	0.0053
Bottom side	GSM850	0.1598	--	0.1598
Right side	GSM850	0.5291	--	0.5291
Left side	GSM850	0.0728	0.0106	0.0834
Back	GSM1900	0.3783	0.0143	0.3926
Front	GSM1900	0.5064	0.0062	0.5126
Top side	GSM1900	--	0.0053	0.0053
Bottom side	GSM1900	0.5531	--	0.5531
Right side	GSM1900	0.1390	--	0.1390
Left side	GSM1900	0.0389	0.0106	0.0495
Back	WCDMA Band V	0.3148	0.0143	0.3291
Front	WCDMA Band V	0.2178	0.0062	0.224
Top side	WCDMA Band V	--	0.0053	0.0053
Bottom side	WCDMA Band V	0.0567	--	0.0567
Right side	WCDMA Band V	0.1840	--	0.1840
Left side	WCDMA Band V	0.1610	0.0106	0.1716
Back	WCDMA Band II	0.2291	0.0143	0.2434
Front	WCDMA Band II	0.3007	0.0062	0.3069
Top side	WCDMA Band II	--	0.0053	0.0053
Bottom side	WCDMA Band II	0.2969	--	0.2969
Right side	WCDMA Band II	0.0946	--	0.0946
Left side	WCDMA Band II	0.0521	0.0106	0.0627

WWAN and Bluetooth

	WWAN		Bluetooth	Summed SAR (W/kg)
Position	Band	Scaled SAR (W/kg)	Scaled SAR (W/kg)	
Back	GSM850	1.2611	0.1052	1.3663
Front	GSM850	0.6098	0.1052	0.715
Top side	GSM850	--	0.1052	0.1052
Bottom side	GSM850	0.1598	0.1052	0.265
Right side	GSM850	0.5291	0.1052	0.6343
Left side	GSM850	0.0728	0.1052	0.178
Back	GSM1900	0.3783	0.1052	0.4835
Front	GSM1900	0.5064	0.1052	0.6116
Top side	GSM1900	--	0.1052	0.1052
Bottom side	GSM1900	0.5531	0.1052	0.6583
Right side	GSM1900	0.1390	0.1052	0.2442
Left side	GSM1900	0.0389	0.1052	0.1441
Back	WCDMA Band V	0.3148	0.1052	0.42
Front	WCDMA Band V	0.2178	0.1052	0.323
Top side	WCDMA Band V	--	0.1052	0.1052
Bottom side	WCDMA Band V	0.0567	0.1052	0.1619
Right side	WCDMA Band V	0.1840	0.1052	0.2892
Left side	WCDMA Band V	0.1610	0.1052	0.2662
Back	WCDMA Band II	0.2291	0.1052	0.3343
Front	WCDMA Band II	0.3007	0.1052	0.4059
Top side	WCDMA Band II	--	0.1052	0.1052
Bottom side	WCDMA Band II	0.2969	0.1052	0.4021
Right side	WCDMA Band II	0.0946	0.1052	0.1998
Left side	WCDMA Band II	0.0521	0.1052	0.1573

Remark: BT the 1g SAR value is not being captured by the measurement system, the 1g-SAR value is conservatively used for simultaneous transmission analysis.

10. Measurement Uncertainty

10.1 Uncertainty for EUT SAR Test

a	b	c	d	e= f(d,k)	f	g	h= c*f/e	i= c*g/e	k
Uncertainty Component	Sec.	Tol (+- %)	Prob. Dist.	Div.	Ci (1g)	Ci (10g)	1g Ui (+- %)	10g Ui (+- %)	Vi
Measurement System									
Probe calibration	E.2.1	7.0	N	1	1	1	7.00	7.00	∞
Axial Isotropy	E.2.2	2.5	R	$\sqrt{3}$	$(1_{Cp})^{1/2}$	$(1_{Cp})^{1/2}$	1.02	1.02	∞
Hemispherical Isotropy	E.2.2	4.0	R	$\sqrt{3}$	$(Cp)^{1/2}$	$(Cp)^{1/2}$	1.63	1.63	∞
Boundary effect	E.2.3	1.0	R	$\sqrt{3}$	1	1	0.58	0.58	∞
Linearity	E.2.4	5.0	R	$\sqrt{3}$	1	1	2.89	2.89	∞
System detection limits	E.2.5	1.0	R	$\sqrt{3}$	1	1	0.58	0.58	∞
Readout Electronics	E.2.6	0.02	N	1	1	1	0.02	0.02	∞
Reponse Time	E.2.7	3.0	R	$\sqrt{3}$	1	1	1.73	1.73	∞
Integration Time	E.2.8	2.0	R	$\sqrt{3}$	1	1	1.15	1.15	∞
RF ambient Conditions	E.6.1	3.0	R	$\sqrt{3}$	1	1	1.73	1.73	∞
Probe positioner Mechanical Tolerance	E.6.2	2.0	R	$\sqrt{3}$	1	1	1.15	1.15	∞
Probe positioning with respect to Phantom Shell	E.6.3	0.05	R	$\sqrt{3}$	1	1	0.03	0.03	∞
Extrapolation, interpolation and integration Algorithms for Max. SAR Evaluation	E.5.2	5.0	R	$\sqrt{3}$	1	1	2.89	2.89	∞
Test Sample Related									
Test sample positioning	E.4.2.1	0.03	N	1	1	1	0.03	0.03	N-1
Device Holder Uncertainty	E.4.1.1	5.00	N	1	1	1	5.00	5.00	
Output power Variation - SAR drift measurement	6.6.2	12.02	R	$\sqrt{3}$	1	1	6.94	6.94	∞
Phantom and Tissue Parameters									
Phantom Uncertainty (Shape and thickness tolerances)	E.3.1	0.05	R	$\sqrt{3}$	1	1	0.03	0.03	∞
Liquid conductivity - deviation from target value	E.3.2	5.00	R	$\sqrt{3}$	0.64	0.43	1.85	1.24	
Liquid conductivity - measurement uncertainty	E.3.3	5.00	N	1	0.64	0.43	3.20	2.15	
Liquid permittivity - deviation from target value	E.3.2	0.37	R	$\sqrt{3}$	0.6	0.49	0.13	0.10	
Liquid permittivity -	E.3.3	10.00	N	1	0.6	0.49	6.00	4.90	M

measurement uncertainty									
Combined Standard Uncertainty			RSS				12.98	12.53	
Expanded Uncertainty (95% Confidence interval)			K=2				25.32	24.43	

10.2 Uncertainty for System Performance Check

a	b	c	d	e= f(d,k)	f	g	h= c*f/e	i= c*g/e	k
Uncertainty Component	Sec.	Tol (+ - %)	Prob. Dist.	Div.	Ci (1g)	Ci (10g)	1g Ui (+-%)	10g Ui (+-%)	Vi
Measurement System									
Probe calibration	E.2.1	7.0	N	1	1	1	7.00	7.00	∞
Axial Isotropy	E.2.2	2.5	R	$\sqrt{3}$	$(1_{Cp})^{1/2}$	$(1_{Cp})^{1/2}$	1.02	1.02	∞
Hemispherical Isotropy	E.2.2	4.0	R	$\sqrt{3}$	$(Cp)^{1/2}$	$(Cp)^{1/2}$	1.63	1.63	∞
Boundary effect	E.2.3	1.0	R	$\sqrt{3}$	1	1	0.58	0.58	∞
Linearity	E.2.4	5.0	R	$\sqrt{3}$	1	1	2.89	2.89	∞
System detection limits	E.2.5	1.0	R	$\sqrt{3}$	1	1	0.58	0.58	∞
Readout Electronics	E.2.6	0.02	N	1	1	1	0.02	0.02	∞
Reponse Time	E.2.7	3.0	R	$\sqrt{3}$	1	1	1.73	1.73	∞
Integration Time	E.2.8	2.0	R	$\sqrt{3}$	1	1	1.15	1.15	∞
RF ambient Conditions	E.6.1	3.0	R	$\sqrt{3}$	1	1	1.73	1.73	∞
Probe positioner Mechanical Tolerance	E.6.2	2.0	R	$\sqrt{3}$	1	1	1.15	1.15	∞
Probe positioning with respect to Phantom Shell	E.6.3	0.05	R	$\sqrt{3}$	1	1	0.03	0.03	∞
Extrapolation, interpolation and integration Algorithms for Max. SAR Evaluation	E.5.2	5.0	R	$\sqrt{3}$	1	1	2.89	2.89	∞
Dipole									
Dipole axis to liquid Distance	8,E.4.2	1.00	N	$\sqrt{3}$	1	1	0.58	0.58	N-1
Input power and SAR drift measurement	8,6.6.2	12.02	R	$\sqrt{3}$	1	1	6.94	6.94	∞
Phantom and Tissue Parameters									
Phantom Uncertainty (Shape and thickness tolerances)	E.3.1	0.05	R	$\sqrt{3}$	1	1	0.03	0.03	∞
Liquid conductivity - deviation from target value	E.3.2	5.00	R	$\sqrt{3}$	0.64	0.43	1.85	1.24	

Liquid conductivity measurement uncertainty	-	E.3.3	5.00	N	1	0.64	0.43	3.20	2.15	
Liquid permittivity - deviation from target value		E.3.2	0.37	R	$\sqrt{3}$	0.6	0.49	0.13	0.10	
Liquid permittivity measurement uncertainty	-	E.3.3	10.00	N	1	0.6	0.49	6.00	4.90	M
Combined Standard Uncertainty				RSS				12.00	11.50	
Expanded Uncertainty (95% Confidence interval)				K=2				23.39	22.43	

Annex A. Plots of System Performance Check

MEASUREMENT 1

For Head Liquid

Type: Validation measurement (Fast, 75.00 %)

Date of measurement: 12/01/2015

Measurement duration: 7 minutes 21 seconds


E-field Probe: SSE5 - SN 09/13 EP168; ConvF: 6.93; Calibrated: 06/03/2015

A. Experimental conditions

Area Scan	dx=8mm dy=8mm
Phantom	Validation plane
Device Position	Dipole
Band	CW835
Signal	Duty Cycle 1:1

B. SAR Measurement Results

Frequency (MHz)	835.000000
Relative Permittivity (real part)	41.110245
Conductivity (S/m)	0.871245
Power Variation (%)	1.814580
Ambient Temperature	21.1
Liquid Temperature	21.3






Maximum location: X=0.00, Y=0.00

SAR 10g (W/Kg)	1.129489
SAR 1g (W/Kg)	2.391250

Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.0000	2.4900	1.8942	1.4811	1.3541	1.1123	1.0539



3D screen shot	Hot spot position
	

MEASUREMENT 2

For Head Liquid

Type: Validation measurement (Fast, 75.00 %)

Date of measurement: 12/01/2015

Measurement duration: 12 minutes 21 seconds


E-field Probe: SSE5 - SN 09/13 EP168; ConvF: 6.35; Calibrated: 06/03/2015

A. Experimental conditions

Area Scan	dx=8mm dy=8mm
Phantom	Validation plane
Device Position	Dipole
Band	CW1900
Signal	Duty Cycle 1:1

B. SAR Measurement Results

Frequency (MHz)	1900.000000
Relative Permittivity (real part)	38.560124
Conductivity (S/m)	1.380369
Power Variation (%)	1.022540
Ambient Temperature	21.1
Liquid Temperature	21.3






Maximum location: X=0.00, Y=0.00

SAR 10g (W/Kg)	7.174526
SAR 1g (W/Kg)	9.913214

Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.0000	10.2354	6.8400	5.0121	4.1189	3.0522	2.8424



3D screen shot	Hot spot position
	

MEASUREMENT 3

For Head Liquid

Type: Validation measurement (Fast, 75.00 %)

Date of measurement: 12/01/2015

Measurement duration: 12 minutes 21 seconds


E-field Probe: SSE5 - SN 09/13 EP168; ConvF: 5.64; Calibrated: 06/03/2015

A. Experimental conditions

Area Scan	dx=8mm dy=8mm
Phantom	Validation plane
Device Position	Dipole
Band	CW2450
Signal	CW (Crest factor: 1.0)

B. SAR Measurement Results

Frequency (MHz)	2450.000000
Relative Permittivity (real part)	38.611212
Conductivity (S/m)	1.761202
Power Variation (%)	1.144120
Ambient Temperature	21.1
Liquid Temperature	21.2






Maximum location: X=0.00, Y=0.00

SAR 10g (W/Kg)	6.352122
SAR 1g (W/Kg)	13.462010

Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.0000	12.1355	10.3301	8.4512	6.4365	5.6123	3.5621



3D screen shot	Hot spot position
	

MEASUREMENT 4

For Body Liquid

Type: Validation measurement (Fast, 75.00 %)

Date of measurement: 12/01/2015

Measurement duration: 12 minutes 21 seconds


E-field Probe: SSE5 - SN 09/13 EP168; ConvF: 7.13; Calibrated: 06/03/2015

A. Experimental conditions

Area Scan	dx=8mm dy=8mm
Phantom	Validation plane
Device Position	Dipole
Band	CW835
Signal	Duty Cycle 1:1

B. SAR Measurement Results

Frequency (MHz)	835.000000
Relative Permittivity (real part)	54.851214
Conductivity (S/m)	0.951454
Power Variation (%)	0.901472
Ambient Temperature	21.1
Liquid Temperature	21.3






Maximum location: X=0.00, Y=0.00

SAR 10g (W/Kg)	1.028956
SAR 1g (W/Kg)	2.364211

Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.0000	2.5789	1.1300	0.8795	0.5940	0.5011	0.5100



3D screen shot	Hot spot position
	

MEASUREMENT 5

For Body Liquid

Type: Validation measurement (Fast, 75.00 %)

Date of measurement: 12/01/2015

Measurement duration: 12 minutes 21 seconds


E-field Probe: SSE5 - SN 09/13 EP168; ConvF: 6.55; Calibrated: 06/03/2015

A. Experimental conditions

Area Scan	dx=8mm dy=8mm
Phantom	Validation plane
Device Position	Dipole
Band	CW1900
Signal	Duty Cycle 1:1

B. SAR Measurement Results

Frequency (MHz)	1900.000000
Relative Permittivity (real part)	52.420415
Conductivity (S/m)	1.501966
Power Variation (%)	0.541872
Ambient Temperature	21.1
Liquid Temperature	21.3






Maximum location: X=0.00, Y=0.00

SAR 10g (W/Kg)	5.134651
SAR 1g (W/Kg)	9.801550

Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.0000	10.2031	6.43001	4.9011	4.5325	3.1201	2.5024



3D screen shot	Hot spot position
	

MEASUREMENT 6

For Body Liquid

Type: Validation measurement (Fast, 75.00 %)

Date of measurement: 12/01/2015

Measurement duration: 12 minutes 21 seconds


E-field Probe: SSE5 - SN 09/13 EP168; ConvF: 5.80; Calibrated: 06/03/2015

A. Experimental conditions

Area Scan	dx=8mm dy=8mm
Phantom	Validation plane
Device Position	Dipole
Band	CW2450
Signal	CW (Crest factor: 1.0)

B. SAR Measurement Results

Frequency (MHz)	2450.000000
Relative Permittivity (real part)	52.315622
Conductivity (S/m)	2.001255
Power Variation (%)	0.542660
Ambient Temperature	21.1
Liquid Temperature	21.2






Maximum location: X=0.00, Y=0.00

SAR 10g (W/Kg)	6.351512
SAR 1g (W/Kg)	12.600533

Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.0000	12.1631	10.01221	9.2566	8.5623	6.3469	4.5626



3D screen shot	Hot spot position
	

Annex B. Plots of SAR Measurement

<u>TYPE</u>	<u>BAND</u>	<u>PARAMETERS</u>
Tablet	GSM850	<u>Measurement 1:</u> Right Head with Cheek device position on Low Channel in GSM mode
Tablet	GSM850	<u>Measurement 2:</u> Right Head with Tilt device position on Low Channel in GSM mode
Tablet	GSM850	<u>Measurement 3:</u> Left Head with Cheek device position on Low Channel in GSM mode
Tablet	GSM850	<u>Measurement 4:</u> Left Head with Tilt device position on Low Channel in GSM mode
Tablet	GSM850	<u>Measurement 5:</u> Flat Plane with Back(Body-worn) device position on Low Channel in GSM mode
Tablet	GSM850	<u>Measurement 6:</u> Flat Plane with Front(Body-worn) device position on Low Channel in GSM mode
Tablet	GPRS850_3TX	<u>Measurement 7:</u> Flat Plane with Back device position on Low Channel in GPRS mode
Tablet	GPRS850_3TX	<u>Measurement 8:</u> Flat Plane with Back device position on Middle Channel in GPRS mode
Tablet	GPRS850_3TX	<u>Measurement 9:</u> Flat Plane with Back device position on High Channel in GPRS mode
Tablet	GPRS850_3TX	<u>Measurement 10:</u> Flat Plane with Front device position on Low Channel in GPRS mode
Tablet	GPRS850_3TX	<u>Measurement 11:</u> Flat Plane with Bottom side device position on Low Channel in GPRS mode
Tablet	GPRS850_3TX	<u>Measurement 12:</u> Flat Plane with Right side device position on Low Channel in GPRS mode
Tablet	GPRS850_3TX	<u>Measurement 13:</u> Flat Plane with Left side device position on Low Channel in GPRS mode
Tablet	GSM1900	<u>Measurement 14:</u> Right Head with Cheek device position on Low Channel in GSM mode
Tablet	GSM1900	<u>Measurement 15:</u> Right Head with Tilt device position on Low Channel in GSM mode
Tablet	GSM1900	<u>Measurement 16:</u> Left Head with Cheek device position on Low Channel in GSM mode
Tablet	GSM1900	<u>Measurement 17:</u> Left Head with Tilt device position on Low Channel in GSM mode
Tablet	GSM1900	<u>Measurement 18:</u> Flat Plane with Back(Body-worn) device position on Low Channel in GSM mode
Tablet	GSM1900	<u>Measurement 19:</u> Flat Plane with Front(Body-worn) device position on Low Channel in GSM mode

Tablet	GPRS1900_3TX	Measurement 20: Flat Plane with Back device position on Low Channel in GPRS mode
Tablet	GPRS1900_3TX	Measurement 21: Flat Plane with Front device position on Low Channel in GPRS mode
Tablet	GPRS1900_3TX	Measurement 22: Flat Plane with Bottom side device position on Low Channel in GPRS mode
Tablet	GPRS1900_3TX	Measurement 23: Flat Plane with Right side device position on Low Channel in GPRS mode
Tablet	GPRS1900_3TX	Measurement 24: Flat Plane with Left side device position on Low Channel in GPRS mode
Tablet	WCDMA850_RMC	Measurement 25: Right Head with Cheek device position on Middle Channel in WCDMA mode
Tablet	WCDMA850_RMC	Measurement 26: Right Head with Tilt device position on Middle Channel in WCDMA mode
Tablet	WCDMA850_RMC	Measurement 27: Left Head with Cheek device position on Middle Channel in WCDMA mode
Tablet	WCDMA850_RMC	Measurement 28: Left Head with Tilt device position on Middle Channel in WCDMA mode
Tablet	WCDMA850_RMC	Measurement 29: Flat Plane with Back device position on Middle Channel in WCDMA mode
Tablet	WCDMA850_RMC	Measurement 30: Flat Plane with Front device position on Middle Channel in WCDMA mode
Tablet	WCDMA850_RMC	Measurement 31: Flat Plane with Bottom side device position on Middle Channel in WCDMA mode
Tablet	WCDMA850_RMC	Measurement 32: Flat Plane with Right side device position on Middle Channel in WCDMA mode
Tablet	WCDMA850_RMC	Measurement 33: Flat Plane with Left side device position on Middle Channel in WCDMA mode
Tablet	WCDMA1900_RMC	Measurement 34: Right Head with Cheek device position on Middle Channel in WCDMA mode
Tablet	WCDMA1900_RMC	Measurement 35: Right Head with Tilt device position on Middle Channel in WCDMA mode
Tablet	WCDMA1900_RMC	Measurement 36: Left Head with Cheek device position on Middle Channel in WCDMA mode
Tablet	WCDMA1900_RMC	Measurement 37: Left Head with Tilt device position on Middle Channel in WCDMA mode
Tablet	WCDMA1900_RMC	Measurement 38: Flat Plane with Back device position on Middle Channel in WCDMA mode
Tablet	WCDMA1900_RMC	Measurement 39: Flat Plane with Front device position on Middle Channel in WCDMA mode
Tablet	WCDMA1900_RMC	Measurement 40: Flat Plane with Bottom side device position on Middle Channel in WCDMA mode
Tablet	WCDMA1900_RMC	Measurement 41: Flat Plane with Right side device position on Middle Channel in WCDMA mode

Tablet	WCDMA1900_RMC	<u>Measurement 42:</u> Flat Plane with Left side device position on Middle Channel in WCDMA mode
Tablet	WiFi_802.11b	<u>Measurement 43:</u> Right Head with Cheek device position on Middle Channel in 802.11b mode
Tablet	WiFi_802.11b	<u>Measurement 44:</u> Right Head with Tilt device position on Middle Channel in 802.11b mode
Tablet	WiFi_802.11b	<u>Measurement 45:</u> Left Head with Cheek device position on Middle Channel in 802.11b mode
Tablet	WiFi_802.11b	<u>Measurement 46:</u> Left Head with Tilt device position on Middle Channel in 802.11b mode
Tablet	WiFi_802.11b	<u>Measurement 47:</u> Flat Plane with Back side device position on Middle Channel in 802.11b mode
Tablet	WiFi_802.11b	<u>Measurement 48:</u> Flat Plane with Front side device position on Middle Channel in 802.11b mode
Tablet	WiFi_802.11b	<u>Measurement 49:</u> Flat Plane with Left side device position on Middle Channel in 802.11b mode
Tablet	WiFi_802.11b	<u>Measurement 50:</u> Flat Plane with Top side device position on Middle Channel in 802.11b mode

MEASUREMENT 1

Type: Phone measurement (Complete)

Date of measurement: 12/01/2015

Measurement duration: 12 minutes 3 seconds


E-field Probe: SSE5 - SN 09/13 EP168; ConvF: 6.93; Calibrated: 06/03/2015

A. Experimental conditions

Area Scan	sam_direct_droit2_surf8mm.txt
Phantom	Right head
Device Position	Cheek
Band	GSM850
Channels	Low
Signal	TDMA (Crest factor: 8.0)



B. SAR Measurement Results

Frequency (MHz)	824.200012
Relative Permittivity (real part)	41.110245
Conductivity (S/m)	0.871245
Power Variation (%)	1.568349
Ambient Temperature	21.1
Liquid Temperature	21.3



Maximum location: X=-53.00, Y=-23.00

SAR 10g (W/Kg)	0.147492
SAR 1g (W/Kg)	0.194331



MEASUREMENT 2

Type: Phone measurement (Complete)

Date of measurement: 12/01/2015

Measurement duration: 12 minutes 3 seconds


E-field Probe: SSE5 - SN 09/13 EP168; ConvF: 6.93; Calibrated: 06/03/2015

A. Experimental conditions

Area Scan	sam_direct_droit2_surf8mm.txt
Phantom	Right head
Device Position	Tilt
Band	GSM850
Channels	Low
Signal	TDMA (Crest factor: 8.0)



B. SAR Measurement Results

Frequency (MHz)	824.200012
Relative Permittivity (real part)	41.110245
Conductivity (S/m)	0.871245
Power Variation (%)	1.341528
Ambient Temperature	21.1
Liquid Temperature	21.3



Maximum location: X=-33.00, Y=-16.00

SAR 10g (W/Kg)	0.072110
SAR 1g (W/Kg)	0.098405



MEASUREMENT 3

Type: Phone measurement (Complete)

Date of measurement: 12/01/2015

Measurement duration: 11 minutes 48 seconds


E-field Probe: SSE5 - SN 09/13 EP168; ConvF: 6.93; Calibrated: 06/03/2015

A. Experimental conditions

Area Scan	sam_direct_droit2_surf8mm.txt
Phantom	Left head
Device Position	Cheek
Band	GSM850
Channels	Low
Signal	TDMA (Crest factor: 8.0)


B. SAR Measurement Results



Frequency (MHz)	824.200012
Relative Permittivity (real part)	41.110245
Conductivity (S/m)	0.871245
Power Variation (%)	1.956700
Ambient Temperature	21.1
Liquid Temperature	21.3



Maximum location: X=-49.00, Y=-39.00

SAR 10g (W/Kg)	0.165567
SAR 1g (W/Kg)	0.223478



3D screen shot	Hot spot position
	

MEASUREMENT 4

Type: Phone measurement (Complete)

Date of measurement: 12/01/2015

Measurement duration: 12 minutes 3 seconds


E-field Probe: SSE5 - SN 09/13 EP168; ConvF: 6.93; Calibrated: 06/03/2015

A. Experimental conditions

Area Scan	sam_direct_droit2_surf8mm.txt
Phantom	Left head
Device Position	Tilt
Band	GSM850
Channels	Low
Signal	TDMA (Crest factor: 8.0)



B. SAR Measurement Results

Frequency (MHz)	824.200012
Relative Permittivity (real part)	41.110245
Conductivity (S/m)	0.871245
Power Variation (%)	1.235473
Ambient Temperature	21.1
Liquid Temperature	21.3



Maximum location: X=-33.00, Y=-24.00

SAR 10g (W/Kg)	0.063894
SAR 1g (W/Kg)	0.083942



MEASUREMENT 5

Type: Phone measurement (Complete)

Date of measurement: 12/01/2015

Measurement duration: 12 minutes 3 seconds


E-field Probe: SSE5 - SN 09/13 EP168; ConvF: 7.13; Calibrated: 06/03/2015

A. Experimental conditions

Area Scan	sam_direct_droit2_surf8mm.txt
Phantom	Flat Plane
Device Position	Back(Body-worn)
Band	GSM850
Channels	Low
Signal	TDMA (Crest factor: 8.0)



B. SAR Measurement Results

Frequency (MHz)	824.200012
Relative Permittivity (real part)	54.851214
Conductivity (S/m)	0.951454
Power Variation (%)	0.785060
Ambient Temperature	21.1
Liquid Temperature	21.3



Maximum location: X=-8.00, Y=-32.00

SAR 10g (W/Kg)	0.251080
SAR 1g (W/Kg)	0.344016



MEASUREMENT 6

Type: Phone measurement (Complete)

Date of measurement: 12/01/2015

Measurement duration: 12 minutes 3 seconds


E-field Probe: SSE5 - SN 09/13 EP168; ConvF: 7.13; Calibrated: 06/03/2015

A. Experimental conditions

Area Scan	sam_direct_droit2_surf8mm.txt
Phantom	Flat Plane
Device Position	Front(Body-worn)
Band	GSM850
Channels	Low
Signal	TDMA (Crest factor: 8.0)



B. SAR Measurement Results

Frequency (MHz)	824.200012
Relative Permittivity (real part)	54.851214
Conductivity (S/m)	0.951454
Power Variation (%)	0.979560
Ambient Temperature	21.1
Liquid Temperature	21.3



Maximum location: X=7.00, Y=-17.00

SAR 10g (W/Kg)	0.163917
SAR 1g (W/Kg)	0.233107



MEASUREMENT 7

Type: Phone measurement (Complete)

Date of measurement: 12/01/2015

Measurement duration: 12 minutes 3 seconds


E-field Probe: SSE5 - SN 09/13 EP168; ConvF: 7.13; Calibrated: 06/03/2015

A. Experimental conditions

Area Scan	sam_direct_droit2_surf8mm.txt
Phantom	Flat plane
Device Position	Back
Band	GPRS850_3TX
Channels	Low
Signal	Duty Cycle: 1:2.66



B. SAR Measurement Results

Frequency (MHz)	824.200000
Relative Permittivity (real part)	54.851214
Conductivity (S/m)	0.951454
Power Variation (%)	0.562472
Ambient Temperature	21.1
Liquid Temperature	21.3



Maximum location: X=8.00, Y=-30.00

SAR 10g (W/Kg)	0.903854
SAR 1g (W/Kg)	1.198827



MEASUREMENT 8

Type: Phone measurement (Complete)

Date of measurement: 12/01/2015

Measurement duration: 12 minutes 3 seconds


E-field Probe: SSE5 - SN 09/13 EP168; ConvF: 7.13; Calibrated: 06/03/2015

A. Experimental conditions

Area Scan	sam_direct_droit2_surf8mm.txt
Phantom	Flat plane
Device Position	Back
Band	GPRS850_3TX
Channels	Middle
Signal	Duty Cycle: 1:2.66



B. SAR Measurement Results

Frequency (MHz)	836.600000
Relative Permittivity (real part)	54.851214
Conductivity (S/m)	0.951454
Power Variation (%)	0.653788
Ambient Temperature	21.1
Liquid Temperature	21.3



Maximum location: X=8.00, Y=-32.00

SAR 10g (W/Kg)	0.809349
SAR 1g (W/Kg)	1.052165



MEASUREMENT 9

Type: Phone measurement (Complete)

Date of measurement: 12/01/2015

Measurement duration: 12 minutes 3 seconds


E-field Probe: SSE5 - SN 09/13 EP168; ConvF: 7.13; Calibrated: 06/03/2015

A. Experimental conditions

Area Scan	sam_direct_droit2_surf8mm.txt
Phantom	Flat plane
Device Position	Back
Band	GPRS850_3TX
Channels	High
Signal	Duty Cycle: 1:2.66



B. SAR Measurement Results

Frequency (MHz)	848.799988
Relative Permittivity (real part)	54.851214
Conductivity (S/m)	0.951454
Power Variation (%)	0.562472
Ambient Temperature	21.1
Liquid Temperature	21.3



Maximum location: X=9.00, Y=-38.00

SAR 10g (W/Kg)	0.689355
SAR 1g (W/Kg)	0.914411



MEASUREMENT 10

Type: Phone measurement (Complete)

Date of measurement: 12/01/2015

Measurement duration: 12 minutes 3 seconds


E-field Probe: SSE5 - SN 09/13 EP168; ConvF: 7.13; Calibrated: 06/03/2015

A. Experimental conditions

Area Scan	sam_direct_droit2_surf8mm.txt
Phantom	Flat plane
Device Position	Front
Band	GPRS850_3TX
Channels	Low
Signal	Duty Cycle: 1:2.66



B. SAR Measurement Results

Frequency (MHz)	824.200012
Relative Permittivity (real part)	54.851214
Conductivity (S/m)	0.951454
Power Variation (%)	0.654735
Ambient Temperature	21.1
Liquid Temperature	21.3



Maximum location: X=5.00, Y=-34.00

SAR 10g (W/Kg)	0.429379
SAR 1g (W/Kg)	0.579696



MEASUREMENT 11

Type: Phone measurement (Complete)

Date of measurement: 12/01/2015

Measurement duration: 12 minutes 3 seconds


E-field Probe: SSE5 - SN 09/13 EP168; ConvF: 7.13; Calibrated: 06/03/2015

A. Experimental conditions

Area Scan	sam_direct_droit2_surf8mm.txt
Phantom	Flat plane
Device Position	Bottom
Band	GPRS850_3TX
Channels	Low
Signal	Duty Cycle: 1:2.66



B. SAR Measurement Results

Frequency (MHz)	824.200012
Relative Permittivity (real part)	54.851214
Conductivity (S/m)	0.951454
Power Variation (%)	0.987500
Ambient Temperature	21.1
Liquid Temperature	21.3



Maximum location: X=7.00, Y=-11.00

SAR 10g (W/Kg)	0.097135
SAR 1g (W/Kg)	0.151895



MEASUREMENT 12

Type: Phone measurement (Complete)

Date of measurement: 12/01/2015

Measurement duration: 12 minutes 3 seconds


E-field Probe: SSE5 - SN 09/13 EP168; ConvF: 7.13; Calibrated: 06/03/2015

A. Experimental conditions

Area Scan	sam_direct_droit2_surf8mm.txt
Phantom	Flat plane
Device Position	Right side
Band	GPRS850_3TX
Channels	Low
Signal	Duty Cycle: 1:2.66



B. SAR Measurement Results

Frequency (MHz)	824.200012
Relative Permittivity (real part)	54.851214
Conductivity (S/m)	0.951454
Power Variation (%)	0.153234
Ambient Temperature	21.1
Liquid Temperature	21.3



Maximum location: X=8.00, Y=-47.00

SAR 10g (W/Kg)	0.352376
SAR 1g (W/Kg)	0.503022



MEASUREMENT 13

Type: Phone measurement (Complete)

Date of measurement: 12/01/2015

Measurement duration: 12 minutes 3 seconds


E-field Probe: SSE5 - SN 09/13 EP168; ConvF: 7.13; Calibrated: 06/03/2015

A. Experimental conditions

Area Scan	sam_direct_droit2_surf8mm.txt
Phantom	Flat plane
Device Position	Left side
Band	GPRS850_3TX
Channels	Low
Signal	Duty Cycle: 1:2.66



B. SAR Measurement Results

Frequency (MHz)	824.200012
Relative Permittivity (real part)	54.851214
Conductivity (S/m)	0.951454
Power Variation (%)	0.187583
Ambient Temperature	21.1
Liquid Temperature	21.3



Maximum location: X=-6.00, Y=14.00

SAR 10g (W/Kg)	0.047368
SAR 1g (W/Kg)	0.069171



MEASUREMENT 14

Type: Phone measurement (Complete)

Date of measurement: 12/01/2015

Measurement duration: 12 minutes 3 seconds


E-field Probe: SSE5 - SN 09/13 EP168; ConvF: 6.35; Calibrated: 06/03/2015

A. Experimental conditions

Area Scan	sam_direct_droit2_surf8mm.txt
Phantom	Right head
Device Position	Cheek
Band	GSM1900
Channels	Low
Signal	TDMA (Crest factor: 8.0)


B. SAR Measurement Results



Frequency (MHz)	1850.199951
Relative Permittivity (real part)	38.560124
Conductivity (S/m)	1.380369
Power Variation (%)	1.869568
Ambient Temperature	21.1
Liquid Temperature	21.3



Maximum location: X=-57.00, Y=-57.00

SAR 10g (W/Kg)	0.121562
SAR 1g (W/Kg)	0.252510



3D screen shot	Hot spot position
	

MEASUREMENT 15

Type: Phone measurement (Complete)

Date of measurement: 12/01/2015

Measurement duration: 12 minutes 3 seconds


E-field Probe: SSE5 - SN 09/13 EP168; ConvF: 6.35; Calibrated: 06/03/2015

A. Experimental conditions

Area Scan	sam_direct_droit2_surf8mm.txt
Phantom	Right head
Device Position	Tilt
Band	GSM1900
Channels	Low
Signal	TDMA (Crest factor: 8.0)


B. SAR Measurement Results



Frequency (MHz)	1850.199951
Relative Permittivity (real part)	38.560124
Conductivity (S/m)	1.380369
Power Variation (%)	1.564858
Ambient Temperature	21.1
Liquid Temperature	21.3



Maximum location: X=-49.00, Y=-41.00

SAR 10g (W/Kg)	0.012926
SAR 1g (W/Kg)	0.022772



3D screen shot	Hot spot position
	

MEASUREMENT 16

Type: Phone measurement (Complete)

Date of measurement: 12/01/2015

Measurement duration: 11 minutes 48 seconds


E-field Probe: SSE5 - SN 09/13 EP168; ConvF: 6.35; Calibrated: 06/03/2015

A. Experimental conditions

Area Scan	sam_direct_droit2_surf8mm.txt
Phantom	Left head
Device Position	Cheek
Band	GSM1900
Channels	Low
Signal	TDMA (Crest factor: 8.0)


B. SAR Measurement Results



Frequency (MHz)	1850.199951
Relative Permittivity (real part)	38.560124
Conductivity (S/m)	1.380369
Power Variation (%)	1.769548
Ambient Temperature	21.1
Liquid Temperature	21.3



Maximum location: X=-55.00, Y=-48.00

SAR 10g (W/Kg)	0.052384
SAR 1g (W/Kg)	0.096932



3D screen shot	Hot spot position
	

MEASUREMENT 17

Type: Phone measurement (Complete)

Date of measurement: 12/01/2015

Measurement duration: 12 minutes 3 seconds


E-field Probe: SSE5 - SN 09/13 EP168; ConvF: 6.35; Calibrated: 06/03/2015

A. Experimental conditions

Area Scan	sam_direct_droit2_surf8mm.txt
Phantom	Left head
Device Position	Tilt
Band	GSM1900
Channels	Low
Signal	TDMA (Crest factor: 8.0)



B. SAR Measurement Results

Frequency (MHz)	1850.199951
Relative Permittivity (real part)	38.560124
Conductivity (S/m)	1.380369
Power Variation (%)	1.785600
Ambient Temperature	21.1
Liquid Temperature	21.3



Maximum location: X=-64.00, Y=-23.00

SAR 10g (W/Kg)	0.013509
SAR 1g (W/Kg)	0.023498



MEASUREMENT 18

Type: Phone measurement (Complete)

Date of measurement: 12/01/2015

Measurement duration: 12 minutes 3 seconds


E-field Probe: SSE5 - SN 09/13 EP168; ConvF: 6.55; Calibrated: 06/03/2015

A. Experimental conditions

Area Scan	sam_direct_droit2_surf8mm.txt
Phantom	Flat Plane
Device Position	Back(Body-worn)
Band	GSM1900
Channels	Low
Signal	TDMA (Crest factor: 8.0)



B. SAR Measurement Results

Frequency (MHz)	1850.199951
Relative Permittivity (real part)	52.420415
Conductivity (S/m)	1.501966
Power Variation (%)	0.568946
Ambient Temperature	21.1
Liquid Temperature	21.3



Maximum location: X=31.00, Y=6.00

SAR 10g (W/Kg)	0.115940
SAR 1g (W/Kg)	0.230051



MEASUREMENT 19

Type: Phone measurement (Complete)

Date of measurement: 12/01/2015

Measurement duration: 12 minutes 3 seconds


E-field Probe: SSE5 - SN 09/13 EP168; ConvF: 6.55; Calibrated: 06/03/2015

A. Experimental conditions

Area Scan	sam_direct_droit2_surf8mm.txt
Phantom	Flat Plane
Device Position	Front(Body-worn)
Band	GSM1900
Channels	Low
Signal	TDMA (Crest factor: 8.0)



B. SAR Measurement Results

Frequency (MHz)	1850.199951
Relative Permittivity (real part)	52.420415
Conductivity (S/m)	1.501966
Power Variation (%)	0.760430
Ambient Temperature	21.1
Liquid Temperature	21.3



Maximum location: X=-15.00, Y=18.00

SAR 10g (W/Kg)	0.158389
SAR 1g (W/Kg)	0.322743



MEASUREMENT 20

Type: Phone measurement (Complete)

Date of measurement: 12/01/2015

Measurement duration: 12 minutes 3 seconds


E-field Probe: SSE5 - SN 09/13 EP168; ConvF: 6.55; Calibrated: 06/03/2015

A. Experimental conditions

Area Scan	sam_direct_droit2_surf8mm.txt
Phantom	Flat plane
Device Position	Back side
Band	GPRS1900_3TX
Channels	Low
Signal	Duty Cycle: 1:2.66



B. SAR Measurement Results

Frequency (MHz)	1850.199951
Relative Permittivity (real part)	52.420415
Conductivity (S/m)	1.501966
Power Variation (%)	0.986340
Ambient Temperature	21.1
Liquid Temperature	21.3



Maximum location: X=24.00, Y=9.00

SAR 10g (W/Kg)	0.168241
SAR 1g (W/Kg)	0.338706



MEASUREMENT 21

Type: Phone measurement (Complete)

Date of measurement: 12/01/2015

Measurement duration: 12 minutes 3 seconds


E-field Probe: SSE5 - SN 09/13 EP168; ConvF: 6.55; Calibrated: 06/03/2015

A. Experimental conditions

Area Scan	sam_direct_droit2_surf8mm.txt
Phantom	Flat plane
Device Position	Front side
Band	GPRS1900_3TX
Channels	Low
Signal	Duty Cycle: 1:2.66



B. SAR Measurement Results

Frequency (MHz)	1850.199951
Relative Permittivity (real part)	52.420415
Conductivity (S/m)	1.501966
Power Variation (%)	0.596045
Ambient Temperature	21.1
Liquid Temperature	21.3



Maximum location: X=-14.00, Y=10.00

SAR 10g (W/Kg)	0.218709
SAR 1g (W/Kg)	0.453430



MEASUREMENT 22

Type: Phone measurement (Complete)

Date of measurement: 12/01/2015

Measurement duration: 12 minutes 3 seconds


E-field Probe: SSE5 - SN 09/13 EP168; ConvF: 6.55; Calibrated: 06/03/2015

A. Experimental conditions

Area Scan	sam_direct_droit2_surf8mm.txt
Phantom	Flat plane
Device Position	Bottom
Band	GPRS1900_3TX
Channels	Low
Signal	Duty Cycle: 1:2.66

B. SAR Measurement Results


Frequency (MHz)	1850.199951
Relative Permittivity (real part)	52.420415
Conductivity (S/m)	1.501966
Power Variation (%)	0.857329
Ambient Temperature	21.1
Liquid Temperature	21.3





Maximum location: X=1.00, Y=16.00

SAR 10g (W/Kg)	0.237646
SAR 1g (W/Kg)	0.495210

Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	0.0000	0.5340	0.2383	0.1018	0.0454



3D screen shot	Hot spot position
	

MEASUREMENT 23

Type: Phone measurement (Complete)

Date of measurement: 12/01/2015

Measurement duration: 12 minutes 3 seconds

E-field Probe: SSE5 - SN 09/13 EP168; ConvF: 6.55; Calibrated: 06/03/2015

A. Experimental conditions

Area Scan	sam_direct_droit2_surf8mm.txt
Phantom	Flat plane
Device Position	Right side
Band	GPRS1900_3TX
Channels	Low
Signal	Duty Cycle: 1:2.66

B. SAR Measurement Results

Frequency (MHz)	1850.199951
Relative Permittivity (real part)	52.420415
Conductivity (S/m)	1.501966
Power Variation (%)	0.509750
Ambient Temperature	21.1
Liquid Temperature	21.3

