




FCC RF Test Report

APPLICANT : Xiaomi Communications Co., Ltd.
EQUIPMENT : Mobile Phone
BRAND NAME : MI
MODEL NAME : M1804C3DG
FCC ID : 2AFZZ-RMSC3DG
STANDARD : 47 CFR Part 2, 22(H), 24(E), 27(L), 27(M)
CLASSIFICATION : PCS Licensed Transmitter Held to Ear (PCE)

The product was received on Apr. 16, 2018 and completely tested on May 22, 2018. We, Sporton International (Kunshan) Inc., would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.26-2015 and shown compliance with the applicable technical standards.

This report contains data that were produced under subcontract by Laboratory Sporton International (Shenzhen) Inc.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International (Kunshan) Inc., the test report shall not be reproduced except in full.



Approved by: James Huang / Manager

Sportun International (Kunshan) Inc.
No.3-2 Ping-Xiang Rd, Kunshan Development Zone Kunshan City Jiangsu Province 215335
China



TABLE OF CONTENTS

REVISION HISTORY.....	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION	5
1.1 Applicant	5
1.2 Manufacturer.....	5
1.3 Product Feature of Equipment Under Test.....	5
1.4 Product Specification of Equipment Under Test.....	6
1.5 Modification of EUT	6
1.6 Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator	7
1.7 Testing Location	10
1.8 Applicable Standards.....	11
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST	12
2.1 Test Mode.....	12
2.2 Connection Diagram of Test System.....	14
2.3 Support Unit used in test configuration and system	14
2.4 Measurement Results Explanation Example.....	14
2.5 Frequency List of Low/Middle/High Channels	15
3 CONDUCTED TEST ITEMS	17
3.1 Measuring Instruments	17
3.2 Test Setup	17
3.3 Test Result of Conducted Test	17
3.4 Conducted Output Power and ERP/EIRP	18
3.5 Peak-to-Average Ratio	19
3.6 Occupied Bandwidth.....	20
3.7 Conducted Band Edge	21
3.8 Conducted Spurious Emission	23
3.9 Frequency Stability	24
4 RADIATED TEST ITEMS	25
4.1 Measuring Instruments	25
4.2 Test Setup	25
4.3 Test Result of Radiated Test	25
4.4 Radiated Spurious Emission	26
5 LIST OF MEASURING EQUIPMENT	27
6 UNCERTAINTY OF EVALUATION	29
APPENDIX A. TEST RESULTS OF CONDUCTED TEST	
APPENDIX B. TEST RESULTS OF RADIATED TEST	
APPENDIX C. TEST SETUP PHOTOGRAPHS	



REVISION HISTORY



SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.4	§2.1046	Conducted Output Power	Reporting Only	PASS	-
	§22.913(a)(5)	Effective Radiated Power (Band 5)	ERP < 7 Watt	PASS	-
	§24.232(c) §27.50(h)(2)	Equivalent Isotropic Radiated Power (Band 2) (Band 7) (Band 38)	EIRP < 2Watt	PASS	-
	§27.50(d)(4)	Equivalent Isotropic Radiated Power (Band 4)	EIRP < 1Watt	PASS	-
3.5	§24.232(d)	Peak-to-Average Ratio	<13 dB	PASS	-
3.6	§2.1049	Occupied Bandwidth	Reporting Only	PASS	-
3.7	§2.1051 §22.917(a) §24.238(a) §27.53(h)	Conducted Band Edge Measurement (Band 2) (Band 4) (Band 5)	< 43+10log ₁₀ (P[Watts])	PASS	-
	§27.53(m)(4)	Conducted Band Edge Measurement (Band 7) (Band 38)	§27.53(m)(4)		
3.8	§2.1051 §22.917(a) §24.238(a) §27.53(h)	Conducted Spurious Emission (Band 2) (Band 4) (Band 5)	< 43+10log ₁₀ (P[Watts])	PASS	-
	§2.1051 §27.53(m)(4)	Conducted Spurious Emission (Band 7) (Band 38)	< 55+10log ₁₀ (P[Watts])		
3.9	§2.1055 §22.355	Frequency Stability Temperature & Voltage	< 2.5 ppm for Part 22H	PASS	-
	§2.1055 §24.235 §27.54		Within Authorized Band		
4.4	§2.1053 §22.917(a) §24.238(a) §27.53(h)	Radiated Spurious Emission (Band 2) (Band 4) (Band 5)	< 43+10log ₁₀ (P[Watts])	PASS	Under limit 17.70 dB at 7771.500 MHz
	§2.1053 §27.53(m)(4)	Radiated Spurious Emission (Band 7) (Band 38)	< 55+10log ₁₀ (P[Watts])		



1 General Description

1.1 Applicant

Xiaomi Communications Co., Ltd.

The Rainbow City of China Resources, NO.68, Qinghe Middle Street, Haidian District, Beijing, China

1.2 Manufacturer

Xiaomi Communications Co., Ltd.

The Rainbow City of China Resources, NO.68, Qinghe Middle Street, Haidian District, Beijing, China

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Mobile Phone
Brand Name	MI
Model Name	M1804C3DG
FCC ID	2AFZZ-RMSC3DG
EUT supports Radios application	GSM/GPRS/EGPRS/WCDMA/HSPA/ DC-HSDPA/HSPA+/LTE WLAN 2.4GHz 802.11b/g/n HT20 Bluetooth v3.0 + EDR/ Bluetooth v 4.0 LE/ Bluetooth v 4.2 LE
IMEI Code	Conducted: 868151030010237/868151030010245 Radiation: 868151030010435/868151030010443 for LTE B2/4/5 868151030010013/868151030010021 for LTE B7/38
HW Version	P2
SW Version	MIUI9
EUT Stage	Production Unit

Remark:

1. The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.
2. There are two types of EUT, the difference between two samples is for memory, the sample 1 is 3+32GB capacity and the sample 2 is 4+64GB capacity. According to the difference, we only choose sample 1 to perform full test.



1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx Frequency	LTE Band 2 : 1850.7 MHz ~ 1909.3 MHz LTE Band 4 : 1710.7 MHz ~ 1754.3 MHz LTE Band 5 : 824.7 MHz ~ 848.3 MHz LTE Band 7 : 2502.5 MHz ~ 2567.5 MHz LTE Band 38 : 2572.5MHz ~ 2617.5MHz
Rx Frequency	LTE Band 2 : 1930.7 MHz ~ 1989.3 MHz LTE Band 4 : 2110.7 MHz ~ 2154.3 MHz LTE Band 5 : 869.7 MHz ~ 893.3 MHz LTE Band 7 : 2622.5MHz ~ 2687.5 MHz LTE Band 38 : 2572.5MHz ~ 2617.5MHz
Bandwidth	LTE Band 2 : 1.4MHz / 3MHz / 5MHz / 10MHz / 15MHz / 20MHz LTE Band 4 : 1.4MHz / 3MHz / 5MHz / 10MHz / 15MHz / 20MHz LTE Band 5 : 1.4MHz / 3MHz / 5MHz / 10MHz LTE Band 7 : 5MHz / 10MHz / 15MHz / 20MHz LTE Band 38 : 5MHz / 10MHz / 15MHz / 20MHz
Maximum Output Power to Antenna	LTE Band 2 : 23.65 dBm LTE Band 4 : 23.50 dBm LTE Band 5 : 23.50 dBm LTE Band 7 : 23.75 dBm LTE Band 38 : 23.62 dBm
Antenna Gain	LTE Band 2 : -0.19 dBi LTE Band 4 : -0.55 dBi LTE Band 5 : -1.67 dBi LTE Band 7 : 1.14 dBi LTE Band 38 : 0.45 dBi
Type of Modulation	QPSK / 16QAM / 64QAM

1.5 Modification of EUT

No modifications are made to the EUT during all test items.



1.6 Maximum ERF/EIRP Power, Frequency Tolerance, and Emission Designator

LTE Band 2		QPSK			16QAM		
BW (MHz)	Frequency Range (MHz)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum EIRP(W)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum EIRP(W)
1.4	1850.7 ~ 1909.3	1M09G7D	-	0.2193	1M10W7D	-	0.1910
3	1851.5 ~ 1908.5	2M71G7D	-	0.2104	2M72W7D	-	0.1910
5	1852.5 ~ 1907.5	4M50G7D	-	0.2163	4M50W7D	-	0.1858
10	1855.0 ~ 1905.0	9M17G7D	0.0026	0.2138	9M13W7D	-	0.1854
15	1857.5 ~ 1902.5	13M5G7D	-	0.2213	13M6W7D	-	0.1888
20	1860.0 ~ 1900.0	18M3G7D	-	0.2218	18M5W7D	-	0.1803
LTE Band 2		64QAM					
BW (MHz)	Frequency Range (MHz)	Emission Designator (99%OBW)		Frequency Tolerance (ppm)		Maximum EIRP(W)	
1.4	1850.7 ~ 1909.3	1M09W7D		-		0.1476	
3	1851.5 ~ 1908.5	2M73W7D		-		0.1396	
5	1852.5 ~ 1907.5	4M51W7D		-		0.1426	
10	1855.0 ~ 1905.0	9M11W7D		-		0.1455	
15	1857.5 ~ 1902.5	13M5W7D		-		0.1500	
20	1860.0 ~ 1900.0	18M4W7D		-		0.1374	
LTE Band 4		QPSK			16QAM		
BW (MHz)	Frequency Range (MHz)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum EIRP(W)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum EIRP(W)
1.4	1710.7 ~ 1754.3	1M09G7D	-	0.1936	1M09W7D	-	0.1652
3	1711.5 ~ 1753.5	2M72G7D	-	0.1968	2M73W7D	-	0.1726
5	1712.5 ~ 1752.5	4M51G7D	-	0.1950	4M51W7D	-	0.1698
10	1715.0 ~ 1750.0	9M07G7D	0.0179	0.1932	9M03W7D	-	0.1722
15	1717.5 ~ 1747.5	13M6G7D	-	0.1963	13M6W7D	-	0.1671
20	1720.0 ~ 1745.0	18M4G7D	-	0.1972	18M5W7D	-	0.1667



LTE Band 4		64QAM					
BW (MHz)	Frequency Range (MHz)	Emission Designator (99%OBW)		Frequency Tolerance (ppm)		Maximum EIRP(W)	
1.4	1710.7 ~ 1754.3	1M09W7D		-		0.1306	
3	1711.5 ~ 1753.5	2M73W7D		-		0.1294	
5	1712.5 ~ 1752.5	4M51W7D		-		0.1324	
10	1715.0 ~ 1750.0	9M07W7D		-		0.1327	
15	1717.5 ~ 1747.5	13M5W7D		-		0.1294	
20	1720.0 ~ 1745.0	18M5W7D		-		0.1303	
LTE Band 5		QPSK			16QAM		
BW (MHz)	Frequency Range (MHz)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum EIRP(W)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum EIRP(W)
1.4	824.7 ~ 848.3	1M10G7D	-	0.0895	1M09W7D	-	0.0764
3	825.5 ~ 847.5	2M72G7D	-	0.0906	2M72W7D	-	0.0820
5	826.5 ~ 846.5	4M53G7D	-	0.0925	4M50W7D	-	0.0826
10	829.0 ~ 844.0	9M09G7D	0.0061	0.0929	9M07W7D	-	0.0796
LTE Band 5		64QAM					
BW (MHz)	Frequency Range (MHz)	Emission Designator (99%OBW)		Frequency Tolerance (ppm)		Maximum EIRP(W)	
1.4	824.7 ~ 848.3	1M10W7D		-		0.0597	
3	825.5 ~ 847.5	2M72W7D		-		0.0634	
5	826.5 ~ 846.5	4M53W7D		-		0.0637	
10	829.0 ~ 844.0	9M07W7D		-		0.0587	
LTE Band 7		QPSK			16QAM		
BW (MHz)	Frequency Range (MHz)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum EIRP(W)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum EIRP(W)
5	2502.5 ~ 2567.5	4M53G7D	-	0.3048	4M51W7D	-	0.2594
10	2505.0 ~ 2565.0	9M07G7D	0.0142	0.3048	9M05W7D	-	0.2570
15	2507.5 ~ 2562.5	13M5G7D	-	0.3027	13M6W7D	-	0.2564
20	2510.0 ~ 2560.0	18M5G7D	-	0.3083	18M4W7D	-	0.2564



LTE Band 7		64QAM					
BW (MHz)	Frequency Range (MHz)	Emission Designator (99%OBW)		Frequency Tolerance (ppm)		Maximum EIRP(W)	
5	2502.5 ~ 2567.5	4M52W7D		-		0.1968	
10	2505.0 ~ 2565.0	9M09W7D		-		0.2014	
15	2507.5 ~ 2562.5	13M5W7D		-		0.2037	
20	2510.0 ~ 2560.0	18M4W7D		-		0.2037	
LTE Band 38		QPSK			16QAM		
BW (MHz)	Frequency Range (MHz)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum EIRP(W)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum EIRP(W)
5	2572.5 ~ 2617.5	4M50G7D	-	0.2500	4M49W7D	-	0.2000
10	2575.0 ~ 2615.0	9M03G7D	0.0023	0.2547	9M05W7D	-	0.2037
15	2577.5 ~ 2612.5	13M5G7D	-	0.2535	13M5W7D	-	0.2014
20	2580.0 ~ 2610.0	18M4G7D	-	0.2553	18M4W7D	-	0.2014
LTE Band 38		64QAM					
BW (MHz)	Frequency Range (MHz)	Emission Designator (99%OBW)		Frequency Tolerance (ppm)		Maximum EIRP(W)	
5	2572.5 ~ 2617.5	4M50W7D		-		0.1500	
10	2575.0 ~ 2615.0	9M05W7D		-		0.1521	
15	2577.5 ~ 2612.5	13M5W7D		-		0.1510	
20	2580.0 ~ 2610.0	18M5W7D		-		0.1517	



1.7 Testing Location

Sportun International (Kunshan) Inc. is accredited to ISO 17025 by National Voluntary Laboratory Accreditation Program (NVLAP code: 600155-0) and the FCC designation No. is CN5013.

Test Site	Sportun International (Kunshan) Inc.	
Test Site Location	No.3-2 Ping-Xiang Rd, Kunshan Development Zone Kunshan City Jiangsu Province 215335 China TEL : +86-512-57900158 FAX : +86-512-57900958	
Test Site No.	Sportun Site No.	FCC Test Firm Registration No.
	TH01-KS	630927

Note: The test site complies with ANSI C63.4 2014 requirement.

Sportun International (Shenzhen) Inc. is accredited to ISO 17025 by National Voluntary Laboratory Accreditation Program (NVLAP code: 600156-0) and the FCC designation No. is N5019.

Test Site	Sportun International (Shenzhen) Inc.	
Test Site Location	No. 3 Bldg the third floor of south, Shahe River west, Fengzeyuan Warehouse, Nanshan District Shenzhen City Guangdong Province 518055 China TEL: +86-755-3320-2398	
Test Site No.	Sportun Site No.	FCC Test Firm Registration No.
	03CH01-SZ 03CH03-SZ	577730

Note:

1. The test site complies with ANSI C63.4 2014 requirement.
2. Test data subcontracted: radiated spurious emissions in section 4.4 of this report.



1.8 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 2, 22(H), 24(E), 27(L), 27(M)
- ♦ ANSI C63.26-2015
- ♦ FCC KDB 971168 D01 Power Meas License Digital Systems v03r01
- ♦ FCC KDB 412172 D01 Determining ERP and EIRP v01r01

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



2 Test Configuration of Equipment Under Test

2.1 Test Mode

Antenna port conducted and radiated test items listed below are performed according to KDB 971168 D01 Power Meas License Digital Systems v03r01 with maximum output power.


Radiated measurements are performed by rotating the EUT in three different orthogonal test planes to find the maximum emission.

Test Items	Band	Bandwidth (MHz)						Modulation			RB #			Test Channel		
		1.4	3	5	10	15	20	QPSK	16QAM	64QAM	1	Half	Full	L	M	H
Max. Output Power	2	v	v	v	v	v	v	v	v	v	v	v	v	v	v	v
	4	v	v	v	v	v	v	v	v	v	v	v	v	v	v	v
	5	v	v	v	v	-	-	v	v	v	v	v	v	v	v	v
	7	-	-	v	v	v	v	v	v	v	v	v	v	v	v	v
	38	-	-	v	v	v	v	v	v	v	v	v	v	v	v	v
Peak-to-Average Ratio	2						v	v	v	v	v		v	v	v	v
	4						v	v	v	v	v		v	v	v	v
	5				v	-	-	v	v	v	v		v	v	v	v
	7	-	-				v	v	v	v	v		v	v	v	v
	38	-	-				v	v	v	v	v		v	v	v	v
26dB and 99% Bandwidth	2	v	v	v	v	v	v	v	v	v			v	v	v	v
	4	v	v	v	v	v	v	v	v	v			v	v	v	v
	5	v	v	v	v	-	-	v	v	v			v	v	v	v
	7	-	-	v	v	v	v	v	v	v			v	v	v	v
	38	-	-	v	v	v	v	v	v	v			v	v	v	v
Conducted Band Edge	2	v	v	v	v	v	v	v	v	v	v	v	v	v	v	v
	4	v	v	v	v	v	v	v	v	v	v	v	v	v	v	v
	5	v	v	v	v	-	-	v	v	v	v	v	v	v	v	v
	7	-	-	v	v	v	v	v	v	v	v	v	v	v	v	v
	38	-	-	v	v	v	v	v	v	v	v	v	v	v	v	v



Test Items	Band	Bandwidth (MHz)						Modulation			RB #			Test Channel		
		1.4	3	5	10	15	20	QPSK	16QAM	64QAM	1	Half	Full	L	M	H
Conducted Spurious Emission	2	v	v	v	v	v	v	v	v	v	v	v		v	v	v
	4	v	v	v	v	v	v	v	v	v	v	v		v	v	v
	5	v	v	v	v	-	-	v	v	v	v			v	v	v
	7	-	-	v	v	v	v	v	v	v	v	v		v	v	v
	38	-	-	v	v	v	v	v	v	v	v	v		v	v	v
Frequency Stability	2				v			v						v		v
	4				v			v						v		v
	5				v	-	-	v						v		v
	7	-	-	v				v						v		v
	38	-	-	v				v						v		v
E.R.P / E.I.R.P	2	v	v	v	v	v	v	v	v	v	v	v		v	v	v
	4	v	v	v	v	v	v	v	v	v	v	v		v	v	v
	5	v	v	v	v	-	-	v	v	v	v	v		v	v	v
	7	-	-	v	v	v	v	v	v	v	v	v		v	v	v
	38	-	-	v	v	v	v	v	v	v	v	v		v	v	v
Radiated Spurious Emission	2	v	v	v	v	v	v	v				v				v
	4	v	v	v	v	v	v	v				v				v
	5	v	v	v	v	-	-	v				v				v
	7	-	-	v	v	v	v	v				v				v
	38	-	-	v	v	v	v	v				v				v
Note	1. The mark "v" means that this configuration is chosen for testing 2. The mark "-" means that this bandwidth is not supported. 3. The device is investigated from 30MHz to 10 times of fundamental signal for radiated spurious emission test under different RB size/offset and modulations in exploratory test. Subsequently, only the worst case emissions are reported.															

2.2 Connection Diagram of Test System



2.3 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	DC Power Supply	GW	GPS-3030D	N/A	N/A	Unshielded, 1.8 m
2.	LTE Base Station	Anritsu	MT8820C	N/A	N/A	Unshielded, 1.8 m
3.	Earphone	Apple	MC690ZP/A	N/A	Shielded, 1.0m	N/A

2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

The spectrum analyzer offset is derived from RF cable loss.

Offset = RF cable loss.

Following shows an offset computation example with cable loss 5.1 dB.

Example :

$$\begin{aligned} \text{Offset(dB)} &= \text{RF cable loss(dB)} (\text{dB}) \\ &= 5.1(\text{dB}) \end{aligned}$$



2.5 Frequency List of Low/Middle/High Channels

LTE Band 2 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
20	Channel	18700	18900	19100
	Frequency	1860	1880	1900
15	Channel	18675	18900	19125
	Frequency	1857.5	1880	1902.5
10	Channel	18650	18900	19150
	Frequency	1855	1880	1905
5	Channel	18625	18900	19175
	Frequency	1852.5	1880	1907.5
3	Channel	18615	18900	19185
	Frequency	1851.5	1880	1908.5
1.4	Channel	18607	18900	19193
	Frequency	1850.7	1880	1909.3

LTE Band 4 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
20	Channel	20050	20175	20300
	Frequency	1720	1732.5	1745
15	Channel	20025	20175	20325
	Frequency	1717.5	1732.5	1747.5
10	Channel	20000	20175	20350
	Frequency	1715	1732.5	1750
5	Channel	19975	20175	20375
	Frequency	1712.5	1732.5	1752.5
3	Channel	19965	20175	20385
	Frequency	1711.5	1732.5	1753.5
1.4	Channel	19957	20175	20393
	Frequency	1710.7	1732.5	1754.3



LTE Band 5 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
10	Channel	20450	20525	20600
	Frequency	829	836.5	844
5	Channel	20425	20525	20625
	Frequency	826.5	836.5	846.5
3	Channel	20415	20525	20635
	Frequency	825.5	836.5	847.5
1.4	Channel	20407	20525	20643
	Frequency	824.7	836.5	848.3

LTE Band 7 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
20	Channel	20850	21100	21350
	Frequency	2510	2535	2560
15	Channel	20825	21100	21375
	Frequency	2507.5	2535	2562.5
10	Channel	20800	21100	21400
	Frequency	2505	2535	2565
5	Channel	20775	21100	21425
	Frequency	2502.5	2535	2567.5

LTE Band 38 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
20	Channel	37850	38000	38150
	Frequency	2580	2595	2610
15	Channel	37825	38000	38175
	Frequency	2577.5	2595	2612.5
10	Channel	37800	38000	38200
	Frequency	2575	2595	2615
5	Channel	37775	38000	38225
	Frequency	2572.5	2595	2617.5


3 Conducted Test Items

3.1 Measuring Instruments


See list of measuring instruments of this test report.

3.2 Test Setup


3.2.1 Conducted Output Power



3.2.2 Peak-to-Average Ratio, Occupied Bandwidth ,Conducted Band-Edge and Conducted Spurious Emission



3.2.3 Frequency Stability



3.3 Test Result of Conducted Test

Please refer to Appendix A.



3.4 Conducted Output Power and ERP/EIRP

3.4.1 Description of the Conducted Output Power Measurement and ERP/EIRP Measurement

A system simulator was used to establish communication with the EUT. Its parameters were set to force the EUT transmitting at maximum output power. The measured power in the radio frequency on the transmitter output terminals shall be reported.

The ERP of mobile transmitters must not exceed 7 Watts for LTE Band 5.

The EIRP of mobile transmitters must not exceed 2 Watts for LTE Band 2 and Band 7 and Band 38.

The EIRP of mobile transmitters must not exceed 1 Watts for LTE Band 4.

According to KDB 412172 D01 Power Approach,

$EIRP = P_T + G_T - L_C$, $ERP = EIRP - 2.15$, where

P_T = transmitter output power in dBm

G_T = gain of the transmitting antenna in dBi

L_C = signal attenuation in the connecting cable between the transmitter and antenna in dB

3.4.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.2
2. The transmitter output port was connected to the system simulator.
3. Set EUT at maximum power through the system simulator.
4. Select lowest, middle, and highest channels for each band and different modulation.
5. Measure and record the power level from the system simulator.



3.5 Peak-to-Average Ratio

3.5.1 Description of the PAR Measurement

Power Complementary Cumulative Distribution Function (CCDF) curves provide a means for characterizing the power peaks of a digitally modulated signal on a statistical basis. A CCDF curve depicts the probability of the peak signal amplitude exceeding the average power level. Most contemporary measurement instrumentation include the capability to produce CCDF curves for an input signal provided that the instrument's resolution bandwidth can be set wide enough to accommodate the entire input signal bandwidth. In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

3.5.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.2.3.4 (CCDF).
2. The EUT was connected to spectrum and system simulator via a power divider.
3. Set the CCDF (Complementary Cumulative Distribution Function) option in spectrum analyzer.
4. The highest RF powers were measured and recorded the maximum PAPR level associated with a probability of 0.1 %.
5. Record the deviation as Peak to Average Ratio.



3.6 Occupied Bandwidth

3.6.1 Description of Occupied Bandwidth Measurement

The occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The 26 dB emission bandwidth is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated 26 dB below the maximum in-band spectral density of the modulated signal. Spectral density (power per unit bandwidth) is to be measured with a detector of resolution bandwidth equal to approximately 1.0% of the emission bandwidth.

3.6.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.4
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the spectrum analyzer shall be between two and five times the anticipated OBW.
4. The nominal resolution bandwidth (RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.
5. Set the detection mode to peak, and the trace mode to max hold.
6. Determine the reference value: Set the EUT to transmit a modulated signal. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace. (this is the reference value)
7. Determine the “-26 dB down amplitude” as equal to (Reference Value – X).
8. Place two markers, one at the lowest and the other at the highest frequency of the envelope of the spectral display such that each marker is at or slightly below the “-X dB down amplitude” determined in step 6. If a marker is below this “-X dB down amplitude” value it shall be placed as close as possible to this value. The OBW is the positive frequency difference between the two markers.
9. Use the 99 % power bandwidth function of the spectrum analyzer and report the measured bandwidth.



3.7 Conducted Band Edge

3.7.1 Description of Conducted Band Edge Measurement

22.917(a)

For operations in the 824 – 849 MHz band, the FCC limit is $43 + 10\log_{10}(P[\text{Watts}])$ dB below the transmitter power P(Watts) in a 100kHz bandwidth. However, in the 1MHz bands immediately outside and adjacent to the licensee's frequency block, a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.

24.238 (a)

For operations in the 1850-1910 and 1930-1990 MHz band, the FCC limit is $43 + 10\log_{10}(P[\text{Watts}])$ dB below the transmitter power P(Watts) in a 1MHz bandwidth. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.

27.53 (h)

For operations in the 1710 – 1755 MHz band, the FCC limit is $43 + 10\log_{10}(P[\text{Watts}])$ dB below the transmitter power P(Watts) in a 1 MHz bandwidth. However, in the 1MHz bands immediately outside and adjacent to the licensee's frequency block, a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.

27.53(m)(4)

For mobile digital stations, the attenuation factor shall be not less than $40 + 10 \log (P)$ dB on all frequencies between the channel edge and 5 megahertz from the channel edge, $43 + 10 \log (P)$ dB on all frequencies between 5 megahertz and X megahertz from the channel edge, and $55 + 10 \log (P)$ dB on all frequencies more than X megahertz from the channel edge, where X is the greater of 6 megahertz or the actual emission bandwidth as defined in paragraph (m)(6) of this section. In addition, the attenuation factor shall not be less than $43 + 10 \log (P)$ dB on all frequencies between 2490.5 MHz and 2496 MHz and $55 + 10 \log (P)$ dB at or below 2490.5 MHz. Mobile Satellite Service licensees operating on frequencies below 2495 MHz may also submit a documented interference complaint against BRS licensees operating on channel BRS Channel 1 on the same terms and conditions as adjacent channel BRS or EBS licensees.



3.7.2 Test Procedures

1. The testing follows ANSI C63.26 section 5.7
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The band edges of low and high channels for the highest RF powers were measured.
4. Set RBW $\geq 1\%$ EBW in the 1MHz band immediately outside and adjacent to the band edge.
5. Beyond the 1 MHz band from the band edge, RBW=1MHz was used.
6. Set spectrum analyzer with RMS detector.
7. Offset has included the duty factor for LTE Band 38. Duty factor = $10 \log(1/x)$, where x is the measured duty cycle
8. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
9. Checked that all the results comply with the emission limit line.

Example:

The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)

$$\begin{aligned} &= P(W) - [43 + 10\log(P)] \text{ (dB)} \\ &= [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)} = -13 \text{ dBm}. \end{aligned}$$

10. For LTE Band 7, 38, the other 40 dB, and 55 dB have additionally applied same calculation above.



3.8 Conducted Spurious Emission

3.8.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log(P)$ dB.

For Band 7,38:

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $55 + 10 \log(P)$ dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10th harmonic.

3.8.2 Test Procedures

1. The testing follows ANSI C63.26 section 5.7
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.
The path loss was compensated to the results for each measurement.
4. The middle channel for the highest RF power within the transmitting frequency was measured.
5. The conducted spurious emission for the whole frequency range was taken.
6. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz.
7. Set spectrum analyzer with RMS detector.
8. Offset has included the duty factor for LTE Band 38. Duty factor = $10 \log(1/x)$, where x is the measured duty cycle
9. Taking the record of maximum spurious emission.
10. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
11. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
 $= P(W) - [43 + 10\log(P)]$ (dB)
 $= [30 + 10\log(P)]$ (dBm) - $[43 + 10\log(P)]$ (dB)
 $= -13$ dBm.
12. For Band 7, 38
The limit line is derived from $55 + 10\log(P)$ dB below the transmitter power P(Watts)
 $= P(W) - [55 + 10\log(P)]$ (dB)
 $= [30 + 10\log(P)]$ (dBm) - $[55 + 10\log(P)]$ (dB)
 $= -25$ dBm.



3.9 Frequency Stability

3.9.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ ($\pm 2.5\text{ppm}$) of the center frequency.

3.9.2 Test Procedures for Temperature Variation

1. The testing follows ANSI C63.26 section 5.6.4
2. The EUT was set up in the thermal chamber and connected with the system simulator.
3. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
4. With power OFF, the temperature was raised in 10°C step up to 50°C . The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

3.9.3 Test Procedures for Voltage Variation

1. The testing follows ANSI C63.26 section 5.6.5
2. The EUT was placed in a temperature chamber at $20 \pm 5^{\circ}\text{C}$ and connected with the system simulator.
3. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value for other than hand carried battery equipment.
4. For hand carried, battery powered equipment, reduce the primary ac or dc supply voltage to the battery operating end point, which shall be specified by the manufacturer.
5. The variation in frequency was measured for the worst case.


4 Radiated Test Items

4.1 Measuring Instruments


See list of measuring instruments of this test report.

4.2 Test Setup

4.2.1 For radiated test from 30MHz to 1GHz



4.2.2 For radiated test above 1GHz



4.3 Test Result of Radiated Test

Please refer to Appendix B.



4.4 Radiated Spurious Emission

4.4.1 Description of Radiated Spurious Emission

The radiated spurious emission was measured by substitution method according to ANSI C63.26.

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43 + 10 \log(P)$ dB.

For Band 7, 38

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $55 + 10 \log(P)$ dB.

The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

4.4.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.5
2. The EUT was placed on a turntable with 0.8 meter height for frequency below 1GHz and 1.5 meter height for frequency above 1GHz respectively above ground.
3. The EUT was set 3 meters from the receiving antenna mounted on the antenna tower.
4. The table was rotated 360 degrees to determine the position of the highest spurious emission.
5. The height of the receiving antenna is varied between 1m to 4m to search the maximum spurious emission for both horizontal and vertical polarizations.
6. During the measurement, the system simulator parameters were set to force the EUT transmitting at maximum output power.
7. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
8. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
9. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
10. $EIRP (\text{dBm}) = S.G. \text{ Power} - \text{Tx Cable Loss} + \text{Tx Antenna Gain}$
11. $ERP (\text{dBm}) = EIRP - 2.15$
12. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)

$$= P(\text{W}) - [43 + 10\log(P)] \text{ (dB)}$$

$$= [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)}$$

$$= -13 \text{ dBm.}$$

13. For Band 7, 38:

The limit line is derived from $55 + 10\log(P)$ dB below the transmitter power P(Watts)



5 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101040	10Hz~40GHz	Aug. 08, 2017	Apr. 26, 2018~May 22, 2018	Aug. 07, 2018	Conducted (TH01-KS)
Radio communication analyzer	Anritsu	MT8820C	6201300652	2G/3G/LTE_full band	Aug. 08, 2017	Apr. 26, 2018~May 22, 2018	Aug. 07, 2018	Conducted (TH01-KS)
Thermal Chamber	Ten Billion	TTC-B3S	TBN-960502	-40~+150°C	Oct. 12, 2017	Apr. 26, 2018~May 22, 2018	Oct. 11, 2018	Conducted (TH01-KS)
EMI Test Receiver&SA	Agilent	N9038A	MY52260185	20Hz~26.5GHz	Apr. 19, 2018	Apr. 30, 2018~May 12, 2018	Apr. 18, 2019	Radiation (03CH01-SZ)
HF Amplifier	KEYSIGHT	83017A	MY53270104	0.5GHz~26.5Ghz	Oct. 19, 2017	Apr. 30, 2018~May 12, 2018	Oct. 18, 2018	Radiation (03CH01-SZ)
Bilog Antenna	TeseQ	CBL6112D	35408	30MHz-2GHz	Apr. 19, 2018	Apr. 30, 2018~May 12, 2018	Apr. 18, 2019	Radiation (03CH01-SZ)
Double Ridge Horn Antenna	ETS Lindgren	3117	119436	1GHz~18GHz	Jul. 28, 2017	Apr. 30, 2018~May 12, 2018	Jul. 27, 2018	Radiation (03CH01-SZ)
SHF-EHF Horn	com-power	AH-840	101071	18Ghz-40GHz	Jun. 16, 2017	Apr. 30, 2018~May 12, 2018	Jun. 15, 2018	Radiation (03CH01-SZ)
LF Amplifier	Burgeon	BPA-530	102209	0.01~3000Mhz	Apr. 19, 2018	Apr. 30, 2018~May 12, 2018	Apr. 18, 2019	Radiation (03CH01-SZ)
HF Amplifier	MITEQ	AMF-7D-00 101800-30-1	1707137	1GHz~18GHz	Oct. 19, 2017	Apr. 30, 2018~May 12, 2018	Oct. 18, 2018	Radiation (03CH01-SZ)
HF Amplifier	MITEQ	TTA1840-35-HG	1871923	18GHz~40GHz	Jul. 18, 2017	Apr. 30, 2018~May 12, 2018	Jul. 17, 2018	Radiation (03CH01-SZ)
AC Power Source	Chroma	61601	616010001985	N/A	NCR	Apr. 30, 2018~May 12, 2018	NCR	Radiation (03CH01-SZ)
Turn Table	EM	EM1000	N/A	0~360 degree	NCR	Apr. 30, 2018~May 12, 2018	NCR	Radiation (03CH01-SZ)
Antenna Mast	EM	EM1000	N/A	1 m~4 m	NCR	Apr. 30, 2018~May 12, 2018	NCR	Radiation (03CH01-SZ)



Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
EXA Spectrum Analyzer	KEYSIGHT	N9010A	MY55150246	10Hz~44GHz;	Apr. 19, 2018	Apr. 30, 2018~May 12, 2018	Apr. 18, 2019	Radiation (03CH03-SZ)
Bilog Antenna	TeseQ	CBL6112D	35408	30MHz-2GHz	Apr. 19, 2018	Apr. 30, 2018~May 12, 2018	Apr. 18, 2019	Radiation (03CH03-SZ)
Double Ridge Horn Antenna	SCHWARZBECK	BBHA9120D	9120D-1355	1GHz~18GHz	Jul. 09, 2017	Apr. 30, 2018~May 12, 2018	Jul. 08, 2018	Radiation (03CH03-SZ)
Amplifier	Burgeon	BPA-530	102210	0.01Hz ~3000MHz	Oct. 09, 2017	Apr. 30, 2018~May 12, 2018	Oct. 08, 2018	Radiation (03CH03-SZ)
HF Amplifier	MITEQ	TTA1840-35-HG	1871923	18GHz~40GHz	Jul. 18, 2017	Apr. 30, 2018~May 12, 2018	Jul. 17, 2018	Radiation (03CH03-SZ)
SHF-EHF Horn	com-power	AH-840	101071	18Ghz-40GHz	Jun. 16, 2017	Apr. 30, 2018~May 12, 2018	Jun. 15, 2018	Radiation (03CH03-SZ)
Amplifier	Agilent Technologies	83017A	MY39501302	500MHz~26.5GHz	Dec. 27, 2017	Apr. 30, 2018~May 12, 2018	Dec. 26, 2018	Radiation (03CH03-SZ)
AC Power Source	Chroma	61601	616010001985	N/A	NCR	Apr. 30, 2018~May 12, 2018	NCR	Radiation (03CH03-SZ)
Turn Table	EM	EM1000	N/A	0~360 degree	NCR	Apr. 30, 2018~May 12, 2018	NCR	Radiation (03CH03-SZ)
Antenna Mast	EM	EM1000	N/A	1 m~4 m	NCR	Apr. 30, 2018~May 12, 2018	NCR	Radiation (03CH03-SZ)

NCR: No Calibration Required



6 Uncertainty of Evaluation

For 03CH01-SZ

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_{c(y)}$)	4.8dB
--	-------

Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_{c(y)}$)	5.0dB
--	-------

Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_{c(y)}$)	4.3dB
--	-------

For 03CH03-SZ

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_{c(y)}$)	5.0dB
--	-------

Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_{c(y)}$)	4.8dB
--	-------

Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_{c(y)}$)	4.6dB
--	-------



Appendix A. Test Results of Conducted Test

Conducted Output Power(Average power)

LTE Band 2 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
20	1	0	QPSK	23.18	23.10	23.07
20	1	49		23.65	23.42	23.45
20	1	99		22.90	22.95	23.03
20	50	0		22.30	22.41	22.39
20	50	24		22.42	22.38	22.33
20	50	50		22.32	22.31	22.16
20	100	0		22.39	22.37	22.24
20	1	0		22.13	22.18	22.51
20	1	49	16-QAM	22.35	22.56	22.75
20	1	99		22.01	22.45	22.56
20	50	0		21.31	21.35	21.45
20	50	24		21.31	21.41	21.33
20	50	50		21.26	21.30	21.23
20	100	0		21.41	21.40	21.26
20	1	0		21.10	21.39	21.07
20	1	49		21.51	21.57	21.36
20	1	99	64QAM	21.20	21.21	20.96
20	50	0		20.35	20.45	20.32
20	50	24		20.31	20.39	20.28
20	50	50		20.31	20.32	20.21
20	100	0		20.30	20.32	20.23
15	1	0	QPSK	23.27	23.19	23.21
15	1	37		23.64	23.40	23.43
15	1	74		23.23	23.15	23.15
15	36	0		22.40	22.42	22.31
15	36	20		22.47	22.46	22.32
15	36	39		22.44	22.41	22.38
15	75	0		22.37	22.46	22.32
15	1	0		22.88	22.47	22.79



15	1	37	64QAM	22.95	22.28	22.83
15	1	74		22.71	22.34	22.73
15	36	0		21.42	21.47	21.39
15	36	20		21.39	21.38	21.29
15	36	39		21.43	21.35	21.40
15	75	0		21.49	21.37	21.43
15	1	0		21.61	21.60	21.50
15	1	37		21.95	21.68	21.50
15	1	74		21.42	21.77	21.50
15	36	0		20.45	20.38	20.45
15	36	20		20.29	20.41	20.41
15	36	39		20.28	20.36	20.37
15	75	0		20.23	20.38	20.25



LTE Band 2 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
10	1	0	QPSK	23.46	23.33	23.27
	1	25		23.49	23.42	23.36
	1	49		23.21	23.26	23.23
	25	0		22.40	22.38	22.42
	25	12		22.36	22.39	22.30
	25	25		22.46	22.36	22.41
	50	0		22.47	22.37	22.41
10	1	0	16-QAM	22.36	22.87	22.51
	1	25		22.46	22.67	22.56
	1	49		22.30	22.41	22.43
	25	0		21.45	21.50	21.39
	25	12		21.47	21.45	21.32
	25	25		21.50	21.33	21.31
	50	0		21.42	21.32	21.30
10	1	0	64QAM	21.71	21.58	21.45
	1	25		21.82	21.69	21.60
	1	49		21.59	21.54	21.58
	25	0		20.29	20.52	20.35
	25	12		20.41	20.44	20.30
	25	25		20.32	20.33	20.32
	50	0		20.41	20.46	20.38
5	1	0	QPSK	23.32	23.29	23.11
	1	12		23.54	23.48	23.52
	1	24		23.23	23.21	23.10
	12	0		22.37	22.39	22.29
	12	7		22.36	22.39	22.38
	12	13		22.46	22.44	22.37
	25	0		22.31	22.31	22.36
5	1	0	16-QAM	22.73	22.49	22.71
	1	12		22.72	22.88	22.76
	1	24		22.41	22.47	22.67
	12	0		21.38	21.42	21.34
	12	7		21.42	21.38	21.35



5	12	13	64QAM	21.48	21.36	21.36
5	25	0		21.45	21.34	21.28
5	1	0		21.50	21.41	21.36
5	1	12		21.70	21.70	21.73
5	1	24		21.57	21.31	21.37
5	12	0		20.44	20.38	20.24
5	12	7		20.43	20.46	20.38
5	12	13		20.35	20.42	20.38
5	25	0		20.41	20.25	20.31



LTE Band 2 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
3	1	0	QPSK	23.40	23.39	23.28
	1	8		23.30	23.42	23.22
	1	14		23.30	23.40	23.33
	8	0		22.36	22.45	22.34
	8	4		22.48	22.51	22.42
	8	7		22.37	22.38	22.43
	15	0		22.45	22.38	22.39
3	1	0	16-QAM	22.58	22.82	22.23
	1	8		23.00	22.77	22.26
	1	14		22.87	22.82	22.50
	8	0		21.46	21.49	21.41
	8	4		21.55	21.53	21.42
	8	7		21.48	21.50	21.45
	15	0		21.49	21.29	21.44
3	1	0	64QAM	21.26	21.54	21.61
	1	8		21.50	21.52	21.64
	1	14		21.24	21.44	21.29
	8	0		20.56	20.37	20.36
	8	4		20.59	20.45	20.36
	8	7		20.51	20.45	20.28
	15	0		20.46	20.41	20.40
1.4	1	0	QPSK	23.23	23.31	23.33
	1	3		23.45	23.38	23.28
	1	5		23.22	23.33	23.17
	3	0		23.42	23.45	23.34
	3	1		23.50	23.32	23.34
	3	3		23.60	23.53	23.21
	6	0		22.45	22.32	22.34
1.4	1	0	16-QAM	22.86	22.74	22.55
	1	3		22.95	23.00	22.60
	1	5		22.82	22.81	22.55
	3	0		22.48	22.34	22.32
	3	1		22.54	22.30	22.41



1.4	3	3	64QAM	22.44	22.30	22.35
1.4	6	0		21.66	21.60	21.36
1.4	1	0		21.67	21.20	21.50
1.4	1	3		21.88	21.34	21.73
1.4	1	5		21.69	21.12	21.53
1.4	3	0		21.61	21.57	21.51
1.4	3	1		21.51	21.60	21.54
1.4	3	3		21.71	21.11	21.43
1.4	6	0		20.27	20.44	20.36



LTE Band 4 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
20	1	0	QPSK	23.06	22.92	22.97
	1	49		23.27	23.38	23.50
	1	99		22.93	22.86	22.83
	50	0		22.23	22.28	22.46
	50	24		22.25	22.20	22.28
	50	50		22.29	22.22	22.27
	100	0		22.32	22.21	22.38
20	1	0	16-QAM	22.36	22.12	22.56
	1	49		22.77	22.21	22.93
	1	99		22.07	22.22	22.48
	50	0		21.31	21.33	21.40
	50	24		21.32	21.30	21.27
	50	50		21.33	21.27	21.20
	100	0		21.34	21.21	21.33
20	1	0	64QAM	21.17	21.36	20.81
	1	49		21.46	21.69	21.70
	1	99		20.95	21.19	21.27
	50	0		20.28	20.21	20.44
	50	24		20.23	20.31	20.33
	50	50		20.27	20.13	20.28
	100	0		20.33	20.15	20.42
15	1	0	QPSK	23.14	23.12	23.15
	1	37		23.30	23.48	23.33
	1	74		23.11	23.07	23.11
	36	0		22.34	22.23	22.40
	36	20		22.24	22.22	22.24
	36	39		22.26	22.33	22.33
	75	0		22.26	22.14	22.35
15	1	0	16-QAM	22.47	22.69	22.22
	1	37		22.78	22.59	22.46
	1	74		22.36	22.59	22.06
	36	0		21.34	21.30	21.34
	36	20		21.21	21.30	21.34



15	36	39	64QAM	21.32	21.16	21.40
15	75	0		21.30	21.20	21.40
15	1	0		21.34	21.40	21.55
15	1	37		21.67	21.36	21.60
15	1	74		21.13	21.27	21.19
15	36	0		20.29	20.33	20.29
15	36	20		20.28	20.26	20.27
15	36	39		20.24	20.26	20.23
15	75	0		20.30	20.28	20.30



LTE Band 4 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
10	1	0	QPSK	23.33	23.37	23.23
	1	25		23.35	23.38	23.41
	1	49		23.22	23.15	23.27
	25	0		22.34	22.16	22.38
	25	12		22.30	22.26	22.37
	25	25		22.29	22.13	22.28
	50	0		22.34	22.19	22.33
10	1	0	16-QAM	22.77	22.50	22.31
	1	25		22.91	22.33	22.30
	1	49		22.70	22.18	22.24
	25	0		21.38	21.20	21.38
	25	12		21.33	21.27	21.42
	25	25		21.33	21.35	21.34
	50	0		21.35	21.23	21.30
10	1	0	64QAM	21.54	21.62	21.38
	1	25		21.50	21.69	21.78
	1	49		21.45	21.47	21.59
	25	0		20.32	20.23	20.32
	25	12		20.38	20.24	20.39
	25	25		20.24	20.17	20.37
	50	0		20.34	20.21	20.35
5	1	0	QPSK	22.99	23.13	23.15
	1	12		23.43	23.45	23.35
	1	24		23.17	23.15	23.16
	12	0		22.24	22.17	22.27
	12	7		22.27	22.21	22.30
	12	13		22.33	22.25	22.32
	25	0		22.22	22.20	22.26
5	1	0	16-QAM	22.35	22.32	22.73
	1	12		22.71	22.39	22.85
	1	24		22.65	22.19	22.71
	12	0		21.27	21.15	21.31
	12	7		21.32	21.24	21.42



5	12	13	64QAM	21.43	21.22	21.30
5	25	0		21.36	21.20	21.31
5	1	0		21.46	21.28	21.05
5	1	12		21.38	21.28	21.77
5	1	24		21.28	21.23	21.37
5	12	0		20.36	20.09	20.30
5	12	7		20.47	20.20	20.34
5	12	13		20.43	20.15	20.35
5	25	0		20.28	20.18	20.43



LTE Band 4 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
3	1	0	QPSK	23.28	23.15	23.24
	1	8		23.37	23.19	23.49
	1	14		23.19	23.06	23.21
	8	0		22.24	22.18	22.38
	8	4		22.22	22.19	22.36
	8	7		22.25	22.21	22.27
	15	0		22.23	22.17	22.27
3	1	0	16-QAM	22.35	22.83	22.59
	1	8		22.55	22.92	22.90
	1	14		22.80	22.75	22.60
	8	0		21.38	21.31	21.35
	8	4		21.44	21.30	21.42
	8	7		21.29	21.28	21.35
	15	0		21.26	21.27	21.30
3	1	0	64QAM	21.51	21.28	21.67
	1	8		21.52	21.56	21.67
	1	14		21.55	21.21	21.63
	8	0		20.33	20.33	20.35
	8	4		20.37	20.31	20.41
	8	7		20.27	20.21	20.35
	15	0		20.31	20.36	20.25
1.4	1	0	QPSK	23.06	23.17	23.21
	1	3		23.32	23.24	23.42
	1	5		23.09	23.24	23.17
	3	0		23.23	23.19	23.25
	3	1		23.17	23.20	23.34
	3	3		23.21	23.39	23.31
	6	0		22.26	22.31	22.35
1.4	1	0	16-QAM	22.29	22.67	22.54
	1	3		22.32	22.73	22.51
	1	5		22.19	22.42	22.37
	3	0		22.27	22.26	22.27
	3	1		22.43	22.39	22.39



1.4	3	3	64QAM	22.29	22.33	22.38
1.4	6	0		21.39	21.39	21.33
1.4	1	0		21.05	21.28	21.67
1.4	1	3		21.19	21.47	21.71
1.4	1	5		21.48	21.28	21.45
1.4	3	0		21.38	21.12	21.53
1.4	3	1		21.38	21.14	21.52
1.4	3	3		21.48	21.16	21.50
1.4	6	0		20.31	20.29	20.31



LTE Band 5 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
10	1	0	QPSK	23.32	23.16	23.26
	1	25		23.28	23.17	23.50
	1	49		23.24	23.19	23.26
	25	0		22.30	22.32	22.33
	25	12		22.37	22.36	22.38
	25	25		22.35	22.34	22.25
	50	0		22.32	22.41	22.32
10	1	0	16-QAM	22.68	22.34	22.47
	1	25		22.83	22.44	22.46
	1	49		22.71	22.33	22.44
	25	0		21.42	21.31	21.30
	25	12		21.40	21.34	21.26
	25	25		21.31	21.41	21.19
	50	0		21.32	21.30	21.37
10	1	0	64QAM	21.41	21.51	21.02
	1	25		21.29	21.49	21.10
	1	49		21.41	21.23	21.08
	25	0		20.36	20.30	20.37
	25	12		20.33	20.38	20.44
	25	25		20.32	20.42	20.32
	50	0		20.36	20.38	20.41
5	1	0	QPSK	23.24	23.24	23.12
	1	12		23.48	23.44	23.41
	1	24		23.20	23.19	23.09
	12	0		22.25	22.28	22.30
	12	7		22.39	22.33	22.32
	12	13		22.30	22.30	22.25
	25	0		22.31	22.24	22.28
5	1	0	16-QAM	22.56	22.61	22.37
	1	12		22.73	22.99	22.73
	1	24		22.36	22.07	22.37
	12	0		21.15	21.32	21.21
	12	7		21.17	21.35	21.22



5	12	13	64QAM	21.23	21.37	21.27
5	25	0		21.12	21.26	21.24
5	1	0		21.54	21.46	21.15
5	1	12		21.86	21.43	21.57
5	1	24		21.51	21.39	21.23
5	12	0		20.31	20.24	20.28
5	12	7		20.32	20.30	20.31
5	12	13		20.29	20.33	20.24
5	25	0		20.20	20.22	20.20



LTE Band 5 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
3	1	0	QPSK	23.21	23.29	23.31
	1	8		23.39	23.36	23.23
	1	14		23.22	23.22	23.20
	8	0		22.22	22.21	22.22
	8	4		22.21	22.33	22.30
	8	7		22.30	22.32	22.31
	15	0		22.27	22.26	22.29
3	1	0	16-QAM	22.28	22.80	22.39
	1	8		22.37	22.96	22.64
	1	14		22.15	22.70	22.62
	8	0		21.30	21.22	21.30
	8	4		21.31	21.31	21.26
	8	7		21.34	21.29	21.27
	15	0		21.31	21.36	21.14
3	1	0	64QAM	21.25	20.99	21.52
	1	8		21.62	21.22	21.84
	1	14		21.19	21.04	21.31
	8	0		20.31	20.34	20.25
	8	4		20.42	20.37	20.38
	8	7		20.29	20.27	20.31
	15	0		20.28	20.22	20.33
1.4	1	0	QPSK	23.21	23.08	23.15
	1	3		23.34	23.22	23.21
	1	5		23.20	23.18	23.19
	3	0		23.28	23.22	23.20
	3	1		23.31	23.17	23.27
	3	3		23.27	23.17	23.21
	6	0		22.37	22.21	22.22
1.4	1	0	16-QAM	22.65	22.31	22.02
	1	3		22.58	22.21	22.32
	1	5		22.61	22.13	22.16
	3	0		22.28	22.21	22.22
	3	1		22.32	22.25	22.15



1.4	3	3	64QAM	22.33	22.30	22.02
1.4	6	0		21.43	21.15	21.21
1.4	1	0		21.44	21.49	21.21
1.4	1	3		21.35	21.58	21.09
1.4	1	5		21.34	21.11	21.17
1.4	3	0		21.42	21.44	21.34
1.4	3	1		21.53	21.33	21.39
1.4	3	3		21.49	21.38	21.49
1.4	6	0		20.23	20.14	20.21



LTE Band 7 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
20	1	0	QPSK	23.20	23.27	23.28
	1	49		23.59	23.55	23.75
	1	99		23.31	23.27	23.24
	50	0		22.45	22.65	22.49
	50	24		22.61	22.63	22.72
	50	50		22.45	22.71	22.65
	100	0		22.52	22.54	22.61
20	1	0	16-QAM	22.76	22.72	22.66
	1	49		22.95	22.91	22.75
	1	99		22.68	22.93	22.49
	50	0		21.38	21.70	21.55
	50	24		21.54	21.76	21.63
	50	50		21.64	21.73	21.54
	100	0		21.62	21.63	21.54
20	1	0	64QAM	21.37	21.57	21.43
	1	49		21.52	21.95	21.73
	1	99		21.28	21.30	21.39
	50	0		20.39	20.78	20.66
	50	24		20.60	20.74	20.62
	50	50		20.68	20.74	20.51
	100	0		20.59	20.79	20.54
15	1	0	QPSK	23.43	23.56	23.53
	1	37		23.48	23.64	23.67
	1	74		23.52	23.55	23.50
	36	0		22.61	22.72	22.58
	36	20		22.66	22.69	22.60
	36	39		22.70	22.76	22.60
	75	0		22.54	22.67	22.52
15	1	0	16-QAM	22.59	22.93	22.88
	1	37		22.66	22.95	22.81
	1	74		22.53	22.90	22.78
	36	0		21.57	21.70	21.57
	36	20		21.67	21.70	21.67



15	36	39	64QAM	21.65	21.75	21.63
15	75	0		21.52	21.77	21.61
15	1	0		21.66	21.53	21.77
15	1	37		21.93	21.95	21.78
15	1	74		21.36	21.97	21.76
15	36	0		20.68	20.71	20.59
15	36	20		20.70	20.71	20.54
15	36	39		20.64	20.77	20.62
15	75	0		20.62	20.70	20.60



LTE Band 7 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
10	1	0	QPSK	23.46	23.53	23.37
	1	25		23.61	23.70	23.69
	1	49		23.43	23.55	23.38
	25	0		22.52	22.66	22.60
	25	12		22.58	22.69	22.59
	25	25		22.62	22.65	22.62
	50	0		22.58	22.66	22.72
10	1	0	16-QAM	22.88	22.77	22.80
	1	25		22.95	22.84	22.96
	1	49		22.87	22.73	22.79
	25	0		21.50	21.71	21.50
	25	12		21.61	21.70	21.61
	25	25		21.73	21.68	21.57
	50	0		21.69	21.72	21.59
10	1	0	64QAM	21.86	21.55	21.68
	1	25		21.80	21.90	21.64
	1	49		21.63	21.70	21.70
	25	0		20.59	20.76	20.63
	25	12		20.74	20.75	20.64
	25	25		20.73	20.76	20.64
	50	0		20.65	20.71	20.72
5	1	0	QPSK	23.34	23.38	23.35
	1	12		23.53	23.65	23.70
	1	24		23.31	23.49	23.40
	12	0		22.48	22.64	22.63
	12	7		22.57	22.72	22.70
	12	13		22.69	22.63	22.59
	25	0		22.52	22.60	22.63
5	1	0	16-QAM	22.87	22.96	22.52
	1	12		23.00	22.94	22.96
	1	24		22.95	22.67	22.72
	12	0		21.57	21.64	21.63
	12	7		21.70	21.72	21.60



5	12	13	64QAM	21.72	21.67	21.56
5	25	0		21.62	21.63	21.48
5	1	0		21.37	21.54	21.58
5	1	12		21.77	21.80	21.76
5	1	24		21.52	21.59	21.54
5	12	0		20.59	20.76	20.68
5	12	7		20.74	20.75	20.59
5	12	13		20.74	20.72	20.63
5	25	0		20.72	20.75	20.66



LTE Band 38 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
20	1	0	QPSK	23.19	23.10	23.09
	1	49		23.62	23.49	23.50
	1	99		23.09	23.04	23.05
	50	0		22.39	22.36	22.37
	50	24		22.37	22.33	22.38
	50	50		22.36	22.26	22.32
	100	0		22.45	22.32	22.37
20	1	0	16-QAM	22.25	22.16	22.12
	1	49		22.56	22.48	22.59
	1	99		22.15	22.08	22.13
	50	0		21.39	21.38	21.41
	50	24		21.44	21.37	21.40
	50	50		21.39	21.32	21.39
	100	0		21.45	21.33	21.39
20	1	0	64QAM	20.96	20.87	20.83
	1	49		21.36	21.28	21.31
	1	99		20.85	20.82	20.85
	50	0		20.42	20.39	20.45
	50	24		20.45	20.39	20.42
	50	50		20.43	20.37	20.38
	100	0		20.46	20.38	20.40
15	1	0	QPSK	23.44	23.36	23.32
	1	37		23.59	23.46	23.49
	1	74		23.36	23.25	23.25
	36	0		22.55	22.44	22.42
	36	20		22.56	22.43	22.43
	36	39		22.51	22.35	22.36
	75	0		22.42	22.36	22.38
15	1	0	16-QAM	22.43	22.32	22.33
	1	37		22.59	22.50	22.54
	1	74		22.34	22.31	22.35
	36	0		21.44	21.35	21.37
	36	20		21.43	21.35	21.36



15	36	39	64QAM	21.41	21.29	21.31
15	75	0		21.45	21.35	21.41
15	1	0		21.17	21.04	21.07
15	1	37		21.34	21.23	21.25
15	1	74		21.09	21.01	21.08
15	36	0		20.47	20.38	20.39
15	36	20		20.48	20.40	20.38
15	36	39		20.43	20.34	20.35
15	75	0		20.46	20.37	20.39



LTE Band 38 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
10	1	0	QPSK	23.46	23.39	23.39
	1	25		23.61	23.54	23.50
	1	49		23.44	23.34	23.34
	25	0		22.52	22.43	22.44
	25	12		22.55	22.46	22.45
	25	25		22.52	22.42	22.46
	50	0		22.45	22.39	22.44
10	1	0	16-QAM	22.49	22.39	22.45
	1	25		22.64	22.54	22.58
	1	49		22.45	22.41	22.48
	25	0		21.54	21.46	21.48
	25	12		21.55	21.48	21.45
	25	25		21.56	21.43	21.49
	50	0		21.51	21.41	21.47
10	1	0	64QAM	21.23	21.11	21.16
	1	25		21.37	21.29	21.31
	1	49		21.19	21.10	21.16
	25	0		20.56	20.49	20.51
	25	12		20.59	20.50	20.51
	25	25		20.56	20.47	20.53
	50	0		20.52	20.42	20.48
5	1	0	QPSK	23.31	23.27	23.25
	1	12		23.53	23.45	23.43
	1	24		23.33	23.27	23.26
	12	0		22.54	22.39	22.37
	12	7		22.58	22.45	22.44
	12	13		22.51	22.37	22.42
	25	0		22.45	22.38	22.41
5	1	0	16-QAM	22.41	22.31	22.37
	1	12		22.55	22.47	22.56
	1	24		22.36	22.29	22.38
	12	0		21.47	21.39	21.34
	12	7		21.49	21.40	21.41



5	12	13	64QAM	21.53	21.37	21.43
5	25	0		21.48	21.38	21.46
5	1	0		21.15	21.07	21.07
5	1	12		21.31	21.22	21.25
5	1	24		21.11	21.02	21.09
5	12	0		20.48	20.37	20.38
5	12	7		20.53	20.41	20.46
5	12	13		20.53	20.40	20.47
5	25	0		20.51	20.40	20.48

**ERP/EIRP**

LTE Band 2 (GT - LC = -0.19 dB) QPSK									
Bandwidth	1.4M			3M			5M		
Channel	18607	18900	19193	18615	18900	19185	18625	18900	19175
	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)
Frequency (MHz)	1850.7	1880	1909.3	1851.5	1880	1908.5	1852.5	1880	1907.5
Conducted Power (dBm)	23.60	23.53	23.21	23.30	23.42	23.22	23.54	23.48	23.52
Conducted Power (Watts)	0.2291	0.2254	0.2094	0.2138	0.2198	0.2099	0.2259	0.2228	0.2249
EIRP(dBm)	23.41	23.34	23.02	23.11	23.23	23.03	23.35	23.29	23.33
EIRP(Watts)	0.2193	0.2158	0.2004	0.2046	0.2104	0.2009	0.2163	0.2133	0.2153

LTE Band 2 (GT - LC = -0.19 dB) QPSK									
Bandwidth	10M			15M			20M		
Channel	18650	18900	19150	18675	18900	19125	18650	18900	19100
	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)
Frequency (MHz)	1855	1880	1905	1857.5	1880	1902.5	1860	1880	1900
Conducted Power (dBm)	23.49	23.42	23.36	23.64	23.40	23.43	23.65	23.42	23.45
Conducted Power (Watts)	0.2234	0.2198	0.2168	0.2312	0.2188	0.2203	0.2317	0.2198	0.2213
EIRP(dBm)	23.30	23.23	23.17	23.45	23.21	23.24	23.46	23.23	23.26
EIRP(Watts)	0.2138	0.2104	0.2075	0.2213	0.2094	0.2109	0.2218	0.2104	0.2118



LTE Band 2 (GT - LC = -0.19 dBi) 16QAM									
Bandwidth	1.4M			3M			5M		
Channel	18607	18900	19193	18615	18900	19185	18625	18900	19175
	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)
Frequency (MHz)	1850.7	1880	1909.3	1851.5	1880	1908.5	1852.5	1880	1907.5
	22.95	23.00	22.60	23.00	22.77	22.26	22.72	22.88	22.76
Conducted Power (dBm)	0.1972	0.1995	0.1820	0.1995	0.1892	0.1683	0.1871	0.1941	0.1888
EIRP(dBm)	22.76	22.81	22.41	22.81	22.58	22.07	22.53	22.69	22.57
EIRP(Watts)	0.1888	0.1910	0.1742	0.1910	0.1811	0.1611	0.1791	0.1858	0.1807

LTE Band 2 (GT - LC = -0.19 dBi) 16QAM									
Bandwidth	10M			15M			20M		
Channel	18650	18900	19150	18675	18900	19125	18650	18900	19100
	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)
Frequency (MHz)	1855	1880	1905	1857.5	1880	1902.5	1860	1880	1900
	22.36	22.87	22.51	22.95	22.28	22.83	22.35	22.56	22.75
Conducted Power (dBm)	0.1722	0.1936	0.1782	0.1972	0.1690	0.1919	0.1718	0.1803	0.1884
EIRP(dBm)	22.17	22.68	22.32	22.76	22.09	22.64	22.16	22.37	22.56
EIRP(Watts)	0.1648	0.1854	0.1706	0.1888	0.1618	0.1837	0.1644	0.1726	0.1803



LTE Band 2 ($G_T - L_C = -0.19 \text{ dBi}$) 64QAM									
Bandwidth	1.4M			3M			5M		
Channel	18607	18900	19193	18615	18900	19185	18625	18900	19175
	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)
Frequency (MHz)	1850.7	1880	1909.3	1851.5	1880	1908.5	1852.5	1880	1907.5
Conducted Power (dBm)	21.88	21.34	21.73	21.50	21.52	21.64	21.70	21.70	21.73
Conducted Power (Watts)	0.1542	0.1361	0.1489	0.1413	0.1419	0.1459	0.1479	0.1479	0.1489
EIRP(dBm)	21.69	21.15	21.54	21.31	21.33	21.45	21.51	21.51	21.54
EIRP(Watts)	0.1476	0.1303	0.1426	0.1352	0.1358	0.1396	0.1416	0.1416	0.1426

LTE Band 2 ($G_T - L_C = -0.19 \text{ dBi}$) 64QAM									
Bandwidth	10M			15M			20M		
Channel	18650	18900	19150	18675	18900	19125	18650	18900	19100
	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)
Frequency (MHz)	1855	1880	1905	1857.5	1880	1902.5	1860	1880	1900
Conducted Power (dBm)	21.82	21.69	21.60	21.95	21.68	21.50	21.51	21.57	21.36
Conducted Power (Watts)	0.1521	0.1476	0.1445	0.1567	0.1472	0.1413	0.1416	0.1435	0.1368
EIRP(dBm)	21.63	21.50	21.41	21.76	21.49	21.31	21.32	21.38	21.17
EIRP(Watts)	0.1455	0.1413	0.1384	0.1500	0.1409	0.1352	0.1355	0.1374	0.1309



LTE Band 4 (GT - LC = -0.55 dBi) QPSK									
Bandwidth	1.4M			3M			5M		
Channel	19957 (Low)	20175 (Mid)	20393 (High)	19965 (Low)	20175 (Mid)	20385 (High)	19975 (Low)	20175 (Mid)	20375 (High)
	1710.7	1732.5	1754.3	1711.5	1732.5	1753.5	1712.5	1732.5	1752.5
Conducted Power (dBm)	23.32	23.24	23.42	23.37	23.19	23.49	23.43	23.45	23.35
Conducted Power (Watts)	0.2148	0.2109	0.2198	0.2173	0.2084	0.2234	0.2203	0.2213	0.2163
EIRP(dBm)	22.77	22.69	22.87	22.82	22.64	22.94	22.88	22.90	22.80
EIRP(Watts)	0.1892	0.1858	0.1936	0.1914	0.1837	0.1968	0.1941	0.1950	0.1905

LTE Band 4 (GT - LC = -0.55 dBi) QPSK									
Bandwidth	10M			15M			20M		
Channel	20000 (Low)	20175 (Mid)	20350 (High)	20025 (Low)	20175 (Mid)	20325 (High)	20050 (Low)	20175 (Mid)	20300 (High)
	1715	1732.5	1750	1717.5	1732.5	1747.5	1720	1732.5	1745
Conducted Power (dBm)	23.35	23.38	23.41	23.30	23.48	23.33	23.27	23.38	23.50
Conducted Power (Watts)	0.2163	0.2178	0.2193	0.2138	0.2228	0.2153	0.2123	0.2178	0.2239
EIRP(dBm)	22.80	22.83	22.86	22.75	22.93	22.78	22.72	22.83	22.95
EIRP(Watts)	0.1905	0.1919	0.1932	0.1884	0.1963	0.1897	0.1871	0.1919	0.1972



LTE Band 4 (GT - LC = -0.55 dB) 16QAM									
Bandwidth	1.4M			3M			5M		
Channel	19957	20175	20393	19965	20175	20385	19975	20175	20375
	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)
Frequency (MHz)	1710.7	1732.5	1754.3	1711.5	1732.5	1753.5	1712.5	1732.5	1752.5
Conducted Power (dBm)	22.32	22.73	22.51	22.55	22.92	22.90	22.71	22.39	22.85
Conducted Power (Watts)	0.1706	0.1875	0.1782	0.1799	0.1959	0.1950	0.1866	0.1734	0.1928
EIRP(dBm)	21.77	22.18	21.96	22.00	22.37	22.35	22.16	21.84	22.30
EIRP(Watts)	0.1503	0.1652	0.1570	0.1585	0.1726	0.1718	0.1644	0.1528	0.1698

LTE Band 4 (GT - LC = -0.55 dB) 16QAM									
Bandwidth	10M			15M			20M		
Channel	20000	20175	20350	20025	20175	20325	20050	20175	20300
	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)
Frequency (MHz)	1715	1732.5	1750	1717.5	1732.5	1747.5	1720	1732.5	1745
Conducted Power (dBm)	22.91	22.33	22.30	22.78	22.59	22.46	22.77	22.21	21.93
Conducted Power (Watts)	0.1954	0.1710	0.1698	0.1897	0.1816	0.1762	0.1892	0.1663	0.1560
EIRP(dBm)	22.36	21.78	21.75	22.23	22.04	21.91	22.22	21.66	21.38
EIRP(Watts)	0.1722	0.1507	0.1496	0.1671	0.1600	0.1552	0.1667	0.1466	0.1374



LTE Band 4 ($G_T - L_C = -0.55 \text{ dBi}$) 64QAM									
Bandwidth	1.4M			3M			5M		
Channel	19957 (Low)	20175 (Mid)	20393 (High)	19965 (Low)	20175 (Mid)	20385 (High)	19975 (Low)	20175 (Mid)	20375 (High)
	1710.7	1732.5	1754.3	1711.5	1732.5	1753.5	1712.5	1732.5	1752.5
Conducted Power (dBm)	21.19	21.47	21.71	21.52	21.56	21.67	21.38	21.28	21.77
Conducted Power (Watts)	0.1315	0.1403	0.1483	0.1419	0.1432	0.1469	0.1374	0.1343	0.1503
EIRP(dBm)	20.64	20.92	21.16	20.97	21.01	21.12	20.83	20.73	21.22
EIRP(Watts)	0.1159	0.1236	0.1306	0.1250	0.1262	0.1294	0.1211	0.1183	0.1324

LTE Band 4 ($G_T - L_C = -0.55 \text{ dBi}$) 64QAM									
Bandwidth	10M			15M			20M		
Channel	20000 (Low)	20175 (Mid)	20350 (High)	20025 (Low)	20175 (Mid)	20325 (High)	20050 (Low)	20175 (Mid)	20300 (High)
	1715	1732.5	1750	1717.5	1732.5	1747.5	1720	1732.5	1745
Conducted Power (dBm)	21.50	21.69	21.78	21.67	21.36	21.60	21.46	21.69	21.70
Conducted Power (Watts)	0.1413	0.1476	0.1507	0.1469	0.1368	0.1445	0.1400	0.1476	0.1479
EIRP(dBm)	20.95	21.14	21.23	21.12	20.81	21.05	20.91	21.14	21.15
EIRP(Watts)	0.1245	0.1300	0.1327	0.1294	0.1205	0.1274	0.1233	0.1300	0.1303



LTE Band 5 (GT - LC = -1.67 dB) QPSK									
Bandwidth	1.4M			3M			5M		
Channel	20407	20525	20643	20415	20525	20635	20425	20525	20625
	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)
Frequency (MHz)	824.7	836.5	848.3	825.5	836.5	847.5	826.5	836.5	846.5
Conducted Power (dBm)	23.34	23.22	23.21	23.39	23.36	23.23	23.48	23.44	23.41
Conducted Power (Watts)	0.2158	0.2099	0.2094	0.2183	0.2168	0.2104	0.2228	0.2208	0.2193
ERP(dBm)	19.52	19.40	19.39	19.57	19.54	19.41	19.66	19.62	19.59
ERP(Watts)	0.0895	0.0871	0.0869	0.0906	0.0899	0.0873	0.0925	0.0916	0.0910

LTE Band 5 (GT - LC = -1.67 dB) QPSK			
Bandwidth	10M		
Channel	20450	20525	20600
	(Low)	(Mid)	(High)
Frequency (MHz)	829	836.5	844
Conducted Power (dBm)	23.28	23.17	23.50
Conducted Power (Watts)	0.2128	0.2075	0.2239
ERP(dBm)	19.46	19.35	19.68
ERP(Watts)	0.0883	0.0861	0.0929



LTE Band 5 (GT - LC = -1.67 dB) 16QAM									
Bandwidth	1.4M			3M			5M		
Channel	20407	20525	20643	20415	20525	20635	20425	20525	20625
	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)
Frequency (MHz)	824.7	836.5	848.3	825.5	836.5	847.5	826.5	836.5	846.5
Conducted Power (dBm)	22.65	22.31	22.02	22.37	22.96	22.64	22.73	22.99	22.73
Conducted Power (Watts)	0.1841	0.1702	0.1592	0.1726	0.1977	0.1837	0.1875	0.1991	0.1875
ERP(dBm)	18.83	18.49	18.20	18.55	19.14	18.82	18.91	19.17	18.91
ERP(Watts)	0.0764	0.0706	0.0661	0.0716	0.0820	0.0762	0.0778	0.0826	0.0778

LTE Band 5 (GT - LC = -1.67 dB) 16QAM			
Bandwidth	10M		
Channel	20450	20525	20600
	(Low)	(Mid)	(High)
Frequency (MHz)	829	836.5	844
Conducted Power (dBm)	22.83	22.44	22.46
Conducted Power (Watts)	0.1919	0.1754	0.1762
ERP(dBm)	19.01	18.62	18.64
ERP(Watts)	0.0796	0.0728	0.0731



LTE Band 5 ($G_T - L_C = -1.67 \text{ dBi}$) 64QAM									
Bandwidth	1.4M			3M			5M		
Channel	20407	20525	20643	20415	20525	20635	20425	20525	20625
	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)
Frequency (MHz)	824.7	836.5	848.3	825.5	836.5	847.5	826.5	836.5	846.5
Conducted Power (dBm)	21.35	21.58	21.09	21.62	21.22	21.84	21.86	21.43	21.57
Conducted Power (Watts)	0.1365	0.1439	0.1285	0.1452	0.1324	0.1528	0.1535	0.1390	0.1435
ERP(dBm)	17.53	17.76	17.27	17.80	17.40	18.02	18.04	17.61	17.75
ERP(Watts)	0.0566	0.0597	0.0533	0.0603	0.0550	0.0634	0.0637	0.0577	0.0596

LTE Band 5 ($G_T - L_C = -1.67 \text{ dBi}$) 64QAM			
Bandwidth	10M		
Channel	20450	20525	20600
	(Low)	(Mid)	(High)
Frequency (MHz)	829	836.5	844
Conducted Power (dBm)	21.41	21.51	21.02
Conducted Power (Watts)	0.1384	0.1416	0.1265
ERP(dBm)	17.59	17.69	17.20
ERP(Watts)	0.0574	0.0587	0.0525



LTE Band 7 (GT - LC = 1.14 dBi) QPSK			
Bandwidth	5M		
Channel	20775 (Low)	21100 (Mid)	21425 (High)
	2502.5	2535	2567.5
Conducted Power (dBm)	23.53	23.65	23.70
Conducted Power (Watts)	0.2254	0.2317	0.2344
EIRP(dBm)	24.67	24.79	24.84
EIRP(Watts)	0.2931	0.3013	0.3048

LTE Band 7 (GT - LC = 1.14 dBi) QPSK									
Bandwidth	10M			15M			20M		
Channel	20800 (Low)	21100 (Mid)	21400 (High)	20825 (Low)	21100 (Mid)	21375 (High)	20850 (Low)	21100 (Mid)	21350 (High)
	2505	2535	2565	2507.5	2535	2562.5	2510	2535	2560
Conducted Power (dBm)	23.61	23.70	23.69	23.48	23.64	23.67	23.59	23.55	23.75
Conducted Power (Watts)	0.2296	0.2344	0.2339	0.2228	0.2312	0.2328	0.2286	0.2265	0.2371
EIRP(dBm)	24.75	24.84	24.83	24.62	24.78	24.81	24.73	24.69	24.89
EIRP(Watts)	0.2985	0.3048	0.3041	0.2897	0.3006	0.3027	0.2972	0.2944	0.3083



LTE Band 7 (GT - LC = 1.14 dBi) 16QAM			
Bandwidth	5M		
Channel	20775 (Low)	21100 (Mid)	21425 (High)
	2502.5	2535	2567.5
Conducted Power (dBm)	23.00	22.94	22.96
Conducted Power (Watts)	0.1995	0.1968	0.1977
EIRP(dBm)	24.14	24.08	24.10
EIRP(Watts)	0.2594	0.2559	0.2570

LTE Band 7 (GT - LC = 1.14 dBi) 16QAM									
Bandwidth	10M			15M			20M		
Channel	20800 (Low)	21100 (Mid)	21400 (High)	20825 (Low)	21100 (Mid)	21375 (High)	20850 (Low)	21100 (Mid)	21350 (High)
	2505	2535	2565	2507.5	2535	2562.5	2510	2535	2560
Conducted Power (dBm)	22.95	22.84	22.96	22.66	22.95	22.81	22.95	22.91	22.75
Conducted Power (Watts)	0.1972	0.1923	0.1977	0.1845	0.1972	0.1910	0.1972	0.1954	0.1884
EIRP(dBm)	24.09	23.98	24.10	23.80	24.09	23.95	24.09	24.05	23.89
EIRP(Watts)	0.2564	0.2500	0.2570	0.2399	0.2564	0.2483	0.2564	0.2541	0.2449



LTE Band 7 ($G_T - L_C = 1.14 \text{ dBi}$) 64QAM			
Bandwidth	5M		
Channel	20775 (Low)	21100 (Mid)	21425 (High)
	2502.5	2535	2567.5
Conducted Power (dBm)	21.77	21.80	21.76
Conducted Power (Watts)	0.1503	0.1514	0.1500
EIRP(dBm)	22.91	22.94	22.90
EIRP(Watts)	0.1954	0.1968	0.1950

LTE Band 7 ($G_T - L_C = 1.14 \text{ dBi}$) 64QAM									
Bandwidth	10M			15M			20M		
Channel	20800 (Low)	21100 (Mid)	21400 (High)	20825 (Low)	21100 (Mid)	21375 (High)	20850 (Low)	21100 (Mid)	21350 (High)
	2505	2535	2565	2507.5	2535	2562.5	2510	2535	2560
Conducted Power (dBm)	21.80	21.90	21.64	21.93	21.95	21.78	21.52	21.95	21.73
Conducted Power (Watts)	0.1514	0.1549	0.1459	0.1560	0.1567	0.1507	0.1419	0.1567	0.1489
EIRP(dBm)	22.94	23.04	22.78	23.07	23.09	22.92	22.66	23.09	22.87
EIRP(Watts)	0.1968	0.2014	0.1897	0.2028	0.2037	0.1959	0.1845	0.2037	0.1936



LTE Band 38 (GT - LC = 0.45 dBi) QPSK					
Bandwidth	5M				
Channel	37775 (Low)		38000 (Mid)		38225 (High)
	2572.5		2595		2617.5
Frequency (MHz)					
Conducted Power (dBm)	23.53		23.45		23.43
Conducted Power (Watts)	0.2254		0.2213		0.2203
EIRP(dBm)	23.98		23.90		23.88
EIRP(Watts)	0.2500		0.2455		0.2443

LTE Band 38 (GT - LC = 0.45 dBi) QPSK									
Bandwidth	10M			15M			20M		
Channel	37800 (Low)	38000 (Mid)	38200 (High)	37825 (Low)	38000 (Mid)	38175 (High)	37850 (Low)	38000 (Mid)	38150 (Mid)
	2575	2595	2615	2577.5	2595	2612.5	2580	2595	2610
Frequency (MHz)	23.61	23.54	23.50	23.59	23.46	23.49	23.62	23.49	23.50
Conducted Power (dBm)	23.61	23.54	23.50	23.59	23.46	23.49	23.62	23.49	23.50
Conducted Power (Watts)	0.2296	0.2259	0.2239	0.2286	0.2218	0.2234	0.2301	0.2234	0.2239
EIRP(dBm)	24.06	23.99	23.95	24.04	23.91	23.94	24.07	23.94	23.95
EIRP(Watts)	0.2547	0.2506	0.2483	0.2535	0.2460	0.2477	0.2553	0.2477	0.2483



LTE Band 38 (GT - LC = 0.45 dBi) 16QAM					
Bandwidth	5M				
Channel	37775 (Low)		38000 (Mid)		38225 (High)
	2572.5		2595		2617.5
Frequency (MHz)					
Conducted Power (dBm)	22.55		22.47		22.56
Conducted Power (Watts)	0.1799		0.1766		0.1803
EIRP(dBm)	23.00		22.92		23.01
EIRP(Watts)	0.1995		0.1959		0.2000

LTE Band 38 (GT - LC = 0.45 dBi) 16QAM									
Bandwidth	10M			15M			20M		
Channel	37800 (Low)	38000 (Mid)	38200 (High)	37825 (Low)	38000 (Mid)	38175 (High)	37850 (Low)	38000 (Mid)	38150 (Mid)
	2575	2595	2615	2577.5	2595	2612.5	2580	2595	2610
Frequency (MHz)	22.64	22.54	22.58	22.59	22.50	22.54	22.56	22.48	22.59
Conducted Power (dBm)	23.09	22.99	23.03	23.04	22.95	22.99	23.01	22.93	23.04
Conducted Power (Watts)	0.1837	0.1795	0.1811	0.1816	0.1778	0.1795	0.1803	0.1770	0.1816
EIRP(dBm)	0.2037	0.1991	0.2009	0.2014	0.1972	0.1991	0.2000	0.1963	0.2014
EIRP(Watts)									



LTE Band 38 ($G_T - L_C = 0.45 \text{ dBi}$) 64QAM			
Bandwidth	5M		
Channel	37775 (Low)	38000 (Mid)	38225 (High)
	2572.5	2595	2617.5
Conducted Power (dBm)	21.31	21.22	21.25
Conducted Power (Watts)	0.1352	0.1324	0.1334
EIRP(dBm)	21.76	21.67	21.70
EIRP(Watts)	0.1500	0.1469	0.1479

LTE Band 38 ($G_T - L_C = 0.45 \text{ dBi}$) 64QAM									
Bandwidth	10M			15M			20M		
Channel	37800 (Low)	38000 (Mid)	38200 (High)	37825 (Low)	38000 (Mid)	38175 (High)	37850 (Low)	38000 (Mid)	38150 (Mid)
	2575	2595	2615	2577.5	2595	2612.5	2580	2595	2610
Conducted Power (dBm)	21.37	21.29	21.31	21.34	21.23	21.25	21.36	21.28	21.31
Conducted Power (Watts)	0.1371	0.1346	0.1352	0.1361	0.1327	0.1334	0.1368	0.1343	0.1352
EIRP(dBm)	21.82	21.74	21.76	21.79	21.68	21.70	21.81	21.73	21.76
EIRP(Watts)	0.1521	0.1493	0.1500	0.1510	0.1472	0.1479	0.1517	0.1489	0.1500



Peak-to-Average Ratio

Mode	LTE Band 2 / 20MHz							
Mod.	QPSK		16QAM		Limit: 13dB			
RB Size	1RB	Full RB	1RB	Full RB	Result			
Lowest CH	5.59	5.71	6.75	6.46	PASS			
Middle CH	5.39	5.65	6.29	6.52				
Highest CH	5.54	5.68	6.67	6.55				
Mod.	64QAM		Limit: 13dB					
RB Size	1RB	Full RB	Result					
Lowest CH	6.43	6.72	PASS					
Middle CH	6.67	6.64						
Highest CH	6.81	6.7						


Mode	LTE Band 4 / 20MHz							
Mod.	QPSK		16QAM		Limit: 13dB			
RB Size	1RB	Full RB	1RB	Full RB	Result			
Lowest CH	5.48	5.68	6.55	6.67	PASS			
Middle CH	5.86	5.71	6.72	6.55				
Highest CH	5.86	5.54	6.81	6.52				
Mod.	64QAM		Limit: 13dB					
RB Size	1RB	Full RB	Result					
Lowest CH	6.90	6.64	PASS					
Middle CH	6.20	6.61						
Highest CH	5.83	6.55						


Mode	LTE Band 5 / 10MHz							
Mod.	QPSK		16QAM		Limit: 13dB			
RB Size	1RB	Full RB	1RB	Full RB	Result			
Lowest CH	4.87	5.16	5.83	6	PASS			
Middle CH	4.61	5.25	5.77	6.14				
Highest CH	5.16	5.13	6.38	5.97				
Mod.	64QAM		Limit: 13dB					
RB Size	1RB	Full RB	Result					
Lowest CH	6.23	6.17	PASS					
Middle CH	6.17	6.35						
Highest CH	6.12	6.12						





Mode	LTE Band 7 / 20MHz					
Mod.	QPSK		16QAM		Limit: 13dB	
RB Size	1RB	Full RB	1RB	Full RB	Result	
Lowest CH	4.75	5.13	5.68	6.12	PASS	
Middle CH	4.17	5.19	5.04	6.14		
Highest CH	5.04	5.01	5.94	6		
Mod.	64QAM		Limit: 13dB			
RB Size	1RB	Full RB	Result		PASS	
Lowest CH	5.39	6.03	PASS			
Middle CH	4.75	6.12				
Highest CH	6.03	6				


Mode	LTE Band 38 / 20MHz					
Mod.	QPSK		16QAM		Limit: 13dB	
RB Size	1RB	Full RB	1RB	Full RB	Result	
Lowest CH	4.49	6.35	5.1	6.52	PASS	
Middle CH	4.17	6.06	5.01	6.38		
Highest CH	4.64	6.12	5.77	6.23		
Mod.	64QAM		Limit: 13dB			
RB Size	1RB	Full RB	Result		PASS	
Lowest CH	5.36	5.77	PASS			
Middle CH	5.45	6.03				
Highest CH	5.91	6.23				

















LTE Band 5 / 10MHz / QPSK


Lowest Channel / 1RB



Lowest Channel / Full RB



Middle Channel / 1RB




Middle Channel / Full RB





Highest Channel / 1RB



Highest Channel / Full RB









LTE Band 7 / 20MHz / QPSK


Lowest Channel / 1RB




Lowest Channel / Full RB




Middle Channel / 1RB



Middle Channel / Full RB





Highest Channel / 1RB





Highest Channel / Full RB














**26dB Bandwidth**

Mode	LTE Band 2 : 26dB BW(MHz)											
BW	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Lowest CH	1.27	1.278	2.979	2.961	5.065	5.115	9.99	9.79	14.655	14.356	20.22	20.3
Middle CH	1.256	1.242	2.949	2.961	5.065	4.965	9.87	9.95	14.416	14.565	20.5	20.38
Highest CH	1.256	1.29	2.973	2.937	4.895	4.925	9.97	9.73	14.296	14.835	20.38	20.22
Mode	LTE Band 2 : 26dB BW(MHz)											
BW	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	64QAM		64QAM		64QAM		64QAM		64QAM		64QAM	
Lowest CH	1.284		2.913		4.955		9.81		14.715		20.06	
Middle CH	1.248		2.931		4.935		10.01		14.625		20.18	
Highest CH	1.292		2.979		5.115		9.89		14.565		20.18	

Mode	LTE Band 4 : 26dB BW(MHz)											
BW	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Lowest CH	1.292	1.29	2.985	2.961	5.005	5.065	9.71	9.99	14.565	14.775	20.1	20.22
Middle CH	1.292	1.312	2.955	2.943	5.035	5.205	10.13	9.91	14.805	14.805	20.1	20.979
Highest CH	1.273	1.262	2.937	2.967	5.015	5.105	9.91	9.93	14.416	14.416	20.26	20.14
Mode	LTE Band 4 : 26dB BW(MHz)											
BW	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	64QAM		64QAM		64QAM		64QAM		64QAM		64QAM	
Lowest CH	1.2671		2.979		4.995		10.19		14.446		20.14	
Middle CH	1.2755		2.985		5.035		9.77		14.505		20.14	
Highest CH	1.2699		2.9491		5.045		9.85		14.146		20.38	



Mode	LTE Band 5 : 26dB BW(MHz)											
BW	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Lowest CH	1.27	1.267	2.979	2.979	5.135	5.085	9.71	9.95	-	-	-	-
Middle CH	1.262	1.29	2.943	2.943	4.935	4.995	9.91	9.99	-	-	-	-
Highest CH	1.264	1.292	2.985	2.979	5.135	5.065	9.91	9.97	-	-	-	-

Mode	LTE Band 5 : 26dB BW(MHz)											
BW	1.4MHz		3MHz		5MHz		10MHz					
Mod.	64QAM		64QAM		64QAM		64QAM					
Lowest CH	1.306		2.967		4.995		9.89					
Middle CH	1.27		2.955		5.135		10.07					
Highest CH	1.278		2.925		5.085		10.25					

Mode	LTE Band 7 : 26dB BW(MHz)											
BW	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Lowest CH	-	-	-	-	5.155	5.055	9.97	9.75	14.535	14.595	20.1	20.22
Middle CH	-	-	-	-	5.055	4.915	9.71	10.03	14.446	14.625	20.42	20.26
Highest CH	-	-	-	-	4.985	4.925	9.91	9.95	14.356	14.655	20.18	20.14

Mode	LTE Band 7 : 26dB BW(MHz)											
BW					5MHz		10MHz		15MHz		20MHz	
Mod.					64QAM		64QAM		64QAM		64QAM	
Lowest CH	-	-	-	-	4.965		9.97		14.476		20.22	
Middle CH	-	-	-	-	5.095		9.87		14.595		20.3	
Highest CH	-	-	-	-	5.095		10.11		14.476		20.62	

Mode	LTE Band 38 : 26dB BW(MHz)											
BW	5MHz	10MHz	15MHz	20MHz	5MHz		10MHz		15MHz		20MHz	
Mod.	64QAM	64QAM	64QAM	64QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Lowest CH	4.785	9.81	14.176	20.1	4.855	4.805	9.63	9.71	14.356	14.206	20.14	20.14
Middle CH	4.785	9.65	14.356	20.22	4.795	4.855	9.67	9.77	14.326	14.326	20.18	20.22
Highest CH	4.805	9.65	14.206	20.26	4.845	4.835	9.77	9.69	14.326	14.176	20.3	20.06