System Check_Body_1750MHz

DUT: D1750V2 - SN:1090

Communication System: UID 0, CW (0); Frequency: 1750 MHz;Duty Cycle: 1:1
Medium: MSL_1750 Medium parameters used: f = 1750 MHz; σ = 1.521 S/m; ε_r = 54.081; ρ = 1000 kg/m^3
Ambient Temperature：23.2 ℃；Liquid Temperature：22.6 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN3843; ConvF(7.41, 7.41, 7.41); Calibrated: 2018.9.27
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1338; Calibrated: 2018.12.3
- Phantom: SAM2; Type: SAM; Serial: TP-1503
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

Pin=250mW/Area Scan (61x61x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 13.4 W/kg

Pin=250mW/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 82.39 V/m; Power Drift = 0.01 dB
Peak SAR (extrapolated) = 16.9 W/kg
SAR(1 g) = 9.45 W/kg; SAR(10 g) = 5.01 W/kg
Maximum value of SAR (measured) = 13.4 W/kg

0 dB = 13.4 W/kg = 11.27 dBW/kg

System Check_Body_1900MHz

DUT: D1900V2 - SN:5d170

Communication System: UID 0, CW (0); Frequency: 1900 MHz;Duty Cycle: 1:1
Medium: MSL_1900 Medium parameters used: f = 1900 MHz; σ = 1.538 S/m; ε_r = 52.781; ρ = 1000 kg/m^3
Ambient Temperature：23.4 ℃；Liquid Temperature：22.6 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN3843; ConvF(7.07, 7.07, 7.07); Calibrated: 2018.9.27
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1338; Calibrated: 2018.12.3
- Phantom: SAM2; Type: SAM; Serial: TP-1503
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

Pin=250mW/Area Scan (61x61x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 16.3 W/kg

Pin=250mW/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 91.18 V/m; Power Drift = 0.01 dB
Peak SAR (extrapolated) = 20.5 W/kg
SAR(1 g) = 9.5 W/kg; SAR(10 g) = 5.57 W/kg
Maximum value of SAR (measured) = 16.4 W/kg

0 dB = 16.4 W/kg = 12.15 dBW/kg

System Check_Body_2450MHz

DUT: D2450V2 - SN:908

Communication System: UID 0, CW (0); Frequency: 2600 MHz;Duty Cycle: 1:1
Medium: MSL_2450 Medium parameters used: f = 2600 MHz; σ = 2.008 S/m; $ε_r$ = 52.277; ρ = 1000 kg/m^3
Ambient Temperature：23.4 ℃；Liquid Temperature：22.8 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN3843; ConvF(6.7, 6.7, 6.7); Calibrated: 2018.9.27
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1338; Calibrated: 2018.12.3
- Phantom: SAM1; Type: SAM; Serial: TP-1839
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

Pin=250mW/Area Scan (81x81x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm
Maximum value of SAR (interpolated) = 20.2 W/kg

Pin=250mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 74.40 V/m; Power Drift = 0.05 dB
Peak SAR (extrapolated) = 33.3 W/kg
SAR(1 g) = 13.6 W/kg; SAR(10 g) = 6.21 W/kg
Maximum value of SAR (measured) = 20.3 W/kg

0 dB = 20.3 W/kg = 13.07 dBW/kg

System Check_Body_2600MHz

DUT: D2600V2 - SN:1061

Communication System: UID 0, CW (0); Frequency: 2600 MHz;Duty Cycle: 1:1
Medium: MSL_2600 Medium parameters used: f = 2600 MHz; σ = 2.217 S/m; ε_r = 52.913; ρ = 1000 kg/m^3
Ambient Temperature：23.4 ℃；Liquid Temperature：22.9 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN3843; ConvF(6.7, 6.7, 6.7); Calibrated: 2018.9.27
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1338; Calibrated: 2018.12.3
- Phantom: SAM1; Type: SAM; Serial: TP-1839
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

Pin=250mW/Area Scan (81x81x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm
Maximum value of SAR (interpolated) = 19.5 W/kg

Pin=250mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 65.96 V/m; Power Drift = 0.08 dB
Peak SAR (extrapolated) = 32.6 W/kg
SAR(1 g) = 14.5 W/kg; SAR(10 g) = 6.35 W/kg
Maximum value of SAR (measured) = 19.5 W/kg

0 dB = 19.5 W/kg = 12.90 dBW/kg

System Check_Body_5250MHz

DUT: D5GHzV2-SN:1006

Communication System: UID 0, CW (0); Frequency: 5250 MHz;Duty Cycle: 1:1
Medium: MSL_5000 Medium parameters used: f = 5250 MHz; σ = 5.452 S/m; ε_r = 48.884; ρ = 1000 kg/m^3
Ambient Temperature：23.3 ℃；Liquid Temperature：22.8 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN3857; ConvF(4.4, 4.4, 4.4); Calibrated: 2018.5.31
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1338; Calibrated: 2018.12.3
- Phantom: SAM1; Type: SAM; Serial: TP-1839
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

Pin=100mW/Area Scan (71x71x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Maximum value of SAR (interpolated) = 16.5 W/kg

Pin=100mW/Zoom Scan (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm
Reference Value = 37.89 V/m; Power Drift = 0.01 dB
Peak SAR (extrapolated) = 27.8 W/kg
SAR(1 g) = 7.28 W/kg; SAR(10 g) = 2.09 W/kg
Maximum value of SAR (measured) = 16.2 W/kg

0 dB = 16.2 W/kg = 12.10 dBW/kg

System Check_Body_5600MHz

DUT: D5GHzV2-SN:1006

Communication System: UID 0, CW (0); Frequency: 5600 MHz;Duty Cycle: 1:1
Medium: MSL_5000 Medium parameters used: f = 5600 MHz; σ = 5.909 S/m; ε_r = 48.311; ρ = 1000 kg/m^3
Ambient Temperature：23.3 ℃；Liquid Temperature：22.8 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN3857; ConvF(3.98, 3.98, 3.98); Calibrated: 2018.5.31
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1338; Calibrated: 2018.12.3
- Phantom: SAM1; Type: SAM; Serial: TP-1839
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

Pin=100mW/Area Scan (71x71x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Maximum value of SAR (interpolated) = 18.4 W/kg

Pin=100mW/Zoom Scan (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm
Reference Value = 36.76 V/m; Power Drift = 0.03 dB
Peak SAR (extrapolated) = 31.5 W/kg
SAR(1 g) = 7.45 W/kg; SAR(10 g) = 2.11 W/kg
Maximum value of SAR (measured) = 17.9 W/kg

0 dB = 17.9 W/kg = 12.53 dBW/kg

System Check_Body_5750MHz

DUT: D5GHzV2-SN:1006

Communication System: UID 0, CW (0); Frequency: 5750 MHz;Duty Cycle: 1:1
Medium: MSL_5000 Medium parameters used: f = 5750 MHz; σ = 6.119 S/m; ε_r = 48.065; ρ = 1000 kg/m^3
Ambient Temperature：23.4 ℃；Liquid Temperature：22.6 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN3857; ConvF(4.31, 4.31, 4.31); Calibrated: 2018.5.31
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1338; Calibrated: 2018.12.3
- Phantom: SAM1; Type: SAM; Serial: TP-1839
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

Pin=100mW/Area Scan (71x71x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Maximum value of SAR (interpolated) = 16.4 W/kg

Pin=100mW/Zoom Scan (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm
Reference Value = 35.26 V/m; Power Drift = 0.08 dB
Peak SAR (extrapolated) = 28.2 W/kg
SAR(1 g) = 7.19 W/kg; SAR(10 g) = 2.04 W/kg
Maximum value of SAR (measured) = 16.2 W/kg

0 dB = 16.2 W/kg = 12.10 dBW/kg

Appendix B.   Plots of High SAR Measurement

The plots are shown as follows.

01_GSM850-UAT_GPRS 4 Tx slots_Right Cheek_0mm_Ch189

Communication System: UID 0, GSM850-4UP (0); Frequency: 836.4 MHz;Duty Cycle: 1:2.08
Medium: HSL_850 Medium parameters used: f = 836.4 MHz; σ = 0.922 S/m; ε_r = 42.532; ρ = 1000

kg/m^3
Ambient Temperature：23.2 ℃；Liquid Temperature：22.7 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN3843; ConvF(9.01, 9.01, 9.01); Calibrated: 2018.9.27
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1338; Calibrated: 2018.12.3
- Phantom: SAM1; Type: SAM; Serial: TP-1839
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

Ch189/Area Scan (71x81x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 1.25 W/kg

Ch189/Zoom Scan (6x6x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 14.80 V/m; Power Drift = 0.04 dB
Peak SAR (extrapolated) = 1.78 W/kg
SAR(1 g) = 0.760 W/kg; SAR(10 g) = 0.378 W/kg
Maximum value of SAR (measured) = 1.43 W/kg

0 dB = 1.43 W/kg = 1.55 dBW/kg

02_GSM1900-UAT_GPRS 4 Tx slots_Right Cheek_0mm_Ch810

Communication System: UID 0, PCS-4UP (0); Frequency: 1909.8 MHz;Duty Cycle: 1:2.08
Medium: HSL_1900 Medium parameters used: f = 1909.8 MHz; σ = 1.41 S/m; ε_r = 39.795; ρ = 1000kg/m^3

Ambient Temperature：23.3 ℃；Liquid Temperature：22.7 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN3843; ConvF(7.4, 7.4, 7.4); Calibrated: 2018.9.27
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1338; Calibrated: 2018.12.3
- Phantom: SAM2; Type: SAM; Serial: TP-1503
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

Ch810/Area Scan (71x81x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 1.25 W/kg

Ch810/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 12.06 V/m; Power Drift = 0.06 dB
Peak SAR (extrapolated) = 1.73 W/kg
SAR(1 g) = 0.820 W/kg; SAR(10 g) = 0.390 W/kg
Maximum value of SAR (measured) = 1.32 W/kg

0 dB = 1.32 W/kg = 1.21 dBW/kg

03_WCDMA V-UAT_RMC 12.2Kbps_Right Cheek_0mm_Ch4182

Communication System: UID 0, WCDMA (0); Frequency: 836.4 MHz;Duty Cycle: 1:1
Medium: HSL_850 Medium parameters used: f = 836.4 MHz; σ = 0.922 S/m; ε_r = 42.532; ρ = 1000 kg/m^3
Ambient Temperature：23.2 ℃；Liquid Temperature：22.7 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN3843; ConvF(9.01, 9.01, 9.01); Calibrated: 2018.9.27
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1338; Calibrated: 2018.12.3
- Phantom: SAM1; Type: SAM; Serial: TP-1839
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

Ch4182/Area Scan (71x81x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 1.37 W/kg

Ch4182/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 15.07 V/m; Power Drift = 0.09 dB
Peak SAR (extrapolated) = 1.97 W/kg
SAR(1 g) = 0.838 W/kg; SAR(10 g) = 0.407 W/kg
Maximum value of SAR (measured) = 1.56 W/kg

0 dB = 1.56 W/kg = 1.93 dBW/kg

04_WCDMA IV-UAT_RMC 12.2Kbps_Right Cheek_0mm_Ch1513

Communication System: UID 0, WCDMA (0); Frequency: 1752.6 MHz;Duty Cycle: 1:1
Medium: HSL_1750 Medium parameters used: f = 1752.6 MHz; σ = 1.374 S/m; ε_r = 40.642; ρ = 1000kg/m^3
Ambient Temperature：23.3 ℃；Liquid Temperature：22.6 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN3843; ConvF(7.79, 7.79, 7.79); Calibrated: 2018.9.27
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1338; Calibrated: 2018.12.3
- Phantom: SAM2; Type: SAM; Serial: TP-1503
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

Ch1513/Area Scan (71x81x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 1.18 W/kg

Ch1513/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 11.79 V/m; Power Drift = 0.11 dB
Peak SAR (extrapolated) = 1.69 W/kg
SAR(1 g) = 0.857 W/kg; SAR(10 g) = 0.425 W/kg
Maximum value of SAR (measured) = 0.982 W/kg

0 dB = 0.982 W/kg = -0.08 dBW/kg

05_WCDMA II-UAT_RMC 12.2Kbps_Right Cheek_0mm_Ch9538

Communication System: UID 0, WCDMA (0); Frequency: 1907.6 MHz;Duty Cycle: 1:1
Medium: HSL_1900 Medium parameters used: f = 1907.6 MHz; σ = 1.408 S/m; ε_r = 39.807; ρ = 1000kg/m^3
Ambient Temperature：23.3 ℃；Liquid Temperature：22.7 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN3843; ConvF(7.4, 7.4, 7.4); Calibrated: 2018.9.27
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1338; Calibrated: 2018.12.3
- Phantom: SAM2; Type: SAM; Serial: TP-1503
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

Ch9538/Area Scan (71x81x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 1.21 W/kg

Ch9538/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 11.87 V/m; Power Drift = 0.10 dB
Peak SAR (extrapolated) = 1.83 W/kg
SAR(1 g) = 0.892 W/kg; SAR(10 g) = 0.428 W/kg
Maximum value of SAR (measured) = 1.02 W/kg

0 dB = 1.02 W/kg = 0.09 dBW/kg

06_LTE Band 5-UAT_10M_QPSK_25RB_0Offset_Right Cheek_0mm_Ch20525

Communication System: UID 0, LTE-FDD (0); Frequency: 836.5 MHz;Duty Cycle: 1:1
Medium: HSL_850 Medium parameters used: f = 836.5 MHz; σ = 0.922 S/m; ε_r = 42.531; ρ = 1000 kg/m^3

Ambient Temperature：23.2 ℃；Liquid Temperature：22.7 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN3843; ConvF(9.01, 9.01, 9.01); Calibrated: 2018.9.27
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1338; Calibrated: 2018.12.3
- Phantom: SAM1; Type: SAM; Serial: TP-1839
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

Ch20525/Area Scan (71x81x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.865 W/kg

Ch20525/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 0.9560 V/m; Power Drift = 0.02 dB
Peak SAR (extrapolated) = 1.55 W/kg
SAR(1 g) = 0.734 W/kg; SAR(10 g) = 0.356 W/kg
Maximum value of SAR (measured) = 0.984 W/kg

0 dB = 0.984 W/kg = -0.07 dBW/kg

07_LTE Band 4-UAT_20M_QPSK_100RB_0Offset_Right Cheek_0mm_Ch20175

Communication System: UID 0, LTE-FDD (0); Frequency: 1732.5 MHz;Duty Cycle: 1:1
Medium: HSL_1750 Medium parameters used: f = 1732.5 MHz; σ = 1.354 S/m; ε_r = 40.729; ρ = 1000kg/m³
Ambient Temperature：23.3 ℃；Liquid Temperature：22.6 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN3843; ConvF(7.79, 7.79, 7.79); Calibrated: 2018.9.27
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1338; Calibrated: 2018.12.3
- Phantom: SAM2; Type: SAM; Serial: TP-1503
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

Ch20175/Area Scan (71x81x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 1.36 W/kg

Ch20175/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 0.6740 V/m; Power Drift = 0.08 dB
Peak SAR (extrapolated) = 1.84 W/kg
SAR(1 g) = 0.930 W/kg; SAR(10 g) = 0.461 W/kg
Maximum value of SAR (measured) = 1.23 W/kg

0 dB = 1.23 W/kg = 0.90 dBW/kg

08_LTE Band 2-UAT_20M_QPSK_100RB_0Offset_Right Cheek_0mm_Ch18900

Communication System: UID 0, LTE-FDD (0); Frequency: 1880 MHz;Duty Cycle: 1:1
Medium: HSL_1900 Medium parameters used: f = 1880 MHz; σ = 1.378 S/m; ε_r = 39.946; ρ = 1000 kg/m^3
Ambient Temperature：23.3 ℃；Liquid Temperature：22.7 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN3843; ConvF(7.4, 7.4, 7.4); Calibrated: 2018.9.27
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1338; Calibrated: 2018.12.3
- Phantom: SAM2; Type: SAM; Serial: TP-1503
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

Ch18900/Area Scan (71x81x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 1.10 W/kg

Ch18900/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 12.24 V/m; Power Drift = 0.02 dB
Peak SAR (extrapolated) = 1.53 W/kg
SAR(1 g) = 0.765 W/kg; SAR(10 g) = 0.372 W/kg
Maximum value of SAR (measured) = 1.03 W/kg

0 dB = 1.03 W/kg = 0.13 dBW/kg

09_LTE Band 7-UAT_20M_QPSK_1RB_0Offset_Right Cheek_0mm_Ch21350

Communication System: UID 0, LTE-FDD (0); Frequency: 2560 MHz;Duty Cycle: 1:1
Medium: HSL_2600 Medium parameters used: f = 2560 MHz; σ = 1.953 S/m; ε_r = 38.615; ρ = 1000 kg/m^3
Ambient Temperature：23.4 ℃；Liquid Temperature：22.6 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN3843; ConvF(6.86, 6.86, 6.86); Calibrated: 2018.9.27
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1338; Calibrated: 2018.12.3
- Phantom: SAM1; Type: SAM; Serial: TP-1839
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

Ch21350/Area Scan (81x101x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm
Maximum value of SAR (interpolated) = 1.12 W/kg

Ch21350/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 9.316 V/m; Power Drift = -0.01 dB
Peak SAR (extrapolated) = 2.22 W/kg
SAR(1 g) = 0.740 W/kg; SAR(10 g) = 0.316 W/kg
Maximum value of SAR (measured) = 1.48 W/kg

0 dB = 1.48 W/kg = 1.70 dBW/kg

10_LTE Band 38-UAT_20M_QPSK_1RB_0Offset_Right Cheek_0mm_Ch38000

Communication System: UID 0, LTE-TDD (0); Frequency: 2595 MHz;Duty Cycle: 1:1.59
Medium: HSL_2600 Medium parameters used: f = 2595 MHz; σ = 1.993 S/m; ε_r = 38.47; ρ = 1000 kg/m^3
Ambient Temperature：23.4 ℃；Liquid Temperature：22.6 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN3843; ConvF(6.86, 6.86, 6.86); Calibrated: 2018.9.27
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1338; Calibrated: 2018.12.3
- Phantom: SAM1; Type: SAM; Serial: TP-1839
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

Ch38000/Area Scan (91x101x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm
Maximum value of SAR (interpolated) = 1.02 W/kg

Ch38000/Zoom Scan (8x10x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 7.915 V/m; Power Drift = 0.11 dB
Peak SAR (extrapolated) = 1.44 W/kg
SAR(1 g) = 0.562 W/kg; SAR(10 g) = 0.245 W/kg
Maximum value of SAR (measured) = 1.08 W/kg

0 dB = 1.08 W/kg = 0.33 dBW/kg

11_WLAN2.4GHz_802.11b 1Mbps_Left Tilted_0mm_Ant 1_Ch11

Communication System: UID 0, 802.11b (0); Frequency: 2462 MHz;Duty Cycle: 1:1
Medium: HSL_2450 Medium parameters used: f = 2462 MHz; σ = 1.841 S/m; ε_r = 39.013; ρ = 1000 kg/m^3
Ambient Temperature　23.3 ℃；Liquid Temperature　22.9 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN3843; ConvF(7.08, 7.08, 7.08); Calibrated: 2018.9.27
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1338; Calibrated: 2018.12.3
- Phantom: SAM1; Type: SAM; Serial: TP-1839
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

Ch11/Area Scan (81x71x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm
Maximum value of SAR (interpolated) = 0.931 W/kg

Ch11/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 13.89 V/m; Power Drift = -0.13 dB
Peak SAR (extrapolated) = 1.32 W/kg
SAR(1 g) = 0.477 W/kg; SAR(10 g) = 0.200 W/kg
Maximum value of SAR (measured) = 0.921 W/kg

0 dB = 0.931 W/kg = -0.31 dBW/kg

12_WLAN5GHz_802.11a 6Mbps_Left Cheek_0mm_Ant 1_Ch56

Communication System: UID 0, 802.11a (0); Frequency: 5280 MHz;Duty Cycle: 1:1.021
Medium: HSL_5000 Medium parameters used: f = 5280 MHz; σ = 4.816 S/m; ε_r = 35.749; ρ = 1000 kg/m^3
Ambient Temperature　23.2 ℃；Liquid Temperature　22.9 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN3857; ConvF(5.2, 5.2, 5.2); Calibrated: 2018.5.31
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1338; Calibrated: 2018.12.3
- Phantom: SAM1; Type: SAM; Serial: TP-1839
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

Ch56/Area Scan (101x81x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Maximum value of SAR (interpolated) = 2.16 W/kg

Ch56/Zoom Scan (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm
Reference Value = 9.978 V/m; Power Drift = -0.05 dB
Peak SAR (extrapolated) = 4.42 W/kg
SAR(1 g) = 0.984 W/kg; SAR(10 g) = 0.277 W/kg
Maximum value of SAR (measured) = 2.56 W/kg

0 dB = 2.16 W/kg = 3.34 dBW/kg

13_WLAN5GHz_802.11a 6Mbps_Left Cheek_0mm_Ant 1_Ch100

Communication System: UID 0, 802.11a (0); Frequency: 5500 MHz;Duty Cycle: 1:1.021
Medium: HSL_5000 Medium parameters used: f = 5500 MHz; σ = 5.035 S/m; ε_r = 35.417; ρ = 1000 kg/m^3
Ambient Temperature　23.3 ℃；Liquid Temperature　22.7 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN3857; ConvF(4.94, 4.94, 4.94); Calibrated: 2018.5.31
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1338; Calibrated: 2018.12.3
- Phantom: SAM1; Type: SAM; Serial: TP-1839
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

Ch100/Area Scan (101x81x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Maximum value of SAR (interpolated) = 1.67 W/kg

Ch100/Zoom Scan (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm
Reference Value = 8.102 V/m; Power Drift = 0.10 dB
Peak SAR (extrapolated) = 3.76 W/kg
SAR(1 g) = 0.779 W/kg; SAR(10 g) = 0.241 W/kg
Maximum value of SAR (measured) = 2.06 W/kg

0 dB = 1.67 W/kg = 2.23 dBW/kg

14_WLAN5GHz_802.11a 6Mbps_Left Cheek_0mm_Ant 1_Ch161

Communication System: UID 0, 802.11a (0); Frequency: 5805 MHz;Duty Cycle: 1:1.021
Medium: HSL_5000 Medium parameters used: f = 5805 MHz; σ = 5.359 S/m; ε_r = 34.958; ρ = 1000 kg/m^3
Ambient Temperature   23.4 ℃；Liquid Temperature   22.8 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN3857; ConvF(5.23, 5.23, 5.23); Calibrated: 2018.5.31
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1338; Calibrated: 2018.12.3
- Phantom: SAM1; Type: SAM; Serial: TP-1839
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

Ch165/Area Scan (101x81x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Maximum value of SAR (interpolated) = 2.36 W/kg

Ch165/Zoom Scan (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm
Reference Value = 6.484 V/m; Power Drift = 0.05 dB
Peak SAR (extrapolated) = 5.70 W/kg
SAR(1 g) = 0.957 W/kg; SAR(10 g) = 0.215 W/kg
Maximum value of SAR (measured) = 2.80 W/kg

0 dB = 2.36 W/kg = 3.73 dBW/kg

15_ Bluetooth_1Mbps_Left Tilted_0mm_Ant 1_Ch78

Communication System: UID 0, Bluetooth (0); Frequency: 2480 MHz;Duty Cycle: 1:1.30
Medium: HSL_2450 Medium parameters used: f = 2480 MHz; σ = 1.859 S/m; ε_r = 38.937; ρ = 1000 kg/m^3
Ambient Temperature：23.3 ℃；Liquid Temperature：22.9 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN3843; ConvF(7.08, 7.08, 7.08); Calibrated: 2018.9.27
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1338; Calibrated: 2018.12.3
- Phantom: SAM1; Type: SAM; Serial: TP-1839
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

Ch78/Area Scan (81x101x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm
Maximum value of SAR (interpolated) = 0.323 W/kg

Ch78/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 9.021 V/m; Power Drift = -0.15 dB
Peak SAR (extrapolated) = 0.493 W/kg
SAR(1 g) = 0.136 W/kg; SAR(10 g) = 0.070 W/kg
Maximum value of SAR (measured) = 0.340 W/kg

0 dB = 0.340 W/kg = -4.69 dBW/kg

16_GSM850-LAT_GPRS 4 Tx slots_Back_10mm_Ch189

Communication System: UID 0, GSM850-4UP (0); Frequency: 836.4 MHz;Duty Cycle: 1:2.08
Medium: MSL_850 Medium parameters used: f = 836.4 MHz; σ = 0.999 S/m; ε_r = 54.634; ρ = 1000 kg/m^3

Ambient Temperature：23.3 ℃；Liquid Temperature：22.9 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN3843; ConvF(9.03, 9.03, 9.03); Calibrated: 2018.9.27
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1338; Calibrated: 2018.12.3
- Phantom: SAM1; Type: SAM; Serial: TP-1839
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

Ch189/Area Scan (71x81x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.359 W/kg

Ch189/Zoom Scan (6x6x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 14.79 V/m; Power Drift = -0.08 dB
Peak SAR (extrapolated) = 0.428 W/kg
SAR(1 g) = 0.239 W/kg; SAR(10 g) = 0.145 W/kg
Maximum value of SAR (measured) = 0.353 W/kg

0 dB = 0.353 W/kg = -4.52 dBW/kg

17_GSM1900-LAT_GPRS 4 Tx slots_Bottom Side_10mm_Ch810

Communication System: UID 0, PCS-4UP (0); Frequency: 1909.8 MHz;Duty Cycle: 1:2.08
Medium: MSL_1900 Medium parameters used: f = 1909.8 MHz; σ = 1.545 S/m; ε_r = 53.003; ρ = 1000kg/m^3
Ambient Temperature：23.4 ℃；Liquid Temperature：22.6 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN3843; ConvF(7.07, 7.07, 7.07); Calibrated: 2018.9.27
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1338; Calibrated: 2018.12.3
- Phantom: SAM2; Type: SAM; Serial: TP-1503
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

Ch810/Area Scan (41x61x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 1.36 W/kg

Ch810/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 26.05 V/m; Power Drift = 0.02 dB
Peak SAR (extrapolated) = 1.48 W/kg
SAR(1 g) = 0.821 W/kg; SAR(10 g) = 0.422 W/kg
Maximum value of SAR (measured) = 1.25 W/kg

0 dB = 1.25 W/kg = 0.97 dBW/kg

18_WCDMA V-LAT_RMC 12.2Kbps_Back_10mm_Ch4182

Communication System: UID 0, WCDMA (0); Frequency: 836.4 MHz;Duty Cycle: 1:1
Medium: MSL_850 Medium parameters used: f = 836.4 MHz; σ = 0.999 S/m; ε_r = 54.634; ρ = 1000 kg/m^3
Ambient Temperature：23.3 ℃；Liquid Temperature：22.9 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN3843; ConvF(9.03, 9.03, 9.03); Calibrated: 2018.9.27
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1338; Calibrated: 2018.12.3
- Phantom: SAM1; Type: SAM; Serial: TP-1839
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

Ch4182/Area Scan (71x81x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.545 W/kg

Ch4182/Zoom Scan (6x6x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 18.21 V/m; Power Drift = -0.05 dB
Peak SAR (extrapolated) = 0.651 W/kg
SAR(1 g) = 0.363 W/kg; SAR(10 g) = 0.220 W/kg
Maximum value of SAR (measured) = 0.537 W/kg

0 dB = 0.537 W/kg = -2.70 dBW/kg

19_WCDMA IV-LAT_RMC 12.2Kbps_Bottom Side_10mm_Ch1413

Communication System: UID 0, WCDMA (0); Frequency: 1732.6 MHz;Duty Cycle: 1:1
Medium: MSL_1750 Medium parameters used: f = 1732.6 MHz; σ = 1.504 S/m; ε_r = 54.131; ρ = 1000kg/m^3
Ambient Temperature：23.2 ℃；Liquid Temperature：22.6 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN3843; ConvF(7.41, 7.41, 7.41); Calibrated: 2018.9.27
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1338; Calibrated: 2018.12.3
- Phantom: SAM2; Type: SAM; Serial: TP-1503
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

Ch1413/Area Scan (41x61x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 1.23 W/kg

Ch1413/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 24.82 V/m; Power Drift = 0.06 dB
Peak SAR (extrapolated) = 1.34 W/kg
SAR(1 g) = 0.769 W/kg; SAR(10 g) = 0.412 W/kg
Maximum value of SAR (measured) = 1.13 W/kg

0 dB = 1.13 W/kg = 0.53 dBW/kg

20_WCDMA II-LAT_RMC 12.2Kbps_Bottom Side_10mm_Ch9262

Communication System: UID 0, WCDMA (0); Frequency: 1852.4 MHz;Duty Cycle: 1:1
Medium: MSL_1900 Medium parameters used: f = 1852.4 MHz; σ = 1.48 S/m; ε_r = 53.181; ρ = 1000 kg/m^3
Ambient Temperature：23.4 ℃；Liquid Temperature：22.6 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN3843; ConvF(7.07, 7.07, 7.07); Calibrated: 2018.9.27
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1338; Calibrated: 2018.12.3
- Phantom: SAM2; Type: SAM; Serial: TP-1503
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

Ch9262/Area Scan (41x61x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 1.14 W/kg

Ch9262/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 24.02 V/m; Power Drift = 0.08 dB
Peak SAR (extrapolated) = 1.28 W/kg
SAR(1 g) = 0.697 W/kg; SAR(10 g) = 0.361 W/kg
Maximum value of SAR (measured) = 1.04 W/kg

0 dB = 1.04 W/kg = 0.17 dBW/kg

21_LTE Band 5-LAT_10M_QPSK_1RB_0Offset_Right Side_10mm_Ch20525

Communication System: UID 0, LTE-FDD (0); Frequency: 836.5 MHz;Duty Cycle: 1:1
Medium: MSL_850 Medium parameters used: f = 836.5 MHz; σ = 0.999 S/m; ε_r = 54.633; ρ = 1000 kg/m^3
Ambient Temperature：23.3 ℃；Liquid Temperature：22.9 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN3843; ConvF(9.03, 9.03, 9.03); Calibrated: 2018.9.27
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1338; Calibrated: 2018.12.3
- Phantom: SAM1; Type: SAM; Serial: TP-1839
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

Ch20525/Area Scan (41x81x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.383 W/kg

Ch20525/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 9.782 V/m; Power Drift = -0.04 dB
Peak SAR (extrapolated) = 0.447 W/kg
SAR(1 g) = 0.291 W/kg; SAR(10 g) = 0.198 W/kg
Maximum value of SAR (measured) = 0.389 W/kg

0 dB = 0.389 W/kg = -4.10 dBW/kg

22_LTE Band 4-LAT_20M_QPSK_50RB_0Offset_Bottom Side_10mm_Ch20175

Communication System: UID 0, LTE-FDD (0); Frequency: 1732.5 MHz;Duty Cycle: 1:1
Medium: MSL_1750 Medium parameters used: f = 1732.5 MHz; σ = 1.504 S/m; ε_r = 54.131; ρ = 1000kg/m^3
Ambient Temperature：23.2 ℃；Liquid Temperature：22.6 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN3843; ConvF(7.41, 7.41, 7.41); Calibrated: 2018.9.27
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1338; Calibrated: 2018.12.3
- Phantom: SAM2; Type: SAM; Serial: TP-1503
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

Ch20175/Area Scan (41x61x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 1.04 W/kg

Ch20175/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 18.08 V/m; Power Drift = 0.08 dB
Peak SAR (extrapolated) = 1.29 W/kg
SAR(1 g) = 0.779 W/kg; SAR(10 g) = 0.417 W/kg
Maximum value of SAR (measured) = 0.970 W/kg

0 dB = 0.970 W/kg = -0.13 dBW/kg

23_LTE Band 2-LAT_20M_QPSK_50RB_0Offset_Bottom Side_10mm_Ch18700

Communication System: UID 0, LTE-FDD (0); Frequency: 1860 MHz;Duty Cycle: 1:1
Medium: MSL_1900 Medium parameters used: f = 1860 MHz; σ = 1.493 S/m; ε_r = 52.947; ρ = 1000 kg/m^3
Ambient Temperature：23.4 ℃；Liquid Temperature：22.6 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN3843; ConvF(7.07, 7.07, 7.07); Calibrated: 2018.9.27
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1338; Calibrated: 2018.12.3
- Phantom: SAM2; Type: SAM; Serial: TP-1503
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

Ch18700/Area Scan (41x61x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 1.21 W/kg

Ch18700/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 20.05 V/m; Power Drift = 0.06 dB
Peak SAR (extrapolated) = 1.41 W/kg
SAR(1 g) = 0.772 W/kg; SAR(10 g) = 0.402 W/kg
Maximum value of SAR (measured) = 1.18 W/kg

0 dB = 1.18 W/kg = 0.72 dBW/kg

24_LTE Band 7_20M_QPSK_100RB_0Offset_Bottom Side_10mm_Ch21100

Communication System: UID 0, LTE-FDD (0); Frequency: 2535 MHz;Duty Cycle: 1:1
Medium: MSL_2600 Medium parameters used: f = 2535 MHz; σ = 2.125 S/m; ε_r = 52.866; ρ = 1000 kg/m^3
Ambient Temperature：23.4 ℃；Liquid Temperature：22.9 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN3843; ConvF(6.7, 6.7, 6.7); Calibrated: 2018.9.27
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1338; Calibrated: 2018.12.3
- Phantom: SAM1; Type: SAM; Serial: TP-1839
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

Ch21100/Area Scan (51x81x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm
Maximum value of SAR (interpolated) = 1.19 W/kg

Ch21100/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 5.656 V/m; Power Drift = 0.07 dB
Peak SAR (extrapolated) = 1.43 W/kg
SAR(1 g) = 0.706 W/kg; SAR(10 g) = 0.346 W/kg
Maximum value of SAR (measured) = 1.15 W/kg

0 dB = 1.15 W/kg = 0.61 dBW/kg

25_LTE Band 38-LAT_20M_QPSK_1RB_0Offset_Bottom Side_10mm_Ch38000

Communication System: UID 0, LTE-TDD (0); Frequency: 2595 MHz;Duty Cycle: 1:1.59
Medium: MSL_2600 Medium parameters used: f = 2595 MHz; σ = 2.21 S/m; ε_r = 52.93; ρ = 1000 kg/m^3
Ambient Temperature：23.4 ℃；Liquid Temperature：22.9 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN3843; ConvF(6.7, 6.7, 6.7); Calibrated: 2018.9.27
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1338; Calibrated: 2018.12.3
- Phantom: SAM1; Type: SAM; Serial: TP-1839
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

Ch38000/Area Scan (41x91x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm
Maximum value of SAR (interpolated) = 1.43 W/kg

Ch38000/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 23.18 V/m; Power Drift = 0.03 dB
Peak SAR (extrapolated) = 1.74 W/kg
SAR(1 g) = 0.868 W/kg; SAR(10 g) = 0.419 W/kg
Maximum value of SAR (measured) = 1.42 W/kg

0 dB = 1.42 W/kg = 1.52 dBW/kg

26_WLAN2.4GHz_802.11b 1Mbps_Top Side_10mm_Ant 1_Ch11

Communication System: UID 0, 802.11b (0); Frequency: 2462 MHz;Duty Cycle: 1:1
Medium: MSL_2600 Medium parameters used: f = 2462 MHz; σ = 2.025 S/m; ε_r = 53.413; ρ = 1000 kg/m^3
Ambient Temperature：23.4 ℃；Liquid Temperature：22.8 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN3843; ConvF(6.7, 6.7, 6.7); Calibrated: 2018.9.27
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1338; Calibrated: 2018.12.3
- Phantom: SAM1; Type: SAM; Serial: TP-1839
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

Ch11/Area Scan (41x81x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm
Maximum value of SAR (interpolated) = 0.340 W/kg

Ch11/Zoom Scan (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm
Reference Value = 8.674 V/m; Power Drift = 0.01 dB
Peak SAR (extrapolated) = 0.415 W/kg
SAR(1 g) = 0.204 W/kg; SAR(10 g) = 0.100 W/kg
Maximum value of SAR (measured) = 0.330 W/kg

0 dB = 0.330 W/kg = -4.81 dBW/kg

27_WLAN5GHz_802.11a 6Mbps_Back_10mm_Ant 1_Ch44

Communication System: UID 0, 802.11a (0); Frequency: 5220 MHz;Duty Cycle: 1:1.021
Medium: MSL_5000 Medium parameters used: f = 5220 MHz; σ = 5.411 S/m; ε_r = 48.931; ρ = 1000 kg/m^3
Ambient Temperature：23.3 ℃；Liquid Temperature：22.8 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN3857; ConvF(4.4, 4.4, 4.4); Calibrated: 2018.5.31
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1338; Calibrated: 2018.12.3
- Phantom: SAM1; Type: SAM; Serial: TP-1839
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

Ch44/Area Scan (101x81x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Maximum value of SAR (interpolated) = 0.687 W/kg

Ch44/Zoom Scan (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm
Reference Value = 1.409 V/m; Power Drift = 0.06 dB
Peak SAR (extrapolated) = 1.17 W/kg
SAR(1 g) = 0.306 W/kg; SAR(10 g) = 0.105 W/kg
Maximum value of SAR (measured) = 0.725 W/kg

0 dB = 0.725 W/kg = -1.40 dBW/kg

28_WLAN5GHz_802.11a 6Mbps_Back_10mm_Ant 1_Ch161

Communication System: UID 0, 802.11a (0); Frequency: 5805 MHz;Duty Cycle: 1:1.021
Medium: MSL_5000 Medium parameters used: f = 5805 MHz; σ = 6.192 S/m; ε_r = 47.995; ρ = 1000 kg/m^3
Ambient Temperature　23.3 ℃；Liquid Temperature　22.8 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN3857; ConvF(3.98, 3.98, 3.98); Calibrated: 2018.5.311
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1338; Calibrated: 2018.12.3
- Phantom: SAM1; Type: SAM; Serial: TP-1839
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

Ch161/Area Scan (101x81x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Maximum value of SAR (interpolated) = 1.38 W/kg

Ch161/Zoom Scan (9x9x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm
Reference Value = 3.319 V/m; Power Drift = 0.14 dB
Peak SAR (extrapolated) = 2.49 W/kg
SAR(1 g) = 0.571 W/kg; SAR(10 g) = 0.229 W/kg
Maximum value of SAR (measured) = 1.37 W/kg

0 dB = 1.38 W/kg = 1.40 dBW/kg

29_ Bluetooth_1Mbps_Top Side_10mm_Ant 1_Ch78

Communication System: UID 0, Bluetooth (0); Frequency: 2480 MHz;Duty Cycle: 1:3.0
Medium: MSL_2450 Medium parameters used: f = 2480 MHz; σ = 2.048 S/m; ε_r = 52.174; ρ = 1000 kg/m^3
Ambient Temperature：23.4 ℃；Liquid Temperature：22.8 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN3843; ConvF(6.7, 6.7, 6.7); Calibrated: 2018.9.27
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1338; Calibrated: 2018.12.3
- Phantom: SAM1; Type: SAM; Serial: TP-1839
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

Ch78/Area Scan (51x81x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm
Maximum value of SAR (interpolated) = 0.101 W/kg

Ch78/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 5.169 V/m; Power Drift = 0.05 dB
Peak SAR (extrapolated) = 0.125 W/kg
SAR(1 g) = 0.066 W/kg; SAR(10 g) = 0.034 W/kg
Maximum value of SAR (measured) = 0.103 W/kg

0 dB = 0.103 W/kg = -9.87 dBW/kg

30_GSM850-LAT_GPRS 4 Tx slots_Back_15mm_Ch189

Communication System: UID 0, GSM850-4UP (0); Frequency: 836.4 MHz;Duty Cycle: 1:2.08
Medium: MSL_850 Medium parameters used: f = 836.4 MHz; σ = 0.999 S/m; ε_r = 54.634; ρ = 1000

kg/m^3
Ambient Temperature：23.3 ℃；Liquid Temperature：22.9 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN3843; ConvF(9.03, 9.03, 9.03); Calibrated: 2018.9.27
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1338; Calibrated: 2018.12.3
- Phantom: SAM1; Type: SAM; Serial: TP-1839
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

Ch189/Area Scan (71x121x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.181 W/kg

Ch189/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 13.48 V/m; Power Drift = -0.05 dB
Peak SAR (extrapolated) = 0.208 W/kg
SAR(1 g) = 0.152 W/kg; SAR(10 g) = 0.116 W/kg
Maximum value of SAR (measured) = 0.187 W/kg

0 dB = 0.187 W/kg = -7.28 dBW/kg

31_GSM1900-LAT_GPRS 4 Tx slots_Back_15mm_Ch661

Communication System: UID 0, PCS-4UP (0); Frequency: 1880 MHz;Duty Cycle: 1:2.08

Medium: MSL_1900 Medium parameters used: f = 1880 MHz; σ = 1.51 S/m; $ε_r$ = 53.095; ρ = 1000 kg/m^3

Ambient Temperature：23.4 ℃；Liquid Temperature：22.6 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN3843; ConvF(7.07, 7.07, 7.07); Calibrated: 2018.9.27
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1338; Calibrated: 2018.12.3
- Phantom: SAM2; Type: SAM; Serial: TP-1503
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

Ch661/Area Scan (71x71x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.343 W/kg

Ch661/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 4.898 V/m; Power Drift = -0.09 dB
Peak SAR (extrapolated) = 0.446 W/kg
SAR(1 g) = 0.231 W/kg; SAR(10 g) = 0.132 W/kg
Maximum value of SAR (measured) = 0.345 W/kg

0 dB = 0.345 W/kg = -4.62 dBW/kg

32_WCDMA V-LAT_RMC 12.2Kbps_Back_15mm_Ch4182

Communication System: UID 0, WCDMA (0); Frequency: 836.4 MHz;Duty Cycle: 1:1
Medium: MSL_850 Medium parameters used: f = 836.4 MHz; σ = 0.999 S/m; ε_r = 54.634; ρ = 1000 kg/m^3
Ambient Temperature：23.3 ℃；Liquid Temperature：22.9 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN3843; ConvF(9.03, 9.03, 9.03); Calibrated: 2018.9.27
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1338; Calibrated: 2018.12.3
- Phantom: SAM1; Type: SAM; Serial: TP-1839
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

Ch4182/Area Scan (71x121x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.293 W/kg

Ch4182/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 17.21 V/m; Power Drift = -0.02 dB
Peak SAR (extrapolated) = 0.331 W/kg
SAR(1 g) = 0.242 W/kg; SAR(10 g) = 0.183 W/kg
Maximum value of SAR (measured) = 0.298 W/kg

0 dB = 0.298 W/kg = -5.26 dBW/kg

33_WCDMA IV_RMC 12.2Kbps_Back_15mm_Ch1513

Communication System: UID 0, WCDMA (0); Frequency: 1752.6 MHz;Duty Cycle: 1:1
Medium: MSL_1750 Medium parameters used: f = 1752.6 MHz; σ = 1.524 S/m; ε_r = 54.068; ρ = 1000kg/m^3
Ambient Temperature：23.2 ℃；Liquid Temperature：22.6 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN3843; ConvF(7.41, 7.41, 7.41); Calibrated: 2018.9.27
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1338; Calibrated: 2018.12.3
- Phantom: SAM2; Type: SAM; Serial: TP-1503
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

Ch1312/Area Scan (71x61x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 1.01 W/kg

Ch1312/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 6.620 V/m; Power Drift = -0.05 dB
Peak SAR (extrapolated) = 1.16 W/kg
SAR(1 g) = 0.715 W/kg; SAR(10 g) = 0.419 W/kg
Maximum value of SAR (measured) = 1.01 W/kg

0 dB = 1.01 W/kg = 0.04 dBW/kg

34_WCDMA II-LAT_RMC 12.2Kbps_Back_15mm_Ch9538

Communication System: UID 0, WCDMA (0); Frequency: 1907.6 MHz;Duty Cycle: 1:1
Medium: MSL_1900 Medium parameters used: f = 1907.6 MHz; σ = 1.543 S/m; ε_r = 53.009; ρ = 1000kg/m^3
Ambient Temperature：23.4 ℃；Liquid Temperature：22.6 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN3843; ConvF(7.07, 7.07, 7.07); Calibrated: 2018.9.27
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1338; Calibrated: 2018.12.3
- Phantom: SAM2; Type: SAM; Serial: TP-1503
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

Ch9538/Area Scan (71x61x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.858 W/kg

Ch9538/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 7.118 V/m; Power Drift = 0.02 dB
Peak SAR (extrapolated) = 1.19 W/kg
SAR(1 g) = 0.721 W/kg; SAR(10 g) = 0.407 W/kg
Maximum value of SAR (measured) = 0.878 W/kg

0 dB = 0.878 W/kg = -0.57 dBW/kg

35_LTE Band 5-LAT_10M_QPSK_1RB_0Offset_Back_15mm_Ch20525

Communication System: UID 0, LTE-FDD (0); Frequency: 836.5 MHz;Duty Cycle: 1:1
Medium: MSL_850 Medium parameters used: f = 836.5 MHz; σ = 0.999 S/m; ε_r = 54.633; ρ = 1000 kg/m^3
Ambient Temperature：23.3 ℃；Liquid Temperature：22.9 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN3843; ConvF(9.03, 9.03, 9.03); Calibrated: 2018.9.27
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1338; Calibrated: 2018.12.3
- Phantom: SAM1; Type: SAM; Serial: TP-1839
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

Ch20525/Area Scan (71x121x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.239 W/kg

Ch20525/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 15.29 V/m; Power Drift = -0.04 dB
Peak SAR (extrapolated) = 0.264 W/kg
SAR(1 g) = 0.193 W/kg; SAR(10 g) = 0.147 W/kg
Maximum value of SAR (measured) = 0.238 W/kg

0 dB = 0.238 W/kg = -6.23 dBW/kg

36_LTE Band 4-LAT_20M_QPSK_1RB_0Offset_Back_15mm_Ch20175

Communication System: UID 0, LTE-FDD (0); Frequency: 1732.5 MHz;Duty Cycle: 1:1
Medium: MSL_1750 Medium parameters used: f = 1732.5 MHz; σ = 1.504 S/m; ε_r = 54.131; ρ = 1000kg/m³
Ambient Temperature：23.2 ℃；Liquid Temperature：22.6 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN3843; ConvF(7.41, 7.41, 7.41); Calibrated: 2018.9.27
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1338; Calibrated: 2018.12.3
- Phantom: SAM2; Type: SAM; Serial: TP-1503
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

Ch20175/Area Scan (71x61x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.841 W/kg

Ch20175/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 6.875 V/m; Power Drift = -0.07 dB
Peak SAR (extrapolated) = 0.990 W/kg
SAR(1 g) = 0.611 W/kg; SAR(10 g) = 0.358 W/kg
Maximum value of SAR (measured) = 0.858 W/kg

0 dB = 0.858 W/kg = -0.67 dBW/kg

37_LTE Band 2-LAT_20M_QPSK_1RB_0Offset_Back_15mm_Ch18900

Communication System: UID 0, LTE-FDD (0); Frequency: 1880 MHz;Duty Cycle: 1:1
Medium: MSL_1900 Medium parameters used: f = 1880 MHz; σ = 1.51 S/m; ε_r = 53.095; ρ = 1000 kg/m^3
Ambient Temperature：23.4 ℃；Liquid Temperature：22.6 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN3843; ConvF(7.07, 7.07, 7.07); Calibrated: 2018.9.27
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1338; Calibrated: 2018.12.3
- Phantom: SAM2; Type: SAM; Serial: TP-1503
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

Ch18900/Area Scan (71x71x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.731 W/kg

Ch18900/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 6.370 V/m; Power Drift = -0.06 dB
Peak SAR (extrapolated) = 0.866 W/kg
SAR(1 g) = 0.528 W/kg; SAR(10 g) = 0.307 W/kg
Maximum value of SAR (measured) = 0.750 W/kg

0 dB = 0.750 W/kg = -1.25 dBW/kg

38_LTE Band 7-LAT_20M_QPSK_1RB_0Offset_Bank_15mm_Ch21100

Communication System: UID 0, LTE-FDD (0); Frequency: 2535 MHz;Duty Cycle: 1:1
Medium: MSL_2600 Medium parameters used: f = 2535 MHz; σ = 2.124 S/m; $ε_r$ = 53.138; ρ = 1000 kg/m^3
Ambient Temperature：23.4 ℃；Liquid Temperature：22.9 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN3843; ConvF(6.7, 6.7, 6.7); Calibrated: 2018.9.27
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1338; Calibrated: 2018.12.3
- Phantom: SAM1; Type: SAM; Serial: TP-1839
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

Ch21100/Area Scan (91x81x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm
Maximum value of SAR (interpolated) = 0.456 W/kg

Ch21100/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 2.197 V/m; Power Drift = 0.08 dB
Peak SAR (extrapolated) = 0.667 W/kg
SAR(1 g) = 0.365 W/kg; SAR(10 g) = 0.200 W/kg
Maximum value of SAR (measured) = 0.452 W/kg

0 dB = 0.452 W/kg = -3.45 dBW/kg

39_LTE Band 38-LAT_20M_QPSK_1RB_0Offset_Back_15mm_Ch38000

Communication System: UID 0, LTE-TDD (0); Frequency: 2595 MHz;Duty Cycle: 1:1.59
Medium: MSL_2600 Medium parameters used: f = 2595 MHz; σ = 2.21 S/m; ε_r = 52.93; ρ = 1000 kg/m^3
Ambient Temperature：23.4 ℃；Liquid Temperature：22.9 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN3843; ConvF(6.7, 6.7, 6.7); Calibrated: 2018.9.27
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1338; Calibrated: 2018.12.3
- Phantom: SAM1; Type: SAM; Serial: TP-1839
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

Ch38000/Area Scan (91x91x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm
Maximum value of SAR (interpolated) = 0.362 W/kg

Ch38000/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 2.307 V/m; Power Drift = 0.05 dB
Peak SAR (extrapolated) = 0.454 W/kg
SAR(1 g) = 0.230 W/kg; SAR(10 g) = 0.123 W/kg
Maximum value of SAR (measured) = 0.363 W/kg

0 dB = 0.363 W/kg = -4.40 dBW/kg

40_WLAN2.4GHz_802.11b 1Mbps_Back_15mm_Ant 1_Ch11

Communication System: UID 0, 802.11b (0); Frequency: 2462 MHz;Duty Cycle: 1:1
Medium: MSL_2450 Medium parameters used: f = 2462 MHz; σ = 2.025 S/m; ε_r = 52.245; ρ = 1000 kg/m^3
Ambient Temperature：23.4 ℃；Liquid Temperature：22.8 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN3843; ConvF(6.7, 6.7, 6.7); Calibrated: 2018.9.27
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1338; Calibrated: 2018.12.3
- Phantom: SAM1; Type: SAM; Serial: TP-1839
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

Ch11/Area Scan (91x81x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm
Maximum value of SAR (interpolated) = 0.231 W/kg

Ch11/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 2.935 V/m; Power Drift = 0.01 dB
Peak SAR (extrapolated) = 0.278 W/kg
SAR(1 g) = 0.145 W/kg; SAR(10 g) = 0.077 W/kg
Maximum value of SAR (measured) = 0.226 W/kg

0 dB = 0.226 W/kg = -6.46 dBW/kg

41_WLAN5GHz_802.11a 6Mbps_Back_15mm_Ant 1_Ch56

Communication System: UID 0, 802.11a (0); Frequency: 5280 MHz;Duty Cycle: 1:1.021
Medium: MSL_5000 Medium parameters used: f = 5280 MHz; σ = 5.488 S/m; ε_r = 48.833; ρ = 1000 kg/m^3
Ambient Temperature：23.3 ℃；Liquid Temperature：22.8 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN3857; ConvF(4.4, 4.4, 4.4); Calibrated: 2018.5.31
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1338; Calibrated: 2018.12.3
- Phantom: SAM1; Type: SAM; Serial: TP-1839
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

Ch56/Area Scan (101x81x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Maximum value of SAR (interpolated) = 1.00 W/kg

Ch56/Zoom Scan (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm
Reference Value = 2.702 V/m; Power Drift = -0.06 dB
Peak SAR (extrapolated) = 1.71 W/kg
SAR(1 g) = 0.440 W/kg; SAR(10 g) = 0.159 W/kg
Maximum value of SAR (measured) = 1.01 W/kg

0 dB = 1.00 W/kg = 0.00 dBW/kg

42_WLAN5GHz_802.11a 6Mbps_Back_15mm_Full Power_Ch132

Communication System: UID 0, WIFI (0); Frequency: 5660 MHz;Duty Cycle: 1:1.021
Medium: MSL_5000 Medium parameters used: f = 5660 MHz; σ = 5.994 S/m; ε_r = 48.214; ρ = 1000 kg/m^3
Ambient Temperature：23.3 ℃；Liquid Temperature：22.8 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN3857; ConvF(3.98, 3.98, 3.98); Calibrated: 2018.5.31
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1338; Calibrated: 2018.12.3
- Phantom: SAM1; Type: SAM; Serial: TP-1839
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

Ch132/Area Scan (111x91x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Maximum value of SAR (interpolated) = 1.86 W/kg

Ch132/Zoom Scan (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm
Reference Value = 4.476 V/m; Power Drift = -0.10 dB
Peak SAR (extrapolated) = 3.12 W/kg
SAR(1 g) = 0.790 W/kg; SAR(10 g) = 0.308 W/kg
Maximum value of SAR (measured) = 1.85 W/kg

0 dB = 1.85 W/kg = 2.67 dBW/kg

43_WLAN5GHz_802.11a 6Mbps_Back_15mm_Full Power_Ch161

Communication System: UID 0, WIFI (0); Frequency: 5805 MHz;Duty Cycle: 1:1.021
Medium: MSL_5000 Medium parameters used: f = 5805 MHz; σ = 6.192 S/m; ε$_r$ = 47.995; ρ = 1000 kg/m^3
Ambient Temperature：23.4 ℃；Liquid Temperature：22.6 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN3857; ConvF(4.31, 4.31, 4.31); Calibrated: 2018.5.31
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1338; Calibrated: 2018.12.3
- Phantom: SAM1; Type: SAM; Serial: TP-1839
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

Ch161/Area Scan (111x91x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Maximum value of SAR (interpolated) = 1.14 W/kg

Ch161/Zoom Scan (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm
Reference Value = 3.762 V/m; Power Drift = 0.01 dB
Peak SAR (extrapolated) = 2.04 W/kg
SAR(1 g) = 0.436 W/kg; SAR(10 g) = 0.163 W/kg
Maximum value of SAR (measured) = 1.16 W/kg

0 dB = 1.16 W/kg = 0.64 dBW/kg

44_ Bluetooth_1Mbps_Back_15mm_Ant 1_Ch78

Communication System: UID 0, Bluetooth (0); Frequency: 2480 MHz;Duty Cycle: 1:1.30
Medium: MSL_2450 Medium parameters used: f = 2480 MHz; σ = 2.048 S/m; ε_r = 52.174; ρ = 1000 kg/m^3

Ambient Temperature：23.4 ℃；Liquid Temperature：22.8 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN3843; ConvF(6.7, 6.7, 6.7); Calibrated: 2018.9.27
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1338; Calibrated: 2018.12.3
- Phantom: SAM1; Type: SAM; Serial: TP-1839
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

Ch78/Area Scan (91x81x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm
Maximum value of SAR (interpolated) = 0.0328 W/kg

Ch78/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 0.9480 V/m; Power Drift = 0.02 dB
Peak SAR (extrapolated) = 0.0400 W/kg
SAR(1 g) = 0.022 W/kg; SAR(10 g) = 0.013 W/kg
Maximum value of SAR (measured) = 0.0322 W/kg

0 dB = 0.0322 W/kg = -14.92 dBW/kg

45_GSM1900-LAT_GPRS 4 Tx slots_Bottom Side_0mm_Ch661

Communication System: UID 0, PCS-4UP (0); Frequency: 1880 MHz;Duty Cycle: 1:2.08
Medium: MSL_1900 Medium parameters used: f = 1880 MHz; σ = 1.51 S/m; ε_r = 53.095; ρ = 1000 kg/m^3
Ambient Temperature 23.4 ℃；Liquid Temperature 22.6 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN3843; ConvF(7.07, 7.07, 7.07); Calibrated: 2018.9.27
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1338; Calibrated: 2018.12.3
- Phantom: SAM2; Type: SAM; Serial: TP-1503
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

Ch661/Area Scan (41x61x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 3.40 W/kg

Ch661/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 31.28 V/m; Power Drift = 0.04 dB
Peak SAR (extrapolated) = 5.91 W/kg
SAR(1 g) = 2.67 W/kg; SAR(10 g) = 1.14 W/kg
Maximum value of SAR (measured) = 3.87 W/kg

0 dB = 3.40 W/kg = 5.31 dBW/kg

46_WCDMA IV-LAT_RMC 12.2Kbps_Bottom Side_0mm_Ch1413

Communication System: UID 0, WCDMA (0); Frequency: 1732.6 MHz;Duty Cycle: 1:1
Medium: MSL_1750 Medium parameters used: f = 1732.6 MHz; σ = 1.504 S/m; ε_r = 54.131; ρ = 1000kg/m³
Ambient Temperature：23.2 ℃；Liquid Temperature：22.6 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN3843; ConvF(7.41, 7.41, 7.41); Calibrated: 2018.9.27
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1338; Calibrated: 2018.12.3
- Phantom: SAM2; Type: SAM; Serial: TP-1503
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

Ch1413/Area Scan (71x81x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 4.82 W/kg

Ch1413/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 1.286 V/m; Power Drift = 0.08 dB
Peak SAR (extrapolated) = 12.0 W/kg
SAR(1 g) = 4.66 W/kg; SAR(10 g) = 2.02 W/kg
Maximum value of SAR (measured) = 5.65 W/kg

0 dB = 5.65 W/kg = 7.52 dBW/kg

47_WCDMA II-LAT_RMC 12.2Kbps_Bottom Side_0mm_Ch9400

Communication System: UID 0, WCDMA (0); Frequency: 1880 MHz;Duty Cycle: 1:1
Medium: MSL_1900 Medium parameters used: f = 1880 MHz; σ = 1.514 S/m; ε_r = 52.857; ρ = 1000 kg/m^3
Ambient Temperature：23.4 ℃；Liquid Temperature：22.6 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN3843; ConvF(7.07, 7.07, 7.07); Calibrated: 2018.9.27
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1338; Calibrated: 2018.12.3
- Phantom: SAM2; Type: SAM; Serial: TP-1503
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

Ch9400/Area Scan (71x81x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 5.76 W/kg

Ch9400/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 4.176 V/m; Power Drift = 0.06 dB
Peak SAR (extrapolated) = 10.8 W/kg
SAR(1 g) = 4.99 W/kg; SAR(10 g) = 2.19 W/kg
Maximum value of SAR (measured) = 9.10 W/kg

0 dB = 9.10 W/kg = 9.59 dBW/kg

48_LTE Band 4-LAT_20M_QPSK_50RB_0Offset_Back_0mm_Ch20175

Communication System: UID 0, LTE-FDD (0); Frequency: 1732.5 MHz;Duty Cycle: 1:1
Medium: MSL_1750 Medium parameters used: f = 1732.5 MHz; σ = 1.504 S/m; ε_r = 54.131; ρ = 1000kg/m^3
Ambient Temperature 23.2 ℃；Liquid Temperature 22.6 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN3843; ConvF(7.41, 7.41, 7.41); Calibrated: 2018.9.27
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1338; Calibrated: 2018.12.3
- Phantom: SAM2; Type: SAM; Serial: TP-1503
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

Ch20175/Area Scan (71x81x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 10.3 W/kg

Ch20175/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 5.138 V/m; Power Drift = 0.01 dB
Peak SAR (extrapolated) = 12.3 W/kg
SAR(1 g) = 5.88 W/kg; SAR(10 g) = 2.68 W/kg
Maximum value of SAR (measured) = 10.3 W/kg

0 dB = 10.3 W/kg = 10.13 dBW/kg

49_LTE Band 2-LAT_20M_QPSK_50RB_0Offset_Bottom Side_0mm_Ch18900

Communication System: UID 0, LTE-FDD (0); Frequency: 1880 MHz;Duty Cycle: 1:1
Medium: MSL_1900 Medium parameters used: f = 1880 MHz; σ = 1.51 S/m; ε_r = 53.095; ρ = 1000 kg/m^3
Ambient Temperature　23.4 ℃；Liquid Temperature　22.6 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN3843; ConvF(7.07, 7.07, 7.07); Calibrated: 2018.9.27
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1338; Calibrated: 2018.12.3
- Phantom: SAM2; Type: SAM; Serial: TP-1503
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

Ch18900/Area Scan (41x61x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 6.73 W/kg

Ch18900/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 36.83 V/m; Power Drift = 0.01 dB
Peak SAR (extrapolated) = 12.2 W/kg
SAR(1 g) = 5.03 W/kg; SAR(10 g) = 2.09 W/kg
Maximum value of SAR (measured) = 10.1 W/kg

0 dB = 6.73 W/kg = 8.28 dBW/kg

50_WLAN5GHz_802.11a 6Mbps_Back_0mm_Ant 1_Ch56

Communication System: UID 0, 802.11a (0); Frequency: 5280 MHz;Duty Cycle: 1:1.021
Medium: MSL_5000 Medium parameters used: f = 5280 MHz; σ = 5.488 S/m; ε_r = 48.833; ρ = 1000 kg/m^3

Ambient Temperature：23.3 ℃；Liquid Temperature：22.8 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN3857; ConvF(4.4, 4.4, 4.4); Calibrated: 2018.5.31
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1338; Calibrated: 2018.12.3
- Phantom: SAM1; Type: SAM; Serial: TP-1839
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

Ch56/Area Scan (101x81x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Maximum value of SAR (interpolated) = 10.8 W/kg

Ch56/Zoom Scan (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm
Reference Value = 2.315 V/m; Power Drift = 0.07 dB
Peak SAR (extrapolated) = 25.1 W/kg
SAR(1 g) = 4.28 W/kg; SAR(10 g) = 1.09 W/kg
Maximum value of SAR (measured) = 12.6 W/kg

0 dB = 12.6 W/kg = 11.00 dBW/kg