



# FCC RF Test Report

**APPLICANT** : Xiaomi Communications Co., Ltd.  
**EQUIPMENT** : Mobile Phone  
**BRAND NAME** : MI  
**MODEL NAME** : M1803E6G  
**FCC ID** : 2AFZZ-RMSE6G  
**STANDARD** : FCC Part 15 Subpart C §15.247  
**CLASSIFICATION** : (DTS) Digital Transmission System

The product was received on Feb. 08, 2018 and testing was completed on Mar. 11, 2018. We, Sporton International (Kunshan) Inc., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International (Kunshan) Inc., the test report shall not be reproduced except in full.

Approved by: James Huang / Manager



***Sporton International (Kunshan) Inc.***

***No.3-2 Ping-Xiang Rd, Kunshan Development Zone Kunshan City Jiangsu Province 215335  
China***



## TABLE OF CONTENTS

<b>SUMMARY OF TEST RESULT .....</b>	<b>4</b>
<b>1 GENERAL DESCRIPTION .....</b>	<b>5</b>
1.1 Applicant .....	5
1.2 Manufacturer .....	5
1.3 Product Feature of Equipment Under Test .....	5
1.4 Product Specification of Equipment Under Test .....	5
1.5 Modification of EUT .....	6
1.6 Testing Location .....	6
1.7 Applicable Standards .....	6
<b>2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST .....</b>	<b>7</b>
2.1 Descriptions of Test Mode .....	7
2.2 Test Mode .....	8
2.3 Connection Diagram of Test System .....	9
2.4 Support Unit used in test configuration and system .....	10
2.5 EUT Operation Test Setup .....	10
2.6 Measurement Results Explanation Example .....	10
<b>3 TEST RESULT .....</b>	<b>11</b>
3.1 6dB Bandwidth Measurement .....	11
3.2 Peak Output Power Measurement .....	14
3.3 Power Spectral Density Measurement .....	15
3.4 Conducted Band Edges and Spurious Emission Measurement .....	20
3.5 Radiated Band Edges and Spurious Emission Measurement .....	25
3.6 AC Conducted Emission Measurement .....	29
3.7 Antenna Requirements .....	35
<b>4 LIST OF MEASURING EQUIPMENT .....</b>	<b>36</b>
<b>5 UNCERTAINTY OF EVALUATION .....</b>	<b>37</b>
<b>APPENDIX A. CONDUCTED TEST RESULTS</b>	
<b>APPENDIX B. RADIATED SPURIOUS EMISSION</b>	
<b>APPENDIX C. DUTY CYCLE PLOTS</b>	
<b>APPENDIX D. SETUP PHOTOGRAPHS</b>	



## REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR820819B	Rev. 01	Initial issue of report	Apr. 04, 2018

## SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(2)	6dB Bandwidth	$\geq 0.5\text{MHz}$	Pass	-
3.2	15.247(b)(3)	Peak Output Power	$\leq 30\text{dBm}$	Pass	-
3.3	15.247(e)	Power Spectral Density	$\leq 8\text{dBm}/3\text{kHz}$	Pass	-
3.4	15.247(d)	Conducted Band Edges and Spurious Emission	$\leq 20\text{dBc}$	Pass	-
3.5	15.247(d)	Radiated Band Edges and Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 4.73 dB at 44.550 MHz
3.6	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 6.28 dB at 0.708 MHz
3.7	15.203 & 15.247(b)	Antenna Requirement	N/A	Pass	-



# 1 General Description

## 1.1 Applicant

Xiaomi Communications Co., Ltd.

The Rainbow City of China Resources, NO.68, Qinghe Middle Street, Haidian District, Beijing, China

## 1.2 Manufacturer

Xiaomi Communications Co., Ltd.

The Rainbow City of China Resources, NO.68, Qinghe Middle Street, Haidian District, Beijing, China

## 1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Mobile Phone
Brand Name	MI
Model Name	M1803E6G
FCC ID	2AFZZ-RMSE6G
EUT supports Radios application	GSM/GPRS/EGPRS/WCDMA/HSPA/DC-HSDPA/ HSPA+(16QAM uplink is not supported)/LTE/ WLAN 2.4GHz 802.11b/g/n HT20/ Bluetooth v3.0 + EDR / Bluetooth v4.0 LE / v4.2 LE
IMEI Code	Conducted: 868041030029271/868041030029289 Conduction: 868041030029339/868041030029347 Radiation: 868041030026913/868041030026917
HW Version	P2
SW Version	MIUI 9
EUT Stage	Identical Prototype

### Remark:

1. The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.
2. There are two types of EUT sample 1 and sample 2, the differences between two samples are only for Flash, sample 1 is 3GB+32GB, sample 2 is 4GB+64GB. According to the difference, choose sample 1 to perform full tests.

## 1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx/Rx Frequency Range	2402 MHz ~ 2480 MHz
Number of Channels	40
Carrier Frequency of Each Channel	40 Channel(37 hopping + 3 advertising channel)
Maximum Output Power to Antenna	0.61 dBm (0.0012 W)
Antenna Type / Gain	LDS Antenna with gain -0.98 dBi
Type of Modulation	Bluetooth LE : GFSK



## 1.5 Modification of EUT

No modifications are made to the EUT during all test items.

## 1.6 Testing Location

Sporton International (Kunshan) Inc. is accredited to ISO 17025 by National Voluntary Laboratory Accreditation Program (NVLAP code: 600155-0) and the FCC designation No is CN5013.

<b>Test Site</b>	Sporton International (Kunshan) Inc.			
<b>Test Site Location</b>	No.3-2 Ping-Xiang Rd, Kunshan Development Zone Kunshan City Jiangsu Province 215335 China TEL : +86-512-57900158 FAX : +86-512-57900958			
<b>Test Site No.</b>	<b>Sporton Site No.</b>			<b>FCC Test Firm Registration No.</b>
	TH01-KS	03CH03-KS	CO01-KS	630927

**Note:** The test site complies with ANSI C63.4 2014 requirement.

## 1.7 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.247
- ♦ FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v04
- ♦ ANSI C63.10-2013

**Remark:**

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



## 2 Test Configuration of Equipment Under Test

### 2.1 Descriptions of Test Mode

The RF output power was recorded in the following table:

Channel	Frequency	Bluetooth – LE RF Output Power
		Data Rate / Modulation
		GFSK
		1Mbps
Ch00	2402MHz	-1.41 dBm
Ch19	2440MHz	<b>0.61 dBm</b>
Ch39	2480MHz	-0.58 dBm

- The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction (150 kHz to 30 MHz), radiation (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). Pre-scanned tests, X, Y, Z in three orthogonal panels to determine the final configuration (Z plane as worst plane) from all possible combinations.
- AC power line Conducted Emission was tested under maximum output power.

## 2.2 Test Mode


The following summary table is showing all test modes to demonstrate in compliance with the standard.

Summary table of Test Cases	
Test Item	Data Rate / Modulation
	Bluetooth – LE / GFSK
Conducted TCs	Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps
	Mode 2: Bluetooth Tx CH19_2440 MHz_1Mbps
	Mode 3: Bluetooth Tx CH39_2480 MHz_1Mbps
Radiated TCs	Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps
	Mode 2: Bluetooth Tx CH19_2440 MHz_1Mbps
	Mode 3: Bluetooth Tx CH39_2480 MHz_1Mbps
AC Conducted Emission	Mode 1 : GSM850 Idle + Bluetooth Link + WLAN Link + USB Cable 1 (Charging from Adapter 1)
	Mode 2 GSM850 Idle + Bluetooth Link + WLAN Link + USB Cable 2 (Charging from Adapter 2)




## 2.3 Connection Diagram of Test System

### <Bluetooth LE Tx Mode>



### <AC Conducted Emission Mode>



## 2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	Anritsu	MT8820C	N/A	N/A	Unshielded, 1.8 m
2.	BT Base Station	R&S	CBT	N/A	N/A	Unshielded, 1.8 m
3.	WLAN AP	D-Link	DIR-855	KA2DIR855A2	N/A	Unshielded, 1.8m
4.	Notebook	Lenovo	G480	PRC4	N/A	AC I/P: Unshielded, 1.8m DC O/P: Shielded, 1.8 m
5.	Bluetooth Earphone	Lenovo	LBH308	N/A	N/A	N/A
6.	SD Card	Kingston	8GB	N/A	N/A	N/A
7.	Earphone	Lenovo	SH100	N/A	N/A	N/A

## 2.5 EUT Operation Test Setup

For Bluetooth LE function, the engineering test program was provided and enabled to make EUT continuous transmit/receive.

For AC power line conducted emissions, the EUT was set to connect with the WLAN AP under large package sizes transmission.

## 2.6 Measurement Results Explanation Example

### For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example:

The spectrum analyzer offset is derived from RF cable loss.

*Offset = RF cable loss.*

Following shows an offset computation example with cable loss 5.4 dB.

*Offset(dB) = RF cable loss(dB).*

*= 5.4 (dB)*

### 3 Test Result

#### 3.1 6dB Bandwidth Measurement

##### 3.1.1 Limit of 6dB Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.

##### 3.1.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

##### 3.1.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v04.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
5. Measure and record the results in the test report.

##### 3.1.4 Test Setup






### 3.1.5 Test Result of 6dB Bandwidth

Test data refer to Appendix A.


6 dB Bandwidth Plot on Channel 00



Date: 2 MAR 2018 22:18:31




### 6 dB Bandwidth Plot on Channel 19



Date: 2.MAR.2018 22:22:17

### 6 dB Bandwidth Plot on Channel 39



Date: 2.MAR.2018 22:25:11

## 3.2 Peak Output Power Measurement

### 3.2.1 Limit of Peak Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. If transmitting antenna of directional gain greater than 6dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.


### 3.2.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

### 3.2.3 Test Procedures

1. The testing follows the Measurement Procedure of FCC KDB No. 558074 DTS D01 Meas. Guidance v04 section 9.1.2 PKPM1 Peak power meter method.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power and record the results in the test report.

### 3.2.4 Test Setup



### 3.2.5 Test Result of Peak Output Power

Test data refers to Appendix A.

### 3.3 Power Spectral Density Measurement

#### 3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.

#### 3.3.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

#### 3.3.3 Test Procedures

1. The testing follows Measurement Procedure 10.2 Method PKPSD of FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v04
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.
7. The Measured power density (dBm)/ 100kHz is a reference level and used as 20dBc down limit line for Conducted Band Edges and Conducted Spurious Emission.

#### 3.3.4 Test Setup






### 3.3.5 Test Result of Power Spectral Density

Test data refers to Appendix A.

### 3.3.6 Test Result of Power Spectral Density Plots (100kHz)

PSD 100kHz Plot on Channel 00




Date: 2.MAR.2018 22:19:02






PSD 100kHz Plot on Channel 19



Date: 2 MAR 2018 22:22:44

PSD 100kHz Plot on Channel 39




Date: 2 MAR 2018 22:25:52




### 3.3.7 Test Result of Power Spectral Density Plots (3kHz)

PSD 3kHz Plot on Channel 00




Date: 2 MAR 2018 22:18:49

### PSD 3kHz Plot on Channel 19



Date: 2.MAR.2018 22:22:33

### PSD 3kHz Plot on Channel 39



Date: 2.MAR.2018 22:25:40

### 3.4 Conducted Band Edges and Spurious Emission Measurement

#### 3.4.1 Limit of Conducted Band Edges and Spurious Emission

All harmonics/spurious must be at least 20 dB down from the highest emission level within the authorized band.


#### 3.4.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

#### 3.4.3 Test Procedure


1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v04.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

#### 3.4.4 Test Setup




### 3.4.5 Test Result of Conducted Band Edges Plots

**Low Band Edge Plot on Channel 00**



Date: 2.MAR.2018 22:19:21


**High Band Edge Plot on Channel 39**



Date: 2.MAR.2018 22:26:02


### 3.4.6 Test Result of Conducted Spurious Emission Plots

#### Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 00



Date: 2.MAR.2018 22:20:29


#### Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 00



Date: 2.MAR.2018 22:20:14




Conducted Spurious Emission Plot on Bluetooth LE 1Mbps  
GFSK Channel 19



Date: 2 MAR 2018 22:23:35


Conducted Spurious Emission Plot on Bluetooth LE 1Mbps  
GFSK Channel 19



Date: 2 MAR 2018 22:23:18




Conducted Spurious Emission Plot on Bluetooth LE 1Mbps  
GFSK Channel 39



Date: 2 MAR 2018 22:26:55

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps  
GFSK Channel 39



Date: 2 MAR 2018 22:26:34



### 3.5 Radiated Band Edges and Spurious Emission Measurement

#### 3.5.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

#### 3.5.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

### 3.5.3 Test Procedures


1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v04.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
7. Use the following spectrum analyzer settings:
  - (1) Span shall wide enough to fully capture the emission being measured;
  - (2) Set RBW=100 kHz for  $f < 1$  GHz; VBW  $\geq$  RBW; Sweep = auto; Detector function = peak; Trace = max hold;
  - (3) Set RBW = 1 MHz, VBW= 3MHz for  $f \geq 1$  GHz for peak measurement.

For average measurement:


    - VBW = 10 Hz, when duty cycle is no less than 98 percent.
    - VBW  $\geq 1/T$ , when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

### 3.5.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



### 3.5.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

### 3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix B.

### 3.5.7 Duty Cycle

Please refer to Appendix C.

### 3.5.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix B.

### 3.6 AC Conducted Emission Measurement

#### 3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dB $\mu$ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\*Decreases with the logarithm of the frequency.


#### 3.6.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

#### 3.6.3 Test Procedures


1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

### 3.6.4 Test Setup



### 3.6.5 Test Result of AC Conducted Emission

Test Mode :	Mode 2	Temperature :	21~23℃
Test Engineer :	Amos Zhang	Relative Humidity :	42~44%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	GSM850 Idle + Bluetooth Link + WLAN Link + USB Cable 2 (Charging from Adapter 2)		




Site : CO01-KS  
Condition : FCC PART 15C LISN-L-171013-060103 LINE  
mode : Mode 2  
: 868041030029339/868041030029347 #7

	Freq	Level	Over	Limit	Read	LISN	Cable	
	MHz	dBuV	Limit	Line	Level	Factor	Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.166	49.23	-15.93	65.16	38.50	0.17	10.56	QP
2	0.166	34.03	-21.13	55.16	23.30	0.17	10.56	Average
3	0.452	45.21	-11.64	56.85	34.61	0.25	10.35	QP
4	0.452	36.21	-10.64	46.85	25.61	0.25	10.35	Average
5	0.579	46.10	-9.90	56.00	35.60	0.26	10.24	QP
6	0.579	38.00	-8.00	46.00	27.50	0.26	10.24	Average
7	0.672	44.04	-11.96	56.00	33.60	0.26	10.18	QP
8	0.672	33.74	-12.26	46.00	23.30	0.26	10.18	Average
9	0.708	47.32	-8.68	56.00	36.90	0.26	10.16	QP
10 *	0.708	39.72	-6.28	46.00	29.30	0.26	10.16	Average
11	0.771	43.58	-12.42	56.00	33.20	0.26	10.12	QP
12	0.771	34.58	-11.42	46.00	24.20	0.26	10.12	Average
13	1.418	40.73	-15.27	56.00	30.30	0.27	10.16	QP
14	1.418	31.93	-14.07	46.00	21.50	0.27	10.16	Average
15	3.399	37.11	-18.89	56.00	26.60	0.33	10.18	QP
16	3.399	26.81	-19.19	46.00	16.30	0.33	10.18	Average
17	15.801	46.87	-13.13	60.00	36.19	0.25	10.43	QP



<b>Test Mode :</b>	Mode 2	<b>Temperature :</b>	21~23℃
<b>Test Engineer :</b>	Amos Zhang	<b>Relative Humidity :</b>	42~44%
<b>Test Voltage :</b>	120Vac / 60Hz	<b>Phase :</b>	Line
<b>Function Type :</b>	GSM850 Idle + Bluetooth Link + WLAN Link + USB Cable 2 (Charging from Adapter 2)		




Site : CO01-KS  
Condition : FCC PART 15C LISN-L-171013-060103 LINE  
mode : Mode 2  
: 868041030029339/868041030029347 #7

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
18	15.801	34.57	-15.43	50.00	23.89	0.25	10.43	Average
19	16.661	48.17	-11.83	60.00	37.50	0.23	10.44	QP
20	16.661	36.17	-13.83	50.00	25.50	0.23	10.44	Average
21	18.039	51.77	-8.23	60.00	41.10	0.21	10.46	QP
22	18.039	38.77	-11.23	50.00	28.10	0.21	10.46	Average
23	18.820	51.26	-8.74	60.00	40.60	0.20	10.46	QP
24	18.820	38.96	-11.04	50.00	28.30	0.20	10.46	Average
25	19.635	50.56	-9.44	60.00	39.90	0.18	10.48	QP
26	19.635	38.26	-11.74	50.00	27.60	0.18	10.48	Average
27	20.377	48.48	-11.52	60.00	37.79	0.20	10.49	QP
28	20.377	37.28	-12.72	50.00	26.59	0.20	10.49	Average
29	21.373	45.66	-14.34	60.00	34.91	0.24	10.51	QP
30	21.373	36.36	-13.64	50.00	25.61	0.24	10.51	Average





Test Mode :	Mode 2	Temperature :	21~23℃
Test Engineer :	Amos Zhang	Relative Humidity :	42~44%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	GSM850 Idle + Bluetooth Link + WLAN Link + USB Cable 2 (Charging from Adapter 2)		




Site : CO01-KS  
Condition : FCC PART 15C LISN-N-171013-060103 NEUTRAL

mode : Mode 2  
: 868041030029339/868041030029347 #7

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.156	56.47	-9.18	65.65	45.60	0.28	10.59	QP
2	0.156	39.07	-16.58	55.65	28.20	0.28	10.59	Average
3	0.164	55.35	-9.90	65.25	44.50	0.28	10.57	QP
4	0.164	38.95	-16.30	55.25	28.10	0.28	10.57	Average
5	0.189	55.37	-8.69	64.06	44.60	0.28	10.49	QP
6	0.189	39.37	-14.69	54.06	28.60	0.28	10.49	Average
7	0.203	51.33	-12.16	63.49	40.60	0.28	10.45	QP
8	0.203	34.63	-18.86	53.49	23.90	0.28	10.45	Average
9	0.221	48.33	-14.46	62.79	37.60	0.28	10.45	QP
10	0.221	32.03	-20.76	52.79	21.30	0.28	10.45	Average
11	0.262	47.92	-13.46	61.38	37.20	0.28	10.44	QP
12	0.262	32.32	-19.06	51.38	21.60	0.28	10.44	Average
13	0.323	47.31	-12.31	59.62	36.60	0.29	10.42	QP
14	0.323	36.31	-13.31	49.62	25.60	0.29	10.42	Average
15	0.389	44.30	-13.78	58.08	33.60	0.29	10.41	QP
16	0.389	34.20	-13.88	48.08	23.50	0.29	10.41	Average
17	0.449	42.14	-14.75	56.89	31.49	0.29	10.36	QP



<b>Test Mode :</b>	Mode 2	<b>Temperature :</b>	21~23℃
<b>Test Engineer :</b>	Amos Zhang	<b>Relative Humidity :</b>	42~44%
<b>Test Voltage :</b>	120Vac / 60Hz	<b>Phase :</b>	Neutral
<b>Function Type :</b>	GSM850 Idle + Bluetooth Link + WLAN Link + USB Cable 2 (Charging from Adapter 2)		



Site : CO01-KS  
 Condition : FCC PART 15C LISN-N-171013-060103 NEUTRAL  
 mode : Mode 2  
 : 868041030029339/868041030029347 #7

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
18	0.449	35.14	-11.75	46.89	24.49	0.29	10.36	Average
19	0.582	43.73	-12.27	56.00	33.20	0.29	10.24	QP
20 *	0.582	38.73	-7.27	46.00	28.20	0.29	10.24	Average
21	0.705	44.36	-11.64	56.00	33.90	0.30	10.16	QP
22	0.705	38.56	-7.44	46.00	28.10	0.30	10.16	Average
23	1.043	39.02	-16.98	56.00	28.60	0.31	10.11	QP
24	1.043	31.92	-14.08	46.00	21.50	0.31	10.11	Average
25	1.289	41.06	-14.94	56.00	30.60	0.31	10.15	QP
26	1.289	32.06	-13.94	46.00	21.60	0.31	10.15	Average
27	17.661	43.20	-16.80	60.00	32.60	0.15	10.45	QP
28	17.661	32.20	-17.80	50.00	21.60	0.15	10.45	Average
29	19.021	44.09	-15.91	60.00	33.49	0.13	10.47	QP
30	19.021	33.49	-16.51	50.00	22.89	0.13	10.47	Average
31	22.775	42.28	-17.72	60.00	31.50	0.23	10.55	QP
32	22.775	34.68	-15.32	50.00	23.90	0.23	10.55	Average



## **3.7 Antenna Requirements**

### **3.7.1 Standard Applicable**

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

### **3.7.2 Antenna Anti-Replacement Construction**

The EUT is designed with SMA connector, connected with external Monopole antenna. And the EUT is professionally installed in the Vending Machine.

### **3.7.3 Antenna Gain**

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



## 4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101040	10Hz~40GHz	Aug. 08, 2017	Feb. 28, 2018~ Mar. 02, 2018	Aug. 07, 2018	Conducted (TH01-KS)
Pulse Power Sensor	Anritsu	MA2411B	0917070	300MHz~40GHz	Jan. 18, 2018	Feb. 28, 2018~ Mar. 02, 2018	Jan. 17, 2019	Conducted (TH01-KS)
Power Meter	Anritsu	ML2495A	1005002	50MHz Bandwidth	Jan. 18, 2018	Feb. 28, 2018~ Mar. 02, 2018	Jan. 17, 2019	Conducted (TH01-KS)
EMI Test Receiver	Keysight	N9038A	MY56400004	3Hz~8.5GHz; Max 30dBm	Oct. 19, 2017	Feb. 28, 2018~ Mar. 11, 2018	Oct. 18, 2018	Radiation (03CH03-KS)
EXA Spectrum Analyzer	Keysight	N9010A	MY55150244	10Hz~44GHz	Apr. 18, 2017	Feb. 28, 2018~ Mar. 11, 2018	Apr. 17, 2018	Radiation (03CH03-KS)
Loop Antenna	R&S	HFH2-Z2	100321	9kHz~30MHz	Oct. 22, 2017	Feb. 28, 2018~ Mar. 11, 2018	Oct. 21, 2018	Radiation (03CH03-KS)
Bilog Antenna	TeseQ	CBL6112D	35406	25MHz~2GHz	Apr. 22, 2017	Feb. 28, 2018~ Mar. 11, 2018	Apr. 21, 2018	Radiation (03CH03-KS)
Horn Antenna	Schwarzbeck	BBHA9120D	9120D-1356	1GHz~18GHz	Apr. 22, 2017	Feb. 28, 2018~ Mar. 11, 2018	Apr. 21, 2018	Radiation (03CH03-KS)
SHF-EHF Horn	Schwarzbeck	BBHA 9170	BBHA170249	15GHz~40GHz	Oct. 07, 2018	Feb. 28, 2018~ Mar. 11, 2018	Oct. 06, 2019	Radiation (03CH03-KS)
Amplifier	com-power	PA-103A	161069	1MHz ~1000MHz / 32 dB	Apr. 18, 2017	Feb. 28, 2018~ Mar. 11, 2018	Apr. 17, 2018	Radiation (03CH03-KS)
Amplifier	MITEQ	TTA1840-35-HG	1887435	18~40GHz	Oct. 12, 2017	Feb. 28, 2018~ Mar. 11, 2018	Oct. 11, 2018	Radiation (03CH03-KS)
high gain Amplifier	MITEQ	AMF-7D-0010 1800-30-10P	2025788	1Ghz-18Ghz	Apr. 18, 2017	Feb. 28, 2018~ Mar. 11, 2018	Apr. 17, 2018	Radiation (03CH03-KS)
Amplifier	Agilent	8449B	3008A02370	1GHz~26.5GHz	Oct. 12, 2017	Feb. 28, 2018~ Mar. 11, 2018	Oct. 11, 2018	Radiation (03CH03-KS)
AC Power Source	Chroma	61601	F104090004	N/A	NCR	Feb. 28, 2018~ Mar. 11, 2018	NCR	Radiation (03CH03-KS)
Turn Table	ChamPro	EM 1000-T	060762-T	0~360 degree	NCR	Feb. 28, 2018~ Mar. 11, 2018	NCR	Radiation (03CH03-KS)
Antenna Mast	ChamPro	EM 1000-A	060762-A	1 m~4 m	NCR	Feb. 28, 2018~ Mar. 11, 2018	NCR	Radiation (03CH03-KS)
EMI Receiver	R&S	ESCI7	100768	9kHz~7GHz;	Apr. 20, 2017	Mar. 07, 2018	Apr. 19, 2018	Conduction (CO01-KS)
AC LISN	MessTec	AN3016	060103	9kHz~30MHz	Oct. 13, 2017	Mar. 07, 2018	Oct. 12, 2018	Conduction (CO01-KS)
AC LISN (for auxiliary equipment)	MessTec	AN3016	060105	9kHz~30MHz	Oct. 13, 2017	Mar. 07, 2018	Oct. 12, 2018	Conduction (CO01-KS)
AC Power Source	Chroma	61602	ABP000000811	AC 0V~300V, 45Hz~1000Hz	Oct. 12, 2017	Mar. 07, 2018	Oct. 11, 2018	Conduction (CO01-KS)

NCR: No Calibration Required

## 5 Uncertainty of Evaluation

### Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2U_c(y)$ )	2.3dB
--	-------

### Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2U_c(y)$ )	4.6dB
--	-------

### Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2U_c(y)$ )	4.5dB
--	-------

### Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2U_c(y)$ )	4.5dB
--	-------



## **Appendix A. Conducted Test Results**

**Bluetooth Low Energy**

Test Engineer:	Silent Hai	Temperature:	21~25	°C
Test Date:	2018/02/28~2018/03/02	Relative Humidity:	51~55	%

**TEST RESULTS DATA****6dB and 99% Occupied Bandwidth**

Mod.	Data Rate	NTx	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
BLE	1Mbps	1	0	2402	1.05	0.68	0.50	Pass
BLE	1Mbps	1	19	2440	1.05	0.68	0.50	Pass
BLE	1Mbps	1	39	2480	1.05	0.68	0.50	Pass

**TEST RESULTS DATA****Peak Power Table**

Mod.	Data Rate	NTx	CH.	Freq. (MHz)	Peak Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
BLE	1Mbps	1	0	2402	-1.41	30.00	-0.98	-2.39	36.00	Pass
BLE	1Mbps	1	19	2440	0.61	30.00	-0.98	-0.37	36.00	Pass
BLE	1Mbps	1	39	2480	-0.58	30.00	-0.98	-1.56	36.00	Pass

**TEST RESULTS DATA****Average Power Table**  
**(Reporting Only)**

Mod.	Data Rate	NTx	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power (dBm)
BLE	1Mbps	1	0	2402	2.03	-1.86
BLE	1Mbps	1	19	2440	2.03	0.22
BLE	1Mbps	1	39	2480	2.03	-0.88

**TEST RESULTS DATA****Peak Power Density**

Mod.	Data Rate	NTx	CH.	Freq. (MHz)	Peak PSD (dBm /100kHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
BLE	1Mbps	1	0	2402	-2.30	-17.01	-0.98	8.00	Pass
BLE	1Mbps	1	19	2440	-0.33	-15.06	-0.98	8.00	Pass
BLE	1Mbps	1	39	2480	-1.37	-16.08	-0.98	8.00	Pass

Note: PSD (dBm/ 100kHz) is a reference level used for Conducted Band Edges and Conducted Spurious Emission 20dBc limit.



## Appendix B. Radiated Spurious Emission

2.4GHz 2400~2483.5MHz

BLE (Band Edge @ 3m)

BLE	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	( P/A )	( H/V )
BLE CH 00 2402MHz		2345.88	52.41	-21.59	74	49.74	31.22	5.59	34.14	100	138	P	H
		2357.06	42.65	-11.35	54	39.93	31.25	5.61	34.14	100	138	A	H
	*	2402	90.94	-	-	88.13	31.3	5.65	34.14	100	138	P	H
	*	2402	90.26	-	-	87.45	31.3	5.65	34.14	100	138	A	H
		2379.55	52.41	-21.59	74	49.65	31.27	5.63	34.14	109	110	P	V
		2371.36	42.71	-11.29	54	39.95	31.27	5.63	34.14	109	110	A	V
	*	2402	92.95	-	-	90.14	31.3	5.65	34.14	109	110	P	V
	*	2402	92.3	-	-	89.49	31.3	5.65	34.14	109	110	A	V
BLE CH 19 2440MHz		2379.42	52.96	-21.04	74	50.2	31.27	5.63	34.14	105	143	P	H
		2380.72	42.7	-11.3	54	39.94	31.27	5.63	34.14	105	143	A	H
		2440	93.52	-	-	90.64	31.39	5.71	34.22	105	143	P	H
		2440	92.9	-	-	90.02	31.39	5.71	34.22	105	143	A	H
		2491.18	52.64	-21.36	74	49.7	31.47	5.77	34.3	105	143	P	H
		2487.4	42.74	-11.26	54	39.83	31.44	5.75	34.28	105	143	A	H
		2341.85	52.08	-21.92	74	49.41	31.22	5.59	34.14	100	109	P	V
		2373.96	42.82	-11.18	54	40.06	31.27	5.63	34.14	100	109	A	V
		2440	93.34	-	-	90.46	31.39	5.71	34.22	100	109	P	V
		2440	92.8	-	-	89.92	31.39	5.71	34.22	100	109	A	V
		2495.44	52.31	-21.69	74	49.37	31.47	5.77	34.3	100	109	P	V
		2489.44	42.81	-11.19	54	39.87	31.47	5.77	34.3	100	109	A	V





<b>BLE CH 39 2480MHz</b>		2480	93.7	-	-	90.79	31.44	5.75	34.28	105	143	P	H
		2480	92.96	-	-	90.05	31.44	5.75	34.28	105	143	A	H
		2499.1	52.61	-21.39	74	49.67	31.47	5.77	34.3	105	143	P	H
		2483.5	43.01	-10.99	54	40.1	31.44	5.75	34.28	105	143	A	H
		2480	92.88	-	-	89.97	31.44	5.75	34.28	100	72	P	V
		2480	91.82	-	-	88.91	31.44	5.75	34.28	100	72	A	V
		2489.2	53.1	-20.9	74	50.16	31.47	5.77	34.3	100	72	P	V
		2491.6	43.03	-10.97	54	40.09	31.47	5.77	34.3	100	72	A	V
<b>Remark</b>	<ol style="list-style-type: none"><li>1. No other spurious found.</li><li>2. All results are PASS against Peak and Average limit line.</li></ol>												



## 2.4GHz 2400~2483.5MHz

## BLE (Harmonic @ 3m)

BLE	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB/m )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. ( P/A )	Pol. ( H/V )
BLE CH 00 2402MHz		4806	44.54	-29.46	74	62.39	35.66	7.84	61.35	100	360	P	H
		4806	45.53	-28.47	74	63.38	35.66	7.84	61.35	100	360	P	V
BLE CH 19 2440MHz		4878	43.27	-30.73	74	60.96	35.61	7.9	61.2	100	360	P	H
		7320	42.07	-31.93	74	59.77	35.9	9.51	63.11	100	360	P	H
		4878	44.18	-29.82	74	61.87	35.61	7.9	61.2	100	360	P	V
		7320	41.72	-32.28	74	59.42	35.9	9.51	63.11	100	360	P	V
BLE CH 39 2480MHz		4962	44.64	-29.36	74	62.14	35.54	7.97	61.01	100	360	P	H
		7440	41.73	-32.27	74	59.41	35.97	9.57	63.22	100	360	P	H
		4962	44.22	-29.78	74	61.72	35.54	7.97	61.01	100	360	P	V
		7440	41.91	-32.09	74	59.59	35.97	9.57	63.22	100	360	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



## Emission below 1GHz

## 2.4GHz BLE (LF)

BLE	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	( P/A )	( H/V )
2.4GHz BLE LF		30	22.15	-17.85	40	26.38	26.3	0.57	31.1	100	300	P	H
		44.55	18.63	-21.37	40	31.51	17.8	0.72	31.4	-	-	P	H
		164.83	16.09	-27.41	43.5	28.82	16.83	1.4	30.96	-	-	P	H
		310.33	18.99	-27.01	46	28.62	19.94	1.93	31.5	-	-	P	H
		692.51	26.14	-19.86	46	27.34	26.72	2.93	30.85	-	-	P	H
		737.13	27.24	-18.76	46	27.88	27.17	3.02	30.83	-	-	P	H
		32.91	35.25	-4.75	40	41.06	24.62	0.61	31.04	-	-	P	V
		44.55	35.27	-4.73	40	48.15	17.8	0.72	31.4	100	230	P	V
		98.87	16.97	-26.53	43.5	28.92	17.7	1.07	30.72	-	-	P	V
		120.21	16.97	-26.53	43.5	28.93	17.6	1.22	30.78	-	-	P	V
		252.13	18.61	-27.39	46	30.12	17.97	1.73	31.21	-	-	P	V
		734.22	27.04	-18.96	46	27.71	27.14	3.02	30.83	-	-	P	V
Remark	1. No other spurious found. 2. All results are PASS against limit line.												

**Note symbol**

*	<b>Fundamental Frequency</b> which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is <b>over limit</b> line.
P/A	<b>P</b> eak or <b>A</b> verage
H/V	<b>H</b> orizontal or <b>V</b> ertical



A calculation example for radiated spurious emission is shown as below:

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1+2		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	( P/A )	( H/V )
802.11b		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
CH 01													
2412MHz		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

1. Level(dBμV/m) =

Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

2. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

**For Peak Limit @ 2390MHz:**

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)

= 55.45 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 55.45(dBμV/m) – 74(dBμV/m)

= -18.55(dB)

**For Average Limit @ 2390MHz:**

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)

= 43.54 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 43.54(dBμV/m) – 54(dBμV/m)


= -10.46(dB)

**Both peak and average measured complies with the limit line, so test result is “PASS”.**

## Appendix C. Duty Cycle Plots

Band	Duty Cycle(%)	T(ms)	1/T(kHz)	VBW Setting
Bluetooth LE	62.59	0.393	2.546	3kHz

### Bluetooth LE



Date: 28.FEB.2018 17:37:45