

FCC TEST REPORT
for
Shenzhen Skylark Audio Industry Co., Ltd.

Levitating Speaker
Model No.: F1, F18, F28, F68, F88, F98

Prepared for : Shenzhen Skylark Audio Industry Co., Ltd.
Address : 3rd Floor, Liyuan Building, No.177 Longcheng Avenue,
Longgang District, Shenzhen City, Guangdong Province, China

Prepared By : Shenzhen Anbotek Compliance Laboratory Limited
Address : 1/F., Building 1, SEC Industrial Park, No.0409 Qianhai Road,
Nanshan District, Shenzhen, Guangdong, China
Tel: (86) 755-26066544
Fax: (86) 755-26014772

Report Number : R011511317U
Date of Test : Nov. 11~ Dec. 29, 2015
Date of Report : Dec. 30, 2015

TABLE OF CONTENTS

Description

Page

Test Report

1. GENERAL INFORMATION.....	4
1.1. Description of Device (EUT).....	4
1.2. Auxiliary Equipment Used during Test.....	5
1.3. Description of Test Facility.....	5
1.4. Measurement Uncertainty.....	5
2. TEST PROCEDURE.....	6
3. Conducted Emission Test.....	7
3.1. Block Diagram of Test Setup.....	7
3.2. Power Line Conducted Emission Measurement Limits (15.207).....	7
3.3. Configuration of EUT on Measurement.....	7
3.4. Operating Condition of EUT.....	7
3.5. Test Procedure.....	8
3.6. Test equipment.....	8
3.7. Power Line Conducted Emission Measurement Results.....	8
4. RADIATION INTERFERENCE.....	13
4.1. Requirements (15.249, 15.209):.....	13
4.2. Test Procedure.....	13
4.3 Test Equipment.....	14
4.4. Test Results.....	14
5. BANDEDGE.....	18
5.1. Requirements (15.249):.....	18
5.2. Test Procedure.....	18
5.3. Test Configuration:.....	18
5.4. Test Results.....	19
6. OCCUPIED BANDWIDTH.....	24
6.1. Requirements :.....	24
6.2. Test SET-UP.....	24
6.3 Test Equipment.....	24
6.4. Test Results.....	24
7. ANTENNA APPLICATION.....	26
7.1. Antenna requirement.....	26
7.2. Result.....	26
8. PHOTOGRAPH.....	27
8.1 Photo of Conducted Emission Test.....	27
8.2 Photo of Radiation Emission Test.....	27

TEST REPORT

Applicant : Shenzhen Skylark Audio Industry Co., Ltd.
Manufacturer : Shenzhen Skylark Audio Industry Co., Ltd.
EUT : Levitating Speaker
Model No. : F1, F18, F28, F68, F88, F98
Serial No. : N.A.
Trade Mark : N.A.
Rating : DC 5V, 1A

Measurement Procedure Used:

FCC Part15 Subpart C 2015, Paragraph 15.207, 15.249 & 15.209

The device described above is tested by Shenzhen Anbotek Compliance Laboratory Limited to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. The measurement results are contained in this test report and Shenzhen Anbotek Compliance Laboratory Limited is assumed full of responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT (Equipment Under Test) is technically compliant with the FCC Part 15 Subpart C requirements.

This report applies to above tested sample only and shall not be reproduced in part without written approval of Shenzhen Anbotek Compliance Laboratory Limited.

Date of Test : Nov. 11~ Dec. 29, 2015

Prepared by :

Kebo Zhang

(Tested Engineer / Kebo Zhang)

Reviewer :

Amy Ding

(Project Manager / Amy Ding)

Approved & Authorized Signer :

Tom Chen

(Manager / Tom Chen)

1. GENERAL INFORMATION

1.1. Description of Device (EUT)

EUT	: Levitating Speaker
Model Number	: F1, F18, F28, F68, F88, F98 (Note: All samples are the same except the model number and colour, so we prepare “F1” for test only.)
Test Power Supply	: AC 120V, 60Hz for Levitating Base USB Port/ AC 240V, 60Hz for Levitating Base USB Port/ DC 3.7V Battery inside
Frequency	: 2438MHz
No. of Channels	: 1
Antenna Specification	: Integrated: 0 dBi
Applicant Address	: Shenzhen Skylark Audio Industry Co., Ltd. 3rd Floor, Liyuan Building, No.177 Longcheng Avenue, Longgang District, Shenzhen City, Guangdong Province, China
Manufacturer Address	: Shenzhen Skylark Audio Industry Co., Ltd. 3rd Floor, Liyuan Building, No.177 Longcheng Avenue, Longgang District, Shenzhen City, Guangdong Province, China
Factory Address	: Shenzhen Skylark Audio Industry Co., Ltd. 3rd Floor, Liyuan Building, No.177 Longcheng Avenue, Longgang District, Shenzhen City, Guangdong Province, China
Date of receipt	: Nov. 11, 2015
Date of Test	: Nov. 11~ Dec. 29, 2015

1.2. Auxiliary Equipment Used during Test

Levitating Base	:	F1
Adapter	:	Model: MYX-1202500 Input: AC 100-240V, 50/60Hz, 1.2A Output: DC 12V, 2500mA

1.3. Description of Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

FCC-Registration No.: 752021

Shenzhen Anbotek Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 752021, July 10, 2013.

IC-Registration No.: 8058A-1

Shenzhen Anbotek Compliance Laboratory Limited., EMC Laboratory has been registered and fully described in a report filed with the (IC) Industry Canada. The acceptance letter from the IC is maintained in our files. Registration 8058A-1, February 22, 2013.

Test Location

All Emissions tests were performed at
Shenzhen Anbotek Compliance Laboratory Limited. at 1/F., Building 1, SEC
Industrial Park, No.0409 Qianhai Road, Nanshan District, Shenzhen, Guangdong,
China

1.4. Measurement Uncertainty

Radiation Uncertainty	:	Ur = 4.1 dB (Horizontal) Ur = 4.3 dB (Vertical)
Conduction Uncertainty	:	Uc = 3.4dB

2. Test Procedure

GENERAL: This report shall NOT be reproduced except in full without the written approval of Shenzhen Anbotek Compliance Laboratory Limited. The EUT was transmitting a test signal during the testing.

RADIATION INTERFERENCE: The test procedure used was ANSI STANDARD C63.10-2013 using a spectrum analyzer with a pre-selector. The analyzer was calibrated in dB above a microvolt at the output of the antenna. The resolution bandwidth was 100KHz and the video bandwidth was 300KHz up to 1.0GHz and 1.0MHz with a video BW of 3.0MHz above 1.0GHz. The ambient temperature of the EUT was 74.3oF with a humidity of 69%.

FORMULA OF CONVERSION FACTORS: The Field Strength at 3m was established by adding the meter reading of the spectrum analyzer (which is set to read in units of dBuV) to the antenna correction factor supplied by the antenna manufacturer. The antenna correction factors are stated in terms of dB. The gain of the Preselector was accounted for in the Spectrum Analyzer Meter Reading.

Example:

Freq (MHz) METER READING + ACF = FS
20 dBuV + 10.36 dB = 30.36 dBuV/m @ 3m


ANSI STANDARD C63.10-2013 10.1.7 MEASUREMENT PROCEDURES: The EUT was placed on a table 80 cm high and with dimensions of 1m by 1.5m. The EUT was placed in the center of the table (1.5m side). The table used for radiated measurements is capable of continuous rotation.

When an emission was found, the table was rotated to produce the maximum signal strength. At this point, the antenna was raised and lowered from 1m to 4m. The antenna was placed in both the horizontal and vertical planes.

3. Conducted Emission Test

3.1. Block Diagram of Test Setup

3.1.1. Block diagram of connection between the EUT and simulators



3.2. Power Line Conducted Emission Measurement Limits (15.207)

Frequency MHz	Limits dB(μV)	
	Quasi-peak Level	Average Level
0.15 ~ 0.50	66 ~ 56*	56 ~ 46*
0.50 ~ 5.00	56	46
5.00 ~ 30.00	60	50

Notes: 1. *Decreasing linearly with logarithm of frequency.
2. The lower limit shall apply at the transition frequencies.

3.3. Configuration of EUT on Measurement

The following equipments are installed on Power Line Conducted Emission Measurement to meet the commission requirement and operating regulations in a manner which tends to maximize its emission characteristics in a normal application.

3.4. Operating Condition of EUT

- 3.4.1. Setup the EUT and simulator as shown as Section 3.1.
- 3.4.2. Turn on the power of all equipment.
- 3.4.3. Let the EUT work in test mode (Charging) and measure it.

3.5. Test Procedure

The EUT system is connected to the power mains through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm coupling impedance for the EUT system. Please refer the block diagram of the test setup and photographs. Both sides of AC line are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to FCC ANSI C63.10-2013 on Conducted Emission Measurement.

The bandwidth of test receiver (ESCI) set at 9KHz.

The frequency range from 150KHz to 30MHz is checked.

The test results are reported on Section 3.6.

3.6. Test equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Two-Line V-network	Rohde & Schwarz	ENV216	100055	Apr. 17, 2015	1 Year
2.	EMI Test Receiver	Rohde & Schwarz	ESCI	100627	Apr. 17, 2015	1 Year
3.	RF Switching Unit	Compliance Direction	RSU-M2	38303	Apr. 17, 2015	1 Year

3.7. Power Line Conducted Emission Measurement Results


PASS.

The frequency range from 150KHz to 30 MHz is investigated.

Please refer the following pages.

CONDUCTED EMISSION TEST DATA


Test Site: 1# Shielded Room
Operating Condition: Charging
Test Specification: AC 120V, 60Hz for Levitating Base USB Port
Comment: Live Line
Tem.:24℃ Hum.:48%



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit dBuV	Over Limit (dB)	Detector	Remark
1	0.1780	34.23	20.00	54.23	64.57	-10.34	QP	
2	0.1819	22.58	20.00	42.58	54.39	-11.81	AVG	
3	0.2500	17.25	20.00	37.25	51.75	-14.50	AVG	
4	0.2580	32.12	20.00	52.12	61.49	-9.37	QP	
5	0.2980	23.31	20.00	43.31	60.30	-16.99	QP	
6	0.2980	10.23	20.00	30.23	50.30	-20.07	AVG	
7	0.3540	25.26	20.00	45.26	58.87	-13.61	QP	
8	0.3540	8.78	20.00	28.78	48.87	-20.09	AVG	
9	1.1220	18.26	20.00	38.26	56.00	-17.74	QP	
10	1.2020	6.07	20.00	26.07	46.00	-19.93	AVG	
11	1.5420	7.52	20.00	27.52	46.00	-18.48	AVG	
12	1.5859	18.15	20.00	38.15	56.00	-17.85	QP	

CONDUCTED EMISSION TEST DATA


Test Site: 1# Shielded Room
Operating Condition: AC 120V, 60Hz for Levitating Base USB Port
Test Specification: DC 5V for Levitating Base USB Port
Comment: Neutral Line
Tem.:24℃ Hum.:48%



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit dBuV	Over Limit (dB)	Detector	Remark
1	0.1819	34.21	20.00	54.21	64.39	-10.18	QP	
2	0.1900	20.17	20.00	40.17	54.03	-13.86	AVG	
3	0.2460	32.13	20.00	52.13	61.89	-9.76	QP	
4	0.2460	17.98	20.00	37.98	51.89	-13.91	AVG	
5	0.2940	26.18	20.00	46.18	60.41	-14.23	QP	
6	0.2940	11.18	20.00	31.18	50.41	-19.23	AVG	
7	0.3580	25.32	20.00	45.32	58.77	-13.45	QP	
8	0.3580	9.48	20.00	29.48	48.77	-19.29	AVG	
9	0.6540	18.26	20.00	38.26	56.00	-17.74	QP	
10	0.6540	7.36	20.00	27.36	46.00	-18.64	AVG	
11	1.1300	5.63	20.00	25.63	46.00	-20.37	AVG	
12	1.2340	16.33	20.00	36.33	56.00	-19.67	QP	

CONDUCTED EMISSION TEST DATA


Test Site: 1# Shielded Room
Operating Condition: Charging
Test Specification: AC 240V, 60Hz for Levitating Base USB Port
Comment: Live Line
Tem.:24℃ Hum.:48%



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit dBuV	Over Limit (dB)	Detector	Remark
1	0.1819	18.04	20.00	38.04	54.39	-16.35	AVG	
2	0.1860	30.13	20.00	50.13	64.21	-14.08	QP	
3	0.2380	14.19	20.00	34.19	52.16	-17.97	AVG	
4	0.2620	29.26	20.00	49.26	61.36	-12.10	QP	
5	0.2940	28.56	20.00	48.56	60.41	-11.85	QP	
6	0.3060	17.04	20.00	37.04	50.08	-13.04	AVG	
7	0.3820	28.13	20.00	48.13	58.23	-10.10	QP	
8	0.3820	14.80	20.00	34.80	48.23	-13.43	AVG	
9	1.1580	22.13	20.00	42.13	56.00	-13.87	QP	
10	1.1780	11.69	20.00	31.69	46.00	-14.31	AVG	
11	1.9500	10.45	20.00	30.45	46.00	-15.55	AVG	
12	2.0300	19.26	20.00	39.26	56.00	-16.74	QP	

CONDUCTED EMISSION TEST DATA

Test Site: 1# Shielded Room
Operating Condition: AC 240V, 60Hz for Levitating Base USB Port
Test Specification: DC 5V for Levitating Base USB Port
Comment: Neutral Line
Tem.:24℃ Hum.:48%



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit dBuV	Over Limit (dB)	Detector	Remark
1	0.1780	31.26	20.00	51.26	64.57	-13.31	QP	
2	0.1860	18.82	20.00	38.82	54.21	-15.39	AVG	
3	0.2540	15.82	20.00	35.82	51.62	-15.80	AVG	
4	0.2620	30.32	20.00	50.32	61.36	-11.04	QP	
5	0.2940	31.27	20.00	51.27	60.41	-9.14	QP	
6	0.3020	18.74	20.00	38.74	50.19	-11.45	AVG	
7	0.3820	15.10	20.00	35.10	48.23	-13.13	AVG	
8	0.3860	28.26	20.00	48.26	58.15	-9.89	QP	
9	1.1580	23.16	20.00	43.16	56.00	-12.84	QP	
10	1.2340	12.16	20.00	32.16	46.00	-13.84	AVG	
11	1.8660	10.74	20.00	30.74	46.00	-15.26	AVG	
12	1.9380	19.38	20.00	39.38	56.00	-16.62	QP	

4. Radiation Interference

4.1. Requirements (15.249, 15.209):

FIELD STRENGTH of Fundamental: @3M	FIELD STRENGTH of Harmonics	S15.209	
902-928 MHZ		30 - 88 MHz	40 dBuV/m
2.4-2.4835 GHz		88 - 216 MHz	43.5
94 dB μ V/m @3m	54 dB μ V/m @3m	216 - 960 MHz	46
		ABOVE 960 MHz	54dBuV/m

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in 15.209, whichever is the lesser attenuation.

4.2. Test Procedure

For below 1GHz, the EUT is placed on a turn table which is 0.8 meter high above the ground. For above 1GHz, the EUT is placed on a turn table which is 1.5 meter high above the ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT is set 3 meters away from the receiving antenna which is mounted on a antenna tower. The antenna can be moved up and down from 1 to 4 meters to find out the maximum emission level. Both horizontal and vertical polarization of the antenna are set on test.

All readings from 30MHz to 1GHz are quasi-peak values with a resolution bandwidth of 120kHz. All reading are above 1GHz, peak & average values with a resolution bandwidth of 1MHz. The EUT is tested in 9*6*6 Chamber. The device is evaluated in xyz orientation. The test results are listed in Section 4.3.

4.3 Test Equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Spectrum Analysis	Agilent	E4407B	US39390582	Apr. 17, 2015	1 Year
2.	Preamplifier	Instruments corporation	EMC011830	980100	Apr. 17, 2015	1 Year
3.	EMI Test Receiver	Rohde & Schwarz	ESPI	101604	Apr. 17, 2015	1 Year
4.	Double Ridged Horn Antenna	Instruments corporation	GTH-0118	351600	Apr. 20, 2015	1 Year
5.	Bilog Broadband Antenna	Schwarzbeck	VULB9163	VULB 9163-289	Apr. 20, 2015	1 Year
6.	Pre-amplifier	SONOMA	310N	186860	Apr. 17, 2015	1 Year
7.	EMI Test Software EZ-EMC	SHURPLE	N/A	N/A	N/A	N/A
8	Power Sensor	DAER	RPR3006W	15I00041SN046	Jun 30, 2015	1 Year
9	MXA Spectrum Analysis	Agilent	N9020A	MY51170037	Jun 30, 2015	1 Year
10	MXG RF Vector Signal Generator	Agilent	N5182A	MY48180656	Jun 30, 2015	1 Year
11	Signal Generator	Agilent	E4421B	MY41000743	Jun 30, 2015	1 Year
12	DC Power supply	IV	IV-8080	YQSB0096	Jun 30, 2015	1 Year
13	TEMP&HUMI PROGRAMMABLE CHAMBER	Bell Group	BE-THK-150M8	SE-0137	Mar 16, 2015	1 Year

4.4. Test Results


PASS.

The EUT was tested on (Charging, BT Mode) modes, only the worst data of (BT Mode) is attached in the following pages.

Only the worst case (x orientation).


Below 1GHz:

Job No.:	011511317I	Polarziation:	Horizontal
Standard:	(RE)FCC PART15 C _3m	Power Source:	DC 3.7V
Test item:	Radiation Test	Temp.(C)/Hum.(%RH):	24.3(C)/52%RH
Mode:	BT Mode	Distance:	3m
Note:	30-1000MHz		



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	30.3173	35.46	-16.77	18.69	40.00	-21.31	QP	300	360	
2	37.2855	33.17	-12.49	20.68	40.00	-19.32	QP	300	0	
3	56.1974	32.26	-15.05	17.21	40.00	-22.79	QP	300	360	
4	129.4677	44.30	-22.73	21.57	43.50	-21.93	QP	300	360	
5	157.5588	41.27	-22.98	18.29	43.50	-25.21	QP	300	0	
6	316.5890	44.34	-15.67	28.67	46.00	-17.33	QP	300	0	

Job No.: 011511317I Polarization: Vertical
Standard: (RE)FCC PART15 C _3m Power Source: DC 3.7V
Test item: Radiation Test Temp.(C)/Hum.(%RH): 24.3(C)/52%RH
Mode: BT Mode Distance: 3m
Note: 30-1000MHz



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	33.7986	48.06	-14.92	33.14	40.00	-6.86	QP	100	360	
2	37.3755	46.17	-12.42	33.75	40.00	-6.25	QP	100	0	
3	131.7577	46.91	-17.93	28.98	43.50	-14.52	QP	100	360	
4	150.5378	47.47	-18.33	29.14	43.50	-14.36	QP	100	0	
5	304.6099	49.80	-14.59	35.21	46.00	-10.79	QP	100	360	
6	426.5210	42.03	-11.25	30.78	46.00	-15.22	QP	100	0	

Above 1 GHz:

Horizontal CH 2438MHz								
Frequency MHz	Cable Loss dB	Ant Factor dB/m	Preamp Factor dB	Read Level dBμV	Level dBμV/m	Limit dBμV/m	Over Limit dB	Remark
2438.000	2.19	31.22	34.60	88.25	87.06	114.0	-26.94	Peak
2438.000	2.19	31.22	34.60	78.32	77.13	94.0	-16.87	AV
4876.160	2.57	35.00	34.58	43.13	46.12	74.0	-27.88	Peak
4876.160	2.57	35.00	34.58	35.98	38.97	54.0	-15.03	AV
7314.540	3.00	36.17	35.14	40.15	44.18	74.0	-29.82	Peak
7314.540	3.00	36.17	35.14	31.60	35.63	54.0	-18.37	AV
9752.000	---	---	---	---	---	---	---	---
12190.00	---	---	---	---	---	---	---	---
14628.00	---	---	---	---	---	---	---	---
17066.00	---	---	---	---	---	---	---	---
---	---	---	---	---	---	---	---	---

Vertical CH 2438MHz								
Frequency MHz	Cable Loss dB	Ant Factor dB/m	Preamp Factor dB	Read Level dBμV	Level dBμV/m	Limit dBμV/m	Over Limit dB	Remark
2438.000	2.19	31.22	34.60	90.12	88.93	114.0	-25.07	Peak
2438.000	2.19	31.22	34.60	80.23	79.04	94.0	-14.96	AV
4876.080	2.57	35.00	34.58	43.85	46.84	74.0	-27.16	Peak
4876.080	2.57	35.00	34.58	35.03	38.02	54.0	-15.98	AV
7314.450	3.00	36.17	35.14	42.91	46.94	74.0	-27.06	Peak
7314.450	3.00	36.17	35.14	34.02	38.05	54.0	-15.95	AV
9752.000	---	---	---	---	---	---	---	---
12190.00	---	---	---	---	---	---	---	---
14628.00	---	---	---	---	---	---	---	---
17066.00	---	---	---	---	---	---	---	---
---	---	---	---	---	---	---	---	---

**NOTE: “ --- ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
The results of different modulations are the same.**

5. Bandedge

5.1. Requirements (15.249):

The field strength of any emissions appearing outside the band edges and up to 10 kHz above and below the band edges shall be attenuated at least 50 dB below the level of the carrier or to the general limits of 15.249.

5.2. Test Procedure


The EUT is placed on a turn table which is 1.5 meter high above the ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT is set 3 meters away from the receiving antenna which is mounted on a antenna tower. The antenna can be moved up and down from 1 to 4 meters to find out the maximum emission level. Both horizontal and vertical polarization of the antenna are set on test. The device is evaluated in xyz orientation.

Test Equipment


Same as the equipment listed in 3.3.

5.3. Test Configuration:

30M to 1G emissions:



1G to 40G emissions:




5.4. Test Results

Pass.


Please refer the following plot. Only the worst case (x orientation).

Job No.:	011511317I	Polarization:	Horizontal
Standard:	(RE)FCC PART15 C _3m	Power Source:	DC 3.7V
Test item:	Radiation Test	Temp.(C)/Hum.(%RH):	24.3(C)/52%RH
Note:	PEAK	Distance:	3m




No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	2348.250	53.16	-2.61	50.55	74.00	-23.45	peak			
2	2390.000	43.19	-2.51	40.68	74.00	-33.32	peak			
3	2400.000	44.21	-2.49	41.72	74.00	-32.28	peak			

Job No.:	011511317I	Polarization:	Vertical
Standard:	(RE)FCC PART15 C _3m	Power Source:	DC 3.7V
Test item:	Radiation Test	Temp.(C)/Hum.(%RH):	24.3(C)/52%RH
Note:	PEAK	Distance:	3m




No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	2483.500	41.48	-2.31	39.17	74.00	-34.83	peak			
2	2492.988	41.49	-2.29	39.20	74.00	-34.80	peak			

Job No.:	011511317I	Polarization:	Horizontal
Standard:	(RE)FCC PART15 C _3m	Power Source:	DC 3.7V
Test item:	Radiation Test	Temp.(C)/Hum.(%RH):	24.3(C)/52%RH
Note:	AV	Distance:	3m



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	2362.875	40.18	-2.57	37.61	54.00	-16.39	AVG			
2	2390.000	39.19	-2.51	36.68	54.00	-17.32	AVG			
3	2400.000	40.21	-2.49	37.72	54.00	-16.28	AVG			

Job No.:	011511317I	Polarization:	Vertical
Standard:	(RE)FCC PART15 C _3m	Power Source:	DC 3.7V
Test item:	Radiation Test	Temp.(C)/Hum.(%RH):	24.3(C)/52%RH
Note:	AV	Distance:	3m




No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	2483.500	38.48	-2.31	36.17	54.00	-17.83	AVG			
2	2492.350	38.57	-2.29	36.28	54.00	-17.72	AVG			

6. Occupied Bandwidth

6.1. Requirements :

According to 15.215 (c), intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated. The requirement to contain the designated bandwidth of the emission within the specified frequency band includes the effects from frequency sweeping, frequency hopping and other modulation techniques that may be employed as well as the frequency stability of the transmitter over expected variations in temperature and supply voltage. If a frequency stability is not specified in the regulations, it is recommended that the fundamental emission be kept within at least the central 80% of the permitted band in order to minimize the possibility of out-of-band operation.

6.2. Test SET-UP



6.3 Test Equipment


Same as the equipment listed in 4.3.

6.4. Test Results

Pass.

Please refer the following plot.

20dB Down:



7. ANTENNA APPLICATION


7.1. Antenna requirement

The EUT'S antenna is met the requirement of FCC part 15C section 15.203.

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §15.211, §15.213, §15.217, §15.219, or §15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

7.2. Result

The EUT's antenna used a Integrated antenna which is permanently attached, The antenna's gain is 0dBi and meets the requirement.





8. PHOTOGRAPH

8.1 Photo of Conducted Emission Test



8.2 Photo of Radiation Emission Test





APPENDIX I (External Photos)

Figure 1
The EUT-Top View




Figure 2
The EUT-Bottom View




Figure 3
The EUT-Front View




Figure 4
The EUT-Back View




Figure 5
The EUT-Right View



Figure 6
The EUT-Left View



APPENDIX II (Internal Photos)

Figure 7
The EUT-Inside View




Figure 8
The EUT-Inside View




Figure 9
PCB of the EUT-Front View



Figure 10
PCB of the EUT-Back View




Figure 11
The EUT-Inside View




Figure 12
PCB of the EUT-Front View




Figure 13
PCB of the EUT-Back View




Figure 14
PCB of the EUT-Front View




Figure 15
PCB of the EUT-Back View




Figure 16
PCB of the EUT-Front View




Figure 17
PCB of the EUT-Back View

