

FCC PART 15 B TEST REPORT

For

Fujian Landi Commercial Equipment Co., Ltd.

No.68, Hong Shan Yuan Road, Gulou District, Fuzhou Municipality, Fujian Province, P.R. China.

FCC ID: 2AG6N-E820RFWDWF

Report Type: Original Report	Product Type: POS Payment Terminal
Test Engineer: Lion Xiao	
Report Number: RXM160127053-00A	
Report Date: 2016-03-10	
Reviewed By: Sula Huang RF Leader	
Test Laboratory: Bay Area Compliance Laboratories Corp. (Dongguan) No.69 Pulongcun, Puxinhu Industrial Zone, Tangxia, Dongguan, Guangdong, China Tel: +86-769-86858888 Fax: +86-769-86858891 www.baclcorp.com.cn	

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Dongguan).

TABLE OF CONTENTS

GENERAL INFORMATION.....	3
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	3
OBJECTIVE	3
RELATED SUBMITTAL(S)/GRANT(S).....	3
TEST METHODOLOGY	3
TEST FACILITY	4
SYSTEM TEST CONFIGURATION.....	5
DESCRIPTION OF TEST CONFIGURATION	5
EUT EXERCISE SOFTWARE	5
EQUIPMENT MODIFICATIONS	5
LOCAL SUPPORT EQUIPMENT LIST AND DETAILS	5
SUPPORT CABLE LIST AND DETAILS	5
CONFIGURATION OF TEST SETUP	6
SUMMARY OF TEST RESULTS	7
FCC§15.107 - CONDUCTED EMISSIONS.....	8
MEASUREMENT UNCERTAINTY	8
EUT SETUP.....	8
EMI TEST RECEIVER SETUP.....	9
TEST EQUIPMENT LIST AND DETAILS.....	9
TEST PROCEDURE	9
CORRECTED AMPLITUDE & MARGIN CALCULATION	9
TEST RESULTS SUMMARY	10
TEST DATA	10
FCC §15.109 - RADIATED SPURIOUS EMISSIONS	15
MEASUREMENT UNCERTAINTY	15
EUT SETUP	15
EMI TEST RECEIVER SETUP.....	16
TEST PROCEDURE	16
TEST EQUIPMENT LIST AND DETAILS.....	17
CORRECTED AMPLITUDE & MARGIN CALCULATION	17
TEST RESULTS SUMMARY	17
TEST DATA	17
ENVIRONMENTAL CONDITIONS.....	17

GENERAL INFORMATION

Product Description for Equipment Under Test (EUT)

The *Fujian Landi Commercial Equipment Co., Ltd.*'s product, model number: E820 (the "EUT") in this report was a *POS Payment Terminal*, which was measured approximately: 14.6 cm (L) x 8.0cm (W) x 3.6 cm (H), rated input voltage: DC 3.6V rechargeable Li-ion battery or DC5.0V charging from adapter or base. The highest operating frequency is 2462 MHz.

Adapter#1 information:
Model: HKA04824018-8D
Input: AC100-240V, 50/60 Hz, 1.2A
Output: DC24.0V, 1.8A

Adapter#2 information:
Model: HKA00505010-XA
Input: AC100-240V, 50/60 Hz, 0.2A
Output: DC 5.0V, 1.0A

All measurement and test data in this report was gathered from production sample serial number: 160127053 (Assigned by BACL, Dongguan). The EUT was received on 2016-02-16.

Objective

This test report is prepared on behalf of *Fujian Landi Commercial Equipment Co., Ltd.* in accordance with Part 2, Subpart J, and Part 15-Subparts A and B of the Federal Communications Commission's rules.

The objective of the manufacturer is to determine the compliance of EUT with FCC Part 15 B Class B.

Related Submittal(s)/Grant(s)

FCC Part15C DTS submissions with FCC ID: 2AG6N-E820RFWDWF.
FCC Part 15C DXX submissions with FCC ID: 2AG6N-E820RFWDWF.
FCC Part 22H & 24E PCB submissions with FCC ID: 2AG6N-E820RFWDWF.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2014, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

All radiated and conducted emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Dongguan).

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.69 Pulongcun, Puxinhu Industrial Zone, Tangxia, Dongguan, Guangdong, China

Test site at Bay Area Compliance Laboratories Corp. (Dongguan) has been fully described in reports submitted to the Federal Communications Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on February 06, 2015.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 273710. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

FINAL

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in a typical fashion (as normally used by a typical user).

EUT Exercise Software

N/A

Equipment Modifications

No modification was made to the EUT tested.

Local Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
DELL	Laptop	PP11L	QDS-BRCM1017
HP	Printer	C3941A	JPTVOB2337
DELL	Keyboard	L100	CNORH656658907BL05DC
SAST	Modem	AEM-2100	0293
KINGSTON	USB Disk	N/A	N/A
ARESCOM	DSLAM	CDS6020	N/A

Support Cable List and Details


Cable Description	Shielding Type	Ferrite Core	Length (m)	From	To
Serial Cable	Yes	No	1.2	Serial Port of Laptop	Modem
Parallel Cable	Yes	No	1.2	Parallel Port of Laptop	Printer
Keyboard Cable	Yes	No	1.8	USB Port of Laptop	Keyboard
RJ45 Cable*1	No	No	0.8	LAN Port of Laptop	EUT
RJ11 Cable*2	No	No	10	RJ11 port of DSL	EUT

Configuration of Test Setup

Adatper#1



Adatper#2



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Results
§15.107	Conducted Emissions	Compliance
§15.109	Radiated Emissions	Compliance

FCC§15.107 - CONDUCTED EMISSIONS

Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are Receiver, cable loss, and LISN.

Compliance or non-compliance with a disturbance limit shall be determined in the following manner:

If U_{lab} is less than or equal to U_{cisp} of Table 1, then:

- compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.

If U_{lab} is greater than U_{cisp} of Table 1, then:

- compliance is deemed to occur if no measured disturbance level, increased by $(U_{lab} - U_{cisp})$, exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level, increased by $(U_{lab} - U_{cisp})$, exceeds the disturbance limit.


Based on CISPR 16-4-2: 2011, measurement uncertainty of conducted disturbance at mains port using AMN at Bay Area Compliance Laboratories Corp. (Dongguan) is 3.12 dB (150 kHz to 30 MHz).

Table 1 – Values of U_{cisp}

Measurement	U_{cisp}
Conducted disturbance at mains port using AMN (150 kHz to 30 MHz)	3.4 dB

Note: The $U_{lab} > U_{cisp}$, so the U_{lab} is add in the calculation.

EUT Setup



- Note: 1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.4-2014 measurement procedure. The specification used was with the FCC Part 15 B Class B limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The adapter was connected to a 120V/60Hz AC power source.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESCS 30	830245/006	2015-10-20	2016-10-20
R&S	L.I.S.N	ESH2-Z5	892107/021	2015-07-16	2016-07-15
R&S	Two-line V-network	ENV 216	3560.6550.12	2015-11-26	2016-11-25
N/A	Coaxial Cable	1.8m	N/A	2015-05-06	2016-05-06
R&S	Test Software	EMC32	Version8.53.0	N/A	N/A

* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the first LISN and the other support equipments were connected to the outlet of the second LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

Corrected Amplitude & Margin Calculation

The basic equation is as follows:

$$V_C = V_R + A_C + VDF$$

Herein,

V_C : corrected voltage amplitude

V_R : reading voltage amplitude

A_C : attenuation caused by cable loss

VDF: voltage division factor of AMN or ISN

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. For example, a margin of 7dB means the emission is 7dB below the maximum limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15 B Class B, with the worst margin reading of:

9.5 dB at 0.922769 MHz in the **Line** conducted mode

Test Data


Environmental Conditions

Temperature:	24.3°C
Relative Humidity:	46 %
ATM Pressure:	101.7 kPa

The testing was performed by Lion Xiao on 2016-02-23.


Adapter#1

Test Mode: Operating (Reading IC card +LAN +DSL+USB)

AC120V, 60Hz, Line:


Frequency (MHz)	Quasi Peak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.152410	45.8	9.000	L1	9.8	20.1	65.9	Compliance
0.171759	42.4	9.000	L1	9.7	22.5	64.9	Compliance
0.204669	38.2	9.000	L1	9.7	25.2	63.4	Compliance
0.317235	23.5	9.000	L1	9.7	36.3	59.8	Compliance
1.239175	30.7	9.000	L1	9.8	25.3	56.0	Compliance
1.385415	33.6	9.000	L1	9.8	22.4	56.0	Compliance

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.150000	30.1	9.000	L1	9.8	25.9	56.0	Compliance
0.491712	22.5	9.000	L1	9.8	23.6	46.1	Compliance
0.519918	24.7	9.000	L1	9.8	21.3	46.0	Compliance
1.190776	23.0	9.000	L1	9.8	23.0	46.0	Compliance
1.239175	24.3	9.000	L1	9.8	21.7	46.0	Compliance
1.385415	25.1	9.000	L1	9.8	20.9	46.0	Compliance

AC120V, 60Hz, Neutral:


Frequency (MHz)	Quasi Peak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.157346	45.0	9.000	N	9.7	20.6	65.6	Compliance
0.171759	42.8	9.000	N	9.7	22.1	64.9	Compliance
0.187494	42.1	9.000	N	9.7	22.0	64.1	Compliance
1.407671	32.9	9.000	N	9.8	23.1	56.0	Compliance
1.476605	32.4	9.000	N	9.8	23.6	56.0	Compliance
1.624765	34.5	9.000	N	9.8	21.5	56.0	Compliance

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.153629	29.5	9.000	N	9.7	26.3	55.8	Compliance
0.503608	20.3	9.000	N	9.7	25.7	46.0	Compliance
1.144267	20.0	9.000	N	9.8	26.0	46.0	Compliance
1.190776	23.0	9.000	N	9.8	23.0	46.0	Compliance
1.310256	23.4	9.000	N	9.8	22.6	46.0	Compliance
1.430284	25.1	9.000	N	9.8	20.9	46.0	Compliance

Adapter#2*Test Mode: Operating (Reading IC card)***AC120V, 60Hz, Line:**

Frequency (MHz)	Quasi Peak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.511698	44.1	9.000	L1	9.8	11.9	56.0	Compliance
0.709407	43.4	9.000	L1	9.8	12.6	56.0	Compliance
0.825364	43.7	9.000	L1	9.8	12.3	56.0	Compliance
0.908180	44.8	9.000	L1	9.8	11.2	56.0	Compliance
1.171949	42.1	9.000	L1	9.8	13.9	56.0	Compliance
1.269154	42.4	9.000	L1	9.8	13.6	56.0	Compliance

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.429420	33.6	9.000	L1	9.8	13.7	47.3	Compliance
0.432855	32.9	9.000	L1	9.8	14.3	47.2	Compliance
0.709407	33.9	9.000	L1	9.8	12.1	46.0	Compliance
0.922769	36.5	9.000	L1	9.8	9.5	46.0	Compliance
1.259081	32.3	9.000	L1	9.8	13.7	46.0	Compliance
2.199332	27.3	9.000	L1	9.8	18.7	46.0	Compliance

AC120V, 60Hz, Neutral:

Frequency (MHz)	Quasi Peak (dB μ V)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)	Comment
0.402900	37.1	9.000	N	9.7	20.7	57.8	Compliance
0.457684	38.8	9.000	N	9.7	17.9	56.7	Compliance
0.499611	40.7	9.000	N	9.7	15.3	56.0	Compliance
0.649874	38.5	9.000	N	9.7	17.5	56.0	Compliance
1.099574	40.5	9.000	N	9.8	15.5	56.0	Compliance
1.374420	38.6	9.000	N	9.8	17.4	56.0	Compliance

Frequency (MHz)	Average (dB μ V)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)	Comment
0.402900	29.1	9.000	N	9.7	18.7	47.8	Compliance
0.499611	28.2	9.000	N	9.7	17.8	46.0	Compliance
0.726569	29.3	9.000	N	9.7	16.7	46.0	Compliance
0.922769	29.9	9.000	N	9.8	16.1	46.0	Compliance
1.259081	30.8	9.000	N	9.8	15.2	46.0	Compliance
4.469698	27.5	9.000	N	9.9	18.5	46.0	Compliance

FCC §15.109 - RADIATED SPURIOUS EMISSIONS

Measurement Uncertainty

Compliance or non-compliance with a disturbance limit shall be determined in the following manner:

If U_{lab} is less than or equal to U_{cisp} of Table 1, then:

- compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.

If U_{lab} is greater than U_{cisp} of Table 1, then:

- compliance is deemed to occur if no measured disturbance level, increased by $(U_{lab} - U_{cisp})$, exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level, increased by $(U_{lab} - U_{cisp})$, exceeds the disturbance limit.


Based on CISPR 16-4-2: 2011, measurement uncertainty of radiated emission at a distance of 10m at Bay Area Compliance Laboratories Corp. (Dongguan) is: 30M~200MHz: 4.55 dB for Horizontal, 4.57 dB for Vertical; 200M~1GHz: 4.66 dB for Horizontal, 4.56 dB for Vertical; measurement uncertainty of radiated emission at a distance of 3m at Bay Area Compliance Laboratories Corp. (Dongguan) is: 30M~200MHz: 4.58 dB for Horizontal, 4.59 dB for Vertical; 200M~1GHz: 4.83 dB for Horizontal, 5.85 dB for Vertical; 1G~6GHz: 4.45 dB, 6G~18GHz: 5.23 dB

Table 1 – Values of U_{cisp}


Measurement		U_{cisp}
Radiated disturbance (electric field strength at an OATS or in a SAC)	(30 MHz to 1000 MHz)	6.3 dB
Radiated disturbance (electric field strength in a FAR)	(1 GHz to 6 GHz)	5.2 dB
Radiated disturbance (electric field strength in a FAR)	(6 GHz to 18 GHz)	5.5 dB

EUT Setup

Below 1GHz:



Above 1GHz:



The radiated emission tests were performed in the 3 meters chamber test site, using the setup accordance with the ANSI C63.4-2014. The specification used was the FCC Part 15.109 Class B limits.

EMI Test Receiver Setup

The system was investigated from 30 MHz to 13 GHz.

During the radiated emission test, the EMI test receiver was set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
30 MHz – 1000 MHz	120 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1 MHz	3 MHz	/	Peak
	1 MHz	10 Hz	/	AVG

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

The data was recorded in the Quasi-peak detection mode for below 1 GHz, peak and average detection mode above 1 GHz.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESCI	100224	2015-08-03	2016-08-02
Sunol Sciences	Antenna	JB3	A060611-3	2014-11-06	2017-11-05
HP	Amplifier	8447E	2434A02181	2015-09-01	2016-09-01
Agilent	Spectrum Analyzer	E4440A	SG43360054	2015-11-23	2016-11-22
ETS-Lindgren	Horn Antenna	3115	9808-5557	2015-09-06	2018-09-06
Mini-Circuit	Amplifier	ZVA-213-S+	054201245	2016-02-19	2017-02-19
N/A	Coaxial Cable	14m	N/A	2015-05-06	2016-05-06
N/A	Coaxial Cable	8m	N/A	2015-05-06	2016-05-06
Farad	Test Software	EZ-EMC	V1.1.4.2	N/A	N/A

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Loss and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Loss} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Results Summary

According to the data in the following table, the EUT complied with the FCC Part 15 B Class B, with the worst margin reading of:

0.80 dB at 750.7100 MHz in the Horizontal polarization

Test Data

Environmental Conditions


Temperature:	21.4 °C
Relative Humidity:	73 %
ATM Pressure:	101.9 kPa

The testing was performed by Lion Xiao on 2016-03-02.


Test Result: Compliance

1) Below 1GHz:

Adapter#1

*Test Mode: Charging&Operating (Reading IC card +LAN +DSL+USB)***Horizontal**


Frequency (MHz)	Receiver Reading (dBμV)	Detector	Correction Factor (dB/m)	Cord. Amp. (dBμV/m)	Limit (dBμV/m)	Margin (dB)
350.1000	48.77	QP	-5.07	43.70	46.00	2.30
450.0100	43.24	QP	-2.84	40.40	46.00	5.60
750.7100	43.88	QP	1.32	45.20	46.00	0.80
774.9600	42.90	QP	1.90	44.80	46.00	1.20
825.4000	39.30	QP	2.10	41.40	46.00	4.60
875.8400	38.50	QP	2.60	41.10	46.00	4.90

Vertical


Frequency (MHz)	Receiver Reading (dBμV)	Detector	Correction Factor (dB/m)	Cord. Amp. (dBμV/m)	Limit (dBμV/m)	Margin (dB)
58.1300	49.42	QP	-13.22	36.20	40.00	3.80
119.2400	41.91	QP	-6.01	35.90	43.50	7.60
156.1000	44.48	QP	-7.38	37.10	43.50	6.40
537.3100	41.94	QP	-1.54	40.40	46.00	5.60
650.8000	42.70	QP	-0.20	42.50	46.00	3.50
750.7100	42.48	QP	1.32	43.80	46.00	2.20

Adapter#2

Test Mode: Charging&Operating (Reading IC card)

Horizontal


Frequency (MHz)	Receiver Reading (dBμV)	Detector	Correction Factor (dB/m)	Cord. Amp. (dBμV/m)	Limit (dBμV/m)	Margin (dB)
40.6700	36.99	QP	-6.89	30.10	40.00	9.90
675.0500	37.61	QP	0.19	37.80	46.00	8.20
725.4900	36.38	QP	1.12	37.50	46.00	8.50
775.9300	42.98	QP	1.92	44.90	46.00	1.10
825.4000	41.20	QP	2.10	43.30	46.00	2.70
875.8400	37.40	QP	2.70	40.10	46.00	5.90

Vertical

Frequency (MHz)	Receiver Reading (dBμV)	Detector	Correction Factor (dB/m)	Cord. Amp. (dBμV/m)	Limit (dBμV/m)	Margin (dB)
44.5500	44.28	QP	-9.68	34.60	40.00	5.40
587.7500	36.65	QP	-1.25	35.40	46.00	10.60
675.0500	35.91	QP	0.19	36.10	46.00	9.90
725.4900	35.58	QP	1.12	36.70	46.00	9.30
774.9600	37.30	QP	1.90	39.20	46.00	6.80
825.4000	37.80	QP	2.10	39.90	46.00	6.10


2) Above 1GHz:

Adapter#1

Horizontal

Frequency (MHz)	Receiver Reading (dBμV)	Detector	Correction Factor (dB/m)	Cord. Amp. (dBμV/m)	Limit (dBμV/m)	Margin (dB)
1012.000	40.40	peak	5.25	45.65	74.00	28.35
1012.000	27.81	AVG	5.25	33.06	54.00	20.94
2104.000	41.75	peak	3.78	45.53	74.00	28.47
2104.000	29.34	AVG	3.78	33.12	54.00	20.88
7696.000	28.08	peak	22.16	50.24	74.00	23.76
7696.000	15.60	AVG	22.16	37.76	54.00	16.24


Note: For above 6GHz, no emissions were detected.

Vertical

Frequency (MHz)	Receiver Reading (dB μ V)	Detector	Correction Factor (dB/m)	Cord. Amp. (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
1096.000	42.50	peak	4.59	47.09	74.00	26.91
1096.000	29.87	AVG	4.59	34.46	54.00	19.54
1486.000	42.67	peak	2.80	45.47	74.00	28.53
1486.000	30.23	AVG	2.80	33.03	54.00	20.97
4132.000	34.51	peak	9.23	43.74	74.00	30.26
4132.000	22.02	AVG	9.23	31.25	54.00	22.75


Note: For above 6GHz, no emissions were detected.

Adapter#2

Horizontal

Frequency (MHz)	Receiver Reading (dBμV)	Detector	Correction Factor (dB/m)	Cord. Amp. (dBμV/m)	Limit (dBμV/m)	Margin (dB)
1024.000	39.02	peak	5.15	44.17	74.00	29.83
1024.000	26.61	AVG	5.15	31.76	54.00	22.24
9466.000	30.28	peak	19.48	49.76	74.00	24.24
9466.000	17.80	AVG	19.48	37.28	54.00	16.72
12676.000	8.87	peak	43.96	52.83	74.00	21.17
12676.000	-3.79	AVG	43.96	40.17	54.00	13.83

Note: For above 6GHz, no emissions were detected.

Vertical

Frequency (MHz)	Receiver Reading (dBμV)	Detector	Correction Factor (dB/m)	Cord. Amp. (dBμV/m)	Limit (dBμV/m)	Margin (dB)
1198.000	41.11	peak	4.34	45.45	74.00	28.55
1198.000	28.67	AVG	4.34	33.01	54.00	20.99
1900.000	41.22	peak	3.86	45.08	74.00	28.92
1900.000	28.78	AVG	3.86	32.64	54.00	21.36
2662.000	37.84	peak	6.65	44.49	74.00	29.51
2662.000	25.49	AVG	6.65	32.14	54.00	21.86

Note: For above 6GHz, no emissions were detected.

*****END OF REPORT*****