

## FCC Test Report

**Report No.:** RF151102C10

**FCC ID:** 2AG6R-AN500APIAC

**Test Model:** AN-500-AP-I-AC

**Received Date:** Nov. 02, 2015

**Test Date:** Nov. 09 ~ Nov. 18, 2015

**Issued Date:** Dec. 01, 2015

**Applicant:** Araknis Networks

**Address:** 1800 Continental Blvd. Ste 200, Charlotte, NC 28273, United States

**Issued By:** Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

**Lab Address:** No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan, R.O.C.

**Test Location:** No.19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City 33383, TAIWAN (R.O.C.)



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. This report should not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

## Table of Contents

<b>Release Control Record</b>	<b>4</b>
<b>1 Certificate of Conformity</b>	<b>5</b>
<b>2 Summary of Test Results</b>	<b>6</b>
2.1 Measurement Uncertainty	6
2.2 Modification Record	6
<b>3 General Information</b>	<b>7</b>
3.1 General Description of EUT	7
3.2 Description of Test Modes	9
3.2.1 Test Mode Applicability and Tested Channel Detail	10
3.3 Duty Cycle of Test Signal	12
3.4 Description of Support Units	13
3.4.1 Configuration of System under Test	13
3.5 General Description of Applied Standards	15
<b>4 Test Types and Results</b>	<b>16</b>
4.1 Radiated Emission and Bandedge Measurement	16
4.1.1 Limits of Radiated Emission and Bandedge Measurement	16
4.1.2 Test Instruments	17
4.1.3 Test Procedures	18
4.1.4 Deviation from Test Standard	18
4.1.5 Test Set Up	19
4.1.6 EUT Operating Conditions	19
4.1.7 Test Results	20
4.2 Conducted Emission Measurement	34
4.2.1 Limits of Conducted Emission Measurement	34
4.2.2 Test Instruments	34
4.2.3 Test Procedures	35
4.2.4 Deviation from Test Standard	35
4.2.5 Test Setup	35
4.2.6 EUT Operating Conditions	35
4.2.7 Test Results	36
4.3 6dB Bandwidth Measurement	40
4.3.1 Limits of 6dB Bandwidth Measurement	40
4.3.2 Test Setup	40
4.3.3 Test Instruments	40
4.3.4 Test Procedure	40
4.3.5 Deviation from Test Standard	40
4.3.6 EUT Operating Conditions	40
4.3.7 Test Result	41
4.4 Conducted Output Power Measurement	43
4.4.1 Limits of Conducted Output Power Measurement	43
4.4.2 Test Setup	43
4.4.3 Test Instruments	43
4.4.4 Test Procedures	43
4.4.5 Deviation from Test Standard	43
4.4.6 EUT Operating Conditions	43
4.4.7 Test Results	44
4.5 Power Spectral Density Measurement	45
4.5.1 Limits of Power Spectral Density Measurement	45
4.5.2 Test Setup	45
4.5.3 Test Instruments	45
4.5.4 Test Procedure	45
4.5.5 Deviation from Test Standard	46
4.5.6 EUT Operating Condition	46

4.5.7 Test Results .....	47
4.6 Conducted Out of Band Emission Measurement.....	50
4.6.1 Limits of Conducted Out of Band Emission Measurement .....	50
4.6.2 Test Setup.....	50
4.6.3 Test Instruments .....	50
4.6.4 Test Procedure .....	50
4.6.5 Deviation from Test Standard .....	51
4.6.6 EUT Operating Condition .....	51
4.6.7 Test Results .....	51
<b>5 Pictures of Test Arrangements.....</b>	<b>60</b>
<b>Appendix – Information on the Testing Laboratories .....</b>	<b>61</b>



A D T

### Release Control Record

Issue No.	Description	Date Issued
RF151102C10	Original release.	Dec. 01, 2015

## 1 Certificate of Conformity

**Product:** Araknis Networks 500-series Dual-Band Concurrent Wireless-AC Indoor Access Point

**Brand:** Araknis Networks ®

**Test Model:** AN-500-AP-I-AC

**Sample Status:** Engineering sample

**Applicant:** Araknis Networks

**Test Date:** Nov. 09 ~ Nov. 18, 2015

**Standards:** 47 CFR FCC Part 15, Subpart C (Section 15.247)  
ANSI C63.10:2013

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

**Prepared by :** Ivy Lin , **Date:** Dec. 01, 2015  
Ivy Lin / Specialist

**Approved by :** Ken Liu , **Date:** Dec. 01, 2015  
Ken Liu / Senior Manager

## 2 Summary of Test Results

47 CFR FCC Part 15, Subpart C (Section 15.247)			
FCC Clause	Test Item	Result	Remarks
15.207	AC Power Conducted Emission	Pass	Meet the requirement of limit. Minimum passing margin is -14.09dB at 0.29897MHz
15.205 / 15.209 / 15.247(d)	Radiated Emissions and Band Edge Measurement	Pass	Meet the requirement of limit. Minimum passing margin is -0.8dB at 2483.50MHz
15.247(d)	Antenna Port Emission	Pass	Meet the requirement of limit.
15.247(a)(2)	6dB bandwidth	Pass	Meet the requirement of limit.
15.247(b)	Conducted power	Pass	Meet the requirement of limit.
15.247(e)	Power Spectral Density	Pass	Meet the requirement of limit.
15.203	Antenna Requirement	Pass	Antenna connector is IPEX not a standard connector.

### 2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Frequency	Expanded Uncertainty (k=2) ( $\pm$ )
Conducted Emissions at mains ports	150kHz ~ 30MHz	2.44 dB
Radiated Emissions up to 1 GHz	30MHz ~ 200MHz	3.86 dB
	200MHz ~ 1000MHz	3.87 dB
Radiated Emissions above 1 GHz	1GHz ~ 18GHz	2.29 dB
	18GHz ~ 40GHz	2.29 dB

### 2.2 Modification Record

There were no modifications required for compliance.

### 3 General Information

#### 3.1 General Description of EUT

Product	Araknis Networks 500-series Dual-Band Concurrent Wireless-AC Indoor Access Point
Brand	Araknis Networks ®
Test Model	AN-500-AP-I-AC
Sample Status	Engineering sample
Power Supply Rating	12Vdc from adapter 48Vdc from PoE
Modulation Type	CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM
Modulation Technology	DSSS, OFDM
Transfer Rate	802.11b:11.0/ 5.5/ 2.0/ 1.0Mbps 802.11g: 54.0/ 48.0/ 36.0/ 24.0/ 18.0/ 12.0/ 9.0/ 6.0Mbps 802.11n: up to 300Mbps
Operating Frequency	2412 ~ 2462MHz
Number of Channel	11 for 802.11b, 802.11g, 802.11n (HT20) 7 for 802.11n (HT40)
Output Power	420.208mW
Antenna Type	Refer to note
Antenna Connector	Refer to note
Accessory Device	Adapter
Data Cable Supplied	0.5m RJ45 non-shielded cable w/o core

Note:

- The EUT incorporates a MIMO function. Physically, the EUT provides 2 completed transmitters and 2 receivers.

Modulation Mode	TX Function
802.11b	2TX
802.11g	2TX
802.11n (HT20)	2TX
802.11n (HT40)	2TX

- The following antennas were provided to the EUT.

Antenna Type	PIFA		
Antenna Connector	IPEX		
Gain (dBi)	Frequency (MHz)		
	2400	2450	2500
Ant. 1	2.49	2.67	3.52
Ant. 2	2.76	3.01	3.16

Antenna Type	PIFA							
Antenna Connector	IPEX							
Gain (dBi)	Frequency (MHz)							
	5150	5250	5350	5450	5550	5650	5750	5850
Ant. 3	5.30	5.40	5.54	5.98	5.89	5.57	5.02	5.23
Ant. 4	3.98	4.08	4.63	4.93	5.63	5.58	5.68	5.66

### 3. The EUT consumes power from the following adapter and PoE.

Adapter	
Brand	Powertron Electronics Corp.
Model	PA1024-120HUB200
Input Power	100-240Vac, 50-60Hz, 0.6A
Output Power	12Vdc/ 2.0A, 24W Max
Power Line	DC 1.5m power cable with 1 core attached on adapter

PoE (support unit)	
Brand	EnGenius
Model	EPE-48GR
Rating	48Vdc, 0.8A, 38.4W Max

Adapter of PoE (support unit)	
Brand	Powertron Electronics Corp.
Model	PA1040-480IB080
Input Power	100-240Vac, 50-60Hz 1.5A
Output Power	48Vdc, 0.8A, 38.4W Max
Power Line	DC 1.5m power cable with 1 core attached on adapter



### 3.2 Description of Test Modes

11 channels are provided for 802.11b, 802.11g and 802.11n (HT20):

Channel	Frequency	Channel	Frequency
1	2412MHz	7	2442MHz
2	2417MHz	8	2447MHz
3	2422MHz	9	2452MHz
4	2427MHz	10	2457MHz
5	2432MHz	11	2462MHz
6	2437MHz		

7 channels are provided for 802.11n (HT40):

Channel	Frequency	Channel	Frequency
3	2422MHz	7	2442MHz
4	2427MHz	8	2447MHz
5	2432MHz	9	2452MHz
6	2437MHz		

### 3.2.1 Test Mode Applicability and Tested Channel Detail

EUT CONFIGURE MODE	APPLICABLE TO				DESCRIPTION
	RE≥1G	RE<1G	PLC	APCM	
A	√	√	√	√	Power from adapter
B	-	√	√	-	Power from PoE

Where **RE≥1G**: Radiated Emission above 1GHz & Bandedge Measurement  
**RE<1G**: Radiated Emission below 1GHz  
**PLC**: Power Line Conducted Emission  
**APCM**: Antenna Port Conducted Measurement

#### Note:

1. The EUT had been pre-tested on the positioned of each 3 axis. The worst case was found when positioned on **Z-plane**.
2. "-" means no effect.

#### Radiated Emission Test (Above 1GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
A	802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1.0
A	802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6.0
A	802.11n (HT20)	1 to 11	1, 6, 11	OFDM	BPSK	7.2
A	802.11n (HT40)	3 to 9	3, 6, 9	OFDM	BPSK	15.0

#### Radiated Emission Test (Below 1GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
A, B	802.11g	1 to 11	6	OFDM	BPSK	6.0

#### Power Line Conducted Emission Test:

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
A, B	802.11g	1 to 11	6	OFDM	BPSK	6.0

### Antenna Port Conducted Measurement:

- ☒ This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
A	802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1.0
A	802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6.0
A	802.11n (HT20)	1 to 11	1, 6, 11	OFDM	BPSK	7.2
A	802.11n (HT40)	3 to 9	3, 6, 9	OFDM	BPSK	15.0

### Test Condition:

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	INPUT POWER	TESTED BY
RE $\geq$ 1G	18deg. C, 70%RH	120Vac, 60Hz	Jones Chang
RE<1G	18deg. C, 70%RH	120Vac, 60Hz, 48Vdc	Nick Hsu
PLC	25deg. C, 70%RH	120Vac, 60Hz, 48Vdc	Jones Chang
APCM	25deg. C, 60%RH	120Vac, 60Hz	Leo Tsai

### 3.3 Duty Cycle of Test Signal


802.11b: Duty cycle of test signal is 100 %, duty factor is not required.

Duty cycle of test signal is < 98 %, duty factor shall be considered.

802.11g: Duty cycle =  $2.020/2.090 = 0.967$ , Duty factor =  $10 * \log(1/0.967) = 0.15$

802.11n (HT20): Duty cycle =  $1.885/1.940 = 0.972$ , Duty factor =  $10 * \log(1/0.972) = 0.12$

802.11n (HT40): Duty cycle =  $0.924/0.967 = 0.956$ , Duty factor =  $10 * \log(1/0.956) = 0.20$



### 3.4 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

ID	Product	Brand	Model No.	Serial No.	FCC ID	Remarks
A.	Notebook	DELL	E5410	1HC2XM1	FCC DoC Approved	-
B.	PoE	EnGenius	EPE-48GR	NA	NA	Supplied by the manufacturer
C.	Adapter of PoE	Powertron Electronics Corp.	PA1040-480IB080	NA	NA	Supplied by the manufacturer


Note:

1. All power cords of the above support units are non-shielded (1.8m).
2. Items A acted as a communication partner to transfer data.


ID	Descriptions	Qty.	Length (m)	Shielding (Yes/No)	Cores (Qty.)	Remarks
1.	LAN cable	1	5	N	0	-
2.	LAN cable	1	1.8	N	0	-
3.	DC cable	1	1.5	-	1	Attached on adapter of PoE

#### 3.4.1 Configuration of System under Test

<Test Mode A>



<Test Mode B>



### 3.5 General Description of Applied Standards

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

**FCC Part 15, Subpart C (15.247)**

**558074 D01 DTS Meas Guidance v03r04**

**662911 D01 Multiple Transmitter Output v02r01**

ANSI C63.10-2013

All test items have been performed and recorded as per the above standards.

Note: The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC). The test report has been issued separately.

## 4 Test Types and Results

### 4.1 Radiated Emission and Bandedge Measurement

#### 4.1.1 Limits of Radiated Emission and Bandedge Measurement

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 30dB below the highest level of the desired power:

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

**Note:**

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 30dB under any condition of modulation.



#### 4.1.2 Test Instruments

Description & Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Due
Test Receiver ROHDE & SCHWARZ	ESIB7	100187	Apr. 10, 2015	Apr. 09, 2016
Spectrum Analyzer ROHDE & SCHWARZ	FSP40	100041	Sep. 02, 2015	Sep. 01, 2016
BILOG Antenna SCHWARZBECK	VULB9168	9168-160	Feb. 05, 2015	Feb. 04, 2016
HORN Antenna SCHWARZBECK	9120D	209	Feb. 09, 2015	Feb. 08, 2016
HORN Antenna SCHWARZBECK	BBHA 9170	BBHA9170241	Feb. 09, 2015	Feb. 08, 2016
Preamplifier Agilent	8447D	2944A10738	Oct. 18, 2015	Oct. 17, 2016
Preamplifier Agilent	8449B	3008A01964	Aug. 22, 2015	Aug. 21, 2016
RF signal cable HUBER+SUHNER	SUCOFLEX 104	Cable-CH3-03 (214378)	Aug. 22, 2015	Aug. 21, 2016
RF signal cable HUBER+SUHNER	SUCOFLEX 106	Cable-CH3-03 (309224+12738)	Aug. 22, 2015	Aug. 21, 2016
Software BV ADT	ADT_Radiated_ V7.6.15.9.4	NA	NA	NA
Antenna Tower inn-co GmbH	MA 4000	013303	NA	NA
Antenna Tower Controller BV ADT	AT100	AT93021702	NA	NA
Turn Table BV ADT	TT100	TT93021702	NA	NA
Turn Table Controller BV ADT	SC100	SC93021702	NA	NA
High Speed Peak Power Meter	ML2495A	0824011	Jul. 09, 2015	Jul. 08, 2016
Power Sensor	MA2411B	0738171	Jul. 09, 2015	Jul. 08, 2016

- Note: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.  
2. The test was performed in HwaYa Chamber 3.  
3. The horn antenna and preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.  
4. The FCC Site Registration No. is 988962.  
5. The IC Site Registration No. is IC 7450F-3.

#### 4.1.3 Test Procedures

- a. The EUT was placed on the top of a rotating table 0.8 meters (for below 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

**Note:**


1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 3MHz for RMS Average (Duty cycle < 98%) for Average detection (AV) at frequency above 1GHz, then the measurement results was added to a correction factor ( $10 \log(1/\text{duty cycle})$ ).
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz (Duty cycle  $\geq 98\%$ ) for Average detection (AV) at frequency above 1GHz.
5. All modes of operation were investigated and the worst-case emissions are reported.

#### 4.1.4 Deviation from Test Standard


No deviation.

#### 4.1.5 Test Set Up

##### <Frequency Range below 1GHz>



##### <Frequency Range above 1GHz>



For the actual test configuration, please refer to the attached file (Test Setup Photo).

#### 4.1.6 EUT Operating Conditions

- Placed the EUT on the testing table.
- Prepared notebook to act as communication partner and placed it outside of testing area.
- The communication partner connected with EUT via a RJ45 cable and ran a test program (provided by manufacturer) to enable EUT under transmission condition continuously at specific channel frequency.
- The communication partner sent data to EUT by command "PING".
- The necessary accessories enable the system in full functions.

#### 4.1.7 Test Results

Above 1GHz worst-case data:

802.11b

CHANNEL	TX Channel 1	DETECTOR	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz	FUNCTION	Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2375.00	61.8 PK	74.0	-12.2	1.64 H	41	29.30	32.50
2	2375.00	52.8 AV	54.0	-1.2	1.64 H	41	20.30	32.50
3	*2412.00	118.4 PK			2.27 H	39	85.80	32.60
4	*2412.00	114.6 AV			2.27 H	39	82.00	32.60
5	4824.00	50.1 PK	74.0	-23.9	2.00 H	179	44.00	6.10
6	4824.00	38.4 AV	54.0	-15.6	2.00 H	179	32.30	6.10
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2387.00	65.1 PK	74.0	-8.9	1.37 V	295	32.60	32.50
2	2387.00	50.6 AV	54.0	-3.4	1.37 V	295	18.10	32.50
3	*2412.00	115.0 PK			1.26 V	318	82.40	32.60
4	*2412.00	111.2 AV			1.26 V	318	78.60	32.60
5	4824.00	49.6 PK	74.0	-24.4	1.60 V	277	43.50	6.10
6	4824.00	37.8 AV	54.0	-16.2	1.60 V	277	31.70	6.10

#### REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2357.00	65.9 PK	74.0	-8.1	1.61 H	36	33.50	32.40
2	2357.00	48.8 AV	54.0	-5.2	1.61 H	36	16.40	32.40
3	*2437.00	118.2 PK			1.75 H	46	85.50	32.70
4	*2437.00	114.2 AV			1.75 H	46	81.50	32.70
5	2483.50	59.9 PK	74.0	-14.1	1.52 H	31	27.20	32.70
6	2483.50	48.6 AV	54.0	-5.4	1.52 H	31	15.90	32.70
7	4874.00	46.9 PK	74.0	-27.1	1.06 H	243	40.70	6.20
8	4874.00	34.1 AV	54.0	-19.9	1.06 H	243	27.90	6.20
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2357.00	60.7 PK	74.0	-13.3	1.19 V	298	28.30	32.40
2	2357.00	48.2 AV	54.0	-5.8	1.19 V	298	15.80	32.40
3	*2437.00	113.6 PK			1.00 V	298	80.90	32.70
4	*2437.00	110.3 AV			1.00 V	298	77.60	32.70
5	2483.50	59.0 PK	74.0	-15.0	1.38 V	266	26.30	32.70
6	2483.50	47.3 AV	54.0	-6.7	1.38 V	266	14.60	32.70
7	4874.00	47.9 PK	74.0	-26.1	1.18 V	183	41.70	6.20
8	4874.00	34.9 AV	54.0	-19.1	1.18 V	183	28.70	6.20

#### REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

CHANNEL	TX Channel 11	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	116.6 PK			1.36 H	47	84.00	32.60
2	*2462.00	112.8 AV			1.36 H	47	80.20	32.60
3	2483.50	64.4 PK	74.0	-9.6	1.94 H	34	31.70	32.70
4	2483.50	52.2 AV	54.0	-1.8	1.94 H	34	19.50	32.70
5	4924.00	48.7 PK	74.0	-25.3	1.75 H	359	42.40	6.30
6	4924.00	37.1 AV	54.0	-16.9	1.75 H	359	30.80	6.30
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	112.2 PK			1.01 V	267	79.60	32.60
2	*2462.00	108.7 AV			1.01 V	267	76.10	32.60
3	2483.50	59.5 PK	74.0	-14.5	1.31 V	295	26.80	32.70
4	2483.50	47.6 AV	54.0	-6.4	1.31 V	295	14.90	32.70
5	4924.00	48.3 PK	74.0	-25.7	1.61 V	358	42.00	6.30
6	4924.00	37.6 AV	54.0	-16.4	1.61 V	358	31.30	6.30

#### REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

802.11g

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	70.6 PK	74.0	-3.4	1.62 H	34	38.10	32.50
2	2390.00	52.8 AV	54.0	-1.2	1.62 H	34	20.30	32.50
3	*2412.00	114.9 PK			2.28 H	40	82.30	32.60
4	*2412.00	105.2 AV			2.28 H	40	72.60	32.60
5	4824.00	48.6 PK	74.0	-25.4	1.77 H	256	42.50	6.10
6	4824.00	35.6 AV	54.0	-18.4	1.77 H	256	29.50	6.10
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	62.2 PK	74.0	-11.8	1.66 V	313	29.70	32.50
2	2390.00	50.9 AV	54.0	-3.1	1.66 V	313	18.40	32.50
3	*2412.00	111.0 PK			1.27 V	320	78.40	32.60
4	*2412.00	102.0 AV			1.27 V	320	69.40	32.60
5	4824.00	48.3 PK	74.0	-25.7	1.23 V	296	42.20	6.10
6	4824.00	35.3 AV	54.0	-18.7	1.23 V	296	29.20	6.10

## REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	68.2 PK	74.0	-5.8	1.60 H	45	35.70	32.50
2	2390.00	51.2 AV	54.0	-2.8	1.60 H	45	18.70	32.50
3	*2437.00	120.6 PK			2.22 H	38	87.90	32.70
4	*2437.00	111.0 AV			2.22 H	38	78.30	32.70
5	2483.50	71.3 PK	74.0	-2.7	1.67 H	37	38.60	32.70
6	2483.50	52.4 AV	54.0	-1.6	1.67 H	37	19.70	32.70
7	4874.00	49.5 PK	74.0	-24.5	1.50 H	96	43.30	6.20
8	4874.00	36.5 AV	54.0	-17.5	1.50 H	96	30.30	6.20
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	66.2 PK	74.0	-7.8	1.19 V	319	33.70	32.50
2	2390.00	50.3 AV	54.0	-3.7	1.19 V	319	17.80	32.50
3	*2437.00	117.2 PK			1.06 V	317	84.50	32.70
4	*2437.00	107.8 AV			1.06 V	317	75.10	32.70
5	2483.50	61.4 PK	74.0	-12.6	1.85 V	303	28.70	32.70
6	2483.50	49.3 AV	54.0	-4.7	1.85 V	303	16.60	32.70
7	4874.00	49.8 PK	74.0	-24.2	1.21 V	261	43.60	6.20
8	4874.00	36.7 AV	54.0	-17.3	1.21 V	261	30.50	6.20

#### REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* " : Fundamental frequency.



CHANNEL	TX Channel 11	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	113.4 PK			2.16 H	45	80.80	32.60
2	*2462.00	103.9 AV			2.16 H	45	71.30	32.60
3	2483.50	72.6 PK	74.0	-1.4	1.71 H	47	39.90	32.70
4	2483.50	51.4 AV	54.0	-2.6	1.71 H	47	18.70	32.70
5	4924.00	48.9 PK	74.0	-25.1	1.48 H	244	42.60	6.30
6	4924.00	36.0 AV	54.0	-18.0	1.48 H	244	29.70	6.30
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	110.8 PK			1.16 V	315	78.20	32.60
2	*2462.00	101.3 AV			1.16 V	315	68.70	32.60
3	2483.50	70.0 PK	74.0	-4.0	1.35 V	322	37.30	32.70
4	2483.50	49.1 AV	54.0	-4.9	1.35 V	322	16.40	32.70
5	4924.00	47.8 PK	74.0	-26.2	1.11 V	299	41.50	6.30
6	4924.00	34.6 AV	54.0	-19.4	1.11 V	299	28.30	6.30

#### REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

## 802.11n (HT20)

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	72.5 PK	74.0	-1.5	1.47 H	23	40.00	32.50
2	2390.00	51.8 AV	54.0	-2.2	1.47 H	23	19.30	32.50
3	*2412.00	113.2 PK			1.98 H	35	80.60	32.60
4	*2412.00	103.9 AV			1.98 H	35	71.30	32.60
5	4824.00	48.4 PK	74.0	-25.6	1.72 H	77	42.30	6.10
6	4824.00	35.5 AV	54.0	-18.5	1.72 H	77	29.40	6.10
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	67.3 PK	74.0	-6.7	1.21 V	318	34.80	32.50
2	2390.00	49.8 AV	54.0	-4.2	1.21 V	318	17.30	32.50
3	*2412.00	110.2 PK			1.10 V	319	77.60	32.60
4	*2412.00	100.9 AV			1.10 V	319	68.30	32.60
5	4824.00	48.0 PK	74.0	-26.0	1.43 V	230	41.90	6.10
6	4824.00	34.9 AV	54.0	-19.1	1.43 V	230	28.80	6.10

## REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* " : Fundamental frequency.

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	69.4 PK	74.0	-4.6	1.60 H	37	36.90	32.50
2	2390.00	52.1 AV	54.0	-1.9	1.60 H	37	19.60	32.50
3	*2437.00	119.0 PK			2.20 H	30	86.30	32.70
4	*2437.00	109.7 AV			2.20 H	30	77.00	32.70
5	2483.50	70.4 PK	74.0	-3.6	1.75 H	45	37.70	32.70
6	2483.50	52.4 AV	54.0	-1.6	1.75 H	45	19.70	32.70
7	4874.00	49.7 PK	74.0	-24.3	1.53 H	149	43.50	6.20
8	4874.00	36.4 AV	54.0	-17.6	1.53 H	149	30.20	6.20
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	67.8 PK	74.0	-6.2	1.35 V	320	35.30	32.50
2	2390.00	50.1 AV	54.0	-3.9	1.35 V	320	17.60	32.50
3	*2437.00	117.6 PK			1.05 V	315	84.90	32.70
4	*2437.00	107.5 AV			1.05 V	315	74.80	32.70
5	2483.50	67.6 PK	74.0	-6.4	1.36 V	319	34.90	32.70
6	2483.50	49.8 AV	54.0	-4.2	1.36 V	319	17.10	32.70
7	4874.00	48.7 PK	74.0	-25.3	1.23 V	34	42.50	6.20
8	4874.00	35.7 AV	54.0	-18.3	1.23 V	34	29.50	6.20

#### REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

CHANNEL	TX Channel 11	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	113.6 PK			2.44 H	40	81.00	32.60
2	*2462.00	103.9 AV			2.44 H	40	71.30	32.60
3	2483.50	72.4 PK	74.0	-1.6	1.65 H	37	39.70	32.70
4	2483.50	51.4 AV	54.0	-2.6	1.65 H	37	18.70	32.70
5	4924.00	48.3 PK	74.0	-25.7	1.36 H	243	42.00	6.30
6	4924.00	35.3 AV	54.0	-18.7	1.36 H	243	29.00	6.30
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	110.3 PK			1.16 V	310	77.70	32.60
2	*2462.00	101.2 AV			1.16 V	310	68.60	32.60
3	2483.50	63.4 PK	74.0	-10.6	1.37 V	315	30.70	32.70
4	2483.50	48.3 AV	54.0	-5.7	1.37 V	315	15.60	32.70
5	4924.00	47.7 PK	74.0	-26.3	1.50 V	286	41.40	6.30
6	4924.00	34.4 AV	54.0	-19.6	1.50 V	286	28.10	6.30

#### REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

## 802.11n (HT40)

CHANNEL	TX Channel 3	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	70.5 PK	74.0	-3.5	1.59 H	42	38.00	32.50
2	2390.00	52.3 AV	54.0	-1.7	1.59 H	42	19.80	32.50
3	*2422.00	108.1 PK			2.00 H	43	75.50	32.60
4	*2422.00	98.6 AV			2.00 H	43	66.00	32.60
5	4844.00	48.0 PK	74.0	-26.0	1.78 H	80	41.90	6.10
6	4844.00	35.0 AV	54.0	-19.0	1.78 H	80	28.90	6.10
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	68.2 PK	74.0	-5.8	1.36 V	319	35.70	32.50
2	2390.00	51.8 AV	54.0	-2.2	1.36 V	319	19.30	32.50
3	*2422.00	105.5 PK			1.06 V	318	72.90	32.60
4	*2422.00	95.5 AV			1.06 V	318	62.90	32.60
5	4844.00	47.2 PK	74.0	-26.8	1.26 V	19	41.10	6.10
6	4844.00	34.2 AV	54.0	-19.8	1.26 V	19	28.10	6.10

## REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* " : Fundamental frequency.

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	69.0 PK	74.0	-5.0	1.28 H	0	36.50	32.50
2	2390.00	52.0 AV	54.0	-2.0	1.28 H	0	19.50	32.50
3	*2437.00	111.7 PK			2.24 H	42	79.00	32.70
4	*2437.00	101.6 AV			2.24 H	42	68.90	32.70
5	2483.50	71.0 PK	74.0	-3.0	1.63 H	35	38.30	32.70
6	2483.50	52.8 AV	54.0	-1.2	1.63 H	35	20.10	32.70
7	4874.00	47.7 PK	74.0	-26.3	1.60 H	178	41.50	6.20
8	4874.00	34.6 AV	54.0	-19.4	1.60 H	178	28.40	6.20
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	65.8 PK	74.0	-8.2	1.35 V	322	33.30	32.50
2	2390.00	50.8 AV	54.0	-3.2	1.35 V	322	18.30	32.50
3	*2437.00	109.3 PK			1.11 V	314	76.60	32.70
4	*2437.00	99.4 AV			1.11 V	314	66.70	32.70
5	2483.50	68.2 PK	74.0	-5.8	1.34 V	297	35.50	32.70
6	2483.50	51.5 AV	54.0	-2.5	1.34 V	297	18.80	32.70
7	4874.00	47.4 PK	74.0	-26.6	1.20 V	289	41.20	6.20
8	4874.00	34.2 AV	54.0	-19.8	1.20 V	289	28.00	6.20

#### REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

CHANNEL	TX Channel 9	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2452.00	109.3 PK			1.99 H	43	76.60	32.70
2	*2452.00	99.2 AV			1.99 H	43	66.50	32.70
3	2483.50	69.8 PK	74.0	-4.2	1.52 H	43	37.10	32.70
4	<b>2483.50</b>	<b>53.2 AV</b>	<b>54.0</b>	<b>-0.8</b>	<b>1.52 H</b>	<b>43</b>	<b>20.50</b>	<b>32.70</b>
5	4904.00	47.3 PK	74.0	-26.7	1.80 H	353	41.20	6.10
6	4904.00	34.5 AV	54.0	-19.5	1.80 H	353	28.40	6.10
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2452.00	105.5 PK			1.01 V	322	72.80	32.70
2	*2452.00	96.1 AV			1.01 V	322	63.40	32.70
3	2483.50	67.2 PK	74.0	-6.8	1.35 V	310	34.50	32.70
4	2483.50	50.7 AV	54.0	-3.3	1.35 V	310	18.00	32.70
5	4904.00	47.0 PK	74.0	-27.0	1.29 V	122	40.90	6.10
6	4904.00	33.9 AV	54.0	-20.1	1.29 V	122	27.80	6.10

#### REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

# BELOW 1GHz WORST-CASE DATA

802.11g

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	30MHz ~ 1GHz		
TEST MODE	A		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	144.61	35.3 QP	43.5	-8.2	1.99 H	243	49.50	-14.20
2	327.38	42.7 QP	46.0	-3.3	1.00 H	294	54.40	-11.70
3	368.21	43.4 QP	46.0	-2.6	1.00 H	294	54.60	-11.20
4	395.43	40.9 QP	46.0	-5.1	1.00 H	289	51.70	-10.80
5	690.96	42.6 QP	46.0	-3.4	1.00 H	144	47.10	-4.50
6	741.51	41.2 QP	46.0	-4.8	1.00 H	307	44.50	-3.30
7	757.06	40.5 QP	46.0	-5.5	1.00 H	313	43.50	-3.00
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	57.12	33.3 QP	40.0	-6.7	1.50 V	16	48.10	-14.80
2	333.21	39.0 QP	46.0	-7.0	1.50 V	290	50.80	-11.80
3	652.07	40.8 QP	46.0	-5.2	1.00 V	5	46.00	-5.20
4	686.93	42.4 QP	46.0	-3.6	1.00 V	126	46.90	-4.50
5	731.79	42.2 QP	46.0	-3.8	1.50 V	90	45.70	-3.50
6	755.12	40.4 QP	46.0	-5.6	1.00 V	145	43.40	-3.00

## REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value



CHANNEL	TX Channel 6	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	30MHz ~ 1GHz		
TEST MODE	B		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	57.12	30.9 QP	40.0	-9.1	2.00 H	6	45.70	-14.80
2	90.17	28.2 QP	43.5	-15.3	2.00 H	250	48.10	-19.90
3	140.72	26.8 QP	43.5	-16.7	2.00 H	233	41.40	-14.60
4	169.89	27.8 QP	43.5	-15.7	1.50 H	76	42.10	-14.30
5	202.94	28.1 QP	43.5	-15.4	1.00 H	248	44.90	-16.80
6	725.96	34.8 QP	46.0	-11.2	1.00 H	177	38.50	-3.70
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	36.53	35.5 QP	40.0	-4.5	1.00 V	26	51.10	-15.60
2	49.85	34.6 QP	40.0	-5.4	1.00 V	20	49.20	-14.60
3	70.73	32.8 QP	40.0	-7.2	1.00 V	270	49.10	-16.30
4	171.83	26.8 QP	43.5	-16.7	1.00 V	102	41.30	-14.50
5	201.00	33.0 QP	43.5	-10.5	1.00 V	282	49.80	-16.80
6	720.12	31.2 QP	46.0	-14.8	1.50 V	17	35.20	-4.00

#### REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value

## 4.2 Conducted Emission Measurement

### 4.2.1 Limits of Conducted Emission Measurement

Frequency (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15 - 0.5	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30.0	60	50

**Note:** 1. The lower limit shall apply at the transition frequencies.  
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

### 4.2.2 Test Instruments

Description & Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Due
Test Receiver ROHDE & SCHWARZ	ESCI	100613	Nov. 16, 2015	Nov. 15, 2016
RF signal cable (with 10dB PAD) Woken	5D-FB	Cable-cond1-01	Dec. 26, 2014	Dec. 25, 2015
LISN ROHDE & SCHWARZ (EUT)	ESH3-Z5	835239/001	Feb. 26, 2015	Feb. 25, 2016
LISN ROHDE & SCHWARZ (Peripheral)	ESH3-Z5	100311	Jul. 24, 2015	Jul. 23, 2016
Software ADT	BV ADT_Conc_ V7.3.7.3	NA	NA	NA

**Note:** 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.  
2. The test was performed in HwaYa Shielded Room 1.  
3. The VCCI Site Registration No. is C-2040.

#### 4.2.3 Test Procedures


- The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

**Note:** The resolution bandwidth and video bandwidth of test receiver is 9kHz for quasi-peak detection (QP) and average detection (AV) at frequency 0.15MHz-30MHz.

#### 4.2.4 Deviation from Test Standard

No deviation.

#### 4.2.5 Test Setup



**Note:** 1.Support units were connected to second LISN.

For the actual test configuration, please refer to the attached file (Test Setup Photo).

#### 4.2.6 EUT Operating Conditions

Same as 4.1.6.

## 4.2.7 Test Results


Worst-case data: 802.11g

Phase	Line (L)	Detector Function	Quasi-Peak (QP) / Average (AV)
Test Mode	A		

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.16173	9.86	38.32	25.74	48.18	35.60	65.37	55.37	-17.19	-19.77
2	0.18910	9.91	32.16	22.54	42.07	32.45	64.08	54.08	-22.01	-21.63
3	0.23211	9.93	29.53	21.11	39.46	31.04	62.37	52.37	-22.92	-21.34
4	<b>0.29897</b>	<b>9.92</b>	<b>29.66</b>	<b>26.27</b>	<b>39.58</b>	<b>36.19</b>	<b>60.27</b>	<b>50.27</b>	<b>-20.70</b>	<b>-14.09</b>
5	0.41979	9.90	15.50	9.67	25.40	19.57	57.45	47.45	-32.05	-27.88
6	8.20069	10.44	15.31	7.63	25.75	18.07	60.00	50.00	-34.25	-31.93

### Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




Phase	Neutral (N)	Detector Function	Quasi-Peak (QP) / Average (AV)
Test Mode	A		

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15719	9.91	35.11	24.15	45.02	34.06	65.61	55.61	-20.59	-21.55
2	0.18128	9.98	32.87	20.09	42.85	30.07	64.43	54.43	-21.58	-24.36
3	0.20865	10.03	32.09	20.76	42.12	30.79	63.26	53.26	-21.14	-22.47
4	0.27903	10.01	26.12	17.53	36.13	27.54	60.84	50.84	-24.71	-23.30
5	0.97501	10.03	11.84	8.98	21.87	19.01	56.00	46.00	-34.13	-26.99
6	8.45093	10.52	15.49	8.44	26.01	18.96	60.00	50.00	-33.99	-31.04

#### Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




Phase	Line (L)	Detector Function	Quasi-Peak (QP) / Average (AV)
Test Mode	B		

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15000	9.84	31.36	23.19	41.20	33.03	66.00	56.00	-24.80	-22.97
2	0.19305	9.92	23.73	11.13	33.65	21.05	63.90	53.90	-30.26	-32.86
3	0.22429	9.93	20.51	12.13	30.44	22.06	62.66	52.66	-32.22	-30.60
4	0.44325	9.91	18.94	11.20	28.85	21.11	57.00	47.00	-28.15	-25.89
5	1.54587	10.07	15.07	6.68	25.14	16.75	56.00	46.00	-30.86	-29.25
6	20.19266	11.16	13.87	6.55	25.03	17.71	60.00	50.00	-34.97	-32.29

#### Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




Phase	Neutral (N)	Detector Function	Quasi-Peak (QP) / Average (AV)
Test Mode	B		

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15000	9.89	31.68	23.50	41.57	33.39	66.00	56.00	-24.43	-22.61
2	0.18128	9.98	26.02	14.15	36.00	24.13	64.43	54.43	-28.43	-30.30
3	0.22434	10.03	21.75	14.33	31.78	24.36	62.66	52.66	-30.88	-28.30
4	0.45816	9.99	19.65	13.11	29.64	23.10	56.73	46.73	-27.08	-23.62
5	4.48619	10.35	16.21	10.44	26.56	20.79	56.00	46.00	-29.44	-25.21
6	20.30214	11.06	16.27	8.90	27.33	19.96	60.00	50.00	-32.67	-30.04

#### Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




### 4.3 6dB Bandwidth Measurement

#### 4.3.1 Limits of 6dB Bandwidth Measurement

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

#### 4.3.2 Test Setup



#### 4.3.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

#### 4.3.4 Test Procedure

- Set resolution bandwidth (RBW) = 100kHz
- Set the video bandwidth (VBW)  $\geq 3 \times$  RBW, Detector = Peak.
- Trace mode = max hold.
- Sweep = auto couple.
- Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission

#### 4.3.5 Deviation from Test Standard

No deviation.

#### 4.3.6 EUT Operating Conditions

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.



#### 4.3.7 Test Result

##### 802.11b

Channel	Frequency (MHz)	6dB Bandwidth (MHz)		Minimum Limit (MHz)	Pass / Fail
		Chain 0	Chain 1		
1	2412	10.10	10.10	0.5	Pass
6	2437	10.12	10.11	0.5	Pass
11	2462	10.12	10.12	0.5	Pass

##### 802.11g

Channel	Frequency (MHz)	6dB Bandwidth (MHz)		Minimum Limit (MHz)	Pass / Fail
		Chain 0	Chain 1		
1	2412	16.39	16.41	0.5	Pass
6	2437	16.37	16.36	0.5	Pass
11	2462	16.37	16.40	0.5	Pass

##### 802.11n (HT20)

Channel	Frequency (MHz)	6dB Bandwidth (MHz)		Minimum Limit (MHz)	Pass / Fail
		Chain 0	Chain 1		
1	2412	17.60	17.62	0.5	Pass
6	2437	17.59	17.11	0.5	Pass
11	2462	17.59	17.61	0.5	Pass


##### 802.11n (HT40)

Channel	Frequency (MHz)	6dB Bandwidth (MHz)		Minimum Limit (MHz)	Pass / Fail
		Chain 0	Chain 1		
3	2422	36.40	36.41	0.5	Pass
6	2437	36.12	35.91	0.5	Pass
9	2452	36.12	36.14	0.5	Pass


# Spectrum Plot of Worst Value

802.11b

802.11g




A D T




A D T

802.11n (HT20)

802.11n (HT40)



A D T



A D T

## 4.4 Conducted Output Power Measurement

### 4.4.1 Limits of Conducted Output Power Measurement

For systems using digital modulation in the 2400–2483.5 MHz bands: 1 Watt (30dBm)

Per KDB 662911 D01 Multiple Transmitter Output Method of conducted output power measurement on IEEE 802.11 devices,


Array Gain = 0 dB (i.e., no array gain) for  $NANT \leq 4$ ;

Array Gain = 0 dB (i.e., no array gain) for channel widths  $\geq 40$  MHz for any NANT;

Array Gain =  $5 \log(NANT/NSS)$  dB or 3 dB, whichever is less for 20-MHz channel widths with  $NANT \geq 5$ .

For power measurements on all other devices: Array Gain =  $10 \log(NANT/NSS)$  dB.

### 4.4.2 Test Setup



### 4.4.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

### 4.4.4 Test Procedures

An average power sensor was used on the output port of the EUT. A power meter was used to read the response of the average power sensor. Record the power level.

### 4.4.5 Deviation from Test Standard

No deviation.

### 4.4.6 EUT Operating Conditions

Same as Item 4.3.6.

#### 4.4.7 Test Results

##### 802.11b

Channel	Frequency (MHz)	Average Power (dBm)		Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1				
1	2412	23.33	22.56	395.58	25.97	30	Pass
6	2437	23.59	22.50	406.388	26.09	30	Pass
11	2462	23.16	22.61	389.404	25.90	30	Pass

##### 802.11g

Channel	Frequency (MHz)	Average Power (dBm)		Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1				
1	2412	18.60	18.32	140.364	21.47	30	Pass
6	2437	23.50	22.93	<b>420.208</b>	26.23	30	Pass
11	2462	18.19	17.48	121.893	20.86	30	Pass

##### 802.11n (HT20)

Channel	Frequency (MHz)	Average Power (dBm)		Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1				
1	2412	18.22	17.73	125.667	20.99	30	Pass
6	2437	23.47	22.71	408.969	26.12	30	Pass
11	2462	17.73	17.44	114.756	20.60	30	Pass

##### 802.11n (HT40)


Channel	Frequency (MHz)	Average Power (dBm)		Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1				
3	2422	14.72	14.48	57.702	17.61	30	Pass
6	2437	19.19	18.74	157.802	21.98	30	Pass
9	2452	15.54	15.27	69.461	18.42	30	Pass

## 4.5 Power Spectral Density Measurement

### 4.5.1 Limits of Power Spectral Density Measurement

The Maximum of Power Spectral Density Measurement is 8dBm.

### 4.5.2 Test Setup



### 4.5.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

### 4.5.4 Test Procedure

For duty cycle  $\geq 98\%$

- Set instrument center frequency to DTS channel center frequency.
- Set span to at least 1.5 times the OBW.
- Set RBW to:  $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$ .
- Set VBW  $\geq 3 \times \text{RBW}$ .
- Detector = power averaging (RMS) or sample detector (when RMS not available).
- Ensure that the number of measurement points in the sweep  $\geq 2 \times \text{span}/\text{RBW}$ .
- Sweep time = auto couple.
- Employ trace averaging (RMS) mode over a minimum of 100 traces.
- Use the peak marker function to determine the maximum amplitude level.

For duty cycle  $< 98\%$

- Measure the duty cycle (x).
- Set instrument center frequency to DTS channel center frequency.
- Set span to at least 1.5 times the OBW.
- Set RBW to:  $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$ .
- Set VBW  $\geq 3 \times \text{RBW}$ .
- Detector = power averaging (RMS) or sample detector (when RMS not available).
- Ensure that the number of measurement points in the sweep  $\geq 2 \times \text{span}/\text{RBW}$ .
- Sweep time = auto couple.
- Do not use sweep triggering. Allow sweep to “free run”.
- Employ trace averaging (RMS) mode over a minimum of 100 traces.
- Use the peak marker function to determine the maximum amplitude level.
- Add  $10 \log (1/x)$ , where x is the duty cycle measured in step (a), to the measured PSD to compute the average PSD during the actual transmission time.

#### **4.5.5 Deviation from Test Standard**

No deviation.

#### **4.5.6 EUT Operating Condition**

Same as Item 4.3.6

#### 4.5.7 Test Results

##### 802.11b

TX chain	Channel	Frequency (MHz)	PSD (dBm)	10 log (N=2) dB	Total PSD (dBm)	Limit (dBm)	Pass / Fail
0	1	2412	-5.51	3.01	-2.50	7.47	Pass
	6	2437	-4.52	3.01	-1.51	7.47	Pass
	11	2462	-5.08	3.01	-2.07	7.47	Pass
1	1	2412	-5.93	3.01	-2.92	7.47	Pass
	6	2437	-5.37	3.01	-2.36	7.47	Pass
	11	2462	-5.22	3.01	-2.21	7.47	Pass

Note:

- Method 1 of power density measurement of KDB 662911 is using for calculating total power density. Total power density is summing entire spectra across corresponding frequency bins on the various outputs by computer.
- Directional gain =  $3.52\text{dBi} + 10\log(2) = 6.53\text{dBi} > 6\text{dBi}$ , so the power density limit shall be reduced to  $8 - (6.53 - 6) = 7.47\text{dBm}$ .

##### 802.11g

TX chain	Channel	Frequency (MHz)	PSD (dBm)	10 log (N=2) dB	Duty Factor	Total PSD with Duty Factor (dBm)	Limit (dBm)	Pass / Fail
0	1	2412	-12.16	3.01	0.15	-9.00	7.47	Pass
	6	2437	-7.32	3.01	0.15	-4.16	7.47	Pass
	11	2462	-10.92	3.01	0.15	-7.76	7.47	Pass
1	1	2412	-9.29	3.01	0.15	-6.13	7.47	Pass
	6	2437	-7.54	3.01	0.15	-4.38	7.47	Pass
	11	2462	-10.65	3.01	0.15	-7.49	7.47	Pass

Note:

- Method 1 of power density measurement of KDB 662911 is using for calculating total power density. Total power density is summing entire spectra across corresponding frequency bins on the various outputs by computer.
- Directional gain =  $3.52\text{dBi} + 10\log(2) = 6.53\text{dBi} > 6\text{dBi}$ , so the power density limit shall be reduced to  $8 - (6.53 - 6) = 7.47\text{dBm}$ .
- Refer to section 3.3 for duty cycle spectrum plot.

### 802.11n (HT20)

TX chain	Channel	Frequency (MHz)	PSD (dBm)	10 log (N=2) dB	Duty Factor	Total PSD with Duty Factor (dBm)	Limit (dBm)	Pass / Fail
0	1	2412	-13.40	3.01	0.12	-10.27	7.47	Pass
	6	2437	-7.87	3.01	0.12	-4.74	7.47	Pass
	11	2462	-9.01	3.01	0.12	-5.88	7.47	Pass
1	1	2412	-8.80	3.01	0.12	-5.67	7.47	Pass
	6	2437	-8.22	3.01	0.12	-5.09	7.47	Pass
	11	2462	-11.64	3.01	0.12	-8.51	7.47	Pass

Note:

1. Method 1 of power density measurement of KDB 662911 is using for calculating total power density. Total power density is summing entire spectra across corresponding frequency bins on the various outputs by computer.
2. Directional gain =  $3.52\text{dBi} + 10\log(2) = 6.53\text{dBi} > 6\text{dBi}$ , so the power density limit shall be reduced to  $8-(6.53-6) = 7.47\text{dBm}$ .
3. Refer to section 3.3 for duty cycle spectrum plot.

### 802.11n (HT40)

TX chain	Channel	Frequency (MHz)	PSD (dBm)	10 log (N=2) dB	Duty Factor	Total PSD with Duty Factor (dBm)	Limit (dBm)	Pass / Fail
0	3	2422	-18.60	3.01	0.20	-15.39	7.47	Pass
	6	2437	-14.17	3.01	0.20	-10.96	7.47	Pass
	9	2452	-18.04	3.01	0.20	-14.83	7.47	Pass
1	3	2422	-18.72	3.01	0.20	-15.51	7.47	Pass
	6	2437	-14.34	3.01	0.20	-11.13	7.47	Pass
	9	2452	-18.14	3.01	0.20	-14.93	7.47	Pass

Note:


1. Method 1 of power density measurement of KDB 662911 is using for calculating total power density. Total power density is summing entire spectra across corresponding frequency bins on the various outputs by computer.
2. Directional gain =  $3.52\text{dBi} + 10\log(2) = 6.53\text{dBi} > 6\text{dBi}$ , so the power density limit shall be reduced to  $8-(6.53-6) = 7.47\text{dBm}$ .
3. Refer to section 3.3 for duty cycle spectrum plot.




# Spectrum Plot of Worst Value

802.11b

802.11g




A D T




A D T

802.11n (HT20)

802.11n (HT40)



A D T




A D T

## 4.6 Conducted Out of Band Emission Measurement

### 4.6.1 Limits of Conducted Out of Band Emission Measurement

Below 30dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

### 4.6.2 Test Setup



### 4.6.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

### 4.6.4 Test Procedure

#### MEASUREMENT PROCEDURE REF

- Set the RBW = 100 kHz.
- Set the VBW  $\geq$  300 kHz.
- Detector = average.
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.

#### MEASUREMENT PROCEDURE OOB

- Set RBW = 100 kHz.
- Set VBW  $\geq$  300 kHz.
- Ensure that the number of measurement points  $\geq$  span/RBW
- According to measurement points to set differ measurement span.
- Detector = peak.
- Trace Mode = max hold.
- Sweep = auto couple.

#### **4.6.5 Deviation from Test Standard**

No deviation.

#### **4.6.6 EUT Operating Condition**


Same as Item 4.3.6

#### **4.6.7 Test Results**


The spectrum plots are attached on the following pages. D1 line indicates the highest level, and D2 line indicates the 30dB offset below D1. It shows compliance with the requirement.

## 802.11b\_Chain 0


## CH 1




## CH 6




## CH 11



## CH 1 Band edge



## CH 11 Band edge







A D T

## 802.11b\_Chain 1

## CH 1




A D T




A D T

## CH 6




A D T




A D T

## CH 11




A D T




A D T

## CH 1 Band edge



A D T


## CH 11 Band edge




A D T

# 802.11g\_Chain 0


## CH 1




## CH 6




## CH 11



## CH 1 Band edge





## CH 11 Band edge





# 802.11g\_Chain 1



## CH 1




## CH 6




## CH 11



## CH 1 Band edge



## CH 11 Band edge









A D T

## 802.11n (HT20)\_Chain 0



### CH 1




### CH 6




### CH 11



### CH 1 Band edge





### CH 11 Band edge







# 802.11n (HT20)\_Chain 1



## CH 1




## CH 6




## CH 11



## CH 1 Band edge




## CH 11 Band edge




# 802.11n (HT40)\_Chain 0


## CH 3




## CH 6




## CH 9



## CH 3 Band edge



## CH 9 Band edge







A D T

## 802.11n (HT40)\_Chain 1


## CH 3




## CH 6




## CH 9



## CH 3 Band edge



## CH 9 Band edge



## 5 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo).

## Appendix – Information on the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

**Linko EMC/RF Lab**

Tel: 886-2-26052180

Fax: 886-2-26051924

**Hsin Chu EMC/RF/Telecom Lab**

Tel: 886-3-5935343

Fax: 886-3-5935342

**Hwa Ya EMC/RF/Safety Lab**

Tel: 886-3-3183232

Fax: 886-3-3270892

**Email:** [service.adt@tw.bureauveritas.com](mailto:service.adt@tw.bureauveritas.com)

**Web Site:** [www.bureauveritas-adt.com](http://www.bureauveritas-adt.com)

The address and road map of all our labs can be found in our web site also.

--- END ---