FCC ID: 2AG8JTB8

RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency	Electric Field	Magnetic Field Power		Average Time		
Range(MHz)	Strength(V/m)	Strength(A/m)	Density(mW/cm ²)	_		
(A) Limits for Occupational/Control Exposures						
300-1500		F/300		6		
1500-100000			5	6		
(B) Limits for General Population/Uncontrol Exposures						
300-1500		F/1500		6		
1500-100000			1	30		

11.1 Friis transmission formula: Pd= (Pout*G)\ (4*pi*R²)

Where

Pd= Power density in mW/cm²

Pout=output power to antenna in mW

G= Numeric gain of the antenna relative to isotropic antenna

Pi=3.1416

R= distance between observation point and center of the radiator in cm

Pd the limit of MPE, 1mW/cm², If we know the maximum gain of the nd total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

11.2 Measurement Result

Wifi mode: AP6212 Antenna gain: 4.93dBi

modulation	Channel Freq. (MHz)	Measured power (dBm)	Tune-up power (dBm)	Max tune-up power (dBm)	Antenna Gain Numeric	Evaluation result (mW/cm2)	Power density Limits (mW/cm2)
11b	2412	15.44	14 to 16	16	3.11	0.024631	1
	2437	14.86	13 to 15	15	3.11	0.019565	1
	2462	14.61	13 to 15	15	3.11	0.019565	1
11g	2412	14.39	13 to 15	15	3.11	0.019564	1
	2437	14.24	13 to 15	15	3.11	0.019564	1
	2462	14.10	13 to 15	15	3.11	0.019564	1
11n HT20	2412	14.56	13 to 15	15	3.11	0.019564	1
	2437	14.43	13 to 15	15	3.11	0.019564	1
	2462	14.13	13 to 15	15	3.11	0.019564	1

Wifi mode: RTL8188EUS Antenna gain: 4.93dBi

modulation	Channel Freq. (MHz)	Measured power (dBm)	Tune-up power (dBm)	Max tune-up power (dBm)	Antenna Gain Numeric	Evaluation result (mW/cm2)	Power density Limits (mW/cm2)
11b	2412	15.44	14 to 16	16	3.11	0.024631	1
	2437	16.14	15 to 17	17	3.11	0.031009	1
	2462	16.94	15 to 17	17	3.11	0.031009	1
11g	2412	14.85	13 to 15	15	3.11	0.019564	1
	2437	15.94	14 to 16	16	3.11	0.024631	1
	2462	16.98	15 to 17	17	3.11	0.031010	1
11n HT20	2412	14.97	13 to 15	15	3.11	0.019564	1
	2437	15.97	14 to 16	16	3.11	0.024631	1
	2462	16.82	15 to 17	17	3.11	0.031010	1