

## RF EXPOSURE EVALUATION

### EUT Specification

<b>EUT</b>	<b>Waterproof MP3 Radio Receiver</b>
<b>Frequency band (Operating)</b>	<input type="checkbox"/> WLAN: 2.412GHz ~ 2.462GHz <input type="checkbox"/> WLAN: 5.18GHz ~ 5.32GHz / 5.50GHz ~ 5.70GHz <input type="checkbox"/> WLAN: 5.745GHz ~ 5.825GHz <input checked="" type="checkbox"/> Others(Bluetooth: 2.402GHz ~ 2.480GHz)
<b>Device category</b>	<input type="checkbox"/> Portable (<20cm separation) <input checked="" type="checkbox"/> Mobile (>20cm separation) <input type="checkbox"/> Others ____
<b>Antenna diversity</b>	<input checked="" type="checkbox"/> Single antenna <input type="checkbox"/> Multiple antennas <input type="checkbox"/> Tx diversity <input type="checkbox"/> Rx diversity <input type="checkbox"/> Tx/Rx diversity
<b>Max. output power</b>	-1.08dBm(0.78mW)
<b>Antenna gain</b>	0dBi
<b>Evaluation applied</b>	<input checked="" type="checkbox"/> MPE Evaluation <input type="checkbox"/> SAR Evaluation

Limits for Maximum Permissible Exposure (MPE)

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density(mW/cm <sup>2</sup> )	Average Time
<b>(A) Limits for Occupational/Control Exposures</b>				
<b>300-1500</b>	--	--	<b>F/300</b>	<b>6</b>
<b>1500-100000</b>	--	--	<b>5</b>	<b>6</b>
<b>(B) Limits for General Population/Uncontrol Exposures</b>				
<b>300-1500</b>	--	--	<b>F/1500</b>	<b>6</b>
<b>1500-100000</b>	--	--	<b>1</b>	<b>30</b>

## Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

$P_d$  = Power density in  $mW/cm^2$

$P_{out}$  = output power to antenna in Mw

$G$  = gain of antenna in linear scale

$\pi = 3.1416$

$R$  = distance between observation point and center of the radiator in cm

$P_d$  the limit of MPE,  $1mW/cm^2$ . If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

## Measurement Result

Channel	Channel Frequency (MHz)	Max Output power (dBm)	Tolerance	Max Tune-UP power (mW)	Power density at 20cm ( $mW/cm^2$ )	Power density Limits ( $mW/cm^2$ )
Test mode: GFSK						
Low	2402	-3.29	$\pm 0.1$	0.48	$9.54e-5$	1
Middle	2441	-2.10	$\pm 0.1$	0.63	$1.26e-4$	1
High	2480	-1.08	$\pm 0.1$	0.80	$1.59e-4$	1
Test mode: $\pi/4$ -DQPSK						
Low	2402	-4.93	$\pm 0.1$	0.33	$6.54e-5$	1
Middle	2441	-3.81	$\pm 0.1$	0.43	$8.47e-5$	1
High	2480	-2.89	$\pm 0.1$	0.53	$1.05e-4$	1
Test mode: 8DPSK						
Low	2402	-4.57	$\pm 0.1$	0.36	$7.11e-5$	1
Middle	2441	-3.31	$\pm 0.1$	0.48	$9.50e-5$	1
High	2480	-2.26	$\pm 0.1$	0.61	$1.21e-4$	1

**Remark: Both of transmitters can not transmit simultaneously.**

**According to KDB447498 D01 V06, no simultaneous SAR measurement is required.**