RF Exposure Evaluation Declaration

Product Name	:	LED lamp
Model No.	:	9290022166
FCC ID	:	2AGBW9290022166X
IC	:	20812-2166X

Applicant	:	Signify (China) Investment Co., Ltd.
Address	:	Building no.9, Lane 888, Tianlin Road, Minhang District, Shanghai 200233, China

Date of Receipt	:	May. 22, 2019
Issued Date	:	May. 24, 2019
Report No.	:	1952138R-RF-US-P20V01
Report Version	:	V 1.0

The test results relate only to the samples tested.
The test results shown in the test report are traceable to the national/international standard through the calibration of the equipment and evaluated measurement uncertainty herein.
This report must not be used to claim product endorsement by A2LA or any agency of the government.
The test report shall not be reproduced without the written approval of DEKRA Testing & Certification (Suzhou) Co., Ltd.

Test Report Certification

Issued Date : May. 24, 2019
Report No. : 1952138R-RF-US-P20V01

Product Name	:	LED lamp
Applicant	:	Signify (China) Investment Co., Ltd.
Address	:	Building no.9, Lane 888, Tianlin Road, Minhang District, Shanghai 200233, China
Manufacturer	:	Signify (China) Investment Co., Ltd.
Address	:	Building no.9, Lane 888, Tianlin Road, Minhang District, Shanghai 200233, China
Model No.	:	9290022166
FCC ID	:	2AGBW9290022166X
IC	:	20812-2166X
Brand Name	:	PHILIPS
EUT Voltage	:	110-130 Vac, 50-60 Hz, 9.5W
Test Voltage	:	AC 120V/60Hz
Applicable Standard	:	KDB 447498D01V06 FCC Part1.1310 RSS-102: Issue 5, 2015
Test Result	:	Complied
Performed Location	:	DEKRA Testing & Certification (Suzhou) Co., Ltd. No.99 Hongye Rd., Suzhou Industrial Park, Suzhou, 215006, Jiangsu, China TEL: +86-512-6251-5088 / FAX: +86-512-6251-5098 FCC Registration Number: CN1199;ISED CAB identifier: CN0040

Documented By : Kathy Feng

(Adm. Specialist: Kathy Feng)

Reviewed By : Frank he

(Senior Project Manager: Frank He)

Approved By : Jack zhang

(Engineering Supervisor: Jack Zhang)

1. RF Exposure Evaluation

1.1. Limits

For FCC:

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm2)	Average Time (Minutes)
(A) Limits for Occupational/ Control Exposures				
300-1500	--	--	F/300	6
1500-100,000	--	--	5	6
(B) Limits for General Population/ Uncontrolled Exposures				
300-1500	--	--	F/1500	6
1500-100,000	--	--	1	30

F= Frequency in MHz

Friis Formula

Friis transmission formula: Pd = (Pout*G)/(4*pi*r2)

Where

Pd = power density in mW/ cm^2

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

Pd is the limit of MPE, 1 mW/cm^2 . If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

For ISED:

According to RSS 102 Issue 5: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in RSS 102 Clause 4

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field (V/m rms)	Magnetic Field (A/m rms)	Power Density (W/m^2)	Reference Period (minutes)
0.003-10[21]	83	90	-	Instantaneous*
0.1-10	-	$0.73/f$	-	6**
1.1-10	$87/f^{0.5}$	-	-	6**
10-20	27.46	0.0728	2	6
20-48	$58.07/f^{0.25}$	$0.1540/f^{0.25}$	$8.944/f^{0.5}$	6
48-300	22.06	0.05852	1.291	6
300-6000	$3.142f^{0.3417}$	$0.008335f^{0.3417}$	$0.02619f^{0.6834}$	6
6000-15000	61.4	0.163	10	6
15000-150000	61.4	0.163	10	$616000/f^{1.2}$
150000-300000	$0.158f^{0.5}$	$4.21 \times 10^{-4} f^{0.5}$	$6.67 \times 10^{-5} f$	$616000/f^{1.2}$

Note: f is frequency in MHz.
*Based on nerve stimulation (NS).
** Based on specific absorption rate (SAR).

F= Frequency in MHz

Friis Formula

Friis transmission formula: Pd = (Pout*G)/(4*pi*r2)

Where

Pd = power density in mW/cm2

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

Pd is the limit of MPE, 0.540 mW/cm^2 for 2.4GHz . If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

1.2. Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.
The temperature and related humidity: 18℃and 78% RH.

1.3. Test Result of RF Exposure Evaluation

Product	:	LED Lamp
Test Item	:	RF Exposure Evaluation
Test Site	:	AC-6

- **Antenna Information:**

Antenna manufacturer	N/A					
Antenna Delivery	☒	1*TX+1*RX	☐	2*TX+2*RX	☐	3*TX+3*RX
Antenna technology	☒	SISO				
	☐	MIMO	☐	Basic		
			☐	CDD		
			☐	Beam-forming		
Antenna Type	☐	External	☐	Dipole		
	☒	Internal	☐	PIFA		
			☒	PCB		
			☐	Ceramic Chip Antenna		
			☐	Metal plate type F antenna		
Antenna Gain	-1.22dBi					

- **Power Density:**

The tune-up power is ±0.5dB, so the maximum conducted power we used to calculate RF exposure is 9.06dBm.

Test Mode	Frequency Band (MHz)	EIRP (dBm)	Limit of Power Density S(mW/cm^2)		Power Density at R = 20 cm (mW/cm^2)
			FCC	IC	
Zigbee	2400 ~ 2483.5	7.84	1	0.54	0.00121

Note:

1. The power density is 0.00121mW/cm^2 for LED Lamp without any other radio equipment.

The End