Test Result of Band Edge Emissions, LTE Band IV, LCH(16QAM, Bandwidth=20.0MHz, RB=RB1#0)



Test Result of Band Edge Emissions, LTE Band IV, LCH(16QAM, Bandwidth=20.0MHz, RB=RB1#99)



Test Result of Band Edge Emissions, LTE Band IV, LCH(16QAM, Bandwidth=20.0MHz, RB=RB50#25)



Test Result of Band Edge Emissions, LTE Band IV, LCH(16QAM, Bandwidth=20.0MHz, RB=RB100#0)



Test Result of Band Edge Emissions, LTE Band IV, HCH(16QAM, Bandwidth=20.0MHz, RB=RB1#0)



Test Result of Band Edge Emissions, LTE Band IV, HCH(16QAM, Bandwidth=20.0MHz, RB=RB1#99)



Test Result of Band Edge Emissions, LTE Band IV, HCH(16QAM, Bandwidth=20.0MHz, RB=RB50#25)



Test Result of Band Edge Emissions, LTE Band IV, HCH(16QAM, Bandwidth=20.0MHz, RB=RB100#0)



NOTE: All conditions have been tested and we only record the worst results in each bands.

Appendix V: RADIATED SPURIOUS EMISSIONS MEASUREMENT

Part I: Test result

The Worst Test Result For GSM 850, CH 128(30M~10G)				
Frequency (MHz)	Emission Level (dBm)	Limit (dBm)	Result	Polarity
34.85	-67.59			
1649.52	-21.79	-13	Pass	Н
2474.15	-19.46			
42.61	-61.51			
1649.52	-24.78	-13	Pass	V
2474.15	-20.03			

The Worst Test Result For GSM 850, CH 190(30M~10G)				
Frequency (MHz)	Emission Level (dBm)	Limit (dBm)	Result	Polarity
34.85	-67.16	-13		
1673.23	-21.71	-13	Pass	Н
2510.87	-19.52	-13		
42.61	-61.78	-13		
1673.23	-24.59	-13	Pass	V
2510.87	-20.41	-13		

The Worst Test Result For GSM 850, CH 251(30M~10G)				
Frequency (MHz)	Emission Level (dBm)	Limit (dBm)	Result	Polarity
34.85	-67.13	-13		
1697.52	-21.44	-13	Pass	Н
2546.41	-19.78	-13		
42.61	-61.36	-13		
1697.52	-24.52	-13	Pass	V
2546.41	-20.41	-13		

Th	The Worst Test Result For GSM 850 EGPRS, CH 128(30M~10G)				
Frequency (MHz)	Emission Level (dBm)	Limit (dBm)	Result	Polarity	
34.85	-67.13				
1649.52	-24.74	-13	Pass	Н	
2474.15	-22.05				
42.61	-61.31				
1649.52	-25.22	-13	Pass	V	
2474.15	-23.46				

The Worst Test Result For GSM 850 EGPRS, CH 190(30M~10G)				
Frequency (MHz)	Emission Level (dBm)	Limit (dBm)	Result	Polarity
34.85	-67.08	-13		
1673.23	-24.69	-13	Pass	Н
2510.87	-22.58	-13		
42.61	-61.16	-13		
1673.23	-25.24	-13	Pass	V
2510.87	-23.72	-13		

The Worst Test Result For GSM 850 EGPRS, CH 251(30M~10G)				
Frequency (MHz)	Emission Level (dBm)	Limit (dBm)	Result	Polarity
34.85	-67.46	-13		
1697.52	-24.85	-13	Pass	Н
2546.41	-22.36	-13		
42.61	-61.02	-13		
1697.52	-25.71	-13	Pass	V
2546.41	-23.48	-13		

The Worst Test Result For PCS 1900, CH 512(30MHz~20GHz)				
Frequency (MHz)	Emission Level (dBm)	Limit (dBm)	Result	Polarity
34.85	-67.12	-13		
3700.49	-22.41	-13	Pass	Н
5550.41	-21.78	-13		
42.61	-61.06	-13		
3700.49	-25.63	-13	Pass	V
5550.41	-22.51	-13		

The Worst Test Result For PCS 1900, CH 661(30MHz~20GHz)				
Frequency (MHz)	Emission Level (dBm)	Limit (dBm)	Result	Polarity
34.85	-67.43	-13		
3760.28	-22.58	-13	Pass	Н
5640.75	-21.71	-13		
42.61	-61.26	-13		
3760.28	-25.45	-13	Pass	V
5640.75	-22.03	-13		

The Worst Test Result For PCS 1900, CH 810(30MHz~20GHz)				
Frequency (MHz)	Emission Level (dBm)	Limit (dBm)	Result	Polarity
34.85	-67.41	-13		
3819.85	-22.89	-13	Pass	Н
5728.93	-21.66	-13		
42.61	-61.23	-13		
3819.85	-25.51	-13	Pass	V
5728.93	-22.78	-13		

The Worst Test Result For PCS 1900 EGPRS, CH 512(30MHz~20GHz)				
Frequency (MHz)	Emission Level (dBm)	Limit (dBm)	Result	Polarity
34.85	-67.16	-13		
3700.49	-23.44	-13	Pass	Н
5550.41	-22.28	-13		
42.61	-61.23	-13		
3700.49	-26.75	-13	Pass	V
5550.41	-24.01	-13		

The Worst Test Result For PCS 1900 EGPRS, CH 661(30MHz~20GHz)				
Frequency (MHz)	Emission Level (dBm)	Limit (dBm)	Result	Polarity
34.85	-67.03	-13		
3760.28	-23.11	-13	Pass	Н
5640.75	-22.41	-13		
42.61	-61.78	-13		
3760.28	-26.36	-13	Pass	V
5640.75	-24.01	-13		

The Worst Test Result For PCS 1900 EGPRS, CH 810(30MHz~20GHz)				
Frequency (MHz)	Emission Level (dBm)	Limit (dBm)	Result	Polarity
34.85	-67.42	-13		
3819.85	-23.87	-13	Pass	Н
5728.93	-22.69	-13		
42.61	-61.15	-13		
3819.85	-26.74	-13	Pass	V
5728.93	-24.31	-13		

The Worst Test Result For UMTS 850, CH 4132, 12.2K RMC(30MHz~10GHz)				
Frequency (MHz)	Emission Level (dBm)	Limit (dBm)	Result	Polarity
34.85	-67.40			
1652.38	-24.78	-13	Pass	Н
2480.14	-22.06			
42.61	-61.11			
1652.38	-25.45	-13	Pass	V
2480.14	-23.02			

The Worst Test Result For UMTS 850, CH 4180, 12.2K RMC(30MHz~10GHz)				
Frequency (MHz)	Emission Level (dBm)	Limit (dBm)	Result	Polarity
34.85	-67.40		Pass	Н
1672.58	-24.78	-13		
2508.11	-22.59			
42.61	-61.16			
1672.58	-25.78	-13	Pass	V
2508.11	-23.31			

The Worst Test Result For UMTS 850, CH 4233, 12.2K RMC(30MHz~10GHz)				
Frequency (MHz)	Emission Level (dBm)	Limit (dBm)	Result	Polarity
34.85	-67.54			
1694.25	-24.02	-13	Pass	Н
2540.86	-22.52			
42.61	-61.23			
1694.25	-25.56	-13	Pass	V
2540.86	-23.41			

The Worst Test Result For UMTS 1900, CH 9262, 12.2K RMC(30MHz~20GHz)				
Frequency (MHz)	Emission Level (dBm)	Limit (dBm)	Result	Polarity
34.85	-67.16	-13		
3704.85	-23.41	-13	Pass	Н
5557.28	-22.75	-13		
42.61	-61.63	-13		
3704.85	-26.25	-13	Pass	V
5557.28	-24.01	-13		

The Worst Test Result For UMTS 1900, CH 9400, 12.2K RMC(30MHz~20GHz)				
Frequency (MHz)	Emission Level (dBm)	Limit (dBm)	Result	Polarity
34.85	-67.89	-13		
3760.58	-23.46	-13	Pass	Н
5640.89	-22.52	-13		
42.61	-61.07	-13		
3760.58	-26.23	-13	Pass	V
5640.89	-24.64	-13		

The Worst Test Result For UMTS 1900, CH 9538, 12.2K RMC(30MHz~20GHz)				
Frequency (MHz)	Emission Level (dBm)	Limit (dBm)	Result	Polarity
34.85	-67.56	-13		
3815.24	-23.15	-13	Pass	Н
5722.41	-22.74	-13		
42.61	-61.33	-13		
3815.24	-26.52	-13	Pass	V
5722.41	-24.17	-13		

The Worst Test Result For LTE Band II, LCH, Bandwidth=1.4MHz(30MHz~20GHz)				
Frequency (MHz)	Emission Level (dBm)	Limit (dBm)	Result	Polarity
34.85	-67.78	-13		
3701.69	-26.55	-13	Pass	Н
5552.36	-25.02	-13		
42.61	-61.41	-13		
3701.69	-28.78	-13	Pass	V
5552.36	-27.36	-13		

The Worst Test Result For LTE Band II, MCH, Bandwidth=1.4MHz(30MHz~20GHz)				
Frequency (MHz)	Emission Level (dBm)	Limit (dBm)	Result	Polarity
34.85	-67.51	-13		
3760.58	-26.06	-13	Pass	Н
5640.89	-25.22	-13		
42.61	-61.56	-13		
3760.58	-28.47	-13	Pass	V
5640.89	-27.41	-13		

The Worst Test Result For LTE Band II, HCH, Bandwidth=1.4MHz(30MHz~20GHz)				
Frequency (MHz)	Emission Level (dBm)	Limit (dBm)	Result	Polarity
34.85	-67.11	-13		
3818.96	-26.74	-13	Pass	Н
5727.84	-25.56	-13		
42.61	-61.03	-13		
3818.96	-28.74	-13	Pass	V
5727.84	-27.02	-13		

The Worst Test Result For LTE Band II, LCH, Bandwidth=5.0MHz(30MHz~20GHz)				
Frequency (MHz)	Emission Level (dBm)	Limit (dBm)	Result	Polarity
34.85	-67.35	-13		
3705.51	-26.02	-13	Pass	Н
5557.83	-25.14	-13		
42.61	-61.25	-13		
3705.51	-28.74	-13	Pass	V
5557.83	-27.69	-13		

The Worst	The Worst Test Result For LTE Band II, MCH, Bandwidth=5.0MHz(30MHz~20GHz)				
Frequency (MHz)	Emission Level (dBm)	Limit (dBm)	Result	Polarity	
34.85	-67.03	-13			
3760.58	-26.12	-13	Pass	Н	
5640.89	-25.74	-13			
42.61	-61.89	-13			
3760.58	-28.56	-13	Pass	V	
5640.89	-27.41	-13			

The Worst Test Result For LTE Band II, HCH, Bandwidth=5.0MHz(30MHz~20GHz)				
Frequency (MHz)	Emission Level (dBm)	Limit (dBm)	Result	Polarity
34.85	-67.28	-13		
3815.69	-26.03	-13	Pass	Н
5722.24	-25.41	-13		
42.61	-61.74	-13		
3815.69	-28.62	-13	Pass	V
5722.24	-27.20	-13		

The Worst Test Result For LTE Band II, LCH, Bandwidth=20.0MHz(30MHz~20GHz)				
Frequency (MHz)	Emission Level (dBm)	Limit (dBm)	Result	Polarity
34.85	-67.41	-13		
3720.36	-26.87	-13	Pass	Н
5580.41	-25.06	-13		
42.61	-61.13	-13		
3720.36	-28.87	-13	Pass	V
5580.41	-26.45	-13		

The Worst T	The Worst Test Result For LTE Band II, MCH, Bandwidth=20.0MHz(30MHz~20GHz)				
Frequency (MHz)	Emission Level (dBm)	Limit (dBm)	Result	Polarity	
34.85	-67.07	-13			
3760.58	-26.26	-13	Pass	Н	
5640.89	-25.78	-13			
42.61	-61.51	-13			
3760.58	-28.47	-13	Pass	V	
5640.89	-26.03	-13			

The Worst Test Result For LTE Band II, HCH, Bandwidth=20.0MHz(30MHz~20GHz)				
Frequency (MHz)	Emission Level (dBm)	Limit (dBm)	Result	Polarity
34.85	-67.71	-13		
3800.49	-26.41	-13	Pass	Н
5700.38	-25.74	-13		
42.61	-61.36	-13		
3800.49	-28.15	-13	Pass	V
5700.38	-26.24	-13		

The Worst Test Result For LTE Band IV, LCH, Bandwidth=1.4MHz(30MHz~20GHz)				
Frequency (MHz)	Emission Level (dBm)	Limit (dBm)	Result	Polarity
34.85	-67.71	-13		
3421.31	-26.35	-13	Pass	Н
5132.98	-25.02	-13		
42.61	-61.41	-13		
3421.31	-28.73	-13	Pass	V
5132.98	-26.69	-13		

The Worst Test Result For LTE Band IV, MCH, Bandwidth=1.4MHz(30MHz~20GHz)				
Frequency (MHz)	Emission Level (dBm)	Limit (dBm)	Result	Polarity
34.85	-67.46	-13		
3465.16	-26.81	-13	Pass	Н
5197.31	-25.26	-13		
42.61	-61.11	-13		
3465.16	-28.77	-13	Pass	V
5197.31	-26.68	-13		

The Worst Test Result For LTE Band IV, HCH, Bandwidth=1.4MHz(30MHz~20GHz)				
Frequency (MHz)	Emission Level (dBm)	Limit (dBm)	Result	Polarity
34.85	-67.78	-13		
3508.45	-26.69	-13	Pass	Н
5262.76	-25.41	-13		
42.61	-61.78	-13		
3508.45	-28.26	-13	Pass	V
5262.76	-26.30	-13		

The Worst Test Result For LTE Band IV, LCH, Bandwidth=5.0MHz(30MHz~20GHz)				
Frequency (MHz)	Emission Level (dBm)	Limit (dBm)	Result	Polarity
34.85	-67.11	-13		
3425.68	-26.74	-13	Pass	Н
5137.82	-25.21	-13		
42.61	-61.36	-13		
3425.68	-28.75	-13	Pass	V
5137.82	-26.12	-13		

The Worst Test Result For LTE Band IV, MCH, Bandwidth=5.0MHz(30MHz~20GHz)				
Frequency (MHz)	Emission Level (dBm)	Limit (dBm)	Result	Polarity
34.85	-67.66	-13		
3465.16	-26.15	-13	Pass	Н
5197.31	-25.74	-13]	
42.61	-61.23	-13		
3465.16	-28.43	-13	Pass	V
5197.31	-26.02	-13		

The Worst Test Result For LTE Band IV, HCH, Bandwidth=5.0MHz(30MHz~20GHz)				
Frequency (MHz)	Emission Level (dBm)	Limit (dBm)	Result	Polarity
34.85	-67.58	-13		
3451.25	-26.03	-13	Pass	Н
5176.87	-25.12	-13		
42.61	-61.41	-13		
3451.25	-28.23	-13	Pass	V
5176.87	-26.02	-13		

The Worst Test Result For LTE Band IV, LCH, Bandwidth=20.0MHz(30MHz~20GHz)				
Frequency (MHz)	Emission Level (dBm)	Limit (dBm)	Result	Polarity
34.85	-67.85	-13		
3440.39	-26.03	-13	Pass	Н
5160.37	-25.22	-13		
42.61	-61.44	-13		
3440.39	-28.69	-13	Pass	V
5160.37	-26.55	-13		

The Worst Test Result For LTE Band IV, MCH, Bandwidth=20.0MHz(30MHz~20GHz)				
Frequency (MHz)	Emission Level (dBm)	Limit (dBm)	Result	Polarity
34.85	-67.11	-13		
3465.16	-26.74	-13	Pass	Н
5197.31	-25.86	-13		
42.61	-61.36	-13		
3465.16	-28.02	-13	Pass	V
5197.31	-26.41	-13		

The Worst Test Result For LTE Band IV, HCH, Bandwidth=20.0MHz(30MHz~20GHz)				
Frequency (MHz)	Emission Level (dBm)	Limit (dBm)	Result	Polarity
34.85	-67.23	-13		
3490.85	-26.40	-13	Pass	Н
5235.14	-25.78	-13		
42.61	-61.14	-13		
3490.85	-28.40	-13	Pass	V
5235.14	-26.78	-13		

NOTE: The result below 30MHz is too low, there is only base environmental noise. We Only record the worst results above 30MHz.

Appendix VI: FREQUENCY STABILITY OVER TEMPERATURE AND VOLTAGE

Part I: Test result

VARIATIONS

Mode	Test Channel	Test Volt.	Test Temp.	Frequency error (Hz)	Result (ppm)	Limit (ppm)	Verdict
		LV		49.24	0.05885	\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	Pass
		NV	25	17.41	0.02081		Pass
		HV		21.64	0.02586		Pass
			-30	36.56	0.04370		Pass
			-20	11.94	0.01427		Pass
GSM	Middle		-10	40.68	0.04862	./ 2.5	Pass
850	CH		0	40.01	0.04782	+/- 2.5	Pass
		NV	10	33.38	0.03989		Pass
			20	20.76	0.02481		Pass
			30	12.63	0.01509		Pass
			40	37.75	0.04512		Pass
			50	11.02	0.01317		Pass
		LV		18.46	0.02206		Pass
		NV	25	38.23	0.04569		Pass
		HV		12.74	0.01522		Pass
			-30	24.97	0.02984		Pass
GSM			-20	39.50	0.04721		Pass
850	Middle		-10	37.98	0.04539	+/ 2.5	Pass
EGPRS	СН	СН	0	26.28	0.03141	+/- 2.5	Pass
EGFKS		NV	10	17.60	0.02103	+/- 2.5	Pass
			20	20.54	0.02455		Pass
			30	14.98	0.01790		Pass
			40	25.53	0.03051		Pass
			50	23.39	0.02795		Pass
		LV		23.70	0.01260		Pass
		NV	25	30.87	0.01642		Pass
		HV		18.35	0.00976		Pass
			-30	18.44	0.00980		Pass
			-20	41.37	0.02200		Pass
PCS	Middle		-10	31.20	0.01659	+/- 2.5	Pass
1900	СН		0	37.49	0.01994	17- 2.0	Pass
		NV	10	34.83	0.01852		Pass
			20	41.96	0.02231		Pass
			30	45.51	0.02420		Pass
			40	12.73	0.00677	-	Pass
			50	33.83	0.01799		Pass

NOTE:All conditions have been tested and we only record the worst results in each bands.

LV=3.25V, NV=3.80V, HV=4.35V

HENZHEN LCS COMPLIANCE TESTING LABORATORY LTD.	FCC ID: 2AGDXSP5049G	Report No.: LCS151102003.

Mode	Test Channel	Test Volt.	Test Temp.	Frequency error (Hz)	Result (ppm)	Limit (ppm)	Verdict
		LV		26.42	0.01405	\\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	Pass
		NV	25	49.70	0.02643		Pass
		HV		36.87	0.01961		Pass
			-30	22.96	0.01221		Pass
			-20	36.88	0.01961		Pass
PCS	Middle		-10	14.83	0.00788	. / 0.5	Pass
1900 EGPRS	СН		0	23.08	0.01227	+/- 2.5	Pass
		NV	10	15.42	0.00820		Pass
			20	29.22	0.01554		Pass
			30	26.62	0.01415		Pass
			40	38.84	0.02065		Pass
			50	48.32	0.02570		Pass
		LV		2.12	0.00253		Pass
		NV	25	1.75	0.00209		Pass
		HV		-2.05	-0.00245		Pass
			-30	1.02	0.00122		Pass
LIMTO	Middle CH		-20	-0.11	-0.00013		Pass
UMTS 850		Middle	-10	-1.63	-0.00195	./ 2.5	Pass
RMC		СН		0	-2.08	-0.00249	+/- 2.5
KIVIC		NV	10	-0.44	-0.00052	+/- 2.5	Pass
			20	-0.37	-0.00044		Pass
			30	0.35	0.00042		Pass
			40	1.80	0.00215		Pass
			50	2.99	0.00358		Pass
		LV		1.67	0.00199		Pass
		NV	25	2.33	0.00278		Pass
		HV		1.53	0.00183		Pass
			-30	-2.67	-0.00319		Pass
LIMTO			-20	1.34	0.00160		Pass
UMTS	Middle		-10	-1.68	-0.00200	+/- 2.5	Pass
	850 CH		0	0.23	0.00027	T/- 2.5	Pass
ПОЛЬК		NV	10	-1.55	-0.00185		Pass
			20	0.68	0.000813		Pass
			30	-0.09	-0.00010		Pass
			40	-2.16	-0.00258		Pass
			50	-1.72	-0.00206		Pass

NOTE:All conditions have been tested and we only record the worst results in each bands. LV=3.25V, NV=3.80V, HV=4.35V

Mode	Test Channel	Test Volt.	Test Temp.	Frequency error (Hz)	Result (ppm)	Limit (ppm)	Verdict
	- Cildinioi	LV		1.82	0.00217	(PP)	Pass
		NV	25	0.42	0.00050		Pass
		HV		-1.48	-0.00177		Pass
			-30	-2.98	-0.00356		Pass
	LIMTS		-20	1.45	0.00173		Pass
UMTS	Middle		-10	-2.01	-0.00240		Pass
850 HSUPA	CH		0	-2.71	-0.00324	+/- 2.5	Pass
110017		NV	10	2.54	0.00303		Pass
			20	1.63	0.00194		Pass
			30	-1.95	-0.00233		Pass
			40	-1.76	-0.00210		Pass
			50	-2.54	-0.00303		Pass
		LV		-2.44	-0.00291		Pass
		NV	25	0.48	0.00574		Pass
		HV		-1.36	-0.00162		Pass
			-30	0.91	0.00108		Pass
			-20	-2.70	-0.00328		Pass
UMTS	Middle	Middle CH	-10	0.35	0.00041	,	Pass
1900	СН		0	-1.94	-0.00232	+/- 2.5	Pass
RMC		NV	10	1.60	0.00191		Pass
			20	-2.41	-0.00288		Pass
			30	-0.91	-0.00108		Pass
			40	0.68	0.00081		Pass
			50	0.94	0.00112		Pass
		LV		1.62	0.00193		Pass
		NV	25	0.27	0.00032		Pass
		HV		2.58	0.00308		Pass
			-30	-0.98	-0.00117		Pass
LIMTO			-20	2.53	0.00302		Pass
UMTS	Middle		-10	-2.39	-0.00285	./ 2.5	Pass
1900 HSDPA	СН		0	1.56	0.00186	+/- 2.5	Pass
IIODEA		NV	10	1.96	0.00234		Pass
		144	20	-0.83	-0.00099		Pass
			30	-2.52	-0.00301		Pass
			40	0.78	0.00093		Pass
			50	-2.24	-0.00267		Pass

NOTE:All conditions have been tested and we only record the worst results in each bands. LV=3.25V, NV=3.80V, HV=4.35V

Mode	Test Channel	Test Volt.	Test Temp.	Frequency error (Hz)	Result (ppm)	Limit (ppm)	Verdict
		LV		2.75	0.00146		Pass
		NV	25	-2.72	-0.00145		Pass
		HV		0.11	0.00059		Pass
			-30	2.39	0.00127		Pass
			-20	-1.96	-0.00104		Pass
UMTS 1900	Middle		-10	-0.26	-0.00014	+/- 2.5	Pass
HSUPA	CH		0	-2.18	-0.00116	+/- 2.5	Pass
		NV	10	-2.53	-0.00135		Pass
			20	1.95	0.00104		Pass
			30	1.25	0.00066		Pass
			40	2.93	0.00156		Pass
			50	0.13	0.00069		Pass

NOTE:All conditions have been tested and we only record the worst results in each bands. LV=3.25V, NV=3.80V, HV=4.35V

Mode	Test Bandwidth	Test Channel	Test Volt.	Test Temp.	Frequency error (Hz)	Result (ppm)	Limit (ppm)	Verdict			
			LV		0.23	0.000124	_ \	Pass			
			NV	25	-25.45	-0.013751		Pass			
			HV		0.27	0.000147		Pass			
				-30	-0.04	-0.000023		Pass			
				-20	0.57	0.000309		Pass			
		Law CII		-10	-0.72	-0.000386	./ 2.5	Pass			
		Low CH		0	-0.49	-0.000263	+/- 2.5	Pass			
			NV	10	-0.64	-0.000348		Pass			
				20	3.58	0.001932		Pass			
				30	-1.34	-0.000727		Pass			
				40	-0.41	-0.000224		Pass			
				50	0.87	0.000472		Pass			
			LV		-1.07	-0.000571		Pass			
			NV	25	0.87	0.000464		Pass			
			HV		4.28	0.002275	İ	Pass			
				-30	0.30	0.000160		Pass			
								-20 0.93 0.0004	0.000495		Pass
LTE	1.4	Middle		-10	0.00	0.000000	./ 2.5	Pass			
BAND II	1.4	СН		0	-0.33	-0.000175	+/- 2.5	Pass			
(QPSK)			NV	10	0.27	0.000145		Pass			
				20	1.00	0.000533		Pass			
				30	-0.17	-0.000091		Pass			
				40	-0.13	-0.000068		Pass			
				50	0.07	0.000038		Pass			
			LV		-0.77	-0.000405		Pass			
			NV	25	0.33	0.000172		Pass			
			HV		2.93	0.001536		Pass			
				-30	-2.00	-0.001049		Pass			
				-20	0.11	0.000060		Pass			
		High C⊔		-10	0.13	0.000067	±/ 2.5	Pass			
		High CH		0	1.02	0.000532	+/- 2.5	Pass			
			NV	10	0.17	0.000090		Pass			
				20	-0.14	-0.000075		Pass			
				30	1.95	0.001019		Pass			
				40	2.45	0.001281		Pass			
				50	-1.27	-0.000667		Pass			
LV=3.25V,	NV=3.80V, H	V=4.35V									

Mode	Test Bandwidth	Test Channel	Test Volt.	Test Temp.	Frequency error (Hz)	Result	Limit (ppm)	Verdict
	Bandwidth	Chamilei	LV		-2.27	(ppm) -0.001228	(ррііі)	Pass
			NV	25	3.13	0.001692		Pass
			HV		0.06	0.000031		Pass
			110	-30	0.74	0.000402		Pass
				-20	-1.16	-0.000626		Pass
				-10	-0.40	-0.000216		Pass
		Low CH		0	-0.27	-0.000147	+/- 2.5	Pass
			NV	10	0.30	0.000162		Pass
				20	0.10	0.000054		Pass
				30	-3.92	-0.002117		Pass
				40	-1.72	-0.000927		Pass
				50	1.37	0.000742		Pass
			LV		0.72	0.000380		Pass
			NV	25	0.76	0.000403		Pass
			HV		-1.50	-0.000799		Pass
				-30	-0.01	-0.000008		Pass
				-20	1.76	0.000936		Pass
LTE	3.0	Middle		-10	0.82	0.000434	+/- 2.5	Pass
BAND II (QPSK)	3.0	CH		0	2.95	0.001567	+/- 2.5	Pass
(Qi Oit)			NV	10	3.58	0.001902		Pass
				20	-0.97	-0.000517		Pass
				30	4.13	0.002199		Pass
				40	-0.26	-0.000137		Pass
				50	-0.04	-0.000023		Pass
			LV		0.74	0.000390		Pass
			NV	25	2.66	0.001394		Pass
			HV		-1.60	-0.000839		Pass
				-30	0.14	0.000075		Pass
				-20	-0.39	-0.000202		Pass
		High CH		-10	-0.96	-0.000502	+/- 2.5	Pass
		1.19.1 011		0	0.41	0.000217		Pass
			NV	10	0.93	0.000487		Pass
				20	1.66	0.000869		Pass
				30	1.50	0.000787		Pass
				40	1.23	0.000645		Pass
				50	0.57	0.000300		Pass
LV=3.25V	, NV=3.80V, H	V=4.35V						

Mode	Test Bandwidth	Test Channel	Test Volt.	Test Temp.	Frequency error (Hz)	Result (ppm)	Limit (ppm)	Verdict
			LV		4.92	0.002656		Pass
			NV	25	-2.47	-0.001336		Pass
			HV		3.23	0.001745		Pass
				-30	-1.86	-0.001004		Pass
				-20	3.00	0.001622		Pass
		Law CII		-10	-0.90	-0.000486	./ 2.5	Pass
		Low CH		0	-2.46	-0.001328	+/- 2.5	Pass
			NV	10	-3.12	-0.001683		Pass
				20	-1.10	-0.000595		Pass
				30	1.65	0.000888		Pass
				40	2.16	0.001166		Pass
				50	1.80	0.000973		Pass
			LV		0.97	0.000517		Pass
			NV	25	-0.23	-0.000122		Pass
			HV		0.30	0.000160		Pass
				-30	0.94	0.000502		Pass
				-20	-0.62	-0.000327	-	Pass
LTE	5.0	Middle		-10	-2.32	-0.001233	./ 2.5	Pass
BAND II	5.0	СН		0	-0.39	-0.000205	+/- 2.5	Pass
(QPSK)			NV	10	0.47	0.000251		Pass
				20	1.14	0.000609		Pass
				30	0.66	0.000350		Pass
				40	-0.30	-0.000160		Pass
				50	0.10	0.000053		Pass
			LV		2.20	0.001155		Pass
			NV	25	3.50	0.001837		Pass
			HV		-0.11	-0.000060		Pass
				-30	0.10	0.000052		Pass
				-20	1.34	0.000705		Pass
		High C⊔		-10	0.94	0.000495	±/ 2.5	Pass
		High CH		0	-0.13	-0.000067	+/- 2.5	Pass
			NV	10	1.49	0.000780		Pass
				20	2.35	0.001230		Pass
				30	-1.34	-0.000705		Pass
				40	-2.69	-0.001410		Pass
				50	-1.87	-0.000982		Pass
LV=3.25V,	NV=3.80V, H	V=4.35V						

FCC ID: 2AGDXSP5049G

Mode	Test Bandwidth	Test Channel	Test Volt.	Test Temp.	Frequency error (Hz)	Result (ppm)	Limit (ppm)	Verdict						
			LV		-0.49	-0.000262		Pass						
			NV	25	-0.06	-0.000031		Pass						
			HV		0.84	0.000455		Pass						
				-30	0.96	0.000517		Pass						
				-20	0.03	0.000015		Pass						
		Low CH		-10	0.57	0.000308	+/- 2.5	Pass						
		LOW CIT		0	-0.10	-0.000054	+/- 2.5	Pass						
			NV	10	-0.90	-0.000486		Pass						
				20	-0.11	-0.000062		Pass						
				30	0.84	0.000455		Pass						
				40	-0.51	-0.000278		Pass						
				50	-0.20	-0.000108		Pass						
			LV		0.83	0.000441		Pass						
			NV	25	-0.27	-0.000145		Pass						
			HV		-0.87	-0.000464		Pass						
				-30	-0.27	-0.000145]	Pass						
		Middle CH								-20	-0.24	-0.000129		Pass
LTE	10.0			-10	-0.29	-0.000152	+/- 2.5	Pass						
BAND II (QPSK)	10.0		СН	СН		0	0.50	0.000266	· i - Z.J	Pass				
(QI OIL)			NV	10	-0.31	-0.000167	_	Pass						
				20	0.36	0.000190		Pass						
				30	0.26	0.000137		Pass						
				40	0.57	0.000304		Pass						
				50	-0.07	-0.000038		Pass						
			LV		-0.41	-0.000218		Pass						
			NV	25	-1.00	-0.000526		Pass						
			HV		-0.64	-0.000338		Pass						
				-30	0.73	0.000383		Pass						
				-20	1.04	0.000548		Pass						
		High CH		-10	0.30	0.000158	+/- 2.5	Pass						
		High CH		0	1.02	0.000533	+/- 2.5	Pass						
		NV	10	-1.07	-0.000563		Pass							
				20	-1.42	-0.000743		Pass						
			30	0.21	0.000113		Pass							
				40	-0.11	-0.000060		Pass						
				50	0.31	0.000165		Pass						
LV=3.25V	, NV=3.80V, H	V=4.35V												

Mode	Test Bandwidth	Test Channel	Test Volt.	Test Temp.	Frequency error (Hz)	Result (ppm)	Limit (ppm)	Verdict			
			LV		3.15	0.001694		Pass			
			NV	25	3.00	0.001617		Pass			
			HV		3.66	0.001972		Pass			
				-30	2.90	0.001563		Pass			
				-20	2.50	0.001348		Pass			
		Law CII		-10 3.65 0.001964 +/- 2.5	Pass						
		Low CH		0	1.80	0.000970	+/- 2.5	Pass			
			NV	10	4.12	0.002218		Pass			
				20	3.22	0.001733		Pass			
				30	2.73	0.001471		Pass			
				40	2.62	0.001409		Pass			
				50	3.63	0.001956		Pass			
			LV		0.16	0.000084		Pass			
			NV	25	1.00	0.000533		Pass			
			HV		0.03	0.000015		Pass			
				-30	-0.07	-0.000038		Pass			
							-20	0.82	0.000434		Pass
LTE	15.0	Middle		-10	0.53	0.000282	+/- 2.5	Pass			
BAND II	15.0	СН		0	1.09	0.000578	+/- 2.5	Pass			
(QPSK)			NV	10	-0.31	-0.000167		Pass			
				20	-0.73	-0.000388		Pass			
				30	0.59	0.000312		Pass			
				40	-0.62	-0.000327		Pass			
				50	-0.27	-0.000145		Pass			
			LV		0.31	0.000165		Pass			
			NV	25	-0.29	-0.000150		Pass			
			HV		-0.44	-0.000233		Pass			
				-30	-1.10	-0.000579		Pass			
				-20	-0.46	-0.000241		Pass			
		High C⊔		-10	-0.29	-0.000150	±/ 25	Pass			
		High CH		0	0.49	0.000256	+/- 2.5	Pass			
			NV	10	0.13	0.000068		Pass			
				20	0.33	0.000173		Pass			
				30	-0.34	-0.000180		Pass			
				40	0.34	0.000180		Pass			
				50	-0.39	-0.000203		Pass			
LV=3.25V,	NV=3.80V, H	V=4.35V									

Mode	Test Bandwidth	Test Channel	Test Volt.	Test Temp.	Frequency error (Hz)	Result (ppm)	Limit (ppm)	Verdict			
			LV		-0.01	-0.000008		Pass			
			NV	25	-0.26	-0.000138		Pass			
			HV		0.37	0.000200		Pass			
				-30	-1.07	-0.000577		Pass			
				-20	-0.87	-0.000469		Pass			
		Law CII		-10	0 -0.69 -0.000369	Pass					
		Low CH		0	-0.86	-0.000461	+/- 2.5	Pass			
			NV	10	-0.62	-0.000331		Pass			
				20	-0.04	-0.000023		Pass			
				30	-0.53	-0.000285		Pass			
				40	-0.31	-0.000169		Pass			
				50	-0.11	-0.000062		Pass			
			LV		0.80	0.000426		Pass			
			NV	25	-0.49	-0.000259		Pass			
			HV		-0.27	-0.000145		Pass			
				-30	0.03	0.000015		Pass			
							-20	0.16	0.000084		Pass
LTE	20.0	Middle		-10	-0.46	-0.000243	./ 2.5	Pass			
BAND II	20.0	СН		0	0.74	0.000396	+/- 2.5	Pass			
(QPSK)			NV	10	-0.27	-0.000145		Pass			
				20	0.27	0.000145		Pass			
				30	0.89	0.000472		Pass			
				40	0.43	0.000228		Pass			
				50	0.47	0.000251		Pass			
			LV		-0.20	-0.000105		Pass			
			NV	25	0.30	0.000158		Pass			
			HV		-0.46	-0.000241		Pass			
				-30	-1.16	-0.000610		Pass			
				-20	0.44	0.000233		Pass			
		Himb CH		-10	0.51	0.000271	./ 2.5	Pass			
		High CH		0	-0.10	-0.000053	+/- 2.5	Pass			
			NV	10	0.29	0.000151		Pass			
				20	-1.44	-0.000760		Pass			
				30	0.83	0.000437		Pass			
				40	-0.21	-0.000113		Pass			
				50	0.14	0.000075		Pass			
LV=3.25V,	NV=3.80V, H	V=4.35V									

Mode	Test Bandwidth	Test Channel	Test Volt.	Test Temp.	Frequency error (Hz)	Result (ppm)	Limit (ppm)	Verdict							
			LV		-0.04	-0.000023	(рржу	Pass							
			NV	25	1.33	0.000719		Pass							
			HV		-0.04	-0.000023		Pass							
				-30	-0.96	-0.000518		Pass							
				-20	-1.69	-0.000912		Pass							
		Law CII		-10	-1.13	-0.000611	./ 2.5	Pass							
		Low CH		0	-0.36	-0.000193	+/- 2.5	Pass							
			NV	10	0.03	0.000015		Pass							
				20	-0.80	-0.000433		Pass							
				30	-0.04	-0.000023		Pass							
				40	-0.86	-0.000464		Pass							
				50	-0.41	-0.000224		Pass							
			LV		-0.53	-0.000282		Pass							
			NV	25	1.49	0.000791		Pass							
			HV		0.17	0.000091		Pass							
				-30	0.49	0.000259		Pass							
											-20	0.23	0.000122		Pass
LTE	1.4	Middle		-10	-0.79	-0.000419	+/- 2.5	Pass							
BAND II (16QAM)	1.4	CH		0	0.19	0.000099	+/- 2.5	Pass							
(10QAIVI)			NV	10	-1.13	-0.000601		Pass							
				20	-1.39	-0.000738		Pass							
				30	0.21	0.000114		Pass							
				40	0.26	0.000137		Pass							
				50	0.10	0.000053		Pass							
			LV		-2.07	-0.001086		Pass							
			NV	25	-2.83	-0.001483		Pass							
			HV		0.66	0.000345		Pass							
				-30	1.63	0.000854		Pass							
				-20	-2.09	-0.001094		Pass							
		High CH		-10	-2.88	-0.001506	+/- 2.5	Pass							
		i iigii Ci i		0	-2.60	-0.001364	1,- 2.0	Pass							
			NV	10	-4.19	-0.002195		Pass							
				20	-3.89	-0.002038		Pass							
				30	-4.09	-0.002143		Pass							
				40	-4.86	-0.002547		Pass							
				50	-3.22	-0.001686		Pass							
LV=3.25V,	, NV=3.80V, H	V=4.35V													

Mode	Test Bandwidth	Test Channel	Test Volt.	Test Temp.	Frequency error (Hz)	Result (ppm)	Limit (ppm)	Verdict		
			LV		-0.76	-0.000409		Pass		
			NV	25	1.27	0.000688		Pass		
			HV		2.66	0.001437		Pass		
				-30	3.62	0.001955		Pass		
				-20	3.86	0.002086		Pass		
		Low CH		-10	2.70	0.001460	+/- 2.5	Pass		
		LOW CH		0	2.78	0.001499	+/- 2.5	Pass		
			NV	10	2.40	0.001298		Pass		
				20	-1.19	-0.000641		Pass		
				30	-1.22	-0.000657		Pass		
				40	1.13	0.000610		Pass		
				50	0.86	0.000464		Pass		
			LV		-2.19	-0.001164		Pass		
			NV	25	-2.62	-0.001392		Pass		
			HV		2.43	0.001294		Pass		
				-30	1.52	0.000807		Pass		
				-20	-2.95	-0.001567		Pass		
LTE	2.0	Middle		-10	-2.76	-0.001469	. / 0.5	Pass		
BAND II	3.0	СН		0	-1.63	-0.000867	+/- 2.5	Pass		
(16QAM)			NV	10	-1.76	-0.000936		Pass		
				20	-2.25	-0.001195		Pass		
				30	-2.72	-0.001446		Pass		
				40	-4.01	-0.002131		Pass		
				50	-2.72	-0.001446		Pass		
			LV		-0.50	-0.000262		Pass		
			NV	25	-1.63	-0.000854		Pass		
			HV		-1.19	-0.000622		Pass		
				-30	-1.96	-0.001027		Pass		
				-20	-1.56	-0.000817		Pass		
				-10	-2.03	-0.001064	. / 0.5	Pass		
		High CH		0	-2.37	-0.001244	+/- 2.5	Pass		
			NV	10	2.02	0.001057		Pass Pass Pass Pass Pass Pass Pass Pass		
				20	3.30	0.001731		Pass		
				30	2.95	0.001544		Pass		
				40	1.99	0.001042		Pass		
				50	2.85	0.001492		Pass		
LV=3.25V,	LV=3.25V, NV=3.80V, HV=4.35V									

Mode	Test Bandwidth	Test Channel	Test Volt.	Test Temp.	Frequency error (Hz)	Result (ppm)	Limit (ppm)	Verdict
			LV		2.15	0.001158	TI-I- /	Pass
			NV	25	-4.31	-0.002324		Pass
			HV		-0.14	-0.000077		Pass
			_	-30	-0.11	-0.000062		Pass
				-20	-1.69	-0.000911		Pass
		Law CII		-10	0.82	0.000440	./ 2.5	Pass
		Low CH		0	-0.92	-0.000494	+/- 2.5	Pass
			NV	10	0.13	0.000069		Pass
				20	-1.19	-0.000641		Pass
				30	-1.50	-0.000811		Pass
				40	1.92	0.001035		Pass
				50	-1.77	-0.000958		Pass
			LV		-1.06	-0.000563		Pass
			NV	25	-1.87	-0.000997		Pass
			HV		0.93	0.000495		Pass
				-30	-1.26	-0.000670		Pass
				-20	2.26	0.001202		Pass
LTE	5.0	Middle		-10	-1.77	-0.000944	+/- 2.5	Pass
BAND II (16QAM)	5.0	CH		0	0.21	0.000114	+/- 2.5	Pass
(10QAIVI)			NV	10	1.86	0.000989		Pass
				20	2.82	0.001499		Pass
				30	1.99	0.001058		Pass
				40	2.25	0.001195		Pass
				50	0.96	0.000510		Pass
			LV		0.01	0.000007		Pass
			NV	25	-0.87	-0.000457		Pass
			HV		-1.99	-0.001042		Pass
				-30	-0.53	-0.000277		Pass
				-20	2.89	0.001515		Pass
		High CH		-10	3.10	0.001627	+/- 2.5	Pass
		Tilgil CIT		0	-0.83	-0.000435	17-2.5	Pass
			NV	10	-2.40	-0.001260		Pass Pass Pass Pass Pass Pass
				20	-1.90	-0.000997		Pass
				30	1.09	0.000570		Pass
				40	3.46	0.001815		Pass
				50	3.19	0.001672		Pass
LV=3.25V,	, NV=3.80V, H	V=4.35V						

FCC ID: 2AGDXSP5049G

Mode	Test Bandwidth	Test Channel	Test Volt.	Test Temp.	Frequency error (Hz)	Result (ppm)	Limit (ppm)	Verdict					
			LV		-2.10	-0.001134		Pass					
			NV	25	-1.16	-0.000625		Pass					
			HV		-0.93	-0.000501		Pass					
				-30	0.33	0.000177		Pass					
				-20	-1.04	-0.000563		Pass					
		Low CH		-10	-0.84	-0.000455	+/- 2.5	Pass					
		LOW CIT		0	0.39	0.000208	17- 2.5	Pass					
			NV	10	-0.90	-0.000486		Pass					
				20	-1.14	-0.000617		Pass					
				30	-0.40	-0.000216		Pass					
				40	-0.43	-0.000231		Pass					
				50	-1.10	-0.000594		Pass					
			LV		-0.57	-0.000304		Pass					
			NV	25	-1.12	-0.000594		Pass					
			HV		-0.33	-0.000175		Pass					
				-30	-0.07	-0.000038		Pass					
				-20	-0.54	-0.000289		Pass					
LTE	10.0	Middle		-10	-0.86	-0.000457	+/- 2.5	Pass					
BAND II (16QAM)	10.0	СН		0	-0.53	-0.000282	+/- 2.5	Pass					
(10QAIVI)			NV	10	1.57	0.000837		Pass					
				20	0.93	0.000495		Pass					
				30	0.76	0.000403		Pass					
				40	0.19	0.000099		Pass					
				50	-0.97	-0.000517		Pass					
			LV		-0.84	-0.000443		Pass					
			NV	25	0.06	0.000030		Pass					
			HV		-0.39	-0.000203		Pass					
				-30	0.14	0.000075		Pass Pass Pass Pass Pass Pass Pass Pass					
				-20	-0.86	-0.000451		Pass					
		Himb OH		-10	-1.02	-0.000533	./ 2.5	Pass					
		High CH		0	-0.17	-0.000090	+/- 2.5	Pass					
			NV	10	-0.16	-0.000083		Pass					
				20	-0.47	-0.000248		Pass					
				30	-1.27	-0.000668		Pass					
				40	0.44	0.000233		Pass					
				50	-0.76	-0.000398		Pass					
LV=3.25V,	, NV=3.80V, H	V=4.35V		LV=3.25V, NV=3.80V, HV=4.35V									

Mode	Test Bandwidth	Test Channel	Test Volt.	Test Temp.	Frequency error (Hz)	Result (ppm)	Limit (ppm)	Verdict		
			LV		3.15	0.001694		Pass		
			NV	25	2.88	0.001548		Pass		
			HV		3.42	0.001841		Pass		
				-30	2.72	0.001463		Pass		
				-20	1.82	0.000978		Pass		
		1 av. (CL)		-10	2.30	0.001240	. / 2.5	Pass		
		Low CH		0	2.90	0.001563	+/- 2.5	Pass		
			NV	10	3.23	0.001740		Pass		
				20	2.33	0.001255		Pass		
				30	1.82	0.000978		Pass		
				40	1.87	0.001009		Pass		
				50	1.95	0.001047		Pass		
			LV		0.54	0.000289		Pass		
			NV	25	-1.39	-0.000738		Pass		
			HV		-0.33	-0.000175		Pass		
				-30	-1.53	-0.000814		Pass		
				-20	-0.53	-0.000282		Pass		
LTE	15.0	Middle		-10	-0.30	-0.000160	./ 2.5	Pass		
BAND II	15.0	СН		0	-1.06	-0.000563	+/- 2.5	Pass		
(16QAM)			NV	10	1.24	0.000662		Pass		
				20	-0.86	-0.000457		Pass		
				30	-0.03	-0.000015		Pass		
				40	-0.07	-0.000038		Pass		
				50	0.72	0.000380		Pass		
					LV		-1.32	-0.000692		Pass
			NV	25	0.54	0.000286		Pass		
			HV		-0.10	-0.000053		Pass		
				-30	-1.52	-0.000797		Pass		
				-20	-0.46	-0.000241		Pass		
		Himb CH		-10	-1.00	-0.000526	./ 2.5	Pass		
		High CH		0	-0.67	-0.000353	+/- 2.5	Pass Pass Pass Pass Pass Pass Pass Pass		
			NV	10	-0.77	-0.000406		Pass		
				20	-1.27	-0.000669		Pass		
				30	-0.93	-0.000489		Pass		
				40	-1.02	-0.000534		Pass		
				50	0.19	0.000098		Pass		
LV=3.25V,	NV=3.80V, H	V=4.35V								

Mode	Test Bandwidth	Test Channel	Test Volt.	Test Temp.	Frequency error (Hz)	Result (ppm)	Limit (ppm)	Verdict
			LV		-0.31	-0.000169		Pass
			NV	25	0.23	0.000123		Pass
			HV		0.47	0.000254		Pass
				-30	0.04	0.000023		Pass
				-20	-1.36	-0.000731		Pass
		Low CH		-10	-0.47	-0.000254	+/- 2.5	Pass
		LOW CH		0	-1.26	-0.000677	+/- 2.5	Pass
			NV	10	0.03	0.000015		Pass
				20	0.50	0.000269		Pass
				30	-0.54	-0.000292		Pass
				40	-0.44	-0.000238		Pass
				50	0.83	0.000446		Pass
			LV		0.23	0.000122		Pass
			NV	25	-1.04	-0.000555		Pass
			HV		-0.76	-0.000403		Pass
				-30	0.04	0.000023		Pass
				-20	0.00	0.000000		Pass
LTE	20.0	Middle		-10	1.33	0.000708	./ 2.5	Pass
BAND II	20.0	СН		0	-0.17	-0.000091	+/- 2.5	Pass
(16QAM)			NV	10	0.33	0.000175		Pass
				20	-0.97	-0.000517		Pass
				30	-0.30	-0.000160		Pass
				40	0.04	0.000023		Pass
				50	-0.60	-0.000320		Pass
			LV		0.21	0.000113		Pass
			NV	25	0.50	0.000264		Pass
			HV		-0.49	-0.000256		Pass
				-30	-0.36	-0.000188		Pass
				-20	1.04	0.000550		Pass
		Himb CH		-10	-0.62	-0.000324	./ 2.5	Pass
		High CH		0	0.92	0.000482	+/- 2.5	Pass
			NV	10	0.04	0.000023		Pass Pass Pass Pass Pass Pass Pass Pass
				20	0.27	0.000143		Pass
				30	-0.69	-0.000361		Pass
				40	0.06	0.000030		Pass
				50	-0.89	-0.000467		Pass
LV=3.25V,	NV=3.80V, H	V=4.35V						

Mode	Test Bandwidth	Test Channel	Test Volt.	Test Temp.	Frequency error (Hz)	Result (ppm)	Limit (ppm)	Verdict		
			LV		1.53	0.000895	(ррин)	Pass		
			NV	25	1.39	0.000811		Pass		
			HV		2.55	0.001488		Pass		
				-30	1.72	0.001003		Pass		
				-20	1.24	0.000728		Pass		
		1 av. (CL)		-10	-1.56	-0.000911	., 0.5	Pass		
		Low CH		0	-1.27	-0.000744	+/- 2.5	Pass		
			NV	10	1.72	0.001003		Pass		
				20	3.15	0.001840		Pass		
				30	3.15	0.001840		Pass		
				40	-1.17	-0.000686		Pass		
				50	-0.63	-0.000368		Pass		
			LV		-0.23	-0.000132		Pass		
			NV	25	-3.20	-0.001850		Pass		
			HV		-2.86	-0.001651		Pass		
				-30	-1.62	-0.000933		Pass		
				-20	-1.14	-0.000661		Pass		
LTE	1.4	Middle		-10	2.65	0.001528	./ 25	Pass		
BAND IV	1.4	СН		0	-0.90	-0.000520	+/- 2.5	Pass		
(QPSK)			NV	10	-0.21	-0.000124		Pass		
				20	0.21	0.000124		Pass		
				30	-1.13	-0.000652		Pass		
				40	-0.24	-0.000140		Pass		
				50	-0.43	-0.000248		Pass		
					LV		1.09	0.000620		Pass
			NV	25	0.27	0.000155		Pass		
			HV		2.15	0.001223		Pass		
				-30	0.82	0.000465		Pass		
				-20	2.39	0.001362		Pass		
		High CH		-10	1.00	0.000571	1/ 25	Pass		
		High CH		0	0.80	0.000457	+/- 2.5	Pass		
			NV	10	1.42	0.000807		Pass		
				20	0.87	0.000497		Pass		
				30	1.02	0.000579		Pass		
				40	-2.85	-0.001623		Pass		
				50	-1.87	-0.001068		Pass		
LV=3.25V,	NV=3.80V, H	V=4.35V						· <u> </u>		

Mode	Test Bandwidth	Test Channel	Test Volt.	Test Temp.	Frequency error (Hz)	Result (ppm)	Limit (ppm)	Verdict
			LV		1.17	0.000685	(рржу	Pass
			NV	25	0.13	0.000075		Pass
			HV		3.16	0.001847		Pass
				-30	-1.93	-0.001128		Pass
				-20	-1.29	-0.000752		Pass
		1 av. (CL)		-10	-1.75	-0.001020	. / 2.5	Pass
		Low CH		0	-1.86	-0.001087	+/- 2.5	Pass
			NV	10	2.66	0.001555		Pass
				20	3.56	0.002081		Pass
				30	-0.60	-0.000351		Pass
				40	3.39	0.001981		Pass
				50	2.60	0.001521		Pass
			LV		-2.00	-0.001156		Pass
			NV	25	0.00	0.000000		Pass
			HV		1.86	0.001073		Pass
				-30	-2.69	-0.001552		Pass
				-20	-3.53	-0.002039		Pass
LTE	3.0	Middle		-10	1.13	0.000652	+/- 2.5	Pass
BAND IV (QPSK)	3.0	CH		0	0.23	0.000132	+/- 2.5	Pass
(QFSK)			NV	10	-1.02	-0.000586		Pass
				20	2.60	0.001503		Pass
				30	-2.17	-0.001255		Pass
				40	-2.13	-0.001230		Pass
				50	2.68	0.001544		Pass
			LV		-0.30	-0.000171		Pass
			NV	25	2.40	0.001371		Pass
			HV		0.96	0.000547		Pass
				-30	0.14	0.000082		Pass
				-20	-0.17	-0.000098		Pass
		High CH		-10	-0.57	-0.000326	+/- 2.5	Pass
		Tilgil CH		0	-0.07	-0.000041	17- 2.0	Pass Pass Pass Pass Pass Pass Pass Pass
			NV	10	1.73	0.000987		Pass
				20	1.63	0.000930		Pass
				30	2.72	0.001550		Pass
				40	-2.22	-0.001264		Pass
				50	-1.79	-0.001020		Pass
LV=3.25V,	NV=3.80V, H	V=4.35V					_	

Mode	Test Bandwidth	Test Channel	Test Volt.	Test Temp.	Frequency error (Hz)	Result (ppm)	Limit (ppm)	Verdict		
			LV		2.42	0.001412	,, ,	Pass		
			NV	25	-0.66	-0.000384		Pass		
			HV		-1.90	-0.001111		Pass		
				-30	0.41	0.000242		Pass		
				-20	0.94	0.000551		Pass		
		Low CH		-10	0.01	0.000008	./ 2.5	Pass		
		LOW CH		0	-0.14	-0.000084	+/- 2.5	Pass		
			NV	10	-0.07	-0.000042		Pass		
				20	-1.22	-0.000710		Pass		
				30	0.72	0.000418		Pass		
				40	0.77	0.000451		Pass		
				50	2.53	0.001479		Pass		
			LV		-1.06	-0.000611		Pass		
			NV	25	-1.75	-0.001007		Pass		
			HV		-0.13	-0.000074		Pass		
				-30	-0.49	-0.000281		Pass		
				-20	-1.07	-0.000619		Pass		
LTE	F 0	Middle		-10	1.97	0.001139	./ 2.5	Pass		
BAND IV	5.0	СН		0	-1.66	-0.000958	+/- 2.5	Pass		
(QPSK)			NV	10	-1.63	-0.000941		Pass		
				20	-2.02	-0.001164		Pass		
				30	1.10	0.000636		Pass		
				40	-0.27	-0.000157		Pass		
				50	1.19	0.000685		Pass		
			LV		0.79	0.000449		Pass		
			NV	25	0.80	0.000457		Pass		
			HV		-0.90	-0.000514		Pass		
				-30	-0.99	-0.000563		Pass		
				-20	-1.32	-0.000751		Pass		
		Himb OH		-10	4.09	0.002335	./ 2.5	Pass		
		High CH		0	-0.70	-0.000400	+/- 2.5	Pass		
			NV	10	2.46	0.001404		Pass Pass Pass Pass Pass Pass Pass Pass		
				20	-1.10	-0.000629		Pass		
				30	-1.23	-0.000702		Pass		
				40	-0.69	-0.000392	-	Pass		
				50	4.68	0.002669		Pass		
LV=3.25V,	LV=3.25V, NV=3.80V, HV=4.35V									

Mode	Test Bandwidth	Test Channel	Test Volt.	Test Temp.	Frequency error (Hz)	Result (ppm)	Limit (ppm)	Verdict						
			LV		0.41	0.000242	```	Pass						
			NV	25	0.36	0.000209		Pass						
			HV		0.53	0.000309		Pass						
				-30	-0.31	-0.000184		Pass						
				-20	0.66	0.000384		Pass						
		Low CH		-10	-0.93	-0.000542	+/- 2.5	Pass						
		LOW CH		0	1.63	0.000951	+/- 2.5	Pass						
			NV	10	0.93	0.000542		Pass						
				20	-0.24	-0.000142		Pass						
				30	-0.56	-0.000325		Pass						
				40	0.39	0.000225		Pass						
				50	-0.64	-0.000375		Pass						
			LV		-0.87	-0.000504		Pass						
			NV	25	-0.60	-0.000347		Pass						
			HV		1.06	0.000611		Pass						
				-30	0.37	0.000215		Pass						
				-20	0.57	0.000330		Pass						
LTE	10.0	Middle		-10	-0.39	-0.000223	+/- 2.5	Pass						
BAND IV	10.0	СН		0	0.10	0.000058	+/- 2.5	Pass						
(QPSK)			NV	10	0.17	0.000099		Pass						
				20	0.21	0.000124		Pass						
				30	-0.30	-0.000173		Pass						
				40	1.19	0.000685		Pass						
				50	0.20	0.000116		Pass						
			LV		0.23	0.000131		Pass						
			NV	25	0.23	0.000131		Pass						
			HV		0.86	0.000490		Pass						
				-30	0.14	0.000082		Pass						
				-20	-0.11	-0.000065		Pass						
		High CII		-10	-0.09	-0.000049	1/ 25	Pass						
		High CH		0	0.27	0.000155	+/- 2.5	Pass						
			NV	10	-0.51	-0.000294		Pass Pass Pass Pass Pass Pass Pass Pass						
				20	-0.09	-0.000049		Pass						
				30	-0.07	-0.000041		Pass						
				40	0.31	0.000180		Pass						
				50	0.31	0.000180		Pass						
LV=3.25V,	, NV=3.80V, H	V=4.35V			LV=3.25V, NV=3.80V, HV=4.35V									

Mode	Test Bandwidth	Test Channel	Test Volt.	Test Temp.	Frequency error (Hz)	Result (ppm)	Limit (ppm)	Verdict
			LV		1.83	0.001066	(I ¹ I ¹)	Pass
			NV	25	-0.34	-0.000200		Pass
			HV		-0.33	-0.000192		Pass
			_	-30	0.13	0.000075		Pass
				-20	0.39	0.000225		Pass
		1 av. (CL)		-10	0.43	0.000250	. / 0.5	Pass
		Low CH		0	0.16	0.000092	+/- 2.5	Pass
			NV	10	0.00	0.000000		Pass
				20	0.80	0.000466		Pass
				30	0.40	0.000233		Pass
				40	-0.29	-0.000167		Pass
				50	0.53	0.000308		Pass
			LV		0.10	0.000058		Pass
			NV	25	0.33	0.000190		Pass
			HV		-0.13	-0.000074		Pass
				-30	0.09	0.000050		Pass
				-20	0.76	0.000438		Pass
LTE	15.0	Middle		-10	-0.69	-0.000396	+/- 2.5	Pass
BAND IV (QPSK)	15.0	CH		0	-0.70	-0.000405	+/- 2.5	Pass
(Qr Sit)			NV	10	-0.50	-0.000289		Pass
				20	0.27	0.000157		Pass
				30	0.33	0.000190		Pass
				40	0.50	0.000289		Pass
				50	0.41	0.000239		Pass
			LV		0.64	0.000368		Pass
			NV	25	0.92	0.000524		Pass
			HV		0.16	0.000090		Pass
				-30	0.62	0.000352		Pass
				-20	-0.80	-0.000458		Pass
		High CH		-10	1.06	0.000606	+/- 2.5	Pass
		Tilgil Oll		0	0.70	0.000401	1,- 2.0	Pass Pass Pass Pass Pass Pass Pass Pass
			NV	10	0.11	0.000065		Pass
				20	1.00	0.000573		Pass
				30	1.13	0.000647		Pass
				40	-0.40	-0.000229		Pass
				50	0.72	0.000409		Pass
LV=3.25V,	NV=3.80V, H	V=4.35V						

Mode	Test Bandwidth	Test Channel	Test Volt.	Test Temp.	Frequency error (Hz)	Result (ppm)	Limit (ppm)	Verdict						
			LV		1.14	0.000665	TI-I- /	Pass						
			NV	25	0.29	0.000166		Pass						
			HV		1.44	0.000840		Pass						
			_	-30	0.34	0.000200		Pass						
				-20	0.00	0.000000		Pass						
		1 av. (CL)		-10	0.84	0.000491	. / 2.5	Pass						
		Low CH		0	0.72	0.000416	+/- 2.5	Pass						
			NV	10	-0.21	-0.000125		Pass						
				20	0.30	0.000175		Pass						
				30	1.34	0.000782		Pass						
				40	0.47	0.000274		Pass						
				50	0.37	0.000216		Pass						
			LV		-0.23	-0.000132		Pass						
			NV	25	1.10	0.000636		Pass						
			HV		-0.49	-0.000281		Pass						
				-30	0.14	0.000083		Pass						
				-20	0.69	0.000396		Pass						
LTE	20.0	Middle		-10	1.00	0.000578	+/- 2.5	Pass						
BAND IV (QPSK)	20.0	CH		0	1.65	0.000950	+/- 2.5	Pass						
(QFSK)			NV	10	0.30	0.000173		Pass						
				20	0.92	0.000528		Pass						
				30	0.17	0.000099		Pass						
				40	-0.07	-0.000041		Pass						
				50	0.21	0.000124		Pass						
			LV		-0.30	-0.000172		Pass						
			NV	25	1.77	0.001017		Pass						
			HV		1.14	0.000656		Pass						
				-30	0.80	0.000459		Pass						
				-20	0.86	0.000492		Pass						
		High CH		-10	0.14	0.000082	+/- 2.5	Pass						
		Tilgil CH		0	0.19	0.000107	17- 2.0	Pass Pass Pass Pass Pass Pass Pass Pass						
			NV	10	-0.67	-0.000385		Pass						
				20	-0.44	-0.000254		Pass						
				30	-0.11	-0.000066		Pass						
				40	-0.40	-0.000230		Pass						
				50	-0.13	-0.000074		Pass						
LV=3.25V,	NV=3.80V, H	V=4.35V			LV=3.25V, NV=3.80V, HV=4.35V									

FCC ID: 2AGDXSP5049G

Mode	Test Bandwidth	Test Channel	Test Volt.	Test Temp.	Frequency error (Hz)	Result (ppm)	Limit (ppm)	Verdict
			LV		1.83	0.001070		Pass
			NV	25	0.62	0.000360		Pass
			HV		0.13	0.000075		Pass
				-30	-2.16	-0.001263		Pass
				-20	-1.77	-0.001037		Pass
		Low CH		-10	-1.33	-0.000778	./ 2.5	Pass
		Low CH		0	-0.07	-0.000042	+/- 2.5	Pass
			NV	10	0.04	0.000025		Pass
				20	0.99	0.000577		Pass
				30	1.63	0.000953		Pass
				40	1.66	0.000970		Pass
				50	-0.36	-0.000209		Pass
			LV		-1.56	-0.000900		Pass
			NV	25	-1.06	-0.000611		Pass
			HV		-1.70	-0.000983		Pass
				-30	1.40	0.000809		Pass
				-20	2.89	0.001668		Pass
LTE	1.4	Middle		-10	-0.83	-0.000479	+/- 2.5	Pass
BAND IV (16QAM)	1.4	CH		0	-2.59	-0.001495	17- 2.5	Pass
(10QAIVI)			NV	10	3.20	0.001850		Pass
				20	3.03	0.001750		Pass
				30	2.55	0.001470		Pass
				40	1.83	0.001057		Pass
				50	2.12	0.001222		Pass
			LV		-0.80	-0.000457		Pass
			NV	25	-1.87	-0.001068		Pass
			HV		0.11	0.000065		Pass
				-30	-0.16	-0.000090		Pass
				-20	0.83	0.000473		Pass
		High CH		-10	1.46	0.000832	+/- 2.5	Pass
		Tilgil CH		0	1.79	0.001019	17- 2.0	Pass
			NV	10	1.60	0.000913		Pass
				20	3.28	0.001867		Pass
				30	1.09	0.000620		Pass
				40	2.07	0.001182		Pass
				50	1.52	0.000864		Pass
LV=3.25V,	, NV=3.80V, H	V=4.35V						

Mode	Test Bandwidth	Test Channel	Test Volt.	Test Temp.	Frequency error (Hz)	Result (ppm)	Limit (ppm)	Verdict		
			LV		1.17	0.000685		Pass		
			NV	25	0.13	0.000075		Pass		
			HV	3.16 0.001847		Pass				
				-30	-0.44	-0.000259	+/- 2.5	Pass		
		1 011		-20	0.84	0.000493		Pass		
				-10	1.19	0.000694		Pass		
		Low CH		0	-2.70	-0.001580		Pass		
			NV	10	0.80	0.000468		Pass		
				20	1.75	0.001020		Pass		
				30	-2.32	-0.001354		Pass		
				40	-1.34	-0.000786		Pass		
				50	-0.11	-0.000067		Pass		
			LV		-2.00	-0.001156	+/- 2.5	Pass		
			NV	25	0.00	0.000000		Pass		
			HV		1.86	0.001073		Pass		
	3.0	Middle CH	NV	-30	-1.86	-0.001073		Pass		
				-20	-1.92	-0.001106		Pass		
LTE				-10	1.93	0.001115		Pass		
BAND IV (16QAM)				0	2.53	0.001461		Pass		
(TOQAIVI)				10	2.19	0.001263		Pass		
				20	1.24	0.000718		Pass		
				30	1.73	0.000999		Pass		
				40	1.73	0.000999		Pass		
				50	1.30	0.000751		Pass		
			LV		-0.30	-0.000171		Pass		
			NV	25	2.40	0.001371		Pass		
			HV		0.96	0.96 0.000547		Pass		
				-30	1.57	0.000897		Pass		
				-20	-2.53	-0.001444		Pass		
		Himb CH		-10	3.15	0.001795	./ 2.5	Pass		
	Hig	High CH		0	3.75	0.002137	+/- 2.5	Pass		
			NV	10	-0.31	-0.000179		Pass		
				20	-2.10	-0.001199		Pass		
				30	-2.09	-0.001191		Pass		
				40	2.60	0.001485		Pass		
				50	2.90	0.001656		Pass		
LV=3.25V,	LV=3.25V, NV=3.80V, HV=4.35V									

Mode	Test Bandwidth	Test Channel	Test Volt.	Test Temp.	Frequency error (Hz)	Result (ppm)	Limit (ppm)	Verdict						
			LV		0.50	0.000292	+/- 2.5	Pass						
			NV	25	-1.99	-0.001161		Pass						
			HV		-1.37	-0.000802		Pass						
				-30	-1.02	-0.000593		Pass						
				-20	1.22	0.000710		Pass						
				-10	0.94	0.000551		Pass						
		Low CH		0	0.57	0.000334		Pass						
			NV	10	2.29	0.001337		Pass						
				20	0.39	0.000226		Pass						
				30	-0.84	-0.000493		Pass						
				40	0.59	0.000342		Pass						
				50	-0.09	-0.000050		Pass						
			LV		-2.22	-0.001280	+/- 2.5	Pass						
			NV	25	2.69	0.001552		Pass						
			HV		0.39	0.000223		Pass						
	5.0	Middle CH High CH	NV	-30	-2.49	-0.001437		Pass						
				-20	-1.33	-0.000768		Pass						
LTE				-10	0.99	0.000570		Pass						
BAND IV (16QAM)				0	-1.87	-0.001082		Pass						
(TOQAIVI)				10	-1.36	-0.000784		Pass						
				20	-1.57	-0.000908		Pass						
				30	-1.50	-0.000867		Pass						
				40	-2.70	-0.001561		Pass						
				50	2.35	0.001354		Pass						
			LV NV	25	1.93	0.001102		Pass						
					-0.89	-0.000506		Pass						
			HV		0.62	0.000351		Pass						
				-30	0.60	0.000343		Pass						
				-20	2.03	0.001159		Pass						
				-10	-2.10	-0.001200	., 25	Pass						
				0	0.67	0.000384	+/- 2.5	Pass						
			NV	10	2.65	0.001510		Pass						
				20	4.02	0.002294		Pass						
				30	4.16	0.002375		Pass						
				40	0.20	0.000114		Pass						
				50	0.70	0.000400		Pass						
LV=3.25V,	NV=3.80V, H	V=4.35V			LV=3.25V, NV=3.80V, HV=4.35V									

Mode	Test Bandwidth	Test Channel	Test Volt.	Test Temp.	Frequency error (Hz)	Result (ppm)	Limit (ppm)	Verdict		
			LV	25	-0.03	-0.000017	+/- 2.5	Pass		
			NV		0.39	0.000225		Pass		
			HV		0.20	0.000117		Pass		
				-30	0.00	0.000000		Pass		
		Low CH		-20	0.10	0.000058		Pass		
				-10	0.69	0.000400		Pass		
				0	0.24	0.000142		Pass		
			NV	10	0.51	0.000300		Pass		
				20	0.74	0.000434		Pass		
				30	0.01	0.000008		Pass		
				40	0.14	0.000083		Pass		
				50	-0.09	-0.000050		Pass		
			LV		-0.26	-0.000149		Pass		
			NV	25	-0.89	-0.000512		Pass		
		Middle CH	HV	1	-0.33	-0.000190	+/- 2.5	Pass		
	10.0		NV	-30	-0.76	-0.000438		Pass		
				-20	-0.82	-0.000471		Pass		
LTE				-10	-0.90	-0.000520		Pass		
BAND IV (16QAM)				0	0.33	0.000190		Pass		
(TOQ/NIVI)				10	0.34	0.000198		Pass		
				20	-1.46	-0.000842		Pass		
				30	-0.27	-0.000157		Pass		
				40	0.21	0.000124		Pass		
				50	0.10	0.000058		Pass		
			LV NV	25	1.59	0.000907		Pass		
					-0.40	-0.000229		Pass		
			HV		0.86	0.000490		Pass		
				-30	-0.04	-0.000025		Pass		
				-20	0.60	0.000343		Pass		
		High CH		-10	0.00	0.000000	+/- 2.5	Pass		
		High CH		0	-0.20	-0.000114	17- 2.0	Pass		
			NV	10	1.07	0.000613		Pass		
				20	0.44	0.000253		Pass		
				30	0.69	0.000392		Pass		
				40	-0.37	-0.000213	1	Pass		
				50	0.62	0.000351		Pass		
LV=3.25V,	LV=3.25V, NV=3.80V, HV=4.35V									

Mode	Test Bandwidth	Test Channel	Test Volt.	Test Temp.	Frequency error (Hz)	Result (ppm)	Limit (ppm)	Verdict		
			LV		1.10	0.000641	+/- 2.5	Pass		
			NV HV	25	0.84	0.000491		Pass		
					0.41	0.000242		Pass		
				-30	0.96	0.000558		Pass		
				-20	0.40	0.000233		Pass		
				-10	0.34	0.000200		Pass		
		Low CH		0	0.33	0.000192		Pass		
			NV	10	0.69	0.000400		Pass		
				20	0.51	0.000300		Pass		
				30	-0.33	-0.000192		Pass		
				40	0.46	0.000267		Pass		
				50	0.69	0.000400		Pass		
			LV		0.92	0.000528		Pass		
			NV	25	1.30	0.000751		Pass		
			HV]	0.57	0.000330	+/- 2.5	Pass		
	15.0	Middle CH	NV	-30	0.19	0.000107		Pass		
				-20	0.60	0.000347		Pass		
LTE				-10	0.31	0.000182		Pass		
BAND IV (16QAM)				0	-0.31	-0.000182		Pass		
(TOQAIVI)				10	0.59	0.000339		Pass		
				20	0.03	0.000017		Pass		
				30	0.07	0.000041		Pass		
				40	0.67	0.000388		Pass		
				50	0.36	0.000206		Pass		
			LV NV	25	0.07	0.000041		Pass		
					-0.73	-0.000417		Pass		
			HV		0.33	0.000188		Pass		
				-30	0.99	0.000565		Pass		
				-20	0.62	0.000352		Pass		
				-10	-0.63	-0.000360	1 2.5	Pass		
		High CH		0	-0.16	-0.000090	+/- 2.5	Pass		
			NV	10	0.19	0.000106		Pass		
				20	-0.06	-0.000033		Pass		
				30	0.56	0.000319		Pass		
				40	-1.33	-0.000761		Pass		
				50	0.07	0.000041		Pass		
LV=3.25V,	LV=3.25V, NV=3.80V, HV=4.35V									

Mode	Test Bandwidth	Test Channel	Test Volt.	Test Temp.	Frequency error (Hz)	Result (ppm)	Limit (ppm)	Verdict	
			LV		1.32	0.000765	(I-I-)	Pass	
			NV			Pass			
			HV		-0.21	-0.000125	+/- 2.5	Pass	
				-30	0.86	0.000499		Pass	
		Low CH		-20	1.76	0.001023		Pass	
				-10	0.56	0.000324		Pass	
				0	0.37	0.000216		Pass	
			NV	10	0.63	0.000366		Pass	
				20	0.82	0.000474		Pass	
				30	-0.04	-0.000025		Pass	
				40	-0.14	-0.000083		Pass	
				50	0.56	0.000324		Pass	
			LV		0.34	0.000198	+/- 2.5	Pass	
			NV	25	-0.19	-0.000107		Pass	
	20.0	Middle CH High CH	HV		-0.07	-0.000041		Pass	
			NV	-30	-0.56	-0.000322		Pass	
				-20	0.00	0.000000		Pass	
LTE				-10	-0.17	-0.000099		Pass	
BAND IV (16QAM)				0	0.49	0.000281		Pass	
(10QAIVI)				10	-0.10	-0.000058		Pass	
				20	-0.17	-0.000099		Pass	
				30	-0.31	-0.000182		Pass	
				40	0.07	0.000041		Pass	
				50	1.37	0.000793		Pass	
			LV NV HV	25	0.24	0.000139		Pass	
					0.36	0.000205		Pass	
					-0.31	-0.000180		Pass	
				-30	1.07	0.000615		Pass	
				-20	0.60	0.000344		Pass	
				-10	0.93	0.000533	+/- 2.5	Pass	
				0	0.21	0.000123	.,- 2.5	Pass	
			NV	10	0.17	0.000098		Pass	
				20	-0.24	-0.000139		Pass	
				30	0.72	0.000410	-	Pass	
				40	-0.64	-0.000369		Pass	
				50	-0.16	-0.000090		Pass	
LV=3.25V, NV=3.80V, HV=4.35V									