

# FCC §15.247 (i), §2.1091 - RF Exposure

# FCC ID: 2AGDZRLC-410WS

### Applied procedures / limit

According to FCC §15.247(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

**Limits for Occupational / Controlled Exposure** 

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> , H  <sup>2</sup> or S (minutes)	
0.3-3.0	614	1.63	(100)*	6	
3.0-30	1842 / f	4.89 / f	(900 / f)*	6	
30-300	61.4	0.163	1.0	6	
300-1500			F/300	6	
1500-100,000			5	6	

Note: *f* is frequency in MHz

#### **Limits for General Population / Uncontrolled Exposure**

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm²)	Averaging Time  E  <sup>2</sup> , H  <sup>2</sup> or S (minutes)	
0.3-1.34	614	1.63	(100)*	30	
1.34-30	824/f	2.19/f	(180/f)*	30	
30-300	27.5	0.073	0.2	30	
300-1500			F/1500	30	
1500-100,000			1.0	30	

Note: f = frequency in MHz

<sup>\* =</sup> Power density limit is applicable at frequencies greater than 100 MHz

<sup>\* =</sup> Plane-wave equivalent power density



## MPE PREDICTION

Predication of MPE limit at a given distance, Equation from OET Bulletin 65, Edition 97-01

 $S = PG/4\pi R^2$ 

Where: S = power density

P = power input to antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator R = distance to the center of radiation of the antenna, R=0.2m

#### **TEST RESULTS**

	Tune up Produce power	Maximum peak output power (dBm)	Output power to antenna (mW)	Antenna Gain (numeric)	Power Density (S) (mW/ cm2)	Limit of Power Density (S) (mW/ cm2)	Result
WIFI 2.4G 802.11b	17±1	18	63.10	2.00(3.0dBi)	0.02505	1	Pass
WIFI 2.4G 802.11g	15±1	16	39.81	2.00(3.0dBi)	0.01580	1	Pass
WIFI 2.4G 802.11n(HT 20)	14±1	15	31.62	2.00(3.0dBi)	0.01255	1	Pass
5G WIFI 802.11a	14±1	14	25.12	2.00(3.0dBi)	0.00997	1	Pass
5G WIFI 802.11n(HT 20)	13±1	14	25.12	2.00(3.0dBi)	0.00997	1	Pass