

## RF EXPOSURE EVALUATION

### 1. PRODUCT INFORMATION

Product Description	TWS Earphones
Model Name	Q65, QAIR-BUDS, Q61, Q62, Q63, Q64, Q66, Q67, Q68, Q69, Q70, Qxx (xx represents 01~99)
FCC ID	2AGHA-Q65

### 2. EVALUATION METHOD

According to 447498 D01 General RF Exposure Guidance v05

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR.

Where  $f(\text{GHz})$  is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

### 3. CALCULATION

$$P_t = -6.229\text{dBm} = 0.24\text{mW}$$

The value of the Maximum output power  $P_t$  is referred to the test report of the **CFR47**

**§15.247.**

The result for RF exposure evaluation  $\text{SAR} = (0.24\text{mW} / 5\text{mm}) \cdot [\sqrt{2.480(\text{GHz})}] = 0.08 < 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR.

### 4. CONCLUSION

The SAR evaluation is not required.