



# EMC TEST REPORT

**Report No.:** SET2015-17333

**Product Name:** GPON SFU

**FCC ID:** 2AGHCHBMT04

**Model No. :** 7279G/7278G/7272G

**Applicant:** Guangdong Hisense Broadband Technology Co.,Ltd

**Address:** Building 2, No.8, Hisense Road, Tangxia Town, Pengjiang District,  
Jiangmen City, Guangdong China

**Received Date:** 2015-11-16

**Tested Date:** 2015-11-16—2015-12-07

**Issued by:** CCIC-SET

**Lab Location:** Electronic Testing Building, Shahe Road, Xili, Nanshan District,  
Shenzhen, 518055, P. R. China

**Tel:** 86 755 26627338    **Fax:** 86 755 26627238

This test report consists of **28** pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by CCIC-SET. The test results in the report only apply to the tested sample. The test report shall be invalid without all the signatures of testing engineers, reviewer and approver. Any objections must be raised to CCIC-SET within 15 days since the date when the report is received. It will not be taken into consideration beyond this limit.



## Test Report

**Product Name** ..... : GPON SFU

**Model No.** ..... : 7279G/7278G/7272G

**Applicant** ..... : Guangdong Hisense Broadband Technology Co.,Ltd

**Applicant Address** ..... : Building 2, No.8, Hisense Road, Tangxia Town,  
Pengjiang District, Jiangmen City, Guangdong China

**Manufacturer** ..... : Guangdong Hisense Broadband Technology Co.,Ltd

**Manufacturer Address** ..... : Building 2, No.8, Hisense Road, Tangxia Town,  
Pengjiang District, Jiangmen City, Guangdong China

**Test Standards** ..... : 47 CFR Part 15 Subpart B: Radio Frequency Devices

**Test Result** ..... : PASS

**Tested by** ..... : Xiaolong Zhang 2015.12.24  
Xiaolong Zhang, Test Engineer

**Reviewed by** ..... : Shuangwen Zhang 2015.12.24  
Shuangwen Zhang, Senior Engineer

**Approved by** ..... : Wu Lian 2015.12.24  
Wu Li'an, Manager

**TABLE OF CONTENTS**

<b>1.</b>	<b>GENERAL INFORMATION .....</b>	<b>4</b>
<b>1.1</b>	<b>EUT Description .....</b>	<b>4</b>
<b>1.2</b>	<b>Test Standards and Results .....</b>	<b>5</b>
<b>1.3</b>	<b>Facilities and Accreditations .....</b>	<b>6</b>
1.3.1	Facilities .....	6
1.3.2	Test Environment Conditions .....	6
1.3.3	Measurement Uncertainty .....	6
<b>2.</b>	<b>TEST CONDITIONS SETTING.....</b>	<b>7</b>
<b>2.1</b>	<b>Test Peripherals .....</b>	<b>7</b>
<b>2.2</b>	<b>Test Mode .....</b>	<b>7</b>
<b>2.3</b>	<b>Test Setup and Equipments List.....</b>	<b>8</b>
2.3.1	Conducted Emission.....	8
2.3.2	Radiated Emission.....	8
<b>3.</b>	<b>47 CFR PART 15B REQUIREMENTS .....</b>	<b>11</b>
<b>3.1</b>	<b>Conducted Emission .....</b>	<b>11</b>
3.1.1	Requirement .....	11
3.1.2	Test Description .....	11
3.1.3	Test Result .....	11
<b>3.2</b>	<b>Radiated Emission .....</b>	<b>18</b>
3.2.1	Requirement .....	18
3.2.2	Test Description .....	19
3.2.3	Test Result .....	19

Change History		
Issue	Date	Reason for change
1.0	2015.12.24	First edition
2.0	2016.01.10	Second edition



## 1. GENERAL INFORMATION

### 1.1 EUT Description

EUT Name ..... : GPON SFU  
FCC ID ..... : 2AGHCHBMT04  
Trade Name..... : iPhotonix /Ligent /Hisense  
Brand Name..... : iPhotonix /Ligent /Hisense  
Hardware Version..... : RGAC7.820.916  
Software Version ..... : /  
Ancillary Equipment 1 ..... : AC Adapter1  
Model No.: YJS024U-1202000U  
Rated Input: 100-240V, 50/60Hz ,0.8A  
Rated Output: 12V=2.0A  
AC Adapter 2  
Model No.: RD1202000-C55-29MG  
Rated Input: 100-240V, 50/60Hz ,0.6A  
Rated Output: 12V=2.0A  
RJ45 cable  
Model No.: CAT5E-2M-YELLOW-AL

*Note1:*The EUT is a GPON SFU, it supports the following operating frequency band: WiFi 2.4G(b/g/n20/n40),WiFi 5G.

*Note2:* The highest operation frequency or processor operate frequency is 400 MHz.

*Note3:*The EUT has three models: 7279G/7278G/7272G.Only the model 7279G contains all the functions, which is recorded in this report .The difference of them is listed as below:

Main Model No	Serial Model No	Difference
7279G	7278G/7272G	7279G: 2POTS+2GE+MOCA+CATV+Return+WiFi 7278G: 2POTS+2GE+MOCA+CATV+WiFi 7272G: 2POTS+2GE+MOCA+WiFi

*Note 3:*For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.



## 1.2 Test Standards and Results

The objective of the report is to perform testing according to 47 CFR Part 15 Subpart B:

No.	Identity	Document Title
1	47 CFR Part 15 Subpart B 2014	Radio Frequency Devices

Test detailed items/section required by FCC rules and results are as below:

No.	Section	Description	Result
1	15.107	Conducted Emission	PASS
2	15.109	Radiated Emission	PASS

NOTE:

(1) The EUT has been tested according to 47 CFR Part 15 Subpart B, Class B. The test procedure is according to ANSI C63.4:2009.



## 1.3 Facilities and Accreditations

### 1.3.1 Facilities

#### **CNAS-Lab Code: L1659**

CCIC Southern Electronic Product Testing (Shenzhen) Co., Ltd. CCIC is a third party testing organization accredited by China National Accreditation Service for Conformity Assessment (CNAS) according to ISO/IEC 17025. The accreditation certificate number is L1659. A 12.8\*6.8\*6.4 (m) fully anechoic chamber was used for the radiated spurious emissions test.

#### **FCC-Registration No.: 406086**

CCIC Southern Electronic Product Testing (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files. Registration 406086, valid time is until October 28, 2017.

### 1.3.2 Test Environment Conditions

During the measurement, the environmental conditions were within the listed ranges:

Temperature (°C):	15°C - 35°C
Relative Humidity (%):	25% -75%
Atmospheric Pressure (kPa):	86kPa-106kPa

### 1.3.3 Measurement Uncertainty

The uncertainty is calculated using the methods suggested in the "Guide to the Expression of Uncertainty in Measurement" (GUM) published by ISO.

Uncertainty of Conducted Emission:	Uc = 3.6 dB (k=2)
Uncertainty of Radiated Emission:	Uc = 4.5 dB (k=2)



## 2. TEST CONDITIONS SETTING

### 2.1 Test Peripherals

The following is a listing of the EUT and peripherals utilized during the performance of EMC test:

Description	Brand name	Model	Serial No.	FCCID /DOC
Notebook	ThinkPad	E430C	A131101550	/
Mouse	deiog			DOC
Telephone	BOTEL	T186	/	/

### 2.2 Test Mode

- (1) The first test mode


The EUT configuration of the emission test is EUT + PC+Telephone+Adapter.

**Note:** The EUT has three models and two adapters, all of them have been tested in this report.  
Only the worse case was recorded in this report.

## 2.3 Test Setup and Equipments List

### 2.3.1 Conducted Emission

#### A. Test Setup:



The EUT is placed on a 0.8m high insulating table, which stands on the grounded conducting floor, and keeps 0.4m away from the grounded conducting wall. The EUT is connected to the power mains through a LISN which provides 50Ω/50μH of coupling impedance for the measuring instrument. The Common Antenna is used for the call between the EUT and the System Simulator (SS). A Pulse Limiter is used to protect the measuring instrument. The factors of the whole test system are calibrated to correct the reading.

#### B. Equipments List:


Description	Manufacturer	Model	Serial No.	Calibration Date	Calibration Due. Date
Test Receiver	ROHDE&SCHWARZ	ESCI	A130901475	2015.09.09	2016.09.08
LISN	ROHDE&SCHWARZ	ENV216	/	2015.04.28	2016.04.27
Cable	MATCHING PAD	W7	/	2015.06.05	2016.06.04

### 2.3.2 Radiated Emission


#### A. Test Setup:



- 1) For radiated emissions from 30MHz to 1GHz



- 2) For radiated emissions above 1GHz



## B. Test Procedure

The test is performed in a 3m Semi-Anechoic Chamber; the antenna factor, cable loss and so on of the site (factors) is calculated to correct the reading. The EUT is placed on a 0.8m high insulating Turn Table, and keeps 3m away from the Test Antenna, which is mounted on a

variable-height antenna master tower.

For the test Antenna:

- 1) In the frequency range above 30MHz, Bi-Log Test Antenna (30MHz to 1GHz) and Horn Test Antenna (above 1GHz) are used. Test Antenna is 3m away from the EUT. Test Antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength. The emission levels at both horizontal and vertical polarizations should be tested.

### C. Equipments List:

Description	Manufacturer	Model	Serial No.	Calibration Date	Calibration Due. Date
Test Receiver	ROHDE&SCHWARZ	ESIB7	A0501375	2015.06.10	2016.06.09
Test Receiver	ROHDE&SCHWARZ	ESIB26	A0304218	2015.06.10	2016.06.09
Semi-Anechoic Chamber	Albatross	9m*6m*6m	A0412372	2015.03.22	2016.03.21
Test Antenna - Bi-Log	HP	CBL6111A	A9704202	2015.06.10	2016.06.09
Test Antenna – Horn	ROHDE&SCHWARZ	HF906	A0304225	2015.06.10	2016.06.09
Anechoic Chamber	Albatross	SAC-5MAC 12.8x6.8x6.4m	A0304210	2015.03.22	2016.03.21
Amplifier 1G~18GHz	ROHDE&SCHWARZ	MITEQ AFS42-001018 00	A0509366	2015.06.10	2016.06.09
Amplifier 20M~3GHz	Compliance Direction System	PAP-0203H	A0509377	2015.06.10	2016.06.09
Cable	SUNHNER	SUCOFLEX 100	/	2015.06.10	2016.06.09
Cable	SUNHNER	SUCOFLEX 104	MY1758/4	2015.06.10	2016.06.09

### 3. 47 CFR PART 15B REQUIREMENTS

#### 3.1 Conducted Emission

##### 3.1.1 Requirement

According to FCC section 15.107, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150kHz to 30MHz shall not exceed the limits in the following table, as measured using a 50 $\mu$ H/50 $\Omega$  line impedance stabilization network (LISN).

Frequency range (MHz)	Conducted Limit (dB $\mu$ V)	
	Quasi-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
5 - 30	60	50

**Note:**

- The limit subjects to the Class B digital device.
- The lower limit shall apply at the band edges.
- The limit decreases linearly with the logarithm of the frequency in the range 0.15 - 0.50MHz.

##### 3.1.2 Test Description

See section 2.3.1 of this report.

##### 3.1.3 Test Result


The maximum conducted interference is searched using Peak (PK), Quasi-peak (QP) and Average (AV) detectors; the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. All test modes are considered, refer to recorded points and plots below.

**Note:**

Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a Nominal 120V AC,50/60Hz) for which the device is capable of operation. A device rated for 50/60 Hz operation need not be tested at both frequencies provided the radiated and line conducted emissions are the same at both frequencies.


# A. Test Plot and Suspicious Points:

EUT model:7279G, adapter model: YJS024U-1202000U




(Plot A: L Phase)

Conducted Disturbance at Mains Terminals							
L Test Data							
QP				AV			
Frequency (MHz)	Limits (dBμV)	Measurement Value (dBμV)	Margin (dB)	Frequency (MHz)	Limits (dBμV)	Measurement Value (dBμV)	Margin (dB)
0.5010	56.00	45.97	10.03	0.5010	46.00	35.70	10.30
0.5370	56.00	45.86	10.14	0.5370	46.00	35.02	10.98
0.6045	56.00	46.45	9.55	0.6045	46.00	33.38	12.62



(Plot B: N Phase)


Conducted Disturbance at Mains Terminals							
N Test Data							
QP				AV			
Frequency (MHz)	Limits (dBμV)	Measurement Value (dBμV)	Margin (dB)	Frequency (MHz)	Limits (dBμV)	Measurement Value (dBμV)	Margin (dB)
0.3705	58.50	44.92	13.58	0.3705	48.50	36.26	12.24
0.6810	56.00	40.39	15.61	0.6810	46.00	30.12	15.88
1.9050	56.00	41.36	14.64	1.9050	46.00	29.65	16.35

**EUT model:7278G, adapter model RD1202000-C55-29MG**


(Plot C: L Phase)

Conducted Disturbance at Mains Terminals							
L Test Data							
QP				AV			
Frequency (MHz)	Limits (dBμV)	Measurement Value (dBμV)	Margin (dB)	Frequency (MHz)	Limits (dBμV)	Measurement Value (dBμV)	Margin (dB)
0.1920	63.90	52.73	11.17	0.1920	53.90	37.51	16.39
0.3040	60.10	47.54	12.56	0.3040	50.10	35.44	14.66
0.3880	58.10	44.26	13.84	0.3880	48.10	32.14	15.96






(Plot D: N Phase)

Conducted Disturbance at Mains Terminals							
N Test Data							
QP				AV			
Frequency (MHz)	Limits (dBμV)	Measurement Value (dBμV)	Margin (dB)	Frequency (MHz)	Limits (dBμV)	Measurement Value (dBμV)	Margin (dB)
0.1920	63.90	48.95	14.95	0.1920	53.90	36.73	17.17
0.3880	58.10	41.81	16.29	0.3880	48.10	31.59	16.51
0.4650	56.60	40.58	16.02	0.4650	46.60	32.09	14.51


EUT model:7272G, adapter model RD1202000-C55-29MG



(Plot E: L Phase)

Conducted Disturbance at Mains Terminals							
L Test Data							
QP				AV			
Frequency (MHz)	Limits (dBμV)	Measurement Value (dBμV)	Margin (dB)	Frequency (MHz)	Limits (dBμV)	Measurement Value (dBμV)	Margin (dB)
0.1994	63.60	44.36	19.24	0.1994	53.60	33.65	19.95
0.4280	57.30	47.65	9.65	0.4424	47.00	36.49	10.51
2.9975	56.00	38.96	17.04	2.9725	46.00	27.53	18.47





(Plot F: N Phase)

Conducted Disturbance at Mains Terminals							
N Test Data							
QP				AV			
Frequency (MHz)	Limits (dBμV)	Measurement Value (dBμV)	Margin (dB)	Frequency (MHz)	Limits (dBμV)	Measurement Value (dBμV)	Margin (dB)
0.2581	61.50	44.39	17.11	0.2714	51.50	33.59	17.91
0.4245	57.40	47.28	10.12	0.4240	47.40	38.12	9.28
1.9825	56.00	40.18	15.82	2.0815	46.00	30.41	15.59

**Test Result: PASS**

## 3.2 Radiated Emission

### 3.2.1 Requirement

According to FCC section 15.109, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:

Frequency range (MHz)	Field Strength		Field Strength Limitation at 3m Measurement Dist	
	$\mu\text{V/m}$	Dist	( $\mu\text{V/m}$ )	( $\text{dBuV/m}$ )
0.009 - 0.490	$2400/F(\text{kHz})$	300m	$10000 * 2400/F(\text{kHz})$	$20\log 2400/F(\text{kHz}) + 80$
0.490 - 1.705	$2400/F(\text{kHz})$	30m	$100 * 2400/F(\text{kHz})$	$20\log 2400/F(\text{kHz}) + 40$
1.705 - 30.00	30	30m	$100 * 30$	$20\log 30 + 40$
30.0 - 88.0	100	3m	100	$20\log 100$
88.0 - 216.0	150	3m	150	$20\log 150$
216.0 - 960.0	200	3m	200	$20\log 200$
Above 960.0	500	3m	500	$20\log 500$

- As shown in FCC section 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector. When average radiated emission measurements are specified in this part, including emission measurements below 1000MHz, there also is a limit on the radio frequency emissions, as measured using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit for the frequency being investigated unless a different peak emission limit is otherwise specified in the rules.
- Test Antenna is 3m away from the EUT. Test Antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength.
- For below 1G :QP detector RBW 120kHz ,VBW 300kHz.
- For Above 1G: PK detector RBW 1MHz,VBW 3MHz for PK value ;PK detector RBW 1MHz, VBW 10Hz for AV value.

#### Note:

- The tighter limit shall apply at the boundary between two frequency range.
- Limitation expressed in  $\text{dBuV/m}$  is calculated by  $20\log \text{Emission Level}(\mu\text{V/m})$ .
- If measurement is made at 3m distance, then F.S Limitation at 3m distance is adjusted by using the formula of  $Ld1 = Ld2 * (d2/d1)^2$ .

Example:

F.S Limit at 30m distance is  $30\mu\text{V/m}$ , then F.S Limitation at 3m distance is adjusted as

$$Ld1 = L1 = 30\mu\text{V/m} * (10)^2 = 100 * 30\mu\text{V/m}.$$

### **3.2.2 Test Description**

See section 2.3.2 of this report.

### **3.2.3 Test Result**

The maximum radiated emission is searched using PK, QP and AV detectors; the emission levels more than the limits, and that have narrow margins from the limits will be re-measured with AV and QP detectors. Both the vertical and the horizontal polarizations of the Test Antenna are considered to perform the tests. All test modes are considered, refer to recorded points and plots below.


The amplitude of spurious emissions which are attenuated more than 20 dB below the permissible value need not be reported.

Note: All radiated emission tests were performed in X, Y, Z axis direction, and only the worst axis test condition was recorded in this test report.

## B. Test Plots and Suspicious Points:


EUT model:7279G ,adapter model YJS024U-1202000U

Test result of radiated emission below 1GHz



(Plot A: Test Antenna Vertical 30M - 1G)


Frequency (MHz)	QuasiPeak (dBμV/m)	Bandwidth (kHz)	Antenna height (cm)	Limit (dBμV/m)	Margin (dB)	Antenna	Verdict
30.05000	31.09	120.000	153.0	40.00	8.91	Vertical	Pass
49.08000	29.37	120.000	258.0	40.00	10.63	Vertical	Pass
362.51000	34.68	120.000	196.0	46.00	11.32	Vertical	Pass




(Plot B: Test Antenna Horizontal 30M - 1G)

Frequency (MHz)	QuasiPeak (dB $\mu$ V/m)	Bandwidth (kHz)	Antenna height (cm)	Limit (dB $\mu$ V/m)	Margin (dB)	Antenna	Verdict
179.38000	32.16	120.000	246.0	43.50	11.34	Horizontal	Pass
276.19000	35.04	120.000	169.0	46.00	10.96	Horizontal	Pass
361.28000	34.86	120.000	278.0	46.00	11.14	Horizontal	Pass

### Test result of radiated emission above 1GHz




(Plot C: Test Antenna Horizontal 1G – 6G)



(Plot D: Test Antenna Vertical 1G – 6G)


# EUT model:7278G, adapter model RD1202000-C55-29MG

## Test result of radiated emission below 1GHz



(Plot E: Test Antenna Vertical 30M - 1G)

Frequency (MHz)	QuasiPeak (dBμV/m)	Bandwidth (kHz)	Antenna height (cm)	Limit (dBμV/m)	Margin (dB)	Antenna	Verdict
37.16000	30.02	120.000	268.0	40.00	9.98	Vertical	Pass
47.43000	33.27	120.000	239.0	40.00	6.73	Vertical	Pass
99.29000	32.09	120.000	137.0	43.50	11.41	Vertical	Pass




(Plot F: Test Antenna Horizontal 30M - 1G)


Frequency (MHz)	QuasiPeak (dB $\mu$ V/m)	Bandwidth (kHz)	Antenna height (cm)	Limit (dB $\mu$ V/m)	Margin (dB)	Antenna	Verdict
30.36000	27.96	120.000	293.0	40.00	12.04	Horizontal	Pass
278.36000	31.20	120.000	174.0	46.00	14.80	Horizontal	Pass
830.17000	32.61	120.000	186.0	46.00	13.39	Horizontal	Pass



### Test result of radiated emission above 1GHz




(Plot G: Test Antenna Horizontal 1G – 6G)



(Plot H: Test Antenna Vertical 1G – 6G)


# EUT model:7272G, adapter model YJS024U-1202000U

## Test result of radiated emission below 1GHz



(Plot I: Test Antenna Vertical 30M - 1G)


Frequency (MHz)	QuasiPeak (dB $\mu$ V/m)	Bandwidth (kHz)	Antenna height (cm)	Limit (dB $\mu$ V/m)	Margin (dB)	Antenna	Verdict
144.36000	30.48	120.000	196.0	43.50	13.02	Vertical	Pass
361.38000	36.19	120.000	168.0	46.00	9.81	Vertical	Pass
724.19000	36.27	120.000	285.0	46.00	9.73	Vertical	Pass




(Plot J: Test Antenna Horizontal 30M - 1G)

Frequency (MHz)	QuasiPeak (dB $\mu$ V/m)	Bandwidth (kHz)	Antenna height (cm)	Limit (dB $\mu$ V/m)	Margin (dB)	Antenna	Verdict
144.36000	28.37	120.000	258.0	43.50	15.13	Horizontal	Pass
362.21000	35.67	120.000	184.0	46.00	10.33	Horizontal	Pass
375.16000	36.17	120.000	228.0	46.00	9.83	Horizontal	Pass

### Test result of radiated emission above 1GHz



(Plot K: Test Antenna Horizontal 1G – 6G)



(Plot L: Test Antenna Vertical 1G – 6G)

**Test Result: PASS**

**\*\* END OF REPORT \*\***