

# FCC Part 22H & 24E

## Measurement and Test Report

### For

**MACATE GROUP CORPORATION**

**3401 SW 160th AVENUE, SUITE 430, MIRAMAR/FLORIDA, USA**

**FCC ID: 2AGMA-SGB1G**

**FCC Rules:** FCC Part 22H, FCC Part 24E

**Product Description:** 4G-LTE Smartphone

**Tested Model:** SGB1G-W

**Report No.:** STR15118239I-1

**Tested Date:** 2015-12-03 to 2015-12-07

**Issued Date:** 2015-12-08

**Tested By:** Silin Chen / EMC Manager

*Silin Chen*

**Reviewed By:** Suan Su / Engineer

*Suan Su*

**Approved & Authorized By:** Jandy So / PSQ Manager

*Jandy So*

**Prepared By:**

**Shenzhen SEM.Test Technology Co., Ltd.**

1/F, Building A, Hongwei Industrial Park, Liuxian 2nd Road,  
Bao'an District, Shenzhen, P.R.C. (518101)

Tel.: +86-755-33663308 Fax.: +86-755-33663309 Website: www.semtest.com.cn

Note: This test report is limited to the above client company and the product model only. It may not be duplicated without prior permitted by Shenzhen SEM. Test Technology Co., Ltd.

**TABLE OF CONTENTS**

<b>1. GENERAL INFORMATION.....</b>	<b>3</b>
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	3
1.2 TEST STANDARDS.....	5
1.3 TEST METHODOLOGY.....	5
1.4 TEST FACILITY.....	5
1.5 EUT SETUP AND TEST MODE.....	6
1.6 TEST EQUIPMENT LIST AND DETAILS.....	7
<b>2. SUMMARY OF TEST RESULTS.....</b>	<b>8</b>
<b>3. RF EXPOSURE.....</b>	<b>9</b>
3.1 STANDARD APPLICABLE.....	9
3.2 TEST RESULT.....	9
<b>4. RF OUTPUT POWER.....</b>	<b>10</b>
4.1 STANDARD APPLICABLE.....	10
4.2 TEST PROCEDURE.....	10
4.3 ENVIRONMENTAL CONDITIONS.....	10
4.4 SUMMARY OF TEST RESULTS/PLOTS.....	10
<b>5. PEAK-TO-AVERAGE RADIO (PAR) OF TRANSMITTER.....</b>	<b>19</b>
5.1 STANDARD APPLICABLE.....	19
5.2 TEST PROCEDURE.....	19
5.3 ENVIRONMENTAL CONDITIONS.....	19
5.4 SUMMARY OF TEST RESULTS.....	20
<b>6. EMISSION BANDWIDTH.....</b>	<b>21</b>
6.1 STANDARD APPLICABLE.....	21
6.2 TEST PROCEDURE.....	21
6.3 ENVIRONMENTAL CONDITIONS.....	21
6.4 SUMMARY OF TEST RESULTS/PLOTS.....	22
<b>7. OUT OF BAND EMISSIONS AT ANTENNA TERMINAL.....</b>	<b>42</b>
7.1 STANDARD APPLICABLE.....	42
7.2 TEST PROCEDURE.....	42
7.3 ENVIRONMENTAL CONDITIONS.....	42
7.4 SUMMARY OF TEST RESULTS/PLOTS.....	43
<b>8. SPURIOUS RADIATED EMISSIONS.....</b>	<b>91</b>
8.1 MEASUREMENT UNCERTAINTY.....	91
8.2 STANDARD APPLICABLE.....	91
8.3 TEST PROCEDURE.....	91
8.4 ENVIRONMENTAL CONDITIONS.....	91
8.5 SUMMARY OF TEST RESULTS/PLOTS.....	91
<b>9. FREQUENCY STABILITY.....</b>	<b>102</b>
9.1 STANDARD APPLICABLE.....	102
9.2 TEST PROCEDURE.....	102
9.3 ENVIRONMENTAL CONDITIONS.....	102
9.4 SUMMARY OF TEST RESULTS/PLOTS.....	102

## 1. GENERAL INFORMATION

### 1.1 Product Description for Equipment Under Test (EUT)

#### Client Information

Applicant: MACATE GROUP CORPORATION  
Address of applicant: 3401 SW 160th AVENUE, SUITE 430,  
MIRAMAR/FLORIDA, USA

Manufacturer: COOSEA GROUP(HK) COMPANY LIMITED  
Address of manufacturer: UNIT 5-6 16F MULTIFIELD PLAZA 3-7A PRAT  
AVENUE TSIM SHA TSUI KL HONGKONG

General Description of EUT	
Product Name:	4G-LTE Smartphone
Trade Name:	BELÉCI
Model No.:	SGB1G-W
Adding Model(s):	SGB1G-BL
Hardware Version:	V12
Software Version:	KD7LE22A.L1.ORIGINAL.SW.AM.SZ.V0.05
IMEI:	356590470001351/356590470001369
Rated Voltage:	Battery: DC 3.8V(8.17Wh)
Power Adaptor:	Model: A88A-120130U-US1
	INPUT: AC100-240V 50/60Hz,0.5A OUTPUT: DC5V/2A, DC9V/1.8A, DC12V/1.3A
<i>Note: The test data is gathered from a production sample provided by the manufacturer. The appearance of others models listed in the report is different from main-test model SGB1G-W, but the circuit and the electronic construction do not change, declared by the manufacturer.</i>	

<b>Technical Characteristics of EUT</b>	
<b>2G</b>	
Support Networks:	GSM, GPRS, EDGE
Support Band:	GSM850/PCS1900
Uplink Frequency:	GSM/GPRS/EDGE 850: 824~849MHz GSM/GPRS/EDGE 1900: 1850~1910MHz
Downlink Frequency:	GSM/GPRS/EDGE 850: 869~894MHz GSM/GPRS/EDGE 1900: 1930~1990MHz
Max RF Output Power:	GSM850: 32.18dBm, GSM1900: 29.15dBm EDGE850: 26.55dBm, EDGE1900: 26.57dBm
Type of Modulation:	GMSK, 8PSK
Type of Emission:	GSM850: 260KGXW, GSM1900: 265KGXW EDGE850: 266KG7W, EDGE1900: 280KG7W
Type of Antenna:	Integral Antenna
Antenna Gain:	850: -0.16dBi    1900: 0.8dBi
GPRS/ EDGE Class:	Class 12
<b>3G</b>	
Support Networks:	WCDMA, HSDPA, HSUPA
Support Band:	WCDMA Band II, WCDMA Band V
Uplink Frequency:	WCDMA Band II: 1850~1980MHz WCDMA Band V: 824~849MHz
Downlink Frequency:	WCDMA Band II: 1930~1990MHz WCDMA Band V: 869~894MHz
Max RF Output Power:	WCDMA Band II: 22.90dBm WCDMA Band V: 22.70dBm
Type of Modulation:	BPSK
Type of Emission:	WCDMA Band II: 4M27F9W WCDMA Band V: 4M28F9W
Type of Antenna:	Integral Antenna
Antenna Gain:	band 2: 0.8dBi                      band 5: -0.16dBi

## 1.2 Test Standards

The following report is prepared on behalf of the MACATE GROUP CORPORATION in accordance with FCC Part 2 subpart J, FCC Part 22 subpart H and FCC Part 24 subpart E of the Federal Communication Commissions rules.

The objective is to determine compliance with FCC Part 2 subpart J, FCC Part 22 subpart H and FCC Part 24 subpart E of the Federal Communication Commissions rules.

**Maintenance of compliance** is the responsibility of the manufacturer. Any modification of the product, which result in lowering the emission, should be checked to ensure compliance has been maintained.

## 1.3 Test Methodology

All measurements contained in this report were conducted with ANSI/TIA-603-D: 2010 and ANSI C63.4-2014, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

## 1.4 Test Facility

- **FCC – Registration No.: 934118**

Shenzhen SEM.Test Technology Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files and the Registration is 934118.

- **Industry Canada (IC) Registration No.: 11464A**

The 3m Semi-anechoic chamber of Shenzhen SEM.Test Technology Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 11464A.

- **CNAS Registration No.: L4062**

Shenzhen SEM.Test Technology Co., Ltd. is a testing organization accredited by China National Accreditation Service for Conformity Assessment (CNAS) according to ISO/IEC 17025. The accreditation certificate number is L4062. All measurement facilities used to collect the measurement data are located at 1/F, Building A, Hongwei Industrial Park, Liuxian 2nd Road, Bao'an District, Shenzhen, P.R.C (518101)

## 1.5 EUT Setup and Test Mode

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. All testing shall be performed under maximum output power condition, and to measure its highest possible emissions level, more detailed description as follows:

Test Mode List		
Test Mode	Description	Remark
TM1	GSM 850	Low, Middle, High Channels
TM2	GPRS 850	Low, Middle, High Channels
TM3	EDGE 850	Low, Middle, High Channels
TM4	GSM 1900	Low, Middle, High Channels
TM5	GPRS 1900	Low, Middle, High Channels
TM6	EDGE 1900	Low, Middle, High Channels
TM7	WCDMA Band II	Low, Middle, High Channels
TM8	HSDPA Band II	Low, Middle, High Channels
TM9	HSUPA Band II	Low, Middle, High Channels
TM10	WCDMA Band V	Low, Middle, High Channels
TM11	HSDPA Band V	Low, Middle, High Channels
TM12	HSUPA Band V	Low, Middle, High Channels

Testing Configure			
Support Band	Support Standard	Channel Frequency	Channel Number
GSM 850	GSM/GPRS/EDGE	824.2 MHz	128
		836.6 MHz	190
		848.8 MHz	251
PCS 1900	GSM/GPRS/EDGE	1850.2 MHz	512
		1880.0 MHz	661
		1909.8 MHz	810
WCDMA Band 2	WCDMA/HSDPA/HSUPA	1852.4 MHz	9262
		1880.0 MHz	9400
		1907.6 MHz	9538
WCDMA Band 5	WCDMA/HSDPA/HSUPA	826.4 MHz	4132
		836.6 MHz	4183
		846.6 MHz	4233

Note: the transmitter has been tested on the communications mode of GSM, GPRS, EDGE, WCDMA, HSDPA, HSUPA compliance test and record the worst case.

**EUT Cable List and Details**

Cable Description	Length (M)	Shielded/Unshielded	With Core/Without Core
Earphone Cable	1.3	Unshielded	Without Core
USB Cable	1.0	Shielded	Without Core

**Auxiliary Equipment List and Details**

Description	Manufacturer	Model	Serial Number
Notebook	Lenovo	E10	LR-63C8R

**Special Cable List and Details**

Cable Description	Length (M)	Shielded/Unshielded	With Core/Without Core
/	/	/	/

**1.6 Test Equipment List and Details**

Kind of Equipment	Manufacturer	Type	S/N	Cal Date	Due Date
Equipment list of < Shenzhen SEM.Test Technology Co., Ltd.>					
Test SIM card	-		-	N/A	
GSM Tester	Rohde & Schwarz	CMU200	104036	2015-06-17	2016-06-16
Spectrum Analyzer	Agilent	E4407B	MY41440400	2015-06-17	2016-06-16
Spectrum Analyzer	Agilent	N9020A	US47140102	2015-06-17	2016-06-16
Signal Generator	Agilent	83752A	3610A01453	2015-06-17	2016-06-16
Vector Signal Generator	Agilent	N5182A	MY47070202	2015-06-17	2016-06-16
Power Divider	Weinschel	1506A	PM204	2015-06-17	2016-06-16
Power Divider	RF-Lambda	RFLT4W5M18G	14110400027	2015-06-17	2016-06-16
Spectrum Analyzer	Rohde & Schwarz	FSP	836079/035	2015-06-17	2016-06-16
EMI Test Receiver	Rohde & Schwarz	ESVB	825471/005	2015-06-17	2016-06-16
Amplifier	Agilent	8447F	3113A06717	2015-06-17	2016-06-16
Amplifier	C&D	PAP-1G18	2002	2015-06-17	2016-06-16
Broadband Antenna	Schwarz beck	VULB9163	9163-333	2015-06-17	2016-06-16
Broadband Antenna	Schwarz beck	VULB9163	9163-332	2015-06-17	2016-06-16
Horn Antenna	ETS	3117	00086197	2015-06-17	2016-06-16
Horn Antenna	ETS	3117	00086168	2015-06-17	2016-06-16
Horn Antenna	ETS	3116B	00088203	2015-06-17	2016-06-16
Horn Antenna	ETS	3116B	00088221	2015-06-17	2016-06-16

## 2. SUMMARY OF TEST RESULTS

FCC Rules	Description of Test Item	Result
§ 1.1307, § 2.1093	RF Exposure	Compliant
§ 22.913 (a), § 24.232 (c)	RF Output Power	Compliant
§ 24.51	Peak-to-average Radio (PAR) of Transmitter	Compliant
§ 22.917 (b), § 24.238 (b)	Emission Bandwidth	Compliant
§ 22.917 (a), § 24.238 (a)	Spurious Emissions at Antenna Terminal	Compliant
§ 22.917 (a), § 24.238 (a)	Spurious Radiation Emissions	Compliant
§ 22.917 (a), § 24.238 (a)	Out of Band Emissions	Compliant
§ 22.355, § 24.235	Frequency Stability	Compliant



### **3. RF Exposure**

---

#### **3.1 Standard Applicable**

According to § 1.1307 and § 2.1093, the portable transmitter must comply the RF exposure requirements.

#### **3.2 Test Result**

This product complied with the requirement of the RF exposure, please see the SAR report.

## 4. RF Output Power


### 4.1 Standard Applicable

According to §22.913(a)(2), The ERP of mobile and portable stations transmitters and auxiliary test transmitters must not exceed 7 Watts.

According to §24.232 (c), Mobile and portable stations are limited to 2 watts EIRP and the equipment must employ a means for limiting power to the minimum necessary for successful communications.

### 4.2 Test Procedure

Conducted output power test method:



Radiated power test method:

- 1.The setup of EUT is according with per ANSI/TIA-603-D: 2010 and ANSI C63.4-2014 measurement procedure.
2. The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.
3. The frequency range up to tenth harmonic of the fundamental frequency was investigated.
4. Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution.

### 4.3 Environmental Conditions

Temperature:	24 °C
Relative Humidity:	54%
ATM Pressure:	1011 mbar

### 4.4 Summary of Test Results/Plots

## Radiated Power

## ERP For GSM Mode GSM850

Frequency	Substitute SG	Height	Table	Polar	Cable loss	Antenna Gain	Result	FCC Part 22H Limit
MHz	dBm	Meter	Degree	H / V	dB	dB	dBm	dBm
Low Channel								
824.2	31.58	1.5	0	H	1.5	0	30.08	38.45
824.2	29.73	1.5	0	V	1.5	0	28.23	38.45
Middle Channel								
836.6	31.79	1.5	0	H	1.5	0	30.29	38.45
836.6	29.82	1.5	0	V	1.5	0	28.32	38.45
High Channel								
848.8	30.05	1.5	0	H	1.5	0	28.55	38.45
848.8	29.47	1.5	0	V	1.5	0	27.97	38.45

## EIRP For GSM Mode PCS1900

Frequency	Substitute SG	Height	Table	Polar	Cable loss	Antenna Gain	Result	FCC Part 24E Limit
MHz	dBm	Meter	Degree	H / V	dB	dB	DBm	dBm
Low Channel								
1850.2	20.41	1.5	0	H	1.9	7.7	26.21	33
1850.2	21.19	1.5	0	V	1.9	7.7	26.99	33
Middle Channel								
1880.0	20.88	1.5	0	H	1.9	7.7	26.68	33
1880.0	21.42	1.5	0	V	1.9	7.7	27.22	33
High Channel								
1909.8	19.28	1.5	0	H	1.9	7.7	25.08	33
1909.8	22.42	1.5	0	V	1.9	7.7	28.22	33

## ERP For GPRS Mode GSM850

Frequency	Substitute SG	Height	Table	Polar	Cable loss	Antenna Gain	Result	FCC Part 22H Limit
MHz	dBm	Meter	Degree	H / V	dB	dB	dBm	dBm
Low Channel								
824.2	29.47	1.5	0	H	1.5	0	27.97	38.45
824.2	28.16	1.5	0	V	1.5	0	26.66	38.45
Middle Channel								
836.6	29.12	1.5	0	H	1.5	0	27.62	38.45
836.6	29.32	1.5	0	V	1.5	0	27.82	38.45
High Channel								
848.8	30.68	1.5	0	H	1.5	0	29.18	38.45
848.8	28.72	1.5	0	V	1.5	0	27.22	38.45

## EIRP For GPRS Mode PCS1900

Frequency	Substitute SG	Height	Table	Polar	Cable loss	Antenna Gain	Result	FCC Part 24E Limit
MHz	dBm	Meter	Degree	H / V	dB	dB	DBm	dBm
Low Channel								
1850.2	18.92	1.5	0	H	1.9	7.7	24.72	33
1850.2	21.63	1.5	0	V	1.9	7.7	27.43	33
Middle Channel								
1880.0	19.16	1.5	0	H	1.9	7.7	24.96	33
1880.0	21.68	1.5	0	V	1.9	7.7	27.48	33
High Channel								
1909.8	19.28	1.5	0	H	1.9	7.7	25.08	33
1909.8	21.26	1.5	0	V	1.9	7.7	27.06	33

## ERP For EDGE Mode GSM850

Frequency	Substitute SG	Height	Table	Polar	Cable loss	Antenna Gain	Result	FCC Part 22H Limit
MHz	dBm	Meter	Degree	H / V	dB	dB	dBm	dBm
Low Channel								
824.2	23.79	1.5	0	H	1.5	0	22.29	38.45
824.2	26.28	1.5	0	V	1.5	0	24.78	38.45
Middle Channel								
836.6	23.69	1.5	0	H	1.5	0	22.19	38.45
836.6	26.15	1.5	0	V	1.5	0	24.65	38.45
High Channel								
848.8	23.47	1.5	0	H	1.5	0	21.97	38.45
848.8	25.89	1.5	0	V	1.5	0	24.39	38.45

## EIRP For EDGE Mode PCS1900

Frequency	Substitute SG	Height	Table	Polar	Cable loss	Antenna Gain	Result	FCC Part 24E Limit
MHz	dBm	Meter	Degree	H / V	dB	dB	DBm	dBm
Low Channel								
1850.2	17.27	1.5	0	H	1.9	7.7	23.07	33
1850.2	19.61	1.5	0	V	1.9	7.7	25.41	33
Middle Channel								
1880.0	17.81	1.5	0	H	1.9	7.7	23.61	33
1880.0	18.99	1.5	0	V	1.9	7.7	24.79	33
High Channel								
1909.8	17.97	1.5	0	H	1.9	7.7	23.77	33
1909.8	18.21	1.5	0	V	1.9	7.7	24.01	33

## ERP For WCDMA Mode Band V

Frequency	Substitute SG	Height	Table	Polar	Cable loss	Antenna Gain	Result	FCC Part 22H Limit
MHz	dBm	Meter	Degree	H / V	dB	dBd	dBm	dBm
Low Channel								
826.4	20.69	1.5	0	H	1.5	0	19.19	38.45
826.4	22.07	1.5	0	V	1.5	0	20.57	38.45
Middle Channel								
836.6	21.96	1.5	0	H	1.5	0	20.46	38.45
836.6	21.34	1.5	0	V	1.5	0	19.84	38.45
High Channel								
846.6	20.49	1.5	0	H	1.5	0	18.99	38.45
846.6	21.69	1.5	0	V	1.5	0	20.19	38.45

## ERP For HSDPA Mode Band V

Frequency	Substitute SG	Height	Table	Polar	Cable loss	Antenna Gain	Result	FCC Part 22H Limit
MHz	dBm	Meter	Degree	H / V	dB	dBd	dBm	dBm
Low Channel								
826.4	18.25	1.5	0	H	1.5	0	16.75	38.45
826.4	20.07	1.5	0	V	1.5	0	18.57	38.45
Middle Channel								
836.6	19.23	1.5	0	H	1.5	0	17.73	38.45
836.6	20.72	1.5	0	V	1.5	0	19.22	38.45
High Channel								
846.6	19.88	1.5	0	H	1.5	0	18.38	38.45
846.6	20.64	1.5	0	V	1.5	0	19.14	38.45

## ERP For HSUPA Mode Band V

Frequency	Substitute SG	Height	Table	Polar	Cable loss	Antenna Gain	Result	FCC Part 22H Limit
MHz	dBm	Meter	Degree	H / V	dB	dBd	dBm	dBm
Low Channel								
826.4	18.55	1.5	0	H	1.5	0	17.05	38.45
826.4	20.01	1.5	0	V	1.5	0	18.51	38.45
Middle Channel								
836.6	19.03	1.5	0	H	1.5	0	17.53	38.45
836.6	20.71	1.5	0	V	1.5	0	19.21	38.45
High Channel								
846.6	18.33	1.5	0	H	1.5	0	16.83	38.45
846.6	20.17	1.5	0	V	1.5	0	18.67	38.45

## EIRP For WCDMA Mode Band II

Frequency	Substitute SG	Height	Table	Polar	Cable loss	Antenna Gain	Result	FCC Part 24E Limit
MHz	dBm	Meter	Degree	H / V	dB	dB	DBm	dBm
Low Channel								
1852.4	14.85	1.5	0	H	1.9	7.7	20.65	33
1852.4	15.56	1.5	0	V	1.9	7.7	21.36	33
Middle Channel								
1880.0	14.39	1.5	0	H	1.9	7.7	20.19	33
1880.0	15.38	1.5	0	V	1.9	7.7	21.18	33
High Channel								
1907.6	15.05	1.5	0	H	1.9	7.7	20.85	33
1907.6	15.36	1.5	0	V	1.9	7.7	21.16	33

**EIRP For HSDPA Mode Band II**

Frequency	Substitute SG	Height	Table	Polar	Cable loss	Antenna Gain	Result	FCC Part 24E Limit
MHz	dBm	Meter	Degree	H / V	dB	dB	DBm	dBm
Low Channel								
1852.4	13.68	1.5	0	H	1.9	7.7	19.48	33
1852.4	14.75	1.5	0	V	1.9	7.7	20.55	33
Middle Channel								
1880.0	13.37	1.5	0	H	1.9	7.7	19.17	33
1880.0	14.91	1.5	0	V	1.9	7.7	20.71	33
High Channel								
1907.6	13.14	1.5	0	H	1.9	7.7	18.94	33
1907.6	14.18	1.5	0	V	1.9	7.7	19.98	33

**EIRP For HSUPA Mode Band II**

Frequency	Substitute SG	Height	Table	Polar	Cable loss	Antenna Gain	Result	FCC Part 24E Limit
MHz	dBm	Meter	Degree	H / V	dB	dB	DBm	dBm
Low Channel								
1852.4	13.34	1.5	0	H	1.9	7.7	19.14	33
1852.4	14.33	1.5	0	V	1.9	7.7	20.13	33
Middle Channel								
1880.0	12.75	1.5	0	H	1.9	7.7	18.55	33
1880.0	14.62	1.5	0	V	1.9	7.7	20.42	33
High Channel								
1907.6	12.91	1.5	0	H	1.9	7.7	18.71	33
1907.6	13.76	1.5	0	V	1.9	7.7	19.56	33

Note: Result = Substitute - Cable loss + Antenna Gain



Max. Conducted Output Power

For Cellular Band (GSM850)

Test Mode	Channel	Frequency (MHz)	Average Power (dBm)	FCC Part 22.913 Limit (dBm)
GSM	Low Channel	824.2	31.76	38.45
	Middle Channel	836.6	31.97	38.45
	High Channel	848.8	32.18	38.45
GPRS(1 Slot)	Low Channel	824.2	31.93	38.45
	Middle Channel	836.6	32.14	38.45
	High Channel	848.8	31.81	38.45
EDGE(1 Slot)	Low Channel	824.2	26.50	38.45
	Middle Channel	836.6	26.55	38.45
	High Channel	848.8	26.54	38.45

For PCS Band (GSM1900)

Test Mode	Channel	Frequency (MHz)	Average Power (dBm)	FCC Part 24.232 Limit (dBm)
GSM	Low Channel	1850.2	29.15	33.0
	Middle Channel	1880.0	28.45	33.0
	High Channel	1909.8	28.81	33.0
GPRS(1 Slot)	Low Channel	1850.2	30.27	33.0
	Middle Channel	1880.0	29.57	33.0
	High Channel	1909.8	28.94	33.0
EDGE(1 Slot)	Low Channel	1850.2	26.01	33.0
	Middle Channel	1880.0	26.57	33.0
	High Channel	1909.8	26.02	33.0

For WCDMA Band V

Test Mode	Channel	Frequency (MHz)	Average Power (dBm)	FCC Part 22.913 Limit (dBm)
WCDMA	Low Channel	826.4	22.56	38.45
	Middle Channel	836.6	22.60	38.45
	High Channel	846.6	22.90	38.45
HSDPA	Low Channel	826.4	21.45	38.45
	Middle Channel	836.6	21.49	38.45
	High Channel	846.6	21.76	38.45
HSUPA	Low Channel	826.4	21.53	38.45
	Middle Channel	836.6	21.63	38.45
	High Channel	846.6	21.94	38.45

For WCDMA Band II

Test Mode	Channel	Frequency (MHz)	Average Power (dBm)	FCC Part 24.232 Limit (dBm)
WCDMA	Low Channel	1852.4	22.52	33.0
	Middle Channel	1880.0	22.63	33.0
	High Channel	1907.6	22.70	33.0
HSDPA	Low Channel	1852.4	21.41	33.0
	Middle Channel	1880.0	21.67	33.0
	High Channel	1907.6	21.64	33.0
HSUPA	Low Channel	1852.4	21.56	33.0
	Middle Channel	1880.0	21.39	33.0
	High Channel	1907.6	21.57	33.0

## 5. Peak-to-average Radio (PAR) of Transmitter


### 5.1 Standard Applicable

According to §24.232(d), Power measurements for transmissions by stations authorized under this section may be made either in accordance with a Commission-approved average power technique or in compliance with paragraph (e) of this section. In both instances, equipment employed must be authorized in accordance with the provisions of §24.51. In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

### 5.2 Test Procedure

The RF output terminal of the transmitter was connected to the input of the spectrum analyzer via a suitable attenuation. The RBW of the spectrum analyzer was set to 30kHz and the peak-to-average ratio (PAR) of the transmission was recorded.

Test Configuration for the emission bandwidth testing:



### 5.3 Environmental Conditions

Temperature:	25 °C
Relative Humidity:	54%
ATM Pressure:	1011 mbar

## 5.4 Summary of Test Results

For PCS Band

Test Mode	Channel	Frequency (MHz)	Peak Power (dBm)	Average Power (dBm)	PAR (dB)	Limit (dB)
GSM	512	1850.2	31.13	28.23	2.9	13
	661	1880.0	31.79	29.47	2.32	13
	810	1909.8	31.77	28.83	2.94	13
GPRS (1 Slot)	512	1850.2	32.24	29.01	3.23	13
	661	1880.0	32.84	29.37	3.47	13
	810	1909.8	32.42	28.18	4.24	13
EDGE (1 Slot)	512	1850.2	27.85	25.58	2.27	13
	661	1880.0	27.37	24.24	3.13	13
	810	1909.8	27.84	24.25	3.59	13

For WCDMA Band II

Test Mode	Channel	Frequency (MHz)	Peak Power (dBm)	Average Power (dBm)	PAR (dB)	Limit (dB)
WCDMA	9262	1852.4	24.83	23.17	1.66	13
	9400	1880.0	25.8	23.89	1.91	13
	9538	1907.6	25.47	22.8	2.67	13
HSDPA	9262	1852.4	22.27	20.36	1.91	13
	9400	1880.0	22.68	20.49	2.19	13
	9538	1907.6	22.51	21.5	1.01	13
HSDPA	9262	1852.4	23.42	21.26	2.16	13
	9400	1880.0	23	21.96	1.04	13
	9538	1907.6	22.01	20.6	1.41	13

## 6. Emission Bandwidth

### 6.1 Standard Applicable


According to §22.917(b), The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

According to §24.238(b), The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

### 6.2 Test Procedure

The RF output terminal of the transmitter was connected to the input of the spectrum analyzer via a suitable attenuation. The RBW of the spectrum analyzer was set to 30kHz and the 26dB bandwidth was recorded.

Test Configuration for the emission bandwidth testing:



### 6.3 Environmental Conditions

Temperature:	25 °C
Relative Humidity:	54%
ATM Pressure:	1011 mbar

## 6.4 Summary of Test Results/Plots

For Cellular Band

Test Mode	Channel	Frequency (MHz)	99% Emission Bandwidth (kHz)	26 dB Emission Bandwidth (kHz)
GSM	128	824.2	256.4348	335.960
	190	836.6	253.1145	337.132
	251	848.8	256.0335	327.859
GPRS	128	824.2	259.2792	332.816
	190	836.6	259.5922	340.181
	251	848.8	255.8789	337.912
EDGE	128	824.2	265.5739	331.129
	190	836.6	252.1229	332.146
	251	848.8	264.4299	341.020

For PCS Band

Test Mode	Channel	Frequency (MHz)	99% Emission Bandwidth (kHz)	26 dB Emission Bandwidth (kHz)
GSM	512	1850.2	257.2569	334.643
	661	1880.0	260.6648	331.829
	810	1909.8	257.6937	336.860
GPRS	512	1850.2	254.1113	337.138
	661	1880.0	264.9267	341.097
	810	1909.8	255.8007	334.862
EDGE	512	1850.2	280.1634	365.173
	661	1880.0	275.8201	362.576
	810	1909.8	278.6574	366.713

## For Band V


Test Mode	Channel	Frequency (MHz)	99% Emission Bandwidth (MHz)	26 dB Emission Bandwidth (MHz)
WCDMA	4132	826.4	4.2545	5.003
	4182	836.6	4.2323	4.887
	4233	846.6	4.2475	4.996
HSDPA	4132	826.4	4.2787	4.957
	4182	836.6	4.2354	4.893
	4233	846.6	4.2713	4.988
HSUPA	4132	826.4	4.2746	4.988
	4182	836.6	4.2199	4.864
	4233	846.6	4.2339	4.974

## For Band II


Test Mode	Channel	Frequency (MHz)	99% Emission Bandwidth (MHz)	26 dB Emission Bandwidth (MHz)
WCDMA	9262	1852.4	4.2249	4.908
	9400	1880.0	4.2357	4.974
	9538	1907.6	4.2657	5.036
HSDPA	9262	1852.4	4.2328	4.863
	9400	1880.0	4.2528	4.926
	9538	1907.6	4.2617	5.040
HSUPA	9262	1852.4	4.2328	4.863
	9400	1880.0	4.2723	4.977
	9538	1907.6	4.2661	5.023

Please refer to the following test plots:

For Cellular Band  
GSM Low Channel




GSM Middle Channel







### GSM High channel




### GPRS Low Channel




### GPRS Middle Channel




### GPRS High Channel




## EDGE Low Channel




## EDGE Middle Channel




### EDGE High channel




### For PCS Band GSM Low Channel




### GSM Middle Channel




### GSM High channel




### GPRS Low Channel




### GPRS Middle Channel




### GPRS High Channel




### EDGE Low Channel



## EDGE Middle Channel




## EDGE High channel






For Band V


WCDMA Low Channel




WCDMA Middle Channel




### WCDMA High Channel




### HSDPA Low Channel




### HSDPA Middle Channel




### HSDPA High Channel




### HSUPA Low Channel



### HSUPA Middle Channel




## HSUPA High Channel




## For Band II


## WCDMA Low Channel




### WCDMA Middle Channel




### WCDMA High Channel




## HSDPA Low Channel




## HSDPA Middle Channel



## HSDPA High Channel




## HSUPA Low Channel






### HSUPA Middle Channel



### HSUPA High Channel



## 7. Out of Band Emissions at Antenna Terminal

### 7.1 Standard Applicable


According to §22.917(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10 \log(P)$  dB.

According to §24.238(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10 \log(P)$  dB.

### 7.2 Test Procedure

The RF output terminal of the transmitter was connected to the input of the spectrum analyzer via a suitable attenuation. The RBW of the spectrum analyzer was set to 100kHz and 1MHz for the scan frequency from 30MHz to 1GHz and the scan frequency from 1GHz to up to 10<sup>th</sup> harmonic.

Test Configuration for the out of band emissions testing:




### 7.3 Environmental Conditions

Temperature:	25 °C
Relative Humidity:	53%
ATM Pressure:	1018 mbar


## 7.4 Summary of Test Results/Plots

Please refer to the following test plots For Cellular Band


GSM Low Channel 30MHz to 1GHz




Above 1GHz




# GSM Middle Channel 30MHz to 1GHz




# Above 1GHz




## GSM High Channel 30MHz to 1GHz




## Above 1GHz




### GSM Low Band Emission




### GSM High Band Emission




GPRS Low Channel  
30MHz to 1GHz




Above 1GHz



## GPRS Middle Channel 30MHz to 1GHz




## Above 1GHz







## GPRS High Channel 30MHz to 1GHz




## Above 1GHz




### GPRS Low Band Emission




### GPRS High Band Emission




EDGE Low Channel  
30MHz to 1GHz




Above 1GHz




EDGE Middle Channel  
30MHz to 1GHz




Above 1GHz




EDGE High Channel  
30MHz to 1GHz




Above 1GHz




### EDGE Low Band Emission




### EDGE High Band Emission




For PCS Band  
GSM Low Channel  
30MHz to 1GHz




Above 1GHz



GSM Middle Channel  
30MHz to 1GHz




Above 1GHz







GSM High Channel  
30MHz to 1GHz




Above 1GHz




### GSM Low Band Emission




### GSM High Band Emission




GPRS Low Channel  
30MHz to 1GHz




Above 1GHz




GPRS Middle Channel  
30MHz to 1GHz




Above 1GHz




## GPRS High Channel 30MHz to 1GHz




## Above 1GHz




## GPRS Low Band Emission




## GPRS High Band Emission




EDGE Low Channel  
30MHz to 1GHz




Above 1GHz



EDGE Middle Channel  
30MHz to 1GHz




Above 1GHz







EDGE High Channel  
30MHz to 1GHz




Above 1GHz



## EDGE Low Band Emission




## EDGE High Band Emission




### For Band V

WCDMA Low Channel


30MHz to 1GHz




Above 1GHz




# WCDMA Middle Channel 30MHz to 1GHz




## Above 1GHz




# WCDMA High Channel 30MHz to 1GHz




# Above 1GHz




### WCDMA Low Band Spurious Emission




### WCDMA High Band Spurious Emission




## HSDPA Low Channel 30MHz to 1GHz




## Above 1GHz



## HSDPA Middle Channel 30MHz to 1GHz




## Above 1GHz







## HSDPA High Channel 30MHz to 1GHz




## Above 1GHz




### HSDPA Low Band Spurious Emission




### HSDPA High Band Spurious Emission




## HSUPA Low Channel 30MHz to 1GHz




## Above 1GHz




## HSUPA Middle Channel 30MHz to 1GHz




## Above 1GHz




## HSUPA High Channel 30MHz to 1GHz




## Above 1GHz



### HSUPA Low Band Spurious Emission




### HSUPA High Band Spurious Emission




## For Band II

WCDMA Low Channel


30MHz to 1GHz




Above 1GHz



# WCDMA Middle Channel 30MHz to 1GHz




# Above 1GHz







## WCDMA High Channel 30MHz to 1GHz




## Above 1GHz




### WCDMA Low Band Spurious Emission




### WCDMA High Band Spurious Emission




HSDPA Low Channel  
30MHz to 1GHz




Above 1GHz




HSDPA Middle Channel  
30MHz to 1GHz




Above 1GHz




## HSDPA High Channel 30MHz to 1GHz




## Above 1GHz




### HSDPA Low Band Spurious Emission




### HSDPA High Band Spurious Emission




HSUPA Low Channel  
30MHz to 1GHz




Above 1GHz



HSUPA Middle Channel  
30MHz to 1GHz




Above 1GHz







HSUPA High Channel  
30MHz to 1GHz




Above 1GHz



### HSUPA Low Band Spurious Emission



### HSUPA High Band Spurious Emission



## 8. Spurious Radiated Emissions

### 8.1 Measurement Uncertainty

Based on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of a radiation emissions measurement is  $\pm 5.20$  dB.

### 8.2 Standard Applicable

According to §22.917(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10 \log(P)$  dB.

According to §24.238(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10 \log(P)$  dB.

### 8.3 Test Procedure

1. The setup of EUT is according with per ANSI/TIA-603-D: 2010 and ANSI C63.4-2009 measurement procedure.
2. The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.
3. The frequency range up to tenth harmonic of the fundamental frequency was investigated.
4. Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution.

Spurious attenuation limit in dB =  $43 + 10 \log_{10}$  (power out in Watts)

### 8.4 Environmental Conditions

Temperature:	25 °C
Relative Humidity:	52%
ATM Pressure:	1012 mbar

### 8.5 Summary of Test Results/Plots


According to the data below, the FCC Part 22.917 and 24.238 standards, and had the worst margin of:

*Note: this EUT was tested in 3 orthogonal positions and the worst case position data was reported.*

Spurious Emission From 30MHz to 1GHz


For Cellular Band\_ GSM850 Mode

Horizontal:



No.	Frequency (MHz)	Reading (dBm)	Correct dB	Result (dBm)	Limit (dBm)	Margin (dB)	Remark
1	42.4508	-67.01	3.83	-63.18	-13.00	-50.18	ERP
2	437.1199	-67.89	9.50	-58.39	-13.00	-45.39	ERP
3	942.1305	-67.47	17.64	-49.83	-13.00	-36.83	ERP


Vertical:



No.	Frequency (MHz)	Reading (dBm)	Correct dB	Result (dBm)	Limit (dBm)	Margin (dB)	Remark
1	45.2166	-68.82	4.33	-64.49	-13.00	-51.49	ERP
2	98.4866	-68.84	2.05	-66.79	-13.00	-53.79	ERP
3	922.5157	-67.65	17.43	-50.22	-13.00	-37.22	ERP


For Cellular Band\_ GSM1900 Mode

Horizontal:



No.	Frequency (MHz)	Reading (dBm)	Correct dB	Result (dBm)	Limit (dBm)	Margin (dB)	Remark
1	42.4508	-67.01	3.83	-63.18	-13.00	-50.18	ERP
2	513.6331	-68.17	10.61	-57.56	-13.00	-44.56	ERP
3	989.5355	-67.66	18.32	-49.34	-13.00	-36.34	ERP


Vertical:



No.	Frequency (MHz)	Reading (dBm)	Correct dB	Result (dBm)	Limit (dBm)	Margin (dB)	Remark
1	49.1866	-68.00	4.35	-63.65	-13.00	-50.65	ERP
2	102.3597	-68.24	2.23	-66.01	-13.00	-53.01	ERP
3	958.7943	-67.76	17.86	-49.90	-13.00	-36.90	ERP

For band V Mode


Horizontal:



No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBm)	dB	(dBm)	(dBm)	(dB)	
1	48.5016	-69.10	4.35	-64.75	-13.00	-51.75	ERP
2	96.7749	-68.65	1.85	-66.80	-13.00	-53.80	ERP
3	955.4381	-68.75	17.81	-50.94	-13.00	-37.94	ERP




Vertical:



No.	Frequency (MHz)	Reading (dBm)	Correct dB	Result (dBm)	Limit (dBm)	Margin (dB)	Remark
1	54.2610	-68.33	3.92	-64.41	-13.00	-51.41	ERP
2	109.7960	-68.29	2.20	-66.09	-13.00	-53.09	ERP
3	979.1804	-67.81	18.17	-49.64	-13.00	-36.64	ERP


For band II Mode

Horizontal:



No.	Frequency (MHz)	Reading (dBm)	Correct dB	Result (dBm)	Limit (dBm)	Margin (dB)	Remark
1	46.8303	-68.45	4.35	-64.10	-13.00	-51.10	ERP
2	513.6331	-67.70	10.61	-57.09	-13.00	-44.09	ERP
3	965.5421	-68.07	17.96	-50.11	-13.00	-37.11	ERP

Vertical:



No.	Frequency (MHz)	Reading (dBm)	Correct dB	Result (dBm)	Limit (dBm)	Margin (dB)	Remark
1	50.9420	-68.67	4.26	-64.41	-13.00	-51.41	ERP
2	109.7960	-69.05	2.20	-66.85	-13.00	-53.85	ERP
3	942.1305	-67.99	17.64	-50.35	-13.00	-37.35	ERP

Note:  $\text{Margin} = (\text{Reading} + \text{Correct}) - \text{Limit}$

*Spurious Emissions Above 1GHz*  
*For Cellular Band\_GSM850 Mode*

Frequency	Reading	Correct	Result	Limit	Margin	Polar
(MHz)	(dBm)	dB	(dBm)	(dBm)	(dB)	H/V
Low Channel (824.2MHz)						
1648.4	-46.88	4.94	-41.94	-13	-28.94	H
2472.6	-46.12	8.46	-37.66	-13	-24.66	H
1648.4	-46.28	4.94	-41.34	-13	-28.34	V
2472.6	-49.36	8.46	-40.9	-13	-27.90	V
Middle Channel (836.6MHz)						
1673.2	-49.04	8.46	-40.58	-13	-27.58	H
2509.8	-47.36	5.11	-42.25	-13	-29.25	H
1673.2	-49.29	8.54	-40.75	-13	-27.75	V
2509.8	-48.53	5.11	-43.42	-13	-30.42	V
High Channel (848.8MHz)						
1697.6	-48.58	5.29	-43.29	-13	-30.29	H
2546.4	-48.16	8.59	-39.57	-13	-26.57	H
1697.6	-48.94	5.29	-43.65	-13	-30.65	V
2546.4	-48.61	8.59	-40.02	-13	-27.02	V

*For PCS Band\_GSM1900 Mode*

Frequency	Reading	Correct	Result	Limit	Margin	Polar
(MHz)	(dBm)	dB	(dBm)	(dBm)	(dB)	H/V
Low Channel (1850.2MHz)						
3700.4	-47.85	10.54	-37.31	-13	-24.31	H
5550.6	-46.74	13.37	-33.37	-13	-20.37	H
3700.4	-47.94	10.54	-37.4	-13	-24.4	V
5550.6	-46.85	13.37	-33.48	-13	-20.48	V
Middle Channel (1880MHz)						
3760.0	-49.87	10.64	-39.23	-13	-26.23	H
5640.0	-47.92	13.54	-34.38	-13	-21.38	H
3760.0	-47.26	10.64	-36.62	-13	-23.62	V
5640.0	-49.71	13.54	-36.17	-13	-23.17	V
High Channel (1909.8MHz)						
3819.6	-48.88	10.74	-38.14	-13	-25.14	H
5729.4	-49.95	13.71	-36.24	-13	-23.24	H
3819.6	-47.05	10.74	-36.31	-13	-23.31	V
5729.4	-48.20	13.71	-34.49	-13	-21.49	V

## For Band V Mode

Frequency	Reading	Correct	Result	Limit	Margin	Polar
(MHz)	(dBm)	dB	(dBm)	(dBm)	(dB)	H/V
Low Channel (826.4MHz)						
1652.8	-49.66	4.97	-44.69	-13	-31.69	H
2479.2	-49.02	8.47	-40.55	-13	-27.55	H
1652.8	-47.72	4.97	-42.75	-13	-29.75	V
2479.2	-46.76	8.47	-38.29	-13	-25.29	V
Middle Channel (836.6MHz)						
1672.8	-49.96	5.11	-44.85	-13	-31.85	H
2509.2	-46.61	8.54	-38.07	-13	-25.07	H
1672.8	-47.84	5.11	-42.73	-13	-29.73	V
2509.2	-47.46	8.54	-38.92	-13	-25.92	V
High Channel (846.6MHz)						
1693.2	-46.18	5.25	-40.93	-13	-27.93	H
2539.8	-46.05	8.57	-37.48	-13	-24.48	H
1693.2	-48.12	5.25	-42.87	-13	-29.87	V
2539.8	-46.01	8.57	-37.44	-13	-24.44	V

## For Band II Mode

Frequency	Reading	Correct	Result	Limit	Margin	Polar
(MHz)	(dBm)	dB	(dBm)	(dBm)	(dB)	H/V
Low Channel (1852.4MHz)						
3704.8	-52.88	10.55	-42.33	-13	-29.33	H
5557.2	-53.48	13.38	-40.1	-13	-27.1	H
3704.8	-52.53	10.55	-41.98	-13	-28.98	V
5557.2	-54.16	13.38	-40.78	-13	-27.78	V
Middle Channel (1880MHz)						
3760.8	-54.96	10.64	-44.32	-13	-31.32	H
5640.0	-52.45	13.54	-38.91	-13	-25.91	H
3760.8	-52.32	10.64	-41.68	-13	-28.68	V
5640.0	-51.21	13.54	-37.67	-13	-24.67	V
High Channel (1907.6MHz)						
3815.2	-53.72	10.74	-42.98	-13	-29.98	H
5722.8	-51.83	13.69	-38.14	-13	-25.14	H
3815.2	-53.06	10.74	-42.32	-13	-29.32	V
5722.8	-53.32	13.69	-39.63	-13	-26.63	V

Note: Result=Reading+ Correct, Margin= Result- Limit

Testing is carried out with frequency rang 9kHz to 20GHz, which above 3<sup>th</sup> Harmonics are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured, so the data is not display.

## 9. Frequency Stability

### 9.1 Standard Applicable

According to §22.355, the carrier frequency of each transmitter in the Public Mobile Services must be maintained within the tolerances given in Table below:

Frequency Tolerance for Cellular Band

Frequency range (MHz)	Base, fixed (ppm)	Mobile ≤3 watts (ppm)	Mobile ≤3 watts (ppm)
25 to 50	20.0	20.0	50.0
50 to 450	5.0	5.0	50.0
450 to 512	2.5	5.0	5.0
821 to 896	1.5	2.5	2.5
928 to 929	5.0	N/A	N/A
929 to 960	1.5	N/A	N/A
2110 to 2220	10.0	N/A	N/A

According to §24.235, the frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.

### 9.2 Test Procedure

According to §2.1055, the following test procedure was performed.

The Frequency Stability is measured directly with a Frequency Domain Analyzer. Frequency Deviation in ppm is calculated from the measured peak to peak value.

The Carrier Frequency Stability over Power Supply Voltage and over Temperature is measured with a Frequency Domain Analyzer in histogram mode

Temperature:	Supply Voltage
20°C	DC 3.3-4.4V of nominal voltage declared by manufacturer
-30°C to +50°C	Normal

### 9.3 Environmental Conditions

Temperature:	20°C
Relative Humidity:	54%
ATM Pressure:	1011 mbar

### 9.4 Summary of Test Results/Plots

## For Cellular Band GSM Mode

Reference Frequency(Middle Channel): 836.6 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		MCF (Hz)	Error (ppm)
50	3.8	40	0.0478
40	3.8	36	0.0430
30	3.8	41	0.0490
20	3.8	45	0.0538
10	3.8	42	0.0502
0	3.8	39	0.0466
-10	3.8	43	0.0514
-20	3.8	41	0.0490
-30	3.8	41	0.0490

## For PCS Band GSM Mode

Reference Frequency(Middle Channel): 1880 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		MCF (Hz)	Error (ppm)
50	3.8	81	0.0431
40	3.8	82	0.0436
30	3.8	82	0.0436
20	3.8	76	0.0404
10	3.8	80	0.0426
0	3.8	81	0.0431
-10	3.8	79	0.0420
-20	3.8	84	0.0447
-30	3.8	84	0.0447

## For Cellular Band GPRS Mode

Reference Frequency(Middle Channel): 836.6 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		MCF (Hz)	Error (ppm)
50	3.8	44	0.0526
40	3.8	42	0.0502
30	3.8	41	0.0490
20	3.8	44	0.0526
10	3.8	38	0.0454
0	3.8	37	0.0442
-10	3.8	39	0.0466
-20	3.8	44	0.0526
-30	3.8	42	0.0502

## For PCS Band GPRS Mode

Reference Frequency(Middle Channel): 1880 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		MCF (Hz)	Error (ppm)
50	3.8	85	0.0452
40	3.8	75	0.0399
30	3.8	78	0.0415
20	3.8	76	0.0404
10	3.8	75	0.0399
0	3.8	84	0.0447
-10	3.8	81	0.0431
-20	3.8	83	0.0441
-30	3.8	79	0.0420



## For Cellular Band EDGE Mode

Reference Frequency(Middle Channel): 836.6MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		MCF (Hz)	Error (ppm)
50	3.8	38	0.0454
40	3.8	40	0.0478
30	3.8	39	0.0466
20	3.8	36	0.0430
10	3.8	39	0.0466
0	3.8	36	0.0430
-10	3.8	39	0.0466
-20	3.8	44	0.0526
-30	3.8	35	0.0418

## For PCS Band EDGE Mode

Reference Frequency(Middle Channel): 1880 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		MCF (Hz)	Error (ppm)
50	3.8	85	0.0452
40	3.8	76	0.0404
30	3.8	80	0.0426
20	3.8	82	0.0436
10	3.8	78	0.0415
0	3.8	80	0.0426
-10	3.8	81	0.0431
-20	3.8	77	0.0410
-30	3.8	78	0.0415

## For WCDMA Band V Mode

Reference Frequency(Middle Channel): 836.4 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		MCF (Hz)	Error (ppm)
50	3.8	-30	-0.0359
40	3.8	-29	-0.0347
30	3.8	-27	-0.0323
20	3.8	-31	-0.0371
10	3.8	-27	-0.0323
0	3.8	-26	-0.0311
-10	3.8	-29	-0.0347
-20	3.8	-29	-0.0347
-30	3.8	-30	-0.0359

## For HSDPA Band V Mode

Reference Frequency(Middle Channel): 836.4 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		MCF (Hz)	Error (ppm)
50	3.8	-34	-0.0407
40	3.8	-31	-0.0371
30	3.8	-32	-0.0383
20	3.8	-28	-0.0335
10	3.8	-27	-0.0323
0	3.8	-30	-0.0359
-10	3.8	-31	-0.0371
-20	3.8	-29	-0.0347
-30	3.8	-29	-0.0347

## For HSUPA Band V Mode

Reference Frequency(Middle Channel): 836.4 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		MCF (Hz)	Error (ppm)
50	3.8	-31	-0.0371
40	3.8	-31	-0.0371
30	3.8	-29	-0.0347
20	3.8	-34	-0.0407
10	3.8	-29	-0.0347
0	3.8	-30	-0.0359
-10	3.8	-26	-0.0311
-20	3.8	-27	-0.0323
-30	3.8	-26	-0.0311

## WCDMA Band II Mode

Reference Frequency(Middle Channel): 1880 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		MCF (Hz)	Error (ppm)
50	3.8	29	0.0154
40	3.8	30	0.0160
30	3.8	28	0.0149
20	3.8	26	0.0138
10	3.8	27	0.0144
0	3.8	33	0.0176
-10	3.8	26	0.0138
-20	3.8	28	0.0149
-30	3.8	34	0.0181

## For HSDPA Band II Mode

Reference Frequency(Middle Channel): 1880 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		MCF (Hz)	Error (ppm)
50	3.8	35	0.0186
40	3.8	29	0.0154
30	3.8	30	0.0160
20	3.8	25	0.0133
10	3.8	32	0.0170
0	3.8	28	0.0149
-10	3.8	33	0.0176
-20	3.8	33	0.0176
-30	3.8	32	0.0170

## For HSUDA Band II Mode

Reference Frequency(Middle Channel): 1880 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		MCF (Hz)	Error (ppm)
50	3.8	26	0.0138
40	3.8	32	0.0170
30	3.8	27	0.0144
20	3.8	28	0.0149
10	3.8	32	0.0170
0	3.8	31	0.0165
-10	3.8	31	0.0165
-20	3.8	31	0.0165
-30	3.8	31	0.0165

So, Frequency Stability Versus Input Voltage is:

Reference Frequency(Middle Channel): GSM 836.6MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		Frequency (Hz)	Error (ppm)
20	3.3	48	0.0574
	3.8	47	0.0562
	4.4	42	0.0502
Reference Frequency(Middle Channel): GSM 1880 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		Frequency (Hz)	Error (ppm)
20	3.3	73	0.0388
	3.8	80	0.0426
	4.4	77	0.0410
Reference Frequency(Middle Channel): GPRS 836.6MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		Frequency (Hz)	Error (ppm)
20	3.3	46	0.0550
	3.8	48	0.0574
	4.4	48	0.0574
Reference Frequency(Middle Channel): GPRS 1880 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		Frequency (Hz)	Error (ppm)
20	3.3	77	0.0410
	3.8	80	0.0426
	4.4	76	0.0404

Reference Frequency(Middle Channel): EDGE 836.6MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		Frequency (Hz)	Error (ppm)
20	3.3	42	0.0502
	3.8	46	0.0550
	4.4	43	0.0514
Reference Frequency(Middle Channel): EDGE 1880 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		Frequency (Hz)	Error (ppm)
20	3.3	74	0.0394
	3.8	76	0.0404
	4.4	75	0.0399
Reference Frequency(Middle Channel): WCDMA 836.4MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		Frequency (Hz)	Error (ppm)
20	3.3	-21	-0.0251
	3.8	-21	-0.0251
	4.4	-19	-0.0227
Reference Frequency(Middle Channel): HSDPA 836.4MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		Frequency (Hz)	Error (ppm)
20	3.3	-21	-0.0251
	3.8	-17	-0.0203
	4.4	-18	-0.0215
Reference Frequency(Middle Channel): HSUPA 836.4MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		Frequency (Hz)	Error (ppm)
20	3.3	-23	-0.0275
	3.8	-18	-0.0215
	4.4	-23	-0.0275

Reference Frequency(Middle Channel): WCDMA 1880 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		Frequency (Hz)	Error (ppm)
20	3.3	34	0.0181
	3.8	31	0.0165
	4.4	34	0.0181
Reference Frequency(Middle Channel): HSDPA 1880 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		Frequency (Hz)	Error (ppm)
20	3.3	29	0.0154
	3.8	25	0.0133
	4.4	26	0.0138
Reference Frequency(Middle Channel): HSUPA 1880 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		Frequency (Hz)	Error (ppm)
20	3.3	28	0.0149
	3.8	30	0.0160
	4.4	34	0.0181

\*\*\*\*\* END OF REPORT \*\*\*\*\*