

FCC Test Report

FCC ID : 2AGMRTRM989DB
Equipment : 802.11bgn/Scanning WiFi Radio Module
Brand Name : EVEREST™ Network Solutions
Model Name : TRM989DB
Applicant : Tembo Systems, Inc.
2933 Bunker Hill lane, Suite 100, Santa
Clara, CA 95054 U.S.A
Manufacturer : Tembo Systems, Inc.
2933 Bunker Hill lane, Suite 100, Santa
Clara, CA 95054 U.S.A
Standard : 47 CFR FCC Part 15.247

The product was received on Mar. 19, 2018, and testing was started from Mar. 19, 2018 and completed on Apr. 09, 2018. We, SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.10-2013 and shown compliance with the applicable technical standards.

The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any agency of government.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.



Approved by: Allen Lin

SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory

No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)



Table of Contents

HISTORY OF THIS TEST REPORT	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION	5
1.1 Information.....	5
1.2 Testing Applied Standards	7
1.3 Testing Location Information	7
1.4 Measurement Uncertainty	7
2 TEST CONFIGURATION OF EUT	8
2.1 Test Condition	8
2.2 Test Channel Mode	8
2.3 The Worst Case Measurement Configuration.....	9
2.4 Support Equipment.....	10
2.5 Test Setup Diagram	11
3 TRANSMITTER TEST RESULT	13
3.1 AC Power-line Conducted Emissions	13
3.2 DTS Bandwidth	14
3.3 Maximum Conducted Output Power	15
3.4 Power Spectral Density	17
3.5 Emissions in Non-restricted Frequency Bands	18
3.6 Emissions in Restricted Frequency Bands.....	19
4 TEST EQUIPMENT AND CALIBRATION DATA	23
APPENDIX A. TEST RESULTS OF AC POWER-LINE CONDUCTED EMISSIONS	
APPENDIX B. TEST RESULTS OF DTS BANDWIDTH	
APPENDIX C. TEST RESULTS OF MAXIMUM CONDUCTED OUTPUT POWER	
APPENDIX D. TEST RESULTS OF POWER SPECTRAL DENSITY	
APPENDIX E. TEST RESULTS OF EMISSIONS IN NON-RESTRICTED FREQUENCY BANDS	
APPENDIX F. TEST RESULTS OF EMISSIONS IN RESTRICTED FREQUENCY BANDS	
APPENDIX G. TEST PHOTOS	
PHOTOGRAPHS OF EUT v02	

[illegible]

Summary of Test Result

Report Clause	Ref. Std. Clause	Test Items	Result (PASS/FAIL)	Remark
1.1.2	15.203	Antenna Requirement	PASS	FCC 15.203
3.1	15.207	AC Power-line Conducted Emissions	PASS	FCC 15.207
3.2	15.247(a)	DTS Bandwidth	PASS	≥500kHz
3.3	15.247(b)	Maximum Conducted Output Power	PASS	Power [dBm]: 30
3.4	15.247(e)	Power Spectral Density	PASS	PSD [dBm/3kHz]: 8
3.5	15.247(d)	Emissions in Non-restricted Frequency Bands	PASS	Non-Restricted Bands: > 30 dBc
3.6	15.247(d)	Emissions in Restricted Frequency Bands	PASS	Restricted Bands: FCC 15.209

Reviewed by: Jeremy Lin

Report Producer: Jackson Tsai

1 General Description

1.1 Information

1.1.1 RF General Information

Frequency Range (MHz)	IEEE Std. 802.11	Ch. Frequency (MHz)	Channel Number
2400-2483.5	b, g, n (HT20) , ac (VHT20)	2412-2462	1-11 [11]
2400-2483.5	n (HT40) , ac (VHT40)	2422-2452	3-9 [7]

Band	Mode	BWch (MHz)	Nant
2.4-2.4835GHz	802.11b	20	3TX
2.4-2.4835GHz	802.11g	20	3TX
2.4-2.4835GHz	802.11n HT20	20	3TX
2.4-2.4835GHz	802.11n VHT20	20	3TX
2.4-2.4835GHz	802.11n HT40	40	3TX
2.4-2.4835GHz	802.11n VHT40	40	3TX

Note:

- 11b mode uses a combination of DSSS-DBPSK, DQPSK, CCK modulation.
- 11g, HT20 and HT40 use a combination of OFDM-BPSK, QPSK, 16QAM, 64QAM modulation.
- VHT20, VHT40 use a combination of OFDM-BPSK, QPSK, 16QAM, 64QAM, 256QAM modulation.
- BWch is the nominal channel bandwidth.
- The EUT supports 5GHz function for receiver only.

1.1.2 Antenna Information

Ant.	Brand Holder	Model Name	Antenna Type	Connector	Gain (dBi)	TX Function	Host System Model
	Tembo Systems Inc.	PCA-000020-000-X	OMNI Antenna	I-PEX	Note	3TX/3RX	AP24I612

Note:

Ant.	Gain (dBi)	Cable loss	True Gain (dBi)	Array Gain (dBi)
	-0.5	0.7	-1.2	4.77

1.1.3 EUT Information

Operational Condition			
EUT Power Type	From Host System		
Beamforming Function	<input type="checkbox"/> With beamforming	<input checked="" type="checkbox"/> Without beamforming	
Type of EUT			
<input type="checkbox"/>	Stand-alone		
<input type="checkbox"/>	Combined (EUT where the radio part is fully integrated within another device)		
	Combined Equipment - Brand Name / Model No.:		...
<input checked="" type="checkbox"/>	Plug-in radio (EUT intended for a variety of host systems)		
	Host System - Brand Name / Model No.:		EVEREST™ Network Solutions / AP24I612
<input type="checkbox"/>	Other:		

1.1.4 Mode Test Duty Cycle

Mode	DC	DCF(dB)	T(s)	VBW(Hz) ≥ 1/T
802.11b	0.994	0.026	n/a (DC>=0.98)	n/a (DC>=0.98)
802.11g	0.965	0.155	2.067m	1k
802.11ac VHT20	0.962	0.168	1.934m	1k
802.11ac VHT40	0.922	0.353	954.688u	3k

1.2 Testing Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR FCC Part 15
- ♦ ANSI C63.10-2013
- ♦ KDB 558074 D01 v04
- ♦ KDB 662911 D01 v02r01

1.3 Testing Location Information

Testing Location			
<input checked="" type="checkbox"/>	HWA YA	ADD : No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)	
		TEL : 886-3-327-3456	FAX : 886-3-327-0973
Test site Designation No. TW1190 with FCC.			
<input type="checkbox"/>	JHUBEI	ADD : No.8, Ln. 724, Bo'ai St., Zhubei City, Hsinchu County, Taiwan (R.O.C.)	
		TEL : 886-3-656-9065	FAX : 886-3-656-9085
Test site Designation No. TW0006 with FCC.			

Test Condition	Test Site No.	Test Engineer	Test Environment	Test Date
RF Conducted	TH06-HY	Barry Xiao	22.5°C / 65%	28/Mar/2018
Radiated	03CH01-HY	Jeff Lin	22.2°C / 51.8%	03/Apr/2018
AC Conduction	CO04-HY	Kevin Pan	22.2°C / 51.8%	09/Apr/2018

1.4 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2))

Test Items	Uncertainty	Remark
Conducted Emission (150kHz ~ 30MHz)	3.6 dB	Confidence levels of 95%
Radiated Emission (9kHz ~ 30MHz)	3.0 dB	Confidence levels of 95%
Radiated Emission (30MHz ~ 1,000MHz)	4.3 dB	Confidence levels of 95%
Radiated Emission (1GHz ~ 18GHz)	3.9 dB	Confidence levels of 95%
Radiated Emission (18GHz ~ 40GHz)	3.5 dB	Confidence levels of 95%
Conducted Emission	1.3 dB	Confidence levels of 95%
Temperature	0.7 °C	Confidence levels of 95%
Humidity	4 %	Confidence levels of 95%

2 Test Configuration of EUT

2.1 Test Condition

RF Conducted	Abbreviation	Remark
TnomVnom	Tnom	20°C
-	Vnom	120V

2.2 Test Channel Mode




Test Software Version	QCARCT Ver 3.0.197.0
-----------------------	----------------------

Mode	Power Setting
802.11b_Nss1,(1Mbps)_3TX	-
2412MHz	18
2437MHz	18
2462MHz	18
802.11g_Nss1,(6Mbps)_3TX	-
2412MHz	18
2437MHz	18
2462MHz	18
802.11ac VHT20_Nss1,(MCS0)_3TX	-
2412MHz	18
2437MHz	18
2462MHz	18
802.11ac VHT40_Nss1,(MCS0)_3TX	-
2422MHz	17
2427MHz	18
2437MHz	18
2447MHz	18
2452MHz	17.5

2.3 The Worst Case Measurement Configuration

The Worst Case Mode for Following Conformance Tests	
Tests Item	AC power-line conducted emissions
Condition	AC power-line conducted measurement for line and neutral
Operating Mode	CTX
1	Adapter mode

The Worst Case Mode for Following Conformance Tests	
Tests Item	DTS Bandwidth Maximum Conducted Output Power Power Spectral Density Emissions in Non-restricted Frequency Bands
Test Condition	Conducted measurement at transmit chains

The Worst Case Mode for Following Conformance Tests			
Tests Item	Emissions in Restricted Frequency Bands		
Test Condition	Radiated measurement If EUT consist of multiple antenna assembly (multiple antenna are used in EUT regardless of spatial multiplexing MIMO configuration), the radiated test should be performed with highest antenna gain of each antenna type.		
Operating Mode < 1GHz	CTX		
1	Adapter mode		
Operating Mode > 1GHz	CTX		
Orthogonal Planes of EUT	X Plane	Y Plane	Z Plane
			
Worst Planes of EUT		V	

2.4 Support Equipment

Support Equipment – RF Conducted				
No.	Equipment	Brand Name	Model Name	FCC ID
1	Notebook	DELL	E5410	DoC
2	Adapter for NB	DELL	HA65NM130	DoC
3	AC Source	GW	APS-9102	-
4	Fixture	EVEREST™ Network Solutions	AP24I612	-

Note: Support equipment No.4 was provided by customer.

Support Equipment – Radiated Emission				
No.	Equipment	Brand Name	Model Name	FCC ID
1	Fixture	EVEREST™ Network Solutions	AP24I612	-
2	AC Adapter	DELTA	ADP-66CR B	DoC

Note: Support equipment No.1 and 2 was provided by customer.

Support Equipment – AC Conduction				
No.	Equipment	Brand Name	Model Name	FCC ID
1	Fixture	EVEREST™ Network Solutions	AP24I612	-
2	AC Adapter	DELTA	ADP-66CR B	DoC
3	Notebook	DELL	E5530	DoC
4	Notebook	DELL	E5530	DoC


Note: Support equipment No.1 and 2 was provided by customer.

2.5 Test Setup Diagram

Test Setup Diagram – AC Line Conducted Emission Test



Item	Connection	Shielded	Length(m)	Remark
1	DC Power Line	No	1.5m	-
2	AC Power Line	No	1.5m	-

Test Setup Diagram – Radiated Test


Item	Connection	Shielded	Length(m)	Remark
1	DC Power Line	No	1.5m	-
2	AC Power Line	No	1.5m	-

3 Transmitter Test Result

3.1 AC Power-line Conducted Emissions

3.1.1 AC Power-line Conducted Emissions Limit

AC Power-line Conducted Emissions Limit		
Frequency Emission (MHz)	Quasi-Peak	Average
0.15-0.5	66 - 56 *	56 - 46 *
0.5-5	56	46
5-30	60	50

Note 1: * Decreases with the logarithm of the frequency.


3.1.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.1.3 Test Procedures

Test Method
<input checked="" type="checkbox"/> Refer as ANSI C63.10-2013, clause 6.2 for AC power-line conducted emissions.

3.1.4 Test Setup



3.1.5 Test Result of AC Power-line Conducted Emissions

Refer as Appendix A

3.2 DTS Bandwidth

3.2.1 6dB Bandwidth Limit

6dB Bandwidth Limit	
Systems using digital modulation techniques:	
▪	6 dB bandwidth \geq 500 kHz.


3.2.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.2.3 Test Procedures

Test Method	
▪	For the emission bandwidth shall be measured using one of the options below:
<input checked="" type="checkbox"/>	Refer as KDB 558074, clause 8.1 Option 1 for 6 dB bandwidth measurement.
<input type="checkbox"/>	Refer as KDB 558074, clause 8.2 Option 2 for 6 dB bandwidth measurement.
<input type="checkbox"/>	Refer as RSS-Gen, clause 6.6 for for occupied bandwidth testing.
<input type="checkbox"/>	Refer as ANSI C63.10, clause 6.9.3 for occupied bandwidth testing.

3.2.4 Test Setup



3.2.5 Test Result of Emission Bandwidth

Refer as Appendix B

3.3 Maximum Conducted Output Power

3.3.1 Maximum Conducted Output Power Limit

Maximum Conducted Output Power Limit		
	<ul style="list-style-type: none"> If $G_{TX} \leq 6$ dBi, then $P_{Out} \leq 30$ dBm (1 W) 	
	<ul style="list-style-type: none"> Point-to-multipoint systems (P2M): If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)$ dBm 	
	<ul style="list-style-type: none"> Point-to-point systems (P2P): If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)/3$ dBm 	
	<ul style="list-style-type: none"> Smart antenna system (SAS): 	
	-	Single beam: If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)/3$ dBm
	-	Overlap beam: If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)/3$ dBm
	-	Aggregate power on all beams: If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)/3 + 8$ dB dBm
e.i.r.p. Power Limit:		
	<ul style="list-style-type: none"> 2400-2483.5 MHz Band 	
	<ul style="list-style-type: none"> Point-to-multipoint systems (P2M): $P_{eirp} \leq 36$ dBm (4 W) 	
	<ul style="list-style-type: none"> Point-to-point systems (P2P): $P_{eirp} \leq \text{MAX}(36, [P_{Out} + G_{TX}])$ dBm 	
	<ul style="list-style-type: none"> Smart antenna system (SAS) 	
	-	Single beam: $P_{eirp} \leq \text{MAX}(36, P_{Out} + G_{TX})$ dBm
	-	Overlap beam: $P_{eirp} \leq \text{MAX}(36, P_{Out} + G_{TX})$ dBm
	-	Aggregate power on all beams: $P_{eirp} \leq \text{MAX}(36, [P_{Out} + G_{TX} + 8])$ dBm
P_{Out} = maximum peak conducted output power or maximum conducted output power in dBm, G_{TX} = the maximum transmitting antenna directional gain in dBi.		


3.3.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.3.3 Test Procedures

Test Method	
<ul style="list-style-type: none"> Maximum Peak Conducted Output Power 	
<input type="checkbox"/>	Refer as KDB 558074, clause 9.1.1 Option 1 (RBW ≥ EBW method).
<input type="checkbox"/>	Refer as KDB 558074, clause 9.1.2 Option 2 (integrated band power method)
<input type="checkbox"/>	Refer as KDB 558074, clause 9.1.3 Option 3 (peak power meter for VBW ≥ DTS BW)
<ul style="list-style-type: none"> Maximum Average Conducted Output Power 	
Duty cycle ≥ 98%	
<input type="checkbox"/>	Refer as KDB 558074, clause 9.2.2.4 Method AVGSA-2 (spectral trace averaging).
Duty cycle < 98%	
<input type="checkbox"/>	Refer as KDB 558074, clause 9.2.2.5 Method AVGSA-2 Alt. (slow sweep speed)
RF power meter and average over on/off periods with duty factor or gated trigger	
<input checked="" type="checkbox"/>	Refer as KDB 558074, clause 9.2.3.1 Method AVGPM (using an RF average power meter).
<ul style="list-style-type: none"> For conducted measurement. 	
<ul style="list-style-type: none"> If the EUT supports multiple transmit chains using options given below: Refer as KDB 662911, In-band power measurements. Using the measure-and-sum approach, measured all transmit ports individually. Sum the power (in linear power units e.g., mW) of all ports for each individual sample and save them. 	
<ul style="list-style-type: none"> If multiple transmit chains, EIRP calculation could be following as methods: $P_{total} = P_1 + P_2 + \dots + P_n$ (calculated in linear unit [mW] and transfer to log unit [dBm]) $EIRP_{total} = P_{total} + DG$ 	

3.3.4 Test Setup



3.3.5 Test Result of Maximum Conducted Output Power

Refer as Appendix C

3.4 Power Spectral Density

3.4.1 Power Spectral Density Limit

Power Spectral Density Limit	
▪	Power Spectral Density (PSD) ≤ 8 dBm/3kHz


3.4.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.4.3 Test Procedures

Test Method	
▪	Peak power spectral density procedures that the same method as used to determine the conducted output power. If maximum peak conducted output power was measured to demonstrate compliance to the output power limit, then the peak PSD procedure below (Method PKPSD) shall be used. If maximum conducted output power was measured to demonstrate compliance to the output power limit, then one of the average PSD procedures shall be used, as applicable based on the following criteria (the peak PSD procedure is also an acceptable option).
<input checked="" type="checkbox"/>	Refer as KDB 558074, clause 10.2 Method PKPSD (RBW=3-100kHz; Detector=peak).
▪	For conducted measurement.
▪	If The EUT supports multiple transmit chains using options given below:
▪	Measure and sum the spectra across the outputs. Refer as KDB 662911, In-band power spectral density (PSD). Sample all transmit ports simultaneously using a spectrum analyzer for each transmit port. Where the trace bin-by-bin of each transmit port summing can be performed. (i.e., in the first spectral bin of output 1 is summed with that in the first spectral bin of output 2 and that from the first spectral bin of output 3, and so on up to the NTX output to obtain the value for the first frequency bin of the summed spectrum.). Add up the amplitude (power) values for the different transmit chains and use this as the new data trace.

3.4.4 Test Setup



3.4.5 Test Result of Power Spectral Density

Refer as Appendix D

3.5 Emissions in Non-restricted Frequency Bands

3.5.1 Emissions in Non-restricted Frequency Bands Limit

Un-restricted Band Emissions Limit	
RF output power procedure	Limit (dB)
Peak output power procedure	20
Average output power procedure	30
<p>Note 1: If the peak output power procedure is used to measure the fundamental emission power to demonstrate compliance to requirements, then the peak conducted output power measured within any 100 kHz outside the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum measured in-band peak PSD level.</p> <p>Note 2: If the average output power procedure is used to measure the fundamental emission power to demonstrate compliance to requirements, then the power in any 100 kHz outside of the authorized frequency band shall be attenuated by at least 30 dB relative to the maximum measured in-band average PSD level.</p>	


3.5.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.5.3 Test Procedures

Test Method
<ul style="list-style-type: none"> Refer as KDB 558074, clause 11 for unwanted emissions into non-restricted bands.

3.5.4 Test Setup



3.5.5 Test Result of Emissions in Non-restricted Frequency Bands

Refer as Appendix E

3.6 Emissions in Restricted Frequency Bands

3.6.1 Emissions in Restricted Frequency Bands Limit

Restricted Band Emissions Limit			
Frequency Range (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m)	Measure Distance (m)
0.009~0.490	2400/F(kHz)	48.5 - 13.8	300
0.490~1.705	24000/F(kHz)	33.8 - 23	30
1.705~30.0	30	29	30
30~88	100	40	3
88~216	150	43.5	3
216~960	200	46	3
Above 960	500	54	3

Note 1: Test distance for frequencies at or above 30 MHz, measurements may be performed at a distance other than the limit distance provided they are not performed in the near field and the emissions to be measured can be detected by the measurement equipment. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse of linear distance for field-strength measurements, inverse of linear distance-squared for power-density measurements).

Note 2: Test distance for frequencies at below 30 MHz, measurements may be performed at a distance closer than the EUT limit distance; however, an attempt should be made to avoid making measurements in the near field. When performing measurements below 30 MHz at a closer distance than the limit distance, the results shall be extrapolated to the specified distance by either making measurements at a minimum of two or more distances on at least one radial to determine the proper extrapolation factor or by using the square of an inverse linear distance extrapolation factor (40 dB/decade). The test report shall specify the extrapolation method used to determine compliance of the EUT.

Note 3: Using the distance of 1m during the test for above 18 GHz, and the test value to correct for the distance factor at 3m.


3.6.2 Measuring Instruments


Refer a test equipment and calibration data table in this test report.

3.6.3 Test Procedures

Test Method	
<ul style="list-style-type: none"> The average emission levels shall be measured in [duty cycle ≥ 98 or duty factor]. 	
<ul style="list-style-type: none"> Refer as ANSI C63.10, clause 6.10.3 band-edge testing shall be performed at the lowest frequency channel and highest frequency channel within the allowed operating band. 	
<ul style="list-style-type: none"> For the transmitter unwanted emissions shall be measured using following options below: 	
	<ul style="list-style-type: none"> Refer as KDB 558074, clause 12 for unwanted emissions into restricted bands.
	<input checked="" type="checkbox"/> Refer as KDB 558074, clause 12.2.5.3 (ANSI C63.10, clause 4.1.4.2.3), Reduced VBW $\geq 1/T$.
	<input checked="" type="checkbox"/> Refer as KDB 558074, clause 12.2.4 measurement procedure peak limit.
<ul style="list-style-type: none"> For the transmitter band-edge emissions shall be measured using following options below: 	
	<ul style="list-style-type: none"> Refer as KDB 558074 clause 13.1, When the performing peak or average radiated measurements, emissions within 2 MHz of the authorized band edge may be measured using the marker-delta method described below.
	<ul style="list-style-type: none"> Refer as KDB 558074, clause 13.2 (ANSI C63.10, clause 6.10.6) for marker-delta method for band-edge measurements.
	<ul style="list-style-type: none"> Refer as KDB 558074, clause 13.3 for narrower resolution bandwidth (100kHz) using the band power and summing the spectral levels (i.e., 1 MHz).
<ul style="list-style-type: none"> For conducted and cabinet radiation measurement, refer as KDB 558074, clause 12.2.2. 	
	<ul style="list-style-type: none"> For conducted unwanted emissions into restricted bands (absolute emission limits). Devices with multiple transmit chains using options given below: (1) Measure and sum the spectra across the outputs or (2) Measure and add 10 log(N) dB
	<ul style="list-style-type: none"> For KDB 662911 The methodology described here may overestimate array gain, thereby resulting in apparent failures to satisfy the out-of-band limits even if the device is actually compliant. In such cases, compliance may be demonstrated by performing radiated tests around the frequencies at which the apparent failures occurred.

3.6.4 Test Setup





3.6.5 Test Result of Emissions in Restricted Frequency Bands (Below 30MHz)

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

3.6.6 Test Result of Emissions in Restricted Frequency Bands

Refer as Appendix F

4 Test Equipment and Calibration Data

Instrument for AC Conduction

Instrument	Manufacturer	Model No.	Serial No.	Spec.	Calibration Date	Calibration Due Date
EMC Receiver	R&S	ESR3	102052	9 kHz ~ 3.6 GHz	29/Apr/2017	28/Apr/2018
LISN	R&S	ENV216	101295	9 kHz ~ 30 MHz	17/Nov/2017	16/Nov/2018
RF Cable-CON	HUBER+SUHNER	RG213/U	07611832020001	9 kHz ~ 30 MHz	06/Oct/2017	05/Oct/2018
AC POWER	APC	AFC-11005G	F310050055	47 Hz ~ 63 Hz 5~300V	NCR	NCR
Impuls Begrenzer Pulse Limiter	SCHWARZBECK	VTSD 9561-F	9561-F041	9 kHz ~ 30 MHz	12/Oct/2017	11/Oct/2018

NCR : Non-Calibration Require

Instrument for Radiated Test


Instrument	Manufacturer	Model No.	Serial No.	Spec.	Calibration Date	Calibration Due Date
3m Semi Anechoic Chamber	SIDT FRANKONIA	SAC-3M	03CH03-HY	30 MHz ~ 1 GHz 3m	31/Oct/2017	30/Oct/2018
3m Semi Anechoic Chamber	SIDT FRANKONIA	SAC-3M	03CH03-HY	1 GHz ~ 18 GHz 3m	01/Nov/2017	31/Oct/2018
Amplifier	HP	8447D	2944A08033	10 kHz ~ 1.3 GHz	19/Apr/2017	18/Apr/2018
Amplifier	Keysight	83017A	MY53270196	1 GHz ~ 26.5 GHz	31/Aug/2017	30/Aug/2018
Spectrum	R&S	FSV40	101500	9 kHz ~ 40 GHz	28/Jun/2017	27/Jun/2018
Receiver	R&S	ESR3	102052	9 kHz ~ 3.6 GHz	29/Apr/2017	28/Apr/2018
RF Cable-R03m	Jye Bao	RG142	CB021	9 kHz ~ 1 GHz	26/Jan/2018	25/Jan/2019
RF Cable-high	SUHNER	SUCOFLEX106	CB222	1 GHz ~ 40 GHz	26/Jan/2018	25/Jan/2019
Bilog Antenna	SCHAFFNER	CBL 6112B	22237	30 MHz ~ 1 GHz	08/Jul/2017	07/Jul/2018
Horn Antenna	SCHWARZBECK	BBHA9170	BBHA9170154	18 GHz ~ 40 GHz	09/Feb/2018	08/Feb/2019
Horn Antenna	SCHWARZBECK	BBHA9120D	1531	1 GHz ~ 18 GHz	25/Apr/2017	24/Apr/2018
Loop Antenna	TESEQ	HLA 6120	31244	9 kHz ~ 30 MHz	16/Mar/2018	15/Mar/2019

**Instrument for Conducted Test**

Instrument	Manufacturer	Model No.	Serial No.	Spec.	Calibration Date	Calibration Due Date
Spectrum Analyzer	R&S	FSV 40	101013	9 kHz ~ 40 GHz	29/Dec/2017	28/Dec/2018
Signal Generator	R&S	SMR40	100116	10 MHz ~ 40 GHz	27/Jul/2017	26/Jul/2018
Power Sensor	Anritsu	MA2411B	0917017	300 MHz ~ 40 GHz	05/Feb/2018	04/Feb/2019
Power Meter	Anritsu	ML2495A	0949003	300 MHz ~ 40 GHz	05/Feb/2018	04/Feb/2019
RF Cable-0.2m	HUBER+SUHNER	SUCOFLEX_104	MY10709/4	30 MHz ~ 26.5 GHz	25/Aug/2017	24/Aug/2018
RF Cable-0.2m	HUBER+SUHNER	SUCOFLEX_104	MY10712/4	30 MHz ~ 26.5 GHz	25/Aug/2017	24/Aug/2018
RF Cable-0.5m	HUBER+SUHNER	SUCOFLEX_104	MY10713/4	30 MHz ~ 26.5 GHz	25/Aug/2017	24/Aug/2018

AC Power-line Conducted Emissions Result

Operating Mode	1	Power Phase	Neutral
Operating Function	Adapter Mode		




	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.1924	34.45	-19.48	53.93	24.82	9.62	0.01	Average
2	0.1924	45.98	-17.95	63.93	36.35	9.62	0.01	QP
3	0.6305	33.66	-12.34	46.00	24.00	9.61	0.05	Average
4 MAX	0.6305	44.96	-11.04	56.00	35.30	9.61	0.05	QP
5	0.7198	29.59	-16.41	46.00	19.93	9.62	0.04	Average
6	0.7198	43.41	-12.59	56.00	33.75	9.62	0.04	QP
7	0.7876	25.63	-20.37	46.00	15.98	9.62	0.03	Average
8	0.7876	41.11	-14.89	56.00	31.46	9.62	0.03	QP
9	0.9431	27.32	-18.68	46.00	17.69	9.62	0.01	Average
10	0.9431	38.70	-17.30	56.00	29.07	9.62	0.01	QP
11	1.9080	30.02	-15.98	46.00	20.39	9.63	0.00	Average
12	1.9080	38.49	-17.51	56.00	28.86	9.63	0.00	QP

Note 1: ">20dB" means emission levels that exceed the level of 20 dB below the applicable limit.
Note 2: "N/F" means Nothing Found emissions (No emissions were detected.)

AC Power-line Conducted Emissions Result

Operating Mode	1	Power Phase	Line
Operating Function	Adapter Mode		



	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.1965	32.94	-20.82	53.76	23.32	9.62	0.00	Average
2	0.1965	43.60	-20.16	63.76	33.98	9.62	0.00	QP
3	0.6186	32.89	-13.11	46.00	23.23	9.61	0.05	Average
4	0.6186	45.09	-10.91	56.00	35.43	9.61	0.05	QP
5	0.6406	32.07	-13.93	46.00	22.41	9.61	0.05	Average
6 MAX	0.6406	45.38	-10.62	56.00	35.72	9.61	0.05	QP
7	0.7876	25.63	-20.37	46.00	15.99	9.61	0.03	Average
8	0.7876	38.48	-17.52	56.00	28.84	9.61	0.03	QP
9	1.4107	24.48	-21.52	46.00	14.87	9.61	0.00	Average
10	1.4107	36.44	-19.56	56.00	26.83	9.61	0.00	QP
11	2.8845	25.41	-20.59	46.00	15.73	9.63	0.05	Average
12	2.8845	35.61	-20.39	56.00	25.93	9.63	0.05	QP

Note 1: ">20dB" means emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found emissions (No emissions were detected.)

Summary

Mode	Max-N dB (Hz)	Max-OBW (Hz)	ITU-Code	Min-N dB (Hz)	Min-OBW (Hz)
2.4-2.4835GHz	-	-	-	-	-
802.11b_Nss1,(1Mbps)_3TX	11.05M	13.968M	14M0G1D	9.575M	13.818M
802.11g_Nss1,(6Mbps)_3TX	16.325M	16.517M	16M5D1D	16.025M	16.442M
802.11ac_VHT20_Nss1,(MCS0)_3TX	17.525M	17.691M	17M7D1D	16.25M	17.641M
802.11ac_VHT40_Nss1,(MCS0)_3TX	35.65M	36.182M	36M2D1D	35M	36.082M

Max-N dB = Maximum 6dB down bandwidth; **Max-OBW** = Maximum 99% occupied bandwidth;

Min-N dB = Minimum 6dB down bandwidth; **Min-OBW** = Minimum 99% occupied bandwidth;


Result

Mode	Result	Limit (Hz)	Port 1-N dB (Hz)	Port 1-OBW (Hz)	Port 2-N dB (Hz)	Port 2-OBW (Hz)	Port 3-N dB (Hz)	Port 3-OBW (Hz)
802.11b_Nss1,(1Mbps)_3TX	-	-	-	-	-	-	-	-
2412MHz_TnomVnom	Pass	500k	10.025M	13.868M	9.65M	13.818M	9.575M	13.893M
2437MHz_TnomVnom	Pass	500k	10.05M	13.818M	11.05M	13.893M	11.025M	13.843M
2462MHz_TnomVnom	Pass	500k	10.025M	13.818M	10.025M	13.868M	10.05M	13.968M
802.11g_Nss1,(6Mbps)_3TX	-	-	-	-	-	-	-	-
2412MHz_TnomVnom	Pass	500k	16.275M	16.467M	16.325M	16.517M	16.3M	16.467M
2437MHz_TnomVnom	Pass	500k	16.325M	16.492M	16.025M	16.492M	16.05M	16.442M
2462MHz_TnomVnom	Pass	500k	16.05M	16.517M	16.325M	16.517M	16.325M	16.442M
802.11ac_VHT20_Nss1,(MCS0)_3TX	-	-	-	-	-	-	-	-
2412MHz_TnomVnom	Pass	500k	16.775M	17.641M	17.175M	17.691M	16.5M	17.691M
2437MHz_TnomVnom	Pass	500k	16.8M	17.666M	16.775M	17.641M	16.75M	17.666M
2462MHz_TnomVnom	Pass	500k	17.525M	17.691M	17.275M	17.666M	16.25M	17.666M
802.11ac_VHT40_Nss1,(MCS0)_3TX	-	-	-	-	-	-	-	-
2422MHz_TnomVnom	Pass	500k	35.35M	36.082M	35.65M	36.132M	35.65M	36.132M
2437MHz_TnomVnom	Pass	500k	35.05M	36.082M	35.35M	36.182M	35.35M	36.082M
2452MHz_TnomVnom	Pass	500k	35.15M	36.132M	35M	36.082M	35.25M	36.132M


Port X-N dB = Port X 6dB down bandwidth; **Port X-OBW** = Port X 99% occupied bandwidth;

802.11b_Nss1,(1Mbps)_3TX
EBW
2412MHz


21/03/2018


802.11b_Nss1,(1Mbps)_3TX
EBW
2437MHz

21/03/2018



802.11b_Nss1,(1Mbps)_3TX
EBW
2462MHz

21/03/2018




802.11g_Nss1,(6Mbps)_3TX
EBW
2412MHz


21/03/2018


802.11g_Nss1,(6Mbps)_3TX
EBW
2437MHz

21/03/2018



802.11g_Nss1,(6Mbps)_3TX
EBW
2462MHz

21/03/2018




802.11ac VHT20_Nss1,(MCS0)_3TX
EBW
2412MHz


21/03/2018


802.11ac VHT20_Nss1,(MCS0)_3TX
EBW
2437MHz

21/03/2018



802.11ac VHT20_Nss1,(MCS0)_3TX
EBW
2462MHz

21/03/2018




802.11ac VHT40_Nss1,(MCS0)_3TX
EBW
2422MHz


21/03/2018


802.11ac VHT40_Nss1,(MCS0)_3TX
EBW
2437MHz

21/03/2018


802.11ac VHT40_Nss1,(MCS0)_3TX
EBW
2452MHz

21/03/2018



Summary

Mode	Total Power (dBm)	Total Power (W)
2.4-2.4835GHz	-	-
802.11b_Nss1,(1Mbps)_3TX	22.83	0.19187
802.11g_Nss1,(6Mbps)_3TX	22.88	0.19409
802.11ac_VHT20_Nss1,(MCS0)_3TX	22.83	0.19187
802.11ac_VHT40_Nss1,(MCS0)_3TX	22.23	0.16711

Result

Mode	Result	DG (dBi)	Port 1 (dBm)	Port 2 (dBm)	Port 3 (dBm)	Total Power (dBm)	Power Limit (dBm)
802.11b_Nss1,(1Mbps)_3TX	-	-	-	-	-	-	-
2412MHz_TnomVnom	Pass	-1.20	17.84	17.95	17.96	22.69	30.00
2437MHz_TnomVnom	Pass	-1.20	18.11	18.05	18.01	22.83	30.00
2462MHz_TnomVnom	Pass	-1.20	18.09	18.03	18.03	22.82	30.00
802.11g_Nss1,(6Mbps)_3TX	-	-	-	-	-	-	-
2412MHz_TnomVnom	Pass	-1.20	17.81	17.76	17.54	22.48	30.00
2437MHz_TnomVnom	Pass	-1.20	18.35	17.98	17.75	22.80	30.00
2462MHz_TnomVnom	Pass	-1.20	18.38	18.14	17.78	22.88	30.00
802.11ac_VHT20_Nss1,(MCS0)_3TX	-	-	-	-	-	-	-
2412MHz_TnomVnom	Pass	-1.20	17.74	17.76	17.56	22.46	30.00
2437MHz_TnomVnom	Pass	-1.20	18.29	17.94	17.66	22.74	30.00
2462MHz_TnomVnom	Pass	-1.20	18.27	18.11	17.78	22.83	30.00
802.11ac_VHT40_Nss1,(MCS0)_3TX	-	-	-	-	-	-	-
2422MHz_TnomVnom	Pass	-1.20	16.27	16.18	15.99	20.92	30.00
2427MHz_TnomVnom	Pass	-1.20	17.42	17.25	17.02	22.00	30.00
2437MHz_TnomVnom	Pass	-1.20	17.60	17.41	17.10	22.15	30.00
2447MHz_TnomVnom	Pass	-1.20	17.79	17.44	17.12	22.23	30.00
2452MHz_TnomVnom	Pass	-1.20	17.23	17.06	16.62	21.75	30.00

DG = Directional Gain; **Port X** = Port X output power

Summary

Mode	PD (dBm/RBW)
2.4-2.4835GHz	-
802.11b_Nss1,(1Mbps)_3TX	-2.96
802.11g_Nss1,(6Mbps)_3TX	-6.55
802.11ac VHT20_Nss1,(MCS0)_3TX	-6.74
802.11ac VHT40_Nss1,(MCS0)_3TX	-8.98

RBW=3kHz.

Result

Mode	Result	DG (dBi)	Port 1 (dBm/RBW)	Port 2 (dBm/RBW)	Port 3 (dBm/RBW)	PD (dBm/RBW)	PD Limit (dBm/RBW)
802.11b_Nss1,(1Mbps)_3TX	-	-	-	-	-	-	-
2412MHz_TnomVnom	Pass	3.57	-7.83	-7.98	-2.96	-2.96	8.00
2437MHz_TnomVnom	Pass	3.57	-9.96	-9.86	-7.96	-5.78	8.00
2462MHz_TnomVnom	Pass	3.57	-3.11	-9.20	-8.23	-3.11	8.00
802.11g_Nss1,(6Mbps)_3TX	-	-	-	-	-	-	-
2412MHz_TnomVnom	Pass	3.57	-10.36	-10.88	-10.68	-7.16	8.00
2437MHz_TnomVnom	Pass	3.57	-10.56	-9.77	-10.30	-6.75	8.00
2462MHz_TnomVnom	Pass	3.57	-8.58	-10.08	-11.21	-6.55	8.00
802.11ac VHT20_Nss1,(MCS0)_3TX	-	-	-	-	-	-	-
2412MHz_TnomVnom	Pass	3.57	-9.67	-10.43	-9.74	-7.22	8.00
2437MHz_TnomVnom	Pass	3.57	-9.31	-10.61	-9.55	-6.74	8.00
2462MHz_TnomVnom	Pass	3.57	-9.60	-9.12	-10.60	-7.07	8.00
802.11ac VHT40_Nss1,(MCS0)_3TX	-	-	-	-	-	-	-
2422MHz_TnomVnom	Pass	3.57	-13.92	-13.93	-13.75	-10.14	8.00
2437MHz_TnomVnom	Pass	3.57	-12.90	-10.95	-12.40	-8.98	8.00
2452MHz_TnomVnom	Pass	3.57	-13.13	-13.52	-11.64	-9.50	8.00

DG = Directional Gain; RBW=3kHz;


PD = trace bin-by-bin of each transmits port summing can be performed maximum power density; **Port X** = Port X power density;

802.11b_Nss1,(1Mbps)_3TX

PSD

2412MHz

21/03/2018




Sum	PD	Port 1	Port 2	Port 3
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-2.96	-2.96	-7.83	-7.98	-2.96

802.11b_Nss1,(1Mbps)_3TX

PSD

2437MHz

21/03/2018




Sum	PD	Port 1	Port 2	Port 3
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-5.78	-5.78	-9.96	-9.86	-7.96

802.11b_Nss1,(1Mbps)_3TX

PSD

2462MHz

21/03/2018




Sum	PD	Port 1	Port 2	Port 3
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-3.11	-3.11	-3.11	-9.20	-8.23

802.11g_Nss1,(6Mbps)_3TX

PSD

2412MHz

21/03/2018




802.11g_Nss1,(6Mbps)_3TX

PSD

2437MHz

21/03/2018




802.11g_Nss1,(6Mbps)_3TX

PSD

2462MHz

21/03/2018




802.11ac VHT20_Nss1,(MCS0)_3TX

PSD

2412MHz

21/03/2018




802.11ac VHT20_Nss1,(MCS0)_3TX

PSD

2437MHz

21/03/2018




802.11ac VHT20_Nss1,(MCS0)_3TX

PSD

2462MHz

21/03/2018




802.11ac VHT40_Nss1,(MCS0)_3TX

2422MHz

PSD

21/03/2018




802.11ac VHT40_Nss1,(MCS0)_3TX

2437MHz

PSD

21/03/2018




802.11ac VHT40_Nss1,(MCS0)_3TX

2452MHz

PSD

21/03/2018



Summary

Mode	Result	Ref (Hz)	Ref (dBm)	Limit (dBm)	Freq (Hz)	Level (dBm)	Freq (Hz)	Level (dBm)	Freq (Hz)	Level (dBm)	Freq (Hz)	Level (dBm)	Port
2.4-2.4835GHz	-	-	-	-	-	-	-	-	-	-	-	-	-
802.11b_Nss1,(1Mbps)_3TX	Pass	2.435404G	7.46	-22.54	1.61906G	-59.87	2.39752G	-37.44	2.50814G	-56.53	6.749082G	-54.56	1
802.11g_Nss1,(6Mbps)_3TX	Pass	2.465798G	6.86	-23.14	2.305245G	-59.47	2.39984G	-24.83	2.50102G	-57.09	6.976657G	-52.40	2
802.11ac VHT20_Nss1,(MCS0)_3TX	Pass	2.464462G	7.31	-22.69	2.30175G	-60.52	2.39992G	-24.55	2.4959G	-56.68	6.937323G	-52.90	2
802.11ac VHT40_Nss1,(MCS0)_3TX	Pass	2.432064G	3.93	-26.07	2.309695G	-59.41	2.39888G	-28.17	2.48622G	-55.84	6.949836G	-53.47	1

Result

Mode	Result	Ref (Hz)	Ref (dBm)	Limit (dBm)	Freq (Hz)	Level (dBm)	Freq (Hz)	Level (dBm)	Freq (Hz)	Level (dBm)	Freq (Hz)	Level (dBm)	Port
802.11b_Nss1,(1Mbps)_3TX	-	-	-	-	-	-	-	-	-	-	-	-	-
2412MHz_TnomVnom	Pass	2.435404G	7.46	-22.54	1.61906G	-59.87	2.39752G	-37.44	2.50814G	-56.53	6.749082G	-54.56	1
2412MHz_TnomVnom	Pass	2.435404G	7.46	-22.54	2.30408G	-59.60	2.39752G	-39.26	2.49894G	-56.52	6.914846G	-53.42	2
2412MHz_TnomVnom	Pass	2.435404G	7.46	-22.54	2.116515G	-59.20	2.39752G	-40.84	2.51214G	-56.30	6.985085G	-53.66	3
2437MHz_TnomVnom	Pass	2.435404G	7.46	-22.54	2.302915G	-59.24	2.39264G	-56.71	2.48974G	-55.78	6.979466G	-53.75	1
2437MHz_TnomVnom	Pass	2.435404G	7.46	-22.54	2.300585G	-58.71	2.39928G	-54.74	2.49302G	-56.22	6.406315G	-54.05	2
2437MHz_TnomVnom	Pass	2.435404G	7.46	-22.54	2.14331G	-59.79	2.39336G	-54.88	2.5027G	-55.63	6.940132G	-54.19	3
2462MHz_TnomVnom	Pass	2.435404G	7.46	-22.54	2.30408G	-59.38	2.3936G	-56.42	2.48374G	-52.72	6.926084G	-53.17	1
2462MHz_TnomVnom	Pass	2.435404G	7.46	-22.54	2.302915G	-60.48	2.39336G	-54.99	2.48358G	-53.44	6.931704G	-53.83	2
2462MHz_TnomVnom	Pass	2.435404G	7.46	-22.54	2.30408G	-59.40	2.39496G	-54.97	2.48414G	-53.41	6.95699G	-52.74	3
802.11g_Nss1,(6Mbps)_3TX	-	-	-	-	-	-	-	-	-	-	-	-	-
2412MHz_TnomVnom	Pass	2.465798G	6.86	-23.14	2.30874G	-57.91	2.39984G	-24.99	2.51758G	-54.52	6.858655G	-54.25	1
2412MHz_TnomVnom	Pass	2.465798G	6.86	-23.14	2.305245G	-59.47	2.39984G	-24.83	2.50102G	-57.09	6.976657G	-52.40	2
2412MHz_TnomVnom	Pass	2.465798G	6.86	-23.14	1.85905G	-59.38	2.39976G	-25.62	2.51486G	-56.22	6.867084G	-53.73	3
2437MHz_TnomVnom	Pass	2.465798G	6.86	-23.14	2.30641G	-57.67	2.39976G	-52.53	2.48982G	-53.77	6.218075G	-52.76	1
2437MHz_TnomVnom	Pass	2.465798G	6.86	-23.14	2.30175G	-58.91	2.39944G	-53.45	2.48766G	-54.75	6.386648G	-53.66	2
2437MHz_TnomVnom	Pass	2.465798G	6.86	-23.14	2.305245G	-59.06	2.3996G	-52.99	2.50406G	-55.36	6.779987G	-53.54	3
2462MHz_TnomVnom	Pass	2.465798G	6.86	-23.14	2.30874G	-58.08	2.39824G	-55.78	2.48382G	-37.10	6.779987G	-52.87	1
2462MHz_TnomVnom	Pass	2.465798G	6.86	-23.14	2.30641G	-59.05	2.39448G	-53.31	2.48382G	-38.51	6.434411G	-53.65	2
2462MHz_TnomVnom	Pass	2.465798G	6.86	-23.14	2.302915G	-59.02	2.39416G	-55.79	2.48382G	-41.84	6.962609G	-53.71	3
802.11ac VHT20_Nss1,(MCS0)_3TX	-	-	-	-	-	-	-	-	-	-	-	-	-
2412MHz_TnomVnom	Pass	2.464462G	7.31	-22.69	2.30175G	-57.87	2.39952G	-25.37	2.50246G	-55.09	6.749082G	-53.55	1
2412MHz_TnomVnom	Pass	2.464462G	7.31	-22.69	2.30175G	-60.52	2.39992G	-24.55	2.4959G	-56.68	6.937323G	-52.90	2
2412MHz_TnomVnom	Pass	2.464462G	7.31	-22.69	2.30408G	-59.65	2.39952G	-26.00	2.49238G	-55.68	6.973847G	-52.65	3
2437MHz_TnomVnom	Pass	2.464462G	7.31	-22.69	2.300585G	-57.38	2.39992G	-50.57	2.48446G	-53.72	6.779987G	-52.56	1
2437MHz_TnomVnom	Pass	2.464462G	7.31	-22.69	2.30641G	-60.15	2.39984G	-52.17	2.48798G	-55.77	5.754497G	-52.38	2
2437MHz_TnomVnom	Pass	2.464462G	7.31	-22.69	2.151465G	-59.87	2.3964G	-53.08	2.52166G	-55.62	6.996324G	-54.29	3
2462MHz_TnomVnom	Pass	2.464462G	7.31	-22.69	2.300585G	-57.43	2.39472G	-54.58	2.48478G	-37.22	6.993514G	-53.65	1
2462MHz_TnomVnom	Pass	2.464462G	7.31	-22.69	2.300585G	-58.16	2.39808G	-53.34	2.48382G	-38.04	5.599971G	-53.57	2
2462MHz_TnomVnom	Pass	2.464462G	7.31	-22.69	2.30641G	-58.39	2.39872G	-55.28	2.48358G	-41.73	6.976657G	-53.21	3
802.11ac VHT40_Nss1,(MCS0)_3TX	-	-	-	-	-	-	-	-	-	-	-	-	-
2422MHz_TnomVnom	Pass	2.432064G	3.93	-26.07	2.309695G	-59.41	2.39888G	-28.17	2.48622G	-55.84	6.949836G	-53.47	1
2422MHz_TnomVnom	Pass	2.432064G	3.93	-26.07	2.160845G	-60.23	2.39888G	-30.19	2.48382G	-55.93	6.994709G	-54.27	2
2422MHz_TnomVnom	Pass	2.432064G	3.93	-26.07	2.17115G	-59.77	2.39936G	-29.71	2.51438G	-55.82	6.983491G	-52.60	3
2427MHz_TnomVnom													
2437MHz_TnomVnom	Pass	2.432064G	3.93	-26.07	2.307405G	-57.14	2.39952G	-35.36	2.48574G	-42.83	6.991904G	-52.72	1
2437MHz_TnomVnom	Pass	2.432064G	3.93	-26.07	2.30855G	-58.88	2.39824G	-38.49	2.48414G	-45.38	6.9891G	-53.87	2
2437MHz_TnomVnom	Pass	2.432064G	3.93	-26.07	2.025735G	-59.99	2.39984G	-39.14	2.48382G	-43.96	6.924595G	-53.61	3
2447MHz_TnomVnom													



CSE Non-restricted Band Result

Appendix E





Mode	Result	Ref (Hz)	Ref (dBm)	Limit (dBm)	Freq (Hz)	Level (dBm)	Freq (Hz)	Level (dBm)	Freq (Hz)	Level (dBm)	Freq (Hz)	Level (dBm)	Port
2452MHz_TnomVnom	Pass	2.432064G	3.93	-26.07	2.305115G	-58.62	2.39952G	-47.29	2.48382G	-34.31	6.397337G	-52.81	1
2452MHz_TnomVnom	Pass	2.432064G	3.93	-26.07	2.30855G	-60.35	2.3968G	-48.89	2.48446G	-36.32	6.986295G	-53.83	2
2452MHz_TnomVnom	Pass	2.432064G	3.93	-26.07	2.14825G	-59.67	2.3968G	-49.35	2.48382G	-34.68	6.994709G	-52.79	3

802.11b_Nss1,(1Mbps)_3TX

CSE NdB

2412MHz

21/03/2018







Ref(Hz)	Ref(dBm)	Limit(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Port
2.435404G	7.46	-22.54	1.61906G	-59.87	2.39752G	-37.44	2.50814G	-56.53	6.749082G	-54.56	1
2.435404G	7.46	-22.54	2.30408G	-59.60	2.39752G	-39.26	2.49894G	-56.52	6.914846G	-53.42	2
2.435404G	7.46	-22.54	2.116515G	-59.20	2.39752G	-40.84	2.51214G	-56.30	6.985085G	-53.66	3

802.11b_Nss1,(1Mbps)_3TX

CSE NdB

2437MHz

21/03/2018







Ref(Hz)	Ref(dBm)	Limit(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Port
2.435404G	7.46	-22.54	2.302915G	-59.24	2.39264G	-56.71	2.48974G	-55.78	6.979466G	-53.75	1
2.435404G	7.46	-22.54	2.300585G	-58.71	2.39928G	-54.74	2.49302G	-56.22	6.406315G	-54.05	2
2.435404G	7.46	-22.54	2.14331G	-59.79	2.39336G	-54.88	2.5027G	-55.63	6.940132G	-54.19	3

802.11b_Nss1,(1Mbps)_3TX

CSE NdB

2462MHz

21/03/2018





Ref(Hz)	Ref(dBm)	Limit(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Port
2.435404G	7.46	-22.54	2.30408G	-59.38	2.3936G	-56.42	2.48374G	-52.72	6.926084G	-53.17	1
2.435404G	7.46	-22.54	2.302915G	-60.48	2.39336G	-54.99	2.48358G	-53.44	6.931704G	-53.83	2
2.435404G	7.46	-22.54	2.30408G	-59.40	2.39496G	-54.97	2.48414G	-53.41	6.95699G	-52.74	3

802.11g_Nss1,(6Mbps)_3TX

CSE NdB

2412MHz

21/03/2018



Port 1
Port 2
Port 3

RBW VBW
100kHz 300kHz
Detector Type
Peak



Ref(Hz)	Ref(dBm)	Limit(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Port
2.465798G	6.86	-23.14	2.30874G	-57.91	2.39984G	-24.99	2.51758G	-54.52	6.858655G	-54.25	1
2.465798G	6.86	-23.14	2.305245G	-59.47	2.39984G	-24.83	2.50102G	-57.09	6.976657G	-52.40	2
2.465798G	6.86	-23.14	1.85905G	-59.38	2.39976G	-25.62	2.51486G	-56.22	6.867084G	-53.73	3

802.11g_Nss1,(6Mbps)_3TX

CSE NdB

2437MHz

21/03/2018



Port 1
Port 2
Port 3

RBW VBW
100kHz 300kHz
Detector Type
Peak



Ref(Hz)	Ref(dBm)	Limit(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Port
2.465798G	6.86	-23.14	2.30641G	-57.67	2.39976G	-52.53	2.48982G	-53.77	6.218075G	-52.76	1
2.465798G	6.86	-23.14	2.30175G	-58.91	2.39944G	-53.45	2.48766G	-54.75	6.386648G	-53.66	2
2.465798G	6.86	-23.14	2.305245G	-59.06	2.3996G	-52.99	2.50406G	-55.36	6.779987G	-53.54	3

802.11g_Nss1,(6Mbps)_3TX

CSE NdB

2462MHz

21/03/2018



Port 1
Port 2
Port 3

RBW VBW
100kHz 300kHz
Detector Type
Peak




Ref(Hz)	Ref(dBm)	Limit(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Port
2.465798G	6.86	-23.14	2.30874G	-58.08	2.39824G	-55.78	2.48382G	-37.10	6.779987G	-52.87	1
2.465798G	6.86	-23.14	2.30641G	-59.05	2.39448G	-53.31	2.48382G	-38.51	6.434411G	-53.65	2
2.465798G	6.86	-23.14	2.302915G	-59.02	2.39416G	-55.79	2.48382G	-41.84	6.962609G	-53.71	3

802.11ac VHT20_Nss1,(MCS0)_3TX

CSE NdB

2412MHz

21/03/2018



RBW VBW
100kHz 300kHz
Detector Type
Peak




Ref(Hz)	Ref(dBm)	Limit(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Port
2.464462G	7.31	-22.69	2.30175G	-57.87	2.39952G	-25.37	2.50246G	-55.09	6.749082G	-53.55	1
2.464462G	7.31	-22.69	2.30175G	-60.52	2.39992G	-24.55	2.4959G	-56.68	6.937323G	-52.90	2
2.464462G	7.31	-22.69	2.30408G	-59.65	2.39952G	-26.00	2.49238G	-55.68	6.973847G	-52.65	3

802.11ac VHT20_Nss1,(MCS0)_3TX

CSE NdB

2437MHz

21/03/2018



RBW VBW
100kHz 300kHz
Detector Type
Peak




Ref(Hz)	Ref(dBm)	Limit(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Port
2.464462G	7.31	-22.69	2.300585G	-57.38	2.39992G	-50.57	2.48446G	-53.72	6.779987G	-52.56	1
2.464462G	7.31	-22.69	2.30641G	-60.15	2.39984G	-52.17	2.48798G	-55.77	5.754497G	-52.38	2
2.464462G	7.31	-22.69	2.151465G	-59.87	2.3964G	-53.08	2.52166G	-55.62	6.996324G	-54.29	3

802.11ac VHT20_Nss1,(MCS0)_3TX

CSE NdB

2462MHz

21/03/2018



RBW VBW
100kHz 300kHz
Detector Type
Peak




Ref(Hz)	Ref(dBm)	Limit(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Port
2.464462G	7.31	-22.69	2.300585G	-57.43	2.39472G	-54.58	2.48478G	-37.22	6.993514G	-53.65	1
2.464462G	7.31	-22.69	2.300585G	-58.16	2.39808G	-53.34	2.48382G	-38.04	5.599971G	-53.57	2
2.464462G	7.31	-22.69	2.30641G	-58.39	2.39872G	-55.28	2.48358G	-41.73	6.976657G	-53.21	3

802.11ac VHT40_Nss1,(MCS0)_3TX

CSE NdB

2422MHz

21/03/2018



RBW VBW
100kHz 300kHz
Detector Type
Peak




Ref(Hz)	Ref(dBm)	Limit(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Port
2.432064G	3.93	-26.07	2.309695G	-59.41	2.39888G	-28.17	2.48622G	-55.84	6.949836G	-53.47	1
2.432064G	3.93	-26.07	2.160845G	-60.23	2.39888G	-30.19	2.48382G	-55.93	6.994709G	-54.27	2
2.432064G	3.93	-26.07	2.17115G	-59.77	2.39936G	-29.71	2.51438G	-55.82	6.983491G	-52.60	3

802.11ac VHT40_Nss1,(MCS0)_3TX

CSE NdB

2437MHz

21/03/2018



RBW VBW
100kHz 300kHz
Detector Type
Peak




Ref(Hz)	Ref(dBm)	Limit(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Port
2.432064G	3.93	-26.07	2.307405G	-57.14	2.39952G	-35.36	2.48574G	-42.83	6.991904G	-52.72	1
2.432064G	3.93	-26.07	2.30855G	-58.88	2.39824G	-38.49	2.48414G	-45.38	6.9891G	-53.87	2
2.432064G	3.93	-26.07	2.025735G	-59.99	2.39984G	-39.14	2.48382G	-43.96	6.924595G	-53.61	3

802.11ac VHT40_Nss1,(MCS0)_3TX

CSE NdB

2452MHz

21/03/2018



RBW VBW
100kHz 300kHz
Detector Type
Peak

Ref(Hz)	Ref(dBm)	Limit(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Port
2.432064G	3.93	-26.07	2.305115G	-58.62	2.39952G	-47.29	2.48382G	-34.31	6.397337G	-52.81	1
2.432064G	3.93	-26.07	2.30855G	-60.35	2.3968G	-48.89	2.48446G	-36.32	6.986295G	-53.83	2
2.432064G	3.93	-26.07	2.14825G	-59.67	2.3968G	-49.35	2.48382G	-34.68	6.994709G	-52.79	3

**Summary**

Mode	Result	Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
2.4-2.4835GHz	-	-	-	-	-	-	-	-	-	-	-	-
802.11ac VHT40_Nss1,(MCS0)_3TX	Pass	PK	455.956522M	42.77	46.00	-3.23	-2.84	3	Vertical	0	1.00	-


Result

Mode	Result	Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
802.11ac VHT40_Nss1,(MCS0)_3TX	-	-	-	-	-	-	-	-	-	-	-	-
2437MHz	Pass	PK	30M	25.47	40.00	-14.53	-4.45	3	Horizontal	360	1.00	-
2437MHz	Pass	PK	238.057971M	40.25	46.00	-5.75	-8.33	3	Horizontal	360	1.00	-
2437MHz	Pass	PK	288.666667M	37.03	46.00	-8.97	-6.04	3	Horizontal	360	1.00	-
2437MHz	Pass	PK	439.086957M	41.56	46.00	-4.44	-3.08	3	Horizontal	360	1.00	-
2437MHz	Pass	PK	791.942029M	42.10	46.00	-3.90	1.27	3	Horizontal	360	1.00	-
2437MHz	Pass	PK	999.999M	48.25	54.00	-5.75	4.45	3	Horizontal	360	1.00	-
2437MHz	Pass	PK	30M	30.43	40.00	-9.57	-4.45	3	Vertical	0	1.00	-
2437MHz	Pass	PK	198.695652M	22.62	43.50	-20.88	-10.68	3	Vertical	0	1.00	-
2437MHz	Pass	PK	238.057971M	30.97	46.00	-15.03	-8.33	3	Vertical	0	1.00	-
2437MHz	Pass	PK	455.956522M	42.77	46.00	-3.23	-2.84	3	Vertical	0	1.00	-
2437MHz	Pass	PK	999.999M	48.84	54.00	-5.16	4.45	3	Vertical	0	1.00	-
2437MHz	Pass	QP	380.043478M	42.06	46.00	-3.94	-4.44	3	Vertical	10	1.43	-

802.11ac VHT40_Nss1,(MCS0)_3TX

2437MHz_adapter

03/04/2018




Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments	Raw (dBuV)	AF (dB)	CL (dB)	PA (dB)
PK	30M	30.43	40.00	-9.57	-4.45	3	Vertical	0	1.00	-	34.88	23.11	0.29	27.85
PK	198.695652M	22.62	43.50	-20.88	-10.68	3	Vertical	0	1.00	-	33.30	14.47	2.30	27.45
PK	238.057971M	30.97	46.00	-15.03	-8.33	3	Vertical	0	1.00	-	39.30	16.35	2.66	27.35
PK	455.956522M	42.77	46.00	-3.23	-2.84	3	Vertical	0	1.00	-	45.61	22.18	3.24	28.26
PK	999.999M	48.84	54.00	-5.16	4.45	3	Vertical	0	1.00	-	44.39	26.65	5.04	27.24
QP	380.043478M	42.06	46.00	-3.94	-4.44	3	Vertical	10	1.43	-	46.50	20.22	3.15	27.81

802.11ac VHT40_Nss1,(MCS0)_3TX

2437MHz_adapter

03/04/2018



Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments	Raw (dBuV)	AF (dB)	CL (dB)	PA (dB)
PK	30M	25.47	40.00	-14.53	-4.45	3	Horizontal	360	1.00	-	29.92	23.11	0.29	27.85
PK	238.057971M	40.25	46.00	-5.75	-8.33	3	Horizontal	360	1.00	-	48.58	16.35	2.66	27.35
PK	288.666667M	37.03	46.00	-8.97	-6.04	3	Horizontal	360	1.00	-	43.07	18.24	2.95	27.22
PK	439.086957M	41.56	46.00	-4.44	-3.08	3	Horizontal	360	1.00	-	44.64	21.86	3.22	28.17
PK	791.942029M	42.10	46.00	-3.90	1.27	3	Horizontal	360	1.00	-	40.83	25.21	4.16	28.09
PK	999.999M	48.25	54.00	-5.75	4.45	3	Horizontal	360	1.00	-	43.80	26.65	5.04	27.24

Summary

Mode	Result	Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
2.4-2.4835GHz	-	-	-	-	-	-	-	-	-	-	-	-
802.11b_Nss1,(1Mbps)_3TX	Pass	AV	7.31172G	53.57	54.00	-0.43	24.80	3	Vertical	351	1.50	-
802.11g_Nss1,(6Mbps)_3TX	Pass	AV	2.389998G	53.43	54.00	-0.57	30.57	3	Vertical	87	1.74	-
802.11ac VHT20_Nss1,(MCS0)_3TX	Pass	AV	2.4846G	53.60	54.00	-0.40	30.92	3	Horizontal	29	2.87	-
802.11ac VHT40_Nss1,(MCS0)_3TX	Pass	AV	2.4848G	53.88	54.00	-0.12	30.92	3	Vertical	30	2.09	-

Result

Mode	Result	Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
802.11b_Nss1,(1Mbps)_3TX	-	-	-	-	-	-	-	-	-	-	-	-
2412MHz	Pass	AV	2.3894G	45.52	54.00	-8.48	30.57	3	Horizontal	14	1.84	-
2412MHz	Pass	AV	2.4112G	101.64	Inf	-Inf	30.65	3	Horizontal	14	1.84	-
2412MHz	Pass	PK	2.374G	55.90	74.00	-18.10	30.52	3	Horizontal	14	1.84	-
2412MHz	Pass	PK	2.4112G	103.34	Inf	-Inf	30.65	3	Horizontal	14	1.84	-
2412MHz	Pass	AV	2.3898G	45.07	54.00	-8.93	30.57	3	Vertical	88	1.48	-
2412MHz	Pass	AV	2.411G	99.39	Inf	-Inf	30.65	3	Vertical	88	1.48	-
2412MHz	Pass	PK	2.3752G	55.98	74.00	-18.02	30.52	3	Vertical	88	1.48	-
2412MHz	Pass	PK	2.4112G	101.19	Inf	-Inf	30.65	3	Vertical	88	1.48	-
2412MHz	Pass	AV	4.82394G	34.25	54.00	-19.75	3.13	3	Horizontal	340	1.50	-
2412MHz	Pass	PK	4.82388G	43.99	74.00	-30.01	3.13	3	Horizontal	340	1.50	-
2412MHz	Pass	AV	4.824G	36.00	54.00	-18.00	3.13	3	Vertical	345	1.90	-
2412MHz	Pass	PK	4.82382G	45.17	74.00	-28.83	3.13	3	Vertical	345	1.90	-
2437MHz	Pass	AV	2.389G	44.82	54.00	-9.18	30.57	3	Horizontal	24	1.98	-
2437MHz	Pass	AV	2.4334G	99.75	Inf	-Inf	30.73	3	Horizontal	24	1.98	-
2437MHz	Pass	AV	2.4982G	45.64	54.00	-8.36	30.96	3	Horizontal	24	1.98	-
2437MHz	Pass	PK	2.353G	55.76	74.00	-18.24	30.45	3	Horizontal	24	1.98	-
2437MHz	Pass	PK	2.433G	101.35	Inf	-Inf	30.73	3	Horizontal	24	1.98	-
2437MHz	Pass	PK	2.4942G	56.54	74.00	-17.46	30.95	3	Horizontal	24	1.98	-
2437MHz	Pass	AV	2.3894G	44.82	54.00	-9.18	30.57	3	Vertical	1	2.98	-
2437MHz	Pass	AV	2.435G	99.44	Inf	-Inf	30.74	3	Vertical	1	2.98	-
2437MHz	Pass	AV	2.4914G	45.56	54.00	-8.44	30.94	3	Vertical	1	2.98	-
2437MHz	Pass	PK	2.3898G	55.72	74.00	-18.28	30.57	3	Vertical	1	2.98	-
2437MHz	Pass	PK	2.4342G	100.95	Inf	-Inf	30.73	3	Vertical	1	2.98	-
2437MHz	Pass	PK	2.483502G	56.59	74.00	-17.41	30.91	3	Vertical	1	2.98	-
2437MHz	Pass	AV	7.30938G	51.74	54.00	-2.26	24.79	3	Horizontal	80	1.26	-
2437MHz	Pass	PK	7.32342G	65.34	74.00	-8.66	24.86	3	Horizontal	80	1.26	-
2437MHz	Pass	AV	7.31172G	53.57	54.00	-0.43	24.80	3	Vertical	351	1.50	-
2437MHz	Pass	PK	7.31202G	66.10	74.00	-7.90	24.80	3	Vertical	351	1.50	-
2462MHz	Pass	AV	2.4648G	100.01	Inf	-Inf	30.84	3	Horizontal	26	1.87	-
2462MHz	Pass	AV	2.4936G	45.63	54.00	-8.37	30.94	3	Horizontal	26	1.87	-
2462MHz	Pass	PK	2.4648G	102.29	Inf	-Inf	30.84	3	Horizontal	26	1.87	-
2462MHz	Pass	PK	2.486G	56.40	74.00	-17.60	30.92	3	Horizontal	26	1.87	-
2462MHz	Pass	AV	2.4602G	96.55	Inf	-Inf	30.83	3	Vertical	74	1.50	-
2462MHz	Pass	AV	2.499998G	45.61	54.00	-8.39	30.97	3	Vertical	74	1.50	-
2462MHz	Pass	PK	2.46G	97.84	Inf	-Inf	30.83	3	Vertical	74	1.50	-
2462MHz	Pass	PK	2.4918G	55.61	74.00	-18.39	30.94	3	Vertical	74	1.50	-
2462MHz	Pass	AV	7.39476G	37.30	54.00	-16.70	9.62	3	Horizontal	53	1.97	-
2462MHz	Pass	PK	7.38234G	51.12	74.00	-22.88	9.56	3	Horizontal	53	1.97	-
2462MHz	Pass	AV	7.38822G	39.82	54.00	-14.18	9.59	3	Vertical	356	2.63	-
2462MHz	Pass	PK	7.38402G	51.69	74.00	-22.31	9.57	3	Vertical	356	2.63	-
802.11g_Nss1,(6Mbps)_3TX	-	-	-	-	-	-	-	-	-	-	-	-
2412MHz	Pass	AV	2.389998G	52.32	54.00	-1.68	30.57	3	Horizontal	22	2.01	-
2412MHz	Pass	AV	2.41G	99.34	Inf	-Inf	30.65	3	Horizontal	22	2.01	-
2412MHz	Pass	PK	2.3894G	63.26	74.00	-10.74	30.57	3	Horizontal	22	2.01	-
2412MHz	Pass	PK	2.41G	106.26	Inf	-Inf	30.65	3	Horizontal	22	2.01	-
2412MHz	Pass	AV	2.389998G	53.43	54.00	-0.57	30.57	3	Vertical	87	1.74	-
2412MHz	Pass	AV	2.4104G	97.49	Inf	-Inf	30.65	3	Vertical	87	1.74	-

Mode	Result	Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
2412MHz	Pass	PK	2.3898G	63.96	74.00	-10.04	30.57	3	Vertical	87	1.74	-
2412MHz	Pass	PK	2.4102G	104.01	Inf	-Inf	30.65	3	Vertical	87	1.74	-
2412MHz	Pass	AV	4.82112G	31.15	54.00	-22.85	3.13	3	Horizontal	50	2.95	-
2412MHz	Pass	PK	4.83012G	44.63	74.00	-29.37	3.15	3	Horizontal	50	2.95	-
2412MHz	Pass	AV	4.82106G	31.24	54.00	-22.76	3.13	3	Vertical	11	1.50	-
2412MHz	Pass	PK	4.81254G	44.87	74.00	-29.13	3.11	3	Vertical	11	1.50	-
2437MHz	Pass	AV	2.3762G	45.51	54.00	-8.49	30.52	3	Horizontal	41	2.17	-
2437MHz	Pass	AV	2.4338G	97.62	Inf	-Inf	30.73	3	Horizontal	41	2.17	-
2437MHz	Pass	AV	2.4998G	46.34	54.00	-7.66	30.97	3	Horizontal	41	2.17	-
2437MHz	Pass	PK	2.3894G	55.79	74.00	-18.21	30.57	3	Horizontal	41	2.17	-
2437MHz	Pass	PK	2.4338G	105.07	Inf	-Inf	30.73	3	Horizontal	41	2.17	-
2437MHz	Pass	PK	2.487G	56.15	74.00	-17.85	30.92	3	Horizontal	41	2.17	-
2437MHz	Pass	AV	2.3674G	45.51	54.00	-8.49	30.50	3	Vertical	0	1.02	-
2437MHz	Pass	AV	2.4378G	96.54	Inf	-Inf	30.75	3	Vertical	0	1.02	-
2437MHz	Pass	AV	2.487G	46.18	54.00	-7.82	30.92	3	Vertical	0	1.02	-
2437MHz	Pass	PK	2.3818G	55.16	74.00	-18.84	30.55	3	Vertical	0	1.02	-
2437MHz	Pass	PK	2.4374G	103.30	Inf	-Inf	30.74	3	Vertical	0	1.02	-
2437MHz	Pass	PK	2.4934G	55.52	74.00	-18.48	30.94	3	Vertical	0	1.02	-
2437MHz	Pass	AV	7.3104G	37.28	54.00	-16.72	9.25	3	Horizontal	277	1.50	-
2437MHz	Pass	PK	7.31862G	50.47	74.00	-23.53	9.29	3	Horizontal	277	1.50	-
2437MHz	Pass	AV	7.31574G	38.49	54.00	-15.51	9.28	3	Vertical	356	2.68	-
2437MHz	Pass	PK	7.3056G	51.55	74.00	-22.45	9.23	3	Vertical	356	2.68	-
2462MHz	Pass	AV	2.46G	98.07	Inf	-Inf	30.83	3	Horizontal	30	1.67	-
2462MHz	Pass	AV	2.489G	48.80	54.00	-5.20	30.93	3	Horizontal	30	1.67	-
2462MHz	Pass	PK	2.4604G	104.62	Inf	-Inf	30.83	3	Horizontal	30	1.67	-
2462MHz	Pass	PK	2.4896G	61.07	74.00	-12.93	30.93	3	Horizontal	30	1.67	-
2462MHz	Pass	AV	2.4596G	98.31	Inf	-Inf	30.82	3	Vertical	30	2.23	-
2462MHz	Pass	AV	2.4896G	48.66	54.00	-5.34	30.93	3	Vertical	30	2.23	-
2462MHz	Pass	PK	2.4596G	105.15	Inf	-Inf	30.82	3	Vertical	30	2.23	-
2462MHz	Pass	PK	2.489G	60.49	74.00	-13.51	30.93	3	Vertical	30	2.23	-
2462MHz	Pass	AV	7.38432G	38.61	54.00	-15.39	9.57	3	Horizontal	287	1.50	-
2462MHz	Pass	PK	7.3959G	51.78	74.00	-22.22	9.62	3	Horizontal	287	1.50	-
2462MHz	Pass	AV	7.38996G	39.92	54.00	-14.08	9.60	3	Vertical	357	2.52	-
2462MHz	Pass	PK	7.38042G	52.95	74.00	-21.05	9.56	3	Vertical	357	2.52	-
802.11ac VHT20_Nss1,(MCS0)_3TX	-	-	-	-	-	-	-	-	-	-	-	-
2412MHz	Pass	AV	2.389998G	52.68	54.00	-1.32	30.57	3	Horizontal	25	2.28	-
2412MHz	Pass	AV	2.4082G	99.81	Inf	-Inf	30.64	3	Horizontal	25	2.28	-
2412MHz	Pass	PK	2.3898G	63.64	74.00	-10.36	30.57	3	Horizontal	25	2.28	-
2412MHz	Pass	PK	2.4082G	107.63	Inf	-Inf	30.64	3	Horizontal	25	2.28	-
2412MHz	Pass	AV	2.389998G	53.41	54.00	-0.59	30.57	3	Vertical	89	1.73	-
2412MHz	Pass	AV	2.4086G	97.56	Inf	-Inf	30.64	3	Vertical	89	1.73	-
2412MHz	Pass	PK	2.3896G	65.24	74.00	-8.76	30.57	3	Vertical	89	1.73	-
2412MHz	Pass	PK	2.4082G	105.27	Inf	-Inf	30.64	3	Vertical	89	1.73	-
2412MHz	Pass	AV	4.80936G	30.10	54.00	-23.90	3.10	3	Horizontal	250	1.50	-
2412MHz	Pass	PK	4.81704G	43.82	74.00	-30.18	3.12	3	Horizontal	250	1.50	-
2412MHz	Pass	AV	4.82616G	30.65	54.00	-23.35	3.14	3	Vertical	339	1.49	-
2412MHz	Pass	PK	4.8093G	43.58	74.00	-30.42	3.10	3	Vertical	339	1.49	-
2437MHz	Pass	AV	2.3478G	45.54	54.00	-8.46	30.42	3	Horizontal	44	1.50	-
2437MHz	Pass	AV	2.4442G	98.28	Inf	-Inf	30.77	3	Horizontal	44	1.50	-

Mode	Result	Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
2437MHz	Pass	AV	2.4838G	46.40	54.00	-7.60	30.91	3	Horizontal	44	1.50	-
2437MHz	Pass	PK	2.3538G	55.94	74.00	-18.06	30.45	3	Horizontal	44	1.50	-
2437MHz	Pass	PK	2.4434G	105.17	Inf	-Inf	30.77	3	Horizontal	44	1.50	-
2437MHz	Pass	PK	2.4998G	56.59	74.00	-17.41	30.97	3	Horizontal	44	1.50	-
2437MHz	Pass	AV	2.3706G	45.48	54.00	-8.52	30.51	3	Vertical	30	2.25	-
2437MHz	Pass	AV	2.4418G	97.53	Inf	-Inf	30.76	3	Vertical	30	2.25	-
2437MHz	Pass	AV	2.4922G	46.02	54.00	-7.98	30.94	3	Vertical	30	2.25	-
2437MHz	Pass	PK	2.3614G	55.57	74.00	-18.43	30.47	3	Vertical	30	2.25	-
2437MHz	Pass	PK	2.4422G	104.49	Inf	-Inf	30.76	3	Vertical	30	2.25	-
2437MHz	Pass	PK	2.4874G	55.92	74.00	-18.08	30.92	3	Vertical	30	2.25	-
2437MHz	Pass	AV	7.32528G	37.05	54.00	-16.95	9.32	3	Horizontal	11	1.50	-
2437MHz	Pass	PK	7.32414G	49.93	74.00	-24.07	9.31	3	Horizontal	11	1.50	-
2437MHz	Pass	AV	7.31838G	37.39	54.00	-16.61	9.29	3	Vertical	356	1.46	-
2437MHz	Pass	PK	7.29936G	50.98	74.00	-23.02	9.21	3	Vertical	356	1.46	-
2462MHz	Pass	AV	2.4682G	98.73	Inf	-Inf	30.86	3	Horizontal	29	2.87	-
2462MHz	Pass	AV	2.4846G	53.60	54.00	-0.40	30.92	3	Horizontal	29	2.87	-
2462MHz	Pass	PK	2.4684G	106.26	Inf	-Inf	30.86	3	Horizontal	29	2.87	-
2462MHz	Pass	PK	2.4844G	67.13	74.00	-6.87	30.92	3	Horizontal	29	2.87	-
2462MHz	Pass	AV	2.467G	97.95	Inf	-Inf	30.85	3	Vertical	33	2.34	-
2462MHz	Pass	AV	2.484G	53.53	54.00	-0.47	30.92	3	Vertical	33	2.34	-
2462MHz	Pass	PK	2.466G	104.99	Inf	-Inf	30.85	3	Vertical	33	2.34	-
2462MHz	Pass	PK	2.4838G	65.55	74.00	-8.45	30.91	3	Vertical	33	2.34	-
2462MHz	Pass	AV	7.3905G	40.73	54.00	-13.27	9.60	3	Horizontal	223	2.25	-
2462MHz	Pass	PK	7.3881G	54.11	74.00	-19.89	9.59	3	Horizontal	223	2.25	-
2462MHz	Pass	AV	7.38408G	40.82	54.00	-13.18	9.57	3	Vertical	333	1.96	-
2462MHz	Pass	PK	7.3872G	54.52	74.00	-19.48	9.58	3	Vertical	333	1.96	-
802.11ac VHT40_Nss1,(MCS0)_3TX	-	-	-	-	-	-	-	-	-	-	-	-
2422MHz	Pass	AV	2.389998G	53.60	54.00	-0.40	30.57	3	Horizontal	42	1.47	-
2422MHz	Pass	AV	2.4304G	94.94	Inf	-Inf	30.72	3	Horizontal	42	1.47	-
2422MHz	Pass	AV	2.4904G	46.88	54.00	-7.12	30.93	3	Horizontal	42	1.47	-
2422MHz	Pass	PK	2.389998G	63.41	74.00	-10.59	30.57	3	Horizontal	42	1.47	-
2422MHz	Pass	PK	2.43G	101.91	Inf	-Inf	30.72	3	Horizontal	42	1.47	-
2422MHz	Pass	PK	2.4896G	56.81	74.00	-17.19	30.93	3	Horizontal	42	1.47	-
2422MHz	Pass	AV	2.3888G	53.84	54.00	-0.16	30.57	3	Vertical	89	1.73	-
2422MHz	Pass	AV	2.4092G	93.20	Inf	-Inf	30.64	3	Vertical	89	1.73	-
2422MHz	Pass	AV	2.4912G	46.68	54.00	-7.32	30.94	3	Vertical	89	1.73	-
2422MHz	Pass	PK	2.3888G	64.35	74.00	-9.65	30.57	3	Vertical	89	1.73	-
2422MHz	Pass	PK	2.4088G	99.83	Inf	-Inf	30.64	3	Vertical	89	1.73	-
2422MHz	Pass	PK	2.4944G	56.14	74.00	-17.86	30.95	3	Vertical	89	1.73	-
2422MHz	Pass	AV	4.8479G	32.16	54.00	-21.84	3.19	3	Horizontal	239	1.48	-
2422MHz	Pass	PK	4.82942G	44.49	74.00	-29.51	3.14	3	Horizontal	239	1.48	-
2422MHz	Pass	AV	4.8572G	32.09	54.00	-21.91	3.21	3	Vertical	225	1.50	-
2422MHz	Pass	PK	4.82984G	44.81	74.00	-29.19	3.15	3	Vertical	225	1.50	-
2427MHz	Pass	AV	2.389G	51.07	54.00	-2.93	30.57	3	Horizontal	39	1.96	-
2427MHz	Pass	AV	2.4202G	94.30	Inf	-Inf	30.68	3	Horizontal	39	1.96	-
2427MHz	Pass	AV	2.4862G	47.03	54.00	-6.97	30.92	3	Horizontal	39	1.96	-
2427MHz	Pass	PK	2.389G	60.83	74.00	-13.17	30.57	3	Horizontal	39	1.96	-
2427MHz	Pass	PK	2.4198G	101.34	Inf	-Inf	30.68	3	Horizontal	39	1.96	-
2427MHz	Pass	PK	2.4854G	55.85	74.00	-18.15	30.92	3	Horizontal	39	1.96	-



RSE TX above 1GHz Result

Appendix F

Mode	Result	Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
2427MHz	Pass	AV	2.3894G	53.73	54.00	-0.27	30.57	3	Vertical	357	1.18	-
2427MHz	Pass	AV	2.4282G	92.99	Inf	-Inf	30.71	3	Vertical	357	1.18	-
2427MHz	Pass	AV	2.4894G	46.93	54.00	-7.07	30.93	3	Vertical	357	1.18	-
2427MHz	Pass	PK	2.3894G	62.48	74.00	-11.52	30.57	3	Vertical	357	1.18	-
2427MHz	Pass	PK	2.429G	99.18	Inf	-Inf	30.71	3	Vertical	357	1.18	-
2427MHz	Pass	PK	2.4946G	56.36	74.00	-17.64	30.95	3	Vertical	357	1.18	-
2437MHz	Pass	AV	2.3898G	48.09	54.00	-5.91	30.57	3	Horizontal	41	2.11	-
2437MHz	Pass	AV	2.4302G	94.34	Inf	-Inf	30.72	3	Horizontal	41	2.11	-
2437MHz	Pass	AV	2.4862G	48.67	54.00	-5.33	30.92	3	Horizontal	41	2.11	-
2437MHz	Pass	PK	2.3898G	57.30	74.00	-16.70	30.57	3	Horizontal	41	2.11	-
2437MHz	Pass	PK	2.4294G	100.68	Inf	-Inf	30.72	3	Horizontal	41	2.11	-
2437MHz	Pass	PK	2.4882G	58.11	74.00	-15.89	30.93	3	Horizontal	41	2.11	-
2437MHz	Pass	AV	2.387G	46.67	54.00	-7.33	30.56	3	Vertical	357	1.14	-
2437MHz	Pass	AV	2.4382G	93.36	Inf	-Inf	30.75	3	Vertical	357	1.14	-
2437MHz	Pass	AV	2.483502G	48.90	54.00	-5.10	30.91	3	Vertical	357	1.14	-
2437MHz	Pass	PK	2.3806G	55.79	74.00	-18.21	30.55	3	Vertical	357	1.14	-
2437MHz	Pass	PK	2.439G	99.64	Inf	-Inf	30.75	3	Vertical	357	1.14	-
2437MHz	Pass	PK	2.4858G	57.21	74.00	-16.79	30.92	3	Vertical	357	1.14	-
2437MHz	Pass	AV	7.3245G	38.41	54.00	-15.59	9.32	3	Horizontal	296	1.50	-
2437MHz	Pass	PK	7.31838G	50.35	74.00	-23.65	9.29	3	Horizontal	296	1.50	-
2437MHz	Pass	AV	7.3209G	39.14	54.00	-14.86	9.30	3	Vertical	359	1.83	-
2437MHz	Pass	PK	7.31598G	51.79	74.00	-22.21	9.28	3	Vertical	359	1.83	-
2447MHz	Pass	AV	2.3794G	46.12	54.00	-7.88	30.54	3	Horizontal	38	1.96	-
2447MHz	Pass	AV	2.4358G	95.82	Inf	-Inf	30.74	3	Horizontal	38	1.96	-
2447MHz	Pass	AV	2.4902G	50.62	54.00	-3.38	30.93	3	Horizontal	38	1.96	-
2447MHz	Pass	PK	2.3698G	55.88	74.00	-18.12	30.51	3	Horizontal	38	1.96	-
2447MHz	Pass	PK	2.4358G	102.27	Inf	-Inf	30.74	3	Horizontal	38	1.96	-
2447MHz	Pass	PK	2.491G	60.66	74.00	-13.34	30.93	3	Horizontal	38	1.96	-
2447MHz	Pass	AV	2.3898G	46.67	54.00	-7.33	30.57	3	Vertical	32	2.06	-
2447MHz	Pass	AV	2.4526G	93.00	Inf	-Inf	30.80	3	Vertical	32	2.06	-
2447MHz	Pass	AV	2.4898G	52.41	54.00	-1.59	30.93	3	Vertical	32	2.06	-
2447MHz	Pass	PK	2.389G	55.92	74.00	-18.08	30.57	3	Vertical	32	2.06	-
2447MHz	Pass	PK	2.4514G	99.77	Inf	-Inf	30.80	3	Vertical	32	2.06	-
2447MHz	Pass	PK	2.4922G	63.03	74.00	-10.97	30.94	3	Vertical	32	2.06	-
2452MHz	Pass	AV	2.3888G	45.46	54.00	-8.54	30.57	3	Horizontal	43	1.47	-
2452MHz	Pass	AV	2.4492G	94.46	Inf	-Inf	30.79	3	Horizontal	43	1.47	-
2452MHz	Pass	AV	2.4872G	53.53	54.00	-0.47	30.92	3	Horizontal	43	1.47	-
2452MHz	Pass	PK	2.3888G	55.48	74.00	-18.52	30.57	3	Horizontal	43	1.47	-
2452MHz	Pass	PK	2.4496G	101.29	Inf	-Inf	30.79	3	Horizontal	43	1.47	-
2452MHz	Pass	PK	2.4876G	65.54	74.00	-8.46	30.93	3	Horizontal	43	1.47	-
2452MHz	Pass	AV	2.384G	45.46	54.00	-8.54	30.56	3	Vertical	30	2.09	-
2452MHz	Pass	AV	2.4476G	93.09	Inf	-Inf	30.78	3	Vertical	30	2.09	-
2452MHz	Pass	AV	2.4848G	53.88	54.00	-0.12	30.92	3	Vertical	30	2.09	-
2452MHz	Pass	PK	2.376G	55.16	74.00	-18.84	30.52	3	Vertical	30	2.09	-
2452MHz	Pass	PK	2.448G	100.36	Inf	-Inf	30.78	3	Vertical	30	2.09	-
2452MHz	Pass	PK	2.4876G	64.09	74.00	-9.91	30.93	3	Vertical	30	2.09	-
2452MHz	Pass	AV	7.3689G	38.70	54.00	-15.30	9.51	3	Horizontal	4	1.53	-
2452MHz	Pass	PK	7.36458G	51.61	74.00	-22.39	9.49	3	Horizontal	4	1.53	-
2452MHz	Pass	AV	7.36122G	38.57	54.00	-15.43	9.47	3	Vertical	247	1.50	-



RSE TX above 1GHz Result


Appendix F

Mode	Result	Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
2452MHz	Pass	PK	7.365G	51.23	74.00	-22.77	9.49	3	Vertical	247	1.50	-

802.11b_Nss1,(1Mbps)_3TX

2412MHz_TX

19/03/2018




Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments	Raw (dBuV)	AF (dB)	CL (dB)	PA (dB)
AV	2.3898G	45.07	54.00	-8.93	30.57	3	Vertical	88	1.48	-	14.50	26.99	3.58	-
AV	2.411G	99.39	Inf	-Inf	30.65	3	Vertical	88	1.48	-	68.74	27.05	3.60	-
PK	2.3752G	55.98	74.00	-18.02	30.52	3	Vertical	88	1.48	-	25.46	26.95	3.57	-
PK	2.4112G	101.19	Inf	-Inf	30.65	3	Vertical	88	1.48	-	70.54	27.05	3.60	-

802.11b_Nss1,(1Mbps)_3TX

2412MHz_TX

19/03/2018




Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments	Raw (dBuV)	AF (dB)	CL (dB)	PA (dB)
AV	2.3894G	45.52	54.00	-8.48	30.57	3	Horizontal	14	1.84	-	14.95	26.99	3.58	-
AV	2.4112G	101.64	Inf	-Inf	30.65	3	Horizontal	14	1.84	-	70.99	27.05	3.60	-
PK	2.374G	55.90	74.00	-18.10	30.52	3	Horizontal	14	1.84	-	25.38	26.95	3.57	-
PK	2.4112G	103.34	Inf	-Inf	30.65	3	Horizontal	14	1.84	-	72.69	27.05	3.60	-

802.11b_Nss1,(1Mbps)_3TX

2412MHz_TX

20/03/2018




Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments	Raw (dBuV)	AF (dB)	CL (dB)	PA (dB)
AV	4.824G	36.00	54.00	-18.00	3.13	3	Vertical	345	1.90	-	32.87	31.28	6.43	34.59
PK	4.82382G	45.17	74.00	-28.83	3.13	3	Vertical	345	1.90	-	42.04	31.28	6.43	34.59

802.11b_Nss1,(1Mbps)_3TX

2412MHz_TX

20/03/2018




Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments	Raw (dBuV)	AF (dB)	CL (dB)	PA (dB)
AV	4.82394G	34.25	54.00	-19.75	3.13	3	Horizontal	340	1.50	-	31.12	31.28	6.43	34.59
PK	4.82388G	43.99	74.00	-30.01	3.13	3	Horizontal	340	1.50	-	40.86	31.28	6.43	34.59

802.11b_Nss1,(1Mbps)_3TX

2437MHz_TX

19/03/2018




Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments	Raw (dBuV)	AF (dB)	CL (dB)	PA (dB)
AV	2.3894G	44.82	54.00	-9.18	30.57	3	Vertical	1	2.98	-	14.25	26.99	3.58	-
AV	2.435G	99.44	Inf	-Inf	30.74	3	Vertical	1	2.98	-	68.70	27.12	3.62	-
AV	2.4914G	45.56	54.00	-8.44	30.94	3	Vertical	1	2.98	-	14.62	27.28	3.66	-
PK	2.3898G	55.72	74.00	-18.28	30.57	3	Vertical	1	2.98	-	25.15	26.99	3.58	-
PK	2.4342G	100.95	Inf	-Inf	30.73	3	Vertical	1	2.98	-	70.22	27.12	3.62	-
PK	2.483502G	56.59	74.00	-17.41	30.91	3	Vertical	1	2.98	-	25.68	27.25	3.66	-

802.11b_Nss1,(1Mbps)_3TX

2437MHz_TX

19/03/2018




Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments	Raw (dBuV)	AF (dB)	CL (dB)	PA (dB)
AV	2.389G	44.82	54.00	-9.18	30.57	3	Horizontal	24	1.98	-	14.25	26.99	3.58	-
AV	2.4334G	99.75	Inf	-Inf	30.73	3	Horizontal	24	1.98	-	69.02	27.11	3.62	-
AV	2.4982G	45.64	54.00	-8.36	30.96	3	Horizontal	24	1.98	-	14.68	27.29	3.67	-
PK	2.353G	55.76	74.00	-18.24	30.45	3	Horizontal	24	1.98	-	25.31	26.89	3.56	-
PK	2.433G	101.35	Inf	-Inf	30.73	3	Horizontal	24	1.98	-	70.62	27.11	3.62	-
PK	2.4942G	56.54	74.00	-17.46	30.95	3	Horizontal	24	1.98	-	25.59	27.28	3.67	-

802.11b_Nss1,(1Mbps)_3TX

2437MHz_TX

20/03/2018




Type	Freq	Level	Limit	Margin	Factor	Dist	Condition	Azimuth	Height	Comments	Raw	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dB)	(m)		(°)	(m)		(dBuV)	(dB)	(dB)	(dB)
AV	7.31172G	53.57	54.00	-0.43	24.80	3	Vertical	351	1.50	-	28.77	35.81	23.98	34.98
PK	7.31202G	66.10	74.00	-7.90	24.80	3	Vertical	351	1.50	-	41.30	35.81	23.98	34.98

802.11b_Nss1,(1Mbps)_3TX

2437MHz_TX

20/03/2018




Type	Freq	Level	Limit	Margin	Factor	Dist	Condition	Azimuth	Height	Comments	Raw	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dB)	(m)		(°)	(m)		(dBuV)	(dB)	(dB)	(dB)
AV	7.30938G	51.74	54.00	-2.26	24.79	3	Horizontal	80	1.26	-	26.95	35.80	23.97	34.98
PK	7.32342G	65.34	74.00	-8.66	24.86	3	Horizontal	80	1.26	-	40.48	35.84	24.01	34.99

802.11b_Nss1,(1Mbps)_3TX

2462MHz_TX

19/03/2018




Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments	Raw (dBuV)	AF (dB)	CL (dB)	PA (dB)
AV	2.4602G	96.55	Inf	-Inf	30.83	3	Vertical	74	1.50	-	65.72	27.19	3.64	-
AV	2.499998G	45.61	54.00	-8.39	30.97	3	Vertical	74	1.50	-	14.64	27.30	3.67	-
PK	2.46G	97.84	Inf	-Inf	30.83	3	Vertical	74	1.50	-	67.01	27.19	3.64	-
PK	2.4918G	55.61	74.00	-18.39	30.94	3	Vertical	74	1.50	-	24.67	27.28	3.66	-

802.11b_Nss1,(1Mbps)_3TX

2462MHz_TX

19/03/2018




Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments	Raw (dBuV)	AF (dB)	CL (dB)	PA (dB)
AV	2.4648G	100.01	Inf	-Inf	30.84	3	Horizontal	26	1.87	-	69.17	27.20	3.64	-
AV	2.4936G	45.63	54.00	-8.37	30.94	3	Horizontal	26	1.87	-	14.69	27.28	3.66	-
PK	2.4648G	102.29	Inf	-Inf	30.84	3	Horizontal	26	1.87	-	71.45	27.20	3.64	-
PK	2.486G	56.40	74.00	-17.60	30.92	3	Horizontal	26	1.87	-	25.48	27.26	3.66	-

802.11b_Nss1,(1Mbps)_3TX

2462MHz_TX

20/03/2018




Type	Freq	Level	Limit	Margin	Factor	Dist	Condition	Azimuth	Height	Comments	Raw	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dB)	(m)		(°)	(m)		(dBuV)	(dB)	(dB)	(dB)
AV	7.38822G	39.82	54.00	-14.18	9.59	3	Vertical	356	2.63	-	30.23	36.01	8.59	35.01
PK	7.38402G	51.69	74.00	-22.31	9.57	3	Vertical	356	2.63	-	42.12	36.00	8.58	35.01

802.11b_Nss1,(1Mbps)_3TX

2462MHz_TX

20/03/2018




Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments	Raw (dBuV)	AF (dB)	CL (dB)	PA (dB)
AV	7.39476G	37.30	54.00	-16.70	9.62	3	Horizontal	53	1.97	-	27.68	36.03	8.60	35.01
PK	7.38234G	51.12	74.00	-22.88	9.56	3	Horizontal	53	1.97	-	41.56	35.99	8.57	35.00

802.11g_Nss1,(6Mbps)_3TX

2412MHz_TX

19/03/2018




Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments	Raw (dBuV)	AF (dB)	CL (dB)	PA (dB)
AV	2.389998G	53.43	54.00	-0.57	30.57	3	Vertical	87	1.74	-	22.86	26.99	3.58	-
AV	2.4104G	97.49	Inf	-Inf	30.65	3	Vertical	87	1.74	-	66.84	27.05	3.60	-
PK	2.3898G	63.96	74.00	-10.04	30.57	3	Vertical	87	1.74	-	33.39	26.99	3.58	-
PK	2.4102G	104.01	Inf	-Inf	30.65	3	Vertical	87	1.74	-	73.36	27.05	3.60	-



2412MHz_TX

19/03/2018




Type	Freq	Level	Limit	Margin	Factor	Dist	Condition	Azimuth	Height	Comments	Raw	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dB)	(m)		(°)	(m)		(dBuV)	(dB)	(dB)	(dB)
AV	2.389998G	52.32	54.00	-1.68	30.57	3	Horizontal	22	2.01	-	21.75	26.99	3.58	-
AV	2.41G	99.34	Inf	-Inf	30.65	3	Horizontal	22	2.01	-	68.69	27.05	3.60	-
PK	2.3894G	63.26	74.00	-10.74	30.57	3	Horizontal	22	2.01	-	32.69	26.99	3.58	-
PK	2.41G	106.26	Inf	-Inf	30.65	3	Horizontal	22	2.01	-	75.61	27.05	3.60	-

802.11g_Nss1,(6Mbps)_3TX

2412MHz_TX

20/03/2018




Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments	Raw (dBuV)	AF (dB)	CL (dB)	PA (dB)
AV	4.82106G	31.24	54.00	-22.76	3.13	3	Vertical	11	1.50	-	28.11	31.28	6.43	34.59
PK	4.81254G	44.87	74.00	-29.13	3.11	3	Vertical	11	1.50	-	41.76	31.26	6.43	34.59

802.11g_Nss1,(6Mbps)_3TX

2412MHz_TX

20/03/2018




Type	Freq	Level	Limit	Margin	Factor	Dist	Condition	Azimuth	Height	Comments	Raw	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dB)	(m)		(°)	(m)		(dBuV)	(dB)	(dB)	(dB)
AV	4.82112G	31.15	54.00	-22.85	3.13	3	Horizontal	50	2.95	-	28.02	31.28	6.43	34.59
PK	4.83012G	44.63	74.00	-29.37	3.15	3	Horizontal	50	2.95	-	41.48	31.29	6.44	34.58

802.11g_Nss1,(6Mbps)_3TX

2437MHz_TX

19/03/2018




Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments	Raw (dBuV)	AF (dB)	CL (dB)	PA (dB)
AV	2.3674G	45.51	54.00	-8.49	30.50	3	Vertical	0	1.02	-	15.01	26.93	3.57	-
AV	2.4378G	96.54	Inf	-Inf	30.75	3	Vertical	0	1.02	-	65.79	27.13	3.62	-
AV	2.487G	46.18	54.00	-7.82	30.92	3	Vertical	0	1.02	-	15.26	27.26	3.66	-
PK	2.3818G	55.16	74.00	-18.84	30.55	3	Vertical	0	1.02	-	24.61	26.97	3.58	-
PK	2.4374G	103.30	Inf	-Inf	30.74	3	Vertical	0	1.02	-	72.56	27.12	3.62	-
PK	2.4934G	55.52	74.00	-18.48	30.94	3	Vertical	0	1.02	-	24.58	27.28	3.66	-

802.11g_Nss1,(6Mbps)_3TX

2437MHz_TX

19/03/2018




Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments	Raw (dBuV)	AF (dB)	CL (dB)	PA (dB)
AV	2.3762G	45.51	54.00	-8.49	30.52	3	Horizontal	41	2.17	-	14.99	26.95	3.57	-
AV	2.4338G	97.62	Inf	-Inf	30.73	3	Horizontal	41	2.17	-	66.89	27.11	3.62	-
AV	2.4998G	46.34	54.00	-7.66	30.97	3	Horizontal	41	2.17	-	15.37	27.30	3.67	-
PK	2.3894G	55.79	74.00	-18.21	30.57	3	Horizontal	41	2.17	-	25.22	26.99	3.58	-
PK	2.4338G	105.07	Inf	-Inf	30.73	3	Horizontal	41	2.17	-	74.34	27.11	3.62	-
PK	2.487G	56.15	74.00	-17.85	30.92	3	Horizontal	41	2.17	-	25.23	27.26	3.66	-

802.11g_Nss1,(6Mbps)_3TX

2437MHz_TX

20/03/2018




Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments	Raw (dBuV)	AF (dB)	CL (dB)	PA (dB)
AV	7.31574G	38.49	54.00	-15.51	9.28	3	Vertical	356	2.68	-	29.21	35.82	8.44	34.98
PK	7.3056G	51.55	74.00	-22.45	9.23	3	Vertical	356	2.68	-	42.32	35.79	8.42	34.98

802.11g_Nss1,(6Mbps)_3TX

2437MHz_TX

20/03/2018




Type	Freq	Level	Limit	Margin	Factor	Dist	Condition	Azimuth	Height	Comments	Raw	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dB)	(m)		(°)	(m)		(dBuV)	(dB)	(dB)	(dB)
AV	7.3104G	37.28	54.00	-16.72	9.25	3	Horizontal	277	1.50	-	28.03	35.81	8.43	34.98
PK	7.31862G	50.47	74.00	-23.53	9.29	3	Horizontal	277	1.50	-	41.18	35.83	8.45	34.99

802.11g_Nss1,(6Mbps)_3TX

2462MHz_TX

19/03/2018




Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments	Raw (dBuV)	AF (dB)	CL (dB)	PA (dB)
AV	2.4596G	98.31	Inf	-Inf	30.82	3	Vertical	30	2.23	-	67.49	27.19	3.64	-
AV	2.4896G	48.66	54.00	-5.34	30.93	3	Vertical	30	2.23	-	17.73	27.27	3.66	-
PK	2.4596G	105.15	Inf	-Inf	30.82	3	Vertical	30	2.23	-	74.33	27.19	3.64	-
PK	2.489G	60.49	74.00	-13.51	30.93	3	Vertical	30	2.23	-	29.56	27.27	3.66	-

802.11g_Nss1,(6Mbps)_3TX

2462MHz_TX

19/03/2018




Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments	Raw (dBuV)	AF (dB)	CL (dB)	PA (dB)
AV	2.46G	98.07	Inf	-Inf	30.83	3	Horizontal	30	1.67	-	67.24	27.19	3.64	-
AV	2.489G	48.80	54.00	-5.20	30.93	3	Horizontal	30	1.67	-	17.87	27.27	3.66	-
PK	2.4604G	104.62	Inf	-Inf	30.83	3	Horizontal	30	1.67	-	73.79	27.19	3.64	-
PK	2.4896G	61.07	74.00	-12.93	30.93	3	Horizontal	30	1.67	-	30.14	27.27	3.66	-

802.11g_Nss1,(6Mbps)_3TX

2462MHz_TX

20/03/2018




Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments	Raw (dBuV)	AF (dB)	CL (dB)	PA (dB)
AV	7.38996G	39.92	54.00	-14.08	9.60	3	Vertical	357	2.52	-	30.32	36.01	8.59	35.01
PK	7.38042G	52.95	74.00	-21.05	9.56	3	Vertical	357	2.52	-	43.39	35.99	8.57	35.00

802.11g_Nss1,(6Mbps)_3TX

2462MHz_TX

20/03/2018




Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments	Raw (dBuV)	AF (dB)	CL (dB)	PA (dB)
AV	7.38432G	38.61	54.00	-15.39	9.57	3	Horizontal	287	1.50	-	29.04	36.00	8.58	35.01
PK	7.3959G	51.78	74.00	-22.22	9.62	3	Horizontal	287	1.50	-	42.16	36.03	8.60	35.01

802.11ac VHT20_Nss1,(MCS0)_3TX

2412MHz_TX

19/03/2018




Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments	Raw (dBuV)	AF (dB)	CL (dB)	PA (dB)
AV	2.389998G	53.41	54.00	-0.59	30.57	3	Vertical	89	1.73	-	22.84	26.99	3.58	-
AV	2.4086G	97.56	Inf	-Inf	30.64	3	Vertical	89	1.73	-	66.92	27.04	3.60	-
PK	2.3896G	65.24	74.00	-8.76	30.57	3	Vertical	89	1.73	-	34.67	26.99	3.58	-
PK	2.4082G	105.27	Inf	-Inf	30.64	3	Vertical	89	1.73	-	74.63	27.04	3.60	-

802.11ac VHT20_Nss1,(MCS0)_3TX

2412MHz_TX

19/03/2018




Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments	Raw (dBuV)	AF (dB)	CL (dB)	PA (dB)
AV	2.389998G	52.68	54.00	-1.32	30.57	3	Horizontal	25	2.28	-	22.11	26.99	3.58	-
AV	2.4082G	99.81	Inf	-Inf	30.64	3	Horizontal	25	2.28	-	69.17	27.04	3.60	-
PK	2.3898G	63.64	74.00	-10.36	30.57	3	Horizontal	25	2.28	-	33.07	26.99	3.58	-
PK	2.4082G	107.63	Inf	-Inf	30.64	3	Horizontal	25	2.28	-	76.99	27.04	3.60	-

802.11ac VHT20_Nss1,(MCS0)_3TX

2412MHz_TX

20/03/2018




Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments	Raw (dBuV)	AF (dB)	CL (dB)	PA (dB)
AV	4.82616G	30.65	54.00	-23.35	3.14	3	Vertical	339	1.49	-	27.51	31.29	6.44	34.58
PK	4.8093G	43.58	74.00	-30.42	3.10	3	Vertical	339	1.49	-	40.48	31.26	6.43	34.59

802.11ac VHT20_Nss1,(MCS0)_3TX

2412MHz_TX

20/03/2018




Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments	Raw (dBuV)	AF (dB)	CL (dB)	PA (dB)
AV	4.80936G	30.10	54.00	-23.90	3.10	3	Horizontal	250	1.50	-	27.00	31.26	6.43	34.59
PK	4.81704G	43.82	74.00	-30.18	3.12	3	Horizontal	250	1.50	-	40.70	31.27	6.43	34.59

802.11ac VHT20_Nss1,(MCS0)_3TX

2437MHz_TX

20/03/2018




Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments	Raw (dBuV)	AF (dB)	CL (dB)	PA (dB)
AV	2.3706G	45.48	54.00	-8.52	30.51	3	Vertical	30	2.25	-	14.97	26.94	3.57	-
AV	2.4418G	97.53	Inf	-Inf	30.76	3	Vertical	30	2.25	-	66.77	27.14	3.62	-
AV	2.4922G	46.02	54.00	-7.98	30.94	3	Vertical	30	2.25	-	15.08	27.28	3.66	-
PK	2.3614G	55.57	74.00	-18.43	30.47	3	Vertical	30	2.25	-	25.10	26.91	3.56	-
PK	2.4422G	104.49	Inf	-Inf	30.76	3	Vertical	30	2.25	-	73.73	27.14	3.62	-
PK	2.4874G	55.92	74.00	-18.08	30.92	3	Vertical	30	2.25	-	25.00	27.26	3.66	-

802.11ac VHT20_Nss1,(MCS0)_3TX

2437MHz_TX

20/03/2018




Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments	Raw (dBuV)	AF (dB)	CL (dB)	PA (dB)
AV	2.3478G	45.54	54.00	-8.46	30.42	3	Horizontal	44	1.50	-	15.12	26.87	3.55	-
AV	2.4442G	98.28	Inf	-Inf	30.77	3	Horizontal	44	1.50	-	67.51	27.14	3.63	-
AV	2.4838G	46.40	54.00	-7.60	30.91	3	Horizontal	44	1.50	-	15.49	27.25	3.66	-
PK	2.3538G	55.94	74.00	-18.06	30.45	3	Horizontal	44	1.50	-	25.49	26.89	3.56	-
PK	2.4434G	105.17	Inf	-Inf	30.77	3	Horizontal	44	1.50	-	74.40	27.14	3.62	-
PK	2.4998G	56.59	74.00	-17.41	30.97	3	Horizontal	44	1.50	-	25.62	27.30	3.67	-

802.11ac VHT20_Nss1,(MCS0)_3TX

2437MHz_TX

20/03/2018




Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments	Raw (dBuV)	AF (dB)	CL (dB)	PA (dB)
AV	7.31838G	37.39	54.00	-16.61	9.29	3	Vertical	356	1.46	-	28.10	35.83	8.45	34.99
PK	7.29936G	50.98	74.00	-23.02	9.21	3	Vertical	356	1.46	-	41.77	35.78	8.41	34.98

802.11ac VHT20_Nss1,(MCS0)_3TX

2437MHz_TX

20/03/2018




Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments	Raw (dBuV)	AF (dB)	CL (dB)	PA (dB)
AV	7.32528G	37.05	54.00	-16.95	9.32	3	Horizontal	11	1.50	-	27.73	35.85	8.46	34.99
PK	7.32414G	49.93	74.00	-24.07	9.31	3	Horizontal	11	1.50	-	40.62	35.84	8.46	34.99

802.11ac VHT20_Nss1,(MCS0)_3TX

2462MHz_TX

20/03/2018




Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments	Raw (dBuV)	AF (dB)	CL (dB)	PA (dB)
AV	2.467G	97.95	Inf	-Inf	30.85	3	Vertical	33	2.34	-	67.10	27.21	3.64	-
AV	2.484G	53.53	54.00	-0.47	30.92	3	Vertical	33	2.34	-	22.61	27.26	3.66	-
PK	2.466G	104.99	Inf	-Inf	30.85	3	Vertical	33	2.34	-	74.14	27.20	3.64	-
PK	2.4838G	65.55	74.00	-8.45	30.91	3	Vertical	33	2.34	-	34.64	27.25	3.66	-

802.11ac VHT20_Nss1,(MCS0)_3TX

2462MHz_TX

20/03/2018




Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments	Raw (dBuV)	AF (dB)	CL (dB)	PA (dB)
AV	2.4682G	98.73	Inf	-Inf	30.86	3	Horizontal	29	2.87	-	67.87	27.21	3.64	-
AV	2.4846G	53.60	54.00	-0.40	30.92	3	Horizontal	29	2.87	-	22.68	27.26	3.66	-
PK	2.4684G	106.26	Inf	-Inf	30.86	3	Horizontal	29	2.87	-	75.40	27.21	3.64	-
PK	2.4844G	67.13	74.00	-6.87	30.92	3	Horizontal	29	2.87	-	36.21	27.26	3.66	-

802.11ac VHT20_Nss1,(MCS0)_3TX

2462MHz_TX

21/03/2018




Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments	Raw (dBuV)	AF (dB)	CL (dB)	PA (dB)
AV	7.38408G	40.82	54.00	-13.18	9.57	3	Vertical	333	1.96	-	31.25	36.00	8.58	35.01
PK	7.3872G	54.52	74.00	-19.48	9.58	3	Vertical	333	1.96	-	44.94	36.01	8.58	35.01

802.11ac VHT20_Nss1,(MCS0)_3TX

2462MHz_TX

21/03/2018




Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments	Raw (dBuV)	AF (dB)	CL (dB)	PA (dB)
AV	7.3905G	40.73	54.00	-13.27	9.60	3	Horizontal	223	2.25	-	31.13	36.02	8.59	35.01
PK	7.3881G	54.11	74.00	-19.89	9.59	3	Horizontal	223	2.25	-	44.52	36.01	8.59	35.01

802.11ac VHT40_Nss1,(MCS0)_3TX

2422MHz_TX

20/03/2018




Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments	Raw (dBuV)	AF (dB)	CL (dB)	PA (dB)
AV	2.3888G	53.84	54.00	-0.16	30.57	3	Vertical	89	1.73	-	23.27	26.99	3.58	-
AV	2.4092G	93.20	Inf	-Inf	30.64	3	Vertical	89	1.73	-	62.56	27.05	3.60	-
AV	2.4912G	46.68	54.00	-7.32	30.94	3	Vertical	89	1.73	-	15.74	27.28	3.66	-
PK	2.3888G	64.35	74.00	-9.65	30.57	3	Vertical	89	1.73	-	33.78	26.99	3.58	-
PK	2.4088G	99.83	Inf	-Inf	30.64	3	Vertical	89	1.73	-	69.19	27.04	3.60	-
PK	2.4944G	56.14	74.00	-17.86	30.95	3	Vertical	89	1.73	-	25.19	27.28	3.67	-

802.11ac VHT40_Nss1,(MCS0)_3TX

2422MHz_TX

20/03/2018




Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments	Raw (dBuV)	AF (dB)	CL (dB)	PA (dB)
AV	2.389998G	53.60	54.00	-0.40	30.57	3	Horizontal	42	1.47	-	23.03	26.99	3.58	-
AV	2.4304G	94.94	Inf	-Inf	30.72	3	Horizontal	42	1.47	-	64.22	27.11	3.61	-
AV	2.4904G	46.88	54.00	-7.12	30.93	3	Horizontal	42	1.47	-	15.95	27.27	3.66	-
PK	2.389998G	63.41	74.00	-10.59	30.57	3	Horizontal	42	1.47	-	32.84	26.99	3.58	-
PK	2.43G	101.91	Inf	-Inf	30.72	3	Horizontal	42	1.47	-	71.19	27.10	3.61	-
PK	2.4896G	56.81	74.00	-17.19	30.93	3	Horizontal	42	1.47	-	25.88	27.27	3.66	-

802.11ac VHT40_Nss1,(MCS0)_3TX

2422MHz_TX

21/03/2018




Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments	Raw (dBuV)	AF (dB)	CL (dB)	PA (dB)
AV	4.8572G	32.09	54.00	-21.91	3.21	3	Vertical	225	1.50	-	28.88	31.34	6.44	34.58
PK	4.82984G	44.81	74.00	-29.19	3.15	3	Vertical	225	1.50	-	41.66	31.29	6.44	34.58

802.11ac VHT40_Nss1,(MCS0)_3TX

2422MHz_TX

21/03/2018




Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments	Raw (dBuV)	AF (dB)	CL (dB)	PA (dB)
AV	4.8479G	32.16	54.00	-21.84	3.19	3	Horizontal	239	1.48	-	28.97	31.33	6.44	34.58
PK	4.82942G	44.49	74.00	-29.51	3.14	3	Horizontal	239	1.48	-	41.35	31.29	6.44	34.58

802.11ac VHT40_Nss1,(MCS0)_3TX

2427MHz_TX

20/03/2018




Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments	Raw (dBuV)	AF (dB)	CL (dB)	PA (dB)
AV	2.3894G	53.73	54.00	-0.27	30.57	3	Vertical	357	1.18	-	23.16	26.99	3.58	-
AV	2.4282G	92.99	Inf	-Inf	30.71	3	Vertical	357	1.18	-	62.28	27.10	3.61	-
AV	2.4894G	46.93	54.00	-7.07	30.93	3	Vertical	357	1.18	-	16.00	27.27	3.66	-
PK	2.3894G	62.48	74.00	-11.52	30.57	3	Vertical	357	1.18	-	31.91	26.99	3.58	-
PK	2.429G	99.18	Inf	-Inf	30.71	3	Vertical	357	1.18	-	68.47	27.10	3.61	-
PK	2.4946G	56.36	74.00	-17.64	30.95	3	Vertical	357	1.18	-	25.41	27.28	3.67	-

802.11ac VHT40_Nss1,(MCS0)_3TX

2427MHz_TX

20/03/2018




Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments	Raw (dBuV)	AF (dB)	CL (dB)	PA (dB)
AV	2.389G	51.07	54.00	-2.93	30.57	3	Horizontal	39	1.96	-	20.50	26.99	3.58	-
AV	2.4202G	94.30	Inf	-Inf	30.68	3	Horizontal	39	1.96	-	63.62	27.08	3.61	-
AV	2.4862G	47.03	54.00	-6.97	30.92	3	Horizontal	39	1.96	-	16.11	27.26	3.66	-
PK	2.389G	60.83	74.00	-13.17	30.57	3	Horizontal	39	1.96	-	30.26	26.99	3.58	-
PK	2.4198G	101.34	Inf	-Inf	30.68	3	Horizontal	39	1.96	-	70.66	27.08	3.61	-
PK	2.4854G	55.85	74.00	-18.15	30.92	3	Horizontal	39	1.96	-	24.93	27.26	3.66	-

802.11ac VHT40_Nss1,(MCS0)_3TX

2437MHz_TX

20/03/2018




Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments	Raw (dBuV)	AF (dB)	CL (dB)	PA (dB)
AV	2.387G	46.67	54.00	-7.33	30.56	3	Vertical	357	1.14	-	16.11	26.98	3.58	-
AV	2.4382G	93.36	Inf	-Inf	30.75	3	Vertical	357	1.14	-	62.61	27.13	3.62	-
AV	2.483502G	48.90	54.00	-5.10	30.91	3	Vertical	357	1.14	-	17.99	27.25	3.66	-
PK	2.3806G	55.79	74.00	-18.21	30.55	3	Vertical	357	1.14	-	25.24	26.97	3.58	-
PK	2.439G	99.64	Inf	-Inf	30.75	3	Vertical	357	1.14	-	68.89	27.13	3.62	-
PK	2.4858G	57.21	74.00	-16.79	30.92	3	Vertical	357	1.14	-	26.29	27.26	3.66	-

802.11ac VHT40_Nss1,(MCS0)_3TX

2437MHz_TX

20/03/2018




Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments	Raw (dBuV)	AF (dB)	CL (dB)	PA (dB)
AV	2.3898G	48.09	54.00	-5.91	30.57	3	Horizontal	41	2.11	-	17.52	26.99	3.58	-
AV	2.4302G	94.34	Inf	-Inf	30.72	3	Horizontal	41	2.11	-	63.62	27.10	3.61	-
AV	2.4862G	48.67	54.00	-5.33	30.92	3	Horizontal	41	2.11	-	17.75	27.26	3.66	-
PK	2.3898G	57.30	74.00	-16.70	30.57	3	Horizontal	41	2.11	-	26.73	26.99	3.58	-
PK	2.4294G	100.68	Inf	-Inf	30.72	3	Horizontal	41	2.11	-	69.96	27.10	3.61	-
PK	2.4882G	58.11	74.00	-15.89	30.93	3	Horizontal	41	2.11	-	27.18	27.27	3.66	-

802.11ac VHT40_Nss1,(MCS0)_3TX

2437MHz_TX

21/03/2018




Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments	Raw (dBuV)	AF (dB)	CL (dB)	PA (dB)
AV	7.3209G	39.14	54.00	-14.86	9.30	3	Vertical	359	1.83	-	29.84	35.83	8.45	34.99
PK	7.31598G	51.79	74.00	-22.21	9.28	3	Vertical	359	1.83	-	42.51	35.82	8.44	34.98

802.11ac VHT40_Nss1,(MCS0)_3TX

2437MHz_TX

21/03/2018




Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments	Raw (dBuV)	AF (dB)	CL (dB)	PA (dB)
AV	7.3245G	38.41	54.00	-15.59	9.32	3	Horizontal	296	1.50	-	29.09	35.84	8.46	34.99
PK	7.31838G	50.35	74.00	-23.65	9.29	3	Horizontal	296	1.50	-	41.06	35.83	8.45	34.99

802.11ac VHT40_Nss1,(MCS0)_3TX

2447MHz_TX

20/03/2018




Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments	Raw (dBuV)	AF (dB)	CL (dB)	PA (dB)
AV	2.3898G	46.67	54.00	-7.33	30.57	3	Vertical	32	2.06	-	16.10	26.99	3.58	-
AV	2.4526G	93.00	Inf	-Inf	30.80	3	Vertical	32	2.06	-	62.20	27.17	3.63	-
AV	2.4898G	52.41	54.00	-1.59	30.93	3	Vertical	32	2.06	-	21.48	27.27	3.66	-
PK	2.389G	55.92	74.00	-18.08	30.57	3	Vertical	32	2.06	-	25.35	26.99	3.58	-
PK	2.4514G	99.77	Inf	-Inf	30.80	3	Vertical	32	2.06	-	68.97	27.16	3.63	-
PK	2.4922G	63.03	74.00	-10.97	30.94	3	Vertical	32	2.06	-	32.09	27.28	3.66	-

802.11ac VHT40_Nss1,(MCS0)_3TX

2447MHz_TX

20/03/2018




Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments	Raw (dBuV)	AF (dB)	CL (dB)	PA (dB)
AV	2.3794G	46.12	54.00	-7.88	30.54	3	Horizontal	38	1.96	-	15.58	26.96	3.58	-
AV	2.4358G	95.82	Inf	-Inf	30.74	3	Horizontal	38	1.96	-	65.08	27.12	3.62	-
AV	2.4902G	50.62	54.00	-3.38	30.93	3	Horizontal	38	1.96	-	19.69	27.27	3.66	-
PK	2.3698G	55.88	74.00	-18.12	30.51	3	Horizontal	38	1.96	-	25.37	26.94	3.57	-
PK	2.4358G	102.27	Inf	-Inf	30.74	3	Horizontal	38	1.96	-	71.53	27.12	3.62	-
PK	2.491G	60.66	74.00	-13.34	30.93	3	Horizontal	38	1.96	-	29.73	27.27	3.66	-

802.11ac VHT40_Nss1,(MCS0)_3TX

2452MHz_TX

20/03/2018




Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments	Raw (dBuV)	AF (dB)	CL (dB)	PA (dB)
AV	2.384G	45.46	54.00	-8.54	30.56	3	Vertical	30	2.09	-	14.90	26.98	3.58	-
AV	2.4476G	93.09	Inf	-Inf	30.78	3	Vertical	30	2.09	-	62.31	27.15	3.63	-
AV	2.4848G	53.88	54.00	-0.12	30.92	3	Vertical	30	2.09	-	22.96	27.26	3.66	-
PK	2.376G	55.16	74.00	-18.84	30.52	3	Vertical	30	2.09	-	24.64	26.95	3.57	-
PK	2.448G	100.36	Inf	-Inf	30.78	3	Vertical	30	2.09	-	69.58	27.15	3.63	-
PK	2.4876G	64.09	74.00	-9.91	30.93	3	Vertical	30	2.09	-	33.16	27.27	3.66	-

802.11ac VHT40_Nss1,(MCS0)_3TX

2452MHz_TX

20/03/2018




Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments	Raw (dBuV)	AF (dB)	CL (dB)	PA (dB)
AV	2.3888G	45.46	54.00	-8.54	30.57	3	Horizontal	43	1.47	-	14.89	26.99	3.58	-
AV	2.4492G	94.46	Inf	-Inf	30.79	3	Horizontal	43	1.47	-	63.67	27.16	3.63	-
AV	2.4872G	53.53	54.00	-0.47	30.92	3	Horizontal	43	1.47	-	22.61	27.26	3.66	-
PK	2.3888G	55.48	74.00	-18.52	30.57	3	Horizontal	43	1.47	-	24.91	26.99	3.58	-
PK	2.4496G	101.29	Inf	-Inf	30.79	3	Horizontal	43	1.47	-	70.50	27.16	3.63	-
PK	2.4876G	65.54	74.00	-8.46	30.93	3	Horizontal	43	1.47	-	34.61	27.27	3.66	-

802.11ac VHT40_Nss1,(MCS0)_3TX

2452MHz_TX

21/03/2018




Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments	Raw (dBuV)	AF (dB)	CL (dB)	PA (dB)
AV	7.36122G	38.57	54.00	-15.43	9.47	3	Vertical	247	1.50	-	29.10	35.94	8.53	35.00
PK	7.365G	51.23	74.00	-22.77	9.49	3	Vertical	247	1.50	-	41.74	35.95	8.54	35.00

802.11ac VHT40_Nss1,(MCS0)_3TX

2452MHz_TX

21/03/2018



Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments	Raw (dBuV)	AF (dB)	CL (dB)	PA (dB)
AV	7.3689G	38.70	54.00	-15.30	9.51	3	Horizontal	4	1.53	-	29.19	35.96	8.55	35.00
PK	7.36458G	51.61	74.00	-22.39	9.49	3	Horizontal	4	1.53	-	42.12	35.95	8.54	35.00