

March 03, 2016

TUV SUD BABT FCB Octagon House, Segensworth Road, Fareham, Hampshire, PO15 5RL

Attention: Director of Certification

RE: Analysis of RF Exposure for Portable and Mobile use per KDB 447498 D01 RF Exposure Procedures and Equipment Authorization Policies for Mobile and Portable Devices v06 and RSS-102 Issue 5 March 2015

IC: 20934-IPG FCC ID: 2AGS5-IPG

Portable exposure SAR Exemption Calculation using a 6mm separation distance:

As per Clause 4.3.1 (a) of KDB 447498 D01 v06:

$$\left(\frac{\text{max.power of channel,including tune-up tolerance,mW}}{\text{min.test separation distance,mm}}\right) \times \left(\sqrt{f(GHz)}\right) \le 3.0$$

$$\left(\frac{0.000993 \text{ mW}}{0.5 \text{ mm}}\right) x \left(\sqrt{0.40185(GHz)}\right) \le 3.0$$

0.0012≤ 3.0 (complies)

The EUT complies with the exemption limits for routine evaluation based on frequency and separation distance as per Table 1 of RSS-102 Issue 5 March 2015 with an EIRP of 0.993µW.

Sincerely,

Name

Authorized Signatory

Ferdie S. Custodio

Title: Senior EMC/Wireless Test Engineer