

FCC Radio Test Report

FCC ID: 2AGUA-EXPLORERS

Original Grant

Report No. : TB-FCC151501
Applicant : HK ELEPHONE COMMUNICATION TECH CO.,LIMITED
Equipment Under Test (EUT)
EUT Name : Action camera
Model No. : Explorer S
Series No. : N/A
Brand Name : ELE
Receipt Date : 2017-02-17
Test Date : 2017-02-18 to 2017-03-06
Issue Date : 2017-03-07
Standards : FCC Part 15, Subpart C (15.247:2016)
Test Method : ANSI C63.10: 2013
Conclusions : **PASS**

In the configuration tested, the EUT complied with the standards specified above,
The EUT technically complies with the FCC and IC requirements

Test/Witness Engineer :

IVAN SU

**Approved &
Authorized**

:

Long



This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in the report.

Contents

CONTENTS.....	2
1. GENERAL INFORMATION ABOUT EUT	4
1.1 Client Information.....	4
1.2 General Description of EUT (Equipment Under Test)	4
1.3 Block Diagram Showing the Configuration of System Tested.....	5
1.4 Description of Support Units	6
1.5 Description of Test Mode.....	6
1.6 Description of Test Software Setting	7
1.7 Measurement Uncertainty	7
1.8 Test Facility.....	8
2. TEST SUMMARY.....	9
3. TEST EQUIPMENT.....	10
4. CONDUCTED EMISSION TEST	11
4.1 Test Standard and Limit.....	11
4.2 Test Setup.....	11
4.3 Test Procedure.....	11
4.4 EUT Operating Mode	12
4.5 Test Data.....	12
5. RADIATED EMISSION TEST	17
5.1 Test Standard and Limit.....	17
5.2 Test Setup.....	18
5.3 Test Procedure.....	19
5.4 EUT Operating Condition	19
5.5 Test Data.....	20
6. RESTRICTED BANDS REQUIREMENT	41
6.1 Test Standard and Limit.....	41
6.2 Test Setup.....	41
6.3 Test Procedure.....	41
6.4 EUT Operating Condition	42
6.5 Test Data.....	42
7. BANDWIDTH TEST.....	58
7.1 Test Standard and Limit.....	58
7.2 Test Setup.....	58
7.3 Test Procedure.....	58
7.4 EUT Operating Condition	58
7.5 Test Data.....	59
8. PEAK OUTPUT POWER TEST.....	65
8.1 Test Standard and Limit.....	65
8.2 Test Setup.....	65

8.3 Test Procedure.....	65
8.4 EUT Operating Condition	65
8.5 Test Data.....	66
9. POWER SPECTRAL DENSITY TEST	69
9.1 Test Standard and Limit.....	69
9.2 Test Setup.....	69
9.3 Test Procedure.....	69
9.4 EUT Operating Condition	69
9.5 Test Data.....	70
10. ANTENNA REQUIREMENT.....	76
10.1 Standard Requirement.....	76
10.2 Antenna Connected Construction.....	76

1. General Information about EUT

1.1 Client Information

Applicant : HK ELEPHONE COMMUNICATION TECH CO.,LIMITED
Address : UNIT 04, 7/F BRIGHT WAY TOWER NO.33 MONG KOK RD KL,
HONGKONG
Manufacturer : HK ELEPHONE COMMUNICATION TECH CO.,LIMITED
Address : UNIT 04, 7/F BRIGHT WAY TOWER NO.33 MONG KOK RD KL,
HONGKONG

1.2 General Description of EUT (Equipment Under Test)

EUT Name	:	Action camera	
Models No.	:	Explorer S	
Model Difference	:	N/A	
Product Description	:	Operation Frequency:	802.11b/g/n(HT20): 2412MHz~2462MHz
		Number of Channel:	802.11b/g/n(HT20):11 channels see note(3)
		RF Output Power:	802.11b: 9.34 dBm 802.11g: 9.15 dBm 802.11n (HT20): 9.13 dBm
		Antenna Gain:	2.11 dBi Internal Antenna
		Modulation Type:	802.11b: DSSS(CCK, DQPSK, DBPSK) 802.11g/n:OFDM(BPSK,QPSK,16QAM, 64QAM)
		Bit Rate of Transmitter:	802.11b:11/5.5/2/1 Mbps 802.11g:54/48/36/24/18/12/9/6 Mbps 802.11n:up to 150Mbps
Power Supply	:	DC power by USB cable. DC power by Li-ion battery.	
Power Rating	:	DC 5.0V by USB cable. DC 3.7V by 900mAh Li-ion battery.	
Connecting I/O Port(S)	:	Please refer to the User's Manual	

Note:


- (1) This Test Report is FCC Part 15.247 for 802.11b/g/n, the test procedure follows the FCC KDB 558074 D01 DTS Meas Guidance v03r05.
- (2) For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.
- (3) Channel List:

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
01	2412	05	2432	09	2452
02	2417	06	2437	10	2457
03	2422	07	2442	11	2462
04	2427	08	2447		
Note:CH 01~CH 11 for 802.11b/g/n(HT20)					


(4) The Antenna information about the equipment is provided by the applicant.

1.3 Block Diagram Showing the Configuration of System Tested

USB Charging with TX Mode



TX Mode



1.4 Description of Support Units

Equipment Information				
Name	Model	FCC ID/VOC	Manufacturer	Used “√”
AC/DC Adapter	TEKA012	VOC	TEKA	√
AC/DC Adapter: Input:100~240V, 50/60Hz, 0.2A. Output: 5V, 1A				
Cable Information				
Number	Shielded Type	Ferrite Core	Length	Note
Cable 1	YES	YES	1.2M	

1.5 Description of Test Mode

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned follow was evaluated respectively.

For Conducted Test	
Final Test Mode	Description
Mode 1	USB Charging with TX B Mode

For Radiated Test	
Final Test Mode	Description
Mode 2	TX Mode B Mode Channel 01/06/11
Mode 3	TX Mode G Mode Channel 01/06/11
Mode 4	TX Mode N(HT20) Mode Channel 01/06/11

Note:

- (1) For all test, we have verified the construction and function in typical operation. And all the test modes were carried out with the EUT in transmitting operation in maximum power with all kinds of data rate.
According to ANSI C63.10 standards, the measurements are performed at the highest, Middle, lowest available channels, and the worst case data rate as follows:
802.11b Mode: CCK (1 Mbps)
802.11g Mode: OFDM (6 Mbps)
802.11n (HT20) Mode: MCS 0 (6.5 Mbps)
- (2) During the testing procedure, the continuously transmitting with the maximum power mode was programmed by the customer.
- (3) The EUT is considered a portable unit; in normal use it was positioned on X-plane. The

worst case was found positioned on X-plane. Therefore only the test data of this X-plane was used for radiated emission measurement test.

1.6 Description of Test Software Setting

During testing channel&Power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters of WLAN.

Test Software Version	N/A		
Channel	CH 01	CH 06	CH 11
IEEE 802.11b DSSS	DEF	DEF	DEF
IEEE 802.11g OFDM	DEF	DEF	DEF
IEEE 802.11n (HT20)	DEF	DEF	DEF

1.7 Measurement Uncertainty

The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

Test Item	Parameters	Expanded Uncertainty (U_{Lab})
Conducted Emission	Level Accuracy: 9kHz~150kHz 150kHz to 30MHz	± 3.42 dB ± 3.42 dB
Radiated Emission	Level Accuracy: 9kHz to 30 MHz	± 4.60 dB
Radiated Emission	Level Accuracy: 30MHz to 1000 MHz	± 4.40 dB
Radiated Emission	Level Accuracy: Above 1000MHz	± 4.20 dB

1.8 Test Facility

The testing report were performed by the Shenzhen Toby Technology Co., Ltd., in their facilities located at 1A/F., Bldg.6, Yusheng Industrial Zone, The National Road No.107 Xixiang Section 467, Xixiang, Bao'an, Shenzhen, Guangdong, China. At the time of testing, the following bodies accredited the Laboratory:

CNAS (L5813)

The Laboratory has been accredited by CNAS to ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories for the competence in the field of testing. And the Registration No.: CNAS L5813.

FCC List No.: (811562)

The Laboratory is listed in the United States of American Federal Communications Commission (FCC), and the registration number is 811562.

IC Registration No.: (11950A-1)

The Laboratory has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing. The site registration: Site# 11950A-1.

2. Test Summary

FCC Part 15 Subpart C(15.247)/ RSS 247 Issue 1				
Standard Section		Test Item	Judgment	Remark
FCC	IC			
15.203	/	Antenna Requirement	PASS	N/A
15.207	RSS-GEN 7.2.4	Conducted Emission	PASS	N/A
15.205	RSS-GEN 7.2.2	Restricted Bands	PASS	N/A
15.247(a)(2)	RSS 247 5.2 (1)	6dB Bandwidth	PASS	N/A
15.247(b)	RSS 247 5.4 (4)	Peak Output Power	PASS	N/A
15.247(e)	RSS 247 5.2 (2)	Power Spectral Density	PASS	N/A
15.247(d)	RSS 247 5.5	Band Edge	PASS	N/A
15.247(d)& 15.209	RSS 247 5.5	Transmitter Radiated Spurious Emission	PASS	N/A
Note: “/” for no requirement for this test item. N/A is an abbreviation for Not Applicable.				

3. Test Equipment

Conducted Emission Test					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Due Date
EMI Test Receiver	Rohde & Schwarz	ESCI	100321	Jul. 22, 2016	Jul. 21, 2017
RF Switching Unit	Compliance Direction Systems Inc	RSU-A4	34403	Jul. 22, 2016	Jul. 21, 2017
AMN	SCHWARZBECK	NNBL 8226-2	8226-2/164	Jul. 22, 2016	Jul. 21, 2017
LISN	Rohde & Schwarz	ENV216	101131	Jul. 22, 2016	Jul. 21, 2017
Radiation Emission Test					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Due Date
Spectrum Analyzer	Agilent	E4407B	MY45106456	Jul. 22, 2016	Jul. 21, 2017
EMI Test Receiver	Rohde & Schwarz	ESPI	100010/007	Jul. 22, 2016	Jul. 21, 2017
Bilog Antenna	ETS-LINDGREN	3142E	00117537	Mar. 20, 2016	Mar. 19, 2017
Bilog Antenna	ETS-LINDGREN	3142E	00117542	Mar. 20, 2016	Mar. 19, 2017
Horn Antenna	ETS-LINDGREN	3117	00143207	Mar. 19, 2016	Mar. 18, 2017
Horn Antenna	ETS-LINDGREN	3117	00143209	Mar. 19, 2016	Mar. 18, 2017
Loop Antenna	Laplace instrument	RF300	0701	Mar. 19, 2016	Mar. 18, 2017
Pre-amplifier	Sonoma	310N	185903	Mar. 20, 2016	Mar. 19, 2017
Pre-amplifier	HP	8447B	3008A00849	Mar. 26, 2016	Mar. 25, 2017
Cable	HUBER+SUHNER	100	SUCOFLEX	Mar. 26, 2016	Mar. 25, 2017
Positioning Controller	ETS-LINDGREN	2090	N/A	N/A	N/A
Antenna Conducted Emission					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Due Date
Spectrum Analyzer	Agilent	E4407B	MY45106456	Jul. 22, 2016	Jul. 21, 2017
Spectrum Analyzer	Rohde & Schwarz	ESCI	100321	Jul. 22, 2016	Jul. 21, 2017
Power Meter	Anritsu	ML2495A	25406005	Jul. 22, 2016	Jul. 21, 2017
Power Sensor	Anritsu	ML2411B	25406005	Jul. 22, 2016	Jul. 21, 2017

4. Conducted Emission Test

4.1 Test Standard and Limit

4.1.1 Test Standard

FCC Part 15.207

4.1.2 Test Limit

Conducted Emission Test Limit

Frequency	Maximum RF Line Voltage (dB μ V)	
	Quasi-peak Level	Average Level
150kHz~500kHz	66 ~ 56 *	56 ~ 46 *
500kHz~5MHz	56	46
5MHz~30MHz	60	50


Notes:

(1) *Decreasing linearly with logarithm of the frequency.

(2) The lower limit shall apply at the transition frequencies.

(3) The limit decrease in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

4.2 Test Setup



4.3 Test Procedure

The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.

Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.

I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.

LISN at least 80 cm from nearest part of EUT chassis.

The bandwidth of EMI test receiver is set at 9kHz, and the test frequency band is from 0.15MHz to 30MHz.


4.4 EUT Operating Mode

Please refer to the description of test mode.

4.5 Test Data

Please see the next page.


EUT:	Action camera	Model Name :	Explorer S
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60Hz		
Terminal:	Line		
Test Mode:	USB Charging with TX B Mode		
Remark:	Only worse case is reported		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector
1		0.1580	45.64	9.94	55.58	65.56	-9.98	QP
2		0.1580	28.44	9.94	38.38	55.56	-17.18	AVG
3	*	0.1940	43.99	10.01	54.00	63.86	-9.86	QP
4		0.1940	27.72	10.01	37.73	53.86	-16.13	AVG
5		0.5899	26.69	10.06	36.75	56.00	-19.25	QP
6		0.5899	16.75	10.06	26.81	46.00	-19.19	AVG
7		1.2300	18.96	10.06	29.02	56.00	-26.98	QP
8		1.2300	5.53	10.06	15.59	46.00	-30.41	AVG
9		6.1620	16.27	10.02	26.29	60.00	-33.71	QP
10		6.1620	5.01	10.02	15.03	50.00	-34.97	AVG
11		15.1860	22.29	10.26	32.55	60.00	-27.45	QP
12		15.1860	9.22	10.26	19.48	50.00	-30.52	AVG

Emission Level= Read Level+ Correct Factor


EUT:	Action camera	Model Name :	Explorer S
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60Hz		
Terminal:	Neutral		
Test Mode:	USB Charging with TX B Mode		
Remark:	Only worse case is reported		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector
1		0.1660	39.40	10.12	49.52	65.15	-15.63	QP
2		0.1660	22.10	10.12	32.22	55.15	-22.93	AVG
3	*	0.2060	40.02	10.12	50.14	63.36	-13.22	QP
4		0.2060	23.56	10.12	33.68	53.36	-19.68	AVG
5		0.5780	24.95	10.02	34.97	56.00	-21.03	QP
6		0.5780	19.04	10.02	29.06	46.00	-16.94	AVG
7		1.0060	16.10	10.16	26.26	56.00	-29.74	QP
8		1.0060	5.39	10.16	15.55	46.00	-30.45	AVG
9		5.7940	15.48	10.06	25.54	60.00	-34.46	QP
10		5.7940	6.52	10.06	16.58	50.00	-33.42	AVG
11		14.7540	19.13	10.06	29.19	60.00	-30.81	QP
12		14.7540	6.85	10.06	16.91	50.00	-33.09	AVG

Emission Level= Read Level+ Correct Factor


EUT:	Action camera	Model Name :	Explorer S
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 240V/60Hz		
Terminal:	Line		
Test Mode:	USB Charging with TX B Mode		
Remark:	Only worse case is reported		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector
1	*	0.1620	40.29	9.94	50.23	65.36	-15.13	QP
2		0.1620	21.91	9.94	31.85	55.36	-23.51	AVG
3		0.5500	27.32	10.04	37.36	56.00	-18.64	QP
4		0.5500	14.05	10.04	24.09	46.00	-21.91	AVG
5		1.1019	21.70	10.06	31.76	56.00	-24.24	QP
6		1.1019	9.89	10.06	19.95	46.00	-26.05	AVG
7		2.1860	20.85	10.05	30.90	56.00	-25.10	QP
8		2.1860	7.46	10.05	17.51	46.00	-28.49	AVG
9		6.3659	19.83	10.03	29.86	60.00	-30.14	QP
10		6.3659	7.23	10.03	17.26	50.00	-32.74	AVG
11		14.7580	19.11	10.26	29.37	60.00	-30.63	QP
12		14.7580	4.27	10.26	14.53	50.00	-35.47	AVG

Emission Level= Read Level+ Correct Factor

EUT:	Action camera	Model Name :	Explorer S
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 240V/60Hz		
Terminal:	Neutral		
Test Mode:	USB Charging with TX B Mode		
Remark:	Only worse case is reported		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector
1	*	0.1620	41.22	10.12	51.34	65.36	-14.02	QP
2		0.1620	23.91	10.12	34.03	55.36	-21.33	AVG
3		0.2060	37.91	10.12	48.03	63.36	-15.33	QP
4		0.2060	21.25	10.12	31.37	53.36	-21.99	AVG
5		0.5899	25.62	10.02	35.64	56.00	-20.36	QP
6		0.5899	19.68	10.02	29.70	46.00	-16.30	AVG
7		1.4220	18.64	10.12	28.76	56.00	-27.24	QP
8		1.4220	9.21	10.12	19.33	46.00	-26.67	AVG
9		2.3060	19.44	10.06	29.50	56.00	-26.50	QP
10		2.3060	13.81	10.06	23.87	46.00	-22.13	AVG
11		15.3740	16.70	10.06	26.76	60.00	-33.24	QP
12		15.3740	2.74	10.06	12.80	50.00	-37.20	AVG

Emission Level= Read Level+ Correct Factor

5. Radiated Emission Test

5.1 Test Standard and Limit

5.1.1 Test Standard

FCC Part 15.209

5.1.2 Test Limit

Radiated Emission Limits (9 kHz~1000 MHz)

Frequency (MHz)	Field Strength (microvolt/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3


Radiated Emission Limit (Above 1000MHz)

Frequency (MHz)	Class A (dBuV/m)(at 3 M)		Class B (dBuV/m)(at 3 M)	
	Peak	Average	Peak	Average
Above 1000	80	60	74	54


Note:

- (1) The tighter limit applies at the band edges.
- (2) Emission Level(dBuV/m)=20log Emission Level(uV/m)

5.2 Test Setup



Below 30MHz Test Setup



Below 1000MHz Test Setup



Above 1GHz Test Setup

5.3 Test Procedure

- (1) Measurements at frequency above 1GHz. The EUT was placed on a rotating 1.5m high above the ground. RF absorbers covered the ground plane with a minimum area of 3.0m by 3.0m between the EUT and measurement receiver antenna. The RF absorber shall not exceed 30cm in high above the conducting floor. The table was rotated 360 degrees to determine the position of the highest radiation.
- (2) The Test antenna shall vary between 1m and 4m, Both Horizontal and Vertical antenna are set to make measurement.
- (3) The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- (4) If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit Bellow 1 GHz, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed. But the Peak Value and average value both need to comply with applicable limit above 1 GHz.
- (5) Testing frequency range below 1GHz the measuring instrument use VBW=120 kHz with Quasi-peak detection.
- (6) Testing frequency range above 1GHz the measuring instrument use RBW=1 MHz and VBW=3 MHz with Peak Detector for Peak Values, and use RBW=1 MHz and VBW=10 Hz with Peak Detector for Average Values.
- (7) For the actual test configuration, please see the test setup photo.

5.4 EUT Operating Condition

The Equipment Under Test was set to Continual Transmitting in maximum power.

5.5 Test Data

Remark: During testing above 1GHz the measuring instrument use RBW=1 MHz and VBW=3 MHz with Peak Detector for Peak Values, and use RBW=1 MHz and VBW=10 Hz with Peak Detector for Average Values.

Test data please refer the following pages.


9KHz~30MHz

From 9KHz to 30MHz: Conclusion: PASS

Note: The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

30MHz~1GHz

EUT:	Action camera	Model:	Explorer S
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Ant. Pol.	Horizontal		
Test Mode:	TX B Mode 2412MHz		
Remark:	Only worse case is reported		




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		221.3920	54.63	-19.05	35.58	46.00	-10.42	peak
2	!	341.9786	54.73	-14.65	40.08	46.00	-5.92	peak
3	!	582.7424	51.20	-9.22	41.98	46.00	-4.02	peak
4	!	684.7454	47.73	-6.14	41.59	46.00	-4.41	peak
5	!	744.8660	47.70	-6.00	41.70	46.00	-4.30	peak
6	*	884.5028	46.31	-4.24	42.07	46.00	-3.93	peak

*:Maximum data x:Over limit !:over margin

Emission Level= Read Level+ Correct Factor

EUT:	Action camera	Model:	Explorer S
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Ant. Pol.	Vertical		
Test Mode:	TX B Mode 2412MHz		
Remark:	Only worse case is reported		




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		124.1329	47.58	-22.30	25.28	43.50	-18.22	peak
2		191.0738	51.94	-20.50	31.44	43.50	-12.06	peak
3		221.3920	53.38	-19.05	34.33	46.00	-11.67	peak
4		341.9786	52.42	-14.65	37.77	46.00	-8.23	peak
5	!	582.7424	50.54	-9.22	41.32	46.00	-4.68	peak
6	*	724.2611	48.30	-6.09	42.21	46.00	-3.79	peak

*:Maximum data x:Over limit !:over margin

Emission Level= Read Level+ Correct Factor

Above 1GHz


EUT:	Action camera	Model:	Explorer S
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Ant. Pol.	Horizontal		
Test Mode:	TX B Mode 2412MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	*	4824.147	37.73	13.56	51.29	54.00	-2.71	AVG
2		4824.351	49.38	13.56	62.94	74.00	-11.06	peak

Emission Level= Read Level+ Correct Factor


EUT:	Action camera	Model:	Explorer S
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Ant. Pol.	Vertical		
Test Mode:	TX B Mode 2412MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		4823.427	49.16	13.56	62.72	74.00	-11.28	peak
2	*	4823.970	35.45	13.56	49.01	54.00	-4.99	AVG

Emission Level= Read Level+ Correct Factor


EUT:	Action camera	Model:	Explorer S
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Ant. Pol.	Horizontal		
Test Mode:	TX B Mode 2437MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	*	4874.009	38.00	13.86	51.86	54.00	-2.14	AVG
2		4874.198	49.71	13.86	63.57	74.00	-10.43	peak

Emission Level= Read Level+ Correct Factor


EUT:	Action camera	Model:	Explorer S
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Ant. Pol.	Vertical		
Test Mode:	TX B Mode 2437MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	*	4873.991	35.07	13.86	48.93	54.00	-5.07	AVG
2		4874.237	48.74	13.86	62.60	74.00	-11.40	peak

Emission Level= Read Level+ Correct Factor


EUT:	Action camera	Model:	Explorer S
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Ant. Pol.	Horizontal		
Test Mode:	TX B Mode 2462MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		4923.706	50.61	14.15	64.76	74.00	-9.24	peak
2	*	4924.051	38.78	14.15	52.93	54.00	-1.07	AVG

Emission Level= Read Level+ Correct Factor


EUT:	Action camera	Model:	Explorer S
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Ant. Pol.	Vertical		
Test Mode:	TX B Mode 2462MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	*	4924.108	35.70	14.15	49.85	54.00	-4.15	AVG
2		4924.996	49.41	14.15	63.56	74.00	-10.44	peak

Emission Level= Read Level+ Correct Factor


EUT:	Action camera	Model:	Explorer S
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Ant. Pol.	Horizontal		
Test Mode:	TX G Mode 2412MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		4823.013	48.42	13.56	61.98	74.00	-12.02	peak
2	*	4823.016	34.20	13.56	47.76	54.00	-6.24	AVG

Emission Level= Read Level+ Correct Factor


EUT:	Action camera	Model:	Explorer S
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Ant. Pol.	Vertical		
Test Mode:	TX G Mode 2412MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	*	4823.652	34.21	13.56	47.77	54.00	-6.23	AVG
2		4823.853	48.48	13.56	62.04	74.00	-11.96	peak

Emission Level= Read Level+ Correct Factor


EUT:	Action camera	Model:	Explorer S
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Ant. Pol.	Horizontal		
Test Mode:	TX G Mode 2437MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	*	4873.472	34.64	13.86	48.50	54.00	-5.50	AVG
2		4874.963	48.46	13.86	62.32	74.00	-11.68	peak

Emission Level= Read Level+ Correct Factor


EUT:	Action camera	Model:	Explorer S
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Ant. Pol.	Vertical		
Test Mode:	TX G Mode 2437MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		4872.779	49.29	13.85	63.14	74.00	-10.86	peak
2	*	4874.111	34.61	13.86	48.47	54.00	-5.53	AVG

Emission Level= Read Level+ Correct Factor


EUT:	Action camera	Model:	Explorer S
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Ant. Pol.	Horizontal		
Test Mode:	TX G Mode 2462MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		4924.765	49.26	14.15	63.41	74.00	-10.59	peak
2	*	4925.002	35.01	14.16	49.17	54.00	-4.83	AVG

Emission Level= Read Level+ Correct Factor


EUT:	Action camera	Model:	Explorer S
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Ant. Pol.	Vertical		
Test Mode:	TX G Mode 2462MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		4923.730	49.30	14.15	63.45	74.00	-10.55	peak
2	*	4923.811	35.13	14.15	49.28	54.00	-4.72	AVG

Emission Level= Read Level+ Correct Factor


EUT:	Action camera	Model:	Explorer S
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Ant. Pol.	Horizontal		
Test Mode:	TX N(HT20) Mode 2412MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		4823.877	48.12	13.56	61.68	74.00	-12.32	peak
2	*	4823.892	34.23	13.56	47.79	54.00	-6.21	AVG

Emission Level= Read Level+ Correct Factor


EUT:	Action camera	Model:	Explorer S
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Ant. Pol.	Vertical		
Test Mode:	TX N(HT20) Mode 2412MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	*	4822.560	34.21	13.55	47.76	54.00	-6.24	AVG
2		4824.381	47.78	13.56	61.34	74.00	-12.66	peak

Emission Level= Read Level+ Correct Factor


EUT:	Action camera	Model:	Explorer S
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Ant. Pol.	Horizontal		
Test Mode:	TX N(HT20) Mode 2437MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	*	4873.475	34.62	13.86	48.48	54.00	-5.52	AVG
2		4873.676	48.90	13.86	62.76	74.00	-11.24	peak

Emission Level= Read Level+ Correct Factor


EUT:	Action camera	Model:	Explorer S
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Ant. Pol.	Vertical		
Test Mode:	TX N(HT20) Mode 2437MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		4873.937	49.37	13.86	63.23	74.00	-10.77	peak
2	*	4874.486	34.63	13.86	48.49	54.00	-5.51	AVG

Emission Level= Read Level+ Correct Factor


EUT:	Action camera	Model:	Explorer S
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Ant. Pol.	Horizontal		
Test Mode:	TX N(HT20) Mode 2462MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	*	4923.631	35.01	14.15	49.16	54.00	-4.84	AVG
2		4924.612	48.45	14.15	62.60	74.00	-11.40	peak

Emission Level= Read Level+ Correct Factor

EUT:	Action camera	Model:	Explorer S
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Ant. Pol.	Vertical		
Test Mode:	TX N(HT20) Mode 2462MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	*	4923.574	34.94	14.15	49.09	54.00	-4.91	AVG
2		4924.147	49.64	14.15	63.79	74.00	-10.21	peak

Emission Level= Read Level+ Correct Factor

6. Restricted Bands Requirement

6.1 Test Standard and Limit

6.1.1 Test Standard

FCC Part 15.247(d)


FCC Part 15.209

FCC Part 15.205

6.1.2 Test Limit

Restricted Frequency Band (MHz)	Class B (dBuV/m)(at 3 M)	
	Peak	Average
2310 ~2390	74	54
2483.5 ~2500	74	54

6.2 Test Setup



6.3 Test Procedure

- (1) The measuring distance of 3m shall be used for measurements at frequency up to 1GHz and above 1 GHz. The EUT was placed on a rotating 0.8m high above ground, the table was rotated 360 degrees to determine the position of the highest radiation.
- (2) Measurements at frequency above 1GHz. The EUT was placed on a rotating 1.5m high above the ground. RF absorbers covered the ground plane with a minimum area of 3.0m by 3.0m between the EUT and measurement receiver antenna. The RF absorber shall not exceed 30cm in high above the conducting floor. The table was rotated 360 degrees to determine the position of the highest radiation.

- (3) The Test antenna shall vary between 1m and 4m, Both Horizontal and Vertical antenna are set to make measurement.
- (4) The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- (5) If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit Bellow 1 GHz, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed. But the Peak Value and average value both need to comply with applicable limit above 1 GHz.
- (6) Testing frequency range below 1GHz the measuring instrument use VBW=120 kHz with Quasi-peak detection.
- (7) Testing frequency range above 1GHz the measuring instrument use RBW=1 MHz and VBW=3 MHz with Peak Detector for Peak Values, and use RBW=1 MHz and VBW=10 Hz with Peak Detector for Average Values.
- (8) For the actual test configuration, please see the test setup photo.

6.4 EUT Operating Condition


The Equipment Under Test was set to Continual Transmitting in maximum power.

6.5 Test Data

Please see the next page.

(1) Radiation Test


EUT:	Action camera	Model:	Explorer S
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Ant. Pol.	Horizontal		
Test Mode:	TX B Mode 2412MHz		
Remark:	N/A		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		2390.000	48.72	0.77	49.49	74.00	-24.51	peak
2		2390.000	36.62	0.77	37.39	54.00	-16.61	AVG
3	*	2411.200	90.99	0.86	91.85	Fundamental Frequency		AVG
4	X	2413.100	96.48	0.86	97.34	Fundamental Frequency		peak

Emission Level= Read Level+ Correct Factor


EUT:	Action camera	Model:	Explorer S
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Ant. Pol.	Vertical		
Test Mode:	TX B Mode 2412MHz		
Remark:	N/A		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		2390.000	45.52	0.77	46.29	74.00	-27.71	peak
2		2390.000	35.95	0.77	36.72	54.00	-17.28	AVG
3	X	2410.900	94.27	0.86	95.13	Fundamental Frequency		peak
4	*	2411.200	89.34	0.86	90.20	Fundamental Frequency		AVG

Emission Level= Read Level+ Correct Factor


EUT:	Action camera	Model:	Explorer S
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Ant. Pol.	Horizontal		
Test Mode:	TX B Mode 2462MHz		
Remark:	N/A		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1	X	2460.900	95.17	1.06	96.23	Fundamental Frequency		peak
2	*	2461.200	90.55	1.07	91.62	Fundamental Frequency		AVG
3		2483.500	45.89	1.17	47.06	74.00	-26.94	peak
4		2483.500	34.91	1.17	36.08	54.00	-17.92	AVG

Emission Level= Read Level+ Correct Factor


EUT:	Action camera	Model:	Explorer S
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Ant. Pol.	Vertical		
Test Mode:	TX B Mode 2462MHz		
Remark:	N/A		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1	*	2462.800	91.08	1.08	92.16	Fundamental Frequency		AVG
2	X	2463.100	96.23	1.08	97.31	Fundamental Frequency		peak
3		2483.500	54.03	1.17	55.20	74.00	-18.80	peak
4		2483.500	36.00	1.17	37.17	54.00	-16.83	AVG

Emission Level= Read Level+ Correct Factor


EUT:	Action camera	Model:	Explorer S
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Ant. Pol.	Horizontal		
Test Mode:	TX G Mode 2412MHz		
Remark:	N/A		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		2390.000	47.12	0.77	47.89	74.00	-26.11	peak
2		2390.000	36.17	0.77	36.94	54.00	-17.06	AVG
3	X	2418.600	93.32	0.89	94.21	Fundamental Frequency		peak
4	*	2418.600	83.26	0.89	84.15	Fundamental Frequency		AVG

Emission Level= Read Level+ Correct Factor


EUT:	Action camera	Model:	Explorer S
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Ant. Pol.	Vertical		
Test Mode:	TX G Mode 2412MHz		
Remark:	N/A		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		2390.000	42.70	0.77	43.47	74.00	-30.53	peak
2		2390.000	30.70	0.77	31.47	54.00	-22.53	AVG
3	X	2418.600	90.61	0.89	91.50	Fundamental Frequency		peak
4	*	2418.800	80.47	0.89	81.36	Fundamental Frequency		AVG

Emission Level= Read Level+ Correct Factor


EUT:	Action camera	Model:	Explorer S
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Ant. Pol.	Horizontal		
Test Mode:	TX G Mode 2462MHz		
Remark:	N/A		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	X	2455.500	93.69	1.05	94.74	Fundamental Frequency		peak
2	*	2456.700	87.77	1.05	88.82	Fundamental Frequency		AVG
3		2483.500	48.39	1.17	49.56	74.00	-24.44	peak
4		2483.500	36.86	1.17	38.03	54.00	-15.97	AVG

Emission Level= Read Level+ Correct Factor


EUT:	Action camera	Model:	Explorer S
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Ant. Pol.	Vertical		
Test Mode:	TX G Mode 2462MHz		
Remark:	N/A		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	*	2467.700	84.53	1.10	85.63	Fundamental Frequency		AVG
2	X	2468.000	94.43	1.11	95.54	Fundamental Frequency		peak
3		2483.500	48.47	1.17	49.64	74.00	-24.36	peak
4		2483.500	37.05	1.17	38.22	54.00	-15.78	AVG

Emission Level= Read Level+ Correct Factor


EUT:	Action camera	Model:	Explorer S
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Ant. Pol.	Horizontal		
Test Mode:	TX N(HT20) Mode 2412MHz		
Remark:	N/A		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		2390.000	48.77	0.77	49.54	74.00	-24.46	peak
2		2390.000	36.92	0.77	37.69	54.00	-16.31	AVG
3	*	2418.100	84.34	0.89	85.23	Fundamental Frequency		AVG
4	X	2419.500	93.23	0.89	94.12	Fundamental Frequency		peak

Emission Level= Read Level+ Correct Factor


EUT:	Action camera	Model:	Explorer S
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Ant. Pol.	Vertical		
Test Mode:	TX N(HT20) Mode 2412MHz		
Remark:	N/A		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		2390.000	47.29	0.77	48.06	74.00	-25.94	peak
2		2390.000	34.86	0.77	35.63	74.00	-38.37	peak
3	*	2418.700	92.31	0.89	93.20	Fundamental Frequency		peak
4	X	2419.900	79.17	0.89	80.06	Fundamental Frequency		peak

Emission Level= Read Level+ Correct Factor


EUT:	Action camera	Model:	Explorer S
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Ant. Pol.	Horizontal		
Test Mode:	TX N(HT20) Mode 2462MHz		
Remark:	N/A		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1	*	2456.900	83.16	1.05	84.21	Fundamental Frequency		AVG
2	X	2457.300	92.52	1.05	93.57	Fundamental Frequency		peak
3		2483.500	47.53	1.17	48.70	74.00	-25.30	peak
4		2483.500	35.57	1.17	36.74	54.00	-17.26	AVG

Emission Level= Read Level+ Correct Factor

EUT:	Action camera	Model:	Explorer S
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Ant. Pol.	Vertical		
Test Mode:	TX N(HT20) Mode 2462MHz		
Remark:	N/A		





No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	*	2467.900	80.01	1.10	81.11	Fundamental Frequency		AVG
2	X	2468.900	91.07	1.11	92.18	Fundamental Frequency		peak
3		2483.500	47.82	1.17	48.99	74.00	-25.01	peak
4		2483.500	35.71	1.17	36.88	54.00	-17.12	AVG



Emission Level= Read Level+ Correct Factor

(2) Conducted Test



EUT:	Action camera	Model:	Explorer S
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Test Mode:	TX B Mode 2412MHz / TX B Mode 2462MHz		
Remark:	The EUT is programed in continuously transmitting mode		



EUT:	Action camera	Model:	Explorer S
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Test Mode:	TX G Mode 2412MHz / TX G Mode 2462MHz		
Remark:	The EUT is programed in continuously transmitting mode		



EUT:	Action camera	Model:	Explorer S
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Test Mode:	TX N(HT20) Mode 2412MHz / TX N(HT20) Mode 2462MHz		
Remark:	The EUT is programed in continuously transmitting mode		



7. Bandwidth Test

7.1 Test Standard and Limit


7.1.1 Test Standard

FCC Part 15.247 (a)(2)

7.1.2 Test Limit

FCC Part 15 Subpart C(15.247)/RSS-210		
Test Item	Limit	Frequency Range(MHz)
Bandwidth	≥ 500 KHz (6dB bandwidth)	2400~2483.5

7.2 Test Setup




7.3 Test Procedure

- (1) The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
- (2) The bandwidth is measured at an amplitude level reduced 6dB from the reference level. The reference level is the level of the highest amplitude signal observed from the transmitter at the fundamental frequency. Once the reference level is established, the equipment is conditioned with typical modulating signal to produce the worst -case (i.e the widest) bandwidth.
- (3) Measure the channel separation the spectrum analyzer was set to Resolution Bandwidth:100 kHz, and Video Bandwidth:300 kHz, Detector: Peak, Sweep Time set auto.

7.4 EUT Operating Condition


The EUT was set to continuously transmitting in each mode and low, Digital photo framesdle and high channel for the test.

7.5 Test Data




802.11B Mode

2437 MHz



802.11B Mode

2462 MHz



EUT:	Action camera	Model:	Explorer S
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Test Mode:	TX 802.11G Mode		
Channel frequency (MHz)	6dB Bandwidth (MHz)	99% Bandwidth (MHz)	Limit (MHz)
2412	16.407	16.4833	>=0.5
2437	16.419	16.4856	
2462	16.481	16.4965	
802.11G Mode			
2412 MHz			

Agilent15:54:22 Feb 27, 2017

Ref 15 dBm

Atten 25 dB

#Peak

Log

10

dB/

Offst

1

dB

Center

2.412000000 GHz

Center 2.412 GHz

#Res BW 100 kHz

#VBW 300 kHz

Span 20 MHz

Sweep 4 ms (401 pts)

Occupied Bandwidth

16.4833 MHz

Occ BW % Pwr

99.00 %

x dB

-6.00 dB

Transmit Freq Error


2.970 kHz

x dB Bandwidth

16.407 MHz


802.11G Mode

2437 MHz



802.11G Mode

2462 MHz



EUT:	Action camera	Model:	Explorer S
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Test Mode:	TX 802.11N(HT20) Mode		
Channel frequency (MHz)	6dB Bandwidth (MHz)	99% Bandwidth (MHz)	Limit (MHz)
2412	17.615	17.6258	>=0.5
2437	17.622	17.6222	
2462	17.636	17.6159	
802.11N(HT20) Mode			
2412 MHz			

Agilent15:56:56 Feb 27, 2017

Ref 15 dBm

Atten 25 dB

#Peak

Log

10

dB/

Offst

1

dB

Center

2.412000000 GHz

Center 2.412 GHz

#Res BW 100 kHz

#VBW 300 kHz

Span 20 MHz

Sweep 4 ms (401 pts)

Occupied Bandwidth

17.6258 MHz

Occ BW % Pwr

99.00 %

x dB

-6.00 dB

Transmit Freq Error


-2.759 kHz

x dB Bandwidth

17.615 MHz


802.11N(HT20) Mode

2437 MHz



802.11N(HT20) Mode

2462 MHz



8. Peak Output Power Test

8.1 Test Standard and Limit


8.1.1 Test Standard

FCC Part 15.247 (b)

8.1.2 Test Limit

FCC Part 15 Subpart C(15.247)/RSS-210		
Test Item	Limit	Frequency Range(MHz)
Peak Output Power	1 Watt or 30 dBm	2400~2483.5

8.2 Test Setup



8.3 Test Procedure

The measurement is according to section 9.1.2 of KDB 558074 D01 DTS Meas Guidance v03r05.

The EUT was connected to RF power meter via a broadband power sensor as show the block above. The power sensor video bandwidth is greater than or equal to the DTS bandwidth of the equipment.

8.4 EUT Operating Condition


The EUT was set to continuously transmitting in the max power during the test.

8.5 Test Data


EUT:	Action camera	Model:	Explorer S
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Mode	Channel frequency (MHz)	Test Result (dBm)	Limit (dBm)
802.11b	2412	9.34	30
	2437	9.28	
	2462	9.31	
802.11g	2412	9.12	
	2437	9.08	
	2462	9.15	
802.11n (HT20)	2412	9.09	
	2437	9.13	
	2462	9.06	
Result: PASS			


Duty Cycle		
Mode	Channel frequency (MHz)	Test Result
802.11b	2412	>98%
	2437	
	2462	
802.11g	2412	
	2437	
	2462	
802.11n (HT20)	2412	
	2437	
	2462	
Please see below plots		

802.11 B Mode 2437 MHz



802.11 G Mode 2437 MHz





9. Power Spectral Density Test

9.1 Test Standard and Limit


9.1.1 Test Standard

FCC Part 15.247 (e)

9.1.2 Test Limit

FCC Part 15 Subpart C(15.247)		
Test Item	Limit	Frequency Range(MHz)
Power Spectral Density	8dBm(in any 3 kHz)	2400~2483.5

9.2 Test Setup



9.3 Test Procedure

The EUT was directly connected to the Spectrum Analyzer and antenna output port as show in the block diagram above. The measurement according to section 10.2 of KDB 558074 D01 DTS Meas Guidance v03r05.

- (1) The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
- (2) Set analyser center frequency to DTS channel center frequency.
- (3) Set the span to 1.5 times the DTS bandwidth.
- (4) Set the RBW to: 3 kHz
- (5) Set the VBW to: 10 kHz
- (6) Detector: peak
- (7) Sweep time: auto
- (8) Allow trace to fully stabilize. Then use the peak marker function to determine the maximum amplitude level.

9.4 EUT Operating Condition

The EUT was set to continuously transmitting in each mode and low, Digital photo framesdle and high channel for the test.

9.5 Test Data

EUT:	Action camera	Model:	Explorer S
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Test Mode:	TX 802.11B Mode		
Channel Frequency (MHz)	Power Density (3 kHz/dBm)	Limit (dBm)	
2412	-16.15	8	
2437	-16.73		
2462	-16.43		
802.11B Mode			
2412 MHz			

Agilent16:14:58 Feb 27, 2017

Ref 15 dBmAtten 25 dB

Mkr1 2.4109875 GHz-16.15 dBm

PeakLog10 dB/Offst1 dB

Marker2.410987500 GHz-16.15 dBm


M1 S2S3 FC AA

Center 2.412 GHzSpan 15 MHz

#Res BW 3 kHz#VBW 10 kHzSweep 1.715 s (401 pts)


802.11B Mode

2437 MHz



802.11B Mode

2462 MHz



EUT:	Action camera	Model:	Explorer S
Temperature:	25 °C	Temperature:	25 °C
Test Voltage:	DC 3.7V		
Test Mode:	TX 802.11G Mode		
Channel Frequency (MHz)	Power Density (3 kHz/dBm)	Limit (dBm)	
2412	-20.27	8	
2437	-19.87		
2462	-20.81		
802.11G Mode			
2412 MHz			

Agilent16:18:36 Feb 27, 2017

Ref 15 dBmAtten 25 dB

Mkr1 2.4120000 GHz-20.27 dBm

Peak Log 10 dB/ Offst 1 dB

Marker 2.412000000 GHz -20.27 dBm


M1 S2 S3 FC AA

Center 2.412 GHzSpan 25 MHz

#Res BW 3 kHz#VBW 10 kHzSweep 2.859 s (401 pts)


802.11G Mode


2437 MHz



802.11G Mode


2462 MHz






802.11N(HT20) Mode

2437 MHz



802.11N(HT20) Mode

2462 MHz



10. Antenna Requirement

10.1 Standard Requirement

10.1.1 Standard

FCC Part 15.203

10.1.2 Requirement

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

10.2 Antenna Connected Construction

The directional gains of the antenna used for transmitting is 2.11 dBi, and the antenna de-signed with permanent attachment and no consideration of replacement. Please see the EUT photo for details.

Result

The EUT antenna is a Internal Antenna. It complies with the standard requirement.

Antenna Type
<input checked="" type="checkbox"/> Permanent attached antenna
<input type="checkbox"/> Unique connector antenna
<input type="checkbox"/> Professional installation antenna

-----END OF REPORT-----