

|                                            |          |
|--------------------------------------------|----------|
| <b>GPRS 850-Body Front Low CH128 .....</b> | <b>2</b> |
| <b>GPRS 850-Body Rear Low CH128 .....</b>  | <b>3</b> |
| <b>GPRS 1900-Body Front Low CH512.....</b> | <b>4</b> |
| <b>GPRS 1900-Body Rear Low CH512 .....</b> | <b>5</b> |

Test Laboratory: Compliance Certification Services Inc.

Date: 12/25/2015

**GPRS 850-Body Front Low CH128****DUT: Gnss data collector; Type: K2 series; Serial: N/A**

Communication System: UID 0, Generic GSM (0); Communication System Band: GSM850; Frequency: 824.2 MHz; Duty Cycle: 1:4.15911

Medium parameters used (interpolated):  $f = 824.2$  MHz;  $\sigma = 0.944$  S/m;  $\epsilon_r = 55.694$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Room Ambient Temperature: 22°C; Liquid Temperature: 21.5°C

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3798; ConvF(8.87, 8.87, 8.87); Calibrated: 7/24/2015;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1245; Calibrated: 7/22/2015
- Phantom: Twin SAM Phantom; Type: QD 000 P40 CD; Serial: 1609
- DASY52 52.8.8(1222);
- SEMCAD X Version 14.6.10 (7331)

**GPRS 850/Body Front Low CH128/Area Scan (11x9x1):** Measurement grid: dx=15mm, dy=15mm[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.0129 W/kg


**GPRS 850/Body Front Low CH128/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 1.071 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 0.0180 W/kg

**SAR(1 g) = 0.010 W/kg; SAR(10 g) = 0.00616 W/kg**[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.0131 W/kg



0 dB = 0.0131 W/kg = -18.83 dBW/kg

Test Laboratory: Compliance Certification Services Inc.

Date: 12/25/2015

**GPRS 850-Body Rear Low CH128****DUT: Gnss data collector; Type: K2 series; Serial: N/A**

Communication System: UID 0, Generic GSM (0); Communication System Band: GSM850; Frequency: 824.2 MHz; Duty Cycle: 1:4.15911

Medium parameters used (interpolated):  $f = 824.2$  MHz;  $\sigma = 0.944$  S/m;  $\epsilon_r = 55.694$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Room Ambient Temperature: 22°C; Liquid Temperature: 21.5°C

Phantom section: Flat Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3798; ConvF(8.87, 8.87, 8.87); Calibrated: 7/24/2015;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1245; Calibrated: 7/22/2015
- Phantom: Twin SAM Phantom; Type: QD 000 P40 CD; Serial: 1609
- DASY52 52.8.8(1222);
- SEMCAD X Version 14.6.10 (7331)

**GPRS 850/Body Rear Low CH128/Area Scan (13x9x1):** Measurement grid: dx=15mm, dy=15mm[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.0482 W/kg


**GPRS 850/Body Rear Low CH128/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 1.545 V/m; Power Drift = 0.16 dB

Peak SAR (extrapolated) = 0.0710 W/kg

**SAR(1 g) = 0.042 W/kg; SAR(10 g) = 0.025 W/kg**[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.0562 W/kg



0 dB = 0.0562 W/kg = -12.50 dBW/kg

Test Laboratory: Compliance Certification Services Inc.

Date: 12/25/2015

**GPRS 1900-Body Front Low CH512****DUT: Gns data collector; Type: K2 series; Serial: N/A**

Communication System: UID 0, Generic GSM (0); Communication System Band: GSM1900; Frequency: 1850.2 MHz; Duty Cycle: 1:4.15911

Medium parameters used (interpolated):  $f = 1850.2$  MHz;  $\sigma = 1.485$  S/m;  $\epsilon_r = 51.753$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Room Ambient Temperature: 22°C; Liquid Temperature: 21.5°C

Phantom section: Flat Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3798; ConvF(7.29, 7.29, 7.29); Calibrated: 7/24/2015;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1245; Calibrated: 7/22/2015
- Phantom: Twin SAM Phantom; Type: QD 000 P40 CD; Serial: 1609
- DASYS 52.8.8(1222);
- SEMCAD X Version 14.6.10 (7331)

**GPRS 1900/Body Front Low CH512/Area Scan (11x9x1):** Measurement grid: dx=15mm, dy=15mm[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.0784 W/kg


**GPRS 1900/Body Front Low CH512/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 2.795 V/m; Power Drift = 0.14 dB

Peak SAR (extrapolated) = 0.109 W/kg

**SAR(1 g) = 0.055 W/kg; SAR(10 g) = 0.030 W/kg**[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.0805 W/kg



0 dB = 0.0805 W/kg = -10.94 dBW/kg

Test Laboratory: Compliance Certification Services Inc.

Date: 12/25/2015

**GPRS 1900-Body Rear Low CH512****DUT: Gns data collector; Type: K2 series; Serial: N/A**

Communication System: UID 0, Generic GSM (0); Communication System Band: GSM1900; Frequency: 1850.2 MHz; Duty Cycle: 1:4.15911

Medium parameters used (interpolated):  $f = 1850.2$  MHz;  $\sigma = 1.485$  S/m;  $\epsilon_r = 51.753$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Room Ambient Temperature: 22°C; Liquid Temperature: 21.5°C

Phantom section: Flat Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3798; ConvF(7.29, 7.29, 7.29); Calibrated: 7/24/2015;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1245; Calibrated: 7/22/2015
- Phantom: Twin SAM Phantom; Type: QD 000 P40 CD; Serial: 1609
- DASYS 52.8.8(1222);
- SEMCAD X Version 14.6.10 (7331)

**GPRS 1900/Body Rear Low CH512/Area Scan (11x9x1):** Measurement grid: dx=15mm, dy=15mm[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.202 W/kg


**GPRS 1900/Body Rear Low CH512/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 6.328 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 0.336 W/kg

**SAR(1 g) = 0.159 W/kg; SAR(10 g) = 0.079 W/kg**[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.243 W/kg



0 dB = 0.243 W/kg = -6.14 dBW/kg