

FCC TEST REPORT for Shenzhen lianshunwei Technology Co., Ltd

Portable mini speaker Model No.: T-2306A, Z-2306A, BS-306

Prepared for : Shenzhen lianshunwei Technology Co., Ltd

Address : the 2rd floor, Building B, Guotai Industry park, Xintang village,

Guanlan Town, Bao'an District Shenzhen China

Prepared By : Shenzhen Anbotek Compliance Laboratory Limited

Address : 1/F., Building 1, SEC Industrial Park, No.0409 Qianhai Road,

Nanshan District, Shenzhen, Guangdong, China

Tel: (86) 755-26066544 Fax: (86) 755-26014772

Report Number : R011610128I

Date of Test : Oct. 14~ Nov. 02, 2016

Date of Report : Nov. 03, 2016



TABLE OF CONTENTS

Description

Page Test Report 1. GENERAL INFORMATION......5 2. TEST PROCEDURE......7 3. CONDUCTED EMISSION...... 8 3.1 Block Diagram of Test Setup...... 4.4 Test Results 16 5. CHANNEL SEPARATION TEST......25 5.4 Test Results 26 6.4 Test Results 28



8.1 Measurement Procedure	32
8.2 Test SET-UP	
8.3 Test Equipment	
8.4 Test Results	
9. MAX IMUM PEAK OUTPUT POWER TEST	34
9.1 Measurement Procedure	32
9.2 Test SET-UP	32
9.3 Test Equipment	
9.4 Test Results	35
10. BAND EDGE TEST	37
10.1 Measurement Procedure	37
10.2 Test SET-UP	
10.3 Test Equipment	
10.4 Test Results	38
11. ANTENNA APPLICATION	42
11.1 Antenna requirement	42
11.2 Result	
12. PHOTOGRAPH	43
12.1 Photo of Power Line Conducted Emission Measurement	
12.2 Photo of Radiation Emission Test.	
APPENDIX I (EXTERNAL PHOTOS)	
APPENDIX II (INTERNAL PHOTOS)	
ALLENDIA II (IIALENIAL LIIO 103)	シ•••••• 45



TEST REPORT

Applicant : Shenzhen lianshunwei Technology Co., Ltd : Shenzhen lianshunwei Technology Co., Ltd

EUT : Portable mini speaker

Model No. : T-2306A, Z-2306A, BS-306

Serial No. : N.A.
Trade Mark : N.A.

Rating : Input DC 5V, 500mA (via battery DC 3.7V, 500mAh inside)

Measurement Procedure Used:

FCC Part15 Subpart C 2016, Paragraph 15.207, 15.247 & 15.209

The device described above is tested by Shenzhen Anbotek Compliance Laboratory Limited to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. The measurement results are contained in this test report and Shenzhen Anbotek Compliance Laboratory Limited is assumed full of responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT (Equipment Under Test) is technically compliant with the FCC Part 15 Subpart C requirements.

This report applies to above tested sample only and shall not be reproduced in part without written approval of Shenzhen Anbotek Compliance Laboratory Limited.

Date of Test:	Oct. 14~ Nov. 02, 2016				
Prepared by :	Janon Wen.				
	(Tested Engineer / Baron Wen)				
Reviewer:	Amy Ding				
	(Project Manager / Amy Ding)				
Approved & Authorized Signer:	Ton Chen				
-	(Manager / Tom Chen)				



1. GENERAL INFORMATION

1.1 Description of Device (EUT)

EUT : Portable mini speaker

Model Number : T-2306A, Z-2306A, BS-306

(Note: All samples are the same except the model number and

colour, so we prepare "T-2306A" for test only.)

Test Power Supply: AC 120V, 60Hz for adapter/

AC 240V, 60Hz for adapter/DC 3.7V Battery inside

Frequency: 2402~2480MHz

Antenna: 1dBi

Specification

Modulation : GFSK, $\pi/4$ DQPSK, 8DPSK

Applicant : Shenzhen lianshunwei Technology Co., Ltd

Address : the 2rd floor, Building B, Guotai Industry park, Xintang village,

Guanlan Town, Bao'an District Shenzhen China

Manufacturer : Shenzhen lianshunwei Technology Co., Ltd

Address : the 2rd floor, Building B, Guotai Industry park, Xintang village,

Guanlan Town, Bao'an District Shenzhen China

Factory : Shenzhen lianshunwei Technology Co., Ltd

Address : the 2rd floor, Building B, Guotai Industry park, Xintang village,

Guanlan Town, Bao'an District Shenzhen China

Date of receipt : Oct. 14, 2016

Date of Test : Oct. 14~ Nov. 02, 2016



1.2 Auxiliary Equipment Used during Test

Adapter : Manufacturer: ZTE

M/N: STC-A2050I1000USBA-C

S/N: 201202102100876

Input: 100-240V~50/60Hz 0.3A Output: DC 5V, 1000mA

Mobile Phone : Manufacturer: HUAWEI

M/N: C8650

S/N: L6W7NA11B1013157

CE, FCC, DOC

1.3 Description of Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

FCC-Registration No.: 752021

Shenzhen Anbotek Compliance Laboratory Limited, EMC Laboratory has been registed and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 752021, July 06, 2016.

IC-Registration No.: 8058A-1

Shenzhen Anbotek Compliance Laboratory Limited., EMC Laboratory has been registered and fully described in a report filed with the (IC) Industry Canada. The acceptance letter from the IC is maintained in our files. Registration 8058A, Jun. 13, 2016.

Test Location

All Emissions tests were performed at

Shenzhen Anbotek Compliance Laboratory Limited. at 1/F., Building 1, SEC Industrial Park, No.0409 Qianhai Road, Nanshan District, Shenzhen, Guangdong, China

1.4 Measurement Uncertainty

Radiation Uncertainty : Ur = 4.1 dB (Horizontal)

Ur = 4.3 dB (Vertical)

Conduction Uncertainty : Uc = 3.4dB



2. Test Procedure

GENERAL: This report shall NOT be reproduced except in full without the written approval of Shenzhen Anbotek Compliance Laboratory Limited. The EUT was transmitting a test signal during the testing.

RADIATION INTERFERENCE: The test procedure used was ANSI STANDARD C63.10-2013 using a spectrum analyzer with a pre-selector. The analyzer was calibrated in dB above a microvolt at the output of the antenna. The resolution bandwidth was 100KHz and the video bandwidth was 300KHz up to 1.0GHz and 1.0MHz with a video BW of 3.0MHz above 1.0GHz. The ambient temperature of the EUT was 74.3oF with a humidity of 69%.

FORMULA OF CONVERSION FACTORS: The Field Strength at 3m was established by adding the meter reading of the spectrum analyzer (which is set to read in units of dBuV) to the antenna correction factor supplied by the antenna manufacturer. The antenna correction factors are stated in terms of dB. The gain of the Preselector was accounted for in the Spectrum Analyzer Meter Reading.

Example:

ANSI STANDARD C63.10-2013 10.1.7 MEASUREMENT PROCEDURES: The EUT was placed on a table 80 cm high and with dimensions of 1m by 1.5m. The EUT was placed in the center of the table (1.5m side). The table used for radiated measurements is capable of continuous rotation.


When an emission was found, the table was rotated to produce the maximum signal strength. At this point, the antenna was raised and lowered from 1m to 4m. The antenna was placed in both the horizontal and vertical planes.



3. Conducted Emission

3.1 Block Diagram of Test Setup

3.1.1. Block diagram of connection between the EUT and simulators



3.2 Power Line Conducted Emission Measurement Limits (15.207)

Frequency	Limits dB(μV)		
MHz	Quasi-peak Level	Average Level	
0.15 ~ 0.50	66 ~ 56*	56 ~ 46*	
0.50 ~ 5.00	56	46	
5.00 ~ 30.00	60	50	

Notes: 1. *Decreasing linearly with logarithm of frequency.

2. The lower limit shall apply at the transition frequencies.

3.3 Configuration of EUT on Measurement

The following equipments are installed on Power Line Conducted Emission Measurement to meet the commission requirement and operating regulations in a manner which tends to maximize its emission characteristics in a normal application.

3.4 Operating Condition of EUT

- 3.4.1. Setup the EUT and simulator as shown as Section 3.1.
- 3.4.2. Turn on the power of all equipment.
- 3.4.3. Let the EUT work in test mode (Charge+BT Mode) and measure it.



3.5 Test Procedure

The EUT system is connected to the power mains through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm coupling impedance for the EUT system. Please refer the block diagram of the test setup and photographs. Both sides of AC line are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to FCC ANSI C63.10-2013 on Conducted Emission Measurement.

The bandwidth of test receiver (ESCI) set at 9KHz.

The frequency range from 150KHz to 30MHz is checked.

The test results are reported on Section 3.6.

Test Equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Two-Line V-network	Rohde & Schwarz	ENV216	100055	Apr. 16, 2016	1 Year
	V-IICTWOIK					
2.	EMI Test Receiver	Rohde & Schwarz	ESCI	100627	Apr. 16, 2016	1 Year
3.	RF Switching Unit	Compliance Direction	RSU-M2	38303	Apr. 16, 2016	1 Year

3.6 Power Line Conducted Emission Measurement Results **PASS.**

The frequency range from 150KHz to 30 MHz is investigated.

Please refer the following pages.




Test Site: 1# Shielded Room Operating Condition: Charge+BT Mode

Test Specification: AC 120V, 60Hz for adapter

Comment: Live Line

Tem.:25°C Hum.:50%



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit dBuV	Over Limit (dB)	Detector	Remark
1	0.1660	14.75	20.00	34.75	55.15	-20.40	AVG	
2	0.1700	35.37	20.00	55.37	64.96	-9.59	QP	
3	0.3140	22.95	20.00	42.95	59.86	-16.91	QP	
4	0.4140	5.20	20.00	25.20	47.57	-22.37	AVG	
5	0.4300	17.58	20.00	37.58	57.25	-19.67	QP	
6	0.6300	14.11	20.00	34.11	56.00	-21.89	QP	
7	0.6419	3.05	20.00	23.05	46.00	-22.95	AVG	
8	1.0100	12.37	20.00	32.37	56.00	-23.63	QP	
9	1.2780	0.54	20.00	20.54	46.00	-25.46	AVG	
10	1.6340	-0.13	20.00	19.87	46.00	-26.13	AVG	
11	2.0420	-0.19	20.00	19.81	46.00	-26.19	AVG	
12	2.6300	12.47	20.00	32.47	56.00	-23.53	QP	




Test Site: 1# Shielded Room Operating Condition: Charge+BT Mode

Test Specification: AC 120V, 60Hz for adapter

Comment: Neutral Line

Tem.:25°C Hum.:50%






Test Site: 1# Shielded Room Operating Condition: Charge+BT Mode

Test Specification: AC 240V, 60Hz for adapter

Comment: Live Line



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit dBuV	Over Limit (dB)	Detector	Remark
1	0.2340	15.80	20.00	35.80	52.30	-16.50	AVG	
2	0.3379	24.41	20.00	44.41	59.25	-14.84	QP	
3	0.3379	11.12	20.00	31.12	49.25	-18.13	AVG	
4	0.4700	8.89	20.00	28.89	46.51	-17.62	AVG	
5	0.4740	22.80	20.00	42.80	56.44	-13.64	QP	
6	0.6300	9.83	20.00	29.83	46.00	-16.17	AVG	
7	0.6340	19.95	20.00	39.95	56.00	-16.05	QP	
8	0.8340	20.70	20.00	40.70	56.00	-15.30	QP	
9	0.9500	6.43	20.00	26.43	46.00	-19.57	AVG	
10	1.5060	20.43	20.00	40.43	56.00	-15.57	QP	
11	1.5060	5.65	20.00	25.65	46.00	-20.35	AVG	
12	2.0500	19.27	20.00	39.27	56.00	-16.73	QP	




Test Site: 1# Shielded Room Operating Condition: Charge+BT Mode

Test Specification: AC 240V, 60Hz for adapter

Comment: Neutral Line

Tem.:25°C Hum.:50%





4. Radiation Interference

4.1 Requirements (15.247, 15.209):

4.1.1. Test Limits (< 30 MHZ)

Frequency	Field Strength	Measurement Distance	
(MHz)	(microvolts/meter)	(meter)	
0.009-0.490	2400/F(kHz)	300	
0.490-1.705	24000/F(kHz)	30	
1.705-30.0	30	30	

4.1.2. Test Limits (\geq 30 MHZ)

FIELD STRENGTH	FIELD STRENGTH	S15.209	
of Fundamental:	of Harmonics	30 - 88 MHz	40 dBuV/m
@3M			
902-928 MHZ		88 - 216 MHz	43.5
2.4-2.4835 GHz		216 - 960 MHz	46
94 dBμV/m @3m	$54 \text{ dB}\mu\text{V/m} @3\text{m}$	ABOVE 960 MHz	54dBuV/m

For range 9KHz~30MHz, The measured value is really too low to be recorded.

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in 15.209, whichever is the lesser attenuation.

4.2 Test Procedure

For below 1GHz: The EUT is placed on a turntable, which is 0.8m above the ground plane. For above 1GHz: The EUT is placed on a turntable, which is 1.5m above the ground plane. The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT is set 3 meters away from the receiving antenna which is mounted on a antenna tower. The antenna can be moved up and down from 1 to 4 meters to find out the maximum emission level. Rotated the EUT through three orthogonal axes to determine the maximum emissions, both horizontal and vertical polarization of the antenna are set on test. The EUT is tested in 9*6*6 Chamber. The device is evaluated in xyz orientation.

For 30MHz to 1000MHz:

Set the spectrum analyzer as: RBW = 100kHz, VBW =300kHz, Detector= Quasi-Peak Trace mode= Max hold. Sweep- auto couple.

For Above 1GHz:

Set the spectrum analyzer as: RBW = 1MHz, VBW =3MHz, Detector= Peak Trace mode= Max hold. Sweep- auto couple.




Set the spectrum analyzer as: RBW =1MHz, VBW =10Hz Detector= Average Trace mode= Max hold. Sweep- auto couple.

Test Equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Spectrum Analysis		E4407B	US39390582	Apr. 16, 2016	1 Year
2.	Preamplifier Preamplifier	Instruments corporation	EMC01183		Apr. 16, 2016	1 Year
3.	EMI Test Receiver	Rohde & Schwarz	ESPI	101604	Apr. 16, 2016	1 Year
4.	Double Ridged Horn Antenna	Instruments corporation	GTH-0118	351600	Apr. 19, 2016	1 Year
5.	Bilog Broadband Antenna	Schwarzbeck	VULB9163	VULB 9163-289	Apr. 19, 2016	1 Year
6.	Pre-amplifier	SONOMA	310N	186860	Apr. 16, 2016	1 Year
7.	EMI Test Software EZ-EMC	SHURPLE	N/A	N/A	N/A	N/A
8	Power Sensor	DAER	RPR3006 W	15I00041SN0 46	Jun 30, 2016	1 Year
9	MXA Spectrum Analysis	Agilent	N9020A	MY51170037	Jun 30, 2016	1 Year
10	MXG RF Vector Signal Generator	Agilent	N5182A	MY48180656	Jun 30, 2016	1 Year
11	Signal Generator	Agilent	E4421B	MY41000743	Jun 30, 2016	1 Year
12	DC Power supply	IV	IV-8080	YQSB0096	Jun 30, 2016	1 Year
13	TEMP&HUMI PROGRAMMAB LE CHAMBER	Bell Group	BE-THK-1 50M8	SE-0137	Mar. 16, 2016	1 Year


4.3 Test Configuration

4.3.1. 9k to 30MHz emissions:






4.3.2. 30M to 1G emissions:



4.3.3. 1G to 40G emissions:



4.4 Test Results

PASS.

The EUT was tested on (Charge+BT Mode, Charge+AUX Mode, Charge+TF Mode, Charge+USD Mode) modes, only the worst data of (Charge+TF Mode) is attached in the following pages.

Only the worst case (x orientation).

The EDR was tested on $(\pi/4DQPSK, 8DPSK)$ modes, only the worst data of $(\pi/4DQPSK)$ is attached in the following pages.

The test results of above 18000MHz are attenuated more than 20dB below the permissible limits, so the results don't record in the report.




Job No.: 011610128I Polarization: Horizontal

Standard: (RE)FCC PART 15C _3m Power Source: AC 120V, 60Hz for adapter

Test item: Radiation Test (30~1000MHz) Temp.(C)/Hum.(%RH): 24.3(C)/55%RH

Test Mode: Charge+TF Mode Distance: 3m






Job No.: 011610128I Polarization: Vertical

Standard: (RE)FCC PART 15C _3m Power Source: AC 120V, 60Hz for adapter

Test item: Radiation Test (30~1000MHz) Temp.(C)/Hum.(%RH): 24.3(C)/55%RH

Test Mode: Charge+TF Mode Distance: 3m






Job No.: 011610128I Polarization: Horizontal

Standard: (RE)FCC PART 15C_Class B_3m Power Source: DC 3.7V

Test item: Radiation Test (Above 1GHz) Temp.(C)/Hum.(%RH): 24.3(C)/55%RH

Test Mode: TX(2402 MHz) Distance: 3m






Job No.: 011610128I Polarization: Vertical

Standard: (RE)FCC PART 15C_Class B_3m Power Source: DC 3.7V

Test item: Radiation Test (Above 1GHz) Temp.(C)/Hum.(%RH): 24.3(C)/55%RH

Test Mode: TX(2402 MHz) Distance: 3m






Job No.: 011610128I Horizontal **Polarization:**

Standard: (RE)FCC PART 15C_Class B_3m **Power Source: DC 3.7V**

Test item: **Radiation Test (Above 1GHz)** Temp.(C)/Hum.(%RH): 24.3(C)/55%RH

Test Mode: TX(2441 MHz) **Distance:** 3m






Job No.: 011610128I Polarization: Vertical

Standard: (RE)FCC PART 15C_Class B_3m Power Source: DC 3.7V

Test item: Radiation Test (Above 1GHz) Temp.(C)/Hum.(%RH): 24.3(C)/55%RH

Test Mode: TX(2441 MHz) Distance: 3m






Job No.: 011610128I Polarization: Horizontal

Standard: (RE)FCC PART 15C_Class B_3m Power Source: DC 3.7V

Test item: Radiation Test (Above 1GHz) Temp.(C)/Hum.(%RH): 24.3(C)/55%RH

Test Mode: TX(2480 MHz) Distance: 3m






Job No.: 011610128I Polarization: Vertical

Standard: (RE)FCC PART 15C_Class B_3m Power Source: DC 3.7V

Test item: Radiation Test (Above 1GHz) Temp.(C)/Hum.(%RH): 24.3(C)/55%RH

Test Mode: TX(2480 MHz) Distance: 3m





5. CHANNEL SEPARATION TEST

5.1 Measurement Procedure

The EUT must have its hopping function enabled. Using the following spectrum analyzer settings:

- 1. Span= Wide enough to capture the peaks of two adjacent channels
- 2. Set the RBW = 100 kHz.
- 3. Set the VBW = 1.0 MHz.
- 4. Sweep time = auto couple.
- 5. Detector function = peak.
- 6. Trace mode = \max hold.
- 7. Allow trace to fully stabilize.

5.2 Test SET-UP

EUT Spectrum analyzer

5.3 Test Equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Spectrum Analysis	Agilent	E4407B	US39390582	Apr. 16, 2016	1 Year
2.	Preamplifier	Instruments corporation	EMC01183 0	980100	Apr. 16, 2016	1 Year
3.	EMI Test Receiver	Rohde & Schwarz	ESPI	101604	Apr. 16, 2016	1 Year
4.	Double Ridged Horn Antenna	Instruments corporation	GTH-0118	351600	Apr. 19, 2016	1 Year
5.	Bilog Broadband Antenna	Schwarzbeck	VULB9163	VULB 9163-289	Apr. 19, 2016	1 Year
6.	Pre-amplifier	SONOMA	310N	186860	Apr. 16, 2016	1 Year
7.	EMI Test Software EZ-EMC	SHURPLE	N/A	N/A	N/A	N/A
8	Power Sensor	DAER	RPR3006 W	15I00041SN0 46	Jun 30, 2016	1 Year
9	MXA Spectrum Analysis	Agilent	N9020A	MY51170037	Jun 30, 2016	1 Year
10	MXG RF Vector Signal Generator	Agilent	N5182A	MY48180656	Jun 30, 2016	1 Year
11	Signal Generator	Agilent	E4421B	MY41000743	Jun 30, 2016	1 Year
12	DC Power supply	IV	IV-8080	YQSB0096	Jun 30, 2016	1 Year
13	TEMP&HUMI PROGRAMMAB LE CHAMBER	Bell Group	BE-THK-1 50M8	SE-0137	Mar. 16, 2016	1 Year



5.4 Test Results

Test Item : Frequency Separation Test Mode : CH Low ~ CH High

Test Voltage : DC 3.7V Temperature : 24° C Test Result : PASS Humidity : 55%RH

Channel	Frequency	Separation Read	Limit	Modulation
Chamici	(MHz)	Value (kHz)	(kHz)	Mode
Low	2402	1002	927.3	BDR
Mid	2441	1002	919.9	BDR
High	2480	1002	928.3	BDR
Low	2402	1002	844.7	EDR
Mid	2441	1002	840.7	EDR
High	2480	1002	840.7	EDR

Remark:

- 1. The limit of mode (EDR) is 2/3 of 20dB BW;
- 2. The EDR was tested on $(\pi/4DQPSK, 8DPSK)$ modes, only the worst data of $(\pi/4DQPSK)$ is attached in the following pages.







6. 20DB BANDWIDTH TEST

6.1 Measurement Procedure

Using the following spectrum analyzer settings:

- 1. Span= approximately 2 to 3 times the 20dB bandwidth, centered on a hopping channel.
- 2. Set the RBW = 30 kHz.
- 3. Set the VBW = 100 kHz.
- 4. Sweep time = auto couple.
- 5. Detector function = peak.
- 6. Trace mode = max hold.
- 7. Allow trace to fully stabilize.

6.2 Test SET-UP

EUT Spectrum analyzer

6.3 Test Equipment

Same as the equipment listed in 5.3.

6.4 Test Results

Test Item : 20dB BW Test Mode : CH Low ~ CH High

Test Voltage : DC 3.7V Temperature : 24° C Test Result : PASS Humidity : 55%RH

Channel	Frequency (MHz)	20dB Down BW(kHz)	Modulation Mode
Low	2402	927.3	BDR
Mid	2441	919.9	BDR
High	2480	928.3	BDR
Low	2402	1267.0	EDR
Mid	2441	1261.0	EDR
High	2480	1261.0	EDR

Remark: The EDR was tested on (π /4DQPSK, 8DPSK) modes, only the worst data of (π /4DQPSK) is attached in the following pages.







7. QUANTITY OF HOPPING CHANNEL TEST

7.1 Measurement Procedure

The EUT must have its hopping function enabled. Using the following spectrum analyzer setting:

- 1. Span= the frequency band of operation
- 2. Set the RBW = 1 MHz.
- 3. Set the VBW = 1 MHz.
- 4. Sweep time = auto couple.
- 5. Detector function = peak.
- 6. Trace mode = max hold.
- 7. Allow trace to fully stabilize.

7.2 Test SET-UP

EUT Spectrum analyzer

7.3 Test Equipment

Same as the equipment listed in 5.3.

7.4 Test Results


Test Item : Number of Hopping Test Mode : CH Low ~ CH High

Frequency

Test Voltage : DC 3.7V Temperature : 24° C Test Result : PASS Humidity : 55° RH

Hopping Channel	Quantity of Hopping	Quantity of Hopping
Frequency Range	Channel	Channel
2402-2480	79	>15







8. DWELL TIME TEST

8.1 Measurement Procedure

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

- 1. Span= zero span, centered on a hopping channel
- 2. Set the RBW = 1 MHz.
- 3. Set the VBW = 1 MHz.
- 4. Sweep time = as necessary to capture the entire dwell time per hopping channel.
- 5. Detector function = peak.
- 6. Trace mode = max hold.
- 7. Allow trace to fully stabilize.
- 8.2 Test SET-UP

EUT Spectrum analyzer

8.3 Test Equipment

Same as the equipment listed in 5.3.

8.4 Test Results


Test Item : Time of Occupancy Test Mode : CH Low ~ CH High

Test Voltage : DC 3.7V Temperature : 24° C Test Result : PASS Humidity : 55%RH

Package Type	Pulse width (ms)	Time slot length(ms)	Dwell time (ms)	Limit (s)	Modulation
DH1	0.374	time slot length *1600/2 /79 * 31.6	119.68	0.4	BDR
DH3	1.610	time slot length *1600/4 /79 * 31.6	257.60	0.4	BDR
DH5	2.878	time slot length *1600/6 /79 * 31.6	306.99	0.4	BDR
DH1	0.364	time slot length *1600/2 /79 * 31.6	116.48	0.4	EDR
DH3	1.620	time slot length *1600/4 /79 * 31.6	259.20	0.4	EDR
DH5	2.855	time slot length *1600/6 /79 * 31.6	304.53	0.4	EDR

Remark: The EDR was tested on (π /4DQPSK, 8DPSK) modes, only the worst data of (π /4DQPSK) is attached in the following pages.







9. MAX IMUM PEAK OUTPUT POWER TEST

9.1 Measurement Procedure

- a. Check the calibration of the measuring instrument(SA) using either an internal calibrator or a known signal from an external generator.
- b. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
- c. The center frequency of the spectrum analyzer is set to the fundamental frequency and using proper RBW and VBW setting.
- d. Measure the captured power within the band and recording the plot.
- e. Repeat above procedures until all frequencies required were complete.

Using the following spectrum analyzer settings:

- 1. Span= approximately 5 times the 20dB bandwidth, centered on a hopping channel
- 2. Set the RBW = 3 MHz.
- 3. Set the VBW = 3 MHz.
- 4. Sweep time = auto couple.
- 5. Detector function = peak.
- 6. Trace mode = max hold.
- 7. Allow trace to fully stabilize.

9.2 Test SET-UP



9.3 Test Equipment

Same as the equipment listed in 5.3.



9.4 Test Results

Test Item : Max. peak output power Test Mode : CH Low ~ CH High

Test Voltage : DC 3.7V Temperature : 24° C Test Result : PASS Humidity : 55° RH

Channel Frequency (MHz)	Peak Power output(mW)	Peak Power output(dBm)	Peak Power Limit(mW)	Results	Modulation
2402	0.929	-0.320	1000	PASS	BDR
2441	0.940	-0.269	1000	PASS	BDR
2480	1.062	0.262	1000	PASS	BDR
2402	0.919	-0.366	125	PASS	EDR
2441	0.941	-0.266	125	PASS	EDR
2480	1.045	0.193	125	PASS	EDR

Remark: The EDR was tested on (π /4DQPSK, 8DPSK) modes, only the worst data of (π /4DQPSK) is attached in the following pages.







10. BAND EDGE TEST


10.1 Measurement Procedure

- A) Conducted Emission method:
- 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- 2. Position the EUT without connection to measurement instrument. Put it on the Rotated table and turn on the EUT and make it operate in transmitting mode. Then set it to low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.
- 3. Set both RBW and VBW of spectrum analyzer to 100kHz with a convenient frequency span including 100kHz bandwidth from band edge,
- 4. Measurement the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
- 5. Report above procedures until all measured frequencies were complete.

B) Radiated Emission method:

The EUT is placed on a turn table which is 1.5 meter high above the ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT is set 3 meters away from the receiving antenna which is mounted on a antenna tower. The antenna can be moved up and down from 1 to 4 meters to find out the maximum emission level. Rotated the EUT through three orthogonal axes to determine the maximum emissions, both horizontal and vertical polarization of the antenna are set on test. The EUT is tested in 9*6*6 Chamber. for Radiated emissions restricted band RBW= 1 MHz, VBW= 3 MHz.

10.2 Test SET-UP





10.3 Test Equipment

Same as the equipment listed in 5.3.

10.4 Test Results

Pass.

Please refer the following data.


Test Item : Band eadge : CH Low ~ CH High

Test Voltage : DC 3.7V Temperature : 24° C Test Result : PASS Humidity : 55° RH

For Hopping Mode:

Remark: The EDR was tested on $(\pi/4DQPSK, 8DPSK)$ modes, only the worst data of $(\pi/4DQPSK)$ is attached in the following pages.







Test Item : Band eadge : CH Low ~ CH High

Test Voltage : DC 3.7V Temperature : 24° C Test Result : PASS Humidity : 55° RH

For Non-Hopping Mode:

1. Conducted Test

Frequency	Peak Power	Emission read	Result of Band	Band edge	Modulation
(MHz)	Output(dBm)	Value(dBm)	edge(dBc)	Limit(dBc)	
<2400	-0.338	-39.811	39.473	>20dBc	BDR
	-0.752	-30.876	30.124	>20dBc	EDR
>2483.5	0.258	-53.813	54.071	>20dBc	BDR
	-0.208	-52.118	51.910	>20dBc	EDR


2. Radiated emission Test

Frequency (MHz)	Antenna polarization	Emission (dBuV/m)		Band edge Limit (dBuV/m)		Modulation
(141112)	(H/V)	PK	AV	PK	AV	Wiodulation
<2400	V	50.23	38.09	74.00	54.00	BDR
	V	52.46	40.11	74.00	54.00	EDR
>2483.5	V	51.12	41.25	74.00	54.00	BDR
	V	49.87	37.68	74.00	54.00	EDR

Frequency	Antenna	Emission		Band edge Limit		
(MHz)	polarization	(dBuV/m)		(dBuV/m)		Modulation
	(H/V)	PK	AV	PK	AV	
<2400	Н	48.90	37.89	74.00	54.00	BDR
	Н	50.67	40.33	74.00	54.00	EDR
>2483.5	Н	49.78	39.67	74.00	54.00	BDR
	Н	48.03	38.93	74.00	54.00	EDR

Remark: The EDR was tested on (π /4DQPSK, 8DPSK) modes, only the worst data of (π /4DQPSK) is attached in the following pages.







11. ANTENNA APPLICATION

11.1 Antenna requirement


The EUT'S antenna is met the requirement of FCC part 15C section 15.203 and 15.247.

FCC part 15C section 15.247 requirements:

Systems operating in the 2402-2480MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum peak output power of the intentional radiator is reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.


11.2 Result

The EUT's antenna used a PCB Antenna, The antenna's gain is 1dBi and meets the requirement.






12. PHOTOGRAPH






12.2 Photo of Radiation Emission Test











APPENDIX I (EXTERNAL PHOTOS)








4. Figure







6. Figure
The EUT- Right View











APPENDIX II (INTERNAL PHOTOS)










5. Figure PCB of the EUT-Front View



6. Figure PCB of the EUT-Back View

