



TEST REPORT

No. I17D00262-SRD04

For

Client : Shanghai Sunmi Technology Co.,Ltd.

Production : POS System

Model Name : W5920

FCC ID: 2AH25V1SNFC

Hardware Version: 2.0

Software Version: 1.1.0

Issued date: 2018-01-12

Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of ECIT Shanghai.

Test Laboratory:

ECIT Shanghai, East China Institute of Telecommunications

Add: 7-8F, G Area, No.668, Beijing East Road, Huangpu District, Shanghai, P. R. China

Tel: (+86)-021-63843300, E-Mail: welcome@ecit.org.cn

Revision Version

Report Number	Revision	Date	Memo
I17D00262-SRD04	00	2018-01-12	Initial creation of test report

CONTENTS

1.	TEST LABORATORY	4
1.1.	TESTING LOCATION	4
1.2.	TESTING ENVIRONMENT	4
1.3.	PROJECT DATA	4
1.4.	SIGNATURE	4
2.	CLIENT INFORMATION	5
2.1.	APPLICANT INFORMATION	5
2.2.	MANUFACTURER INFORMATION	5
3.	EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE)	6
3.1.	ABOUT EUT	6
3.2.	INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST	6
3.3.	INTERNAL IDENTIFICATION OF AE USED DURING THE TEST	6
3.4.	STATEMENTS.....	6
4.	REFERENCE DOCUMENTS.....	7
4.1.	REFERENCE DOCUMENTS FOR TESTING	7
5.	SUMMARY OF TEST RESULTS.....	8
6.	TEST EQUIPMENT UTILIZED	9
7.	TEST ENVIRONMENT	10
ANNEX A.	MEASUREMENT RESULTS.....	11
ANNEX A.1.	RADIATED.....	11
ANNEX B.	DEVIATIONS FROM PRESCRIBED TEST METHODS.....	21

1. Test Laboratory

1.1. Testing Location

Company Name:	ECIT Shanghai, East China Institute of Telecommunications
Address:	7-8F, G Area, No. 668, Beijing East Road, Huangpu District, Shanghai, P. R. China
Postal Code:	200001
Telephone:	(+86)-021-63843300
Fax:	(+86)-021-63843301


1.2. Testing Environment

Normal Temperature:	15-35°C
Extreme Temperature:	-10/+55°C
Relative Humidity:	20-75%


1.3. Project data

Project Leader:	Zhou Yan
Testing Start Date:	2017-12-14
Testing End Date:	2018-01-05


1.4. Signature



Shi Hongqi
(Prepared this test report)



Ding Li
(Reviewed this test report)



Zheng Zhongbin
Director of the laboratory
(Approved this test report)

2. Client Information

2.1. Applicant Information

Company Name: Shanghai Sunmi Technology Co.,Ltd.
Address: Room 605, Block 7, KIC Plaza, No.388 Song Hu Road, Yang Pu
District, Shanghai, China
Postcode: 200433
Telephone: 18721763396

2.2. Manufacturer Information

Company Name: Shanghai Sunmi Technology Co.,Ltd.
Address: Room 605, Block 7, KIC Plaza, No.388 Song Hu Road, Yang Pu
District, Shanghai, China
Postcode: 200433
Telephone: 18721763396

3. Equipment Under Test (EUT) and Ancillary Equipment (AE)

3.1. About EUT

EUT Description	Wireless data POS System
Model name	W5920
FCC ID	2AH25V1SNFC/FRN:
Frequency	GSM850/900/1800/1900; WCDMA Band I/II/V/VIII
Extreme Temperature	-10/+55°C
Nominal Voltage	3.6 V
Extreme High Voltage	4.2 V
Extreme Low Voltage	3.5 V

Note: Photographs of EUT are shown in ANNEX A of this test report.

3.2. Internal Identification of EUT used during the test

EUT ID*	SN or IMEI	HW Version	SW Version	Date of receipt
N02	865150030317082	2.0	1.1.0	2017-11-24

*EUT ID: is used to identify the test sample in the lab internally.

3.3. Internal Identification of AE used during the test

AE ID*	Description	SN
AE1	RF cable	---
AE2	Dummy Battery	---

*AE ID: is used to identify the test sample in the lab internally.

3.4. Statements

The W5920, supporting GPRS/WCDMA /BT/BLE/WIFI/GPS/NFC, manufactured by Shanghai Sunmi Technology Co.,Ltd.. is a variant product for testing.

We only test worst-case of RSE. The other test cases please refer to the prototype report No: CCISE170603501, which was prepared by Shenzhen Zhongjian Nanfang Testing Co.,Ltd

ECIT has verified that the compliance of the tested device specified in section 5 of this test report is successfully evaluated according to the procedure and test methods as defined in type certification requirement listed in section 5 of this test report.

4. Reference Documents

4.1. Reference Documents for testing

The following documents listed in this section are referred for testing.

Reference	Title	Version
FCC Part 24	PERSONAL COMMUNICATIONS SERVICES	2014
FCC Part 22	PUBLIC MOBILE SERVICES	2014
ANSI-TIA-603-E	Land Mobile FM or PM Communications Equipment Measurement and Performance Standards	2016
ANSI C63.4	Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz	2014

5. SUMMARY OF TEST RESULTS

Item	Test items	FCC rules	result
1	Emission Limit	2.1051/22.917/24.238/22.913/24.232	Pass

6. Test Equipment Utilized

Climate chamber

No.	Equipment	Model	Serial Number	Manufacturer	Calibration date	Cal.interval
1	Climate chamber	SH-641	92012011	ESPEC	2017-12-25	2 Year

Radiated emission test system

The test equipment and ancillaries used are as follows.

No.	Equipment	Model	Serial Number	Manufacturer	Calibration date	Cal.interval
1	Universal Radio Communication Tester	CMU200	123123	R&S	2017-05-11	1 Year
2	EMI Test Receiver	ESU40	100307	R&S	2017-05-11	1 Year
3	TRILOG Broadband Antenna	VULB9163	VULB9163-515	Schwarzbeck	2017-02-25	3 Year
4	Double-ridged Waveguide Antenna	ETS-3117	00135890	ETS	2017-01-11	3 Year
5	2-Line V-Network	ENV216	101380	R&S	2017-05-11	1 Year
6	Substitution Antenna	ETS-3117	00135890	ETS	2017-01-11	3 Year
7	RF Signal Generator	SMF100A	102314	R&S	2017-05-11	1 Year
8	Substitution Antenna	VUBA9117	9117-266	Schwarzbeck	2017-11-18	3 Year
9	Amplifier	SCU08	10146	R&S	2017-05-11	1 Year

7. Test Environment

Shielding Room1 (6.0 meters×3.0 meters×2.7 meters) did not exceed following limits along the conducted RF performance testing:

Temperature	Min. = 15 °C, Max. = 35 °C
Relative humidity	Min. = 20 %, Max. = 75 %
Shielding effectiveness	> 100 dB
Ground system resistance	< 0.5 Ω

Control room did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 35 °C
Relative humidity	Min. = 25 %, Max. = 75 %
Shielding effectiveness	> 100 dB
Electrical insulation	> 10 kΩ
Ground system resistance	< 0.5 Ω

Fully-anechoic chamber1 (6.9 meters×10.9 meters×5.4 meters) did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 35 °C
Relative humidity	Min. = 25 %, Max. = 75 %
Shielding effectiveness	> 100 dB
Electrical insulation	> 10 kΩ
Ground system resistance	< 0.5 Ω
VSWR	Between 0 and 6 dB, from 1GHz to 18GHz
Site Attenuation Deviation	Between -4 and 4 dB, 30MHz to 1GHz
Uniformity of field strength	Between 0 and 6 dB, from 80MHz to 3000 MHz

ANNEX A. MEASUREMENT RESULTS

ANNEX A.1. RADIATED

A.1.1 EMISSION LIMIT (§2.1051/§22.917/§24.238)


A.1.1.1 GSM Measurement Method

The measurement procedures in TIA-603E-2016 are used.

The spectrum was scanned from 30 MHz to the 10th harmonic of the highest frequency generated within the equipment, which is the transmitted carrier that can be as high as 1910 MHz. The resolution bandwidth is set as outlined in Part 24.238 and Part 22.917. The spectrum is scanned with the mobile station transmitting at carrier frequencies that pertain to low, mid and high channels of PCS1900 and GSM850.


A.1.1.2 The procedure of radiated spurious emissions is as follows:

1. EUT was placed on a 1.5 meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT for emission measurements. The height of receiving antenna is 1.5m. The test setup refers to figure below. Detected emissions were maximized at each frequency by rotating the EUT through 360° and adjusting the receiving antenna polarization. The radiated emission measurements of all non-harmonic and harmonics of the transmit frequency through the 10th harmonic were measured with peak detector.



2. The EUT is then put into continuously transmitting mode at its maximum power level during the test. And the maximum value of the receiver should be recorded as (Pr).

3. The EUT shall be replaced by a substitution antenna. The test setup refers to figure below.



In the chamber, a substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power (P_{Mea}) is applied to the input of the substitution antenna, and adjust the level of the signal generator output until the value of the receiver reach the previously recorded (P_r). The power of signal source (P_{Mea}) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.

4. The Path loss (P_{pl}) between the Signal Source with the Substitution Antenna and the Substitution Antenna Gain (G_a) should be recorded after test.

A amplifier should be connected in for the test.

The Path loss (P_{pl}) is the summation of the cable loss .

The measurement results are obtained as described below:

Power(EIRP)= P_{Mea} - P_{pl} + G_a

5. This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dBi) and known input power.

6. ERP can be calculated from EIRP by subtracting the gain of the dipole, ERP = EIRP -2.15dBi

A.1.1.3 Measurement Limit

Part 24.238 and Part 22.917 specify that the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

The specification that emissions shall be attenuated below the transmitter power (P) by at least $43 + 10 \log(P)$ dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.

A.1.1.4 Measurement Results

Radiated emissions measurements were made only at the upper, middle, and lower carrier frequencies of the PCS1900 band (1850.2 MHz, 1880 MHz and 1909.8 MHz) and GSM850 band (824.2MHz, 836.6MHz, 848.8MHz) . It was decided that measurements at these three carrier frequencies would be sufficient to demonstrate compliance with emissions limits because it was seen that all the significant spurs occur well outside the band and no radiation was seen from a carrier in one block of the PCS1900 ,GSM850 into any of the other blocks. The equipment must still, however, meet emissions requirements with the carrier at all frequencies over which it is capable of operating and it is the manufacturer's responsibility to verify this.

A.1.1.5 Measurement Results

Measurements results:

Frequency	Channel	Frequency Range	Result
-----------	---------	-----------------	--------

GSM850	Low	30MHz~10GHz	P
	Middle	30MHz~10GHz	P
	High	30MHz~10GHz	P
GSM1900	Low	30MHz~20GHz	P
	Middle	30MHz~20GHz	P
	High	30MHz~20GHz	P

GSM850
GPRS Mode Channel 128
Final result:

Frequency (MHz)	PMea (dBm)	Pcl (dBm)	Ga (dBd)	Peak ERP (dBm)	Limit (dBm)	Polarization
2809.2857 14	-36.3	5.7	6.4	-35.6	-13	V
3575.7692 31	-49.62	6.4	7.8	-48.22	-13	H
4494.2307 69	-48.62	7.3	8.7	-47.22	-13	V
5300.7692 31	-48.64	8	9.5	-47.14	-13	H
5770.3846 15	-46.69	8.5	10.2	-44.99	-13	H
6804.6153 85	-48.38	9.2	10.9	-46.68	-13	V

Note:
GPRS 850, CH128

Power(ERP)= Pmea-Pcl+Ga=-36.3-5.7+6.4=-35.6dbm

This method Applicable to the following table.

GPRS Mode Channel 189
Final result:

Frequency (MHz)	PMea (dBm)	Pcl (dBm)	Ga (dBd)	Peak ERP (dBm)	Limit (dBm)	Polarization
2509.2857 14	-36.36	5.4	5.6	-36.16	-13	H

3573.4615 39	-50.04	6.4	7.8	-48.64	-13	H
4525.3846 15	-49.29	7.1	8.9	-47.49	-13	V
5468.0769 23	-49.84	8.1	9.8	-48.14	-13	H
6569.2307 69	-48.29	9	10.6	-46.69	-13	V
7609.2307 69	-48.03	9.7	11.7	-46.03	-13	H

GPRS Mode Channel 251
Final result:

Frequency (MHz)	PMea (dBm)	Pcl (dBm)	Ga (dBd)	Peak ERP (dBm)	Limit (dBm)	Polarization
2805	-36.4	5.7	6.3	-35.8	-13	V
3195	-49	6	6.8	-48.2	-13	V
3583.8461 54	-49.72	6.4	7.8	-48.32	-13	V
4586.5384 62	-49.5	7.4	8.8	-48.1	-13	V
5500.3846 15	-49.12	8.2	9.8	-47.52	-13	H
6701.5384 62	-48.47	9.1	10.9	-46.67	-13	V

GSM1900
GPRS Mode Channel 512
Final result:

Frequency (MHz)	PMea (dBm)	Pcl (dBm)	Ga (dBd)	Peak ERP (dBm)	Limit (dBm)	Polarization
3574.8	-53.12	6.4	7.8	-51.72	-13	V
4551.6	-51.4	7.4	8.7	-50.1	-13	H

5729.4	-48.45	8.5	10.2	-46.75	-13	V
7110	-50.57	9.4	11.2	-48.77	-13	H
9548.4	-45.11	10.7	12.7	-43.11	-13	H
13368	-38.45	13.6	13.5	-38.55	-13	V

GPRS Mode Channel 661
Final result:

Frequency (MHz)	PMea (dBm)	Pcl (dBm)	Ga (dBd)	Peak ERP (dBm)	Limit (dBm)	Polarization
3819.6	-51.3	4.7	7.9	-48.1	-13	H
4452.6	-51.67	7.4	8.7	-50.37	-13	V
5730	-48.88	8.5	10.2	-47.18	-13	H
7696.8	-49.6	9.7	11.7	-47.6	-13	H
9548.4	-44.3	10.7	12.7	-42.3	-13	H
13232.4	-38.92	13.6	13.5	-39.02	-13	V

GPRS Mode Channel 810
Final result:

Frequency (MHz)	PMea (dBm)	Pcl (dBm)	Ga (dBd)	Peak ERP (dBm)	Limit (dBm)	Polarization
3595.8	-51.6	6.4	7.8	-50.2	-13	V
4543.2	-51.98	7.4	8.7	-50.68	-13	V
5729.4	-49.33	8.5	10.2	-47.63	-13	H
7707.6	-50.7	9.7	11.7	-48.7	-13	V

9548.4	-46.89	10.7	12.7	-44.89	-13	H
13269.6	-39.94	13.6	13.5	-40.04	-13	V

Conclusion: PASS

Note: the EUT was displayed in several different direction, the worst cases were shown.

A.1.2. WCDMA Measurement Method

The measurements procedures in TIA-603E-2016 are used.

The spectrum was scanned from 30 MHz to the 10th harmonic of the highest frequency generated within the equipment. The resolution bandwidth is set as outlined in Part 24.238 and Part 24.917. The spectrum is scanned with the mobile station transmitting at carrier frequencies that pertain to low, mid and high channels of WCDMA Band V.

The procedure of radiated spurious emissions is the same like GSM.

A.1.1.2. Measurement Limit

Part 24.238 and Part 22.917 specify that the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

The specification that emissions shall be attenuated below the transmitter power (P) by at least $43 + 10 \log(P)$ dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.

A.1.1.3. Measurement Results

Radiated emissions measurements were made only at the upper, middle, and lower carrier frequencies of the WCDMA Band V (826.4MHz, 836.6MHz and 846.6MHz) . It was decided that measurements at these three carrier frequencies would be sufficient to demonstrate compliance with emissions limits because it was seen that all the significant spurs occur well outside the band and no radiation was seen from a carrier in one block of the WCDMA Band V into any of the other blocks. The equipment must still, however, meet emissions requirements with the carrier at all frequencies over which it is capable of operating and it is the manufacturer's responsibility to verify this.

A.1.1.4. Measurement Results Table

Frequency	Channel	Frequency Range	Result
WCDMA Band II	Low	30MHz~20GHz	P
	Middle	30MHz~20GHz	P

	High	30MHz~20GHz	P
WCDMA Band V	Low	30MHz~20GHz	P
	Middle	30MHz~20GHz	P
	High	30MHz~20GHz	P

WCDMA BAND II Mode Channel 9262
Final result:

Frequency (MHz)	PMea (dBm)	Pcl (dBm)	Ga (dBd)	Peak ERP (dBm)	Limit (dBm)	Polarization
3708.4	-59.03	6.6	7.9	-57.73	-13	H
5562	-56.69	8.2	9.8	-55.09	-13	H
7408.8	-45.53	9.7	11.5	-43.73	-13	V
9260.4	-52.74	10.6	12.7	-50.64	-13	H
12600.9	-47.89	12.8	12.8	-47.89	-13	H
15890.55	-41.69	15	13.2	-43.49	-13	H

WCDMA BAND II Mode Channel 9400
Final result:

Frequency (MHz)	PMea (dBm)	Pcl (dBm)	Ga (dBd)	Peak ERP (dBm)	Limit (dBm)	Polarization
3758.4	-58.83	6.6	7.9	-57.53	-13	H
5636.8	-53.46	8.2	9.8	-51.86	-13	H
7515.2	-44.64	9.7	11.5	-42.84	-13	V
9396	-51.86	10.6	12.7	-49.76	-13	H
11760.2	-47.77	12.8	12.7	-47.87	-13	V

15896.85	-40.98	15	13.2	-42.78	-13	V
----------	--------	----	------	--------	-----	---

WCDMA BAND II Mode Channel 9538

Final result:

Frequency (MHz)	PMea (dBm)	Pcl (dBm)	Ga (dBd)	Peak ERP (dBm)	Limit (dBm)	Polarization
3812	-55.78	6.7	8	-54.48	-13	H
5724.8	-51.28	8.5	10.2	-49.58	-13	H
7625.2	-40.89	9.7	11.7	-38.89	-13	H
9539.6	-49.74	10.7	12.7	-47.74	-13	H
12730.4	-47.8	12.8	12.8	-47.8	-13	H
15242.7	-44.15	15	13.2	-45.95	-13	V

WCDMA BAND V Mode Channel 4132

Final result:

Frequency (MHz)	PMea (dBm)	Pcl (dBm)	Ga (dBd)	Peak ERP (dBm)	Limit (dBm)	Polarization
1856.428571	-55.71	4.6	4.6	-55.71	-13	H
2528.846154	-52.75	5.4	5.6	-52.55	-13	V
3621.2	-60.95	6.5	7.8	-59.65	-13	V
4850	-59.8	7.6	9.3	-58.1	-13	V
6001.2	-59.8	8.6	10.2	-58.2	-13	V

7330	-58.86	9.6	11.5	-56.96	-13	V
------	--------	-----	------	--------	-----	---

WCDMA BAND V Mode Channel 4183
Final result:

Frequency (MHz)	PMea (dBm)	Pcl (dBm)	Ga (dBd)	Peak ERP (dBm)	Limit (dBm)	Polarization
1270.357143	-60.37	3.8	3	-61.17	-13	H
1866.428571	-55.13	4.6	4.6	-55.13	-13	H
2788.846154	-50.49	5.7	6.1	-50.09	-13	V
3809.6	-61.38	6.7	8.4	-59.68	-13	H
4862.8	-60.86	7.6	9.4	-59.06	-13	V
6418.4	-59.64	8.9	10.5	-58.04	-13	V

WCDMA BAND V Mode Channel 4233
Final result:

Frequency (MHz)	PMea (dBm)	Pcl (dBm)	Ga (dBd)	Peak ERP (dBm)	Limit (dBm)	Polarization
1277.857143	-60.4	3.8	3	-61.2	-13	H
1835	-56.63	4.6	4.6	-56.63	-13	H
2854.230769	-50.62	5.7	6.1	-50.22	-13	H
3660	-60.53	6.5	7.8	-59.23	-13	H
5846.4	-59.3	8.4	10.2	-57.5	-13	H
9781	-54.92	11	12.6	-53.32	-13	V

Conclusion: PASS

Note: the EUT was displayed in several different direction, the worst cases were shown.

ANNEX B. Deviations from Prescribed Test Methods

No deviation from Prescribed Test Methods.

*****End Of Report*****