



# FCC RF Test Report

**APPLICANT** : Shanghai Sunmi Science and Technology Co., Ltd.  
**EQUIPMENT** : Wireless data ordering system  
**BRAND NAME** : SUNMI  
**MODEL NAME** : W5910  
**FCC ID** : 2AH25M1  
**STANDARD** : FCC Part 15 Subpart C §15.247  
**CLASSIFICATION** : (DSS) Spread Spectrum Transmitter

The product was received on Jul. 27, 2016 and testing was completed on Sep. 15, 2016. We, SPORTON INTERNATIONAL (KUNSHAN) INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL (KUNSHAN) INC., the test report shall not be reproduced except in full.

Prepared by: James Huang / Manager

Approved by: Jones Tsai / Manager



**SPORTON INTERNATIONAL (KUNSHAN) INC.**

**NO. 3-2, PINGXIANG ROAD, KUNSHAN, JIANGSU PROVINCE, P. R. CHINA**



## TABLE OF CONTENTS

<b>REVISION HISTORY .....</b>	<b>3</b>
<b>SUMMARY OF TEST RESULT .....</b>	<b>4</b>
<b>1 GENERAL DESCRIPTION .....</b>	<b>5</b>
1.1 Applicant .....	5
1.2 Manufacturer .....	5
1.3 Product Feature of Equipment Under Test .....	5
1.4 Product Specification of Equipment Under Test .....	5
1.5 Modification of EUT .....	6
1.6 Testing Location .....	6
1.7 Applicable Standards .....	6
<b>2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST .....</b>	<b>7</b>
2.1 Descriptions of Test Mode .....	7
2.2 Test Mode .....	8
2.3 Connection Diagram of Test System .....	9
2.4 Support Unit used in test configuration and system .....	10
2.5 EUT Operation Test Setup .....	10
2.6 Measurement Results Explanation Example .....	11
<b>3 TEST RESULT .....</b>	<b>12</b>
3.1 Number of Channel Measurement .....	12
3.2 Hopping Channel Separation Measurement .....	14
3.3 Dwell Time Measurement .....	21
3.4 20dB Bandwidth Measurement .....	24
3.5 Peak Output Power Measurement .....	31
3.6 Conducted Band Edges Measurement .....	33
3.7 Conducted Spurious Emission Measurement .....	40
3.8 Radiated Band Edges and Spurious Emission Measurement .....	50
3.9 AC Conducted Emission Measurement .....	56
3.10 Antenna Requirements .....	60
<b>4 LIST OF MEASURING EQUIPMENT .....</b>	<b>61</b>
<b>5 UNCERTAINTY OF EVALUATION .....</b>	<b>62</b>
<b>APPENDIX A. RADIATED TEST RESULTS</b>	
<b>APPENDIX B. SETUP PHOTOGRAPHS</b>	



## REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR672716A	Rev. 01	Initial issue of report	Oct. 18, 2016

## SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(1)	Number of Channels	$\geq 15\text{Chs}$	Pass	-
3.2	15.247(a)(1)	Hopping Channel Separation	$\geq 2/3$ of 20dB BW	Pass	-
3.3	15.247(a)(1)	Dwell Time of Each Channel	$\leq 0.4\text{sec}$ in 31.6sec period	Pass	-
3.4	15.247(a)(1)	20dB Bandwidth	NA	Pass	-
3.4	-	99% Bandwidth	-	Pass	-
3.5	15.247(b)(1)	Peak Output Power	$\leq 125\text{ mW}$	Pass	-
3.6	15.247(d)	Conducted Band Edges	$\leq 20\text{dBc}$	Pass	-
3.7	15.247(d)	Conducted Spurious Emission	$\leq 20\text{dBc}$	Pass	-
3.8	15.247(d)	Radiated Band Edges and Radiated Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 10.75 dB at 36.790 MHz
3.9	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 20.91 dB at 0.647 MHz
3.10	15.203 & 15.247(b)	Antenna Requirement	N/A	Pass	-



# 1 General Description

## 1.1 Applicant

Shanghai Sunmi Science and Technology Co., Ltd.

Room 505, KIC Plaza, No.388 Song Hu Road, Yang Pu District, Shanghai, China

## 1.2 Manufacturer

Shanghai Longcheer Technology Co., Ltd.

Building 1, No.401, Caobao Rd, Xuhui District, Shanghai, P. R. China

## 1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Wireless data ordering system
Brand Name	SUNMI
Model Name	W5910
FCC ID	2AH25M1
EUT supports Radios application	GPRS/EGPRS/ WCDMA/HSPA/HSPA+(16QAM uplink is not supported)/ WLAN2.4GHz 802.11b/g/n HT20/HT40/ Bluetooth v3.0+ EDR/Bluetooth v4.0 LE
IMEI Code	Conducted:865843024536382 Radiation:865843024542067 Conduction:865843024542240
HW Version	LWDM591
SW Version	LWDJ610
EUT Stage	Identical Prototype

**Remark:** The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

## 1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx/Rx Frequency Range	2402 MHz ~ 2480 MHz
Number of Channels	79
Carrier Frequency of Each Channel	2402+n*1 MHz; n=0~78
Maximum Output Power to Antenna	Bluetooth BR(1Mbps) : 6.35 dBm (0.0043 W) Bluetooth EDR (2Mbps) : 6.20 dBm (0.0042 W) Bluetooth EDR (3Mbps) : 6.37 dBm (0.0043 W)
Antenna Type / Gain	PIFA Antenna with gain -4.5 dBi
Type of Modulation	Bluetooth BR (1Mbps) : GFSK Bluetooth EDR (2Mbps) : $\pi/4$ -DQPSK Bluetooth EDR (3Mbps) : 8-DPSK

## 1.5 Modification of EUT

No modifications are made to the EUT during all test items.

## 1.6 Testing Location

<b>Test Site</b>	SPORTON INTERNATIONAL (KUNSHAN) INC.	
<b>Test Site Location</b>	No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P. R. China TEL: +86-0512-5790-0158 FAX: +86-0512-5790-0958	
<b>Test Site No.</b>	<b>Sporton Site No.</b>	
	TH01-KS	CO01-KS

<b>Test Site</b>	SPORTON INTERNATIONAL (SHENZHEN) INC.	
<b>Test Site Location</b>	No. 3 Building, the third floor of south, Shahe River west, Fengzeyuan warehouse, Nanshan District, Shenzhen, Guangdong, P. R. China TEL: +86-755- 3320-2398	
<b>Test Site No.</b>	<b>Sporton Site No.</b>	<b>FCC Registration No.</b>
	03CH02-SZ	566869

**Note:** The test site complies with ANSI C63.4 2014 requirement.

## 1.7 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.247
- ♦ ANSI C63.10-2013

### Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

## 2 Test Configuration of Equipment Under Test

### 2.1 Descriptions of Test Mode

Preliminary tests were performed in different data rates and recorded the RF output power in the following table:

Channel	Frequency	Bluetooth RF Output Power		
		Data Rate / Modulation		
		GFSK	$\pi/4$ -DQPSK	8-DPSK
		1Mbps	2Mbps	3Mbps
Ch00	2402MHz	6.35 dBm	6.20 dBm	<b>6.37 dBm</b>
Ch39	2441MHz	6.19 dBm	6.03 dBm	6.20 dBm
Ch78	2480MHz	5.74 dBm	5.70 dBm	5.79 dBm

**Remark:**

1. All the test data for each data rate were verified, but only the worst case was reported.
  2. The data rate was set in 3Mbps for all the test items due to the highest RF output power.
- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction (150 kHz to 30 MHz), radiation (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). Pre-scanned tests, X, Y, Z in three orthogonal panels, and different data rates were conducted to determine the final configuration (Y plane as worst plane) from all possible combinations, and the worst mode of radiated spurious emissions is Bluetooth 3Mbps mode, and recorded in this report.
- b. AC power line Conducted Emission was tested under maximum output power.

## 2.2 Test Mode


The following summary table is showing all test modes to demonstrate in compliance with the standard.

Summary table of Test Cases			
Test Item	Data Rate / Modulation		
	Bluetooth BR 1Mbps GFSK	Bluetooth EDR 2Mbps $\pi$ /4-DQPSK	Bluetooth EDR 3Mbps 8-DPSK
Conducted Test Cases	Mode 1: CH00_2402 MHz	Mode 4: CH00_2402 MHz	Mode 7: CH00_2402 MHz
	Mode 2: CH39_2441 MHz	Mode 5: CH39_2441 MHz	Mode 8: CH39_2441 MHz
	Mode 3: CH78_2480 MHz	Mode 6: CH78_2480 MHz	Mode 9: CH78_2480 MHz
Radiated Test Cases	Bluetooth EDR 3Mbps 8-DPSK		
	Mode 1: CH00_2402 MHz		
	Mode 2: CH39_2441 MHz		
	Mode 3: CH78_2480 MHz		
AC Conducted Emission	Mode 1 :GPRS850 Idle + Bluetooth Link + WLAN Link + Adaptor with Cradle + Earphone		
Remark:  For radiated test cases, the worst mode data rate 3Mbps was reported only, because this data rate has the highest RF output power at preliminary tests, and the conducted spurious emissions and conducted band edge measurement for each data rate are no worse than 3Mbps, and no other significantly frequencies found in conducted spurious emission.			




## 2.3 Connection Diagram of Test System

### <Bluetooth Tx Mode>



### <AC Conducted Emission Mode>



## 2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	Anritus	MT8820C	N/A	N/A	Unshielded, 1.8 m
2.	Bluetooth Base Station	R&S	CBT32	N/A	N/A	Unshielded, 1.8 m
3.	WLAN AP	LINKSYS	WRT600N	Q87-WRT600NV11	N/A	Unshielded, 1.8 m
4.	Notebook	Lenovo	G480	N/A	N/A	AC I/P: Unshielded, 1.8 m DC O/P: Shielded, 1.8 m
5.	Bluetooth Earphone	Lenovo	LBH-308	N/A	N/A	N/A
6.	Earphone	Lenovo	LH102	N/A	Unshielded, 1.2m	N/A

## 2.5 EUT Operation Test Setup

For Bluetooth function, the engineering test program was provided and enabled to make EUT connect with Bluetooth base station to continuous transmit/receive.

For AC power line conducted emissions, the EUT was set to connect with the WLAN AP under large package sizes transmission.



## 2.6 Measurement Results Explanation Example

**For all conducted test items:**

The offset level is set in the spectrum analyzer to compensate the RF cable loss between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example:

The spectrum analyzer offset is derived from RF cable loss.

*Offset = RF cable loss*

Following shows an offset computation example with cable loss 5.5 dB

$$\begin{aligned}\text{Offset(dB)} &= \text{RF cable loss(dB)}. \\ &= 5.5 \text{ (dB)}\end{aligned}$$

### 3 Test Result

#### 3.1 Number of Channel Measurement

##### 3.1.1 Limits of Number of Hopping Frequency

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.

##### 3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

##### 3.1.3 Test Procedure

1. The testing follows ANSI C63.10-2013 clause 7.8.3.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings: Span = the frequency band of operation;  
RBW = 300kHz; VBW  $\geq$  RBW; Sweep = auto; Detector function = peak; Trace = max hold.
6. The number of hopping frequency used is defined as the number of total channel.
7. Record the measurement data derived from spectrum analyzer.

##### 3.1.4 Test Setup




##### 3.1.5 Test Result of Number of Hopping Frequency


<b>Test Mode :</b>	3Mbps	<b>Temperature :</b>	24~25°C
<b>Test Engineer :</b>	Silent Hai	<b>Relative Humidity :</b>	50~55%
Number of Hopping (Channel)	Adaptive Frequency Hopping (Channel)	Limits (Channel)	Pass/Fail
79	20	> 15	Pass



Number of Hopping Channel Plot on Channel 00 - 78



Date: 10.SEP.2016 00:35:11



Date: 10.SEP.2016 00:40:23

## **3.2 Hopping Channel Separation Measurement**

### **3.2.1 Limit of Hopping Channel Separation**

Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.

### **3.2.2 Measuring Instruments**

The measuring equipment is listed in the section 4 of this test report.

### **3.2.3 Test Procedures**

1. The testing follows ANSI C63.10-2013 clause 7.8.2.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings:  
Span = wide enough to capture the peaks of two adjacent channels;  
RBW = 300kHz; VBW  $\geq$  RBW; Sweep = auto; Detector function = peak; Trace = max hold.
6. Measure and record the results in the test report.


### **3.2.4 Test Setup**



**3.2.5 Test Result of Hopping Channel Separation**

Test Mode :	1Mbps	Temperature :	24~25°C
Test Engineer :	Silent Hai	Relative Humidity :	50~55%


Channel	Frequency (MHz)	Frequency Separation (MHz)	(2/3 of 20dB BW) Limits (MHz)	Pass/Fail
00	2402	1.002	0.6453	Pass
39	2441	1.002	0.6453	Pass
78	2480	1.008	0.5893	Pass

**Channel Separation Plot on Channel 00 - 01**

Date: 9.SEP.2016 23:42:03




### Channel Separation Plot on Channel 39 - 40



Date: 9.SEP.2016 23:42:51

### Channel Separation Plot on Channel 77 - 78




Date: 10.SEP.2016 01:13:33





Test Mode :	2Mbps	Temperature :	24~25°C
Test Engineer :	Silent Hai	Relative Humidity :	50~55%


Channel	Frequency (MHz)	Frequency Separation (MHz)	(2/3 of 20dB BW) Limits (MHz)	Pass/Fail
00	2402	1.002	0.8440	Pass
39	2441	1.008	0.8440	Pass
78	2480	1.002	0.8160	Pass

**Channel Separation Plot on Channel 00 - 01**

Date: 12.SEP.2016 19:26:43




Channel Separation Plot on Channel 39 - 40



Date: 10.SEP.2016 00:01:39

Channel Separation Plot on Channel 77 - 78




Date: 10.SEP.2016 00:02:18



Test Mode :	3Mbps	Temperature :	24~25°C
Test Engineer :	Silent Hai	Relative Humidity :	50~55%


Channel	Frequency (MHz)	Frequency Separation (MHz)	(2/3 of 20dB BW) Limits (MHz)	Pass/Fail
00	2402	1.002	0.8200	Pass
39	2441	1.002	0.8200	Pass
78	2480	1.002	0.8240	Pass

**Channel Separation Plot on Channel 00 - 01**

Date: 10.SEP.2016 00:04:50




Channel Separation Plot on Channel 39 - 40



Date: 10.SEP.2016 00:05:28

Channel Separation Plot on Channel 77 - 78



Date: 10.SEP.2016 00:06:07

### 3.3 Dwell Time Measurement

#### 3.3.1 Limit of Dwell Time

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

#### 3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

#### 3.3.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.4.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings: Span = zero span, centered on a hopping channel; RBW = 1 MHz; VBW  $\geq$  RBW; Sweep = as necessary to capture the entire dwell time per hopping channel; Detector function = peak; Trace = max hold.
6. Measure and record the results in the test report.

#### 3.3.4 Test Setup



### 3.3.5 Test Result of Dwell Time

<b>Test Mode :</b>	3DH5	<b>Temperature :</b>	24~25℃
<b>Test Engineer :</b>	Silent Hai	<b>Relative Humidity :</b>	50~55%


Mode	Hopping Channel Number	Hops Over Occupancy Time(hops)	Package Transfer Time (msec)	Dwell Time (sec)	Limits (sec)	Pass/Fail
Normal	79	106.67	2.884	0.31	0.4	Pass
AFH	20	53.33	2.884	0.15	0.4	Pass

**Remark:**

- In normal mode, hopping rate is 1600 hops/s with 6 slots in 79 hopping channels.  
With channel hopping rate (1600 / 6 / 79) in Occupancy Time Limit (0.4 x 79) (s),  
Hops Over Occupancy Time comes to (1600 / 6 / 79) x (0.4 x 79) = 106.67 hops.
- In AFH mode, hopping rate is 800 hops/s with 6 slots in 20 hopping channels.  
With channel hopping rate (800 / 6 / 20) in Occupancy Time Limit (0.4 x 20) (s),  
Hops Over Occupancy Time comes to (800 / 6 / 20) x (0.4 x 20) = 53.33 hops.
- Dwell Time(s) = Hops Over Occupancy Time (hops) x Package Transfer Time



Package Transfer Time Plot



Date: 8.SEP.2016 20:12:29

### 3.4 20dB Bandwidth Measurement

#### 3.4.1 Limit of 20dB Bandwidth

Reporting only

#### 3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

#### 3.4.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 6.9.2 and 6.9.3.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Use the following spectrum analyzer settings for 20dB Bandwidth measurement.  
Span = approximately 2 to 5 times the 20 dB bandwidth, centered on a hopping channel;  
RBW  $\geq$  1% of the 20 dB bandwidth; VBW  $\geq$  RBW; Sweep = auto; Detector function = peak;  
Trace = max hold.
5. Measure and record the results in the test report.

#### 3.4.4 Test Setup






**3.4.5 Test Result of 20dB Bandwidth**

Test Mode :	1Mbps	Temperature :	24~25°C
Test Engineer :	Silent Hai	Relative Humidity :	50~55%


Channel	Frequency (MHz)	20dB Bandwidth (MHz)
00	2402	0.968
39	2441	0.968
78	2480	0.884

**20 dB Bandwidth Plot on Channel 00**

Date: 10.SEP.2016 00:41:00




### 20 dB Bandwidth Plot on Channel 39



Date: 10.SEP.2016 00:41:06

### 20 dB Bandwidth Plot on Channel 78




Date: 10.SEP.2016 00:41:12



Test Mode :	2Mbps	Temperature :	24~25°C
Test Engineer :	Silent Hai	Relative Humidity :	50~55%


Channel	Frequency (MHz)	20dB Bandwidth (MHz)
00	2402	1.266
39	2441	1.266
78	2480	1.224

**20 dB Bandwidth Plot on Channel 00**

Date: 10.SEP.2016 00:41:19




### 20 dB Bandwidth Plot on Channel 39



Date: 10.SEP.2016 00:41:27

### 20 dB Bandwidth Plot on Channel 78




Date: 10.SEP.2016 00:41:35




Test Mode :	3Mbps	Temperature :	24~25°C
Test Engineer :	Silent Hai	Relative Humidity :	50~55%


Channel	Frequency (MHz)	20dB Bandwidth (MHz)
00	2402	1.230
39	2441	1.230
78	2480	1.236

**20 dB Bandwidth Plot on Channel 00**

Date: 10.SEP.2016 00:41:42

**20 dB Bandwidth Plot on Channel 39**

Date: 10.SEP.2016 00:41:50

**20 dB Bandwidth Plot on Channel 78**

Date: 10.SEP.2016 00:41:58

### 3.5 Peak Output Power Measurement

#### 3.5.1 Limit of Peak Output Power

Section 15.247 (b) The maximum peak conducted output power of the intentional radiator shall not exceed the following: (1) For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band 0.125 watts.


#### 3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

#### 3.5.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.5.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power with cable loss and record the results in the test report.
5. Measure and record the results in the test report.

#### 3.5.4 Test Setup



### 3.5.5 Test Result of Peak Output Power

<b>Test Mode :</b>	1Mbps	<b>Temperature :</b>	24~25°C
<b>Test Engineer :</b>	Silent Hai	<b>Relative Humidity :</b>	50~55%

Channel	Frequency (MHz)	RF Power (dBm)		
		GFSK	Max. Limits (dBm)	Pass/Fail
		1 Mbps		
00	2402	6.35	20.97	Pass
39	2441	6.19	20.97	Pass
78	2480	5.74	20.97	Pass

<b>Test Mode :</b>	2Mbps	<b>Temperature :</b>	24~25°C
<b>Test Engineer :</b>	Silent Hai	<b>Relative Humidity :</b>	50~55%

Channel	Frequency (MHz)	RF Power (dBm)		
		$\pi/4$ -DQPSK	Max. Limits (dBm)	Pass/Fail
		2 Mbps		
00	2402	6.20	20.97	Pass
39	2441	6.03	20.97	Pass
78	2480	5.70	20.97	Pass

<b>Test Mode :</b>	3Mbps	<b>Temperature :</b>	24~25°C
<b>Test Engineer :</b>	Silent Hai	<b>Relative Humidity :</b>	50~55%

Channel	Frequency (MHz)	RF Power (dBm)		
		8-DPSK	Max. Limits (dBm)	Pass/Fail
		3 Mbps		
00	2402	6.37	20.97	Pass
39	2441	6.20	20.97	Pass
78	2480	5.79	20.97	Pass



## **3.6 Conducted Band Edges Measurement**

### **3.6.1 Limit of Band Edges**

In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.

### **3.6.2 Measuring Instruments**

The measuring equipment is listed in the section 4 of this test report.

### **3.6.3 Test Procedures**


1. The testing follows ANSI C63.10-2013 clause 7.8.6.
2. Set to the maximum power setting and enable the EUT transmit continuously.
3. Set RBW = 100kHz, VBW = 300kHz. Band edge emissions must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100kHz RBW. The attenuation shall be 30 dB instead of 20 dB when RMS conducted output power procedure is used.
4. Enable hopping function of the EUT and then repeat step 2. and 3.
5. Measure and record the results in the test report.

### **3.6.4 Test Setup**




**3.6.5 Test Result of Conducted Band Edges**

Test Mode :	1Mbps	Temperature :	24~25°C
Test Channel :	00 and 78	Relative Humidity :	50~55%
		Test Engineer :	Silent Hai

**Low Band Edge Plot on Channel 00**


Date: 10.SEP.2016 00:21:10

**High Band Edge Plot on Channel 78**


Date: 10.SEP.2016 00:22:02



Test Mode :	2Mbps	Temperature :	24~25°C
Test Channel :	00 and 78	Relative Humidity :	50~55%
		Test Engineer :	Silent Hai

**Low Band Edge Plot on Channel 00**


Date: 10.SEP.2016 00:22:53

**High Band Edge Plot on Channel 78**

Date: 10.SEP.2016 00:23:45


<b>Test Mode :</b>	3Mbps	<b>Temperature :</b>	24~25℃
<b>Test Channel :</b>	00 and 78	<b>Relative Humidity :</b>	50~55%
		<b>Test Engineer :</b>	Silent Hai

### Low Band Edge Plot on Channel 00



Date: 10.SEP.2016 00:24:37


### High Band Edge Plot on Channel 78




Date: 10.SEP.2016 00:25:28

**3.6.6 Test Result of Conducted Hopping Mode Band Edges**

Test Mode :	1Mbps	Temperature :	24~25℃
Test Engineer :	Silent Hai	Relative Humidity :	50~55%

**1Mbps Hopping Mode Low Band Edge Plot**


Date: 12.SEP.2016 19:49:04

**1Mbps Hopping Mode High Band Edge Plot**

Date: 10.SEP.2016 01:29:02


<b>Test Mode :</b>	2Mbps	<b>Temperature :</b>	24~25℃
<b>Test Engineer :</b>	Silent Hai	<b>Relative Humidity :</b>	50~55%

### 2Mbps Hopping Mode Low Band Edge Plot



Date: 10.SEP.2016 01:36:25


### 2Mbps Hopping Mode High Band Edge Plot



Date: 10.SEP.2016 01:38:07


<b>Test Mode :</b>	3Mbps	<b>Temperature :</b>	24~25℃
<b>Test Engineer :</b>	Silent Hai	<b>Relative Humidity :</b>	50~55%

### 3Mbps Hopping Mode Low Band Edge Plot



Date: 10.SEP.2016 01:33:47

### 3Mbps Hopping Mode High Band Edge Plot



Date: 10.SEP.2016 01:34:48

## **3.7 Conducted Spurious Emission Measurement**

### **3.7.1 Limit of Spurious Emission Measurement**

In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.


### **3.7.2 Measuring Instruments**

The measuring equipment is listed in the section 4 of this test report.

### **3.7.3 Test Procedure**

1. The testing follows ANSI C63.10-2013 clause 7.8.8.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW = 300kHz, scan up through 10th harmonic. All harmonics / spurs must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100 kHz RBW.
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.


### **3.7.4 Test Setup**






**3.7.5 Test Result of Conducted Spurious Emission**

Test Mode :	1Mbps	Temperature :	24~25°C
Test Channel :	00	Relative Humidity :	50~55%
		Test Engineer :	Silent Hai

**1Mbps CSE Plot on Ch 00 between 30MHz ~ 3 GHz**


Date: 15.SEP.2016 21:12:58

**1Mbps CSE Plot on Ch 00 between 2 GHz ~ 25 GHz**


Date: 15.SEP.2016 21:13:20



Test Mode :	1Mbps	Temperature :	24~25°C
Test Channel :	39	Relative Humidity :	50~55%
		Test Engineer :	Silent Hai

**1Mbps CSE Plot on Ch 39 between 30MHz ~ 3 GHz**


Date: 15.SEP.2016 21:15:52

**1Mbps CSE Plot on Ch 39 between 2 GHz ~ 25 GHz**


Date: 15.SEP.2016 21:16:14



Test Mode :	1Mbps	Temperature :	24~25°C
Test Channel :	78	Relative Humidity :	50~55%
		Test Engineer :	Silent Hai

**1Mbps CSE Plot on Ch 78 between 30MHz ~ 3 GHz**


Date: 15.SEP.2016 21:17:10

**1Mbps CSE Plot on Ch 78 between 2 GHz ~ 25 GHz**

Date: 15.SEP.2016 21:17:32


<b>Test Mode :</b>	2Mbps	<b>Temperature :</b>	24~25℃
<b>Test Channel :</b>	00	<b>Relative Humidity :</b>	50~55%
		<b>Test Engineer :</b>	Silent Hai

### 2Mbps CSE Plot on Ch 00 between 30MHz ~ 3 GHz



Date: 15.SEP.2016 21:18:31


### 2Mbps CSE Plot on Ch 00 between 2 GHz ~ 25 GHz




Date: 15.SEP.2016 21:31:46



Test Mode :	2Mbps	Temperature :	24~25°C
Test Channel :	39	Relative Humidity :	50~55%
		Test Engineer :	Silent Hai

**2Mbps CSE Plot on Ch 39 between 30MHz ~ 3 GHz**


Date: 15.SEP.2016 21:23:11

**2Mbps CSE Plot on Ch 39 between 2 GHz ~ 25 GHz**


Date: 15.SEP.2016 21:27:03



Test Mode :	2Mbps	Temperature :	24~25°C
Test Channel :	78	Relative Humidity :	50~55%
		Test Engineer :	Silent Hai

**2Mbps CSE Plot on Ch 78 between 30MHz ~ 3 GHz**


Date: 15.SEP.2016 21:44:09

**2Mbps CSE Plot on Ch 78 between 2 GHz ~ 25 GHz**


Date: 15.SEP.2016 21:38:39



Test Mode :	3Mbps	Temperature :	24~25°C
Test Channel :	00	Relative Humidity :	50~55%
		Test Engineer :	Silent Hai

**3Mbps CSE Plot on Ch 00 between 30MHz ~ 3 GHz**


Date: 15.SEP.2016 21:46:28

**3Mbps CSE Plot on Ch 00 between 2 GHz ~ 25 GHz**


Date: 15.SEP.2016 21:46:49



Test Mode :	3Mbps	Temperature :	24~25°C
Test Channel :	39	Relative Humidity :	50~55%
		Test Engineer :	Silent Hai

**3Mbps CSE Plot on Ch 39 between 30MHz ~ 3 GHz**

Date: 15.SEP.2016 21:58:04


**3Mbps CSE Plot on Ch 39 between 2 GHz ~ 25 GHz**

Date: 15.SEP.2016 21:58:25






Test Mode :	3Mbps	Temperature :	24~25°C
Test Channel :	78	Relative Humidity :	50~55%
		Test Engineer :	Silent Hai

**3Mbps CSE Plot on Ch 78 between 30MHz ~ 3 GHz**

Date: 15.SEP.2016 21:59:52

**3Mbps CSE Plot on Ch 78 between 2 GHz ~ 25 GHz**

Date: 15.SEP.2016 22:06:53

## 3.8 Radiated Band Edges and Spurious Emission Measurement

### 3.8.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. In addition, radiated emissions which fall in the restricted bands must also comply with the FCC section 15.209 limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

### 3.8.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.




### 3.8.3 Test Procedures

1. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
2. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
3. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
4. Set to the maximum power setting and enable the EUT transmit continuously.
5. Use the following spectrum analyzer settings:
  - (1) Span shall wide enough to fully capture the emission being measured;
  - (2) Set RBW=100 kHz for  $f < 1$  GHz, RBW=1MHz for  $f > 1$ GHz ; VBW  $\geq$  RBW; Sweep = auto; Detector function = peak; Trace = max hold for peak
  - (3) For average measurement: use duty cycle correction factor method per 15.35(c).  
Duty cycle = On time/100 milliseconds  
On time =  $N_1 * L_1 + N_2 * L_2 + \dots + N_{n-1} * L_{n-1} + N_n * L_n$   
Where  $N_1$  is number of type 1 pulses,  $L_1$  is length of type 1 pulses, etc.  
Average Emission Level = Peak Emission Level +  $20 * \log(\text{Duty cycle})$
6. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level


Note: The average levels were calculated from the peak level corrected with duty cycle correction factor (-24.83dB) derived from  $20\log(\text{dwell time}/100\text{ms})$ . This correction is only for signals that hop with the fundamental signal, such as band-edge and harmonic. Other spurious signals that are independent of the hopping signal would not use this correction.

### 3.8.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz




### 3.8.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)


The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.

### 3.8.6 Duty cycle correction factor for average measurement

**3DH5 on time (One Pulse) Plot on Channel 39**



**3DH5 on time (Count Pulses) Plot on Channel 39**



**Note:**

1. Worst case Duty cycle = on time/100 milliseconds =  $2 * 2.867 / 100 = 5.73 \%$
2. Worst case Duty cycle correction factor =  $20 * \log(\text{Duty cycle}) = -24.83 \text{ dB}$
3. 3DH5 has the highest duty cycle worst case and is reported.

**Duty Cycle Correction Factor Consideration for AFH mode:**

Bluetooth normal hopping rate is 1600Hz and reduced to 800Hz in AFH mode; due to the reduced number of hopping frequencies, with the same packet configuration the dwell time in each channel frequency within 100msec period is longer in AFH mode than normal mode.

In AFH mode, the minimum hopping frequencies are 20, to get the longest dwell time DH5 packet is observed; the period to have DH5 packet completing one hopping sequence is

$$2.867 \text{ ms} \times 20 \text{ channels} = 57.3 \text{ ms}$$

There cannot be 2 complete hopping sequences within 100ms period, considering the random hopping behavior, maximum 2 hops can be possibly observed within the period.  $[100\text{ms} / 57.6\text{ms}] = 2 \text{ hops}$

Thus, the maximum possible ON time:

$$2.867 \text{ ms} \times 2 = 5.73 \text{ ms}$$

Worst case Duty Cycle Correction factor, which is derived from the maximum possible ON time,

$$20 \times \log(5.73 \text{ ms}/100\text{ms}) = -24.83 \text{ dB}$$

**3.8.7 Test Result of Radiated Spurious at Band Edges**

Please refer to Appendix A.

**3.8.8 Test Result of Radiated Spurious Emission (30MHz ~ 10<sup>th</sup> Harmonic)**

Please refer to Appendix A.

## **3.9 AC Conducted Emission Measurement**

### **3.9.1 Limit of AC Conducted Emission**

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dB $\mu$ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\*Decreases with the logarithm of the frequency.

### **3.9.2 Measuring Instruments**


The measuring equipment is listed in the section 4 of this test report.

### **3.9.3 Test Procedures**

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.




### 3.9.4 Test Setup





## 3.9.5 Test Result of AC Conducted Emission

Test Mode :	Mode 1	Temperature :	22~24℃
Test Engineer :	Amos Zhang	Relative Humidity :	44~47%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	GPRS850 Idle + Bluetooth Link + WLAN Link + Adaptor with Cradle + Earphone		




Site : CO01-KS  
Condition : FCC PART 15C LISN-L-20151024 LINE

mode : Mode 1  
: 865843024542240 #14

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.152	41.92	-23.95	65.87	31.30	0.51	10.11	QP
2 *	0.152	32.82	-23.05	55.87	22.20	0.51	10.11	Average
3	0.169	40.13	-24.90	65.03	29.60	0.41	10.12	QP
4	0.169	29.43	-25.60	55.03	18.90	0.41	10.12	Average
5	0.192	40.88	-23.05	63.93	30.50	0.26	10.12	QP
6	0.192	28.68	-25.25	53.93	18.30	0.26	10.12	Average
7	0.204	38.95	-24.50	63.45	28.60	0.22	10.13	QP
8	0.204	26.95	-26.50	53.45	16.60	0.22	10.13	Average
9	0.262	36.67	-24.71	61.38	26.31	0.22	10.14	QP
10	0.262	23.57	-27.81	51.38	13.21	0.22	10.14	Average
11	0.387	34.30	-23.82	58.12	23.90	0.23	10.17	QP
12	0.387	23.70	-24.42	48.12	13.30	0.23	10.17	Average



<b>Test Mode :</b>	Mode 1	<b>Temperature :</b>	22~24℃
<b>Test Engineer :</b>	Amos Zhang	<b>Relative Humidity :</b>	44~47%
<b>Test Voltage :</b>	120Vac / 60Hz	<b>Phase :</b>	Neutral
<b>Function Type :</b>	GPRS850 Idle + Bluetooth Link + WLAN Link + Adaptor with Cradle + Earphone		



Site : CO01-KS  
Condition : FCC PART 15C LISN-N-20151024 NEUTRAL

mode : Mode 1  
: 865843024542240 #14

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.167	39.72	-25.40	65.12	29.30	0.30	10.12	QP
2	0.167	28.02	-27.10	55.12	17.60	0.30	10.12	Average
3	0.194	40.73	-23.11	63.84	30.30	0.31	10.12	QP
4	0.194	28.73	-25.11	53.84	18.30	0.31	10.12	Average
5	0.255	36.06	-25.54	61.60	25.61	0.31	10.14	QP
6	0.255	23.76	-27.84	51.60	13.31	0.31	10.14	Average
7	0.419	31.79	-25.67	57.46	21.30	0.32	10.17	QP
8	0.419	22.69	-24.77	47.46	12.20	0.32	10.17	Average
9	0.647	33.09	-22.91	56.00	22.60	0.34	10.15	QP
10 *	0.647	25.09	-20.91	46.00	14.60	0.34	10.15	Average
11	1.662	30.72	-25.28	56.00	20.20	0.38	10.14	QP
12	1.662	22.82	-23.18	46.00	12.30	0.38	10.14	Average



## **3.10 Antenna Requirements**

### **3.10.1 Standard Applicable**

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

### **3.10.2 Antenna Anti-Replacement Construction**

An embedded-in antenna design is used.

### **3.10.3 Antenna Gain**

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



## 4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSP40	100319	9kHz~40GHz	Oct. 24, 2015	Sep. 08, 2016~ Sep. 15, 2016	Oct. 23, 2016	Conducted (TH01-KS)
Spectrum Analyzer	R&S	FSV40	101040	10Hz~40GHz	Aug. 09, 2016	Sep. 08, 2016~ Sep. 15, 2016	Aug. 08, 2017	Conducted (TH01-KS)
Pulse Power Sensor	Anritsu	MA2411B	0917070	300MHz~40GHz	Jan. 20, 2016	Sep. 08, 2016~ Sep. 15, 2016	Jan. 19, 2017	Conducted (TH01-KS)
Power Meter	Anritsu	ML2495A	1005002	50MHz Bandwidth	Jan. 20, 2016	Sep. 08, 2016~ Sep. 15, 2016	Jan. 19, 2017	Conducted (TH01-KS)
EMI Test Receiver	R&S	ESR7	101404	9kHz~7GHz; Max 30dBm	Oct. 20, 2015	Sep. 15, 2016	Oct. 19, 2016	Radiation (03CH02-SZ)
Spectrum Analyzer	R&S	FSV40	101041	10kHz~40GHz; Max 30dBm	Oct. 20, 2015	Sep. 15, 2016	Oct. 19, 2016	Radiation (03CH02-SZ)
Loop Antenna	R&S	HFH2-Z2	100354	9kHz~30MHz	May 07, 2016	Sep. 15, 2016	May 06, 2017	Radiation (03CH02-SZ)
Bilog Antenna	TeseQ	CBL6112D	35407	30MHz~2GHz	May 21, 2016	Sep. 15, 2016	May 20, 2017	Radiation (03CH02-SZ)
Double Ridge Horn Antenna	SCHWARZBECK	BBHA 9120D	9120D-128 5	1GHz~18GHz	Jan. 11, 2016	Sep. 15, 2016	Jan. 10, 2017	Radiation (03CH02-SZ)
SHF-EHF Horn	com-power	AH-840	101071	18GHz~40GHz	Aug. 10, 2016	Sep. 15, 2016	Aug. 09, 2017	Radiation (03CH02-SZ)
Amplifier	HP	8447F	3113A046 22	9kHz~1300MHz / 30 dB	Jul. 16, 2016	Sep. 15, 2016	Jul. 15, 2017	Radiation (03CH02-SZ)
HF Amplifier	MITEQ	AMF-7D-001 01800-30-10 P-R	1943528	1GHz~18GHz	Oct. 20, 2015	Sep. 15, 2016	Oct. 19, 2016	Radiation (03CH02-SZ)
Amplifier	Agilent	8449B	3008A010 23	1GHz~26.5GHz	Oct. 20, 2015	Sep. 15, 2016	Oct. 19, 2016	Radiation (03CH02-SZ)
AC Power Source	Chroma	61601	61601000 2470	N/A	NCR	Sep. 15, 2016	NCR	Radiation (03CH02-SZ)
Turn Table	Chaintek	T-200	N/A	0~360 degree	NCR	Sep. 15, 2016	NCR	Radiation (03CH02-SZ)
Antenna Mast	Chaintek	MBS-400	N/A	1 m~4 m	NCR	Sep. 15, 2016	NCR	Radiation (03CH02-SZ)
EMI Receiver	R&S	ESCI7	100768	9kHz~7GHz	Apr. 29, 2016	Aug. 29, 2016	Apr. 28, 2017	Conduction (CO01-KS)
AC LISN	MessTec	AN3016	060103	9kHz~30MHz	Oct. 24, 2015	Aug. 29, 2016	Oct. 23, 2016	Conduction (CO01-KS)
AC LISN (for auxiliary equipment)	MessTec	AN3016	060105	9kHz~30MHz	Oct. 24, 2015	Aug. 29, 2016	Oct. 23, 2016	Conduction (CO01-KS)
AC Power Source	Chroma	61602	ABP00000 0811	AC 0V~300V, 45Hz~1000Hz	Oct. 24, 2015	Aug. 29, 2016	Oct. 23, 2016	Conduction (CO01-KS)

NCR: No Calibration Required

## 5 Uncertainty of Evaluation

### Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	2.3dB
--	-------

### Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	5.0dB
--	-------

### Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	5.1dB
--	-------

### Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	5.1dB
--	-------



## Appendix A. Radiated Spurious Emission

2.4GHz 2400~2483.5MHz

BT (Band Edge @ 3m)

BT	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	( P/A )	( H/V )
BT CH00 2402MHz		2378.355	38.96	-35.04	74	42.52	25.96	3.81	33.33	185	40	P	H
		2378.355	14.13	-39.87	54	-	-	-	-	185	40	A	H
		2402	94.96	-	-	98.48	25.99	3.81	33.32	185	40	P	H
		2402	70.13	-	-	-	-	-	-	185	40	A	H
		2337.405	38.62	-35.38	74	42.29	25.89	3.77	33.33	198	127	P	V
		2337.405	13.79	-40.21	54	-	-	-	-	198	127	A	V
		2402	91.74	-	-	95.26	25.99	3.81	33.32	198	127	P	V
		2402	66.91	-	-	-	-	-	-	198	127	A	V
BT CH 39 2441MHz		2373.08	39.03	-34.97	74	42.59	25.96	3.81	33.33	186	39	P	H
		2373.08	14.2	-39.8	54	-	-	-	-	186	39	A	H
		2441	96.49	-	-	99.86	26.1	3.84	33.31	186	39	P	H
		2441	71.66	-	-	-	-	-	-	186	39	A	H
		2491.07	39.24	-34.76	74	42.44	26.2	3.91	33.31	186	39	P	H
		2491.07	14.41	-39.59	54	-	-	-	-	186	39	A	H
		2354.65	39.08	-34.92	74	42.72	25.92	3.77	33.33	150	100	P	V
		2354.65	14.25	-39.75	54	-	-	-	-	150	100	A	V
		2441	93.52	-	-	96.89	26.1	3.84	33.31	150	100	P	V
		2441	68.69	-	-	-	-	-	-	150	100	A	V
		2497.34	38.49	-35.51	74	41.68	26.2	3.91	33.3	150	100	P	V
		2497.34	13.66	-40.34	54	-	-	-	-	150	100	A	V



<b>BT CH 78 2480MHz</b>		2480	97.91	-	-	101.17	26.17	3.88	33.31	150	38	P	H
		2480	73.08	-	-	-	-	-	-	150	38	A	H
		2483.55	43.28	-30.72	74	46.54	26.17	3.88	33.31	150	38	P	H
		2483.55	18.45	-35.55	54	-	-	-	-	150	38	A	H
		2480	94.04	-	-	97.3	26.17	3.88	33.31	160	95	P	V
		2480	69.21	-	-	-	-	-	-	160	95	A	V
		2483.5	40.68	-33.32	74	43.94	26.17	3.88	33.31	160	95	P	V
		2483.5	15.85	-38.15	54	-	-	-	-	160	95	A	V
<b>Remark</b>	<ol style="list-style-type: none"><li>1. No other spurious found.</li><li>2. All results are PASS against Peak and Average limit line.</li></ol>												





## 2.4GHz 2400~2483.5MHz

## BT (Harmonic @ 3m)

BT	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB/m )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. ( P/A )	Pol. ( H/V )
BT CH 00 2402MHz		4804	40.1	-33.9	74	60.41	30.46	5.87	56.64	250	0	P	H
		4804	15.27	-38.73	54	-	-	-	-	250	0	A	H
		4804	42.01	-31.99	74	62.32	30.46	5.87	56.64	250	0	P	V
		4804	17.18	-36.82	54	-	-	-	-	250	0	A	V
BT CH 39 2441MHz		4882	40.91	-33.09	74	61.26	30.58	5.98	56.91	250	0	P	H
		4882	16.08	-37.92	54	-	-	-	-	250	0	A	H
		7323	43.78	-30.22	74	60.24	34.48	6.92	57.86	150	0	P	H
		7323	18.95	-35.05	54	-	-	-	-	150	0	A	H
		4882	41.69	-32.31	74	62.04	30.58	5.98	56.91	250	0	P	V
		4882	16.86	-37.14	54	-	-	-	-	250	0	A	V
		7323	43.23	-30.77	74	59.69	34.48	6.92	57.86	150	0	P	V
		7323	18.4	-35.6	54	-	-	-	-	150	0	A	V
BT CH 78 2480MHz		4960	41.58	-32.42	74	61	30.74	6.09	56.25	250	0	P	H
		4960	16.75	-37.25	54	-	-	-	-	250	0	A	H
		7440	43.96	-30.04	74	59.77	35.03	6.94	57.78	150	0	P	H
		7440	19.13	-34.87	54	-	-	-	-	150	0	A	H
		4960	40.99	-33.01	74	60.41	30.74	6.09	56.25	250	0	P	V
		4960	16.16	-37.84	54	-	-	-	-	250	0	A	V
		7440	44.61	-29.39	74	60.42	35.03	6.94	57.78	150	0	P	V
		7440	19.78	-34.22	54	-	-	-	-	150	0	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



## Emission below 1GHz

## 2.4GHz BT (LF)

BT	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	(dBμV)	( dB/m )	( dB )	( dB )	( cm )	( deg )	(P/A)	(H/V)
2.4GHz BT LF		30	25.02	-14.98	40	30.96	25.1	0.65	31.69	100	360	P	H
		128.94	18.5	-25	43.5	31.66	17.37	0.96	31.49	-	-	P	H
		256.98	20.49	-25.51	46	32.25	18.03	1.37	31.16	-	-	P	H
		549.92	27.44	-18.56	46	32.56	24.3	1.86	31.28	-	-	P	H
		719.67	29.18	-16.82	46	32.56	25.88	2.1	31.36	-	-	P	H
		835.1	30.91	-15.09	46	32.32	27.59	2.26	31.26	-	-	P	H
		36.79	29.25	-10.75	40	38.93	21.36	0.65	31.69	120	150	P	V
		46.49	23.37	-16.63	40	37.42	16.97	0.65	31.67	-	-	P	V
		71.71	18.97	-21.03	40	36.59	13.18	0.83	31.63	-	-	P	V
		323.91	22.28	-23.72	46	32.25	19.79	1.44	31.2	-	-	P	V
		737.13	29.05	-16.95	46	32.35	25.95	2.15	31.4	-	-	P	V
		959.26	32.94	-13.06	46	32.91	28.98	2.41	31.36	-	-	P	V
Remark	1. No other spurious found. 2. All results are PASS against limit line.												



**Note symbol**

	Fundamental Frequency which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
	Test result is over limit line.
P/A	Peak or Average
H/V	Horizontal or Vertical



A calculation example for radiated spurious emission is shown as below:

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1+2		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	(P/A)	(H/V)
802.11b		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
CH 01													
2412MHz		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

1. Level(dBμV/m) =

Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

2. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

#### For Peak Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)

= 55.45 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 55.45(dBμV/m) – 74(dBμV/m)

= -18.55(dB)

#### For Average Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)

= 43.54 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 43.54(dBμV/m) – 54(dBμV/m)

= -10.46(dB)

Both peak and average measured complies with the limit line, so test result is “PASS”.