

Report Number: F690501/RF-RTL014599

# **TEST REPORT**

of

FCC CFR 47 part 1, 1.1307(b), 1.1310

FCC ID: 2AH2J-KAMIBOTPI001

Equipment Under Test : Kam

: KamiBot Pi

Model Name

: KamiBot Pi-001

**Applicant** 

: 3.14 Co., Ltd.

Manufacturer

: 3.14 Co., Ltd.

Date of Receipt

: 2019.09.30

Date of Test(s)

: 2019.11.15 ~ 2019.11.29

Date of Issue

: 2019.12.11

In the configuration tested, the EUT complied with the standards specified above.

Tested By:

Date:

2019.12.11

Page:

of

5

Technical Manager:

Date:

2019.12.11

Jungmin Yang

Nancy Park



Report Number: F690501/RF-RTL014599 Page: 5 of

## **INDEX**

Table of Contents	Page
1. General Information	3
2. RF Exposure Evaluation	4



Report Number: F690501/RF-RTL014599 Page: 3 of 5

## 1. General Information

## 1.1. Testing Laboratory

SGS Korea Co., Ltd. (Gunpo Laboratory)

- 10-2, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807
- 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807
- Designation number: KR0150

All SGS services are rendered in accordance with the applicable SGS conditions of service available on

request and accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx.

Telephone : +82 31 688 0901 FAX : +82 31 688 0921

## 1.2. Details of Applicant

Applicant : 3.14 Co., Ltd.

Address : 201, 40, Yeonam-ro, Buk-gu, Daegu, Republic of Korea, 41260

Contact Person : Chae, Deok-byeong Phone No. : +82 70 5102 9367

#### 1.3. Details of Manufacturer

Company : Same as applicant Address : Same as applicant

### 1.4. Description of EUT

Kind of Product	KamiBot Pi	
Model Name	KamiBot Pi-001	
Power Supply	DC 3.7 V	
Frequency Range	2 402 Mb ~ 2 480 Mb (Bluetooth Low Energy)	
Modulation Technique	GFSK	
Number of Channels	40 channels (Bluetooth Low Energy)	
Antenna Type	a Type Multilayer Chip antenna	
Antenna Gain	4.36 dBi	

### 1.5. Test Report Revision

Revision	Report Number	Date of Issue	Description
0	F690501/RF-RTL014599	2019.12.11	Initial

The results of this test report are effective only to the items tested. The SGS Korea is not responsible for the sampling, the results of this test report apply to the sample as received. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.



Report Number: F690501/RF-RTL014599 Page: 4 of 5

## 2. RF Exposure Evaluation

## 2.1. Environmental evaluation and exposure limit according to FCC CFR 47 part 1, 1.1307(b), 1.1310

## LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (쌘)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (ﷺ)	Average Time	
(A) Limits for Occupational/Controlled Exposure					
0.3-3.0	614	1.63	*100	6	
3.0-30	1842/f	4.89/f	*900/f²	6	
30-300	61.4	0.163	1.0	6	
300-1 500	-	-	f/300	6	
1 500-100 000	-	-	5	6	
	(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*100	30	
1.34-30	824/f	2.19/f	*180/f²	30	
30-300	27.5	0.073	0.2	30	
300-1 500	-	-	f/1500	30	
1 500-100 000	-	-	1.0	<u>30</u>	

#### 2.1.1. Friis transmission formula: Pd = (Pout\*G)/(4\*pi\*R<sup>2</sup>)

Where Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

Pd the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

The results of this test report are effective only to the items tested. The SGS Korea is not responsible for the sampling, the results of this test report apply to the sample as received. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.



Report Number: F690501/RF-RTL014599 Page: of 5

## 2.1.2. Test Result of RF Exposure Evaluation

Test Item : RF Exposure Evaluation Data

Test Mode: Normal Operation

#### 2.1.3. Output Power into Antenna & RF Exposure Evaluation Distance

- Maximum tune up tolerance

Frequency (脈)	Output Average Power to Antenna (dB m)	Antenna Gain (dB i)	Power Density at 20 cm (ﷺ/ﷺ)	Limits (mW/cm²)
2 402 ~ 2 480	-8	4.36	0.000 086	1

#### Note:

- The power density Pd (5th column) at a distance of 20 cm calculated from the friis transmission formula is far below the limit of 1 mW/cm².
- This equipment complies with FCC radiation exposure limits set forth for an uncontrolled environment.
- This equipment should be installed and operated with minimum 20 cm between the radiator and your
- The antenna gain of this transmitter is less than 6 dBi and must not be collocated or operating in conjunction with any other antenna or transmitter unless authorized to do so by the FCC.

## - End of the Test Report -