BTM-150-B

Bluetooth 4.1 Asset Management Device

Label Specifications
Label Placement/Dimensions and Definitions
Revision: 1.3

Date: July 6, 2016

Product Label Size and Specifications

Size:

|←——— 29.7mm ———→|

Mobilogix, Inc.
Model: BTM-150-B

Major: xxxxx
Minor: yyyyy

FCC ID: 2AH4HBTM150B
IC: 21385 -BTM150B

(24.7mm height)

Product Label Layout, Font, Color and Font Size

TOP

| TEXT 1 |
| TEXT 2 |

| TEXT 3 |
| TEXT 4 |

| TEXT 5 |
| TEXT 6 |

BOTTOM

Note: image not to scale

Product Label Definitions

Title	Max Length/Format	Content/Alignment
TEXT 1	• Single line - 20 Digit/Alphanumeric • Font: Calibri, Size 8 • Color: Black – Bold	Company Name/Alignment Center: Mobilogix, Inc.
TEXT 2	• Single line - 20 Digit/Alphanumeric • Font: Calibri, Size 8 • Color: Black – Bold	P/N/Alignment Left: Model: BTM-150-B
TEXT 3	• Single line - 20 Digit/Alphanumeric • Font: Calibri, Size 8 • Color: Black - Bold	Unique Beacon Major ID (up to 6 digits) /Alignment Left: Major: (Unique ID)
TEXT 4	• Single line - 20 Digit/Alphanumeric • Font: Calibri, Size 8 • Color: Black - Bold	Unique Beacon Minor ID (up to 6 digits) /Alignment Left: Minor: (Unique ID)
TEXT 5	• Single line - 26 Digit/Alphanumeric • Font: Calibri, Size 8 • Color: Black	FCC ID /Alignment Left: FCC ID: 2AH4HBTM150B
TEXT 6	• Single line - 26 Digit/Alphanumeric • Font: Calibri, Size 8 • Color: Black	Industry Canada ID /Alignment Left: IC: ZZZZZZ-BTM150B

Product Label Placement

Label is located on the bottom side of the device:

Mobilogix, Inc.
Model: BTM-150-B

Major: xxxxx
Minor: yyyyy

FCC ID: 2AH4HBTM150B
IC: 21385 -BTM150B

Label Material & Printing Specifications:

Regulatory requirement dictate that the label be permanent adhered to the product. Additionally, the print must be highly resistant to scratches, common chemicals, and extended temperature ranges.

Required Label Stock: Avery Dennison Model MZ0333 (or equivalent with equal or better specifications)
    Approvals: UL indoor & outdoor service
    Adhesive: Industrial Grade, Permanent acrylic adhesive
    Material: white Polyster
    Type: Thermal Transfer
    Service Temperature: -40F to 149F
    Resistance: Abrasion/Smear/Scratch, Chemical, Moisture
    Color: White

Printer Ribbon Stock: Zebra Premium 5100 Resin Ribbon (or equivalent with equal or better specifications)
    Resistance: Smear/Scratch, Chemical (including harsh chemicals gas, acetone, and xylene)
    Color: Black