FCC ID: 2AH9Q-BLEV1-C

RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency	Electric Field	Magnetic Field	Power	Average Time		
Range(MHz)	Strength(V/m)	Strength(A/m)	Density(mW/cm ²)			
(A) Limits for Occupational/Control Exposures						
300-1500			F/300	6		
1500-100000			5	6		
(B) Limits for General Population/Uncontrol Exposures						
300-1500			F/1500	6		
1500-100000			1	30		

11.1 Friis transmission formula: Pd= (Pout*G)\ (4*pi*R²)

Where

Pd= Power density in mW/cm²

Pout=output power to antenna in mW

G= Numeric gain of the antenna relative to isotropic antenna

Pi=3.1416

R= distance between observation point and center of the radiator in cm (R=20cm)

Pd the limit of MPE, 1mW/cm². If we know the maximum gain of the nd total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

11.2 Measurement Result

Antenna gain: 1.5dBi

BT DSS

Channel Freq. (MHz)	modulation	conducted power (dBm)	Tune-up power (dBm)	Max tune-up power (dBm)	Antenna Gain Numeric	Evaluation result (mW/cm2)	Power density Limits (mW/cm2)
2402	GFSK	2.806	1to3	3	1.41	0.00056	1
2441	GFSK	1.793	0to2	2	1.41	0.00044	1
2480	GFSK	1.822	0to2	2	1.41	0.00044	1
2402	π/4 - DQPSK	0.158	-1to1	1	1.41	0.00035	1
2441	π /4- DQPSK	-1.042	-3to-1	-1	1.41	0.00022	1
2480	π /4- DQPSK	-1.257	-3to-1	-1	1.41	0.00022	1
2402	8DPSK	0.909	-1to1	1	1.41	0.00035	1
2441	8DPSK	-0.267	-2to0	0	1.41	0.00028	1
2480	8DPSK	-0.589	-2to0	0	1.41	0.00028	1

BT DTS

Channel Freq. (MHz)	modulation	conducted power (dBm)	Tune-up power (dBm)	Max tune-up power (dBm)	Antenna Gain Numeric	Evaluation result (mW/cm2)	Power density Limits (mW/cm2)
2402	GFSK	2.832	1to3	3	1.41	0.00056	1
2441	GFSK	2.804	1to3	3	1.41	0.00056	1
2480	GFSK	2.795	1to3	3	1.41	0.00056	1