Dongguan Nore Testing Center Co., Ltd. Report No.: NTC1906061FV00-1 FCC ID: 2AHAS-XBS9-1057

RF EXPOSURE EVALUATION

EUT Specification

EUT	Bluetooth Speaker						
Frequency band	□WLAN: 2.412GHz ~ 2.462GHz						
(Operating)	□WLAN: 5.18GHz ~ 5.32GHz / 5.50GHz ~ 5.70GHz						
	□WLAN: 5.745GHz ~ 5825GHz						
	⊠Others(Bluetooth: 2.402GHz ~ 2.480GHz)						
Device category	☐Portable (<20cm separation)						
	⊠Mobile (>20cm separation)						
	Others						
Antenna diversity	⊠Single antenna						
	☐Multiple antennas						
	☐Tx diversity						
	☐Rx diversity						
	☐Tx/Rx diversity						
Max. output power	-3.735 dBm (0.42316mW)						
Antenna gain	-0.68 dBi						
Evaluation applied							
	☐SAR Evaluation						

Limits for Maximum Permissible Exposure (MPE)

Frequency	Electric Field	Magnetic Field	Power Density(mW/cm ²)
Range(MHz)	Strength(V/m)	Strength(A/m)	
300-1500			F/1500
1500-100000			1

Friis transmission formula: Pd=(Pout*G)\(4*pi*R²)

Where

Pd= Power density in mW/cm²
Pout=output power to antenna in Mw
G= gain of antenna in linear scale
Pi=3.1416

R= distance between observation point and center of the radiator in cm

Pd the limit of MPE, 1mW/cm2. If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

Measurement Result

Channel	Gain	Channel	Max Output	Tolerance	Max	Power	Power		
		Frequency	power (dBm)		Tune-UP	density at	density		
		(MHz)			power	20cm	Limits		
					(mW)	(mW/ cm ²)	(mW/cm ²)		
GFSK									
Low	-0.68	2402	-4.909	± 0.5	0.36	0.00006	1		
Middle	-0.68	2441	-4.718	± 0.5	0.38	0.00006	1		
High	-0.68	2480	-4.460	± 0.5	0.40	0.00007	1		
π/4-DQPSK									
Low	-0.68	2402	-4.133	± 0.5	0.43	0.00007	1		
Middle	-0.68	2441	-4.006	± 0.5	0.45	0.00008	1		
High	-0.68	2480	-3.735	± 0.5	0.47	0.00008	1		