



TESTING LABORATORY
CERTIFICATE #4820.01



FCC PART 15.231

TEST REPORT

For

AKUVOX (XIAMEN) NETWORKS CO., LTD.

10/F, No.56, Software Park II, Xiamen, China

FCC ID: 2AHCR-VPR48G433

Report Type: Original Report	Product Type: Video Phone
Report Number: RXM180614051-00C	
Report Date: 2018-08-27	
Reviewed By:	Dean Lau <i>Dean Lau</i>
Test Laboratory: Bay Area Compliance Laboratories Corp. (Dongguan) No.69 Pulongcun, Puxinhu Industry Area, Tangxia, Dongguan, Guangdong, China Tel: +86-769-86858888 Fax: +86-769-86858891 www.baclcorp.com.cn	

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Dongguan). This report must not be used by the customer to claim product certification, approval, or endorsement by A2LA* or any agency of the Federal Government. * This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk “*”.

TABLE OF CONTENTS

GENERAL INFORMATION.....	3
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	3
OBJECTIVE	3
RELATED SUBMITTAL(S)/GRANT(S).....	3
TEST METHODOLOGY	3
MEASUREMENT UNCERTAINTY.....	4
TEST FACILITY	4
SYSTEM TEST CONFIGURATION.....	5
JUSTIFICATION	5
EUT EXERCISE SOFTWARE	5
SUPPORT EQUIPMENT LIST AND DETAILS	5
SUPPORT CABLE LIST AND DETAILS	5
BLOCK DIAGRAM OF TEST SETUP	6
SUMMARY OF TEST RESULTS	7
FCC §15.203 - ANTENNA REQUIREMENT.....	8
APPLICABLE STANDARD	8
FCC §15.207 (A)– AC LINE CONDUCTED EMISSIONS	9
APPLICABLE STANDARD	9
EUT SETUP	9
EMI TEST RECEIVER SETUP.....	9
TEST PROCEDURE	10
CORRECTED AMPLITUDE & MARGIN CALCULATION	10
TEST EQUIPMENT LIST AND DETAILS.....	10
TEST DATA	11
FCC §15.205, §15.209, §15.231 (B) - RADIATED EMISSIONS	15
APPLICABLE STANDARD	15
EUT SETUP	16
EMI TEST RECEIVER SETUP.....	16
TEST EQUIPMENT LIST AND DETAILS.....	17
TEST PROCEDURE	17
CORRECTED AMPLITUDE & MARGIN CALCULATION	17
TEST RESULTS SUMMARY	18
TEST DATA	18
FCC §15.231(C) – 20 DB BANDWIDTH TESTING.....	22
REQUIREMENT	22
TEST EQUIPMENT LIST AND DETAILS.....	22
TEST PROCEDURE	22
TEST DATA	22
FCC §15.231(A) - DEACTIVATION TESTING	24
APPLICABLE STANDARD	24
TEST EQUIPMENT LIST AND DETAILS.....	24
TEST DATA	24

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

EUT Name:		Video Phone
EUT Model:		VP-R48G(433)
Multiple Model:		R48G(433)
FCC ID:		2AHCR-VPR48G433
Rated Input Voltage:		DC12V from adapter or DC48V from POE
Adapter Information	Model:	RD1201000-C55-26MG
	Input:	AC 100-240V, 50/60Hz, 0.6A MAX
	Output:	DC 12V, 1A
External Dimension:		241mm(L)*198mm(W)*95mm(H)
Serial Number:		180614051
EUT Received Date:		2018.06.15

Note: The series product, models VP-R48G(433), R48G(433) are electrically identical, we selected VP-R48G(433) for testing, the details of the differences between them were explained in the declaration letter.

Objective

This report is prepared on behalf of **AKUVOX (XIAMEN) NETWORKS CO., LTD.** in accordance with Part 2, Subpart J, Part 15, Subparts A, and C of the Federal Communications Commission's rules.

The tests were performed in order to determine compliance with FCC Rules Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209, 15.35(c) and 15.231 rules.

Related Submittal(s)/Grant(s)

FCC Part 15C DSS submissions with FCC ID: 2AHCR-VPR48G433.
FCC Part 15C DTS submissions with FCC ID: 2AHCR-VPR48G433.
Submitted with the part of a system with FCC ID: 2AHCR-EP10-433.

Test Methodology

All measurements detailed in this Test Report were performed in accordance with ANSI C63.10-2013 "American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices".

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Dongguan).

Measurement Uncertainty

Parameter	Measurement Uncertainty
Occupied Channel Bandwidth	±5 %
Unwanted Emissions, radiated	30M~200MHz: 4.55 dB, 200M~1GHz: 5.92 dB, 1G~6GHz: 4.98 dB, 6G~18GHz: 5.89 dB, 18G~26.5G: 5.47 dB, 26.5G~40G: 5.63 dB
Temperature	±1 °C
Humidity	±5%
DC and low frequency voltages	±0.4%
Duty Cycle	1%
AC Power Lines Conducted Emission	3.12 dB (150 kHz to 30 MHz)

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.69 Pulongcun, Puxinhu Industry Area, Tangxia, Dongguan, Guangdong, China

The test site has been approved by the FCC under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 897218, the FCC Designation No. : CN1220.

The test site has been registered with ISED Canada under ISED Canada Registration Number 3062D.

SYSTEM TEST CONFIGURATION

Justification

The system was configured in testing mode which was provided by manufacturer.

EUT Exercise Software

No software was used in test.

Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
L.T.E.	SWITCHING MODE POWER SUPPLY	G0548B-480-050	N/A
Tenda	Router	D301	E3941017710003629
Huawei	Headset	N/A	
DELL	Notebook	PP11L	HLKYGB1
Sandisk	U-DISK	N/A	N/A
Dell	Monitor Plano Panel	U3011t	CN-OPH5NY-74445-17M-114L

Support Cable List and Details


Cable Description	Shielding Type	Ferrite Core	Length (m)	From Port	To
Adapter Cable	No	No	1.52	Adapter	EUT
RJ45 Cable	No	No	5.00	PC Port of EUT	Notebook
RJ45 Cable	No	No	5.00	INTERNET Port of EUT	Router
RJ45 Cable	No	No	1.00	INTERNET Port of EUT	POE
HDMI Cable	Yes	Yes	3.05	HDMI Port of EUT	Monitor

Block Diagram of Test Setup

M1



M2



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§15.203	Antenna Requirement	Compliance
§15.207 (a)	Conducted Emissions	Compliance
§15.205, §15.209, §15.231 (b)	Radiated Emissions	Compliance
§15.231 (c)	20dB Bandwidth	Compliance
§15.231 (a)	Deactivation Testing	Compliance

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

Result: Compliant.


The EUT has one internal antenna arrangement, which was permanently attached and the antenna gain is 0 dBi, fulfill the requirement of this section. Please refer to the EUT photos.

FCC §15.207 (a)– AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC§15.207(a)

EUT Setup



Note: 1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207.

The spacing between the peripherals was 10 cm.

The EUT was connected to the main lisn with a 8 or 24 V/60 Hz AC power source.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the adapter was connected to the first LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

Corrected Amplitude & Margin Calculation

The basic equation is as follows:

$$V_C = V_R + A_C + VDF$$

$$C_f = A_C + VDF$$

Herein,

V_C (cord. Reading): corrected voltage amplitude

V_R : reading voltage amplitude

A_C : attenuation caused by cable loss

VDF: voltage division factor of AMN

C_f : Correction Factor

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESCS 30	830245/006	2017-12-11	2018-12-11
Unknown	Coaxial Cable	C-NJNJ-50	C-0200-01	2017-09-05	2018-09-05
R&S	Test Software	EMC32	Version8.53.0	N/A	N/A
R&S	Two-line V-network	ENV 216	101614	2017-12-08	2018-12-08

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data**Environmental Conditions**


Temperature:	29.2 °C
Relative Humidity:	55 %
ATM Pressure:	101.3 kPa

The testing was performed by Sider Huang on 2018-07-03.

Test Mode: Transmitting


Adapter

AC120V, 60 Hz, Line:



Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.162441	46.7	9.000	L1	11.0	18.6	65.3	Compliance
0.186006	43.2	9.000	L1	10.8	21.0	64.2	Compliance
0.415949	34.6	9.000	L1	10.0	22.9	57.5	Compliance
0.715082	34.5	9.000	L1	9.8	21.5	56.0	Compliance
0.805868	34.0	9.000	L1	9.8	22.0	56.0	Compliance
1.573796	32.1	9.000	L1	9.7	23.9	56.0	Compliance

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.157346	35.2	9.000	L1	11.1	20.4	55.6	Compliance
0.343548	33.4	9.000	L1	10.1	15.7	49.1	Compliance
0.422630	29.8	9.000	L1	10.0	17.6	47.4	Compliance
0.681699	28.8	9.000	L1	9.8	17.2	46.0	Compliance
0.812315	28.7	9.000	L1	9.8	17.3	46.0	Compliance
1.599078	25.7	9.000	L1	9.7	20.3	46.0	Compliance


AC120V, 60 Hz, Neutral:

Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.151200	49.2	9.000	N	11.2	16.7	65.9	Compliance
0.167702	44.6	9.000	N	10.9	20.5	65.1	Compliance
0.173134	46.0	9.000	N	10.9	18.8	64.8	Compliance
0.649874	35.2	9.000	N	9.8	20.8	56.0	Compliance
1.039922	36.3	9.000	N	9.8	19.7	56.0	Compliance
1.890344	36.0	9.000	N	9.7	20.0	56.0	Compliance

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.175915	32.5	9.000	N	10.8	22.2	54.7	Compliance
0.319773	32.4	9.000	N	10.1	17.3	49.7	Compliance
0.726569	32.0	9.000	N	9.8	14.0	46.0	Compliance
0.937592	30.8	9.000	N	9.8	15.2	46.0	Compliance
1.860457	31.0	9.000	N	9.7	15.0	46.0	Compliance
2.130339	29.3	9.000	N	9.8	16.7	46.0	Compliance


PoE

AC120V, 60 Hz, Line:



Frequency (MHz)	QuasiPeak (dB μ V)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)	Comment
0.151200	49.5	9.000	L1	11.2	16.4	65.9	Compliance
0.157346	49.7	9.000	L1	11.1	15.9	65.6	Compliance
0.175915	55.3	9.000	L1	10.9	9.4	64.7	Compliance
0.262017	49.6	9.000	L1	10.3	11.8	61.4	Compliance
0.472507	47.4	9.000	L1	9.9	9.1	56.5	Compliance
12.198467	44.4	9.000	L1	9.9	15.6	60.0	Compliance

Frequency (MHz)	Average (dB μ V)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)	Comment
0.157346	44.5	9.000	L1	11.1	11.1	55.6	Compliance
0.190505	37.1	9.000	L1	10.7	16.9	54.0	Compliance
0.262017	47.4	9.000	L1	10.3	4.0	51.4	Compliance
0.387164	34.7	9.000	L1	10.0	13.4	48.1	Compliance
0.439808	40.8	9.000	L1	9.9	6.3	47.1	Compliance
0.476287	41.1	9.000	L1	9.9	5.3	46.4	Compliance

AC120V, 60 Hz, Neutral:

Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.178741	53.2	9.000	N	10.8	11.3	64.5	Compliance
0.193566	46.9	9.000	N	10.7	17.0	63.9	Compliance
0.262017	49.3	9.000	N	10.3	12.1	61.4	Compliance
0.406123	40.4	9.000	N	10.0	17.3	57.7	Compliance
0.465037	46.7	9.000	N	9.9	9.9	56.6	Compliance
12.493579	44.4	9.000	N	9.9	15.6	60.0	Compliance

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.174519	44.8	9.000	N	10.9	9.9	54.7	Compliance
0.262017	48.0	9.000	N	10.3	3.4	51.4	Compliance
0.351859	35.8	9.000	N	10.0	13.1	48.9	Compliance
0.393383	36.5	9.000	N	10.0	11.5	48.0	Compliance
0.429420	39.0	9.000	N	9.9	8.3	47.3	Compliance
0.472507	42.3	9.000	N	9.9	4.2	46.5	Compliance

FCC §15.205, §15.209, §15.231 (b) - RADIATED EMISSIONS**Applicable Standard**

FCC §15.205, §15.209, §15.231 (b)

(b) In addition to the provisions of §15.205, the field strength of emissions from intentional radiators operated under this section shall not exceed the following:

Fundamental frequency (MHz)	Field strength of fundamental (microvolts/meter)	Field strength of spurious emissions (microvolts/meter)
40.66-40.70	2,250	225
70-130	1,250	125
130-174	¹ 1,250 to 3,750	¹ 125 to 375
174-260	3,750	375
260-470	¹ 3,750 to 12,500	¹ 375 to 1,250
Above 470	12,500	1,250

¹Linear interpolations.


(1) The above field strength limits are specified at a distance of 3 meters. The tighter limits apply at the band edges.

(2) Intentional radiators operating under the provisions of this section shall demonstrate compliance with the limits on the field strength of emissions, as shown in the above table, based on the average value of the measured emissions. As an alternative, compliance with the limits in the above table may be based on the use of measurement instrumentation with a CISPR quasi-peak detector. The specific method of measurement employed shall be specified in the application for equipment authorization. If average emission measurements are employed, the provisions in §15.35 for averaging pulsed emissions and for limiting peak emissions apply. Further, compliance with the provisions of §15.205 shall be demonstrated using the measurement instrumentation specified in that section.


(3) The limits on the field strength of the spurious emissions in the above table are based on the fundamental frequency of the intentional radiator. Spurious emissions shall be attenuated to the average (or, alternatively, CISPR quasi-peak) limits shown in this table or to the general limits shown in §15.209, whichever limit permits a higher field strength.

EUT Setup

Below 1 GHz:



Above 1 GHz:



The radiated emission tests were performed in the 3 meters test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15 § 15.209, 15.205 and 15.231.

EMI Test Receiver Setup

The system was investigated from 30 MHz to 5 GHz.

During the radiated emission test, the test receiver was set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
30 MHz – 1000 MHz	100 kHz	300 kHz	100 kHz	PK
1 GHz – 5 GHz	1 MHz	3 MHz	/	PK

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESCI	100224	2017-12-11	2018-12-11
Farad	Test Software	EZ-EMC	V1.1.4.2	N/A	N/A
Sunol Sciences	Antenna	JB3	A060611-1	2017-11-10	2020-11-10
Unknown	Coaxial Cable	C-NJNJ-50	C-0400-01	2017-09-05	2018-09-05
Unknown	Coaxial Cable	C-NJNJ-50	C-0075-01	2017-09-05	2018-09-05
Unknown	Coaxial Cable	C-NJNJ-50	C-1000-01	2017-09-05	2018-09-05
HP	Amplifier	8447D	2727A05902	2017-09-05	2018-09-05
Agilent	Spectrum Analyzer	E4440A	SG43360054	2018-01-04	2019-01-04
ETS-Lindgren	Horn Antenna	3115	000 527 35	2016-01-05	2019-01-04
Unknown	Coaxial Cable	C-SJSJ-50	C-0800-01	2017-09-05	2018-09-05
E-Microwave	Band-stop filter	OBF-ZP-400-470-NF	OE01201051	2018-06-16	2019-06-16
MITEQ	Amplifier	AFS42-00101800-25-S-42	2001271	2017-09-05	2018-09-05

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

According to §15.231, Intentional radiators operating under the provisions of this Section shall demonstrate compliance with the limits on the field strength of emissions, based on the average value of the measured emissions. As an alternative, compliance with the limits in the above table may be based on the use of measurement instrumentation with a CISPR quasi-peak detector

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Results Summary

According to the data in the following table, the EUT complied with the CFR47 §15.205, §15.209, §15.231 (b).

Test Data

Environmental Conditions

Temperature:	26.5~27.6 °C
Relative Humidity:	39 ~59 %
ATM Pressure:	99.9~101.3 kPa

The testing was performed by Sunny Cen & Tyler Pan from 2018-07-05 to 2018-08-23.

Test mode: Transmitting

Field Strength (Peak)

Frequency	Receiver	Rx Antenna		Cable loss	Amplifier Gain	Corrected Amplitude	15.231(b)	
(MHz)	Reading (dBμV)	Polar (H/V)	Factor (dB)	(dB)	(dB)	(dBμV/m)	Limit (dBμV/m)	Margin (dB)
Operating Frequency:434 MHz								
434	59.35	H	16.48	2.65	0	78.48	80.83	2.35
434	56.77	V	16.48	2.65	0	75.90	80.83	4.93
868	35.76	H	21.76	4.09	26.68	34.93	60.83	25.90
868	36.43	V	21.76	4.09	26.68	35.60	60.83	25.23
1302	52.67	H	24.53	1.57	35.95	42.82	54.00	16.17
1302	53.02	V	24.53	1.57	35.95	43.17	54.00	10.83
1736	47.81	H	26.19	1.65	36.06	39.59	60.83	21.40
1736	48.76	V	26.19	1.65	36.06	40.54	60.83	21.09
2170	45.44	H	27.64	1.74	36.18	38.64	60.83	22.17
2170	47.49	V	27.64	1.74	36.18	40.69	60.83	21.42


Note: The peak field strength had been compliant with average limit, it is no need to test average detection.

Peak Test plots

Adapter


Horizontal:

Fundamental
with band-stop
filter




Vertical:

Fundamental
with band-stop
filter




PoE

Horizontal:




Vertical:




TX Mode

Horizontal:



Vertical:



FCC §15.231(c) – 20 dB BANDWIDTH TESTING

Requirement

Per 15.231(c), The bandwidth of the emission shall be no wider than 0.25% of the center frequency for devices operating above 70 MHz and below 900 MHz. Bandwidth is determined at the points 20 dB down from the modulated carrier.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESCI	100224	2017-09-01	2018-09-01
Sunol Sciences	Antenna	JB3	A060611-2	2017-08-25	2020-08-25
HP	Amplifier	8447D	2727A05902	2017-09-05	2018-09-05
N/A	Coaxial Cable	C-NJNJ-50	C-0400-01	2017-09-05	2018-09-05
N/A	Coaxial Cable	C-NJNJ-50	C-0075-01	2017-09-05	2018-09-05

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Procedure

With the EUT's antenna attached, the waveform was received by the test antenna which was connected to the spectrum analyzer, plot the 20 dB bandwidth.

Test Data

Environmental Conditions

Temperature:	26.9 °C
Relative Humidity:	38 %
ATM Pressure:	99.4 kPa

The testing was performed by Sunny Cen on 2018-08-16.


Test Mode: Transmitting

Please refer to following table and plot.

Channel Frequency (MHz)	20 dB Bandwidth (kHz)	Limit (kHz)	Result
434	137.6	1085	Pass

Note: Limit = 0.25% * Center Frequency = 0.25%*434 MHz = 1085 kHz

20 dB Bandwidth



Date: 16.AUG.2018 14:44:49

FCC §15.231(a) - DEACTIVATION TESTING

Applicable Standard

Per 15.231(a) (2), a transmitter activated automatically shall cease transmission within 5 seconds after activation.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESCI	100224	2017-09-01	2018-09-01
Sunol Sciences	Antenna	JB3	A060611-2	2017-08-25	2020-08-25
HP	Amplifier	8447D	2727A05902	2017-09-05	2018-09-05
N/A	Coaxial Cable	C-NJNJ-50	C-0400-01	2017-09-05	2018-09-05
N/A	Coaxial Cable	C-NJNJ-50	C-0075-01	2017-09-05	2018-09-05

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	26.7 °C
Relative Humidity:	45 %
ATM Pressure:	99.6 kPa


The testing was performed by Sunny Cen on 2018-08-22.

Test Mode: Transmitting

Test Result: Compliance. Please refer to following plot.

Deactivate Time (s)	Limit (s)	Result
0.46	<5	Pass

Transmission duration



Date: 22.AUG.2018 23:08:34

*****END OF REPORT*****