

FCC PART 15.247
TEST REPORT

For

AKUVOX (XIAMEN) NETWORKS CO., LTD.

10/F, No.56, Software Park II , Xiamen, China

FCC ID: 2AHCR-IT82X

Report Type: Original Report	Product Name: Indoor Monitor
Report Number: <u>RXM170824056-00B</u>	
Report Date: <u>2017-11-29</u>	
Reviewed By: <u>Jerry Zhang</u> EMC Manager	
Test Laboratory: Bay Area Compliance Laboratories Corp. (Dongguan) No.69 Pulongcun, Puxinhu Industry Area, Tangxia, Dongguan, Guangdong, China Tel: +86-769-86858888 Fax: +86-769-86858891 www.baclcorp.com.cn	

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Dongguan).

TABLE OF CONTENTS

GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY	4
MEASUREMENT UNCERTAINTY	4
TEST FACILITY	5
SYSTEM TEST CONFIGURATION.....	6
DESCRIPTION OF TEST CONFIGURATION	6
EUT EXERCISE SOFTWARE	7
EQUIPMENT MODIFICATIONS	10
SUPPORT EQUIPMENT LIST AND DETAILS	10
SUPPORT CABLE LIST AND DETAILS	10
BLOCK DIAGRAM OF TEST SETUP	10
SUMMARY OF TEST RESULTS	12
FCC §15.247 (i) , §1.1310 , §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)	13
APPLICABLE STANDARD	13
FCC §15.203 - ANTENNA REQUIREMENT.....	14
APPLICABLE STANDARD	14
ANTENNA CONNECTOR CONSTRUCTION	14
FCC §15.207 (a)– AC LINE CONDUCTED EMISSIONS	15
APPLICABLE STANDARD	15
EUT SETUP	15
EMI TEST RECEIVER SETUP.....	15
TEST PROCEDURE	16
CORRECTED AMPLITUDE & MARGIN CALCULATION	16
TEST EQUIPMENT LIST AND DETAILS.....	16
TEST DATA	17
FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS.....	21
APPLICABLE STANDARD	21
EUT SETUP	21
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	22
TEST PROCEDURE	22
CORRECTED AMPLITUDE & MARGIN CALCULATION	22
TEST EQUIPMENT LIST AND DETAILS.....	23
TEST DATA	23
FCC §15.247(a) (2)–6 dB EMISSION BANDWIDTH.....	32
APPLICABLE STANDARD	32
TEST PROCEDURE	32
TEST EQUIPMENT LIST AND DETAILS.....	32
TEST DATA	32
FCC §15.247(b) (3) - MAXIMUM PEAK CONDUCTED OUTPUT POWER.....	40
APPLICABLE STANDARD	40
TEST PROCEDURE	40
TEST EQUIPMENT LIST AND DETAILS.....	40

TEST DATA	41
FCC §15.247(d)– 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE.....	42
APPLICABLE STANDARD	42
TEST PROCEDURE	42
TEST EQUIPMENT LIST AND DETAILS.....	42
TEST DATA	43
FCC §15.247(e) - POWER SPECTRAL DENSITY	48
APPLICABLE STANDARD	48
TEST PROCEDURE	48
TEST EQUIPMENT LIST AND DETAILS.....	48
TEST DATA	48

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The **AKUVOX (XIAMEN) NETWORKS CO., LTD.**'s product, model number: **IT82A (FCC ID: 2AHCR-IT82X)** (the "EUT") in this report was a **Indoor Monitor**, which was measured approximately: 23 cm (L) x 16 cm (W) x 3 cm (H), rated input voltage:DC 12V from adapter or DC 48V from POE.

Note: The series product, models IT82A, IT82, IT82W are electrically identical, we selected IT82A for fully testing, and the differences details between them were explained in the attached declaration letter.

**All measurement and test data in this report was gathered from production sample serial number: 170824056 (Assigned by BACL,Dongguan). The EUT was received on 2017-10-31.*

Objective

This report is prepared on behalf of **AKUVOX (XIAMEN) NETWORKS CO., LTD.** in accordance with Part 2, Subpart J, Part 15, Subparts A and C of the Federal Communications Commission's rules.

The tests were performed in order to determine the compliance of the EUT with FCC Rules Part 15-Subpart C, section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Related Submittal(s)/Grant(s)

FCC Part 15C DSS submissions with FCC ID: 2AHCR-IT82X.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Dongguan).

Measurement Uncertainty

Parameter	Measurement Uncertainty
Occupied Channel Bandwidth	±5 %
RF output power, conducted	±0.61dB
Power Spectral Density, conducted	±0.61 dB
Unwanted Emissions, radiated	30M~200MHz: 4.58 dB for Horizontal, 4.59 dB for Vertical 200M~1GHz: 4.83 dB for Horizontal, 5.85 dB for Vertical 1G~6GHz: 4.45 dB, 6G~26.5GHz: 5.23 dB
Unwanted Emissions, conducted	±1.5 dB
Temperature	±1℃
Humidity	±5%
DC and low frequency voltages	±0.4%
Duty Cycle	1%
AC Power Lines Conducted Emission	3.12 dB (150 kHz to 30 MHz)

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.69 Pulongcun, Puxinhu Industry Area, Tangxia, Dongguan, Guangdong, China

Bay Area Compliance Laboratories Corp. (Dongguan) has been accredited to ISO/IEC 17025 by CNAS(Lab code: L5662). And accredited to ISO/IEC 17025 by NVLAP(Test Laboratory Accreditation Certificate Number 500069-0), the FCC Designation No. CN5002 under the KDB 974614 D01.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 273710. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

Bay Area Compliance Laboratories Corp. (Dongguan) was registered with ISED Canada under ISED Canada Registration Number 3062D.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in Engineering Mode, which was provided by the manufacturer.

For 2.4GHz band, total 11 channels are provided:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	7	2442
2	2417	8	2447
3	2422	9	2452
4	2427	10	2457
5	2432	11	2462
6	2437	/	/

For 802.11b, 802.11g, and 802.11n ht20 modes were test with channel 1,6,11.

The worst-case data rates are determined to be as follows for each mode based upon investigations by measuring the average power and PSD across all data rates bandwidths, and modulations.

For Bluetooth LE mode, 40 channels are provided for testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	20	2442
1	2404
...
...
..	...	38	2478
19	2440	39	2480

EUT was tested with channel 0, 19 and 39.

EUT Exercise Software


The software “Engineer Mode” was used for testing, which was provided by manufacturer. The maximum power was configured as below table, that provided by the manufacturer:

Test Mode	Test Software Version	Engineer Mode		
802.11b	Test Frequency	2412MHz	2437MHz	2462MHz
	Data Rate	1Mbps	1Mbps	1Mbps
	Power Level Setting	10	10	10
802.11g	Test Frequency	2412MHz	2437MHz	2462MHz
	Data Rate	6Mbps	6Mbps	6Mbps
	Power Level Setting	10	10	10
802.11n ht20	Test Frequency	2412MHz	2437MHz	2462MHz
	Data Rate	MCS0	MCS0	MCS0
	Power Level Setting	10	10	10
BLE	Test Frequency	2402MHz	2440Hz	2480MHz
	Power Level Setting	8	8	8

The maximum duty cycle as following table:


Test mode	T _{on} (ms)	T _{on+off} (ms)	Duty Cycle (%)
802.11b	100	100	100
802.11g	1.302	1.400	93.0
802.11n ht20	1.400	1.498	93.4
BLE	0.385	0.625	61.6

802.11b




Date: 17.NOV.2017 19:55:10

802.11g




Date: 17.NOV.2017 19:51:22

802.11n ht20



Date: 17.NOV.2017 20:13:41

BLE



Date: 17.NOV.2017 21:53:08

Equipment Modifications

No modification was made to the EUT.

Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
TZY	PoE Adapter	AP15-120100TB	N/A
TZY	Switching Power Adapter	G0548B-480-050	N/A
DELL	Laptop	PP11L	QDS-BRCM1017
AKUVOX	Indoor Monitor	IT82C	N/A

Support Cable List and Details


Cable Description	Shielding Type	Ferrite Core	Length (m)	From Port	To
RJ45	No	No	10	RJ45 Port of Laptop	EUT
RJ45	No	No	10	RJ45 Port of Indoor Monitor	EUT

Block Diagram of Test Setup

Adapter:



POE:



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
FCC §15.247 (i) & §1.1310 & §2.1091	Maximum Permissible Exposure (MPE)	Compliance
§15.203	Antenna Requirement	Compliance
§15.207 (a)	AC Line Conducted Emissions	Compliance
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliance
§15.247 (a)(2)	6 dB Bandwidth	Compliance
§15.247(b)(3)	Maximum Conducted Output Power	Compliance
§15.247(d)	100 kHz Bandwidth of Frequency Band Edge	Compliance
§15.247(e)	Power Spectral Density	Compliance

FCC §15.247 (i) , §1.1310 , §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to subpart 15.247(i) and subpart §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

(B) Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minutes)
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500	/	/	f/1500	30
1500–100,000	/	/	1.0	30

f = frequency in MHz; * = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

Calculation Formula:

Prediction of power density at the distance of the applicable MPE limit:

$S = PG/4\pi R^2$ = power density (in appropriate units, e.g. mW/cm²);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

Calculated Data:

Frequency (MHz)	Antenna Gain		Tune-up Power		Evaluation Distance (cm)	Power Density (mW/cm ²)	MPE Limit (mW/cm ²)
	(dBi)	(numeric)	(dBm)	(mW)			
2412-2462	2	1.58	23	199.53	20.00	0.0629	1.0
2402-2480	2	1.58	8	6.31	20.00	0.0020	1.0

Note: the Bluetooth and Wifi can't transmit simultaneously.

Result: Compliance, The device meets MPE requirement for Devices Used by the General Public (Uncontrolled Environment) at distance ≥ 20 cm.

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.
- c. Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

Antenna Connector Construction

The EUT has one internal antenna arrangement for BT&WiFi, and the antenna gain is 2.0 dBi, fulfill the requirement of this section. Please refer to the EUT photos.


Result: Compliance.

FCC §15.207 (a)– AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC§15.207(a)

EUT Setup



Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207.

The spacing between the peripherals was 10 cm.

The adapter or POE was connected to the main lisen with a 120 V/60 Hz AC power source.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the adapter or POE was connected to the first LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

Corrected Amplitude & Margin Calculation

The basic equation is as follows:

$$V_C = V_R + A_C + VDF$$

$$C_f = A_C + VDF$$

Herein,

V_C (cord. Reading): corrected voltage amplitude

V_R : reading voltage amplitude

A_C : attenuation caused by cable loss

VDF: voltage division factor of AMN

C_f : Correction Factor

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESCS 30	830245/006	2016/12/8	2017/12/8
R&S	L.I.S.N	ESH2-Z5	892107/021	2017/9/25	2018/9/25
R&S	Two-line V-network	ENV 216	3560.6550.12	2016/12/8	2017/12/8
R&S	Test Software	EMC32	Version8.53.0	N/A	N/A
N/A	Coaxial Cable	C-NJNJ-50	C-0200-01	2017/9/5	2018/9/5

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).


Test Data**Environmental Conditions**

Temperature:	25.9°C
Relative Humidity:	38 %
ATM Pressure:	101.9 kPa

The testing was performed by Gaochao Gong on 2017-11-01.

Test Mode: Transmitting (Adapter)


AC120 V, 60 Hz, Line:



Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.180171	45.0	9.000	L1	10.8	19.5	64.5	Compliance
0.264113	39.7	9.000	L1	10.3	21.6	61.3	Compliance
0.274848	42.5	9.000	L1	10.2	18.5	61.0	Compliance
0.406123	47.9	9.000	L1	10.0	9.8	57.7	Compliance
0.432855	45.1	9.000	L1	9.9	12.1	57.2	Compliance
0.519918	39.4	9.000	L1	9.9	16.6	56.0	Compliance

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.290613	35.7	9.000	L1	10.2	14.8	50.5	Compliance
0.304845	34.0	9.000	L1	10.1	16.1	50.1	Compliance
0.415949	42.0	9.000	L1	10.0	5.5	47.5	Compliance
0.432855	40.8	9.000	L1	9.9	6.4	47.2	Compliance
0.519918	31.1	9.000	L1	9.9	14.9	46.0	Compliance
0.709407	27.1	9.000	L1	9.8	18.9	46.0	Compliance

AC120 V, 60 Hz, Neutral:




Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.157346	44.1	9.000	N	11.1	21.5	65.6	Compliance
0.262017	39.1	9.000	N	10.3	22.3	61.4	Compliance
0.302425	44.2	9.000	N	10.1	16.0	60.2	Compliance
0.409372	48.7	9.000	N	10.0	9.0	57.7	Compliance
0.439808	44.5	9.000	N	9.9	12.6	57.1	Compliance
0.519918	39.5	9.000	N	9.9	16.5	56.0	Compliance

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.312220	39.3	9.000	N	10.1	10.6	49.9	Compliance
0.396530	42.0	9.000	N	10.0	5.9	47.9	Compliance
0.432855	41.9	9.000	N	9.9	5.3	47.2	Compliance
0.507637	37.5	9.000	N	9.9	8.5	46.0	Compliance
0.726569	34.1	9.000	N	9.8	11.9	46.0	Compliance
24.594166	35.3	9.000	N	10.1	14.7	50.0	Compliance


Test Mode: Transmitting (POE)

AC120 V, 60 Hz, Line:



Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.174519	47.6	9.000	L1	10.9	17.1	64.7	Compliance
0.335433	44.2	9.000	L1	10.1	15.1	59.3	Compliance
3.224010	38.9	9.000	L1	9.8	17.1	56.0	Compliance
4.541500	38.8	9.000	L1	9.8	17.2	56.0	Compliance
12.198467	45.9	9.000	L1	9.9	14.1	60.0	Compliance
13.422446	47.2	9.000	L1	9.9	12.8	60.0	Compliance

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.343548	39.6	9.000	L1	10.1	9.5	49.1	Compliance
4.614454	29.3	9.000	L1	9.8	16.7	46.0	Compliance
12.198467	43.9	9.000	L1	9.9	6.1	50.0	Compliance
13.422446	41.6	9.000	L1	9.9	8.4	50.0	Compliance
15.247554	38.9	9.000	L1	10.0	11.1	50.0	Compliance
16.777473	42.4	9.000	L1	10.0	7.6	50.0	Compliance

AC120 V, 60 Hz, Neutral:

Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.190505	49.0	9.000	N	10.7	15.0	64.0	Compliance
0.343548	44.9	9.000	N	10.1	14.2	59.1	Compliance
3.519348	39.3	9.000	N	9.8	16.7	56.0	Compliance
3.604490	39.8	9.000	N	9.8	16.2	56.0	Compliance
13.422446	46.1	9.000	N	9.9	13.9	60.0	Compliance
15.616430	47.9	9.000	N	10.0	12.1	60.0	Compliance

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.343548	38.9	9.000	N	10.1	10.2	49.1	Compliance
12.198467	38.0	9.000	N	9.9	12.0	50.0	Compliance
13.422446	41.9	9.000	N	9.9	8.1	50.0	Compliance
15.247554	42.4	9.000	N	9.9	7.6	50.0	Compliance
15.616430	40.5	9.000	N	10.0	9.5	50.0	Compliance
16.777473	40.2	9.000	N	10.0	9.8	50.0	Compliance


FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS

Applicable Standard


FCC §15.247 (d); §15.209; §15.205;

EUT Setup

Below 1GHz:



Above 1GHz:



The radiated emission tests were performed in the 3 meters distance, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

The spacing between the peripherals was 10 cm.

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

30MHz-1000MHz:

Measurement	RBW	Video B/W	IF B/W
QP	120 kHz	300 kHz	120kHz

1GHz- 25GHz:

Measurement	Duty cycle	RBW	Video B/W
PK	Any	1MHz	3 MHz
AV	>98%	1MHz	10 Hz
	<98%	1MHz	1/T

Note: T is minimum transmission duration

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz, peak and Average detection modes for frequencies above 1 GHz.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESCI	100224	2017/9/1	2018/9/1
Sunol Sciences	Antenna	JB3	A060611-2	2017/8/25	2020/8/25
HP	Amplifier	8447D	2727A05902	2017/9/5	2018/9/5
Agilent	Spectrum Analyzer	E4440A	SG43360054	2016/12/8	2017/12/8
ETS-Lindgren	Horn Antenna	3115	000 527 35	2016/1/5	2019/1/5
MITEQ	Amplifier	AFS42-00101800-25-S-42	2001271	2017/9/5	2018/9/5
Ducommun Technologies	Horn Antenna	ARH-4223-02	1007726-02 1304	2017/11/18	2018/11/18
Quinstar	Amplifier	QLW-18405536-JO	15964001001	2017/6/27	2018/6/27
N/A	Coaxial Cable	C-NJNJ-50	C-0400-01	2017/9/5	2018/9/5
N/A	Coaxial Cable	C-NJNJ-50	C-0075-01	2017/9/5	2018/9/5
N/A	Coaxial Cable	C-NJNJ-50	C-1000-01	2017/9/5	2018/9/5
N/A	Coaxial Cable	C-SJSJ-50	C-0800-01	2017/9/5	2018/9/5
Farad	Test Software	EZ-EMC	V1.1.42	N/A	N/A
Chengdu Ouli	Band Rejection Filter	2400-2483.5	002	2017/9/5	2018/9/5

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).


Test Data**Environmental Conditions**

Temperature:	25.6°C
Relative Humidity:	40 %
ATM Pressure:	101.9 kPa


The testing was performed by Sunny Cen on 2017-11-20.

Test Result: Compliance, please Refer to the following data

Test Mode: Transmitting (adapter mode was the worst)

1) 30MHz-1GHz(802.11b mode High channel was the worst)**Horizontal:**

Frequency (MHz)	Receiver Reading (dBuV)	Detector	Correction Factor (dB/m)	Cord. Amp. (dBuV/m)	Limit (dBuV/m)	Margin (dB)
288.0200	43.72	QP	-3.82	39.90	46.00	6.10
303.5400	47.23	QP	-4.43	42.80	46.00	3.20
367.5600	43.60	QP	-2.60	41.00	46.00	5.00
400.5400	43.69	QP	-2.19	41.50	46.00	4.50
432.5500	44.48	QP	-1.78	42.70	46.00	3.30
450.0100	43.54	QP	-1.34	42.20	46.00	3.80

Vertical:

Frequency (MHz)	Receiver Reading (dBuV)	Detector	Correction Factor (dB/m)	Cord. Amp. (dBuV/m)	Limit (dBuV/m)	Margin (dB)
288.0200	43.52	QP	-3.82	39.70	46.00	6.30
352.0400	44.61	QP	-3.21	41.40	46.00	4.60
367.5600	43.50	QP	-2.60	40.90	46.00	5.10
400.5400	43.49	QP	-2.19	41.30	46.00	4.70
416.0600	44.13	QP	-1.93	42.20	46.00	3.80
450.0100	43.94	QP	-1.34	42.60	46.00	3.40

2) 1-25GHz:

802.11b Mode:

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector (PK/QP/AV)	Polar (H/V)	Factor (dB)					
Low Channel: 2412 MHz									
2412.00	74.37	PK	H	28.12	1.81	0.00	104.3	N/A	N/A
2412.00	69.58	AV	H	28.12	1.81	0.00	99.51	N/A	N/A
2412.00	75.76	PK	V	28.12	1.81	0.00	105.69	N/A	N/A
2412.00	70.34	AV	V	28.12	1.81	0.00	100.27	N/A	N/A
2390.00	25.82	PK	V	28.08	1.80	0.00	55.7	74.00	18.3
2390.00	14.35	AV	V	28.08	1.80	0.00	44.23	54.00	9.77
4824.00	48.24	PK	V	32.95	3.19	37.20	47.18	74.00	26.82
4824.00	33.56	AV	V	32.95	3.19	37.20	32.5	54.00	21.5
7236.00	47.48	PK	V	35.81	4.77	37.27	50.79	74.00	23.21
7236.00	32.37	AV	V	35.81	4.77	37.27	35.68	54.00	18.32
5965.00	46.54	PK	V	34.29	3.82	37.29	47.36	74.00	26.64
5965.00	32.29	AV	V	34.29	3.82	37.29	33.11	54.00	20.89
Middle Channel: 2437 MHz									
2437.00	74.58	PK	H	28.17	1.82	0.00	104.57	N/A	N/A
2437.00	69.37	AV	H	28.17	1.82	0.00	99.36	N/A	N/A
2437.00	76.85	PK	V	28.17	1.82	0.00	106.84	N/A	N/A
2437.00	71.39	AV	V	28.17	1.82	0.00	101.38	N/A	N/A
4874.00	48.09	PK	V	33.05	3.26	37.21	47.19	74.00	26.81
4874.00	36.43	AV	V	33.05	3.26	37.21	35.53	54.00	18.47
7311.00	47.51	PK	V	36.01	4.64	37.36	50.8	74.00	23.2
7311.00	32.57	AV	V	36.01	4.64	37.36	35.86	54.00	18.14
5899.00	46.34	PK	V	34.26	3.79	37.22	47.17	74.00	26.83
5899.00	32.21	AV	V	34.26	3.79	37.22	33.04	54.00	20.96
6125.00	46.28	PK	V	34.28	4.06	37.27	47.35	74.00	26.65
6125.00	32.57	AV	V	34.28	4.06	37.27	33.64	54.00	20.36
High Channel: 2462 MHz									
2462.00	74.67	PK	H	28.22	1.83	0.00	104.72	N/A	N/A
2462.00	69.34	AV	H	28.22	1.83	0.00	99.39	N/A	N/A
2462.00	76.88	PK	V	28.22	1.83	0.00	106.93	N/A	N/A
2462.00	71.26	AV	V	28.22	1.83	0.00	101.31	N/A	N/A
2483.50	28.49	PK	V	28.27	1.84	0.00	58.6	74.00	15.4
2483.50	14.65	AV	V	28.27	1.84	0.00	44.76	54.00	9.24
4924.00	48.06	PK	V	33.15	3.27	37.22	47.26	74.00	26.74
4924.00	33.41	AV	V	33.15	3.27	37.22	32.61	54.00	21.39
7386.00	47.61	PK	V	36.20	4.51	37.46	50.86	74.00	23.14
7386.00	31.35	AV	V	36.20	4.51	37.46	34.6	54.00	19.4
5698.00	46.66	PK	V	34.18	3.68	37.35	47.17	74.00	26.83
5698.00	32.49	AV	V	34.18	3.68	37.35	33	54.00	21

802.11g Mode:

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector (PK/QP/AV)	Polar (H/V)	Factor (dB)					
Low Channel: 2412 MHz									
2412.00	74.69	PK	H	28.12	1.81	0.00	104.62	N/A	N/A
2412.00	64.53	AV	H	28.12	1.81	0.00	94.46	N/A	N/A
2412.00	78.94	PK	V	28.12	1.81	0.00	108.87	N/A	N/A
2412.00	68.75	AV	V	28.12	1.81	0.00	98.68	N/A	N/A
2390.00	35.27	PK	V	28.08	1.80	0.00	65.15	74.00	8.85
2390.00	16.26	AV	V	28.08	1.80	0.00	46.14	54.00	7.86
4824.00	48.19	PK	V	32.95	3.19	37.20	47.13	74.00	26.87
4824.00	33.49	AV	V	32.95	3.19	37.20	32.43	54.00	21.57
7236.00	47.43	PK	V	35.81	4.77	37.27	50.74	74.00	23.26
7236.00	32.32	AV	V	35.81	4.77	37.27	35.63	54.00	18.37
5965.00	46.34	PK	V	34.29	3.82	37.29	47.16	74.00	26.84
5965.00	32.33	AV	V	34.29	3.82	37.29	33.15	54.00	20.85
Middle Channel: 2437 MHz									
2437.00	74.58	PK	H	28.17	1.82	0.00	104.57	N/A	N/A
2437.00	64.44	AV	H	28.17	1.82	0.00	94.43	N/A	N/A
2437.00	79.32	PK	V	28.17	1.82	0.00	109.31	N/A	N/A
2437.00	68.76	AV	V	28.17	1.82	0.00	98.75	N/A	N/A
4874.00	48.05	PK	V	33.05	3.26	37.21	47.15	74.00	26.85
4874.00	33.41	AV	V	33.05	3.26	37.21	32.51	54.00	21.49
7311.00	47.51	PK	V	36.01	4.64	37.36	50.8	74.00	23.2
7311.00	32.67	AV	V	36.01	4.64	37.36	35.96	54.00	18.04
5899.00	46.28	PK	V	34.26	3.79	37.22	47.11	74.00	26.89
5899.00	32.36	AV	V	34.26	3.79	37.22	33.19	54.00	20.81
6125.00	46.16	PK	V	34.28	4.06	37.27	47.23	74.00	26.77
6125.00	32.73	AV	V	34.28	4.06	37.27	33.8	54.00	20.2
High Channel: 2462 MHz									
2462.00	74.81	PK	H	28.22	1.83	0.00	104.86	N/A	N/A
2462.00	64.33	AV	H	28.22	1.83	0.00	94.38	N/A	N/A
2462.00	79.11	PK	V	28.22	1.83	0.00	109.16	N/A	N/A
2462.00	68.75	AV	V	28.22	1.83	0.00	98.8	N/A	N/A
2483.50	36.16	PK	V	28.27	1.84	0.00	66.27	74.00	7.73
2483.50	16.65	AV	V	28.27	1.84	0.00	46.76	54.00	7.24
4924.00	48.23	PK	V	33.15	3.27	37.22	47.43	74.00	26.57
4924.00	33.56	AV	V	33.15	3.27	37.22	32.76	54.00	21.24
7386.00	47.46	PK	V	36.20	4.51	37.46	50.71	74.00	23.29
7386.00	32.55	AV	V	36.20	4.51	37.46	35.8	54.00	18.2
6256.00	46.63	PK	V	34.25	4.30	37.20	47.98	74.00	26.02
6256.00	32.31	AV	V	34.25	4.30	37.20	33.66	54.00	20.34

802.11n ht20 Mode:




Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector (PK/QP/AV)	Polar (H/V)	Factor (dB)					
Low Channel: 2412 MHz									
2412.00	73.39	PK	H	28.12	1.81	0.00	103.32	N/A	N/A
2412.00	63.42	AV	H	28.12	1.81	0.00	93.35	N/A	N/A
2412.00	75.87	PK	V	28.12	1.81	0.00	105.8	N/A	N/A
2412.00	65.49	AV	V	28.12	1.81	0.00	95.42	N/A	N/A
2390.00	35.34	PK	V	28.08	1.80	0.00	65.22	74.00	8.78
2390.00	15.68	AV	V	28.08	1.80	0.00	45.56	54.00	8.44
4824.00	48.09	PK	V	32.95	3.19	37.20	47.03	74.00	26.97
4824.00	33.55	AV	V	32.95	3.19	37.20	32.49	54.00	21.51
7236.00	47.37	PK	V	35.81	4.77	37.27	50.68	74.00	23.32
7236.00	32.28	AV	V	35.81	4.77	37.27	35.59	54.00	18.41
5965.00	46.61	PK	V	34.29	3.82	37.29	47.43	74.00	26.57
5965.00	32.38	AV	V	34.29	3.82	37.29	33.2	54.00	20.8
Middle Channel: 2437 MHz									
2437.00	73.87	PK	H	28.17	1.82	0.00	103.86	N/A	N/A
2437.00	63.76	AV	H	28.17	1.82	0.00	93.75	N/A	N/A
2437.00	76.49	PK	V	28.17	1.82	0.00	106.48	N/A	N/A
2437.00	66.52	AV	V	28.17	1.82	0.00	96.51	N/A	N/A
4874.00	48.44	PK	V	33.05	3.26	37.21	47.54	74.00	26.46
4874.00	33.41	AV	V	33.05	3.26	37.21	32.51	54.00	21.49
7311.00	47.32	PK	V	36.01	4.64	37.36	50.61	74.00	23.39
7311.00	32.17	AV	V	36.01	4.64	37.36	35.46	54.00	18.54
5899.00	46.45	PK	V	34.26	3.79	37.22	47.28	74.00	26.72
5899.00	32.39	AV	V	34.26	3.79	37.22	33.22	54.00	20.78
6125.00	46.48	PK	V	34.28	4.06	37.27	47.55	74.00	26.45
6125.00	32.43	AV	V	34.28	4.06	37.27	33.5	54.00	20.5
High Channel: 2462 MHz									
2462.00	73.64	PK	H	28.22	1.83	0.00	103.69	N/A	N/A
2462.00	63.52	AV	H	28.22	1.83	0.00	93.57	N/A	N/A
2462.00	76.15	PK	V	28.22	1.83	0.00	106.2	N/A	N/A
2462.00	66.23	AV	V	28.22	1.83	0.00	96.28	N/A	N/A
2483.50	35.45	PK	V	28.27	1.84	0.00	65.56	74.00	8.44
2483.50	16.37	AV	V	28.27	1.84	0.00	46.48	54.00	7.52
4924.00	48.28	PK	V	33.15	3.27	37.22	47.48	74.00	26.52
4924.00	33.61	AV	V	33.15	3.27	37.22	32.81	54.00	21.19
7386.00	47.53	PK	V	36.20	4.51	37.46	50.78	74.00	23.22
7386.00	32.24	AV	V	36.20	4.51	37.46	35.49	54.00	18.51
7265.00	46.6	PK	V	35.89	4.72	37.30	49.91	74.00	24.09
7265.00	32.38	AV	V	35.89	4.72	37.30	35.69	54.00	18.31

BLE Mode:

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector	Polar (H/V)	Factor (dB)					
Low Channel: 2402 MHz									
2402.00	71.49	PK	H	28.10	1.80	0.00	101.39	N/A	N/A
2402.00	66.07	AV	H	28.10	1.80	0.00	95.97	N/A	N/A
2402.00	73.82	PK	V	28.10	1.80	0.00	103.72	N/A	N/A
2402.00	68.34	AV	V	28.10	1.80	0.00	98.24	N/A	N/A
2390.00	25.56	PK	V	28.08	1.80	0.00	55.44	74.00	18.56
2390.00	13.28	AV	V	28.08	1.80	0.00	43.16	54.00	10.84
4804.00	48.69	PK	V	32.91	3.17	37.20	47.57	74.00	26.43
4804.00	33.46	AV	V	32.91	3.17	37.20	32.34	54.00	21.66
7206.00	47.67	PK	V	35.74	4.82	37.23	51	74.00	23
7206.00	32.78	AV	V	35.74	4.82	37.23	36.11	54.00	17.89
6296.50	47.34	PK	V	34.24	4.38	37.18	48.78	74.00	25.22
6296.50	33.27	AV	V	34.24	4.38	37.18	34.71	54.00	19.29
Middle Channel: 2440 MHz									
2440.00	72.48	PK	H	28.18	1.82	0.00	102.48	N/A	N/A
2440.00	67.35	AV	H	28.18	1.82	0.00	97.35	N/A	N/A
2440.00	73.76	PK	V	28.18	1.82	0.00	103.76	N/A	N/A
2440.00	68.53	AV	V	28.18	1.82	0.00	98.53	N/A	N/A
4880.00	48.65	PK	V	33.06	3.27	37.21	47.77	74.00	26.23
4880.00	33.48	AV	V	33.06	3.27	37.21	32.6	54.00	21.4
7320.00	47.56	PK	V	36.03	4.62	37.37	50.84	74.00	23.16
7320.00	32.85	AV	V	36.03	4.62	37.37	36.13	54.00	17.87
5899.00	47.36	PK	V	34.26	3.79	37.22	48.19	74.00	25.81
5899.00	32.34	AV	V	34.26	3.79	37.22	33.17	54.00	20.83
6125.00	47.58	PK	V	34.28	4.06	37.27	48.65	74.00	25.35
6125.00	32.42	AV	V	34.28	4.06	37.27	33.49	54.00	20.51
High Channel: 2480 MHz									
2480.00	71.63	PK	H	28.26	1.84	0.00	101.73	N/A	N/A
2480.00	65.89	AV	H	28.26	1.84	0.00	95.99	N/A	N/A
2480.00	73.84	PK	V	28.26	1.84	0.00	103.94	N/A	N/A
2480.00	67.45	AV	V	28.26	1.84	0.00	97.55	N/A	N/A
2483.50	29.55	PK	V	28.27	1.84	0.00	59.66	74.00	14.34
2483.50	14.09	AV	V	28.27	1.84	0.00	44.2	54.00	9.8
4960.00	48.66	PK	V	33.22	3.23	37.25	47.86	74.00	26.14
4960.00	33.59	AV	V	33.22	3.23	37.25	32.79	54.00	21.21
7440.00	47.73	PK	V	36.34	4.41	37.52	50.96	74.00	23.04
7440.00	32.63	AV	V	36.34	4.41	37.52	35.86	54.00	18.14
5985.00	47.51	PK	V	34.29	3.82	37.31	48.31	74.00	25.69
5985.00	32.08	AV	V	34.29	3.82	37.31	32.88	54.00	21.12




**Test plots(802.11b Middle channel was the worst)
Horizontal:**

Fundamental
Test with Band
Rejection Filter



Vertical:

Fundamental
Test with Band
Rejection Filter



FCC §15.247(a) (2)–6 dB EMISSION BANDWIDTH


Applicable Standard

According to FCC §15.247(a) (2)

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Test Procedure

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESCI	101121	2017/3/2	2018/3/2
N/A	Coaxial Cable	C-SJ00-0010	C0010/01	Each Time	/

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	25.1~27.1 °C
Relative Humidity:	45~59 %
ATM Pressure:	101~101.4 kPa


* The testing was performed by Blake Yang from 2017-11-17 to 2017-11-21.

Test Mode: Transmitting

Test Result: Compliant. Please refer to the following table and plots.


Test mode	Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Limit (MHz)
802.11b	Low	2412	8.64	≥ 0.5
	Middle	2437	8.56	≥ 0.5
	High	2462	8.16	≥ 0.5
802.11g	Low	2412	16.16	≥ 0.5
	Middle	2437	16.32	≥ 0.5
	High	2462	16.08	≥ 0.5
802.11n ht20	Low	2412	17.68	≥ 0.5
	Middle	2437	17.52	≥ 0.5
	High	2462	17.68	≥ 0.5
BLE	Low	2402	0.70	≥ 0.5
	Middle	2440	0.70	≥ 0.5
	High	2480	0.69	≥ 0.5

802.11b Low Channel




Date: 21.NOV.2017 23:41:09

802.11b Middle Channel




Date: 17.NOV.2017 20:45:21

802.11b High Channel




Date: 21.NOV.2017 22:54:22

802.11g Low Channel




Date: 17.NOV.2017 21:02:41

802.11g Middle Channel




Date: 17.NOV.2017 21:05:02

802.11g High Channel




Date: 17.NOV.2017 21:06:57

802.11n ht20 Low Channel




Date: 17.NOV.2017 21:09:31

802.11n ht20 Middle Channel




Date: 17.NOV.2017 21:11:01

802.11n ht20 High Channel




Date: 17.NOV.2017 21:14:00

BLE Low Channel




Date: 17.NOV.2017 21:36:04

BLE Middle Channel



Date: 17.NOV.2017 21:30:12

BLE High Channel




Date: 17.NOV.2017 21:34:12

FCC §15.247(b) (3) - MAXIMUM PEAK CONDUCTED OUTPUT POWER**Applicable Standard**

According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

Test Procedure

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to test equipment.
3. Add a correction factor to the display.
4. Set the power Meter to test Peak output power, record the result as peak power.
5. Set the power meter to test average output power, record the result as average power.

**Test Equipment List and Details**

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Agilent	Wideband Power Sensor	N1921A	MY54210016	2017/11/3	2018/11/3
Agilent	Wideband Power Sensor	N1921A	MY54170013	2017/11/3	2018/11/3
Agilent	P-Series Power Meter	N1912A	MY5000448	2017/11/3	2018/11/3
N/A	Coaxial Cable	C-SJ00-0010	C0010/01	Each Time	/

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data**Environmental Conditions**

Temperature:	27.1 °C
Relative Humidity:	59 %
ATM Pressure:	101 kPa

* The testing was performed by Blake Yang on 2017-11-17.

Test Mode: Transmitting

Test Result: Compliant. Please refer to the following table.

Test mode	Channel	Frequency (MHz)	Max Peak Conducted Output Power (dBm)	Max Conducted Average Output Power (dBm)	Limit (dBm)
802.11b	Low	2412	17.13	15.07	30
	Middle	2437	18.41	15.22	30
	High	2462	18.49	15.56	30
802.11g	Low	2412	22.1	13.65	30
	Middle	2437	22.48	14.28	30
	High	2462	22.78	14.22	30
802.11n ht20	Low	2412	20.86	12.32	30
	Middle	2437	21.22	12.67	30
	High	2462	21.45	12.92	30
BLE	Low	2402	7.36	/	30
	Middle	2440	7.61	/	30
	High	2480	7.49	/	30

FCC §15.247(d)– 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE**Applicable Standard**

According to FCC§15.247(d):In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure


1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESCI	101121	2017/3/2	2018/3/2
N/A	Coaxial Cable	C-SJ00-0010	C0010/01	Each Time	/


* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

802.11b: Band Edge, Right Side




Date: 17.NOV.2017 21:01:13

802.11g: Band Edge, Left Side




Date: 17.NOV.2017 21:03:32

802.11g: Band Edge, Right Side




Date: 17.NOV.2017 21:07:58

802.11n ht20 Band Edge, Left Side




Date: 17.NOV.2017 21:10:17

802.11n ht20 Band Edge, Right Side




Date: 17.NOV.2017 21:14:59

BLE Band Edge , Left Side



Date: 17.NOV.2017 21:36:58

BLE Band Edge, Right Side



Date: 17.NOV.2017 21:34:54

FCC §15.247(e) - POWER SPECTRAL DENSITY**Applicable Standard**

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT was set without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set the RBW = 3 kHz, VBW = 10 kHz, Set the span to 1.5 times the DTS bandwidth.
4. Use the peak marker function to determine the maximum amplitude level.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESCI	101121	2017/3/2	2018/3/2
N/A	Coaxial Cable	C-SJ00-0010	C0010/01	Each Time	/

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).


Test Data**Environmental Conditions**

Temperature:	27.1 °C
Relative Humidity:	59 %
ATM Pressure:	101 kPa

* The testing was performed by Blake Yang on 2017-11-17.


Test Result: Compliance*Test Mode: Transmitting**Test Result: Compliant. Please refer to the following table and plots*

Test mode	Channel	Frequency (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)
802.11b	Low	2412	-8.06	≤ 8
	Middle	2437	-7.75	≤ 8
	High	2462	-7.32	≤ 8
802.11g	Low	2412	-11.28	≤ 8
	Middle	2437	-10.24	≤ 8
	High	2462	-10.12	≤ 8
802.11n ht20	Low	2412	-12.76	≤ 8
	Middle	2437	-12.10	≤ 8
	High	2462	-12.75	≤ 8
BLE	Low	2402	-7.07	≤ 8
	Middle	2440	-6.74	≤ 8
	High	2480	-7.04	≤ 8

Power Spectral Density, 802.11b Low Channel


Date: 17.NOV.2017 20:43:19

Power Spectral Density, 802.11b Middle Channel




Date: 17.NOV.2017 20:45:54

Power Spectral Density, 802.11b High Channel




Date: 17.NOV.2017 21:00:57

Power Spectral Density, 802.11g Low Channel




Date: 17.NOV.2017 21:03:07

Power Spectral Density, 802.11g Middle Channel




Date: 17.NOV.2017 21:05:28

Power Spectral Density, 802.11g High Channel




Date: 17.NOV.2017 21:07:32

Power Spectral Density, 802.11n ht20 Low Channel




Date: 17.NOV.2017 21:10:02

Power Spectral Density, 802.11n ht20 Middle Channel




Date: 17.NOV.2017 21:11:47

Power Spectral Density, 802.11n ht20 High Channel




Date: 17.NOV.2017 21:14:26

Power Spectral Density, BLE Low Channel




Date: 17.NOV.2017 21:36:31

Power Spectral Density, BLE Middle Channel



Date: 17.NOV.2017 21:30:39

Power Spectral Density, BLE High Channel



Date: 17.NOV.2017 21:34:39

***** END OF REPORT *****