

**FCC/IC - TEST REPORT**

Report Number : 68.950.16.629.01 Date of Issue: December 09, 2016

Model : MUSE 5

Product Type : Bluetooth Earphone

Applicant : ERATO(HK) CO., LTD

Address : Unit P, 8th Floor, Kaiser Estate 3rd Phase, No.11, Hong Kong.

Production Facility : Charter Media (Dongguan) Co., Ltd.

Address : Dabandi Industrial Zone, Daning District, Humen Town, 523930

Dongguan City, Guangdong Province, PEOPLE'S REPUBLIC

OF CHINA

Test Result : ☒ Positive ☐ NegativeTotal pages including  
Appendices : 47

TÜV SÜD CERTIFICATION AND TESTING (CHINA) CO., LTD. SHENZHEN BRANCH is a subcontractor to TÜV SÜD Product Service GmbH according to the principles outlined in ISO 17025. TÜV SÜD CERTIFICATION AND TESTING (CHINA) CO., LTD. SHENZHEN BRANCH reports apply only to the specific samples tested under stated test conditions. Construction of the actual test samples has been documented. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical components. The manufacturer/importer is responsible to the Competent Authorities in Europe for any modifications made to the production units which result in non-compliance to the relevant regulations TÜV SÜD CERTIFICATION AND TESTING (CHINA) CO., LTD. SHENZHEN BRANCH shall have no liability for any deductions, inferences or generalizations drawn by the client or others from TÜV SÜD CERTIFICATION AND TESTING (CHINA) CO., LTD. SHENZHEN BRANCH issued reports. This report is the confidential property of the client. As a mutual protection to our clients, the public and ourselves, extracts from the test report shall not be reproduced except in full without our written approval.

## 1 Table of Contents

1	Table of Contents .....	2
2	Details about the Test Laboratory .....	3
3	Description of the Equipment Under Test .....	4
4	Summary of Test Standards .....	5
5	Summary of Test Results .....	6
6	General Remarks .....	7
7	Test Setups .....	8
8	Systems test configuration .....	9
9	Technical Requirement .....	10
9.1	Conducted Emission .....	10
9.2	Conducted peak output power .....	13
9.3	20 dB bandwidth and 99% Occupied Bandwidth .....	20
9.4	Carrier Frequency Separation .....	27
9.5	Number of hopping frequencies .....	30
9.6	Dwell Time .....	32
9.7	Spurious RF conducted emissions .....	35
9.8	Band edge testing .....	39
9.9	Spurious radiated emissions for transmitter .....	42
10	Test Equipment List .....	46
11	System Measurement Uncertainty .....	47

## 2 Details about the Test Laboratory

### Details about the Test Laboratory

#### Test Site 1

Company name: TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch  
Building 12 & 13, Zhiheng Wisdomland Business Park, Nantou Checkpoint  
Road 2, Nanshan District  
Shenzhen 518052  
P.R. China

Telephone: 86 755 8828 6998  
Fax: 86 755 828 5299

FCC Registration 502708  
No.:  
IC Registration 10320A -1  
No.:

### 3 Description of the Equipment Under Test

Product:	Bluetooth Earphone
Model no.:	MUSE 5
FCC ID:	2AHD9-ANMU050000
IC:	21132-ANMU050000
Options and accessories:	Nil
Rating:	DC3.7V Supplied by Li-ion Rechargeable Battery DC5.0V Charged by the mini-USB port
RF Transmission Frequency:	2402MHz-2480MHz
No. of Operated Channel:	79
Modulation:	GFSK, $\pi/4$ -DQPSK, 8-DPSK
Antenna Type:	Integrated antenna
Antenna Gain:	2.0dBi
Description of the EUT:	The Equipment Under Test (EUT) is a Bluetooth headset operated at 2.4GHz

## 4 Summary of Test Standards

Test Standards	
FCC Part 15 Subpart C 10-1-2015 Edition	PART 15 - RADIO FREQUENCY DEVICES Subpart C - Intentional Radiators
RSS-247 Issue 1 2015	Digital Transmission Systems (DTSS), Frequency Hopping Systems (FHSS) and License-Exempt Local Area Network (LE-LAN) Devices

All the test methods were according to Public Notice DA 00-705 -Frequency Hopper Spread Spectrum Test Procedure released by FCC on March 30, 2000 and ANSI C63.10-2013.

## 5 Summary of Test Results

Technical Requirements					
FCC Part 15 Subpart C/RSS-247 Issue 1/RSS-Gen Issue 4					
Test Condition			Pages	Test Result	Test Site
§15.207	RSS-GEN 8.8	Conducted emission AC power port	10	Pass	Site 1
§15.247(b)(1)	RSS-247 Clause 5.4(2)	Conducted peak output power	13	Pass	Site 1
§15.247(e)	RSS-247 Clause 5.2(2)	Power spectral density*	--	N/A	--
§15.247(a)(2)	RSS-247 Clause 5.2(1)	6dB bandwidth	--	N/A	--
§15.247(a)(1)	RSS-247 Clause 5.1(1)	20dB bandwidth and 99% Occupied Bandwidth	20	Pass	Site 1
§15.247(a)(1)	RSS-247 Clause 5.1(2)	Carrier frequency separation	27	Pass	Site 1
§15.247(a)(1)(iii)	RSS-247 Clause 5.1(4)	Number of hopping frequencies	30	Pass	Site 1
§15.247(a)(1)(iii)	RSS-247 Clause 5.1(4)	Dwell Time	32	Pass	Site 1
§15.247(d)	RSS-247 Clause 5.5	Spurious RF conducted emissions	35	Pass	Site 1
§15.247(d)	RSS-247 Clause 5.5	Band edge	39	Pass	Site 1
§15.247(d) & §15.209 &	RSS-247 Clause 5.5 & RSS-GEN 6.13	Spurious radiated emissions for transmitter and receiver	44	Pass	Site 1
§15.203	RSS-GEN 8.3	Antenna requirement	See note 1	Pass	--

Note 1: N/A=Not Applicable.

Note 2: The EUT uses a Integrated antenna, which gain is 2.0dBi. In accordance to §15.203, it is considered sufficiently to comply with the provisions of this section.

## 6 General Remarks

### Remarks

This submittal(s) (test report) is intended for FCC ID: 2AHD9-ANMU050000, IC: 21132-ANMU050000 complies with Section 15.207, 15.209, 15.247 of the FCC Part 15, Subpart C, RSS-247 and RSS-Gen rules.

### SUMMARY:

All tests according to the regulations cited on page 5 were

☒ - Performed

☐ - **Not** Performed

The Equipment Under Test


☒ - **Fulfills** the general approval requirements.


☐ - **Does not** fulfill the general approval requirements.

Sample Received Date: November 2, 2016

Testing Start Date: November 2, 2016


Testing End Date: December 9, 2016

Prepared By	2016-12-09	Mark Chen	
EMC Project Engineer	Date	Name	Signature


Approved by	2016-12-09	Cookies Bu	
EMC Project Manager	Date	Name	Signature

## 7 Test Setups


### 7.1 Radiated test setups Below 1GHz




### Above 1GHz



### 7.2 Conducted RF test setups



### 7.3 AC Power Line Conducted Emission test setups





## 8 Systems test configuration

Auxiliary Equipment Used during Test:

DESCRIPTION	MANUFACTURER	MODEL NO.	S/N
Notebook	lenovo	X220	---

Test software: CRS test tool, which used to control the EUT in continues transmitting mode

The system was configured to hopping mode and non-hopping mode.

Hopping mode: typical working mode (normal hopping status)

Non-hopping mode: The system was configured to operate at a signal channel transmitting. The test software allows the configuration and operation at the worst-case duty and the highest transmit power

## 9 Technical Requirement

### 9.1 Conducted Emission

#### Test Method


1. The EUT was placed on a table, which is 0.8m above ground plane
2. The power line of the EUT is connected to the AC mains through a Artificial Mains Network (A.M.N.).
3. Maximum procedure was performed to ensure EUT compliance
4. A EMI test receiver is used to test the emissions from both sides of AC line

#### Limit

Frequency MHz	QP Limit dB $\mu$ V	AV Limit dB $\mu$ V
0.150-0.500	66-56*	56-46*
0.500-5	56	46
5-30	60	50

Decreasing linea

Product Type : Bluetooth Earphone  
 M/N : MUSE 5  
 Operating Condition : Charging & TX  
 Test Specification : Live  
 Comment : AC 120V/60Hz




### Critical\_Freqs

Frequency (MHz)	MaxPeak (dBµV)	Average (dBµV)	Limit (dBµV)	Margin (dB)	Line	Corr. (dB)
0.165500	57.43	---	64.96	7.53	L1	9.7
0.221500	50.64	---	62.60	11.96	L1	9.7
0.286000	44.64	---	60.64	16.00	L1	9.7
1.378000	30.31	---	56.00	25.69	L1	9.7
4.802000	34.98	---	56.00	21.02	L1	9.8
20.673500	41.19	---	60.00	18.81	L1	10.2

### Final\_Result

Frequency (MHz)	QuasiPeak (dBµV)	Average (dBµV)	Limit (dBµV)	Margin (dB)	Line	Corr. (dB)
0.165500	---	35.21	55.18	19.97	L1	9.7
0.165500	53.65	---	65.18	11.53	L1	9.7
0.221500	---	29.10	52.76	23.66	L1	9.7
0.221500	47.97	---	62.76	14.79	L1	9.7
20.673500	---	32.07	50.00	17.93	L1	10.2
20.673500	37.26	---	60.00	22.74	L1	10.2

Product Type : Bluetooth Earphone  
 M/N : MUSE 5  
 Operating Condition : Charging & TX  
 Test Specification : Neutral  
 Comment : AC 120V/60Hz



### Critical\_Freqs

Frequency (MHz)	MaxPeak (dBµV)	Average (dBµV)	Limit (dBµV)	Margin (dB)	Line	Corr. (dB)
0.158500	55.90	---	65.78	9.88	N	9.6
0.205500	49.92	---	63.37	13.45	N	9.6
0.342000	38.80	---	59.15	20.36	N	9.7
3.802000	31.87	---	56.00	24.13	N	9.8
5.658000	33.08	---	60.00	26.92	N	9.8
19.129500	40.37	---	60.00	19.63	N	10.1

### Final\_Result

Frequency (MHz)	QuasiPeak (dBµV)	Average (dBµV)	Limit (dBµV)	Margin (dB)	Line	Corr. (dB)
0.158500	---	33.51	55.54	22.03	N	9.6
0.158500	52.57	---	65.54	12.97	N	9.6
0.205500	---	25.76	53.39	27.63	N	9.6
0.205500	46.21	---	63.39	17.18	N	9.6
19.129500	---	27.39	50.00	22.61	N	10.1
19.129500	33.57	---	60.00	26.43	N	10.1

## 9.2 Conducted peak output power

### Test Method

1. Use the following spectrum analyzer settings:  
Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel  
RBW > the 20 dB bandwidth of the emission being measured, VBW ≥ RBW,  
Sweep = auto, Detector function = peak, Trace = max hold
2. Add a correction factor to the display.
3. Allow the trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. The indicated level is the peak output power


### Limits

Frequency Range MHz	Limit W	Limit dBm
2400-2483.5	≤1	≤30

## Conducted peak output power


### Bluetooth Mode GFSK modulation Test Result

Frequency MHz	Conducted Peak Output Power dBm	Result
Low channel 2402MHz	7.75	Pass
Middle channel 2441MHz	8.05	Pass
High channel 2480MHz	7.60	Pass




Date: 23.NOV.2016 08:56:36

## Middle channel 2441MHz



Date: 23.NOV.2016 08:57:41

## High channel 2480MHz




Date: 23.NOV.2016 08:58:08

Bluetooth Mode  $\pi/4$ -DQPSK modulation Test Result

Frequency MHz	Conducted Peak Output Power dBm	Result
Low channel 2402MHz	5.78	Pass
Middle channel 2441MHz	6.27	Pass
High channel 2480MHz	5.77	Pass


Low channel 2402MHz



Date: 23.NOV.2016 08:58:46




## Middle channel 2441MHz



Date: 23.NOV.2016 08:59:19

## High channel 2480MHz




Date: 23.NOV.2016 08:59:44

## Bluetooth Mode 8DPSK modulation Test Result


Frequency MHz	Conducted Peak Output Power dBm	Result
Low channel 2402MHz	6.06	Pass
Middle channel 2441MHz	6.56	Pass
High channel 2480MHz	6.07	Pass

Low channel 2402MHz




Date: 23.NOV.2016 09:00:21

## Middle channel 2441MHz



Date: 23.NOV.2016 09:00:47

## High channel 2480MHz



Date: 23.NOV.2016 09:01:07

### 9.3 20 dB bandwidth and 99% Occupied Bandwidth

#### Test Method

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.

#### Limit

Limit [kHz]

---


N/A

## 20 dB bandwidth and 99% Occupied Bandwidth

### Bluetooth Mode GFSK Modulation test result


Frequency MHz	20 dB Bandwidth kHz	99% Bandwidth kHz	Limit kHz	Result
2402	1111.4	963.82	--	Pass
2441	1120.1	963.82	--	Pass
2480	1120.1	972.50	--	Pass

Low channel 2402MHz




Date: 7.DEC.2016 11:15:01

## Middle channel 2441MHz



Date: 7.DEC.2016 11:14:12

## High channel 2480MHz




Date: 7.DEC.2016 11:13:18

## 20 dB bandwidth and 99% Occupied Bandwidth

Bluetooth Mode  $\pi/4$ -DQPSK Modulation test result


Frequency MHz	20 dB Bandwidth kHz	99% Bandwidth kHz	Limit kHz	Result
2402	1376.3	1206.9	--	Pass
2441	1380.6	1202.6	--	Pass
2480	1380.6	1206.9	--	Pass

Low channel 2402MHz




Date: 7.DEC.2016 11:10:25

## Middle channel 2441MHz



Date: 7.DEC.2016 11:11:22

## High channel 2480MHz




Date: 7.DEC.2016 11:12:07



## 20 dB bandwidth and 99% Occupied Bandwidth


Bluetooth Mode 8DPSK Modulation test result

Frequency MHz	20 dB Bandwidth kHz	99% Bandwidth kHz	Limit kHz	Result
2402	1380.6	1206.9	--	Pass
2441	1371.9	1206.9	--	Pass
2480	1380.6	1215.6	--	Pass




Date: 7.DEC.2016 11:09:23

## Middle channel 2441MHz



Date: 7.DEC.2016 11:08:31

## High channel 2480MHz



Date: 7.DEC.2016 11:07:33

## 9.4 Carrier Frequency Separation

### Test Method

1. Use the following spectrum analyzer settings:  
Span = wide enough to capture the peaks of two adjacent channels,  $RBW \geq 1\%$  of the span,  $VBW \geq RBW$ , Sweep = auto, Detector function = peak
2. By using the Max-Hold function record the separation of two adjacent channels.
3. Measure the frequency difference of these two adjacent channels by spectrum analyzer marker function.
4. Repeat above procedures until all frequencies measured were complete.

### Limit

Limit kHz
$\geq 25\text{kHz}$ or $2/3$ of the 20 dB bandwidth which is greater

### GFSK Modulation Limit

Frequency MHz	2/3 of 20 dB Bandwidth kHz
2402	740.9333
2441	746.7333
2480	746.7333


## Carrier Frequency Separation

Test result: The measurement was performed with the typical configuration (normal hopping status), here GFSK modulation mode was used to show compliance.

### GFSK Modulation test result


Frequency MHz	Carrier Frequency Separation kHz	Result
2402	1002.9	Pass
2441	1007.2	Pass
2480	1007.2	Pass

Low channel 2402MHz




Date: 12.NOV.2016 14:39:13

## Middle channel 2441MHz



Date: 12.NOV.2016 14:38:42

## High channel 2480MHz



Date: 12.NOV.2016 14:40:02

## 9.5 Number of hopping frequencies

### Test Method

1. Use the following spectrum analyzer settings:  
Span = wide enough to capture the peaks of two adjacent channels,  $RBW \geq 1\%$  of the span,  $VBW \geq RBW$ , Sweep = auto, Detector function = peak
2. Set the spectrum analyzer on Max-Hold Mode, and then keep the EUT in hopping mode.
3. Record all the signals from each channel until each one has been recorded.
4. Repeat above procedures until all frequencies measured were complete.

### Limit

Limit  
number


---

$\geq 15$

Number of hopping frequencies

Test result: The measurement was performed with the typical configuration (normal hopping status), and the total hopping channels is constant for the all modulation mode according with the Bluetooth Core Specification. Here GFSK modulation mode was used to show compliance.

Number of hopping frequencies	Result
79	Pass



Date: 12.NOV.2016 14:40:52

## 9.6 Dwell Time

### Test Method

1. Connect EUT antenna terminal to the spectrum analyzer with a low loss cable.  
Equipment mode: Spectrum analyzer
2. RBW: 1MHz; VBW: 1MHz; SPAN: Zero Span
3. Adjust the center frequency of spectrum analyzer on any frequency be measured.
4. Measure the Dwell Time by spectrum analyzer Marker function.
5. Repeat above procedures until all frequencies measured were complete.

### Limit

The average time of occupancy on any frequency shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.



## Dwell Time

### Dwell time

The maximum dwell time shall be 0.4 s.

According to the Bluetooth Core Specification, the worse result (DH5 mode) was reported to show compliance.

The Dwell Time = Burst Width \* Total Hops. The detailed calculations are showed as follows:

The duration for dwell time calculation: 0.4 [s] \* hopping number = 0.4 [s] \* 79 [ch] = 31.6 [s\*ch];


The burst width, which is directly measured, refers to the duration on one channel hop.

The maximum number of hopping channels in 31.6s for DH5=1600 / 6 / 79 \*31.6=106.67

### Test Result

Modulation	Mode	Reading (us)	Total Hops	Test Result (ms)	Limit (ms)	Result
GFSK	DH5	2956.5	106.67	317.6	< 400	Pass
$\pi/4$ -DQPSK	2DH5	2971.0	106.67	319.2	< 400	Pass
8-DPSK	3DH5	2971.0	106.67	319.2	< 400	Pass


### GFSK Modulation



Date: 12.NOV.2016 14:35:51

DH5


## $\pi/4$ -DQPSK Modulation



Date: 12.NOV.2016 14:34:28

2DH5

## 8-DPSK Modulation



Date: 12.NOV.2016 14:31:10

3DH5

## 9.7 Spurious RF conducted emissions

### Test Method

1. Use the following spectrum analyzer settings:  
Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10<sup>th</sup> harmonic. Typically, several plots are required to cover this entire span.  
RBW = 100 kHz, VBW ≥ RBW, Sweep = auto, Detector function = peak, Trace = max hold
2. Allow the trace to stabilize. Set the marker on the peak of any spurious emission recorded.
3. The level displayed must comply with the limit specified in this Section. Submit these plots.
4. Repeat above procedures until all frequencies measured were complete.

### Limit


Frequency Range MHz	Limit (dBc)
30-25000	-20

## Spurious RF conducted emissions


Only the worse case (which is subject to the maximum EIRP, GFSK mode) test result is listed in the report.

BT3.0 GFSK Modulation:

Low channel 2402MHz




Date: 12.NOV.2016 11:12:28




Date: 12.NOV.2016 11:12:08

## Middle channel 2441MHz




Date: 12.NOV.2016 11:11:17




Date: 12.NOV.2016 11:10:52

## High channel 2480MHz



Date: 12.NOV.2016 11:10:11



Date: 12.NOV.2016 11:09:44

## 9.8 Band edge testing


### Test Method

- 1 Use the following spectrum analyzer settings:  
Span = wide enough to capture the peak level of the in-band emission and all spurious  
RBW = 100 kHz, VBW  $\geq$  RBW, Sweep = auto, Detector function = peak, Trace = max hold
- 2 Allow the trace to stabilize, use the peak and delta measurement to record the result.
- 3 The level displayed must comply with the limit specified in this Section. .
- 4 Repeat the test at the hopping off and hopping on mode, submit all the plots.


### Limit:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits.

## GFSK mode:




Date: 12.NOV.2016 14:23:07




Date: 12.NOV.2016 14:24:55



8DPSK mode:



Date: 12.NOV.2016 14:29:03



Date: 12.NOV.2016 14:29:46

## 9.9 Spurious radiated emissions for transmitter

### Test Method

- 1: The EUT was placed on a turn table which is 1.5m above ground plane for above 1GHz and 0.8m above ground for below 1GHz at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- 2: The EUT was set 3 meters away from the interference – receiving antenna, which was mounted on the top of a variable – height antenna tower.
- 3: The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- 4: For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- 5: Use the following spectrum analyzer settings According to C63.10:

#### For Above 1GHz

Span = wide enough to capture the peak level of the in-band emission and all spurious  
RBW = 1MHz, VBW  $\geq$  RBW for peak measurement and VBW = 10Hz for average measurement, Sweep = auto, Detector function = peak, Trace = max hold.

#### For Below 1GHz

Use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the in-band emission and all spurious  
RBW = 100 KHz, VBW  $\geq$  RBW for peak measurement, Sweep = auto, Detector function = peak, Trace = max hold.

### Note:

- 1: The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 KHz for Quasi-peak detection (QP) at frequency below 1GHz.
- 2: The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 3MHz for peak detection (PK) at frequency above 1GHz.
- 3: The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 3MHz for RMS Average ((duty cycle < 98%) for Average detection (AV) at frequency above 1GHz, then the measurement results was added to a correction factor ( $20\log(1/\text{duty cycle})$ ).
- 4: The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz (duty cycle > 98%) for Average detection (AV) at frequency above 1GHz.

## Limit

The radio emission outside the operating frequency band shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power. Radiated emissions which fall in the restricted bands, as defined in section 15.205, must comply with the radiated emission limits specified in section 15.209.

Frequency MHz	Field Strength uV/m	Field Strength dBµV/m	Detector
30-88	100	40	QP
88-216	150	43.5	QP
216-960	200	46	QP
960-1000	500	54	QP
Above 1000	500	54	AV
Above 1000	5000	74	PK

## Spurious radiated emissions for transmitter

According to C63.10, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement, so AV emission value did not show in below table if the peak value complies with average limit.

The only worse case (which is subject to the maximum EIRP, GFSK mode) test result is listed in the report.

### Transmitting spurious emission test result as below:

#### BT3.0 GFSK Modulation 2402MHz Test Result

Frequency Band	Frequency	Emission Level	Polarization	Limit	Detector	Margin	Result
	MHz	dBuV/m		dBuV/m		dBuV/m	
30-1000MHz	955.65	33.86	H	46	QP	12.15	Pass
	921.27	34.32	V	46	QP	11.68	Pass
1000-25000MHz	12009.38	44.41	H	74	PK	29.59	Pass
	--	--	H	54	AV	--	Pass
	9608.44	48.0	V	74	PK	26.0	Pass
	--	--	V	54	AV	--	Pass

#### BT3.0 GFSK Modulation 2441MHz Test Result

Frequency Band	Frequency	Emission Level	Polarization	Limit	Detector	Margin	Result
	MHz	dBuV/m		dBuV/m		dBuV/m	
30-1000MHz	--	--	H	43.5	QP	--	Pass
	--	--	H	46	QP	--	Pass
1000-25000MHz	9764.53	43.81	H	74	PK	30.19	Pass
	--	--	H	54	AV	--	Pass
	9764.53	49.81	V	74	PK	24.18	Pass
	--	--	V	54	AV	--	Pass

## BT3.0 GFSK Modulation 2480MHz Test Result

Frequency Band	Frequency	Emission Level	Polarization	Limit	Detector	Margin	Result
	MHz	dBuV/m		dBuV/m		dBuV/m	
30-1000MHz	--	--	H	43.5	QP	--	Pass
	--	--	H	46	QP	--	Pass
1000-25000MHz	4960.31	49.51	H	74	PK	24.49	Pass
	--	--	H	54	AV	--	Pass
	4960.31	48.46	V	74	PK	25.54	Pass
	--	--	V	54	AV	--	Pass

## Remark:

- (1) “\*” means the emission(s) appear within the restrict bands shall follow the requirement of section 15.205.
- (2) Data of measurement within this frequency range shown “--” in the table above means the reading of emissions are the noise floor or attenuated more than 10dB below the permissible limits or the field strength is too small to be measured.

## 10 Test Equipment List

### List of Test Instruments

	DESCRIPTION	MANUFACTURER	MODEL NO.	SERIAL NO.	CAL. DUE DATE
CE	EMI Test Receiver	Rohde & Schwarz	ESR 3	101782	2017-7-15
	LISN	Rohde & Schwarz	ENV4200	100249	2017-7-15
	LISN	Rohde & Schwarz	ENV216	100326	2017-7-15
	ISN	Rohde & Schwarz	ENY81	100177	2017-7-15
	ISN	Rohde & Schwarz	ENY81-CAT6	101664	2017-7-15
	High Voltage Probe	Rohde & Schwarz	TK9420(VT9420)	9420-58	2017-7-15
	RF Current probe	Rohde & Schwarz	EZ-17	100816	2017-7-15
C	Signal Generator	Rohde & Schwarz	SMB100A	108272	2017-7-15
	Signal Analyzer	Rohde & Schwarz	FSV40	101030	2017-7-15
	Vector Signal Generator	Rohde & Schwarz	SMU 200A	105324	2017-7-15
	RF Switch Module	Rohde & Schwarz	OSP120/OS P-B157	101226/100851	2017-7-15
RE	EMI Test Receiver	Rohde & Schwarz	ESR 26	101269	2017-7-15
	Trilog Super Broadband Test Antenna	Schwarzbeck	VULB 9163	707	2017-8-3
	Horn Antenna	Rohde & Schwarz	HF907	102294	2017-7-15
	Pre-amplifier	Rohde & Schwarz	SCU 18	102230	2017-7-15
	3m Semi-anechoic chamber	TDK	9X6X6	----	2019-5-29

#### C - Conducted RF tests

- Conducted peak output power
- 6dB bandwidth and 99% Occupied Bandwidth
- Power spectral density\*
- Spurious RF conducted emissions
- Band edge

## 11 System Measurement Uncertainty

For a 95% confidence level, the measurement expanded uncertainties for defined systems, in accordance with the recommendations of ISO 17025 were:

System Measurement Uncertainty	
Items	Extended Uncertainty
Uncertainty for Radiated Emission in 3m chamber 30MHz-1000MHz	Horizontal: 4.83dB; Vertical: 4.91dB;
Uncertainty for Radiated Emission in 3m chamber 1000MHz-18000MHz	Horizontal: 4.89dB; Vertical: 4.88dB;
Uncertainty for Conducted RF test with TS 8997	2.04dB