

FCC Part 15B

Measurement and Test Report

For

Snappa Technology Co., LTD

#1401, Building B, No 7, Lane 8, Yongxiang Road, Longgang Dist,

Shenzhen, China

FCC ID: 2AHFVSP001

Test Rule(s):	<u>FCC Part 15 Subpart B</u>
Product Description:	<u>Handheld 3-Axis Camera Gimbal Stabilizer</u>
Tested Model:	<u>SP001</u>
Report No.:	<u>STR16018128I-1</u>
Tested Date:	<u>2016-01-15 to 2016-01-26</u>
Issued Date:	<u>2016-01-29</u>
Tested By:	<u>Rode Liu / Engineer</u>
Reviewed By:	<u>Lahm Peng / EMC Manager</u>
Approved & Authorized By:	<u>Jandy so / PSQ Manager</u>
Prepared By:	

Shenzhen SEM.Test Technology Co., Ltd.

1/F, Building A, Hongwei Industrial Park, Liuxian 2nd Road,
Bao'an District, Shenzhen, P.R.C. (518101)

Tel.: +86-755-33663308 Fax.: +86-755-33663309 Website: www.semtest.com.cn

Note: This test report is limited to the above client company and the product model only. It may not be duplicated without prior permitted by Shenzhen SEM.Test Technology Co., Ltd.

TABLE OF CONTENTS

1. GENERAL INFORMATION.....	3
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	3
1.2 TEST STANDARDS.....	4
1.3 TEST METHODOLOGY.....	4
1.4 TEST FACILITY.....	4
1.5 EUT SETUP AND OPERATION MODE.....	5
1.6 TEST EQUIPMENT LIST AND DETAILS.....	5
2. SUMMARY OF TEST RESULTS.....	6
3. CONDUCTED EMISSIONS.....	7
3.1 MEASUREMENT UNCERTAINTY.....	7
3.2 TEST PROCEDURE.....	7
3.3 BASIC TEST SETUP BLOCK DIAGRAM.....	7
3.4 ENVIRONMENTAL CONDITIONS.....	8
3.5 SUMMARY OF TEST RESULTS/PLOTS.....	8
3.6 CONDUCTED EMISSIONS TEST DATA.....	8
4. RADIATED EMISSIONS.....	11
4.1 MEASUREMENT UNCERTAINTY.....	11
4.2 TEST PROCEDURE.....	11
4.3 TEST RECEIVER SETUP.....	12
4.4 CORRECTED AMPLITUDE & MARGIN CALCULATION.....	12
4.5 ENVIRONMENTAL CONDITIONS.....	12
4.6 SUMMARY OF TEST RESULTS/PLOTS.....	12

1. GENERAL INFORMATION

1.1 Product Description for Equipment Under Test (EUT)

Client Information

Applicant: Snappa Technology Co., LTD
Address of applicant: #1401, Building B, No 7, Lane 8, Yongxiang Road,
Longgang Dist, Shenzhen, China
Manufacturer: Snappa Technology Co., LTD
Address of manufacturer: #1401, Building B, No 7, Lane 8, Yongxiang Road,
Longgang Dist, Shenzhen, China

General Description of EUT

Product Name:	Handheld 3-Axis Camera Gimbal Stabilizer
Trade Name:	Snappa Go
Model No.:	SP001

Note: The test data is gathered from a production sample, provided by the manufacturer.

Technical Characteristics of EUT

Rated Voltage:	DC 3.6V battery; USB 5V to charging or upgrade software
Rated Current:	/
Rated Power:	/
Highest Internal Frequency:	16MHz
Classification of ITE:	CLASS B

1.2 Test Standards

The following report is prepared on behalf of the Snappa Technology Co., LTD in accordance with Part 2, Subpart J, and Part 15, Subparts A and B of the Federal Communication Commissions rules.

The objective is to determine compliance with FCC Part 15, Subpart B, and section 15.205, 15.107, and 15.109 rules.

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product, which result in lowering the emission, should be checked to ensure compliance has been maintained.

1.3 Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2014, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

1.4 Test Facility

FCC – Registration No.: 934118

Shenzhen SEM.Test Technology Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files and the Registration is 934118.

Industry Canada (IC) Registration No.: 11464A

The 3m Semi-anechoic chamber of Shenzhen SEM.Test Technology Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 11464A.

CNAS Registration No.: L4062

Shenzhen SEM.Test Technology Co., Ltd. is a testing organization accredited by China National Accreditation Service for Conformity Assessment (CNAS) according to ISO/IEC 17025. The accreditation certificate number is L4062. All measurement facilities used to collect the measurement data are located at 1/F, Building A, Hongwei Industrial Park, Liuxian 2nd Road, Bao'an District, Shenzhen, P.R.C (518101).

1.5 EUT Setup and Operation Mode

The equipment under test (EUT) was configured to measure its highest possible emission level. The test modes were adapted according to the operation manual for use, more detailed description as follows:

Test Mode List:

Test Mode	Description	Remark
TM1	Charging & Upgrade software	/
TM2	/	/

EUT Cable List and Details

Cable Description	Length (M)	Shielded/Unshielded	With Core/Without Core
USB Cable	0.9	Unshielded	Without Core

Auxiliary Equipment List and Details

Description	Manufacturer	Model	Serial Number
Notebook	Lenovo	E10	LR-63C8R

Special Cable List and Details

Cable Description	Length (M)	Shielded/Unshielded	With Core/Without Core
/	/	/	/

1.6 Test Equipment List and Details

Description	Manufacturer	Model	Serial Number	Cal Date	Due Date
Spectrum Analyzer	Agilent	E4407B	MY41440400	2015-06-17	2016-06-16
Spectrum Analyzer	Rohde & Schwarz	FSP	836079/035	2015-06-17	2016-06-16
EMI Test Receiver	Rohde & Schwarz	ESVB	825471/005	2015-06-17	2016-06-16
Amplifier	Agilent	8447F	3113A06717	2015-06-17	2016-06-16
Amplifier	C&D	PAP-1G18	2002	2015-06-17	2016-06-16
Broadband Antenna	Schwarz beck	VULB9163	9163-333	2015-06-17	2016-06-16
Horn Antenna	ETS	3117	00086197	2015-06-17	2016-06-16
Loop Antenna	Schwarz beck	FMZB 1516	9773	2015-06-17	2016-06-16
EMI Test Receiver	Rohde & Schwarz	ESPI	101611	2015-06-17	2016-06-16
L.I.S.N	Schwarz beck	NSLK8126	8126-224	2015-06-17	2016-06-16
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100911	2015-06-17	2016-06-16

2. SUMMARY OF TEST RESULTS

FCC Rules	Description of Test Item	Result
§ 15.107 (a)	Conducted Emissions	Compliant
§ 15.109 (a)	Radiated Emissions	Compliant

N/A: not applicable

3. Conducted Emissions


3.1 Measurement Uncertainty

Base on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of any conducted emissions measurement is ± 2.88 dB.

3.2 Test Procedure

Test is conducting under the description of ANSI C63.4-2014, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

3.3 Basic Test Setup Block Diagram



3.4 Environmental Conditions

Temperature:	23 °C
Relative Humidity:	52%
ATM Pressure:	1011 mbar

3.5 Summary of Test Results/Plots

According to the data in section 3.6, the EUT complied with the FCC Part 15.107(a) Conducted margin for a Class B device, with the *worst* margin reading of:

-11.55 dB at **0.6820 MHz** in the **Line, Peak** detector, 0.15-30MHz

3.6 Conducted Emissions Test Data

Plot of Conducted Emissions Test Data


EUT: Handheld 3-Axis Camera Gimbal Stabilizer

Tested Model: SP001

Operating Condition: TM1


Comment: AC 120V/60Hz; USB 5V

Test Specification: Neutral



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.1620	35.52	12.50	48.02	65.36	-17.34	peak
2	0.1620	19.28	12.50	31.78	55.36	-23.58	AVG
3*	1.2740	26.77	13.00	39.77	56.00	-16.23	peak
4	1.2900	13.55	13.00	26.55	46.00	-19.45	AVG
5	18.3740	21.59	11.67	33.26	60.00	-26.74	peak
6	18.9300	7.88	11.79	19.67	50.00	-30.33	AVG

Test Specification: Line



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1*	0.6820	31.77	12.68	44.45	56.00	-11.55	peak
2	0.7140	21.09	12.71	33.80	46.00	-12.20	AVG
3	1.5300	17.64	13.00	30.64	46.00	-15.36	AVG
4	1.6380	31.00	13.00	44.00	56.00	-12.00	peak
5	17.3860	26.58	11.48	38.06	60.00	-21.94	peak
6	17.6820	13.57	11.54	25.11	50.00	-24.89	AVG

4. Radiated Emissions

4.1 Measurement Uncertainty


Base on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of any radiation emissions measurement is ± 5.10 dB.

4.2 Test Procedure

The setup of EUT is according with per ANSI C63.4-2014 measurement procedure. The specification used was with the FCC Part 15.109 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.



4.3 Test Receiver Setup

Frequency :9kHz-30MHz

RBW=10KHz,

VBW =30KHz

Sweep time= Auto

Trace = max hold

Detector function = peak

Frequency :30MHz-1GHz

RBW=120KHz,

VBW=300KHz

Sweep time= Auto

Trace = max hold

Detector function = peak, QP

Frequency :Above 1GHz

RBW=1MHz,

VBW=3MHz(Peak), 10Hz(AV)

Sweep time= Auto

Trace = max hold

Detector function = peak, AV

4.4 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and the Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} - \text{Corr. Factor}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -6dB μ V means the emission is 6dB μ V below the maximum limit for a Class B device. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{FCC Part 15.109(a) Limit}$$

4.5 Environmental Conditions

Temperature:	23 °C
Relative Humidity:	55 %
ATM Pressure:	1011 mbar

4.6 Summary of Test Results/Plots

According to the data, the EUT complied with the FCC Part 15.109(a) rule, and had the worst margin of:

-8.84 dB at 143.8295 MHz in the Horizontal polarization, 30MHz to 1 GHz, 3Meters

Plot of Radiated Emissions Test Data


EUT: *Handheld 3-Axis Camera Gimbal Stabilizer*

Tested Model: *SP001*

Operating Condition: *TM1*


Comment: *AC 120V/60Hz; USB 5V*

Test Specification: *Horizontal*



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	65.8031	27.09	-11.47	15.62	40.00	-24.38	58	200	peak
2	99.1797	34.91	-11.07	23.84	43.50	-19.66	326	200	peak
3	143.8295	47.17	-12.51	34.66	43.50	-8.84	29	200	peak
4	182.5592	45.64	-11.01	34.63	43.50	-8.87	209	200	peak
5	252.0627	38.99	-7.49	31.50	46.00	-14.50	100	100	peak
6	287.9904	37.22	-5.92	31.30	46.00	-14.70	100	100	peak

Test Specification: Vertical



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	32.2925	35.81	-9.72	26.09	40.00	-13.91	51	100	peak
2	75.4464	37.40	-12.37	25.03	40.00	-14.97	308	100	peak
3	83.8156	39.11	-12.35	26.76	40.00	-13.24	120	100	peak
4	143.8295	38.31	-12.51	25.80	43.50	-17.70	359	100	peak
5	287.9904	35.22	-5.92	29.30	46.00	-16.70	100	100	peak
6	599.3212	26.90	-0.17	26.73	46.00	-19.27	100	100	peak

***** END OF REPORT *****