

FCC Test Report

Equipment : MEVO PLUS
Brand Name : LIVESTREAM
Model No. : A20201A
FCC ID : 2AHGTA20201A
Standard : 47 CFR FCC Part 15.247
Operating Band : 2400 MHz – 2483.5 MHz
Function : ☒ Point-to-multipoint; ☐ Point-to-point
Applicant : Livestream, Inc.
195 Morgan Ave. Brooklyn, NY 11237, USA
Manufacturer : Chicony Electronics (Dong Guan) Co.,Ltd.
San Zhong Guan Li Qu, Qingxi Town,
Dongguan City Guangdong 523651 China

The product sample received on Aug. 08, 2017 and completely tested on Sep. 22, 2017. We, SPORTON, would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.10-2013 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.


Phoenix Chen
SPORTON INTERNATIONAL INC.



Table of Contents

1	GENERAL DESCRIPTION	5
1.1	Information.....	5
1.2	Testing Applied Standards	7
1.3	Testing Location Information	7
1.4	Measurement Uncertainty	7
2	TEST CONFIGURATION OF EUT.....	8
2.1	Test Condition	8
2.2	Test Channel Mode	8
2.3	The Worst Case Measurement Configuration.....	9
2.4	Accessories	10
2.5	Support Equipment.....	10
2.6	Test Setup Diagram	11
3	TRANSMITTER TEST RESULT	13
3.1	AC Power-line Conducted Emissions	13
3.2	DTS Bandwidth.....	14
3.3	Maximum Conducted Output Power	15
3.4	Power Spectral Density	17
3.5	Emissions in Non-restricted Frequency Bands	18
3.6	Emissions in Restricted Frequency Bands.....	19
4	TEST EQUIPMENT AND CALIBRATION DATA	23
APPENDIX A. TEST RESULTS OF AC POWER-LINE CONDUCTED EMISSIONS		
APPENDIX B. TEST RESULTS OF DTS BANDWIDTH		
APPENDIX C. TEST RESULTS OF MAXIMUM CONDUCTED OUTPUT POWER		
APPENDIX D. TEST RESULTS OF POWER SPECTRAL DENSITY		
APPENDIX E. TEST RESULTS OF EMISSIONS IN NON-RESTRICTED FREQUENCY BANDS		
APPENDIX F. TEST RESULTS OF EMISSIONS IN RESTRICTED FREQUENCY BANDS		
APPENDIX G. TEST PHOTOS		
PHOTOGRAPHS OF EUT V02		

Summary of Test Result

Conformance Test Specifications				
Report Clause	Ref. Std. Clause	Description	Limit	Result
1.1.2	15.203	Antenna Requirement	FCC 15.203	Complied
3.1	15.207	AC Power-line Conducted Emissions	FCC 15.207	Complied
3.2	15.247(a)	DTS Bandwidth	≥500kHz	Complied
3.3	15.247(b)	Maximum Conducted Output Power	Power [dBm]:30	Complied
3.4	15.247(e)	Power Spectral Density	PSD [dBm/3kHz]:8	Complied
3.5	15.247(d)	Emissions in Non-restricted Frequency Bands	Non-Restricted Bands: > 30 dBc	Complied
3.6	15.247(d)	Emissions in Restricted Frequency Bands	Restricted Bands: FCC 15.209	Complied

Revision History

[illegible]

1 General Description

1.1 Information

1.1.1 RF General Information

Frequency Range (MHz)	IEEE Std. 802.11	Ch. Frequency (MHz)	Channel Number
2400-2483.5	b, g, n (HT20)	2412-2462	1-11 [11]

Band	Mode	BWch (MHz)	Nant
2.4-2.4835GHz	802.11b	20	2TX
2.4-2.4835GHz	802.11g	20	2TX
2.4-2.4835GHz	802.11n HT20	20	2TX

Note:

- ♦ 11b mode uses a combination of DSSS-DBPSK, DQPSK, CCK modulation.
- ♦ 11g, HT20 use a combination of OFDM-BPSK, QPSK, 16QAM, 64QAM modulation.
- ♦ BWch is the nominal channel bandwidth.

1.1.2 Antenna Information

Ant.	Port	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1	1	-	GY196HT337-012	PIFA Antenna	I-PEX	1.2
2	2	-	GY196HT337-011	PIFA Antenna	I-PEX	-0.86

Note: 1: 802.11b/g/n used two antennas are for signal transmitting and receiving.(2T2R Spatial Multiplexing MIMO configuration)

1.1.3 EUT Information

Operational Condition			
EUT Power Type	From AC Adapter		
Beamforming Function	<input type="checkbox"/> With beamforming	<input checked="" type="checkbox"/> Without beamforming	
Type of EUT			
<input checked="" type="checkbox"/>	Stand-alone		
<input type="checkbox"/>	Combined (EUT where the radio part is fully integrated within another device)		
	Combined Equipment - Brand Name / Model No.:		...
<input type="checkbox"/>	Plug-in radio (EUT intended for a variety of host systems)		
	Host System - Brand Name / Model No.:		...
<input type="checkbox"/>	Other:		

1.1.4 Mode Test Duty Cycle

Mode	DC	DCF(dB)	T(s)	VBW(Hz) $\geq 1/T$
802.11b	0.991	0.039	n/a (DC \geq 0.98)	n/a (DC \geq 0.98)
802.11g	0.927	0.329	1.429m	1k
802.11n HT20	0.931	0.311	1.338m	1k

1.2 Testing Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR FCC Part 15
- ♦ ANSI C63.10-2013
- ♦ KDB 558074 D01 v04
- ♦ KDB 662911 D01 v02r01

1.3 Testing Location Information

Testing Location			
<input checked="" type="checkbox"/>	HWA YA	ADD : No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)	
		TEL : 886-3-327-3456	FAX : 886-3-327-0973
Test site Designation No. TW1190 with FCC.			
<input checked="" type="checkbox"/>	LIN KOU	ADD : No. 30-2, Dingfu Vil., Linkou Dist., New Taipei City, Taiwan (R.O.C.)	
		TEL : 886-2-2601-1640	FAX : 886-2-2601-1695
Test site Designation No. TW1095 with FCC.			

Test Condition	Test Site No.	Test Engineer	Test Environment	Test Date
RF Conducted	TH07-HY	Ryan	24.2°C / 65%	24/Aug/2017
Radiated	03CH09-HY	Jerry	24.5°C / 63.8%	22/Sep/2017
AC Conduction	CO01-LK	Morrison	29°C / 51%	21/Aug/2017

1.4 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2))

Test Items	Uncertainty	Remark
Conducted Emission (150kHz ~ 30MHz)	3.6 dB	Confidence levels of 95%
Radiated Emission (30MHz ~ 1,000MHz)	2.1 dB	Confidence levels of 95%
Radiated Emission (1GHz ~ 18GHz)	2.6 dB	Confidence levels of 95%
Radiated Emission (18GHz ~ 40GHz)	2.9 dB	Confidence levels of 95%
Conducted Emission	1.3 dB	Confidence levels of 95%

2 Test Configuration of EUT

2.1 Test Condition

Condition Item	Abbreviation/Remark	Remark
RF Conducted	Abbreviation	Remark
TnomVnom	Tnom	20°C
-	Vnom	120V

2.2 Test Channel Mode




Test Software	Putty
---------------	-------

Mode	Power Setting
802.11b_Nss1,(1Mbps)_2TX	-
2412MHz	88
2437MHz	88
2462MHz	88
802.11g_Nss1,(6Mbps)_2TX	-
2412MHz	78
2437MHz	88
2462MHz	88
802.11n HT20_Nss1,(MCS0)_2TX	-
2412MHz	71
2437MHz	88
2462MHz	88

2.3 The Worst Case Measurement Configuration

The Worst Case Mode for Following Conformance Tests	
Tests Item	AC power-line conducted emissions
Condition	AC power-line conducted measurement for line and neutral
Operating Mode	Normal Link
1	REC, BT ON, WiFi 2.4GHz, adapter(USB charging)

The Worst Case Mode for Following Conformance Tests	
Tests Item	DTS Bandwidth Maximum Conducted Output Power Power Spectral Density Emissions in Non-restricted Frequency Bands
Test Condition	Conducted measurement at transmit chains

The Worst Case Mode for Following Conformance Tests			
Tests Item	Emissions in Restricted Frequency Bands		
Test Condition	Radiated measurement If EUT consist of multiple antenna assembly (multiple antenna are used in EUT regardless of spatial multiplexing MIMO configuration), the radiated test should be performed with highest antenna gain of each antenna type.		
Operating Mode < 1GHz	CTX		
1	Adapter Mode		
Operating Mode > 1GHz	CTX		
Orthogonal Planes of EUT	X Plane	Y Plane	Z Plane
			
Worst Planes of EUT		V	

2.4 Accessories


Accessories				
AC Adapter	Brand Name	I.T.E	Model Name	KSA29B0500200D5
	Power Rating	I/P: 100 - 240Vac, 0.5 A, O/P: 5.0 Vdc, 2.0 A		
Data Cable	Brand Name	Mevo		
	Signal Line	3.04 meter, shielded cable, without ferrite core		
Li-ion Battery	Brand Name	FUJI	Model Name	901935
	Power Rating	3.7V/1200mAh 4.44Wh		


2.5 Support Equipment

Support Equipment – RF Conducted				
No.	Equipment	Brand Name	Model Name	FCC ID
1	Notebook	DELL	E5410	DoC
2	Adapter for NB	DELL	HA65NM130	DoC
3	AC Source	G.W	APS-9102	-

Support Equipment – AC Conduction				
No.	Equipment	Brand Name	Model Name	FCC ID
A	Micro SD Card	SanDisk	8GB	DoC
Z	iPad mini (Remote Workstation)	APPLE	16GB	DoC
Z	Notebook(BT) (Remote Workstation)	DELL	Latitude E5520	DoC

2.6 Test Setup Diagram



Test Setup Diagram - Radiated Test


Item	Connection	Shielded	Length(m)	Remark
1	AC Power line	No	1.8	-
2	Data cable	yes	3.04	-

3 Transmitter Test Result

3.1 AC Power-line Conducted Emissions

3.1.1 AC Power-line Conducted Emissions Limit

AC Power-line Conducted Emissions Limit		
Frequency Emission (MHz)	Quasi-Peak	Average
0.15-0.5	66 - 56 *	56 - 46 *
0.5-5	56	46
5-30	60	50

Note 1: * Decreases with the logarithm of the frequency.


3.1.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.1.3 Test Procedures

Test Method
<input checked="" type="checkbox"/> Refer as ANSI C63.10-2013, clause 6.2 for AC power-line conducted emissions.

3.1.4 Test Setup



3.1.5 Test Result of AC Power-line Conducted Emissions

Refer as Appendix A

3.2 DTS Bandwidth

3.2.1 6dB Bandwidth Limit

6dB Bandwidth Limit	
Systems using digital modulation techniques:	
▪	6 dB bandwidth \geq 500 kHz.


3.2.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.2.3 Test Procedures

Test Method	
▪	For the emission bandwidth shall be measured using one of the options below:
<input checked="" type="checkbox"/>	Refer as KDB 558074, clause 8.1 Option 1 for 6 dB bandwidth measurement.
<input type="checkbox"/>	Refer as KDB 558074, clause 8.2 Option 2 for 6 dB bandwidth measurement.
<input type="checkbox"/>	Refer as RSS-Gen, clause 6.6 for for occupied bandwidth testing.
<input type="checkbox"/>	Refer as ANSI C63.10, clause 6.9.3 for occupied bandwidth testing.

3.2.4 Test Setup



3.2.5 Test Result of Emission Bandwidth

Refer as Appendix B

3.3 Maximum Conducted Output Power

3.3.1 Maximum Conducted Output Power Limit

Maximum Conducted Output Power Limit		
	<ul style="list-style-type: none"> If $G_{TX} \leq 6$ dBi, then $P_{Out} \leq 30$ dBm (1 W) 	
	<ul style="list-style-type: none"> Point-to-multipoint systems (P2M): If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)$ dBm 	
	<ul style="list-style-type: none"> Point-to-point systems (P2P): If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)/3$ dBm 	
	<ul style="list-style-type: none"> Smart antenna system (SAS): 	
	-	Single beam: If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)/3$ dBm
	-	Overlap beam: If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)/3$ dBm
	-	Aggregate power on all beams: If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)/3 + 8$ dB dBm
e.i.r.p. Power Limit:		
	<ul style="list-style-type: none"> 2400-2483.5 MHz Band 	
	<ul style="list-style-type: none"> Point-to-multipoint systems (P2M): $P_{eirp} \leq 36$ dBm (4 W) 	
	<ul style="list-style-type: none"> Point-to-point systems (P2P): $P_{eirp} \leq \text{MAX}(36, [P_{Out} + G_{TX}])$ dBm 	
	<ul style="list-style-type: none"> Smart antenna system (SAS) 	
	-	Single beam: $P_{eirp} \leq \text{MAX}(36, P_{Out} + G_{TX})$ dBm
	-	Overlap beam: $P_{eirp} \leq \text{MAX}(36, P_{Out} + G_{TX})$ dBm
	-	Aggregate power on all beams: $P_{eirp} \leq \text{MAX}(36, [P_{Out} + G_{TX} + 8])$ dBm
P_{Out} = maximum peak conducted output power or maximum conducted output power in dBm, G_{TX} = the maximum transmitting antenna directional gain in dBi.		


3.3.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.3.3 Test Procedures

Test Method	
<ul style="list-style-type: none"> Maximum Peak Conducted Output Power 	
<input type="checkbox"/>	Refer as KDB 558074, clause 9.1.1 Option 1 (RBW ≥ EBW method).
<input type="checkbox"/>	Refer as KDB 558074, clause 9.1.2 Option 2 (integrated band power method)
<input type="checkbox"/>	Refer as KDB 558074, clause 9.1.3 Option 3 (peak power meter for VBW ≥ DTS BW)
<ul style="list-style-type: none"> Maximum Average Conducted Output Power 	
Duty cycle ≥ 98%	
<input type="checkbox"/>	Refer as KDB 558074, clause 9.2.2.4 Method AVGSA-2 (spectral trace averaging).
Duty cycle < 98%	
<input type="checkbox"/>	Refer as KDB 558074, clause 9.2.2.5 Method AVGSA-2 Alt. (slow sweep speed)
RF power meter and average over on/off periods with duty factor or gated trigger	
<input checked="" type="checkbox"/>	Refer as KDB 558074, clause 9.2.3.1 Method AVGPM (using an RF average power meter).
<ul style="list-style-type: none"> For conducted measurement. 	
<ul style="list-style-type: none"> If the EUT supports multiple transmit chains using options given below: Refer as KDB 662911, In-band power measurements. Using the measure-and-sum approach, measured all transmit ports individually. Sum the power (in linear power units e.g., mW) of all ports for each individual sample and save them. 	
<ul style="list-style-type: none"> If multiple transmit chains, EIRP calculation could be following as methods: $P_{total} = P_1 + P_2 + \dots + P_n$ (calculated in linear unit [mW] and transfer to log unit [dBm]) $EIRP_{total} = P_{total} + DG$ 	

3.3.4 Test Setup



3.3.5 Test Result of Maximum Conducted Output Power

Refer as Appendix C

3.4 Power Spectral Density

3.4.1 Power Spectral Density Limit

Power Spectral Density Limit	
▪	Power Spectral Density (PSD) \leq 8 dBm/3kHz


3.4.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.4.3 Test Procedures

Test Method	
▪	Peak power spectral density procedures that the same method as used to determine the conducted output power. If maximum peak conducted output power was measured to demonstrate compliance to the output power limit, then the peak PSD procedure below (Method PKPSD) shall be used. If maximum conducted output power was measured to demonstrate compliance to the output power limit, then one of the average PSD procedures shall be used, as applicable based on the following criteria (the peak PSD procedure is also an acceptable option).
<input checked="" type="checkbox"/>	Refer as KDB 558074, clause 10.2 Method PKPSD (RBW=3-100kHz; Detector=peak).
▪	For conducted measurement.
▪	If The EUT supports multiple transmit chains using options given below:
▪	Measure and sum the spectra across the outputs. Refer as KDB 662911, In-band power spectral density (PSD). Sample all transmit ports simultaneously using a spectrum analyzer for each transmit port. Where the trace bin-by-bin of each transmit port summing can be performed. (i.e., in the first spectral bin of output 1 is summed with that in the first spectral bin of output 2 and that from the first spectral bin of output 3, and so on up to the NTX output to obtain the value for the first frequency bin of the summed spectrum.). Add up the amplitude (power) values for the different transmit chains and use this as the new data trace.

3.4.4 Test Setup



3.4.5 Test Result of Power Spectral Density

Refer as Appendix D

3.5 Emissions in Non-restricted Frequency Bands

3.5.1 Emissions in Non-restricted Frequency Bands Limit

Un-restricted Band Emissions Limit	
RF output power procedure	Limit (dB)
Peak output power procedure	20
Average output power procedure	30
<p>Note 1: If the peak output power procedure is used to measure the fundamental emission power to demonstrate compliance to requirements, then the peak conducted output power measured within any 100 kHz outside the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum measured in-band peak PSD level.</p> <p>Note 2: If the average output power procedure is used to measure the fundamental emission power to demonstrate compliance to requirements, then the power in any 100 kHz outside of the authorized frequency band shall be attenuated by at least 30 dB relative to the maximum measured in-band average PSD level.</p>	


3.5.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.5.3 Test Procedures

Test Method
<ul style="list-style-type: none"> Refer as KDB 558074, clause 11 for unwanted emissions into non-restricted bands.

3.5.4 Test Setup



3.5.5 Test Result of Emissions in Non-restricted Frequency Bands

Refer as Appendix E

3.6 Emissions in Restricted Frequency Bands

3.6.1 Emissions in Restricted Frequency Bands Limit

Restricted Band Emissions Limit			
Frequency Range (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m)	Measure Distance (m)
0.009~0.490	2400/F(kHz)	48.5 - 13.8	300
0.490~1.705	24000/F(kHz)	33.8 - 23	30
1.705~30.0	30	29	30
30~88	100	40	3
88~216	150	43.5	3
216~960	200	46	3
Above 960	500	54	3

Note 1: Test distance for frequencies at or above 30 MHz, measurements may be performed at a distance other than the limit distance provided they are not performed in the near field and the emissions to be measured can be detected by the measurement equipment. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse of linear distance for field-strength measurements, inverse of linear distance-squared for power-density measurements).

Note 2: Test distance for frequencies at below 30 MHz, measurements may be performed at a distance closer than the EUT limit distance; however, an attempt should be made to avoid making measurements in the near field. When performing measurements below 30 MHz at a closer distance than the limit distance, the results shall be extrapolated to the specified distance by either making measurements at a minimum of two or more distances on at least one radial to determine the proper extrapolation factor or by using the square of an inverse linear distance extrapolation factor (40 dB/decade). The test report shall specify the extrapolation method used to determine compliance of the EUT.


3.6.2 Measuring Instruments


Refer a test equipment and calibration data table in this test report.

3.6.3 Test Procedures

Test Method	
<ul style="list-style-type: none"> The average emission levels shall be measured in [duty cycle \geq 98 or duty factor]. 	
<ul style="list-style-type: none"> Refer as ANSI C63.10, clause 6.10.3 band-edge testing shall be performed at the lowest frequency channel and highest frequency channel within the allowed operating band. 	
<ul style="list-style-type: none"> For the transmitter unwanted emissions shall be measured using following options below: 	
	<ul style="list-style-type: none"> Refer as KDB 558074, clause 12 for unwanted emissions into restricted bands.
	<input checked="" type="checkbox"/> Refer as KDB 558074, clause 12.2.5.3 (ANSI C63.10, clause 4.1.4.2.3), Reduced VBW \geq 1/T.
	<input checked="" type="checkbox"/> Refer as KDB 558074, clause 12.2.4 measurement procedure peak limit.
<ul style="list-style-type: none"> For the transmitter band-edge emissions shall be measured using following options below: 	
	<ul style="list-style-type: none"> Refer as KDB 558074 clause 13.1, When the performing peak or average radiated measurements, emissions within 2 MHz of the authorized band edge may be measured using the marker-delta method described below.
	<ul style="list-style-type: none"> Refer as KDB 558074, clause 13.2 (ANSI C63.10, clause 6.10.6) for marker-delta method for band-edge measurements.
	<ul style="list-style-type: none"> Refer as KDB 558074, clause 13.3 for narrower resolution bandwidth (100kHz) using the band power and summing the spectral levels (i.e., 1 MHz).
<ul style="list-style-type: none"> For conducted and cabinet radiation measurement, refer as KDB 558074, clause 12.2.2. 	
	<ul style="list-style-type: none"> For conducted unwanted emissions into restricted bands (absolute emission limits). Devices with multiple transmit chains using options given below: (1) Measure and sum the spectra across the outputs or (2) Measure and add 10 log(N) dB
	<ul style="list-style-type: none"> For KDB 662911 The methodology described here may overestimate array gain, thereby resulting in apparent failures to satisfy the out-of-band limits even if the device is actually compliant. In such cases, compliance may be demonstrated by performing radiated tests around the frequencies at which the apparent failures occurred.

3.6.4 Test Setup





3.6.5 Test Result of Emissions in Restricted Frequency Bands (Below 30MHz)

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported. All amplitude of spurious emissions that are attenuated by more than 20 dB below the permissible value has no need to be reported.

3.6.6 Test Result of Emissions in Restricted Frequency Bands

Refer as Appendix F

4 Test Equipment and Calibration Data

Instrument for AC Conduction

Instrument	Manufacturer	Model No.	Serial No.	Spec.	Calibration Date	Calibration Due Date
Test Receiver	R&S	ESR3	102051	9 KHz ~ 3.6 GHz	29/Apr/2017	28/Apr/2018
Two-Line V-Network	R&S	ENV 216	100003	9 kHz ~ 30 MHz	30/Aug/2016	29/Aug/2017
RF Cable-CON	Weiyang	WY200	CB018	9 kHz ~ 30 MHz	07/Feb/2017	06/Feb/2018
Impulsbegrenzer Pulse Limiter	R&S	ESH3-Z2	100921	10 kHz ~ 30 MHz	20/Oct/2016	19/Oct/2017

Instrument for Radiated Test


Instrument	Manufacturer	Model No.	Serial No.	Spec.	Calibration Date	Calibration Due Date
3m Semi Anechoic Chamber	TDK	SAC-3M	03CH09-HY	30MHz ~ 1GHz	25/Apr/2017	24/Apr/2018
3m Semi Anechoic Chamber	TDK	SAC-3M	03CH09-HY	1GHz ~ 18GHz	28/Jun/2017	27/Jun/2018
Amplifier	Agilent	8449B	3008A02096	1GHz ~ 26.5GHz	25/Apr/2017	24/Apr/2018
Amplifier	EMC	EMC9135	980232	9KHz~1GHz	25/Apr/2017	24/Apr/2018
Spectrum Analyzer	KEYSIGHT	N9010A	MY54200885	10Hz ~ 44GHz	20/Jul/2017	19/Jul/2018
Bilog Antenna	TESEQ	CBL 6111D	35418	30MHz~1GHz	01/Oct/2016	30/Sep/2017
Horn Antenna	SCHWARZBECK	BBHA 9120D	BBHA9120D 1534	1GHz~18GHz	28/Apr/2017	27/Apr/2018
Horn Antenna	SCHWARZBECK	BBHA9170	BBHA9170614	18GHz ~ 40GHz	06/Feb/2017	05/Feb/2018
Loop Antenna	R&S	HFH2-Z2	100330	9 kHz~30 MHz	10/Nov/2016	09/Nov/2017
RF Cable-R03m	Jye Bao	RG142	CB021	9kHz ~ 1GHz	02/Feb/2017	01/Feb/2018
RF Cable-high	Jye Bao	RG142	03CH09-HY	1GHz ~ 40GHz	02/Feb/2017	01/Feb/2018
Receiver	R&S	ESU-26	100422/026	20Hz ~ 26.5GHz	21/Sep/2017	20/Sep/2018

**Instrument for Conducted Test**

Instrument	Manufacturer	Model No.	Serial No.	Spec.	Calibration Date	Calibration Due Date
Spectrum Analyzer	R&S	FSV 40	101500	9kHz~40GHz	28/Jun/2017	27Jun/2018
Power Sensor	Anritsu	MA2411B	1027452	300MHz ~ 40GHz	27/Oct/2016	26/Oct/2017
Power Meter	Anritsu	ML2495A	1124009	300MHz ~ 40GHz	27/Oct/2016	26/Oct/2017
Signal Generator	R&S	SMR40	100116	10MHz ~ 40GHz	27/Jul/2017	26/Jul/2018
RF Cable-0.2m	HUBER+SUHNER	SUCOFLEX_104	MY10709/4	30MHz ~ 26.5GHz	02/Oct/2016	01/Oct/2017
RF Cable-0.2m	HUBER+SUHNER	SUCOFLEX_104	MY10710/4	30MHz ~ 26.5GHz	02/Oct/2016	01/Oct/2017
RF Cable-0.5m	HUBER+SUHNER	SUCOFLEX_104	MY10713/4	30MHz ~ 26.5GHz	02/Oct/2016	01/Oct/2017

AC Power-line Conducted Emissions Result

Operating Mode	1	Power Phase	Neutral
Operating Function	REC , BT ON , WiFi 2.4GHz , adapter(usb charging)		




	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.156	24.60	-31.07	55.67	14.90	9.67	0.03	Average
2	0.156	36.77	-28.90	65.67	27.07	9.67	0.03	QP
3	0.184	23.58	-30.72	54.30	13.90	9.65	0.03	Average
4	0.184	33.79	-30.51	64.30	24.11	9.65	0.03	QP
5	0.424	32.28	-25.09	57.37	22.51	9.73	0.04	QP
6	0.424	22.13	-25.24	47.37	12.36	9.73	0.04	Average
7	0.505	40.27	-15.73	56.00	30.51	9.72	0.04	QP
8	0.505	29.69	-16.31	46.00	19.93	9.72	0.04	Average
9	1.110	18.63	-27.37	46.00	8.85	9.69	0.09	Average
10	1.110	28.38	-27.62	56.00	18.60	9.69	0.09	QP
11	1.410	26.54	-29.46	56.00	16.76	9.68	0.10	QP
12	1.410	18.36	-27.64	46.00	8.58	9.68	0.10	Average

Note 1: ">20dB" means emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found emissions (No emissions were detected.)

AC Power-line Conducted Emissions Result

Operating Mode	1	Power Phase	Line
Operating Function	REC , BT ON , WiFi 2.4GHz , adapter(usb charging)		



	Freq	Level	Over	Limit	Read	LISN	Cable	
	MHz	dBuV	Limit	Line	Level	Factor	Loss	Remark
			dB	dBuV	dBuV	dB	dB	
1	0.156	38.13	-27.56	65.69	28.40	9.70	0.03	QP
2	0.156	29.89	-25.80	55.69	20.16	9.70	0.03	Average
3	0.190	33.25	-30.79	64.04	23.53	9.69	0.03	QP
4	0.190	23.20	-30.84	54.04	13.48	9.69	0.03	Average
5	0.317	35.28	-24.51	59.79	25.53	9.72	0.03	QP
6	0.317	30.47	-19.32	49.79	20.72	9.72	0.03	Average
7	0.521	44.44	-11.56	56.00	34.67	9.73	0.04	QP
8 @	0.521	39.72	-6.28	46.00	29.95	9.73	0.04	Average
9	1.513	32.66	-23.34	56.00	22.90	9.65	0.11	QP
10	1.513	26.29	-19.71	46.00	16.53	9.65	0.11	Average
11	7.410	27.07	-32.93	60.00	16.97	9.83	0.27	QP
12	7.410	21.35	-28.65	50.00	11.25	9.83	0.27	Average

Note 1: ">20dB" means emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found emissions (No emissions were detected.)

Summary

Mode	Max-N dB (Hz)	Max-OBW (Hz)	ITU-Code	Min-N dB (Hz)	Min-OBW (Hz)
802.11b_Nss1,(1Mbps)_2TX	-	-	-	-	-
2.4-2.4835GHz	9.05M	11.869M	11M9G1D	8.05M	11.444M
802.11g_Nss1,(6Mbps)_2TX	-	-	-	-	-
2.4-2.4835GHz	16.35M	16.867M	16M9D1D	16.075M	16.617M
802.11n HT20_Nss1,(MCS0)_2TX	-	-	-	-	-
2.4-2.4835GHz	17.6M	17.891M	17M9D1D	17.525M	17.766M




Max-N dB = Maximum 6dB down bandwidth; **Max-OBW** = Maximum 99% occupied bandwidth;




Min-N dB = Minimum 6dB down bandwidth; **Min-OBW** = Minimum 99% occupied bandwidth;




Result

Mode	Result	Limit (Hz)	Port 1-N dB (Hz)	Port 1-OBW (Hz)	Port 2-N dB (Hz)	Port 2-OBW (Hz)
802.11b_Nss1,(1Mbps)_2TX	-	-	-	-	-	-
2412MHz_TnomVnom	Pass	500k	8.05M	11.444M	9.05M	11.869M
2437MHz_TnomVnom	Pass	500k	8.075M	11.669M	8.575M	11.844M
2462MHz_TnomVnom	Pass	500k	9M	11.469M	9.05M	11.869M
802.11g_Nss1,(6Mbps)_2TX	-	-	-	-	-	-
2412MHz_TnomVnom	Pass	500k	16.075M	16.767M	16.325M	16.717M
2437MHz_TnomVnom	Pass	500k	16.35M	16.617M	16.325M	16.692M
2462MHz_TnomVnom	Pass	500k	16.325M	16.867M	16.3M	16.692M
802.11n HT20_Nss1,(MCS0)_2TX	-	-	-	-	-	-
2412MHz_TnomVnom	Pass	500k	17.525M	17.841M	17.6M	17.866M
2437MHz_TnomVnom	Pass	500k	17.55M	17.816M	17.525M	17.766M
2462MHz_TnomVnom	Pass	500k	17.575M	17.891M	17.575M	17.841M

Port X-N dB = Port X 6dB down bandwidth; **Port X-OBW** = Port X 99% occupied bandwidth;

802.11b_Nss1,(1Mbps)_2TX
EBW
2412MHz

802.11b_Nss1,(1Mbps)_2TX
EBW
2437MHz

802.11b_Nss1,(1Mbps)_2TX
EBW
2462MHz


802.11g_Nss1,(6Mbps)_2TX
EBW
2412MHz

802.11g_Nss1,(6Mbps)_2TX
EBW
2437MHz

802.11g_Nss1,(6Mbps)_2TX
EBW
2462MHz


802.11n HT20_Nss1,(MCS0)_2TX
EBW
2412MHz

802.11n HT20_Nss1,(MCS0)_2TX
EBW
2437MHz

802.11n HT20_Nss1,(MCS0)_2TX
EBW
2462MHz


Summary

Mode	Total Power (dBm)	Total Power (W)
802.11b_Nss1,(1Mbps)_2TX	-	-
2.4-2.4835GHz	22.33	0.17100
802.11g_Nss1,(6Mbps)_2TX	-	-
2.4-2.4835GHz	21.08	0.12823
802.11n HT20_Nss1,(MCS0)_2TX	-	-
2.4-2.4835GHz	20.68	0.11695

Result

Mode	Result	DG (dBi)	Port 1 (dBm)	Port 2 (dBm)	Total Power (dBm)	Power Limit (dBm)
802.11b_Nss1,(1Mbps)_2TX	-	-	-	-	-	-
2412MHz_TnomVnom	Pass	1.20	17.43	18.20	20.84	30.00
2437MHz_TnomVnom	Pass	1.20	16.76	18.03	20.45	30.00
2462MHz_TnomVnom	Pass	1.20	18.64	19.92	22.33	30.00
802.11g_Nss1,(6Mbps)_2TX	-	-	-	-	-	-
2412MHz_TnomVnom	Pass	1.20	16.92	17.47	20.21	30.00
2437MHz_TnomVnom	Pass	1.20	17.14	18.26	20.75	30.00
2462MHz_TnomVnom	Pass	1.20	17.61	18.49	21.08	30.00
802.11n HT20_Nss1,(MCS0)_2TX	-	-	-	-	-	-
2412MHz_TnomVnom	Pass	1.20	17.07	17.69	20.40	30.00
2437MHz_TnomVnom	Pass	1.20	16.63	17.78	20.25	30.00
2462MHz_TnomVnom	Pass	1.20	17.13	18.14	20.68	30.00

DG = Directional Gain; **Port X** = Port X output power

Summary

Mode	PD (dBm/RBW)
802.11b_Nss1,(1Mbps)_2TX	-
2.4-2.4835GHz	-2.86
802.11g_Nss1,(6Mbps)_2TX	-
2.4-2.4835GHz	-5.48
802.11n HT20_Nss1,(MCS0)_2TX	-
2.4-2.4835GHz	-7.31

RBW=3kHz.

Result

Mode	Result	DG (dBi)	Port 1 (dBm/RBW)	Port 2 (dBm/RBW)	PD (dBm/RBW)	PD Limit (dBm/RBW)
802.11b_Nss1,(1Mbps)_2TX	-	-	-	-	-	-
2412MHz_TnomVnom	Pass	3.24	-6.54	-6.43	-4.82	8.00
2437MHz_TnomVnom	Pass	3.24	-6.98	-4.89	-4.30	8.00
2462MHz_TnomVnom	Pass	3.24	-4.83	-3.96	-2.86	8.00
802.11g_Nss1,(6Mbps)_2TX	-	-	-	-	-	-
2412MHz_TnomVnom	Pass	3.24	-8.98	-8.95	-6.35	8.00
2437MHz_TnomVnom	Pass	3.24	-9.11	-7.59	-5.78	8.00
2462MHz_TnomVnom	Pass	3.24	-8.31	-7.47	-5.48	8.00
802.11n HT20_Nss1,(MCS0)_2TX	-	-	-	-	-	-
2412MHz_TnomVnom	Pass	3.24	-9.10	-9.05	-7.31	8.00
2437MHz_TnomVnom	Pass	3.24	-10.13	-9.11	-8.53	8.00
2462MHz_TnomVnom	Pass	3.24	-8.98	-8.13	-7.48	8.00


DG = Directional Gain; RBW=3kHz;

PD = trace bin-by-bin of each transmits port summing can be performed maximum power density; **Port X** = Port X power density;

802.11b_Nss1,(1Mbps)_2TX

PSD

2412MHz




Sum	PD	Port 1	Port 2
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-4.82	-4.82	-6.54	-6.43

802.11b_Nss1,(1Mbps)_2TX

PSD

2437MHz




Sum	PD	Port 1	Port 2
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-4.30	-4.30	-6.98	-4.89

802.11b_Nss1,(1Mbps)_2TX

PSD

2462MHz




Sum	PD	Port 1	Port 2
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-2.86	-2.86	-4.83	-3.96

802.11g_Nss1,(6Mbps)_2TX

PSD

2412MHz




Sum	PD	Port 1	Port 2
(dBm/100kHz)	(dBm/100kHz)	(dBm/100kHz)	(dBm/100kHz)
-6.35	-6.35	-8.98	-8.95

802.11g_Nss1,(6Mbps)_2TX

PSD

2437MHz




Sum	PD	Port 1	Port 2
(dBm/100kHz)	(dBm/100kHz)	(dBm/100kHz)	(dBm/100kHz)
-5.78	-5.78	-9.11	-7.59

802.11g_Nss1,(6Mbps)_2TX

PSD

2462MHz




Sum	PD	Port 1	Port 2
(dBm/100kHz)	(dBm/100kHz)	(dBm/100kHz)	(dBm/100kHz)
-5.48	-5.48	-8.31	-7.47

802.11n HT20_Nss1,(MCS0)_2TX

PSD


2412MHz



802.11n HT20_Nss1,(MCS0)_2TX

PSD


2437MHz



802.11n HT20_Nss1,(MCS0)_2TX

PSD

2462MHz





Summary

Mode	Result	Ref (Hz)	Ref (dBm)	Limit (dBm)	Freq (Hz)	Level (dBm)	Freq (Hz)	Level (dBm)	Freq (Hz)	Level (dBm)	Freq (Hz)	Level (dBm)	Port
802.11n HT20_Nss1,(MCS0)_2TX	-	-	-	-	-	-	-	-	-	-	-	-	-
2.4-2.4835GHz	Pass	2.455778G	6.18	-23.82	1.771675G	-57.07	2.39752G	-25.11	2.48494G	-55.49	16.984318G	-51.41	2


Result

Mode	Result	Ref (Hz)	Ref (dBm)	Limit (dBm)	Freq (Hz)	Level (dBm)	Freq (Hz)	Level (dBm)	Freq (Hz)	Level (dBm)	Freq (Hz)	Level (dBm)	Port
802.11b_Nss1,(1Mbps)_2TX	-	-	-	-	-	-	-	-	-	-	-	-	-
2412MHz_TnomVnom	Pass	2.463126G	11.32	-18.68	847.83M	-57.32	2.39904G	-30.96	2.48742G	-55.56	16.259451G	-50.88	1
2412MHz_TnomVnom	Pass	2.463126G	11.32	-18.68	1.92196G	-57.01	2.39904G	-28.05	2.48742G	-55.35	14.992338G	-51.23	2
2437MHz_TnomVnom	Pass	2.463126G	11.32	-18.68	635.8M	-56.71	2.39952G	-52.00	2.4867G	-55.61	16.942175G	-51.22	1
2437MHz_TnomVnom	Pass	2.463126G	11.32	-18.68	826.86M	-57.73	2.39784G	-50.82	2.48638G	-55.11	16.256642G	-51.25	2
2462MHz_TnomVnom	Pass	2.463126G	11.32	-18.68	795.405M	-56.63	2.39664G	-52.87	2.48598G	-47.92	15.186198G	-51.55	1
2462MHz_TnomVnom	Pass	2.463126G	11.32	-18.68	920.06M	-56.22	2.39784G	-53.31	2.48598G	-43.83	16.84665G	-50.76	2
802.11g_Nss1,(6Mbps)_2TX	-	-	-	-	-	-	-	-	-	-	-	-	-
2412MHz_TnomVnom	Pass	2.460788G	6.95	-23.05	512.31M	-57.56	2.39744G	-26.71	2.48358G	-55.61	17.647375G	-50.77	1
2412MHz_TnomVnom	Pass	2.460788G	6.95	-23.05	875.79M	-57.44	2.39744G	-24.68	2.48662G	-54.27	16.413977G	-51.48	2
2437MHz_TnomVnom	Pass	2.460788G	6.95	-23.05	915.4M	-57.67	2.3996G	-42.87	2.48438G	-53.04	15.180579G	-51.74	1
2437MHz_TnomVnom	Pass	2.460788G	6.95	-23.05	582.21M	-57.66	2.39808G	-42.64	2.48398G	-52.31	16.593789G	-51.45	2
2462MHz_TnomVnom	Pass	2.460788G	6.95	-23.05	853.655M	-57.00	2.39928G	-52.40	2.4839G	-38.80	15.211484G	-51.56	1
2462MHz_TnomVnom	Pass	2.460788G	6.95	-23.05	931.71M	-56.78	2.39976G	-50.47	2.48358G	-37.19	24.005415G	-51.07	2
802.11n HT20_Nss1,(MCS0)_2TX	-	-	-	-	-	-	-	-	-	-	-	-	-
2412MHz_TnomVnom	Pass	2.455778G	6.18	-23.82	943.36M	-56.88	2.398G	-27.75	2.48414G	-56.24	16.225736G	-50.69	1
2412MHz_TnomVnom	Pass	2.455778G	6.18	-23.82	1.771675G	-57.07	2.39752G	-25.11	2.48494G	-55.49	16.984318G	-51.41	2
2437MHz_TnomVnom	Pass	2.455778G	6.18	-23.82	908.41M	-55.39	2.39712G	-44.52	2.4851G	-52.53	16.290356G	-52.10	1
2437MHz_TnomVnom	Pass	2.455778G	6.18	-23.82	953.845M	-57.73	2.39896G	-44.11	2.48454G	-52.79	21.40657G	-51.59	2
2462MHz_TnomVnom	Pass	2.455778G	6.18	-23.82	788.415M	-56.84	2.39976G	-52.16	2.48358G	-37.97	17.655804G	-50.87	1
2462MHz_TnomVnom	Pass	2.455778G	6.18	-23.82	657.935M	-57.61	2.39968G	-51.99	2.48518G	-35.38	17.085462G	-50.63	2

802.11b_Nss1,(1Mbps)_2TX

CSE NdB


2412MHz



802.11b_Nss1,(1Mbps)_2TX

CSE NdB


2437MHz



802.11b_Nss1,(1Mbps)_2TX

CSE NdB


2462MHz



802.11g_Nss1,(6Mbps)_2TX

CSE NdB


2412MHz



802.11g_Nss1,(6Mbps)_2TX

CSE NdB


2437MHz



802.11g_Nss1,(6Mbps)_2TX

CSE NdB


2462MHz



802.11n HT20_Nss1,(MCS0)_2TX

CSE NdB


2412MHz



802.11n HT20_Nss1,(MCS0)_2TX

CSE NdB


2437MHz



802.11n HT20_Nss1,(MCS0)_2TX

CSE NdB

2462MHz



**Summary**


Mode	Result	Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
802.11n HT20_Nss1,(MCS0)_2TX	-	-	-	-	-	-	-	-	-	-	-	-
2.4-2.4835GHz	Pass	PK	1.1649M	47.96	67.80	-19.84	20.78	3	Horizontal	360	1.00	-

Result

Mode	Result	Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
802.11n HT20_Nss1 ₁ (MCS0)_2TX	-	-	-	-	-	-	-	-	-	-	-	-
2437MHz	Pass	PK	12.384k	59.84	128.26	-68.42	21.90	3	Horizontal	0	1.00	-
2437MHz	Pass	PK	35.226k	52.35	126.61	-74.26	21.85	3	Horizontal	0	1.00	-
2437MHz	Pass	PK	112.212k	44.73	121.05	-76.32	20.77	3	Horizontal	0	1.00	-
2437MHz	Pass	PK	1.1649M	47.96	67.80	-19.84	20.78	3	Horizontal	360	1.00	-
2437MHz	Pass	PK	2.4186M	46.66	69.50	-22.84	20.61	3	Horizontal	360	1.00	-
2437MHz	Pass	PK	22.1793M	33.68	69.50	-35.82	22.99	3	Horizontal	360	1.00	-

802.11n HT20_Nss1,(MCS0)_2TX

2437MHz_adapter mode



EUT = Y

Type	Freq	Level	Limit	Margin	Factor	Dist	Condition	Azimuth	Height	Comments	Raw	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dB)	(m)		(°)	(m)		(dBuV)	(dB)	(dB)	(dB)
PK	12.384k	59.84	128.26	-68.42	21.90	3	Horizontal	0	1.00	-	37.94	21.82	0.08	-
PK	35.226k	52.35	126.61	-74.26	21.85	3	Horizontal	0	1.00	-	30.50	21.76	0.08	-
PK	112.212k	44.73	121.05	-76.32	20.77	3	Horizontal	0	1.00	-	23.96	20.69	0.08	-

802.11n HT20_Nss1,(MCS0)_2TX

2437MHz_adapter mode



EUT = Y

Type	Freq	Level	Limit	Margin	Factor	Dist	Condition	Azimuth	Height	Comments	Raw	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dB)	(m)		(°)	(m)		(dBuV)	(dB)	(dB)	(dB)
PK	22.1793M	33.68	69.50	-35.82	22.99	3	Horizontal	360	1.00	-	10.69	22.47	0.52	-
PK	1.1649M	47.96	67.80	-19.84	20.78	3	Horizontal	360	1.00	-	27.18	20.68	0.10	-
PK	2.4186M	46.66	69.50	-22.84	20.61	3	Horizontal	360	1.00	-	26.05	20.49	0.13	-

Summary


Mode	Result	Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
802.11n HT20_Nss1,(MCS0)_2TX	-	-	-	-	-	-	-	-	-	-	-	-
2.4-2.4835GHz	Pass	QP	336.52M	42.81	46.00	-3.19	-14.54	3	Horizontal	0	1.00	-

Result

Mode	Result	Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
802.11n HT20_Nss1,(MCS0)_2TX	-	-	-	-	-	-	-	-	-	-	-	-
2437MHz	Pass	PK	144.46M	31.34	43.50	-12.16	-18.39	3	Horizontal	0	1.00	-
2437MHz	Pass	PK	239.52M	42.28	46.00	-3.72	-17.83	3	Horizontal	0	1.00	-
2437MHz	Pass	PK	307.42M	42.59	46.00	-3.41	-15.23	3	Horizontal	0	1.00	-
2437MHz	Pass	PK	600.36M	29.46	46.00	-16.54	-8.62	3	Horizontal	0	1.00	-
2437MHz	Pass	PK	899.12M	37.58	46.00	-8.42	-4.71	3	Horizontal	0	1.00	-
2437MHz	Pass	QP	336.52M	42.81	46.00	-3.19	-14.54	3	Horizontal	0	1.00	-
2437MHz	Pass	PK	144.46M	29.93	43.50	-13.57	-18.39	3	Vertical	360	1.00	-
2437MHz	Pass	PK	187.14M	36.14	43.50	-7.36	-20.39	3	Vertical	360	1.00	-
2437MHz	Pass	PK	262.8M	40.76	46.00	-5.24	-15.08	3	Vertical	360	1.00	-
2437MHz	Pass	PK	720.64M	34.00	46.00	-12.00	-7.04	3	Vertical	360	1.00	-
2437MHz	Pass	PK	899.12M	34.91	46.00	-11.09	-4.71	3	Vertical	360	1.00	-
2437MHz	Pass	QP	600.36M	42.29	46.00	-3.71	-8.62	3	Vertical	360	1.00	-

802.11n HT20_Nss1,(MCS0)_2TX

2437MHz_adapter mode




EUT = Y

Type	Freq	Level	Limit	Margin	Factor	Dist	Condition	Azimuth	Height	Comments	Raw	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dB)	(m)		(°)	(m)		(dBuV)	(dB)	(dB)	(dB)
PK	144.46M	29.93	43.50	-13.57	-18.39	3	Vertical	360	1.00	-	48.32	16.23	1.99	36.61
PK	187.14M	36.14	43.50	-7.36	-20.39	3	Vertical	360	1.00	-	56.53	13.80	2.24	36.43
PK	262.8M	40.76	46.00	-5.24	-15.08	3	Vertical	360	1.00	-	55.84	18.67	2.67	36.42
PK	720.64M	34.00	46.00	-12.00	-7.04	3	Vertical	360	1.00	-	41.04	25.94	4.40	37.38
PK	899.12M	34.91	46.00	-11.09	-4.71	3	Vertical	360	1.00	-	39.62	27.76	5.06	37.53
QP	600.36M	42.29	46.00	-3.71	-8.62	3	Vertical	360	1.00	-	50.91	24.45	4.12	37.19

802.11n HT20_Nss1,(MCS0)_2TX

2437MHz_adapter mode



EUT = Y

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments	Raw (dBuV)	AF (dB)	CL (dB)	PA (dB)
PK	144.46M	31.34	43.50	-12.16	-18.39	3	Horizontal	0	1.00	-	49.73	16.23	1.99	36.61
PK	239.52M	42.28	46.00	-3.72	-17.83	3	Horizontal	0	1.00	-	60.11	16.06	2.51	36.40
PK	307.42M	42.59	46.00	-3.41	-15.23	3	Horizontal	0	1.00	-	57.82	18.22	3.00	36.45
PK	600.36M	29.46	46.00	-16.54	-8.62	3	Horizontal	0	1.00	-	38.08	24.45	4.12	37.19
PK	899.12M	37.58	46.00	-8.42	-4.71	3	Horizontal	0	1.00	-	42.29	27.76	5.06	37.53
QP	336.52M	42.81	46.00	-3.19	-14.54	3	Horizontal	0	1.00	-	57.35	18.89	3.07	36.50

Summary

Mode	Result	Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
802.11g_(6Mbps)_2TX	-	-	-	-	-	-	-	-	-	-	-	-
2.4-2.4835GHz	Pass	AV	2.39G	53.65	54.00	-0.35	31.17	3	Horizontal	3	1.04	-

Result

Mode	Result	Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
802.11b_(1Mbps)_2TX	-	-	-	-	-	-	-	-	-	-	-	-
2412MHz	Pass	AV	2.3874G	47.91	54.00	-6.09	30.93	3	Horizontal	342	1.16	-
2412MHz	Pass	AV	2.4138G	97.69	Inf	-Inf	31.02	3	Horizontal	342	1.16	-
2412MHz	Pass	PK	2.3874G	57.00	74.00	-17.00	30.93	3	Horizontal	342	1.16	-
2412MHz	Pass	PK	2.413G	101.58	Inf	-Inf	31.02	3	Horizontal	342	1.16	-
2412MHz	Pass	AV	2.3872G	44.85	54.00	-9.15	30.93	3	Vertical	322	1.43	-
2412MHz	Pass	AV	2.4104G	91.29	Inf	-Inf	31.01	3	Vertical	322	1.43	-
2412MHz	Pass	PK	2.3874G	55.33	74.00	-18.67	30.93	3	Vertical	322	1.43	-
2412MHz	Pass	PK	2.4112G	94.87	Inf	-Inf	31.01	3	Vertical	322	1.43	-
2412MHz	Pass	AV	4.824G	49.48	54.00	-4.52	2.48	3	Horizontal	330	2.16	-
2412MHz	Pass	PK	4.824G	52.03	74.00	-21.97	2.48	3	Horizontal	330	2.16	-
2412MHz	Pass	AV	4.824G	50.98	54.00	-3.02	2.48	3	Vertical	319	2.72	-
2412MHz	Pass	PK	4.824G	52.70	74.00	-21.30	2.48	3	Vertical	319	2.72	-
2437MHz	Pass	AV	2.365G	43.94	54.00	-10.06	31.07	3	Horizontal	40	1.12	-
2437MHz	Pass	AV	2.4358G	88.85	Inf	-Inf	31.35	3	Horizontal	40	1.12	-
2437MHz	Pass	AV	2.4978G	44.74	54.00	-9.26	31.58	3	Horizontal	40	1.12	-
2437MHz	Pass	PK	2.3814G	57.08	74.00	-16.92	31.14	3	Horizontal	40	1.12	-
2437MHz	Pass	PK	2.4362G	92.00	Inf	-Inf	31.35	3	Horizontal	40	1.12	-
2437MHz	Pass	PK	2.4966G	58.08	74.00	-15.92	31.58	3	Horizontal	40	1.12	-
2437MHz	Pass	AV	2.3794G	43.88	54.00	-10.12	31.13	3	Vertical	255	3.35	-
2437MHz	Pass	AV	2.4358G	88.33	Inf	-Inf	31.35	3	Vertical	255	3.35	-
2437MHz	Pass	AV	2.4846G	44.75	54.00	-9.25	31.53	3	Vertical	255	3.35	-
2437MHz	Pass	PK	2.3862G	57.52	74.00	-16.48	31.16	3	Vertical	255	3.35	-
2437MHz	Pass	PK	2.437G	91.55	Inf	-Inf	31.35	3	Vertical	255	3.35	-
2437MHz	Pass	PK	2.4978G	57.27	74.00	-16.73	31.58	3	Vertical	255	3.35	-
2437MHz	Pass	AV	4.874G	45.19	54.00	-8.81	2.55	3	Horizontal	324	1.04	-
2437MHz	Pass	AV	7.311G	36.28	54.00	-17.72	8.42	3	Horizontal	0	1.50	-
2437MHz	Pass	PK	4.874G	49.81	74.00	-24.19	2.55	3	Horizontal	324	1.04	-
2437MHz	Pass	PK	7.311G	51.15	74.00	-22.85	8.42	3	Horizontal	0	1.50	-
2437MHz	Pass	AV	4.874G	46.19	54.00	-7.81	2.32	3	Vertical	15	2.41	-
2437MHz	Pass	AV	7.311G	36.13	54.00	-17.87	7.60	3	Vertical	268	1.50	-
2437MHz	Pass	PK	4.874G	50.63	74.00	-23.37	2.32	3	Vertical	15	2.41	-
2437MHz	Pass	PK	7.311G	49.79	74.00	-24.21	7.60	3	Vertical	268	1.50	-
2462MHz	Pass	AV	2.4608G	95.52	Inf	-Inf	31.44	3	Horizontal	301	1.01	-
2462MHz	Pass	AV	2.5G	44.59	54.00	-9.41	31.59	3	Horizontal	301	1.01	-
2462MHz	Pass	PK	2.4606G	98.51	Inf	-Inf	31.44	3	Horizontal	301	1.01	-
2462MHz	Pass	PK	2.5G	57.67	74.00	-16.33	31.59	3	Horizontal	301	1.01	-
2462MHz	Pass	AV	2.461G	93.53	Inf	-Inf	31.44	3	Vertical	57	3.69	-
2462MHz	Pass	AV	2.5G	44.59	54.00	-9.41	31.59	3	Vertical	57	3.69	-
2462MHz	Pass	PK	2.4606G	96.82	Inf	-Inf	31.44	3	Vertical	57	3.69	-
2462MHz	Pass	PK	2.5G	56.06	74.00	-17.94	31.59	3	Vertical	57	3.69	-
2462MHz	Pass	AV	4.924G	51.13	54.00	-2.87	2.63	3	Horizontal	66	2.47	-
2462MHz	Pass	AV	7.386G	42.51	54.00	-11.49	8.51	3	Horizontal	84	1.38	-
2462MHz	Pass	PK	4.924G	54.13	74.00	-19.87	2.63	3	Horizontal	66	2.47	-
2462MHz	Pass	PK	7.386G	52.31	74.00	-21.69	8.51	3	Horizontal	84	1.38	-
2462MHz	Pass	AV	4.924G	53.26	54.00	-0.74	2.63	3	Vertical	10	2.34	-
2462MHz	Pass	AV	7.386G	45.51	54.00	-8.49	8.51	3	Vertical	15	1.50	-
2462MHz	Pass	PK	4.924G	55.63	74.00	-18.37	2.63	3	Vertical	10	2.34	-


Mode	Result	Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
2462MHz	Pass	PK	7.386G	52.71	74.00	-21.29	8.51	3	Vertical	15	1.50	-
802.11g_(6Mbps)_2TX	-	-	-	-	-	-	-	-	-	-	-	-
2412MHz	Pass	AV	2.39G	53.65	54.00	-0.35	31.17	3	Horizontal	3	1.04	-
2412MHz	Pass	AV	2.416G	97.29	Inf	-Inf	31.27	3	Horizontal	3	1.04	-
2412MHz	Pass	PK	2.3898G	66.05	74.00	-7.95	31.17	3	Horizontal	3	1.04	-
2412MHz	Pass	PK	2.4158G	104.55	Inf	-Inf	31.27	3	Horizontal	3	1.04	-
2412MHz	Pass	AV	2.3898G	51.72	54.00	-2.28	31.17	3	Vertical	304	3.69	-
2412MHz	Pass	AV	2.4146G	94.42	Inf	-Inf	31.27	3	Vertical	304	3.69	-
2412MHz	Pass	PK	2.3882G	63.32	74.00	-10.68	31.16	3	Vertical	304	3.69	-
2412MHz	Pass	PK	2.4144G	102.34	Inf	-Inf	31.26	3	Vertical	304	3.69	-
2412MHz	Pass	AV	4.824G	39.20	54.00	-14.80	2.16	3	Horizontal	57	1.01	-
2412MHz	Pass	PK	4.824G	50.32	74.00	-23.68	2.16	3	Horizontal	57	1.01	-
2412MHz	Pass	AV	4.824G	37.25	54.00	-16.75	2.48	3	Vertical	320	1.02	-
2412MHz	Pass	PK	4.824G	45.66	74.00	-28.34	2.48	3	Vertical	320	1.02	-
2437MHz	Pass	AV	2.3894G	46.62	54.00	-7.38	31.17	3	Horizontal	69	1.00	-
2437MHz	Pass	AV	2.4298G	93.88	Inf	-Inf	31.32	3	Horizontal	69	1.00	-
2437MHz	Pass	AV	2.4842G	47.27	54.00	-6.73	31.53	3	Horizontal	69	1.00	-
2437MHz	Pass	PK	2.367G	57.50	74.00	-16.50	31.08	3	Horizontal	69	1.00	-
2437MHz	Pass	PK	2.4302G	100.98	Inf	-Inf	31.32	3	Horizontal	69	1.00	-
2437MHz	Pass	PK	2.4862G	58.03	74.00	-15.97	31.54	3	Horizontal	69	1.00	-
2437MHz	Pass	AV	2.3646G	46.40	54.00	-7.60	31.07	3	Vertical	301	3.60	-
2437MHz	Pass	AV	2.4294G	91.17	Inf	-Inf	31.32	3	Vertical	301	3.60	-
2437MHz	Pass	AV	2.4946G	47.29	54.00	-6.71	31.57	3	Vertical	301	3.60	-
2437MHz	Pass	PK	2.3566G	57.49	74.00	-16.51	31.04	3	Vertical	301	3.60	-
2437MHz	Pass	PK	2.433G	98.99	Inf	-Inf	31.34	3	Vertical	301	3.60	-
2437MHz	Pass	PK	2.4838G	58.12	74.00	-15.88	31.53	3	Vertical	301	3.60	-
2437MHz	Pass	AV	4.874G	35.54	54.00	-18.46	2.55	3	Horizontal	320	1.14	-
2437MHz	Pass	AV	7.311G	38.99	54.00	-15.01	8.42	3	Horizontal	20	1.50	-
2437MHz	Pass	PK	4.874G	46.94	74.00	-27.06	2.55	3	Horizontal	320	1.14	-
2437MHz	Pass	PK	7.311G	50.67	74.00	-23.33	8.42	3	Horizontal	20	1.50	-
2437MHz	Pass	AV	4.874G	37.01	54.00	-16.99	2.55	3	Vertical	17	1.14	-
2437MHz	Pass	AV	7.311G	38.94	54.00	-15.06	8.42	3	Vertical	317	1.50	-
2437MHz	Pass	PK	4.874G	48.85	74.00	-25.15	2.55	3	Vertical	17	1.14	-
2437MHz	Pass	PK	7.311G	50.98	74.00	-23.02	8.42	3	Vertical	317	1.50	-
2462MHz	Pass	AV	2.46G	96.35	Inf	-Inf	31.44	3	Horizontal	61	1.01	-
2462MHz	Pass	AV	2.483502G	50.55	54.00	-3.45	31.53	3	Horizontal	61	1.01	-
2462MHz	Pass	PK	2.46G	102.96	Inf	-Inf	31.44	3	Horizontal	61	1.01	-
2462MHz	Pass	PK	2.483502G	61.12	74.00	-12.88	31.53	3	Horizontal	61	1.01	-
2462MHz	Pass	AV	2.4548G	93.78	Inf	-Inf	31.42	3	Vertical	301	3.57	-
2462MHz	Pass	AV	2.483502G	48.80	54.00	-5.20	31.53	3	Vertical	301	3.57	-
2462MHz	Pass	PK	2.4594G	100.89	Inf	-Inf	31.44	3	Vertical	301	3.57	-
2462MHz	Pass	PK	2.4966G	59.64	74.00	-14.36	31.58	3	Vertical	301	3.57	-
2462MHz	Pass	AV	4.924G	40.29	54.00	-13.71	2.63	3	Horizontal	53	1.04	-
2462MHz	Pass	AV	7.386G	41.10	54.00	-12.90	8.51	3	Horizontal	253	1.50	-
2462MHz	Pass	PK	4.924G	51.85	74.00	-22.15	2.63	3	Horizontal	53	1.04	-
2462MHz	Pass	PK	7.386G	50.75	74.00	-23.25	8.51	3	Horizontal	253	1.50	-
2462MHz	Pass	AV	4.924G	40.49	54.00	-13.51	2.63	3	Vertical	9	3.51	-
2462MHz	Pass	AV	7.386G	39.22	54.00	-14.78	8.51	3	Vertical	219	1.50	-
2462MHz	Pass	PK	4.924G	51.86	74.00	-22.14	2.63	3	Vertical	9	3.51	-

Mode	Result	Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
2462MHz	Pass	PK	7.386G	50.55	74.00	-23.45	8.51	3	Vertical	219	1.50	-
802.11n HT20_Nss1,(MCS0)_2TX	-	-	-	-	-	-	-	-	-	-	-	-
2412MHz	Pass	AV	2.39G	52.61	54.00	-1.39	31.17	3	Horizontal	60	1.01	-
2412MHz	Pass	AV	2.416G	95.40	Inf	-Inf	31.27	3	Horizontal	60	1.01	-
2412MHz	Pass	PK	2.3896G	65.79	74.00	-8.21	31.17	3	Horizontal	60	1.01	-
2412MHz	Pass	PK	2.4158G	103.12	Inf	-Inf	31.27	3	Horizontal	60	1.01	-
2412MHz	Pass	AV	2.39G	50.82	54.00	-3.18	31.17	3	Vertical	316	3.69	-
2412MHz	Pass	AV	2.416G	91.83	Inf	-Inf	31.27	3	Vertical	316	3.69	-
2412MHz	Pass	PK	2.3894G	62.64	74.00	-11.36	31.17	3	Vertical	316	3.69	-
2412MHz	Pass	PK	2.4146G	99.49	Inf	-Inf	31.27	3	Vertical	316	3.69	-
2412MHz	Pass	AV	4.824G	37.66	54.00	-16.34	2.48	3	Horizontal	40	1.01	-
2412MHz	Pass	PK	4.824G	48.41	74.00	-25.59	2.48	3	Horizontal	40	1.01	-
2412MHz	Pass	AV	4.824G	37.20	54.00	-16.80	2.48	3	Vertical	355	3.67	-
2412MHz	Pass	PK	4.824G	47.94	74.00	-26.06	2.48	3	Vertical	355	3.67	-
2437MHz	Pass	AV	2.3878G	46.49	54.00	-7.51	31.16	3	Horizontal	55	1.08	-
2437MHz	Pass	AV	2.4306G	92.42	Inf	-Inf	31.33	3	Horizontal	55	1.08	-
2437MHz	Pass	AV	2.491G	47.05	54.00	-6.95	31.56	3	Horizontal	55	1.08	-
2437MHz	Pass	PK	2.3818G	57.98	74.00	-16.02	31.14	3	Horizontal	55	1.08	-
2437MHz	Pass	PK	2.431G	99.77	Inf	-Inf	31.33	3	Horizontal	55	1.08	-
2437MHz	Pass	PK	2.4866G	58.11	74.00	-15.89	31.54	3	Horizontal	55	1.08	-
2437MHz	Pass	AV	2.389G	46.45	54.00	-7.55	31.17	3	Vertical	317	3.69	-
2437MHz	Pass	AV	2.4306G	88.58	Inf	-Inf	31.33	3	Vertical	317	3.69	-
2437MHz	Pass	AV	2.4966G	47.12	54.00	-6.88	31.58	3	Vertical	317	3.69	-
2437MHz	Pass	PK	2.3622G	57.50	74.00	-16.50	31.06	3	Vertical	317	3.69	-
2437MHz	Pass	PK	2.4306G	96.65	Inf	-Inf	31.33	3	Vertical	317	3.69	-
2437MHz	Pass	PK	2.4922G	57.70	74.00	-16.30	31.56	3	Vertical	317	3.69	-
2437MHz	Pass	AV	4.874G	34.35	54.00	-19.65	2.55	3	Horizontal	323	1.06	-
2437MHz	Pass	AV	7.311G	39.12	54.00	-14.88	8.42	3	Horizontal	23	1.50	-
2437MHz	Pass	PK	4.874G	46.12	74.00	-27.88	2.55	3	Horizontal	323	1.06	-
2437MHz	Pass	PK	7.311G	50.52	74.00	-23.48	8.42	3	Horizontal	23	1.50	-
2437MHz	Pass	AV	4.874G	35.56	54.00	-18.44	2.55	3	Vertical	10	1.33	-
2437MHz	Pass	AV	7.311G	39.09	54.00	-14.91	8.42	3	Vertical	310	1.50	-
2437MHz	Pass	PK	4.874G	46.63	74.00	-27.37	2.55	3	Vertical	10	1.33	-
2437MHz	Pass	PK	7.311G	51.32	74.00	-22.68	8.42	3	Vertical	310	1.50	-
2462MHz	Pass	AV	2.4562G	95.14	Inf	-Inf	31.42	3	Horizontal	57	1.01	-
2462MHz	Pass	AV	2.483502G	51.97	54.00	-2.03	31.53	3	Horizontal	57	1.01	-
2462MHz	Pass	PK	2.4586G	102.85	Inf	-Inf	31.43	3	Horizontal	57	1.01	-
2462MHz	Pass	PK	2.483502G	62.46	74.00	-11.54	31.53	3	Horizontal	57	1.01	-
2462MHz	Pass	AV	2.4562G	90.32	Inf	-Inf	31.42	3	Vertical	316	3.56	-
2462MHz	Pass	AV	2.483502G	49.68	54.00	-4.32	31.53	3	Vertical	316	3.56	-
2462MHz	Pass	PK	2.4562G	98.29	Inf	-Inf	31.42	3	Vertical	316	3.56	-
2462MHz	Pass	PK	2.485G	60.31	74.00	-13.69	31.53	3	Vertical	316	3.56	-
2462MHz	Pass	AV	4.924G	39.98	54.00	-14.02	2.63	3	Horizontal	54	1.00	-
2462MHz	Pass	AV	7.386G	39.10	54.00	-14.90	8.51	3	Horizontal	254	1.50	-
2462MHz	Pass	PK	4.924G	51.62	74.00	-22.38	2.63	3	Horizontal	54	1.00	-
2462MHz	Pass	PK	7.386G	50.87	74.00	-23.13	8.51	3	Horizontal	254	1.50	-
2462MHz	Pass	AV	4.924G	39.52	54.00	-14.48	2.63	3	Vertical	359	2.50	-
2462MHz	Pass	AV	7.386G	39.24	54.00	-14.76	8.51	3	Vertical	59	1.50	-
2462MHz	Pass	PK	4.924G	51.22	74.00	-22.78	2.63	3	Vertical	359	2.50	-

Mode	Result	Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
2462MHz	Pass	PK	7.386G	51.04	74.00	-22.96	8.51	3	Vertical	59	1.50	-

802.11b_(1Mbps)_2TX

2412MHz_TX




EUT = Y

Type	Freq	Level	Limit	Margin	Factor	Dist	Condition	Azimuth	Height	Comments	Raw	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dB)	(m)		(°)	(m)		(dBuV)	(dB)	(dB)	(dB)
AV	2.3872G	44.85	54.00	-9.15	30.93	3	Vertical	322	1.43	-	13.93	27.31	3.62	-
AV	2.4104G	91.29	Inf	-Inf	31.01	3	Vertical	322	1.43	-	60.29	27.37	3.64	-
PK	2.3874G	55.33	74.00	-18.67	30.93	3	Vertical	322	1.43	-	24.41	27.31	3.62	-
PK	2.4112G	94.87	Inf	-Inf	31.01	3	Vertical	322	1.43	-	63.86	27.37	3.64	-

802.11b_(1Mbps)_2TX

2412MHz_TX




EUT = Y

Type	Freq	Level	Limit	Margin	Factor	Dist	Condition	Azimuth	Height	Comments	Raw	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dB)	(m)		(°)	(m)		(dBuV)	(dB)	(dB)	(dB)
AV	2.3874G	47.91	54.00	-6.09	30.93	3	Horizontal	342	1.16	-	16.98	27.31	3.62	-
AV	2.4138G	97.69	Inf	-Inf	31.02	3	Horizontal	342	1.16	-	66.67	27.38	3.64	-
PK	2.3874G	57.00	74.00	-17.00	30.93	3	Horizontal	342	1.16	-	26.07	27.31	3.62	-
PK	2.413G	101.58	Inf	-Inf	31.02	3	Horizontal	342	1.16	-	70.56	27.37	3.64	-

802.11b_(1Mbps)_2TX

2412MHz_TX




EUT = Y

Type	Freq	Level	Limit	Margin	Factor	Dist	Condition	Azimuth	Height	Comments	Raw	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dB)	(m)		(°)	(m)		(dBuV)	(dB)	(dB)	(dB)
AV	4.824G	50.98	54.00	-3.02	2.48	3	Vertical	319	2.72	-	48.50	31.22	6.44	35.18
PK	4.824G	52.70	74.00	-21.30	2.48	3	Vertical	319	2.72	-	50.22	31.22	6.44	35.18

802.11b_(1Mbps)_2TX

2412MHz_TX




EUT = Y

Type	Freq	Level	Limit	Margin	Factor	Dist	Condition	Azimuth	Height	Comments	Raw	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dB)	(m)		(°)	(m)		(dBuV)	(dB)	(dB)	(dB)
AV	4.824G	49.48	54.00	-4.52	2.48	3	Horizontal	330	2.16	-	47.00	31.22	6.44	35.18
PK	4.824G	52.03	74.00	-21.97	2.48	3	Horizontal	330	2.16	-	49.55	31.22	6.44	35.18

802.11b_(1Mbps)_2TX

2437MHz_TX




EUT = Y

Type	Freq	Level	Limit	Margin	Factor	Dist	Condition	Azimuth	Height	Comments	Raw	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dB)	(m)		(°)	(m)		(dBuV)	(dB)	(dB)	(dB)
AV	2.3794G	43.88	54.00	-10.12	31.13	3	Vertical	255	3.35	-	12.75	26.96	4.17	-
AV	2.4358G	88.33	Inf	-Inf	31.35	3	Vertical	255	3.35	-	56.99	27.12	4.23	-
AV	2.4846G	44.75	54.00	-9.25	31.53	3	Vertical	255	3.35	-	13.22	27.26	4.27	-
PK	2.3862G	57.52	74.00	-16.48	31.16	3	Vertical	255	3.35	-	26.36	26.98	4.17	-
PK	2.437G	91.55	Inf	-Inf	31.35	3	Vertical	255	3.35	-	60.20	27.12	4.23	-
PK	2.4978G	57.27	74.00	-16.73	31.58	3	Vertical	255	3.35	-	25.69	27.29	4.29	-

802.11b_(1Mbps)_2TX

2437MHz_TX




EUT = Y

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments	Raw (dBuV)	AF (dB)	CL (dB)	PA (dB)
AV	2.365G	43.94	54.00	-10.06	31.07	3	Horizontal	40	1.12	-	12.87	26.92	4.15	-
AV	2.4358G	88.85	Inf	-Inf	31.35	3	Horizontal	40	1.12	-	57.50	27.12	4.23	-
AV	2.4978G	44.74	54.00	-9.26	31.58	3	Horizontal	40	1.12	-	13.16	27.29	4.29	-
PK	2.3814G	57.08	74.00	-16.92	31.14	3	Horizontal	40	1.12	-	25.94	26.97	4.17	-
PK	2.4362G	92.00	Inf	-Inf	31.35	3	Horizontal	40	1.12	-	60.65	27.12	4.23	-
PK	2.4966G	58.08	74.00	-15.92	31.58	3	Horizontal	40	1.12	-	26.50	27.29	4.29	-

802.11b_(1Mbps)_2TX

2437MHz_TX




EUT = Y

Type	Freq	Level	Limit	Margin	Factor	Dist	Condition	Azimuth	Height	Comments	Raw	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dB)	(m)		(°)	(m)		(dBuV)	(dB)	(dB)	(dB)
AV	4.874G	46.19	54.00	-7.81	2.32	3	Vertical	15	2.41	-	43.87	31.37	5.46	34.52
AV	7.311G	36.13	54.00	-17.87	7.60	3	Vertical	268	1.50	-	28.53	35.81	6.63	34.84
PK	4.874G	50.63	74.00	-23.37	2.32	3	Vertical	15	2.41	-	48.31	31.37	5.46	34.52
PK	7.311G	49.79	74.00	-24.21	7.60	3	Vertical	268	1.50	-	42.20	35.81	6.63	34.84

802.11b_(1Mbps)_2TX

2437MHz_TX




EUT = Y

Type	Freq	Level	Limit	Margin	Factor	Dist	Condition	Azimuth	Height	Comments	Raw	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dB)	(m)		(°)	(m)		(dBuV)	(dB)	(dB)	(dB)
AV	4.874G	45.19	54.00	-8.81	2.55	3	Horizontal	324	1.04	-	42.63	31.30	6.45	35.19
AV	7.311G	36.28	54.00	-17.72	8.42	3	Horizontal	0	1.50	-	27.86	36.01	7.69	35.27
PK	4.874G	49.81	74.00	-24.19	2.55	3	Horizontal	324	1.04	-	47.26	31.30	6.45	35.19
PK	7.311G	51.15	74.00	-22.85	8.42	3	Horizontal	0	1.50	-	42.73	36.01	7.69	35.27

802.11b_(1Mbps)_2TX

2462MHz_TX




EUT = Y

Type	Freq	Level	Limit	Margin	Factor	Dist	Condition	Azimuth	Height	Comments	Raw	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dB)	(m)		(°)	(m)		(dBuV)	(dB)	(dB)	(dB)
AV	2.461G	93.53	Inf	-Inf	31.44	3	Vertical	57	3.69	-	62.09	27.19	4.25	-
AV	2.5G	44.59	54.00	-9.41	31.59	3	Vertical	57	3.69	-	13.00	27.30	4.29	-
PK	2.4606G	96.82	Inf	-Inf	31.44	3	Vertical	57	3.69	-	65.38	27.19	4.25	-
PK	2.5G	56.06	74.00	-17.94	31.59	3	Vertical	57	3.69	-	24.47	27.30	4.29	-

802.11b_(1Mbps)_2TX

2462MHz_TX




EUT = Y

Type	Freq	Level	Limit	Margin	Factor	Dist	Condition	Azimuth	Height	Comments	Raw	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dB)	(m)		(°)	(m)		(dBuV)	(dB)	(dB)	(dB)
AV	2.4608G	95.52	Inf	-Inf	31.44	3	Horizontal	301	1.01	-	64.08	27.19	4.25	-
AV	2.5G	44.59	54.00	-9.41	31.59	3	Horizontal	301	1.01	-	13.00	27.30	4.29	-
PK	2.4606G	98.51	Inf	-Inf	31.44	3	Horizontal	301	1.01	-	67.07	27.19	4.25	-
PK	2.5G	57.67	74.00	-16.33	31.59	3	Horizontal	301	1.01	-	26.08	27.30	4.29	-

802.11b_(1Mbps)_2TX

2462MHz_TX




EUT = Y

Type	Freq	Level	Limit	Margin	Factor	Dist	Condition	Azimuth	Height	Comments	Raw	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dB)	(m)		(°)	(m)		(dBuV)	(dB)	(dB)	(dB)
AV	4.924G	53.26	54.00	-0.74	2.63	3	Vertical	10	2.34	-	50.63	31.38	6.45	35.20
AV	7.386G	45.51	54.00	-8.49	8.51	3	Vertical	15	1.50	-	37.00	36.20	7.61	35.30
PK	4.924G	55.63	74.00	-18.37	2.63	3	Vertical	10	2.34	-	53.00	31.38	6.45	35.20
PK	7.386G	52.71	74.00	-21.29	8.51	3	Vertical	15	1.50	-	44.20	36.20	7.61	35.30

802.11b_(1Mbps)_2TX

2462MHz_TX




EUT = Y

Type	Freq	Level	Limit	Margin	Factor	Dist	Condition	Azimuth	Height	Comments	Raw	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dB)	(m)		(°)	(m)		(dBuV)	(dB)	(dB)	(dB)
AV	4.924G	51.13	54.00	-2.87	2.63	3	Horizontal	66	2.47	-	48.50	31.38	6.45	35.20
AV	7.386G	42.51	54.00	-11.49	8.51	3	Horizontal	84	1.38	-	34.00	36.20	7.61	35.30
PK	4.924G	54.13	74.00	-19.87	2.63	3	Horizontal	66	2.47	-	51.50	31.38	6.45	35.20
PK	7.386G	52.31	74.00	-21.69	8.51	3	Horizontal	84	1.38	-	43.80	36.20	7.61	35.30

802.11g_(6Mbps)_2TX

2412MHz_TX




EUT = Y

Type	Freq	Level	Limit	Margin	Factor	Dist	Condition	Azimuth	Height	Comments	Raw	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dB)	(m)		(°)	(m)		(dBuV)	(dB)	(dB)	(dB)
AV	2.3898G	51.72	54.00	-2.28	31.17	3	Vertical	304	3.69	-	20.55	26.99	4.18	-
AV	2.4146G	94.42	Inf	-Inf	31.27	3	Vertical	304	3.69	-	63.15	27.06	4.20	-
PK	2.3882G	63.32	74.00	-10.68	31.16	3	Vertical	304	3.69	-	32.16	26.99	4.18	-
PK	2.4144G	102.34	Inf	-Inf	31.26	3	Vertical	304	3.69	-	71.07	27.06	4.20	-

802.11g_(6Mbps)_2TX

2412MHz_TX




EUT = Y

Type	Freq	Level	Limit	Margin	Factor	Dist	Condition	Azimuth	Height	Comments	Raw	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dB)	(m)		(°)	(m)		(dBuV)	(dB)	(dB)	(dB)
AV	2.39G	53.65	54.00	-0.35	31.17	3	Horizontal	3	1.04	-	22.48	26.99	4.18	-
AV	2.416G	97.29	Inf	-Inf	31.27	3	Horizontal	3	1.04	-	66.02	27.06	4.21	-
PK	2.3898G	66.05	74.00	-7.95	31.17	3	Horizontal	3	1.04	-	34.88	26.99	4.18	-
PK	2.4158G	104.55	Inf	-Inf	31.27	3	Horizontal	3	1.04	-	73.28	27.06	4.21	-

802.11g_(6Mbps)_2TX

2412MHz_TX




EUT = Y

Type	Freq	Level	Limit	Margin	Factor	Dist	Condition	Azimuth	Height	Comments	Raw	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dB)	(m)		(°)	(m)		(dBuV)	(dB)	(dB)	(dB)
AV	4.824G	37.25	54.00	-16.75	2.48	3	Vertical	320	1.02	-	34.76	31.22	6.44	35.18
PK	4.824G	45.66	74.00	-28.34	2.48	3	Vertical	320	1.02	-	43.17	31.22	6.44	35.18

802.11g_(6Mbps)_2TX

2412MHz_TX




EUT = Y

Type	Freq	Level	Limit	Margin	Factor	Dist	Condition	Azimuth	Height	Comments	Raw	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dB)	(m)		(°)	(m)		(dBuV)	(dB)	(dB)	(dB)
AV	4.824G	39.20	54.00	-14.80	2.16	3	Horizontal	57	1.01	-	37.03	31.28	5.41	34.53
PK	4.824G	50.32	74.00	-23.68	2.16	3	Horizontal	57	1.01	-	48.16	31.28	5.41	34.53

802.11g_(6Mbps)_2TX

2437MHz_TX




EUT = Y

Type	Freq	Level	Limit	Margin	Factor	Dist	Condition	Azimuth	Height	Comments	Raw	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dB)	(m)		(°)	(m)		(dBuV)	(dB)	(dB)	(dB)
AV	2.3646G	46.40	54.00	-7.60	31.07	3	Vertical	301	3.60	-	15.33	26.92	4.15	-
AV	2.4294G	91.17	Inf	-Inf	31.32	3	Vertical	301	3.60	-	59.84	27.10	4.22	-
AV	2.4946G	47.29	54.00	-6.71	31.57	3	Vertical	301	3.60	-	15.72	27.28	4.28	-
PK	2.3566G	57.49	74.00	-16.51	31.04	3	Vertical	301	3.60	-	26.45	26.90	4.14	-
PK	2.433G	98.99	Inf	-Inf	31.34	3	Vertical	301	3.60	-	67.66	27.11	4.22	-
PK	2.4838G	58.12	74.00	-15.88	31.53	3	Vertical	301	3.60	-	26.59	27.25	4.27	-

802.11g_(6Mbps)_2TX

2437MHz_TX




EUT = Y

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments	Raw (dBuV)	AF (dB)	CL (dB)	PA (dB)
AV	2.3894G	46.62	54.00	-7.38	31.17	3	Horizontal	69	1.00	-	15.45	26.99	4.18	-
AV	2.4298G	93.88	Inf	-Inf	31.32	3	Horizontal	69	1.00	-	62.55	27.10	4.22	-
AV	2.4842G	47.27	54.00	-6.73	31.53	3	Horizontal	69	1.00	-	15.74	27.26	4.27	-
PK	2.367G	57.50	74.00	-16.50	31.08	3	Horizontal	69	1.00	-	26.42	26.93	4.15	-
PK	2.4302G	100.98	Inf	-Inf	31.32	3	Horizontal	69	1.00	-	69.65	27.10	4.22	-
PK	2.4862G	58.03	74.00	-15.97	31.54	3	Horizontal	69	1.00	-	26.49	27.26	4.28	-

802.11g_(6Mbps)_2TX

2437MHz_TX




EUT = Y

Type	Freq	Level	Limit	Margin	Factor	Dist	Condition	Azimuth	Height	Comments	Raw	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dB)	(m)		(°)	(m)		(dBuV)	(dB)	(dB)	(dB)
AV	4.874G	37.01	54.00	-16.99	2.55	3	Vertical	17	1.14	-	34.46	31.30	6.45	35.19
AV	7.311G	38.94	54.00	-15.06	8.42	3	Vertical	317	1.50	-	30.52	36.01	7.69	35.27
PK	4.874G	48.85	74.00	-25.15	2.55	3	Vertical	17	1.14	-	46.30	31.30	6.45	35.19
PK	7.311G	50.98	74.00	-23.02	8.42	3	Vertical	317	1.50	-	42.56	36.01	7.69	35.27

802.11g_(6Mbps)_2TX

2437MHz_TX




EUT = Y

Type	Freq	Level	Limit	Margin	Factor	Dist	Condition	Azimuth	Height	Comments	Raw	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dB)	(m)		(°)	(m)		(dBuV)	(dB)	(dB)	(dB)
AV	4.874G	35.54	54.00	-18.46	2.55	3	Horizontal	320	1.14	-	32.99	31.30	6.45	35.19
AV	7.311G	38.99	54.00	-15.01	8.42	3	Horizontal	20	1.50	-	30.57	36.01	7.69	35.27
PK	4.874G	46.94	74.00	-27.06	2.55	3	Horizontal	320	1.14	-	44.39	31.30	6.45	35.19
PK	7.311G	50.67	74.00	-23.33	8.42	3	Horizontal	20	1.50	-	42.24	36.01	7.69	35.27

802.11g_(6Mbps)_2TX

2462MHz_TX




EUT = Y

Type	Freq	Level	Limit	Margin	Factor	Dist	Condition	Azimuth	Height	Comments	Raw	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dB)	(m)		(°)	(m)		(dBuV)	(dB)	(dB)	(dB)
AV	2.4548G	93.78	Inf	-Inf	31.42	3	Vertical	301	3.57	-	62.36	27.17	4.24	-
AV	2.483502G	48.80	54.00	-5.20	31.53	3	Vertical	301	3.57	-	17.27	27.25	4.27	-
PK	2.4594G	100.89	Inf	-Inf	31.44	3	Vertical	301	3.57	-	69.46	27.19	4.25	-
PK	2.4966G	59.64	74.00	-14.36	31.58	3	Vertical	301	3.57	-	28.06	27.29	4.29	-

802.11g_(6Mbps)_2TX

2462MHz_TX




EUT = Y

Type	Freq	Level	Limit	Margin	Factor	Dist	Condition	Azimuth	Height	Comments	Raw	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dB)	(m)		(°)	(m)		(dBuV)	(dB)	(dB)	(dB)
AV	2.46G	96.35	Inf	-Inf	31.44	3	Horizontal	61	1.01	-	64.91	27.19	4.25	-
AV	2.483502G	50.55	54.00	-3.45	31.53	3	Horizontal	61	1.01	-	19.03	27.25	4.27	-
PK	2.46G	102.96	Inf	-Inf	31.44	3	Horizontal	61	1.01	-	71.52	27.19	4.25	-
PK	2.483502G	61.12	74.00	-12.88	31.53	3	Horizontal	61	1.01	-	29.60	27.25	4.27	-

802.11g_(6Mbps)_2TX

2462MHz_TX




EUT = Y

Type	Freq	Level	Limit	Margin	Factor	Dist	Condition	Azimuth	Height	Comments	Raw	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dB)	(m)		(°)	(m)		(dBuV)	(dB)	(dB)	(dB)
AV	4.924G	40.49	54.00	-13.51	2.63	3	Vertical	9	3.51	-	37.86	31.38	6.45	35.20
AV	7.386G	39.22	54.00	-14.78	8.51	3	Vertical	219	1.50	-	30.70	36.20	7.61	35.30
PK	4.924G	51.86	74.00	-22.14	2.63	3	Vertical	9	3.51	-	49.23	31.38	6.45	35.20
PK	7.386G	50.55	74.00	-23.45	8.51	3	Vertical	219	1.50	-	42.03	36.20	7.61	35.30

802.11g_(6Mbps)_2TX

2462MHz_TX




EUT = Y

Type	Freq	Level	Limit	Margin	Factor	Dist	Condition	Azimuth	Height	Comments	Raw	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dB)	(m)		(°)	(m)		(dBuV)	(dB)	(dB)	(dB)
AV	4.924G	40.29	54.00	-13.71	2.63	3	Horizontal	53	1.04	-	37.66	31.38	6.45	35.20
AV	7.386G	41.10	54.00	-12.90	8.51	3	Horizontal	253	1.50	-	32.59	36.20	7.61	35.30
PK	4.924G	51.85	74.00	-22.15	2.63	3	Horizontal	53	1.04	-	49.22	31.38	6.45	35.20
PK	7.386G	50.75	74.00	-23.25	8.51	3	Horizontal	253	1.50	-	42.23	36.20	7.61	35.30

802.11n HT20_Nss1,(MCS0)_2TX

2412MHz_TX




EUT = Y

Type	Freq	Level	Limit	Margin	Factor	Dist	Condition	Azimuth	Height	Comments	Raw	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dB)	(m)		(°)	(m)		(dBuV)	(dB)	(dB)	(dB)
AV	2.39G	50.82	54.00	-3.18	31.17	3	Vertical	316	3.69	-	19.65	26.99	4.18	-
AV	2.416G	91.83	Inf	-Inf	31.27	3	Vertical	316	3.69	-	60.56	27.06	4.21	-
PK	2.3894G	62.64	74.00	-11.36	31.17	3	Vertical	316	3.69	-	31.47	26.99	4.18	-
PK	2.4146G	99.49	Inf	-Inf	31.27	3	Vertical	316	3.69	-	68.22	27.06	4.20	-

802.11n HT20_Nss1,(MCS0)_2TX

2412MHz_TX




EUT = Y

Type	Freq	Level	Limit	Margin	Factor	Dist	Condition	Azimuth	Height	Comments	Raw	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dB)	(m)		(°)	(m)		(dBuV)	(dB)	(dB)	(dB)
AV	2.39G	52.61	54.00	-1.39	31.17	3	Horizontal	60	1.01	-	21.44	26.99	4.18	-
AV	2.416G	95.40	Inf	-Inf	31.27	3	Horizontal	60	1.01	-	64.13	27.06	4.21	-
PK	2.3896G	65.79	74.00	-8.21	31.17	3	Horizontal	60	1.01	-	34.62	26.99	4.18	-
PK	2.4158G	103.12	Inf	-Inf	31.27	3	Horizontal	60	1.01	-	71.85	27.06	4.21	-

802.11n HT20_Nss1,(MCS0)_2TX

2412MHz_TX




EUT = Y

Type	Freq	Level	Limit	Margin	Factor	Dist	Condition	Azimuth	Height	Comments	Raw	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dB)	(m)		(°)	(m)		(dBuV)	(dB)	(dB)	(dB)
AV	4.824G	37.20	54.00	-16.80	2.48	3	Vertical	355	3.67	-	34.72	31.22	6.44	35.18
PK	4.824G	47.94	74.00	-26.06	2.48	3	Vertical	355	3.67	-	45.46	31.22	6.44	35.18

802.11n HT20_Nss1,(MCS0)_2TX

2412MHz_TX




EUT = Y

Type	Freq	Level	Limit	Margin	Factor	Dist	Condition	Azimuth	Height	Comments	Raw	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dB)	(m)		(°)	(m)		(dBuV)	(dB)	(dB)	(dB)
AV	4.824G	37.66	54.00	-16.34	2.48	3	Horizontal	40	1.01	-	35.17	31.22	6.44	35.18
PK	4.824G	48.41	74.00	-25.59	2.48	3	Horizontal	40	1.01	-	45.92	31.22	6.44	35.18

802.11n HT20_Nss1,(MCS0)_2TX

2437MHz_TX




EUT = Y

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments	Raw (dBuV)	AF (dB)	CL (dB)	PA (dB)
AV	2.389G	46.45	54.00	-7.55	31.17	3	Vertical	317	3.69	-	15.28	26.99	4.18	-
AV	2.4306G	88.58	Inf	-Inf	31.33	3	Vertical	317	3.69	-	57.25	27.11	4.22	-
AV	2.4966G	47.12	54.00	-6.88	31.58	3	Vertical	317	3.69	-	15.54	27.29	4.29	-
PK	2.3622G	57.50	74.00	-16.50	31.06	3	Vertical	317	3.69	-	26.44	26.91	4.15	-
PK	2.4306G	96.65	Inf	-Inf	31.33	3	Vertical	317	3.69	-	65.32	27.11	4.22	-
PK	2.4922G	57.70	74.00	-16.30	31.56	3	Vertical	317	3.69	-	26.14	27.28	4.28	-

802.11n HT20_Nss1,(MCS0)_2TX

2437MHz_TX




EUT = Y

Type	Freq	Level	Limit	Margin	Factor	Dist	Condition	Azimuth	Height	Comments	Raw	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dB)	(m)		(°)	(m)		(dBuV)	(dB)	(dB)	(dB)
AV	2.3878G	46.49	54.00	-7.51	31.16	3	Horizontal	55	1.08	-	15.32	26.99	4.18	-
AV	2.4306G	92.42	Inf	-Inf	31.33	3	Horizontal	55	1.08	-	61.10	27.11	4.22	-
AV	2.491G	47.05	54.00	-6.95	31.56	3	Horizontal	55	1.08	-	15.50	27.27	4.28	-
PK	2.3818G	57.98	74.00	-16.02	31.14	3	Horizontal	55	1.08	-	26.84	26.97	4.17	-
PK	2.431G	99.77	Inf	-Inf	31.33	3	Horizontal	55	1.08	-	68.44	27.11	4.22	-
PK	2.4866G	58.11	74.00	-15.89	31.54	3	Horizontal	55	1.08	-	26.58	27.26	4.28	-

802.11n HT20_Nss1,(MCS0)_2TX

2437MHz_TX




EUT = Y

Type	Freq	Level	Limit	Margin	Factor	Dist	Condition	Azimuth	Height	Comments	Raw	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dB)	(m)		(°)	(m)		(dBuV)	(dB)	(dB)	(dB)
AV	4.874G	35.56	54.00	-18.44	2.55	3	Vertical	10	1.33	-	33.01	31.30	6.45	35.19
AV	7.311G	39.09	54.00	-14.91	8.42	3	Vertical	310	1.50	-	30.67	36.01	7.69	35.27
PK	4.874G	46.63	74.00	-27.37	2.55	3	Vertical	10	1.33	-	44.08	31.30	6.45	35.19
PK	7.311G	51.32	74.00	-22.68	8.42	3	Vertical	310	1.50	-	42.89	36.01	7.69	35.27

802.11n HT20_Nss1,(MCS0)_2TX

2437MHz_TX




EUT = Y

Type	Freq	Level	Limit	Margin	Factor	Dist	Condition	Azimuth	Height	Comments	Raw	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dB)	(m)		(°)	(m)		(dBuV)	(dB)	(dB)	(dB)
AV	4.874G	34.35	54.00	-19.65	2.55	3	Horizontal	323	1.06	-	31.80	31.30	6.45	35.19
AV	7.311G	39.12	54.00	-14.88	8.42	3	Horizontal	23	1.50	-	30.69	36.01	7.69	35.27
PK	4.874G	46.12	74.00	-27.88	2.55	3	Horizontal	323	1.06	-	43.56	31.30	6.45	35.19
PK	7.311G	50.52	74.00	-23.48	8.42	3	Horizontal	23	1.50	-	42.10	36.01	7.69	35.27

802.11n HT20_Nss1,(MCS0)_2TX

2462MHz_TX




EUT = Y

Type	Freq	Level	Limit	Margin	Factor	Dist	Condition	Azimuth	Height	Comments	Raw	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dB)	(m)		(°)	(m)		(dBuV)	(dB)	(dB)	(dB)
AV	2.4562G	90.32	Inf	-Inf	31.42	3	Vertical	316	3.56	-	58.90	27.18	4.25	-
AV	2.483502G	49.68	54.00	-4.32	31.53	3	Vertical	316	3.56	-	18.16	27.25	4.27	-
PK	2.4562G	98.29	Inf	-Inf	31.42	3	Vertical	316	3.56	-	66.86	27.18	4.25	-
PK	2.485G	60.31	74.00	-13.69	31.53	3	Vertical	316	3.56	-	28.78	27.26	4.28	-

802.11n HT20_Nss1,(MCS0)_2TX

2462MHz_TX




EUT = Y

Type	Freq	Level	Limit	Margin	Factor	Dist	Condition	Azimuth	Height	Comments	Raw	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dB)	(m)		(°)	(m)		(dBuV)	(dB)	(dB)	(dB)
AV	2.4562G	95.14	Inf	-Inf	31.42	3	Horizontal	57	1.01	-	63.72	27.18	4.25	-
AV	2.483502G	51.97	54.00	-2.03	31.53	3	Horizontal	57	1.01	-	20.44	27.25	4.27	-
PK	2.4586G	102.85	Inf	-Inf	31.43	3	Horizontal	57	1.01	-	71.42	27.18	4.25	-
PK	2.483502G	62.46	74.00	-11.54	31.53	3	Horizontal	57	1.01	-	30.93	27.25	4.27	-

802.11n HT20_Nss1,(MCS0)_2TX

2462MHz_TX




EUT = Y

Type	Freq	Level	Limit	Margin	Factor	Dist	Condition	Azimuth	Height	Comments	Raw	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dB)	(m)		(°)	(m)		(dBuV)	(dB)	(dB)	(dB)
AV	4.924G	39.52	54.00	-14.48	2.63	3	Vertical	359	2.50	-	36.90	31.38	6.45	35.20
AV	7.386G	39.24	54.00	-14.76	8.51	3	Vertical	59	1.50	-	30.72	36.20	7.61	35.30
PK	4.924G	51.22	74.00	-22.78	2.63	3	Vertical	359	2.50	-	48.59	31.38	6.45	35.20
PK	7.386G	51.04	74.00	-22.96	8.51	3	Vertical	59	1.50	-	42.53	36.20	7.61	35.30

802.11n HT20_Nss1,(MCS0)_2TX

2462MHz_TX



EUT = Y

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments	Raw (dBuV)	AF (dB)	CL (dB)	PA (dB)
AV	4.924G	39.98	54.00	-14.02	2.63	3	Horizontal	54	1.00	-	37.35	31.38	6.45	35.20
AV	7.386G	39.10	54.00	-14.90	8.51	3	Horizontal	254	1.50	-	30.59	36.20	7.61	35.30
PK	4.924G	51.62	74.00	-22.38	2.63	3	Horizontal	54	1.00	-	48.99	31.38	6.45	35.20
PK	7.386G	50.87	74.00	-23.13	8.51	3	Horizontal	254	1.50	-	42.36	36.20	7.61	35.30