

RF Exposure Evaluation Report

Product : uKit Robot
Trade mark : UBTECH
Model/Type reference : ERUB101, ERUwxyy
Product : uKit Robot
Report Number : EED32L00034203
FCC ID : 2AHJX-UKITERU
Date of Issue : Apr. 02, 2019
Test Standards : 47 CFR Part 1.1307
47 CFR Part 1.1310
KDB 447498 D01v06
Test result : PASS

Prepared for:

UBTECH ROBOTICS CORP LTD

**16th and 22nd Floor, Block C1, Nanshan I Park, No.1001 Xueyuan Road,
Nanshan District, Shenzhen City, P.R.CHINA**

Prepared by:

**Centre Testing International Group Co., Ltd.
Hongwei Industrial Zone, Bao'an 70 District,
Shenzhen, Guangdong, China**

TEL: +86-755-3368 3668

FAX: +86-755-3368 3385

Tested By:

Jay Zheng

Jay Zheng

Compiled by:

Kevin Lan

Kevin Lan

Reviewed by:

Ware Xin

Ware Xin

Approved by:

Kevin Yang

Kevin Yang

Date:

Apr. 02, 2019

Check No.: 3096316262



2 Version

| Version No. | Date | Description |
|-------------|---------------|-------------|
| 00 | Apr. 02, 2019 | Original |
| | | |
| | | |

3 Contents

| | Page |
|--|----------|
| 1 COVER PAGE..... | 1 |
| 2 VERSION..... | 2 |
| 3 CONTENTS..... | 3 |
| 4 GENERAL INFORMATION..... | 4 |
| 4.1 CLIENT INFORMATION..... | 4 |
| 4.2 GENERAL DESCRIPTION OF EUT..... | 4 |
| 4.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD..... | 4 |
| 4.4 TEST LOCATION..... | 5 |
| 4.5 DEVIATION FROM STANDARDS..... | 5 |
| 4.6 ABNORMALITIES FROM STANDARD CONDITIONS..... | 5 |
| 4.7 OTHER INFORMATION REQUESTED BY THE CUSTOMER..... | 5 |
| 5 RF EXPOSURE EVALUATION..... | 6 |
| 5.1 RF EXPOSURE COMPLIANCE REQUIREMENT..... | 6 |
| 5.1.1 Limits..... | 6 |
| 5.1.2 Test Procedure..... | 6 |
| 5.1.3 EUT RF Exposure Evaluation..... | 7 |
| PHOTOGRAPHS OF EUT CONSTRUCTIONAL DETAILS..... | 8 |

4 General Information

4.1 Client Information

| | |
|--------------------------|--|
| Applicant: | UBTECH ROBOTICS CORP LTD |
| Address of Applicant: | 16th and 22nd Floor, Block C1, Nanshan I Park, No.1001 Xueyuan Road, Nanshan District, Shenzhen City, P.R.CHINA |
| Manufacturer: | UBTECH ROBOTICS CORP LTD |
| Address of Manufacturer: | 16th and 22nd Floor, Block C1, Nanshan I Park, No.1001 Xueyuan Road, Nanshan District, Shenzhen City, P.R.CHINA |
| Factory: | UBTECH ROBOTICS CORP LTD BAOAN BRANCH |
| Address of Factory: | 1-2 Floor, B Block, Huilongda Industry Park, Shilongzai, Shiyan Street, Baoan District, Shenzhen City, P.R.CHINA |

4.2 General Description of EUT

| | |
|----------------------------------|--------------------------------|
| Product Name: | uKit Robot |
| Model No.: | ERUB101, ERUwxyy |
| Test Model No.: | ERUB101 |
| Trade mark: | UBTECH |
| EUT Supports Radios application: | BT 4.0 Dual mode, 2402-2480MHz |

4.3 Product Specification subjective to this standard

| | | |
|---|--|--|
| Frequency Range: | 2402-2480MHz | |
| Modulation Type: | GFSK, π/4DQPSK, 8DPSK | |
| Hardware Version: | 1.5(manufacturer declare) | |
| Software Version: | 1.77(manufacturer declare) | |
| Test Power Grade: | N/A | |
| Test Software of EUT: | ISRT_V2.1.26.4392(manufacturer declare) | |
| Antenna Type: | PCB antenna | |
| Antenna Gain: | 1dBi | |
| Power Supply: | AC Adapter | Model: PS1012-096HIB100 Input: 100-240V~ 50/60Hz, 0.4A Output: 9.6V --- 1.0A |
| | Battery | Lithium-ion Ploymer Battery:1200mAh 7.4V |
| Conducted Peak Output Power: | -0.744dBm | |
| | The Conducted Peak Output Power data refer to the report EED32L00034201, EED32L00034202. | |
| Sample Received Date: | Feb. 28, 2019 | |
| Sample tested Date: | Mar. 13, 2019 to Mar. 28, 2019 | |
| Reamrk:The tested sample(s) and the sample information are provided by the client. Model No.: ERUB101, ERUwxyy Only the model ERUB101 was tested, ERUwxyy(" w "can be a-z, indicating the product version; "x" can be 0-9, indicating the product category; "y" can be 0-9, indicating the product attributes.).All models are identical in interior structure, electrical circuits and components, only different from model name and color. | | |

4.4 Test Location

All tests were performed at:

Centre Testing International Group Co., Ltd

Building C, Hongwei Industrial Park Block 70, Bao'an District, Shenzhen, China

Telephone: +86 (0) 755 33683668 Fax: +86 (0) 755 33683385

No tests were sub-contracted.

FCC Designation No.: CN1164

4.5 Deviation from Standards

None.

4.6 Abnormalities from Standard Conditions

None.

4.7 Other Information Requested by the Customer

None.

5 RF Exposure Evaluation

5.1 RF Exposure Compliance Requirement

5.1.1 Limits

According to FCC Part1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in part1.1307(b)

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

| Frequency range (MHz) | Electric field strength (V/m) | Magnetic field strength (A/m) | Power density (mW/cm ²) | Averaging time (minutes) |
|--|-------------------------------------|-------------------------------------|--|-----------------------------|
| (A) Limits for Occupational/Controlled Exposures | | | | |
| 0.3–3.0 | 614 | 1.63 | *(100) | 6 |
| 3.0–30 | 1842/f | 4.89/f | *(900/f ²) | 6 |
| 30–300 | 61.4 | 0.163 | 1.0 | 6 |
| 300–1500 | | | f/300 | 6 |
| 1500–100,000 | | | 5 | 6 |
| (B) Limits for General Population/Uncontrolled Exposure | | | | |
| 0.3–1.34 | 614 | 1.63 | *(100) | 30 |
| 1.34–30 | 824/f | 2.19/f | *(180/f ²) | 30 |
| 30–300 | 27.5 | 0.073 | 0.2 | 30 |
| 300–1500 | | | f/1500 | 30 |
| 1500–100,000 | | | 1.0 | 30 |

A rough estimation of the expected exposure in power flux density on a given point can be made with the following equation:

$$S = \frac{P \times G}{4 \times \pi \times R^2}$$

Where:

S = power density

P = power input to the antenna

G = numeric gain of the antenna in the direction of interest relative to an isotropic radiator

R= distance to the centre of radiation of the antenna

EIRP = P*G

The antenna of the product, under normal use condition is at least 20 cm away from the body of the user.

Warning statement to the user for keeping at least 20cm separation distance and the prohibition of operating to a person has been printed on the user's manual. Therefore, the S of the device is calculated with R=20cm, and if it is below the limit S, then we can conclude the device complies with the rules.

5.1.2 Test Procedure

Software provided by client enabled the EUT to transmit data at lowest, middle and highest channel individually.

Report No. : EED32L00034203

Page 7 of 8

5.1.3 EUT RF Exposure Evaluation

Antenna Gain: 1dBi

Output Power Into Antenna & RF Exposure Evaluation Distance:

| Channel | Frequency (MHz) | Max Conducted Peak Output Power(dBm) | Gain (dBi) | EIRP* (dBm) | EIRP (mW) | R (cm) | S (mW/cm ²) | Limit (mW/cm ²) | Result |
|---------|--------------------|--|---------------|----------------|--------------|-----------|----------------------------|--------------------------------|--------|
| Lowest | 2402 | -0.744 | 1 | 0.256 | 1.06 | 20 | 0.0002 | 1.0 | Pass |

Note: Refer to report No. EED32L00034201, EED32L00034202 for EUT test Max Conducted Peak Output Power value.

PHOTOGRAPHS OF EUT Constructional Details

Refer to Report No. EED32L00034201 for EUT external and internal photos.

*** End of Report ***

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of CTI, this report can't be reproduced except in full.