

No. 1 Workshop, M-10, Middle section, Science & Technology Park, Nanshan

District, Shenzhen, Guangdong, China 518057

Telephone: +86 (0) 755 2601 2053 Fax: +86 (0) 755 2671 0594 Email: ee.shenzhen@sgs.com

Report No.: SZEM160600451505

Page: 1 of 8

SAR Evaluation Report

Application No.:SZEM1606004515CR (GZEM1606003762CR)Applicant:Guangzhou Rayer Acoustic Technology Co.,LtdManufacturer:Guangzhou Rayer Acoustic Technology Co.,Ltd

1. Shenzhen Gaea Electronics Co., Ltd.

Factory: 2, Guangzhou Singulargold Electronics Co.Ltd

3, DAH DYI AUDIO EQUIPMENT CO., LTD.

Product Name: Wi-Fi Speaker

Model No.(EUT): WH52C

Add Model No.: WG13, WG13C, WH32C, WM12, SD50C

Trade Mark: SOUNIX, SEEWO 2AHKA-WGHM52C

Standards: 47 CFR Part 1.1307 (2015)

47 CFR Part 2.1093 (2015)

KDB447498D01 General RF Exposure Guidance v06

Date of Receipt: 2016-06-14

Date of Test: 2016-06-17 to 2016-06-27

Date of Issue: 2016-06-30

Test Result : PASS*

* In the configuration tested, the EUT complied with the standards specified above. Authorized Signature:



Jack Zhang EMC Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government. All test results in this report can be traceable to National or International Standards.



Report No.: SZEM160600451505

Page: 2 of 8

2 Version

Revision Record				
Version	Chapter	Date	Modifier	Remark
00		2016-06-30		Original

Authorized for issue by:		
Tested By	Brir Chen	2016-06-17
	(Bill Chen) /Project Engineer	Date
Prepared By	Iris Zhou	2016-06-30
	(Iris Zhou) /Clerk	Date
Checked By	Eric Fu	2016-06-30
	(Eric Fu) /Reviewer	Date



Report No.: SZEM160600451505

Page: 3 of 8

3 Contents

		Page
1	1 COVER PAGE	1
2	2 VERSION	2
3	3 CONTENTS	3
4		
	4.1 CLIENT INFORMATION	4
	4.2 GENERAL DESCRIPTION OF EUT	
	4.3 TEST LOCATION	
	4.4 TEST FACILITY	6
	4.5 DEVIATION FROM STANDARDS	6
	4.6 ABNORMALITIES FROM STANDARD CONDITIONS	6
	4.7 OTHER INFORMATION REQUESTED BY THE CUSTOMER	6
5	5 SAR EVALUATION	7
	5.1 RF Exposure Compliance Requirement	7
	5.1.1 Standard Requirement	7
	5.1.2 Limits	
	5.1.3 EUT RF Exposure	7-8



Report No.: SZEM160600451505

Page: 4 of 8

4 General Information

4.1 Client Information

Applicant:	Guangzhou Rayer Acoustic Technology Co.,Ltd
Address of Applicant:	520, 192 Kezhu Road, Guangzhou Science Park, Guangdong, China
Manufacturer:	Guangzhou Rayer Acoustic Technology Co.,Ltd
Address of Manufacturer:	520, 192 Kezhu Road, Guangzhou Science Park, Guangdong, China
Factory:	1, Shenzhen Gaea Electronics Co.,Ltd.
	2, Guangzhou Singulargold Electronics Co.Ltd
	3, DAH DYI AUDIO EQUIPMENT CO., LTD.
Address of Factory:	1, 2-3, Datian Xiaoqu, Tongfuyu Industrial Zone, Buyong, Shajingstreet, Baoan District, Shenzhen, Guangdong Province, China
	2, NO.6 Lianhuayan Road, Science park, Guangzhou, China
	3, JIN SAN JIAO IND. ZONE, SHI BU VILLAGE, LIAO BU TOWN, DONG GUAN CITY, GUANG DONG PROVINCE, CHINA

4.2 General Description of EUT

Product Name:	Wi-Fi Speaker
Model No.:	WH52C
Trade Mark:	SOUNIX, SEEWO
Operation Frequency:	IEEE 802.11b/g/n(HT20): 2412MHz to 2462MHz IEEE 802.11n(HT40): 2422MHz to 2452MHz
Channel Numbers:	IEEE 802.11b/g, IEEE 802.11n HT20: 11 Channels IEEE 802.11n HT40: 7 Channels
Channel Separation:	5MHz
Type of Modulation:	IEEE for 802.11b: DSSS(CCK,DQPSK,DBPSK) IEEE for 802.11g: OFDM(64QAM, 16QAM, QPSK, BPSK) IEEE for 802.11n(HT20 and HT40): OFDM (64QAM, 16QAM, QPSK,BPSK)
Sample Type:	Portable production
Antenna Type:	FPC
Antenna Gain:	2dBi
Power Supply	MODEL: PS30D180K1000UD INPUT: 100-240V 50/60Hz 800mA
	OUYPUT: 18.0V 1000Ma Battery: DC 11.1V 2200mAh DC11.1V 1300mAh
Test Voltage:	AC:120V 60Hz
Cable:	DC cable : 120cm Unshielded



Report No.: SZEM160600451505

Page: 5 of 8

Remark:

Model No.: WG13, WG13C, WH32C, WH52C, WM12, SD50C

Only the Model WH52C was tested fully, and the model WG13, WG13C, WH32C, WM12, SD50C was performed the Radiated Disturbance tests for discrepancy, since the electrical circuit design, layout, components used and internal wiring were identical for all above models. Only different on model number, color, speaker output power, appearance, size and internal construction.



Report No.: SZEM160600451505

Page: 6 of 8

4.3 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch E&E Lab

No. 1 Workshop, M-10, Middle section, Science & Technology Park, Shenzhen, Guangdong, China 518057

Telephone: +86 (0) 755 2601 2053 Fax: +86 (0) 755 2671 0594

No tests were sub-contracted.

4.4 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

• CNAS (No. CNAS L2929)

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

• A2LA (Certificate No. 3816.01)

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

VCCI

The 10m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-823, R-4188, T-1153 and C-2383 respectively.

• FCC - Registration No.: 556682

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No.: 556682.

Industry Canada (IC)

Two 3m Semi-anechoic chambers and the 10m Semi-anechoic chamber of SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab have been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-1, 4620C-2, 4620C-3.

4.5 Deviation from Standards

None.

4.6 Abnormalities from Standard Conditions

None.

4.7 Other Information Requested by the Customer

None.



Report No.: SZEM160600451505

Page: 7 of 8

5 SAR Evaluation

5.1 RF Exposure Compliance Requirement

5.1.1 Standard Requirement

According to KDB447498D01 General RF Exposure Guidance v06

4.3.1. Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

5.1.2 Limits

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] $\cdot [\sqrt{f(GHz)}] \le 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

f(GHz) is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation ¹⁷

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is \leq 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion

5.1.3 EUT RF Exposure



2;

Report No.: SZEM160600451505

Page: 8 of 8

The Max Conducted Average Output Power is 12.61dBm in highest channel (2.462GHz);

12.61dBm logarithmic terms convert to numeric result is nearly 18.239mW

According to the formula. calculate the EIRP test result:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] \cdot [$\sqrt{f(GHz)}$]

General RF Exposure = (18.239mW / 10 mm) x $\sqrt{2.462}$ GHz = 2.862 ① SAR requirement:

S = 3.0

(1) < (2).

So the SAR report is not required.

