RF Exposure Report

Report No.: SA181102E08

FCC ID: 2AHKM-CHITA

Test Model: CHITA

Received Date: Nov. 06, 2018

Test Date: Nov. 20, 2018

Issued Date: June 05, 2019

Applicant: Hitron Technologies Inc.

Address: No. 1-8,Li-Hsin 1st Rd.,Hsinchu Science Park, HSINCHU,30078,Taiwan

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch Hsin Chu Laboratory

Lab Address: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300, Taiwan R.O.C.

Test Location : E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300, Taiwan R.O.C.

FCC Registration / Designation Number: 723255 / TW2022

Table of Contents

Release Control Record

Issue No.	Description	Date Issued
SA181102E08	Original release.	June 05, 2019

1   Certificate of Conformity

Product:	Cable modem
Brand:	Hitron
Test Model:	CHITA
Sample Status:	ENGINEERING SAMPLE
Applicant:	Hitron Technologies Inc.
Test Date:	Nov. 20, 2018
Standards:	FCC Part 2 (Section 2.1091)
	KDB 447498 D01 General RF Exposure Guidance v06
	IEEE C95.1-1992

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by : _____ , **Date:** _____ June 05, 2019 _____

Claire Kuan / Specialist

Approved by : _____ , **Date:** _____ June 05, 2019 _____

May Chen / Manager

2   RF Exposure

2.1   Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm^2)	Average Time (minutes)
Limits For General Population / Uncontrolled Exposure				
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f^2)*	30
30-300	27.5	0.073	0.2	30
300-1500	…	…	f/1500	30
1500-100,000	…	…	1.0	30

f = Frequency in MHz ; *Plane-wave equivalent power density

2.2   MPE Calculation Formula

$$Pd = (Pout*G) / (4*pi*r^2)$$

where

Pd = power density in mW/cm^2

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

2.3   Classification

The antenna of this product, under normal use condition, is at least 36cm away from the body of the user. So, this device is classified as **Mobile Device**.

2.4 Antenna Gain

Antenna No.	Chain No.	Model	Antenna Net Gain(dBi)	Frequency range	Antenna Type	Connector Type	Cable Length (mm)
1	5G Chain 0	393000022328	3.32	5.15~5.85GHz	PCB	i-pex(MHF)	190
2	2G Chain 0	393000022428	2.61	2.4~2.4835GHz	PCB	i-pex(MHF)	71
	5G Chain 1		4.25	5.15~5.85GHz			
3	2G Chain 1	393000022528	3.25	2.4~2.4835GHz	PCB	i-pex(MHF)	61
	5G Chain 2		3.71	5.15~5.85GHz			
4	2G Chain 2	393000022628	3.54	2.4~2.4835GHz	PCB	i-pex(MHF)	75
	5G Chain 3		4.79	5.15~5.85GHz			

2.5 Calculation Result of Maximum Conducted Power

Operation Mode	Evaluation Frequency (MHz)	Max Power (mW)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm^2)	Limit (mW/cm^2)
WLAN 2.4GHz	2462	783.792	7.91	36	0.29743	1
WLAN 5GHz	5745	948.464	10.06	36	0.59048	1

Note:

2.4GHz: Directional gain = $10 \log[(10^{G0/20} + 10^{G1/20} + 10^{G2/20})^2 / 3]$ = 7.91dBi

5GHz: Directional gain = $10 \log[(10^{G0/20} + 10^{G1/20} + 10^{G2/20} + 10^{G3/20})^2 / 4]$ = 10.06dBi

Conclusion:

The formula of calculated the MPE is:

CPD1 / LPD1 + CPD2 / LPD2 + ……etc. < 1

CPD = Calculation power density

LPD = Limit of power density

WLAN 2.4GHz + WLAN 5GHz = 0.29743 / 1 + 0.59048 / 1 = 0.88791

Therefore the maximum calculations of above situations are less than the "1" limit.

--- END ---