




FCC RADIO TEST REPORT

FCC ID : 2AHKM-HIVE2200
Equipment : 2x2 DBCC WiFi Extender
Brand Name : hitron
Model Name : HIXE12AWR
Applicant : Hitron Technologies Inc.
No. 1-8, Li-Hsin 1st Rd. Hsinchu Science Park,
Hsinchu 30078, Taiwan
Manufacturer : Hitron Technologies Inc.
No. 1-8, Li-Hsin 1st Rd. Hsinchu Science Park,
Hsinchu 30078, Taiwan
Standard : 47 CFR FCC Part 15.247

The product was received on Jul. 25, 2018, and testing was started from Oct. 05, 2018 and completed on Oct. 31, 2018. We, SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.10-2013 and shown compliance with the applicable technical standards.

The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any agency of government.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.



Approved by: Sam Chen

SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory
No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)



Table of Contents

History of this test report.....	4
Summary of Test Result.....	5
1 General Description	6
1.1 Information.....	6
1.2 Testing Applied Standards	9
1.3 Testing Location Information	9
1.4 Measurement Uncertainty	9
2 Test Configuration of EUT	10
2.1 Test Channel Mode	10
2.2 The Worst Case Measurement Configuration.....	11
2.3 EUT Operation during Test	11
2.4 Accessories	11
2.5 Support Equipment.....	12
2.6 Test Setup Diagram	13
3 Transmitter Test Result	15
3.1 AC Power-line Conducted Emissions	15
3.2 20dB Bandwidth and Carrier Frequency Separation.....	17
3.3 Maximum Conducted Output Power	18
3.4 Number of Hopping Frequencies and Hopping Bandedge	19
3.5 Time of Occupancy (Dwell Time)	20
3.6 Emissions in Non-restricted Frequency Bands	21
3.7 Emissions in Restricted Frequency Bands.....	22
4 Test Equipment and Calibration Data	25
Appendix A. Test Results of AC Power-line Conducted Emissions	
Appendix B. Test Results of 20dB Bandwidth AND Carrier Frequency Separation	
Appendix C. Test Results of Maximum Conducted Output Power	
Appendix D. Test Results of Number of Hopping Frequencies and Hopping Bandedge	
Appendix E. Test Results of Time of Occupancy (Dwell Time)	
Appendix F. Test Results of Emissions in Non-restricted Frequency Bands	
Appendix G. Test Results of Emissions in Restricted Frequency Bands	



Appendix H. Test Photos

Photographs of EUT v01



TEL : 886-3-656-9065
FAX : 886-3-656-9085
Report Template No.: CB Ver1.0



Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
1.1.2	15.203	Antenna Requirement	PASS	-
3.1	15.207	AC Power-line Conducted Emissions	PASS	-
3.2	15.247(a)	20dB Bandwidth	PASS	-
3.2	15.247(a)	Carrier Frequency Separation	PASS	-
3.3	15.247(b)	Maximum Conducted Output Power	PASS	-
3.4	15.247(a)	Number of Hopping Frequencies and Hopping Band edge	PASS	-
3.5	15.247(a)	Time of Occupancy (Dwell Time)	PASS	-
3.6	15.247(d)	Emissions in Non-restricted Frequency Bands	PASS	-
3.7	15.247(d)	Emissions in Restricted Frequency Bands	PASS	-

Reviewed by: **Sam Chen**

Report Producer: **Viola Huang**



1 General Description

1.1 Information

1.1.1 RF General Information

Frequency Range (MHz)	Bluetooth Version	Ch. Frequency (MHz)	Channel Number
2400-2483.5	BR / EDR	2402-2480	0-78 [79]

Band	Mode	BWch (MHz)	Nant
2.4-2.4835GHz	BT-BR(1Mbps)	1	1TX
2.4-2.4835GHz	BT-EDR(2Mbps)	1	1TX
2.4-2.4835GHz	BT-EDR(3Mbps)	1	1TX

Note:

- ♦ Bluetooth BR uses a GFSK (1Mbps).
- ♦ Bluetooth EDR uses a combination of $\pi/4$ -DQPSK (2Mbps) and 8DPSK (3Mbps).
- ♦ Bluetooth BR/EDR uses as a system using FHSS modulation.
- ♦ BWch is the nominal channel bandwidth.
- ♦ Nss-Min is the minimum number of spatial streams.
- ♦ Nant is the number of outputs. e.g., 2(2, 3) means have 2 outputs for port 2 and port 3. 2 means have 2 outputs for port 1 and port 2.

**1.1.2 Antenna Information**

Ant.	Port	Brand	Model Name	P/N	Antenna Type	Connector	Gain (dBi)
1	1	Ethertronics	XE1v2	-	PCB Antenna	I-PEX	Note
2	2	Ethertronics	XE1v2	-	PCB Antenna	I-PEX	
3	1	PSA	-	RFECA3216060A1T	CERAMIC Antenna	N/A	

Note 1:

Ant.	Port	Gain (dBi)			
		WLAN 2.4G	WLAN 5G Band 1	WLAN 5G Band 4	BT
1	1	4.4	4.8	5.5	-
2	2	3.1	3.8	3.8	-
3	1	-	-	-	2.09

Note 2: The EUT has three antennas.

<For 2.4GHz Band>**For IEEE 802.11b/g/n mode (2TX/2RX)**

Port 1 and Port 2 can be used as transmitting/receiving antenna.

Port 1 and Port 2 could transmit/receive simultaneously.

<For 5GHz Band>**For IEEE 802.11a/n/ac mode (2TX/2RX)**

Port 1 and Port 2 can be used as transmitting/receiving antenna.

Port 1 and Port 2 could transmit/receive simultaneously.

<For Bluetooth>**For BT function (1TX/1RX)**

Only Port 1 can be used as transmitting/receiving antenna.

**1.1.3 Mode Test Duty Cycle**

Mode	DC	DCF(dB)	T(s)	VBW(Hz) $\geq 1/T$
BT-BR(1Mbps)	0.795	0.996	2.928m	1k
BT-EDR(2Mbps)	0.758	1.203	2.957m	1k
BT-EDR(3Mbps)	0.754	1.226	2.957m	1k

Note:

- ♦ DC is Duty Cycle.
- ♦ DCF is Duty Cycle Factor.

1.1.4 EUT Operational Condition

EUT Power Type	Internal power supply
Test Software Version	Telnet(v.25.1)

1.1.5 Table for EUT support type

Function	support type
AP Router	Master
Extender	Master + Slave
Mesh	Master + Slave



1.2 Testing Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR FCC Part 15
- ♦ FCC Public Notice DA 00-705

1.3 Testing Location Information

Testing Location				
<input type="checkbox"/>	HWA YA	ADD : No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)	TEL : 886-3-327-3456	FAX : 886-3-327-0973
<input checked="" type="checkbox"/>	JHUBEI	ADD : No.8, Lane 724, Bo-ai St., Jhubei City, HsinChu County 302, Taiwan, R.O.C.	TEL : 886-3-656-9065	FAX : 886-3-656-9085

Test Condition	Test Site No.	Test Engineer	Test Environment	Test Date
RF Conducted	TH01-CB	Paul Chen	25°C / 65%	Oct. 16, 2018~Oct. 22, 2018
Radiated below 1GHz	03CH01-CB	Welson Chen	22°C / 54%	Oct. 24, 2018
Radiated above 1GHz	03CH01-CB	Welson Chen	22°C / 54%	Oct. 16, 2018
AC Conduction	CO01-CB	GN Hou	23°C / 59%	Oct. 31, 2018

Test site Designation No. TW0006 with FCC.

Test site registered number IC 4086D with Industry Canada.

1.4 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2))

Test Items	Uncertainty	Remark
Conducted Emission (150kHz ~ 30MHz)	3.2 dB	Confidence levels of 95%
Radiated Emission (30MHz ~ 1,000MHz)	3.6 dB	Confidence levels of 95%
Radiated Emission (1GHz ~ 18GHz)	3.7 dB	Confidence levels of 95%
Radiated Emission (18GHz ~ 40GHz)	3.5 dB	Confidence levels of 95%
Conducted Emission	1.7 dB	Confidence levels of 95%
Output Power Measurement	1.33 dB	Confidence levels of 95%
Bandwidth Measurement	9.74×10^{-8}	Confidence levels of 95%



2 Test Configuration of EUT

2.1 Test Channel Mode

Mode	PowerSetting
BT-BR(1Mbps)	-
2402MHz	8
2440MHz	8
2480MHz	8
BT-EDR(2Mbps)	-
2402MHz	8
2440MHz	8
2480MHz	8
BT-EDR(3Mbps)	-
2402MHz	8
2440MHz	8
2480MHz	8

2.2 The Worst Case Measurement Configuration

The Worst Case Mode for Following Conformance Tests	
Tests Item	AC power-line conducted emissions
Condition	AC power-line conducted measurement for line and neutral
Operating Mode	1 CTX-BT

The Worst Case Mode for Following Conformance Tests	
Tests Item	20dB Bandwidth Carrier Frequency Separation Maximum Conducted Output Power Number of Hopping Frequencies Hopping Bandedge Time of Occupancy (Dwell Time) Emissions in Non-restricted Frequency Bands
Test Condition	Conducted measurement at transmit chains

The Worst Case Mode for Following Conformance Tests	
Tests Item	Emissions in Restricted Frequency Bands
Test Condition	Radiated measurement If EUT consist of multiple antenna assembly (multiple antenna are used in EUT regardless of spatial multiplexing MIMO configuration), the radiated test should be performed with highest antenna gain of each antenna type.
Operating Mode < 1GHz	The EUT was performed at Y axis and Z axis position for Radiated emission above 1GHz test, and the worst case was found at Y axis. So the measurement will follow this same test configuration.
1	CTX - EUT in Y axis-BT
Operating Mode > 1GHz	The EUT was performed at Y axis and Z axis position for Radiated emission test, and the worst case was found at Y axis. So the measurement will follow this same test configuration.
1	EUT in Y axis

Note: All the specification of test configurations and test modes were based on customer's request.

2.3 EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

2.4 Accessories

N/A



2.5 Support Equipment


For Test Site No: CO01-CB


N/A

For Test Site No: 03CH01-CB and TH01-CB

Support Equipment				
No.	Equipment	Brand Name	Model Name	FCC ID
1	NB	DELL	E4300	N/A

2.6 Test Setup Diagram



Test Setup Diagram - Radiated Test


Item	Connection	Shielded	Length
1	Power cable	No	1.5m
2	RJ-45 cable	No	10m



3 Transmitter Test Result

3.1 AC Power-line Conducted Emissions

3.1.1 AC Power-line Conducted Emissions Limit

AC Power-line Conducted Emissions Limit		
Frequency Emission (MHz)	Quasi-Peak	Average
0.15-0.5	66 - 56 *	56 - 46 *
0.5-5	56	46
5-30	60	50

Note 1: * Decreases with the logarithm of the frequency.


3.1.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.1.3 Test Procedures

Test Method
▪ Refer as ANSI C63.10-2013, clause 6.2 for AC power-line conducted emissions.

3.1.4 Test Setup



3.1.5 Test Result of AC Power-line Conducted Emissions

Refer as Appendix A

3.2 20dB Bandwidth and Carrier Frequency Separation

3.2.1 20dB Bandwidth and Carrier Frequency Separation Limit

20dB Bandwidth and Carrier Frequency Separation Limit for Frequency Hopping Systems	
▪ 902-928 MHz Band:	
	▪ $N \geq 50$ and $ChS \geq \text{MAX}$ (20 dB bandwidth, 25 kHz); 20 dB bandwidth \leq 250 kHz.
	▪ $50 > N \geq 25$ and $ChS \geq \text{MAX}$ (20 dB bandwidth, 25 kHz); 20 dB bandwidth $>$ 250 kHz.
▪ 2400-2483.5 MHz Band:	
	▪ $N \geq 75$ and $ChS \geq \text{MAX}$ (20 dB bandwidth, 25 kHz).
	▪ $75 > N \geq 15$ and $ChS \geq \text{MAX}$ (20 dB bandwidth 2/3, 25 kHz).
▪ 5725-5850 MHz Band:	
	▪ $N \geq 75$ and $ChS \geq \text{MAX}$ (20 dB bandwidth, 25 kHz); 20 dB bandwidth \leq 1 MHz.
N: Number of Hopping Frequencies; ChS: Hopping Channel Separation	


3.2.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.2.3 Test Procedures

Test Method
▪ Refer as ANSI C63.10-2013, clause 6.9.1 for 20 dB bandwidth measurement.
▪ Refer as ANSI C63.10-2013, clause 7.8.2 for carrier frequency separation measurement.

3.2.4 Test Setup



3.2.5 Test Result of 20dB Bandwidth

Refer as Appendix B

3.2.6 Test Result of Carrier Frequency Separation

Refer as Appendix B

3.3 Maximum Conducted Output Power

3.3.1 Maximum Conducted Output Power Limit

Maximum Conducted Output Power Limit	
▪ 902-928 MHz Band:	
	▪ $N \geq 50$; Power 30dBm; EIRP 36dBm
	▪ $50 > N \geq 25$; Power 24dBm; EIRP 30dBm
▪ 2400-2483.5 MHz Band:	
	▪ $N \geq 75$; Power 30dBm; EIRP 36dBm
	▪ $75 > N \geq 15$; Power 21dBm; EIRP 27dBm
▪ 5725-5850 MHz Band:	
	▪ $N \geq 75$; Power 30dBm; EIRP 36dBm
N: Number of Hopping Frequencies	


3.3.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.3.3 Test Procedures

Test Method
▪ Refer as ANSI C63.10-2013, clause 7.8.5 for output power measurement.

3.3.4 Test Setup



3.3.5 Test Result of Maximum Conducted Output Power

Refer as Appendix C

3.4 Number of Hopping Frequencies and Hopping Bandedge

3.4.1 Number of Hopping Frequencies Limit

Number of Hopping Frequencies Limit	
▪ 902-928 MHz Band:	
	▪ $N \geq 50$ and $ChS \geq MAX$ (20 dB bandwidth, 25 kHz); 20 dB bandwidth \leq 250 kHz.
	▪ $50 > N \geq 25$ and $ChS \geq MAX$ (20 dB bandwidth, 25 kHz); 20 dB bandwidth $>$ 250 kHz.
▪ 2400-2483.5 MHz Band:	
	▪ $N \geq 75$ and $ChS \geq MAX$ (20 dB bandwidth, 25 kHz).
	▪ $75 > N \geq 15$ and $ChS \geq MAX$ (20 dB bandwidth 2/3, 25 kHz).
▪ 5725-5850 MHz Band:	
	▪ $N \geq 75$ and $ChS \geq MAX$ (20 dB bandwidth, 25 kHz); 20 dB bandwidth \leq 1 MHz.
N: Number of Hopping Frequencies; ChS : Hopping Channel Separation	

3.4.2 Hopping Bandedge Limit

Refer clause 3.6.1 and clause 3.7.1


3.4.3 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.4.4 Test Procedures

Test Method
▪ Refer as ANSI C63.10-2013, clause 7.8.3 for number of hopping frequencies measurement.
▪ Refer as ANSI C63.10-2013, clause 7.8.6 for hopping frequencies Bandedge measurement.

3.4.5 Test Setup



3.4.6 Test Result of Number of Hopping Frequencies

Refer as Appendix D

3.4.7 Test Result of Number of Hopping Frequencies Bandedge

Refer as Appendix D

3.5 Time of Occupancy (Dwell Time)

3.5.1 Time of Occupancy (Dwell Time) Limit

20dB Bandwidth and Carrier Frequency Separation Limit for Frequency Hopping Systems	
▪ 902-928 MHz Band:	
	▪ $N \geq 50$; 0.4s in 20s period
	▪ $50 > N \geq 25$; 0.4s in 10s period
▪ 2400-2483.5 MHz Band:	
	▪ $N \geq 75$; 0.4s in $N \times 0.4$ period
	▪ $75 > N \geq 15$; 0.4s in $N \times 0.4$ period
▪ 5725-5850 MHz Band:	
	▪ $N \geq 75$; 0.4s in 30s period
N: Number of Hopping Frequencies	


3.5.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.5.3 Test Procedures

Test Method	
▪ Refer as ANSI C63.10-2013, clause 7.8.4 for dwell time measurement.	
▪ Bluetooth ACL packets can be 1, 3, or 5 time slots. Following as dwell time. Operate DH5 at maximum dwell time and maximum duty cycle.	
	▪ The DH5 packet can cover up to 5 time slots. Operate DH5 at maximum dwell time and maximum duty cycle. A maximum length packet has duration of 5 time slots. The hopping rate is 1600 hops/second so the maximum dwell time is $5/1600$ seconds, or 3.125ms. DH5 Packet permit maximum $1600/79/6 = 3.37$ hops per second in each channel.

3.5.4 Test Setup



3.5.5 Test Result of Time of Occupancy (Dwell Time)

Refer as Appendix E

3.6 Emissions in Non-restricted Frequency Bands

3.6.1 Emissions in Non-restricted Frequency Bands Limit

Un-restricted Band Emissions Limit	
RF output power procedure	Limit (dB)
Peak output power procedure	20
Note 1: If the peak output power procedure is used to measure the fundamental emission power to demonstrate compliance to requirements, then the peak conducted output power measured within any 100 kHz outside the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum measured in-band peak PSD level.	


3.6.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.6.3 Test Procedures

Test Method
<ul style="list-style-type: none"> Refer as ANSI C63.10-2013, clause 7.8.8 for unwanted emissions into non-restricted bands.

3.6.4 Test Setup



3.6.5 Test Result of Emissions in Non-restricted Frequency Bands

Refer as Appendix F

3.7 Emissions in Restricted Frequency Bands

3.7.1 Emissions in Restricted Frequency Bands Limit

Restricted Band Emissions Limit			
Frequency Range (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m)	Measure Distance (m)
0.009~0.490	2400/F(kHz)	48.5 - 13.8	300
0.490~1.705	24000/F(kHz)	33.8 - 23	30
1.705~30.0	30	29	30
30~88	100	40	3
88~216	150	43.5	3
216~960	200	46	3
Above 960	500	54	3

Note 1: Test distance for frequencies at or above 30 MHz, measurements may be performed at a distance other than the limit distance provided they are not performed in the near field and the emissions to be measured can be detected by the measurement equipment. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse of linear distance for field-strength measurements, inverse of linear distance-squared for power-density measurements).

Note 2: Test distance for frequencies at below 30 MHz, measurements may be performed at a distance closer than the EUT limit distance; however, an attempt should be made to avoid making measurements in the near field. When performing measurements below 30 MHz at a closer distance than the limit distance, the results shall be extrapolated to the specified distance by either making measurements at a minimum of two or more distances on at least one radial to determine the proper extrapolation factor or by using the square of an inverse linear distance extrapolation factor (40 dB / decade). The test report shall specify the extrapolation method used to determine compliance of the EUT.

Note 3: Using the distance of 1m during the test for above 18 GHz, and the test value to correct for the distance factor at 3m.


3.7.2 Measuring Instruments


Refer a test equipment and calibration data table in this test report.

3.7.3 Test Procedures

Test Method	
<ul style="list-style-type: none">▪ The average emission levels shall be measured in [hopping duty factor].	
<ul style="list-style-type: none">▪ Refer as ANSI C63.10; clause 6.9.2.2 band-edge testing shall be performed at the lowest frequency channel and highest frequency channel within the allowed operating band.	
<ul style="list-style-type: none">▪ For the transmitter unwanted emissions shall be measured using following options below:	
	<ul style="list-style-type: none">▪ Refer as ANSI C63.10, clause 4.1.4.2.1 QP value.
	<ul style="list-style-type: none">▪ Refer as ANSI C63.10, clause 4.1.4.2.2 measurement procedure peak.
	<ul style="list-style-type: none">▪ Refer as ANSI C63.10, clause 4.1.4.2.4 average value of hopping pulsed emissions.

3.7.4 Test Setup





3.7.5 Transmitter Radiated Unwanted Emissions (Below 30MHz)

All amplitude of spurious emissions that are attenuated by more than 20 dB below the permissible value has no need to be reported.

The radiated emissions were investigated from 9 kHz or the lowest frequency generated within the device, up to the 10 harmonic or 40 GHz, whichever is appropriate.

3.7.6 Transmitter Radiated Unwanted Emissions

Refer as Appendix G



4 Test Equipment and Calibration Data

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Calibration Due Date	Remark
EMI Receiver	Agilent	N9038A	My52260123	9kHz ~ 8.45GHz	Jan. 31, 2018	Jan. 30, 2019	Conduction (CO01-CB)
LISN	F.C.C.	FCC-LISN-50-16-2	04083	150kHz~100MHz	Dec. 20, 2017	Dec. 19, 2018	Conduction (CO01-CB)
LISN	Schwarzbeck	NSLK 8127	8127647	9kHz ~ 30MHz	Dec. 29, 2017	Dec. 28, 2018	Conduction (CO01-CB)
COND Cable	Woken	Cable	Low cable-CO01	150kHz ~ 30MHz	May 22, 2018	May 21, 2019	Conduction (CO01-CB)
Software	Audix	E3	6.120210n	-	N.C.R.	N.C.R.	Conduction (CO01-CB)
BILOG ANTENNA with 6dB Attenuator	TESEQ & EMCI	CBL6112D & N-6-06	37880 & AT-N0609	20MHz ~ 2GHz	Aug. 27, 2018	Aug. 26, 2019	Radiation (03CH01-CB)
Loop Antenna	Teseq	HLA 6120	24155	9kHz - 30 MHz	Mar. 16, 2018	Mar. 15, 2019	Radiation (03CH01-CB)
Horn Antenna	EMCO	3115	00075790	750MHz ~ 18GHz	Nov. 20, 2017	Nov. 19, 2018	Radiation (03CH01-CB)
Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170252	15GHz ~ 40GHz	Jun. 28, 2018	Jun. 27, 2019	Radiation (03CH01-CB)
Pre-Amplifier	EMCI	EMC330N	980332	20MHz ~ 3GHz	May 02, 2018	May 01, 2019	Radiation (03CH01-CB)
Pre-Amplifier	Agilent	8449B	3008A02310	1GHz ~ 26.5GHz	Jan. 09, 2018	Jan. 08, 2019	Radiation (03CH01-CB)
Pre-Amplifier	MITEQ	TTA1840-35-HG	1864479	18GHz ~ 40GHz	Jul. 04, 2018	Jul. 03, 2019	Radiation (03CH01-CB)
Spectrum Analyzer	R&S	FSP40	100056	9kHz ~ 40GHz	Nov. 23, 2017	Nov. 22, 2018	Radiation (03CH01-CB)
EMI Test	R&S	ESCS	100354	9kHz ~ 2.75GHz	Dec. 08, 2017	Dec. 07, 2018	Radiation (03CH01-CB)
RF Cable-low	Woken	Low Cable-16+17	N/A	30 MHz ~ 1 GHz	Oct. 08, 2018	Oct. 07, 2019	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-16	N/A	1 GHz ~ 18 GHz	Oct. 08, 2018	Oct. 07, 2019	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-16+17	N/A	1 GHz ~ 18 GHz	Oct. 08, 2018	Oct. 07, 2019	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-40G#1	N/A	18GHz ~ 40 GHz	Jul. 27, 2018	Jul. 26, 2019	Radiation (03CH01-CB)




Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Calibration Due Date	Remark
RF Cable-high	Woken	High Cable-40G#2	N/A	18GHz ~ 40 GHz	Jul. 27, 2018	Jul. 26, 2019	Radiation (03CH01-CB)
Spectrum analyzer	R&S	FSV40	100979	9kHz~40GHz	Dec. 21, 2017	Dec. 20, 2018	Conducted (TH01-CB)
RF Cable-high	Woken	RG402	High Cable-06	1 GHz – 26.5 GHz	Oct. 08, 2018	Oct. 07, 2019	Conducted (TH01-CB)
RF Cable-high	Woken	RG402	High Cable-07	1 GHz –26.5 GHz	Oct. 08, 2018	Oct. 07, 2019	Conducted (TH01-CB)
RF Cable-high	Woken	RG402	High Cable-08	1 GHz –26.5 GHz	Oct. 08, 2018	Oct. 07, 2019	Conducted (TH01-CB)
RF Cable-high	Woken	RG402	High Cable-09	1 GHz –26.5 GHz	Oct. 08, 2018	Oct. 07, 2019	Conducted (TH01-CB)
RF Cable-high	Woken	RG402	High Cable-10	1 GHz –26.5 GHz	Oct. 08, 2018	Oct. 07, 2019	Conducted (TH01-CB)
Power Sensor	Agilent	U2021XA	MY53410001	50MHz~18GHz	Nov. 20, 2017	Nov. 19, 2018	Conducted (TH01-CB)

Note: Calibration Interval of instruments listed above is one year.

N.C.R. means Non-Calibration required.

AC Power-line Conducted Emissions Result


Operating Mode	1	Power Phase	Neutral
Operating Function	CTX		



	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark	Pol/Phase
	MHz	dBuV	dB	dBuV	dBuV	dB	dB		
1	0.1500	45.27	-10.73	56.00	35.19	9.92	0.16	Average	NEUTRAL
2	0.1500	61.43	-4.57	66.00	51.35	9.92	0.16	QP	NEUTRAL
3	0.1573	44.71	-10.89	55.60	34.63	9.92	0.16	Average	NEUTRAL
4	0.1573	60.05	-5.55	65.60	49.97	9.92	0.16	QP	NEUTRAL
5	0.1787	42.07	-12.48	54.55	32.00	9.92	0.15	Average	NEUTRAL
6	0.1787	56.49	-8.06	64.55	46.42	9.92	0.15	QP	NEUTRAL
7	0.2106	39.35	-13.83	53.18	29.29	9.92	0.14	Average	NEUTRAL
8	0.2106	52.24	-10.94	63.18	42.18	9.92	0.14	QP	NEUTRAL
9	0.2280	37.64	-14.88	52.52	27.58	9.92	0.14	Average	NEUTRAL
10	0.2280	50.06	-12.46	62.52	40.00	9.92	0.14	QP	NEUTRAL
11	0.2378	36.75	-15.42	52.17	26.70	9.92	0.13	Average	NEUTRAL
12	0.2378	49.11	-13.06	62.17	39.06	9.92	0.13	QP	NEUTRAL
13	0.2508	37.13	-14.60	51.73	27.08	9.92	0.13	Average	NEUTRAL
14	0.2508	48.33	-13.40	61.73	38.28	9.92	0.13	QP	NEUTRAL
15	0.2701	35.72	-15.40	51.12	25.67	9.92	0.13	Average	NEUTRAL
16	0.2701	46.23	-14.89	61.12	36.18	9.92	0.13	QP	NEUTRAL
17	0.3067	34.28	-15.78	50.06	24.23	9.92	0.13	Average	NEUTRAL
18	0.3067	44.37	-15.69	60.06	34.32	9.92	0.13	QP	NEUTRAL
19	0.4686	33.64	-12.90	46.54	23.59	9.92	0.13	Average	NEUTRAL
20	0.4686	39.73	-16.81	56.54	29.68	9.92	0.13	QP	NEUTRAL

Note 1: ">20dB" means emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found emissions (No emissions were detected.)



Summary

Mode	Max-N dB (Hz)	Max-OBW (Hz)	ITU-Code	Min-N dB (Hz)	Min-OBW (Hz)
2.4-2.4835GHz	-	-	-	-	-
BT-BR(1Mbps)	922.5k	897.051k	897KF1D	921.25k	892.054k
BT-EDR(2Mbps)	1.311M	1.187M	1M19G1D	1.31M	1.187M
BT-EDR(3Mbps)	1.28M	1.188M	1M19G1D	1.268M	1.184M

Max-N dB = Maximum 20dB down bandwidth; **Max-OBW** = Maximum 99% occupied bandwidth;

Min-N dB = Minimum 20dB down bandwidth; **Min-OBW** = Minimum 99% occupied bandwidth;


Result

Mode	Result	Limit (Hz)	Port 1-N dB (Hz)	Port 1-OBW (Hz)
BT-BR(1Mbps)	-	-	-	-
2402MHz	Pass	Inf	922.5k	897.051k
2440MHz	Pass	Inf	922.5k	895.802k
2480MHz	Pass	Inf	921.25k	892.054k
BT-EDR(2Mbps)	-	-	-	-
2402MHz	Pass	Inf	1.311M	1.187M
2440MHz	Pass	Inf	1.311M	1.187M
2480MHz	Pass	Inf	1.31M	1.187M
BT-EDR(3Mbps)	-	-	-	-
2402MHz	Pass	Inf	1.268M	1.186M
2440MHz	Pass	Inf	1.278M	1.184M
2480MHz	Pass	Inf	1.28M	1.188M


Port X-N dB = Port X 20dB down bandwidth; **Port X-OBW** = Port X 99% occupied bandwidth;

BT-BR(1Mbps)
EBW
2402MHz


22/10/2018


BT-BR(1Mbps)
EBW
2440MHz

22/10/2018



BT-BR(1Mbps)
EBW
2480MHz

22/10/2018




BT-EDR(2Mbps)
EBW
2402MHz


22/10/2018


BT-EDR(2Mbps)
EBW
2440MHz

22/10/2018



BT-EDR(2Mbps)
EBW
2480MHz

22/10/2018




BT-EDR(3Mbps)
EBW
2402MHz


22/10/2018


BT-EDR(3Mbps)
EBW
2440MHz

22/10/2018


BT-EDR(3Mbps)
EBW
2480MHz

22/10/2018



Summary

Mode	Max-Space (Hz)	Min-Space (Hz)
2.4-2.4835GHz	-	-
BT-BR(1Mbps)	1.0005M	1.0005M
BT-EDR(2Mbps)	1.002M	1.0005M
BT-EDR(3Mbps)	1.002M	999k


Result

Mode	Result	Fl (Hz)	Fh (Hz)	Ch.Space (Hz)	Limit (Hz)
BT-BR(1Mbps)	-	-	-	-	-
2402MHz	Pass	2.402008G	2.403009G	1.0005M	616.8825k
2440MHz	Pass	2.440007G	2.441007G	1.0005M	614.385k
2480MHz	Pass	2.479005G	2.480006G	1.0005M	613.5525k
BT-EDR(2Mbps)	-	-	-	-	-
2402MHz	Pass	2.402005G	2.403006G	1.0005M	873.126k
2440MHz	Pass	2.440005G	2.441007G	1.002M	873.126k
2480MHz	Pass	2.479007G	2.480007G	1.0005M	872.46k
BT-EDR(3Mbps)	-	-	-	-	-
2402MHz	Pass	2.402005G	2.403006G	1.0005M	844.488k
2440MHz	Pass	2.440004G	2.441006G	1.002M	851.148k
2480MHz	Pass	2.479008G	2.480007G	999k	852.48k

BT-BR(1Mbps)

Channel Separation


2.402G/2.403GHz



BT-BR(1Mbps)

Channel Separation


2.44G/2.441GHz



BT-BR(1Mbps)

Channel Separation


2.48G/2.479GHz



BT-EDR(2Mbps)

Channel Separation


2.402G/2.403GHz



BT-EDR(2Mbps)

Channel Separation


2.44G/2.441GHz



BT-EDR(2Mbps)

Channel Separation

2.48G/2.479GHz



BT-EDR(3Mbps)

Channel Separation


2.402G/2.403GHz



BT-EDR(3Mbps)

Channel Separation


2.44G/2.441GHz



BT-EDR(3Mbps)

Channel Separation

2.48G/2.479GHz



Summary

Mode	Power (dBm)	Power (W)
2.4-2.4835GHz	-	-
BT-BR(1Mbps)	-5.17	0.00030
BT-EDR(2Mbps)	-4.64	0.00034
BT-EDR(3Mbps)	-4.76	0.00033

Result

Mode	Result	Gain (dBi)	Power (dBm)	Power Limit (dBm)
BT-BR(1Mbps)	-	-	-	-
2402MHz	Pass	2.09	-5.17	21.00
2440MHz	Pass	2.09	-7.98	21.00
2480MHz	Pass	2.09	-7.46	21.00
BT-EDR(2Mbps)	-	-	-	-
2402MHz	Pass	2.09	-4.64	21.00
2440MHz	Pass	2.09	-7.73	21.00
2480MHz	Pass	2.09	-7.32	21.00
BT-EDR(3Mbps)	-	-	-	-
2402MHz	Pass	2.09	-4.76	21.00
2440MHz	Pass	2.09	-7.57	21.00
2480MHz	Pass	2.09	-7.21	21.00

Summary

Mode	Power (dBm)	Power (W)
2.4-2.4835GHz	-	-
BT-BR(1Mbps)	-4.09	0.00039
BT-EDR(2Mbps)	-2.25	0.00060
BT-EDR(3Mbps)	-2.05	0.00062

Result

Mode	Result	Gain (dBi)	Power (dBm)	Power Limit (dBm)
BT-BR(1Mbps)	-	-	-	-
2402MHz	Pass	2.09	-4.09	21.00
2440MHz	Pass	2.09	-6.25	21.00
2480MHz	Pass	2.09	-5.88	21.00
BT-EDR(2Mbps)	-	-	-	-
2402MHz	Pass	2.09	-2.25	21.00
2440MHz	Pass	2.09	-4.69	21.00
2480MHz	Pass	2.09	-4.36	21.00
BT-EDR(3Mbps)	-	-	-	-
2402MHz	Pass	2.09	-2.05	21.00
2440MHz	Pass	2.09	-4.38	21.00
2480MHz	Pass	2.09	-4.15	21.00

Summary


Mode	Max-Hop No
2.4-2.4835GHz	-
BT-BR(1Mbps)	79
BT-EDR(2Mbps)	79
BT-EDR(3Mbps)	79

Result

Mode	Result	Hopping No	Limit
BT-BR(1Mbps)	-	-	-
2440MHz	Pass	79	15
BT-EDR(2Mbps)	-	-	-
2440MHz	Pass	79	15
BT-EDR(3Mbps)	-	-	-
2440MHz	Pass	79	15


BT-BR(1Mbps) 2440MHz

Hopping Ch




BT-BR(1Mbps) 2440MHz

Hopping Ch Bandedge (Non-restricted Band)




BT-BR(1Mbps) 2440MHz

Hopping Ch Bandedge (Restricted Band)




BT-EDR(2Mbps) 2440MHz

Hopping Ch




BT-EDR(2Mbps) 2440MHz

Hopping Ch Bandedge (Non-restricted Band)




BT-EDR(2Mbps) 2440MHz

Hopping Ch Bandedge (Restricted Band)




BT-EDR(3Mbps) 2440MHz

Hopping Ch




BT-EDR(3Mbps) 2440MHz

Hopping Ch Bandedge (Non-restricted Band)



BT-EDR(3Mbps) 2440MHz

Hopping Ch Bandedge (Restricted Band)



Summary


Mode	Max-Dwell (s)
2.4-2.4835GHz	-
BT-BR(1Mbps)	309.4598m
BT-EDR(2Mbps)	293.0434m
BT-EDR(3Mbps)	293.2566m

Result

Mode	Result	Period (s)	Dwell (s)	Limit (s)	Tx On (s)
BT-BR(1Mbps)	-	-	-	-	-
2440MHz	Pass	31.6	309.4598m	400m	2.903m
BT-EDR(2Mbps)	-	-	-	-	-
2440MHz	Pass	31.6	293.0434m	400m	2.749m
BT-EDR(3Mbps)	-	-	-	-	-
2440MHz	Pass	31.6	293.2566m	400m	2.751m

BT-BR(1Mbps)

2440MHz



Period(s)	Dwell(s)	Limit(s)	Tx On(s)
31.6	309.4598m	400m	2.903m

Dwell

22/10/2018

Port 1 

Ch Freq
2.44GHz

RBW
300kHz


VBW
1MHz

Sweep Time
8ms

TX Time
2.903ms

BT-EDR(2Mbps)


2440MHz



Period(s)	Dwell(s)	Limit(s)	Tx On(s)
31.6	293.0434m	400m	2.749m

Dwell

22/10/2018

Port 1 

Ch Freq
2.44GHz

RBW
300kHz


VBW
1MHz

Sweep Time
8ms

TX Time
2.749ms

BT-EDR(3Mbps)


2440MHz



Period(s)	Dwell(s)	Limit(s)	Tx On(s)
31.6	293.2566m	400m	2.751m

Dwell

22/10/2018

Port 1 

Ch Freq
2.44GHz

RBW
300kHz

VBW
1MHz

Sweep Time
8ms


TX Time
2.751ms


Summary


Mode	Result	Ref (Hz)	Ref (dBm)	Limit (dBm)	Freq (Hz)	Level (dBm)	Freq (Hz)	Level (dBm)	Freq (Hz)	Level (dBm)	Freq (Hz)	Level (dBm)	Port
2.4-2.4835GHz	-	-	-	-	-	-	-	-	-	-	-	-	-
BT-BR(1Mbps)	Pass	2.479993G	-8.83	-28.83	706.064M	-61.16	2.398056G	-60.99	2.483704G	-60.38	6.943371G	-56.04	1
BT-EDR(2Mbps)	Pass	2.44008G	-10.39	-30.39	822.096M	-62.10	2.399248G	-61.07	2.484088G	-60.58	6.327037G	-56.01	1
BT-EDR(3Mbps)	Pass	2.439913G	-10.33	-30.33	2.308016G	-62.22	2.399472G	-61.68	2.48424G	-60.81	15.273736G	-55.42	1


Result


Mode	Result	Ref (Hz)	Ref (dBm)	Limit (dBm)	Freq (Hz)	Level (dBm)	Freq (Hz)	Level (dBm)	Freq (Hz)	Level (dBm)	Freq (Hz)	Level (dBm)	Port
BT-BR(1Mbps)	-	-	-	-	-	-	-	-	-	-	-	-	-
2402MHz	Pass	2.401837G	-6.81	-26.81	768.816M	-61.26	2.399956G	-59.11	2.48378G	-60.66	6.377694G	-55.65	1
2440MHz	Pass	2.439913G	-8.64	-28.64	2.163568G	-62.46	2.39996G	-60.84	2.484772G	-60.81	6.873013G	-56.79	1
2480MHz	Pass	2.479993G	-8.83	-28.83	706.064M	-61.16	2.398056G	-60.99	2.483704G	-60.38	6.943371G	-56.04	1
BT-EDR(2Mbps)	-	-	-	-	-	-	-	-	-	-	-	-	-
2402MHz	Pass	2.401837G	-8.31	-28.31	307.056M	-61.05	2.398176G	-59.88	2.485464G	-60.95	24.631325G	-55.65	1
2440MHz	Pass	2.44008G	-10.39	-30.39	822.096M	-62.10	2.399248G	-61.07	2.484088G	-60.58	6.327037G	-56.01	1
2480MHz	Pass	2.479993G	-10.02	-30.02	809.072M	-62.00	2.399952G	-60.73	2.484848G	-60.39	6.70134G	-55.82	1
BT-EDR(3Mbps)	-	-	-	-	-	-	-	-	-	-	-	-	-
2402MHz	Pass	2.401837G	-7.36	-27.36	1.974128G	-60.18	2.399992G	-59.88	2.484772G	-60.62	6.833613G	-55.96	1
2440MHz	Pass	2.439913G	-10.33	-30.33	2.308016G	-62.22	2.399472G	-61.68	2.48424G	-60.81	15.273736G	-55.42	1
2480MHz	Pass	2.479993G	-10.07	-30.07	845.776M	-61.93	2.399212G	-61.59	2.485172G	-59.93	6.282008G	-56.53	1













RSE TX above 1GHz Result

Appendix G.2


Summary

Mode	Result	Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
2.4-2.4835GHz	-	-	-	-	-	-	-	-	-	-	-	-
BT-BR(1Mbps)	Pass	AV	2.5G	45.12	54.00	-8.88	32.46	3	Horizontal	212	1.70	-

BT-BR(1Mbps)

2402MHz_TX

16/10/2018




EUT Y_1TX
Setting 8
03-R-5
FSP

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments						
PK	2.3754G	57.00	74.00	-17.00	32.08	3	Vertical	338	2.65	-						
AV	2.3878G	44.42	54.00	-9.58	32.13	3	Vertical	338	2.65	-						
PK	2.402G	78.65	Inf	-Inf	32.16	3	Vertical	338	2.65	-						
AV	2.402G	77.22	Inf	-Inf	32.16	3	Vertical	338	2.65	-						

BT-BR(1Mbps)

2402MHz_TX

16/10/2018




EUT Y_1TX
Setting 8
03-R-5
FSP

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments								
PK	2.3896G	57.21	74.00	-16.79	32.13	3	Horizontal	227	2.40	-								
AV	2.3882G	44.40	54.00	-9.60	32.13	3	Horizontal	227	2.40	-								
PK	2.4022G	76.23	Inf	-Inf	32.16	3	Horizontal	227	2.40	-								
AV	2.402G	74.58	Inf	-Inf	32.16	3	Horizontal	227	2.40	-								

BT-BR(1Mbps)

2402MHz_TX

16/10/2018




EUT Y_1TX
Setting 8
01-W-3
FSP(100019)

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments						
PK	4.80369G	45.55	74.00	-28.45	3.92	3	Vertical	65	1.11	-						
AV	4.80295G	32.33	54.00	-21.67	3.92	3	Vertical	65	1.11	-						

BT-BR(1Mbps)

2402MHz_TX

16/10/2018




EUT Y_1TX
Setting 8
01-W-3
FSP(100019)

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments						
PK	4.80497G	45.98	74.00	-28.02	3.92	3	Horizontal	299	2.47	-						
AV	4.80358G	32.32	54.00	-21.68	3.92	3	Horizontal	299	2.47	-						

BT-BR(1Mbps)

2440MHz_TX

16/10/2018




EUT Y_1TX
Setting 8
03-R-5
FSP

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments								
PK	2.3796G	56.07	74.00	-17.93	32.10	3	Vertical	319	1.31	-								
AV	2.3896G	44.52	54.00	-9.48	32.13	3	Vertical	319	1.31	-								
PK	2.44G	75.93	Inf	-Inf	32.28	3	Vertical	319	1.31	-								
AV	2.44G	74.22	Inf	-Inf	32.28	3	Vertical	319	1.31	-								
PK	2.4924G	57.27	74.00	-16.73	32.43	3	Vertical	319	1.31	-								
AV	2.4996G	45.11	54.00	-8.89	32.46	3	Vertical	319	1.31	-								

BT-BR(1Mbps)

2440MHz_TX

16/10/2018




EUT Y_1TX
Setting 8
03-R-5
FSP

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
PK	2.3876G	56.49	74.00	-17.51	32.13	3	Horizontal	212	1.70	-
AV	2.3884G	44.40	54.00	-9.60	32.13	3	Horizontal	212	1.70	-
PK	2.44G	72.25	Inf	-Inf	32.28	3	Horizontal	212	1.70	-
AV	2.44G	70.47	Inf	-Inf	32.28	3	Horizontal	212	1.70	-
PK	2.4835G	57.06	74.00	-16.94	32.42	3	Horizontal	212	1.70	-
AV	2.5G	45.12	54.00	-8.88	32.46	3	Horizontal	212	1.70	-

BT-BR(1Mbps)

2440MHz_TX

16/10/2018




EUT Y_1TX
Setting 8
01-W-3
FSP(100019)

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments						
PK	4.8872G	45.71	74.00	-28.29	4.26	3	Vertical	249	1.94	-						
AV	4.8828G	32.89	54.00	-21.11	4.23	3	Vertical	249	1.94	-						

BT-BR(1Mbps)

2440MHz_TX

16/10/2018




EUT Y_1TX
Setting 8
01-W-3
FSP(100019)

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments						
PK	4.87977G	45.82	74.00	-28.18	4.23	3	Horizontal	33	1.98	-						
AV	4.8823G	32.81	54.00	-21.19	4.23	3	Horizontal	33	1.98	-						

BT-BR(1Mbps)

2480MHz_TX

16/10/2018




EUT_Y_1TX
Setting 8
03-R-5
FSP

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
PK	2.4798G	77.03	Inf	-Inf	32.40	3	Vertical	341	2.08	-
AV	2.48G	75.44	Inf	-Inf	32.40	3	Vertical	341	2.08	-
PK	2.4928G	56.84	74.00	-17.16	32.43	3	Vertical	341	2.08	-
AV	2.4996G	45.03	54.00	-8.97	32.46	3	Vertical	341	2.08	-

BT-BR(1Mbps)

2480MHz_TX

16/10/2018




EUT Y_1TX
Setting 8
03-R-5
FSP

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
PK	2.4798G	72.12	Inf	-Inf	32.40	3	Horizontal	220	2.99	-
AV	2.48G	70.00	Inf	-Inf	32.40	3	Horizontal	220	2.99	-
PK	2.4976G	57.09	74.00	-16.91	32.45	3	Horizontal	220	2.99	-
AV	2.4998G	45.00	54.00	-9.00	32.46	3	Horizontal	220	2.99	-

BT-BR(1Mbps)

2480MHz_TX

16/10/2018




EUT Y_1TX
Setting 8
01-W-3
FSP(100019)

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments						
PK	4.96013G	46.05	74.00	-27.95	4.55	3	Vertical	125	2.37	-						
AV	4.95798G	32.74	54.00	-21.26	4.53	3	Vertical	125	2.37	-						

BT-BR(1Mbps)

2480MHz_TX

16/10/2018




EUT Y_1TX
Setting 8
01-W-3
FSP(100019)

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments						
PK	4.95828G	45.80	74.00	-28.20	4.53	3	Horizontal	30	1.91	-						
AV	4.95856G	32.71	54.00	-21.29	4.53	3	Horizontal	30	1.91	-						

BT-EDR(3Mbps)

2402MHz_TX

16/10/2018




EUT Y_1TX
Setting 8
03-R-5
FSP

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
PK	2.3826G	56.99	74.00	-17.01	32.11	3	Vertical	322	2.13	-
AV	2.3844G	44.44	54.00	-9.56	32.11	3	Vertical	322	2.13	-
PK	2.402G	80.86	Inf	-Inf	32.16	3	Vertical	322	2.13	-
AV	2.402G	76.34	Inf	-Inf	32.16	3	Vertical	322	2.13	-

BT-EDR(3Mbps)

2402MHz_TX

16/10/2018




EUT Y_1TX
Setting 8
03-R-5
FSP

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments						
PK	2.371G	56.31	74.00	-17.69	32.07	3	Horizontal	212	1.99	-						
AV	2.3786G	44.40	54.00	-9.60	32.10	3	Horizontal	212	1.99	-						
PK	2.4018G	76.18	Inf	-Inf	32.16	3	Horizontal	212	1.99	-						
AV	2.402G	71.55	Inf	-Inf	32.16	3	Horizontal	212	1.99	-						

BT-EDR(3Mbps)

2402MHz_TX

16/10/2018




EUT Y_1TX
Setting 8
01-W-3
FSP(100019)

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments						
PK	4.80201G	45.90	74.00	-28.10	3.90	3	Vertical	197	1.69	-						
AV	4.80375G	32.29	54.00	-21.71	3.92	3	Vertical	197	1.69	-						

BT-EDR(3Mbps)

2402MHz_TX

16/10/2018




EUT Y_1TX
Setting 8
01-W-3
FSP(100019)

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments						
PK	4.80384G	46.39	74.00	-27.61	3.92	3	Horizontal	308	1.29	-						
AV	4.80415G	32.15	54.00	-21.85	3.92	3	Horizontal	308	1.29	-						

BT-EDR(3Mbps)

2440MHz_TX

16/10/2018




EUT Y_1TX
Setting 8
03-R-5
FSP

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments								
PK	2.3708G	55.92	74.00	-18.08	32.07	3	Vertical	336	1.90	-								
AV	2.39G	44.39	54.00	-9.61	32.13	3	Vertical	336	1.90	-								
PK	2.44G	77.70	Inf	-Inf	32.28	3	Vertical	336	1.90	-								
AV	2.44G	73.20	Inf	-Inf	32.28	3	Vertical	336	1.90	-								
PK	2.4988G	56.93	74.00	-17.07	32.46	3	Vertical	336	1.90	-								
AV	2.5G	44.98	54.00	-9.02	32.46	3	Vertical	336	1.90	-								

BT-EDR(3Mbps)

2440MHz_TX

16/10/2018




EUT Y_1TX
Setting 8
03-R-5
FSP

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
PK	2.3868G	56.44	74.00	-17.56	32.12	3	Horizontal	213	1.72	-
AV	2.3864G	44.38	54.00	-9.62	32.12	3	Horizontal	213	1.72	-
PK	2.44G	73.54	Inf	-Inf	32.28	3	Horizontal	213	1.72	-
AV	2.44G	68.78	Inf	-Inf	32.28	3	Horizontal	213	1.72	-
PK	2.4972G	56.81	74.00	-17.19	32.45	3	Horizontal	213	1.72	-
AV	2.5G	45.06	54.00	-8.94	32.46	3	Horizontal	213	1.72	-

BT-EDR(3Mbps)

2440MHz_TX

16/10/2018




EUT Y_1TX
Setting 8
01-W-3
FSP(100019)

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments						
PK	4.87781 G	45.65	74.00	-28.35	4.21	3	Vertical	353	1.86	-						
AV	4.88244 G	32.84	54.00	-21.16	4.23	3	Vertical	353	1.86	-						

BT-EDR(3Mbps)

2440MHz_TX

16/10/2018




EUT Y_1TX
Setting 8
01-W-3
FSP(100019)

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments						
PK	4.88215G	45.85	74.00	-28.15	4.23	3	Horizontal	33	1.19	-						
AV	4.87808G	32.77	54.00	-21.23	4.21	3	Horizontal	33	1.19	-						

BT-EDR(3Mbps)

2480MHz_TX

16/10/2018




EUT_Y_1TX
Setting 8
03-R-5
FSP

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
PK	2.48G	77.64	Inf	-Inf	32.40	3	Vertical	331	1.11	-
AV	2.48G	73.19	Inf	-Inf	32.40	3	Vertical	331	1.11	-
PK	2.499G	56.80	74.00	-17.20	32.46	3	Vertical	331	1.11	-
AV	2.499G	44.97	54.00	-9.03	32.46	3	Vertical	331	1.11	-

BT-EDR(3Mbps)

2480MHz_TX

16/10/2018




EUT_Y_1TX
Setting 8
03-R-5
FSP

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
PK	2.48G	73.38	Inf	-Inf	32.40	3	Horizontal	218	2.99	-
AV	2.48G	68.48	Inf	-Inf	32.40	3	Horizontal	218	2.99	-
PK	2.4862G	57.46	74.00	-16.54	32.42	3	Horizontal	218	2.99	-
AV	2.5G	45.00	54.00	-9.00	32.46	3	Horizontal	218	2.99	-

BT-EDR(3Mbps)

2480MHz_TX

16/10/2018




EUT Y_1TX
Setting 8
01-W-3
FSP(100019)

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments						
PK	4.96077G	45.87	74.00	-28.13	4.55	3	Vertical	57	1.73	-						
AV	4.96105G	32.75	54.00	-21.25	4.55	3	Vertical	57	1.73	-						

BT-EDR(3Mbps)

2480MHz_TX

16/10/2018



EUT Y_1TX
Setting 8
01-W-3
FSP(100019)

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments						
PK	4.96024G	46.19	74.00	-27.81	4.55	3	Horizontal	124	2.20	-						
AV	4.95954G	32.73	54.00	-21.27	4.55	3	Horizontal	124	2.20	-						