

ELECTROMAGNETIC EMISSION COMPLIANCE REPORT FOR LOW-POWER, NON-LICENSED TRANSMITTER

Test Report No. : W163R-D051

AGR No. : A15DA-017

Applicant : CIAAT Co., Ltd.

Address : 40, Pyeongdongsandan-ro 169beon-gil, Gwangsan-gu, Gwangju, Korea

Manufacturer : CIAAT Co., Ltd.

Address : 40, Pyeongdongsandan-ro 169beon-gil, Gwangsan-gu, Gwangju, Korea

Type of Equipment : Mobile Photo Printer

FCC ID. : 2AHL-CMP-3100W

Model Name : CMP-3100W

Serial number : N/A

Total page of Report : 60 pages (including this page)

Date of Incoming : January 05, 2016

Date of issue : March 22, 2016

SUMMARY

The equipment complies with the regulation; *FCC PART 15 SUBPART C Section 15.247*

This test report only contains the result of a single test of the sample supplied for the examination.

It is not a generally valid assessment of the features of the respective products of the mass-production.

Reviewed by:


Jae-Ho, Lee / Chief Engineer
ONETECH Corp.

Approved by:


Sung-Ik, Han / Managing Director
ONETECH Corp.

CONTENTS

PAGE

1. VERIFICATION OF COMPLIANCE	5
2. TEST SUMMARY	6
2.1 TEST ITEMS AND RESULTS	6
2.2 ADDITIONS, DEVIATIONS, EXCLUSIONS FROM STANDARDS.....	6
2.3 RELATED SUBMITTAL(S) / GRANT(S)	6
2.4 PURPOSE OF THE TEST	6
2.5 TEST METHODOLOGY.....	6
2.6 TEST FACILITY.....	6
3. GENERAL INFORMATION.....	7
3.1 PRODUCT DESCRIPTION.....	7
3.2 ALTERNATIVE TYPE(S)/MODEL(S); ALSO COVERED BY THIS TEST REPORT.....	8
4. EUT MODIFICATIONS.....	8
5. SYSTEM TEST CONFIGURATION	9
5.1 JUSTIFICATION.....	9
5.4 CONFIGURATION OF TEST SYSTEM.....	10
5.5 ANTENNA REQUIREMENT	10
6. PRELIMINARY TEST	11
6.1 AC POWER LINE CONDUCTED EMISSIONS TESTS.....	11
6.2 GENERAL RADIATED EMISSIONS TESTS	11
7. WLAN.....	12
7.1 MINIMUM 6 dB BANDWIDTH	12
7.1.1 Operating environment.....	12
7.1.2 Test set-up	12
7.1.3 Test equipment used.....	12
7.1.4 Test data for 802.11b	13
7.1.5 Test data for 802.11g	15
7.1.6 Test data for 802.11n_HT20.....	17
7.2 MAXIMUM PEAK OUTPUT POWER.....	19
7.2.1 Operating environment.....	19
7.2.2 Test set-up	19
7.2.3 Test equipment used.....	19

7.2.4 Test data for 802.11b	20
7.2.5 Test data for 802.11g	22
7.2.6 Test data for 802.11n_HT20.....	24
7.3 100 kHz BANDWIDTH OUTSIDE THE FREQUENCY BAND	26
7.3.1 Operating environment.....	26
7.3.2 Test set-up for conducted measurement.....	26
7.3.3 Test set-up for radiated measurement.....	26
7.3.4 Test equipment used.....	26
7.3.5 Test data for conducted emission	27
7.4 PEAK POWER SPECTRAL DENSITY	48
7.4.1 Operating environment.....	48
7.4.2 Test set-up	48
7.4.3 Test equipment used.....	48
7.4.4 Test data for 802.11b	49
7.4.5 Test data for 802.11g	51
7.4.6 Test data for 802.11n_HT20.....	53
7.5 RADIATED EMISSION TEST.....	55
7.5.1 Operating environment.....	55
7.5.2 Test set-up	55
7.5.3 Test equipment used.....	55
7.5.4 Test data	56
7.6 CONDUCTED EMISSION TEST	58
7.6.1 Operating environment.....	58
7.6.2 Test set-up	58
7.6.3 Test equipment used.....	58
7.6.4 Test data	59

Revision History

Issued Report No.	Issued Date	Revisions	Effect Section
W163R-D051	March 22, 2016	Initial Issue	All

1. VERIFICATION OF COMPLIANCE

Applicant : CIAAT Co., Ltd.
Address : 40, Pyeongdongsandan-ro 169beon-gil, Gwangsan-gu, Gwangju, Korea
Contact Person : Jung Hoon Kim / Manager
Telephone No. : +82-70-5033-7200
FCC ID : 2AHL-CMP-3100W
Model Name : CMP-3100W
Serial Number : N/A
Date : March 22, 2016

EQUIPMENT CLASS	DTS-Digital Transmission System
EQUIPMENT DESCRIPTION	Mobile Photo Printer
THIS REPORT CONCERNS	Original Grant
MEASUREMENT PROCEDURES	ANSI C63.10: 2013
TYPE OF EQUIPMENT TESTED	Pre-Production
KIND OF EQUIPMENT AUTHORIZATION REQUESTED	Certification
EQUIPMENT WILL BE OPERATED UNDER FCC RULES PART(S)	FCC PART 15 SUBPART C Section 15.247
Modifications on the Equipment to Achieve Compliance	None
Final Test was Conducted On	3 m Semi Anechoic Chamber

-. The above equipment was tested by ONETECH Corp. for compliance with the requirement set forth in the FCC Rules and Regulations. This said equipment in the configuration described in this report, shows the maximum emission levels emanating from equipment are within the compliance requirements.

2. TEST SUMMARY

2.1 Test items and results

SECTION	TEST ITEMS	RESULTS
15.247 (a) (2)	Minimum 6 dB Bandwidth	Met the Limit / PASS
15.247 (b) (3)	Maximum Peak Conducted Output Power	Met the Limit / PASS
15.247 (d)	100 kHz Bandwidth Outside the Frequency Band	Met the Limit / PASS
15.247 (d)	Radiated Emission which fall in the Restricted Band	Met the Limit / PASS
15.247 (e)	Peak Power Spectral Density	Met the Limit / PASS
15.209	Radiated Emission Limits	Met the Limit / PASS
15.207	Conducted Limits	Met the Limit / PASS
15.203	Antenna Requirement	Met requirement / PASS

2.2 Additions, deviations, exclusions from standards

No additions, deviations or exclusions have been made from standard.

2.3 Related Submittal(s) / Grant(s)

Original submittal only

2.4 Purpose of the test

To determine whether the equipment under test fulfills the requirements of the regulation stated in FCC PART 15 SUBPART C Section 15.247

2.5 Test Methodology

Both conducted and radiated testing was performed according to the procedures in ANSI C63.10: 2013. Radiated testing was performed at a distance of 3 m from EUT to the antenna.

2.6 Test Facility

The Onetech Corp. has been designated to perform equipment testing in compliance with ISO/IEC 17025.

The Electromagnetic compatibility measurement facilities are located at 301-14, Daessangnyeong-ri, Chowol-eup, Gwangju-si, Gyeonggi-do, 464-862 Korea.

-. Site Filing:

VCCI (Voluntary Control Council for Interference) – Registration No. R-4112/ C-4617/ G-666/ T-1842

IC (Industry Canada) – Registration No. Site# 3736A-3

-. Site Accreditation:

KOLAS (Korea Laboratory Accreditation Scheme) - Accreditation NO. KT085

FCC (Federal Communications Commission) - Accreditation No. KR0013

RRA (Radio Research Agency) – Designation No. KR0013

3. GENERAL INFORMATION

3.1 Product Description

The CIAAT Co., Ltd., Model CMP-3100W (referred to as the EUT in this report) is a Mobile Photo Printer. Product specification information described herein was obtained from product data sheet or user's manual.

DEVICE TYPE	Mobile Photo Printer
OPERATING FREQUENCY	802.11b/g/n(HT20): 2 412 MHz ~ 2 462 MHz
MAX. RF OUTPUT POWER	802.11b: 8.36 dBm
	802.11g: 1.66 dBm
	802.11n(HT20): 1.56 dBm
MODULATION TYPE	802.11b: DSSS Modulation(DBPSK/DQPSK/CCK) 802.11g/n(HT20): OFDM Modulation(BPSK/QPSK/16QAM/64QAM)
ANTENNA TYPE	PCB Antenna
ANTENNA GAIN	0.9 dBi
List of each Osc. or crystal Freq.(Freq. >= 1 MHz)	32.768 kHz, 24 MHz, 124 MHz

3.2 Alternative type(s)/model(s); also covered by this test report.

-. None

4. EUT MODIFICATIONS

-. None

5. SYSTEM TEST CONFIGURATION

5.1 Justification

This device was configured for testing in a typical way as a normal customer is supposed to be used. During the test, the following components were installed inside of the EUT.

DEVICE TYPE	MANUFACTURER	MODEL/PART NUMBER	FCC ID
Battery	N/A	PE553060 2S1P	N/A
Main Board	N/A	CMP-3100W MAIN V1.0	N/A
Module	TAIYO YUDEN CO.,LTD.	WYSAAVDX7	RYYWYSAAVDX7

5.2 Peripheral equipment

Defined as equipment needed for correct operation of the EUT, but not considered as tested:

Model	Manufacturer	Description	Connected to
CMP-3100W	CIAAT Co., Ltd.	Mobile Photo Printer (EUT)	-
ETA-P10X	Dongguan SAMSUNG Electro-Mechanics Co., Ltd.	AC ADAPTER	-

5.3 Mode of operation during the test

For the testing, software used to control the EUT for staying in continuous transmitting mode is programmed.

The worse case data rate for each modulation is determined in 11 Mbps for IEEE 802.11b, 6 Mbps for IEEE 802.11g, and 6.5 Mbps for HT20.

5.4 Configuration of Test System

Line Conducted Test: The EUT was connected to USB and the power of USB was connected to Notebook PC. All supporting equipments were connected to another LISN. Preliminary Power line Conducted Emission test was performed by using the procedure in ANSI C63.10: 2013 to determine the worse operating conditions.

Radiated Emission Test: Preliminary radiated emissions test were conducted using the procedure in ANSI C63.10: 2013 to determine the worse operating conditions. Final radiated emission tests were conducted at 3 m Semi Anechoic Chamber.

The turntable was rotated through 360 degrees and the EUT was tested by positioned three orthogonal planes to obtain the highest reading on the field strength meter. Once maximum reading was determined, the search antenna was raised and lowered in both vertical and horizontal polarization.

5.5 Antenna Requirement

For intentional device, according to section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

Antenna Construction:

The transmitter antenna of the EUT is PCB antenna, so no consideration of replacement by the user.

6. PRELIMINARY TEST

6.1 AC Power line Conducted Emissions Tests

During Preliminary Test, the following operating mode was investigated.

Operation Mode	The Worse operating condition (Please check one only)
Transmitting Mode	X

6.2 General Radiated Emissions Tests

During Preliminary Test, the following operating mode was investigated.

Operation Mode	The Worse operating condition (Please check one only)
Transmitting Mode	X

7. WLAN


7.1 MINIMUM 6 dB BANDWIDTH

7.1.1 Operating environment

Temperature : 22.4 °C
Relative humidity : 44.2 % R.H.

7.1.2 Test set-up

The antenna output of the EUT was connected to the spectrum analyzer. The resolution bandwidth is set to 100 kHz, and peak detection was used. The 6 dB bandwidth is defined as the total spectrum over which the power is higher than the peak power minus 6 dB.



7.1.3 Test equipment used

Model Number	Manufacturer	Description	Serial Number	Last Cal.
■ - FSV40	Rohde & Schwarz	Signal Analyzer	101009	Jul. 22, 2015 (1Y)

All test equipment used is calibrated on a regular basis.

7.1.4 Test data for 802.11b

-. Test Date : March 14, 2016


-. Test Result : Pass


CHANNEL	FREQUENCY(MHz)	MEASURED VALUE (MHz)	LIMIT(MHz)	Margin(MHz)
Low	2 412	10.09	0.5	9.59
Middle	2 442	10.09	0.5	9.59
High	2 462	10.05	0.5	9.55

Remark. Margin = Measured Value - Limit




Tested by: Min-Gu, Ji / Project Engineer






Middle Channel



High Channel



Middle Channel



High Channel

7.1.6 Test data for 802.11n_HT20


-. Test Date : March 14, 2016


-. Test Result : Pass

CHANNEL	FREQUENCY(MHz)	MEASURED VALUE (MHz)	LIMIT(MHz)	Margin(MHz)
Low	2 412	17.68	0.5	17.18
Middle	2 442	17.68	0.5	17.18
High	2 462	17.68	0.5	17.18

Remark. Margin = Measured Value - Limit

Tested by: Min-Gu, Ji / Project Engineer





Middle Channel



High Channel


7.2 MAXIMUM PEAK OUTPUT POWER

7.2.1 Operating environment

Temperature : 22.4 °C
Relative humidity : 44.2 % R.H.

7.2.2 Test set-up

The maximum peak output power was measured with the spectrum analyzer connected to the antenna output of the EUT. The spectrum analyzer's internal channel power integration function is used to integrate the power over a bandwidth greater than or equal to the 99 % bandwidth. The EUT was operating in transmit mode at the appropriate center frequency.



7.2.3 Test equipment used

Model Number	Manufacturer	Description	Serial Number	Last Cal.
■ - FSV40	Rohde & Schwarz	Signal Analyzer	101009	Jul. 22, 2015 (1Y)

All test equipment used is calibrated on a regular basis.

7.2.4 Test data for 802.11b

-. Test Date : March 14, 2016


-. Test Result : Pass


CHANNEL	FREQUENCY (MHz)	DTS (MHz)	MEASURED VALUE (dBm)	LIMIT (dBm)	MARGIN (dB)
LOW	2 412	10.09	6.65	30.00	23.35
MIDDLE	2 442	10.09	7.55	30.00	22.45
HIGH	2 462	10.05	8.36	30.00	21.64

Remark. Margin = Limit – Measured Value (=Receiver Reading + Cable Loss)




Tested by: Min-Gu, Ji / Project Engineer





Middle Channel



High Channel

7.2.5 Test data for 802.11g

-. Test Date : March 14, 2016


-. Test Result : Pass


CHANNEL	FREQUENCY (MHz)	DTS (MHz)	MEASURED VALUE (dBm)	LIMIT (dBm)	MARGIN (dB)
LOW	2 412	16.43	0.30	30.00	29.70
MIDDLE	2 442	16.43	1.16	30.00	28.84
HIGH	2 462	16.43	1.66	30.00	28.34

Remark. Margin = Limit – Measured Value (=Receiver Reading + Cable Loss)




Tested by: Min-Gu, Ji / Project Engineer





Middle Channel



High Channel

7.2.6 Test data for 802.11n_HT20


-. Test Date : March 14, 2016


-. Test Result : Pass

CHANNEL	FREQUENCY (MHz)	DTS (MHz)	MEASURED VALUE (dBm)	LIMIT (dBm)	MARGIN (dB)
LOW	2 412	17.68	0.23	30.00	29.77
MIDDLE	2 442	17.68	1.02	30.00	28.98
HIGH	2 462	17.68	1.56	30.00	28.44


Remark. Margin = Limit – Measured Value (=Receiver Reading + Cable Loss)

Tested by: Min-Gu, Ji / Project Engineer





Middle Channel



High Channel


7.3 100 kHz BANDWIDTH OUTSIDE THE FREQUENCY BAND

7.3.1 Operating environment

Temperature : 22.4 °C
Relative humidity : 44.2 % R.H.

7.3.2 Test set-up for conducted measurement

The antenna output of the EUT was connected to the spectrum analyzer. The resolution and video bandwidth is set to 100 kHz, and peak detection was used.



7.3.3 Test set-up for radiated measurement

The radiated emissions measurements were performed on the 3 m, open-field test site. The EUT was placed on a non-conductive turntable above the ground plane.

The frequency spectrum from 30 MHz to 26.5 GHz was scanned and maximum emission levels at each frequency recorded. The system was rotated 360°, and the antenna was varied in the height between 1.0 m and 4.0 m in order to determine the maximum emission levels. This procedure was performed for horizontal and vertical polarization of the receiving antenna.


7.3.4 Test equipment used

	Model Number	Manufacturer	Description	Serial Number	Last Cal.(Interval)
■ -	FSV40	Rohde & Schwarz	Signal Analyzer	101009	Jul. 22, 2015 (1Y)
■ -	ESU	Rohde & Schwarz	EMI Test Receiver	100261	Apr. 29, 2015 (1Y)
■ -	310N	Sonoma Instrument	Pre-Amplifier	312544	Apr. 29, 2015 (1Y)
■ -	SCU-18	Rohde & Schwarz	Pre-Amplifier	10041	Nov. 03, 2015 (1Y)
■ -	DT3000	Innco System	Turn Table	930611	N/A
■ -	MA4000-EP	Innco System	Antenna Master	3320611	N/A
■ -	VULB9163	Schwarzbeck	TRILOG Broadband Antenna	9163-421	Jul. 10, 2014 (2Y)
■ -	BBHA9120D	Schwarzbeck	Horn Antenna	BBHA9120D295	Aug. 31, 2015 (2Y)
■ -	BBHA9170	Schwarzbeck	Horn Antenna	BBHA9170178	Aug. 31, 2015 (2Y)


All test equipment used is calibrated on a regular basis.

7.3.5 Test data for conducted emission


7.3.5.1 Test data for 802.11b




Low Channel




Middle Channel







Low Channel




Low Channel




Middle Channel



Middle Channel



High Channel




High Channel


7.3.5.2 Test data for 802.11g




Low Channel




Middle Channel







Low Channel




Low Channel




Middle Channel



Middle Channel



High Channel




High Channel


7.3.5.3 Test data for 802.11n_HT20




Low Channel




Middle Channel







Low Channel




Low Channel




Middle Channel



Middle Channel



High Channel



High Channel

7.3.6 Test data for radiated emission

7.3.6.1 Radiated Emission which fall in the Restricted Band

7.3.6.1.1 Test data for 802.11b

- Test Date : March 13, 2016
- Resolution bandwidth : 1 MHz for Peak and Average Mode
- Video bandwidth : 1 MHz for Peak Mode, 10 Hz for Average Mode
- Frequency range : 30 MHz ~ 26.5 GHz
- Measurement distance : 3 m
- Result : PASSED

Frequency (MHz)	Reading (dBμV)	Detector Mode	Ant. Pol. (H/V)	Ant. Factor	Cable Loss	Amp Gain	Total (dBμV/m)	Limits (dBμV/m)	Margin (dB)
Test Data for Low Channel									
2 390.00	59.34	Peak	H	27.10	7.50	43.00	50.94	74.00	23.06
	34.55	Average	H				26.15	54.00	27.85
	59.76	Peak	V				51.36	74.00	22.64
	30.05	Average	V				21.65	54.00	32.35
Test Data for High Channel									
2 483.50	68.49	Peak	H	27.10	7.50	43.00	60.09	74.00	13.91
	37.37	Average	H				28.97	54.00	25.03
	60.59	Peak	V				52.19	74.00	21.81
	43.88	Average	V				35.48	54.00	18.52

Tabulated test data for Restricted Band

Remark: "H": Horizontal, "V": Vertical

Margin (dB) = Limits (dBμV/m) - Total Level (dBμV/m)

Total Level = Reading + Antenna Factor + Cable Loss – Pre-Amplifier Gain



Tested by: Min-Gu, Ji / Project Engineer

7.3.6.1.2 Test data for 802.11g

- Test Date : March 13, 2016
- Resolution bandwidth : 1 MHz for Peak and Average Mode
- Video bandwidth : 1 MHz for Peak Mode, 10 Hz for Average Mode
- Frequency range : 30 MHz ~ 26.5 GHz
- Measurement distance : 3 m
- Result : PASSED

Frequency (MHz)	Reading (dBμV)	Detector Mode	Ant. Pol. (H/V)	Ant. Factor	Cable Loss	Amp Gain	Total (dBμV/m)	Limits (dBμV/m)	Margin (dB)
Test Data for Low Channel									
2 390.00	67.39	Peak	H	27.10	7.50	43.00	58.99	74.00	15.01
	45.99	Average	H				37.59	54.00	16.41
	58.80	Peak	V				50.40	74.00	23.60
	33.03	Average	V				24.63	54.00	29.37
Test Data for High Channel									
2 483.50	69.52	Peak	H	27.10	7.50	43.00	61.12	74.00	12.88
	55.35	Average	H				46.95	54.00	7.05
	61.49	Peak	V				53.09	74.00	20.91
	53.45	Average	V				45.05	54.00	8.95

Tabulated test data for Restricted Band

Remark: "H": Horizontal, "V": Vertical

Margin (dB) = Limits (dBμV/m) - Total Level (dBμV/m)

Total Level = Reading + Antenna Factor + Cable Loss – Pre-Amplifier Gain



Tested by: Min-Gu, Ji / Project Engineer

7.3.6.1.3 Test data for 802.11n_HT20

- Test Date : March 13, 2016
- Resolution bandwidth : 1 MHz for Peak and Average Mode
- Video bandwidth : 1 MHz for Peak Mode, 10 Hz for Average Mode
- Frequency range : 30 MHz ~ 26.5 GHz
- Measurement distance : 3 m
- Result : PASSED

Frequency (MHz)	Reading (dBμV)	Detector Mode	Ant. Pol. (H/V)	Ant. Factor	Cable Loss	Amp Gain	Total (dBμV/m)	Limits (dBμV/m)	Margin (dB)
Test Data for Low Channel									
2 390.00	67.18	Peak	H	27.10	7.50	43.00	58.78	74.00	15.22
	45.81	Average	H				37.41	54.00	16.59
	59.09	Peak	V				50.69	74.00	23.31
	35.40	Average	V				27.00	54.00	27.00
Test Data for High Channel									
2 483.50	69.03	Peak	H	27.10	7.50	43.00	60.63	74.00	13.37
	56.71	Average	H				48.31	54.00	5.69
	61.93	Peak	V				53.53	74.00	20.47
	53.24	Average	V				44.84	54.00	9.16

Tabulated test data for Restricted Band

Remark: "H": Horizontal, "V": Vertical

Margin (dB) = Limits (dBμV/m) - Total Level (dBμV/m)

Total Level = Reading + Antenna Factor + Cable Loss – Pre-Amplifier Gain



Tested by: Min-Gu, Ji / Project Engineer

7.3.6.2 Spurious & Harmonic Radiated Emission

7.3.6.2.1 Test data for 802.11b

- Test Date : March 13, 2016
- Resolution bandwidth : 1 MHz for Peak and Average Mode for the emissions fall in restricted band,
100 kHz for Peak Mode for the emissions outside restricted band
- Video bandwidth : 1 MHz for Peak Mode, 10 Hz for Average Mode
- Frequency range : 1 GHz ~ 26.5 GHz
- Measurement distance : 3 m
- Result : PASSED

Frequency (GHz)	Reading (dBμV)	Detector Mode	Ant. Pol. (H/V)	Ant. Factor	Cable Loss	Amp Gain	Total (dBμV/m)	Limits (dBμV/m)	Margin (dB)
Test Data for Low Channel									
4 824.00	38.14	Peak	H	30.60	11.10	42.50	37.30	73.98	36.64
	26.97	Average	H				26.17	53.98	27.81
	39.22	Peak	V				38.42	73.98	35.56
	26.64	Average	V				25.84	53.98	28.14
Test Data for Middle Channel									
4 882.00	38.43	Peak	H	30.70	11.20	42.50	37.83	73.98	36.15
	25.30	Average	H				24.70	53.98	29.28
	39.23	Peak	V				38.63	73.98	35.35
	25.30	Average	V				24.70	53.98	29.28
Test Data for High Channel									
4 924.00	38.66	Peak	H	30.80	11.30	42.50	38.26	73.98	35.72
	25.72	Average	H				25.32	53.98	28.66
	39.37	Peak	V				38.97	73.98	35.01
	25.61	Average	V				25.21	53.98	28.77

Tabulated test data for Restricted Band

Remark: "H": Horizontal, "V": Vertical

$$\text{Margin (dB)} = \text{Limits (dB}\mu\text{V/m)} - \text{Total Level (dB}\mu\text{V/m)}$$

$$\text{Total Level} = \text{Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Pre-Amplifier Gain}$$



Tested by: Min-Gu, Ji / Project Engineer

7.3.6.2.2 Test data for 802.11g

- Test Date : March 13, 2016
- Resolution bandwidth : 1 MHz for Peak and Average Mode for the emissions fall in restricted band,
100 kHz for Peak Mode for the emissions outside restricted band
- Video bandwidth : 1 MHz for Peak Mode, 10 Hz for Average Mode
- Frequency range : 1 GHz ~ 26.5 GHz
- Measurement distance : 3 m
- Result : PASSED

Frequency (GHz)	Reading (dBμV)	Detector Mode	Ant. Pol. (H/V)	Ant. Factor	Cable Loss	Amp Gain	Total (dBμV/m)	Limits (dBμV/m)	Margin (dB)
Test Data for Low Channel									
4 824.00	38.23	Peak	H	30.60	11.10	42.50	37.43	73.98	36.55
	26.23	Average	H				25.43	53.98	28.55
	39.13	Peak	V				38.33	73.98	35.65
	26.54	Average	V				25.74	53.98	28.24
Test Data for Middle Channel									
4 882.00	38.64	Peak	H	30.70	11.20	42.50	38.04	73.98	35.94
	25.43	Average	H				24.83	53.98	29.15
	39.33	Peak	V				38.73	73.98	35.25
	25.43	Average	V				24.83	53.98	29.15
Test Data for High Channel									
4 924.00	38.85	Peak	H	30.80	11.30	42.50	38.45	73.98	35.53
	25.29	Average	H				24.89	53.98	29.09
	38.69	Peak	V				38.29	73.98	35.69
	25.22	Average	V				24.82	53.98	29.16

Tabulated test data for Restricted Band

Remark: "H": Horizontal, "V": Vertical

Margin (dB) = Limits (dBμV/m) - Total Level (dBμV/m)

Total Level = Reading + Antenna Factor + Cable Loss – Pre-Amplifier Gain



Tested by: Min-Gu, Ji / Project Engineer

7.3.6.2.3 Test data for 802.11n_HT20

- Test Date : March 13, 2016
- Resolution bandwidth : 1 MHz for Peak and Average Mode for the emissions fall in restricted band,
100 kHz for Peak Mode for the emissions outside restricted band
- Video bandwidth : 1 MHz for Peak Mode, 10 Hz for Average Mode
- Frequency range : 1 GHz ~ 26.5 GHz
- Measurement distance : 3 m
- Result : PASSED

Frequency (GHz)	Reading (dBμV)	Detector Mode	Ant. Pol. (H/V)	Ant. Factor	Cable Loss	Amp Gain	Total (dBμV/m)	Limits (dBμV/m)	Margin (dB)
Test Data for Low Channel									
4 824.00	38.24	Peak	H	30.60	11.10	42.50	37.44	73.98	36.54
	26.16	Average	H				25.36	53.98	28.62
	39.02	Peak	V				38.22	73.98	35.76
	25.23	Average	V				24.43	53.98	29.55
Test Data for Middle Channel									
4 882.00	38.33	Peak	H	30.70	11.20	42.50	37.73	73.98	36.25
	25.13	Average	H				24.53	53.98	29.45
	39.23	Peak	V				38.63	73.98	35.35
	25.56	Average	V				24.96	53.98	29.02
Test Data for High Channel									
4 924.00	38.76	Peak	H	30.80	11.30	42.50	38.36	73.98	35.62
	25.34	Average	H				24.94	53.98	29.04
	38.75	Peak	V				38.35	73.98	35.63
	25.33	Average	V				24.93	53.98	29.05

Tabulated test data for Restricted Band

Remark: "H": Horizontal, "V": Vertical

Margin (dB) = Limits (dBμV/m) - Total Level (dBμV/m)

Total Level = Reading + Antenna Factor + Cable Loss – Pre-Amplifier Gain



Tested by: Min-Gu, Ji / Project Engineer


7.4 PEAK POWER SPECTRAL DENSITY

7.4.1 Operating environment

Temperature : 22.4 °C
Relative humidity : 44.2 % R.H.

7.4.2 Test set-up

The antenna output of the EUT was connected to the spectrum analyzer. The resolution bandwidth is set to 3 kHz, the video bandwidth is set to 3 times the resolution bandwidth.



7.4.3 Test equipment used

	Model Number	Manufacturer	Description	Serial Number	Last Cal.
■ -	FSV40	Rohde & Schwarz	Signal Analyzer	101009	Jul. 22, 2015 (1Y)

All test equipment used is calibrated on a regular basis.

7.4.4 Test data for 802.11b


- Test Date : March 14, 2016
- Test Result : Pass
- Operating Condition : Continuous transmitting mode


CHANNEL	FREQUENCY(MHz)	MEASURED VLAUE (dBm)	LIMIT (dBm)	MARGIN (dB)
Low	2 412	-19.22	8.00	27.22
Middle	2 442	-18.21	8.00	26.21
High	2 462	-17.87	8.00	25.87

Remark. Margin = Limit – Measured value




Tested by: Min-Gu, Ji / Project Engineer





Middle Channel



High Channel

7.4.5 Test data for 802.11g


- Test Date : March 14, 2016
- Test Result : Pass
- Operating Condition : Continuous transmitting mode


CHANNEL	FREQUENCY(MHz)	MEASURED VLAUE (dBm)	LIMIT (dBm)	MARGIN (dB)
Low	2 412	-26.24	8.00	34.24
Middle	2 442	-23.82	8.00	31.82
High	2 412	-24.63	8.00	32.63

Remark. Margin = Limit – Measured value




Tested by: Min-Gu, Ji / Project Engineer





Middle Channel



High Channel

7.4.6 Test data for 802.11n_HT20


- Test Date : March 14, 2016
- Test Result : Pass
- Operating Condition : Continuous transmitting mode

CHANNEL	FREQUENCY(MHz)	MEASURED VLAUE (dBm)	LIMIT (dBm)	MARGIN (dB)
Low	2 412	-25.31	8.00	33.31
Middle	2 442	-25.58	8.00	33.58
High	2 462	-24.04	8.00	32.04


Remark. Margin = Limit – Measured value




Tested by: Min-Gu, Ji / Project Engineer



Low Channel



Middle Channel



High Channel

7.5 RADIATED EMISSION TEST

7.5.1 Operating environment

Temperature : (23 ~ 24) °C
Relative humidity : (44 ~ 45) % R.H.

7.5.2 Test set-up

The radiated emissions measurements were on the 3 m semi anechoic chamber. The EUT and other support equipment were placed on a non-conductive turntable above the ground plane. The interconnecting cables from outside test site were inserted into ferrite clamps at the point where the cables reach the turntable.

The frequency spectrum from 30 MHz to 26.5 GHz was scanned and emission levels maximized at each frequency recorded. The system was rotated 360°, and the antenna was varied in height between 1.0 m and 4.0 m in order to determine the maximum emission levels. This procedure was performed for both horizontal and vertical polarization of the receiving antenna.

7.5.3 Test equipment used

Model Number	Manufacturer	Description	Serial Number	Last Cal.(Interval)
■ - FSV40	Rohde & Schwarz	Signal Analyzer	101009	Jul. 22, 2015 (1Y)
■ - ESCI	Rohde & Schwarz	Test Receiver	101012	Nov. 02, 2015 (1Y)
■ - 310N	Sonoma Instrument	Pre-Amplifier	312544	Apr. 29, 2015 (1Y)
■ - SCU-18	Rohde & Schwarz	Pre-Amplifier	10041	Nov. 03, 2015 (1Y)
■ - DT3000	Innco System	Turn Table	930611	N/A
■ - MA4000-EP	Innco System	Antenna Master	3320611	N/A
■ - VULB9163	Schwarzbeck	TRILOG Broadband Antenna	9163-421	Jul. 10, 2014 (2Y)
■ - BBHA9120D	Schwarzbeck	Horn Antenna	BBHA9120D295	Aug. 31, 2015 (2Y)
■ - BBHA9170	Schwarzbeck	Horn Antenna	BBHA9170178	Aug. 31, 2015 (2Y)

All test equipment used is calibrated on a regular basis.

7.5.4 Test data

7.5.4.1 Test data for 30 MHz ~ 1 000 MHz

Humidity Level : (44 ~ 45) % R.H.

Temperature: (23 ~ 24) °C


Limits apply to : FCC CFR 47, PART 15, SUBPART C, SECTION 15.247

Result : PASSED

EUT : Mobile Photo Printer

Date: March 13, 2016

Detector : CISPR Quasi-Peak (6 dB Bandwidth: 120 kHz)



No.	FREQ	READING	ANT	LOSS	GAIN	RESULT	LIMIT	MARGIN	ANTENNA	TABLE
	[MHz]	[dBuV]	FACTOR	[dB]	[dB]	[dBuV/m]	[dBuV/m]	[dB]	[cm]	[DEG]
----- Horizontal -----										
1	131.850	56.8	9.0	3.1	33.1	35.8	43.5	7.7	300	144
2	238.550	55.8	12.0	4.1	32.8	39.1	46.0	6.9	100	0
3	290.930	49.5	13.4	4.6	32.7	34.8	46.0	11.2	100	0
----- Vertical -----										
4	74.620	50.2	8.7	2.4	33.2	28.1	40.0	11.9	100	166
5	551.859	43.0	18.3	6.3	33.1	34.5	46.0	11.5	100	359

7.5.4.2 Test data for Below 30 MHz

- Test Date : March 13, 2016
- Resolution bandwidth : 200 Hz (from 9 kHz to 0.15 MHz), 9 kHz (from 0.15 MHz to 30 MHz)
- Frequency range : 9 kHz ~ 30 MHz
- Measurement distance : 3 m
- Operating mode : Transmitting mode

Frequency (MHz)	Reading (dBμV)	Ant. Pol. (H/V)	Ant. Height (m)	Angle (°)	Ant. Factor (dB/m)	Cable Loss	Emission Level(dBμV/m)	Limits (dBμV/m)	Margin (dB)
Any emissions less than 20 dB below the limit were not observed.									

7.5.4.3 Test data for above 1 GHz

- Test Date : March 13, 2016
- Resolution bandwidth : 1 MHz for Peak and Average Mode
- Video bandwidth : 1 MHz for Peak Mode, 10 Hz for Average Mode
- Frequency range : 1 GHz ~ 26.5 GHz
- Measurement distance : 3 m
- Operating mode : Transmitting mode

Frequency (MHz)	Reading (dBμV)	Ant. Pol. (H/V)	Ant. Height (m)	Angle (°)	Ant. Factor (dB/m)	Cable Loss	Emission Level(dBμV/m)	Limits (dBμV/m)	Margin (dB)
Any emissions less than 20 dB below the limit were not observed.									



Tested by: Min-Gu, Ji / Project Engineer

7.6 CONDUCTED EMISSION TEST

7.6.1 Operating environment

Temperature : (23 ~ 24) °C
Relative humidity : (47 ~ 48) % R.H.

7.6.2 Test set-up

The EUT was placed on a wooden table, 0.8 m height above the floor. Power was fed to the EUT through a 50 Ω / 50 μ H + 5 Ω Artificial Mains Network (AMN). The ground plane was electrically bonded to the reference ground system and all power lines were filtered from ambient.


7.6.3 Test equipment used

	Model Number	Manufacturer	Description	Serial Number	Last Cal. (Interval)
■ -	ESPI	Rohde & Schwarz	EMI Test Receiver	101278	Nov. 02, 2015 (1Y)
□ -	ESHS10	Rohde & Schwarz	EMI Test Receiver	834467/007	Apr. 29, 2015 (1Y)
□	NSLK8128	Schwarzbeck	AMN	8128-216	Apr. 06, 2015 (1Y)
■ -	NSLK8126	Schwarzbeck	AMN	8126-404	Apr. 29, 2015 (1Y)
□ -	3825/2	EMCO	AMN	9109-1869	Apr. 29, 2015 (1Y)
■ --	3825/2	EMCO	AMN	9109-1867	Apr. 29, 2015 (1Y)

All test equipment used is calibrated on a regular basis.


7.6.4 Test data

- Test Date : January 13, 2016
- Resolution bandwidth : 9 kHz
- Frequency range : 0.15 MHz ~ 30 MHz
- Tested Line : HOT LINE



NO	FREQ [MHz]	READING		C.FACTOR [dB]	RESULT		LIMIT		MARGIN		PHASE
		QP [dBuV]	AV [dBuV]		QP [dBuV]	AV [dBuV]	QP [dBuV]	AV [dBuV]	QP [dBuV]	AV [dBuV]	
1	0.20500	40.8	----	10.0	50.8	----	63.4	----	12.6	----	H(QP)
2	0.83800	39.9	----	10.1	50.0	----	56.0	----	6.0	----	H(QP)
3	0.96400	39.5	----	10.1	49.6	----	56.0	----	6.4	----	H(QP)
4	2.96800	30.1	----	10.1	40.2	----	56.0	----	15.8	----	H(QP)
5	7.92500	26.9	----	10.2	37.1	----	60.0	----	22.9	----	H(QP)
6	12.98000	31.9	----	10.5	42.4	----	60.0	----	17.6	----	H(QP)
7	0.20500	----	20.8	10.0	----	30.8	----	53.4	----	22.6	H(CAV)
8	0.83800	----	19.4	10.1	----	29.5	----	46.0	----	16.5	H(CAV)
9	0.96400	----	20.8	10.1	----	30.9	----	46.0	----	15.1	H(CAV)
10	2.96800	----	12.3	10.1	----	22.4	----	46.0	----	23.6	H(CAV)
11	7.92500	----	9.4	10.2	----	19.6	----	50.0	----	30.4	H(CAV)
12	12.98000	----	8.0	10.5	----	18.5	----	50.0	----	31.5	H(CAV)

-. Tested Line : NEUTRAL LINE



NO	FREQ [MHz]	READING		C. FACTOR [dB]	RESULT		LIMIT		MARGIN		PHASE
		QP [dBuV]	AV [dBuV]		QP [dBuV]	AV [dBuV]	QP [dBuV]	AV [dBuV]	QP [dBuV]	AV [dBuV]	
1	0.20300	40.8	----	10.0	50.8	----	63.5	----	12.7	----	N (QP)
2	0.42000	37.4	----	10.0	47.4	----	57.4	----	10.0	----	N (QP)
3	0.94100	39.7	----	10.1	49.8	----	56.0	----	6.2	----	N (QP)
4	4.40000	28.6	----	10.1	38.7	----	56.0	----	17.3	----	N (QP)
5	9.67500	24.3	----	10.3	34.6	----	60.0	----	25.4	----	N (QP)
6	14.90000	27.3	----	10.5	37.8	----	60.0	----	22.2	----	N (QP)
7	0.20300	----	17.2	10.0	----	27.2	----	53.5	----	26.3	N {CAV}
8	0.42000	----	16.7	10.0	----	26.7	----	47.4	----	20.7	N {CAV}
9	0.94100	----	18.4	10.1	----	28.5	----	46.0	----	17.5	N {CAV}
10	4.40000	----	9.6	10.1	----	19.7	----	46.0	----	26.3	N {CAV}
11	9.67500	----	6.7	10.3	----	17.0	----	50.0	----	33.0	N {CAV}
12	14.90000	----	5.9	10.5	----	16.4	----	50.0	----	33.6	N {CAV}

Remark: Margin (dB) = Limit – Level (Result)

The emission level in above table is included the transducer factor that means insertion loss (LISN), cable loss and attenuator.

DL

Tested by: Min-Gu, Ji / Project Engineer