

FCC TEST REPORT

FCC ID: 2AHMO32760

Product : Wireless Remote Control LED Light

Model Name : 32760

Brand : N/A

Report No. : PT800024160105E-FC01

Prepared for

The NCC NY LLC
140 58th Street, Suite 6W,Brooklyn,
NY 11220, USA

Prepared by

DongGuan Precise Testing Service Co.,Ltd.
Building D, Baoding Technology Park, Guangming Road 2, Guangming Community
Dongcheng District, Dongguan, Guangdong, China

TEST RESULT CERTIFICATION

Applicant's name : The NCC NY LLC

Address : 140 58th Street, Suite 6W, Brooklyn, NY 11220, USA

Manufacture's name : NINGBO SHENGYE ELECTRIC APPLIANCE CO.,LTD

Address : North Guangming Road, Simen Town, Yuyao City, Zhejiang, China

Product name : Wireless Remote Control LED Light

Model name : 32760

Standards : FCC CFR47 Part 15 Section 15.231

Test procedure : ANSI C63.10:2013

Test Date : Jan. 31, 2016 - Mar. 21, 2016

Date of Issue : Mar. 22, 2016


Test Result : Pass

This device described above has been tested by PTS, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of PTS, this document may be altered or revised by PTS, personal only, and shall be noted in the revision of the document.


Testing Engineer

August Qiu



Technical Manager

Hack Ye



Authorized Signatory

Chris Du



Contents

| | Page |
|--|-----------|
| 2 TEST SUMMARY..... | 4 |
| 3 GENERAL INFORMATION..... | 5 |
| 3.1 GENERAL DESCRIPTION OF E.U.T..... | 5 |
| 3.2 TEST MODE..... | 5 |
| 4 EQUIPMENT DURING TEST | 6 |
| 4.1 EQUIPMENTS LIST..... | 6 |
| 4.2 MEASUREMENT UNCERTAINTY | 6 |
| 5 CONDUCTED EMISSION..... | 7 |
| 6 PERIODIC OPERATION..... | 8 |
| 7 RADIATED SPURIOUS EMISSIONS | 12 |
| 7.1 EUT OPERATION | 12 |
| 7.2 TEST SETUP..... | 13 |
| 7.3 SPECTRUM ANALYZER SETUP..... | 14 |
| 7.4 TEST PROCEDURE | 15 |
| 7.5 SUMMARY OF TEST RESULTS..... | 16 |
| 8 20DB BANDWIDTH MEASUREMENT..... | 18 |
| 8.1 TEST PROCEDURE | 18 |
| 8.2 TEST RESULT..... | 18 |
| 9 ANTENNA REQUIREMENT..... | 19 |



2 Test Summary

| Test Items | Test Requirement | Result |
|---------------------|----------------------------------|--------|
| Conducted Emissions | 15.207 | N/A |
| Radiated Emission | 15.231(a) 15.209 15.205(a) | PASS |
| Periodic Operation | 15.35(c) | PASS |
| 20dB Bandwidth | 15.215(c) | PASS |
| Antenna Requirement | 15.203 | PASS |

Remark:

N/A: Not Applicable

3 General Information

3.1 General Description of E.U.T.

Product Name : Wireless Remote Control LED Light

Model Name : 32760

Model Description : N/A

Operation Frequency: : 315MHz

Antenna installation: : Integrated Antenna

Antenna Gain: : 0dBi

Type of Modulation : ASK

The lowest oscillator : 315MHz

Power supply : DC 12V power by battery

3.2 Test Mode

All test mode(s) and condition(s) mentioned were considered and evaluated respectively by performing full tests, the worst data were recorded and reported.

| Modulation | Test mode | Low channel | Middle channel | High channel |
|------------|------------------------------|-------------|----------------|--------------|
| ASK | continuously Transmitting | 315MHz | \ | \ |

4 Equipment During Test

4.1 Equipments List

| Radiated Emissions | | | | | | | |
|--------------------|---------------------------|-----------------|------------|------------|------------------|------------------|--------------------|
| Item | Kind of Equipment | Manufacturer | Type No. | Serial No. | Last calibration | Calibrated until | Calibration period |
| 1 | EMI Test Receiver | Rohde & Schwarz | ESCI | 101417 | July 15, 2015 | July 14, 2016 | 1 year |
| 2 | EMC Analyzer (9k~26.5GHz) | Agilent | E4407B | MY45109572 | Aug.04, 2015 | Aug.03, 2016 | 1 year |
| 3 | Trilog Broadband Antenna | SCHWARZB ECK | VULB9160 | 9160-3355 | July 15, 2015 | July 14, 2016 | 1 year |
| 4 | Amplifier | EM | EM-30180 | 060538 | July 15, 2015 | July 14, 2016 | 1 year |
| 5 | Horn Antenna | SCHWARZB ECK | BBHA9120 D | 9120D-1246 | July 15, 2015 | July 14, 2016 | 1 year |
| 6 | Coaxial Cable(below 1GHz) | LARGE | CALB1 | - | July 15, 2015 | July 14, 2016 | 1 year |
| 7 | Coaxial Cable(above 1GHz) | LARGE | CALB2 | - | July 15, 2015 | July 14, 2016 | 1 year |

4.2 Measurement Uncertainty

| Parameter | Uncertainty |
|------------------------------------|--------------------------|
| RF output power, conducted | ±1.0dB |
| Power Spectral Density, conducted | ±2.2dB |
| Radio Frequency | ± 1 x 10 ⁻⁶ |
| Bandwidth | ± 1.5 x 10 ⁻⁶ |
| Time | ±2% |
| Duty Cycle | ±2% |
| Temperature | ±1°C |
| Humidity | ±5% |
| DC and low frequency voltages | ±3% |
| Conducted Emissions (150kHz~30MHz) | ±3.64dB |
| Radiated Emission(30MHz~1GHz) | ±5.03dB |
| Radiated Emission(1GHz~25GHz) | ±4.74dB |

5 Conducted Emission

| | | |
|-------------------|---|---|
| Test Requirement: | : | FCC CFR 47 Part 15 Section 15.207 |
| Test Method: | : | ANSI C63.10:2013 |
| Frequency Range: | : | 150kHz to 30MHz |
| Class/Severity: | : | Class B |
| Limit: | : | 66-56 dB μ V between 0.15MHz & 0.5MHz |
| | : | 56 dB μ V between 0.5MHz & 5MHz |
| | : | 60 dB μ V between 5MHz & 30MHz |
| Detector: | : | Peak for pre-scan (9kHz Resolution Bandwidth) |
| Test Result: | : | The device is powered by battery, this test is not applicable |

6 Periodic Operation

The duty cycle was determined by the following equation:

To calculate the actual field intensity, the duty cycle correction factor in decibel is needed for later use and can be obtained from following conversion

Duty Cycle(%)=Total On interval in a complete pulse train/ Length of a complete pulse train * %

Duty Cycle Correction Factor (dB)= $20 * \log_{10}(\text{Duty Cycle}(\%))$


| | |
|---|-------------------------|
| Total transmission time(ms) | $0.92*12+0.32*21=17.76$ |
| Length of a complete transmission period(ms) | 49.6 |
| Duty Cycle(%) | 35.80 |
| Duty Cycle Correction Factor(dB) | -8.92 |
| Pulse Desensitization Correction Factor | |
| Pulse Width(PW)=17.76ms $2/PW=2/17.76\text{ms}=0.1126\text{kHz}$; RBW(100kHz)> 2/PW (0.1126kHz); Therefore PDCF is not needed. | |

Refer to the duty cycle plot (as below), This device meets the FCC requirement.


Length of a complete pulse train:

Remark: FCC part15.35(c) required that a complete pulse train is more than 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.


Period 1




Period 2



Long pulses




Short pulses



FCC Part15.231 (a) (1) A manually operated transmitter shall employ a switch that will automatically deactivate the transmitter within not more than 5 seconds of being released.

(2)A transmitter activated automatically shall cease transmission within 5 seconds after activation.



7 Radiated Spurious Emissions

Test Requirement: : FCC CFR47 Part 15 Section 15.231 & 15.207 & 15.205
 Test Method: : ANSI C63.10:2013
 Test Result: : PASS
 Measurement Distance: : 3m
 Limit: : See the follow table

| Frequency (MHz) | Field Strength | | Field Strength Limit at 3m Measurement Dist | |
|-----------------|-----------------------|--------------|---|---------------------------------------|
| | uV/m | Distance (m) | uV/m | dBuV/m |
| 0.009 ~ 0.490 | $2400/F(\text{kHz})$ | 300 | $10000 * 2400/F(\text{kHz})$ | $20\log^{(2400/F(\text{kHz}))} + 80$ |
| 0.490 ~ 1.705 | $24000/F(\text{kHz})$ | 30 | $100 * 24000/F(\text{kHz})$ | $20\log^{(24000/F(\text{kHz}))} + 40$ |
| 1.705 ~ 30 | 30 | 30 | $100 * 30$ | $20\log^{(30)} + 40$ |
| 30 ~ 88 | 100 | 3 | 100 | $20\log^{(100)}$ |
| 88 ~ 216 | 150 | 3 | 150 | $20\log^{(150)}$ |
| 216 ~ 960 | 200 | 3 | 200 | $20\log^{(200)}$ |
| Above 960 | 500 | 3 | 500 | $20\log^{(500)}$ |

7.1 EUT Operation


Operating Environment :

Temperature: : 23.5 °C
 Humidity: : 51.1 % RH
 Atmospheric Pressure: : 101.2kPa
 EUT Operation : : Refer to section 3.3


7.2 Test Setup

The radiated emission tests were performed in the 3m Semi- Anechoic Chamber test site


The test setup for emission measurement below 30MHz.



The test setup for emission measurement from 30 MHz to 1 GHz.



The test setup for emission measurement above 1 GHz.



7.3 Spectrum Analyzer Setup

Below 30MHz

| | |
|----------------------|-------|
| IF Bandwidth | 10kHz |
| Resolution Bandwidth | 10kHz |
| Video Bandwidth | 10kHz |

30MHz ~ 1GHz

| | |
|----------------------|----------|
| Detector | : PK |
| Resolution Bandwidth | : 100kHz |
| Video Bandwidth | : 300kHz |
| Detector | : QP |
| Resolution Bandwidth | : 120kHz |
| Video Bandwidth | : 300kHz |

Above 1GHz

| | |
|----------------------|--------|
| Detector | : PK |
| Resolution Bandwidth | : 1MHz |
| Video Bandwidth | : 3MHz |

7.4 Test Procedure

1. The EUT is placed on a turntable, which is 0.8m or 1.5m above ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is moved from 1m to 4m to find out the maximum emissions. The spectrum was investigated from the lowest radio frequency signal generated in the device, without going below 9 kHz, up to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Repeat above procedures until the measurements for all frequencies are complete.
7. The radiation measurements are tested under 3-axes(X,Y,Z) position(X denotes lying on the table, Y denotes side stand and Z denotes vertical stand), After pre-test, It was found that the worse radiation emission was get at the X position. So the data shown was the X position only.



7.5 Summary of Test Results

Test Frequency: Below 30MHz

The lowest oscillator is 315MHz, the test is not applicable

Test Frequency: 30MHz ~ 5GHz

| Frequency (MHz) | Reading (dBμV) | Detector (PK/QP/Av e) | Turn table Angle (Degree) | RX Antenna | | Corrected Factor (dB/m) | Corrected Amplitude (dBμV/m) | FCC Part 15.231/209/205 | |
|--------------------|-------------------|-----------------------------|------------------------------------|---------------|----------------|-------------------------------|------------------------------------|----------------------------|----------------|
| | | | | Height (m) | Polar (H/V) | | | Limit (dBμV/m) | Margin (dB) |
| 188.14 | 46.45 | QP | 336 | 1.8 | H | -16.93 | 29.52 | 43.5 | -13.98 |
| 188.14 | 42.94 | QP | 146 | 1.7 | V | -16.93 | 26.01 | 43.5 | -17.49 |
| 315.00 | 82.15 | PK | 189 | 1.1 | H | -13.56 | 68.59 | 100.83 | -32.24 |
| 315.00 | 76.86 | PK | 140 | 1.5 | V | -13.56 | 63.30 | 100.83 | -37.53 |
| 630.00 | 66.87 | PK | 142 | 1.6 | H | -6.74 | 60.13 | 80.83 | -20.70 |
| 630.00 | 58.86 | PK | 123 | 1.7 | V | -6.74 | 52.12 | 80.83 | -28.71 |
| 945.00 | 59.92 | PK | 71 | 2.3 | H | -4.99 | 54.93 | 74 | -19.07 |
| 945.00 | 55.73 | PK | 66 | 1.7 | V | -4.99 | 50.74 | 74 | -23.26 |
| 1260.00 | 59.72 | PK | 31 | 2.4 | H | -12.72 | 47.00 | 74 | -27.00 |
| 1260.00 | 55.40 | PK | 23 | 1.4 | V | -12.72 | 42.68 | 74 | -31.32 |



| Frequency | PK | Turn table Angle | RX Antenna | | Duty cycle Factor | AV | FCC Part 15.231/209/205 | |
|-----------|----------|------------------------|------------|-------|-------------------------|----------|----------------------------|--------|
| | | | Height | Polar | | | Limit | Margin |
| (MHz) | (dBμV/m) | Degree | (m) | (H/V) | (dB) | (dBμV/m) | (dBμV/m) | (dB) |
| 315.00 | 68.59 | 189 | 1.1 | H | -8.92 | 59.67 | 80.83 | -21.16 |
| 315.00 | 63.30 | 140 | 1.5 | V | -8.92 | 54.38 | 80.83 | -26.45 |
| 630.00 | 60.13 | 142 | 1.6 | H | -8.92 | 51.21 | 60.83 | -9.62 |
| 630.00 | 52.12 | 123 | 1.7 | V | -8.92 | 43.20 | 60.83 | -17.63 |
| 945.00 | 54.93 | 71 | 2.3 | H | -8.92 | 46.01 | 54 | -7.99 |
| 945.00 | 50.74 | 66 | 1.7 | V | -8.92 | 41.82 | 54 | -12.18 |
| 1260.00 | 47.00 | 31 | 2.4 | H | -8.92 | 38.08 | 54 | -15.92 |
| 1260.00 | 42.68 | 23 | 1.4 | V | -8.92 | 33.76 | 54 | -20.24 |

8 20dB Bandwidth Measurement

Test Requirement : FCC Part15.231(c)

Test Method : FCC Part15.231(c)

Test Mode : Refer to section 3.3

Limit : The bandwidth of the emission shall be no wider than 0.25% of the center frequency for devices operating above 70 MHz and below 900 MHz. For devices operating above 900 MHz, the emission shall be no wider than 0.5% of the center frequency.


8.1 Test Procedure

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
2. Set the spectrum analyzer: For BLE, RBW = 3 kHz, VBW = 10kHz,

8.2 Test Result

| Test Frequency (MHz) | Bandwidth (kHz) | Limit (kHz) | Result |
|----------------------|-----------------|-------------|--------|
| 315 | 55.09 | 787.5 | pass |

Test plots





9 Antenna Requirement

According to the FCC part15.203, a transmitter can only be sold or operated with antennas with which it was approved. This product has an internal permanent antenna which meet the requirement of this section.

*****THE END REPORT*****