

Report No.: SZEM180900842602

No. 1 Workshop, M-10, Middle section, Science & Technology Park,

Shenzhen, Guangdong, China 518057 Telephone: +86 (0) 755 2601 2053 Fax: +86 (0) 755 2671 0594

Email: ee.shenzhen@sgs.com Page: 1 of 6

rage. roro

SAR Evaluation Report

Application No.: SZEM1809008426CR

Applicant: Develco Products

Address of Applicant: Olof Palmes Alle 40, Aarhus N, 8240, Denmark

Manufacturer: Develco Products A/S

Address of Manufacturer: Olof Palmes Alle 40, 8200 Aarhus N, Denmark

Factory: EDA Electronics Co., Ltd

Address of Factory: Shui Wei Inudstrial Zone, TangJiao, Chashan Town, DongGuan City

Equipment Under Test (EUT):

EUT Name: ZigBee Motion Sensor Mini

Model No.: MOSZB-140

Trade mark: Develco Products
FCC ID: 2AHNM-MOSZB140
Standards: 47 CFR Part 1.1307

47 CFR Part 2.1093

KDB447498D01 General RF Exposure Guidance v06

Date of Receipt: 2018-09-19

Date of Test: 2018-09-20 to 2018-09-29

Date of Issue: 2018-09-30

Test Result : PASS*



EMC Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sqs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sqs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawfull and offlenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

^{*} In the configuration tested, the EUT complied with the standards specified above.



Report No.: SZEM180900842602

Page: 2 of 6

2 Version

Revision Record							
Version	Chapter	Date	Modifier	Remark			
01		2018-09-30		Original			

Authorized for issue by:		
	Biu chen	
	Bill Chen /Project Engineer	
	EvicFu	
	Eric Fu /Reviewer	



Report No.: SZEM180900842602

Page: 3 of 6

3 Contents

		Page
1	COVER PAGE	1
2	VERSION	2
3	CONTENTS	3
4	GENERAL INFORMATION	4
4.	1 GENERAL DESCRIPTION OF EUT	4
4.2		
4.3		
4.4		5
4.5		5
4.6	6 OTHER INFORMATION REQUESTED BY THE CUSTOMER	5
5	SAR EVALUATION	
5.	1 RF EXPOSURE COMPLIANCE REQUIREMENT	6
	5.1.1 Standard Requirement	6
	5.1.2 Limits	6
	5.1.3 EUT RF Exposure	6



Report No.: SZEM180900842602

Page: 4 of 6

4 General Information

4.1 General Description of EUT

Power supply:	DC 3.0V by 1.5V x 2"AA" batteries	
Frequency Range:	2405MHz to 2480MHz	
Number of Channels	16	
Modulation Type	O-QPSK	
Channel Spacing	5MHz	
Antenna Type	PCB	
Antenna Gain	2dBi	



Report No.: SZEM180900842602

Page: 5 of 6

4.2 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

No. 1 Workshop, M-10, Middle section, Science & Technology Park, Shenzhen, Guangdong, China 518057

Telephone: +86 (0) 755 2601 2053 Fax: +86 (0) 755 2671 0594

No tests were sub-contracted.

4.3 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

CNAS (No. CNAS L2929)

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

A2LA (Certificate No. 3816.01)

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

VCCI

The 3m Fully-anechoic chamber for above 1GHz, 10m Semi-anechoic chamber for below 1GHz, Shielded Room for Mains Port Conducted Interference Measurement and Telecommunication Port Conducted Interference Measurement of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-20026, R-14188, C-12383 and T-11153 respectively.

• FCC -Designation Number: CN1178

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized as an accredited testing laboratory.

Designation Number: CN1178. Test Firm Registration Number: 406779.

Innovation, Science and Economic Development Canada

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized by ISED as an accredited testing laboratory.

CAB identifier: CN0006.

IC#: 4620C.

4.4 Deviation from Standards

None.

4.5 Abnormalities from Standard Conditions

None.

4.6 Other Information Requested by the Customer

None.



Report No.: SZEM180900842602

Page: 6 of 6

5 SAR Evaluation

5.1 RF Exposure Compliance Requirement

5.1.1 Standard Requirement

According to KDB447498D01 General RF Exposure Guidance v06

4.3.1. Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

5.1.2 Limits

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] $\cdot [\sqrt{f(GHz)}] \le 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

f(GHz) is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation¹⁷

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is \leq 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion

5.1.3 EUT RF Exposure

The Max. power (including tune-up tolerance) is 4.05	dBm on the lowest channel	2.405	GHz (*)
4.05 dBm logarithmic terms convert to numeric result is nearly 2.54 mW			
According to the formula. calculate the test exclusion thresholds:			
General RF Exposure = (Max. Power of channel, including tu	ne –up tolerance, mW) * $\sqrt{f(GHz)}$		
(min.test separation)	on distance,mm)		
General RF Exposure = (2.54 mW / 5 mm) $x \sqrt{2.405}$ GHz = 0.79		(1)	
SAR requirement:			
S = 3.0		(2)	
(1) < (2)			
So the SAR report is not required.			
(*) Max. power refer to Report No.:SZEM18090084260)1		

- End of the Report -