Report No.: NTC1903078FV00

FCC ID: 2AHU2JWM20



# RADIO TEST REPORT

The device described below is tested by Dongguan Nore Testing Center Co., Ltd. to determine the maximum emission levels emanating from the device, the severe levels which the device can endure and E.U.T.'s performance criterion. The test results, data evaluation, test procedures, and equipment of configurations shown in this report were made in accordance with the procedures in ANSI C63.10(2013).

**Applicant** 

: ASA Electronics Shenzhen Limited

Address

: Room 503, 5/F., Unit A, Skyworth Building, Gaoxin Avenue.1.S.,

Nanshan District, Shen Zhen, China

Manufacturer

: Good Grace Far East Limited

Address

: 702 KOWLOON BUILDING, 555 NATHAN ROAD, KOWLOON, HONG

KONG

**Factory** 

: ACTION ASIA (SHENZHEN) CO., LTD

Address

: 4 Floor, Block 1, No.25 Jinxing Industrial Park, Jian'an Road, Fuyong

Town, Bao'an District, Shenzhen, China

E.U.T.

: JENSEN 2-ZONE WALL STEREO

**Brand Name** 

: JENSEN

Model No.

: JWM20

FCC ID

: 2AHU2JWM20

Measurement Standard : FCC PART 15.247: 2017

Date of Receiver

: March 08, 2019

Date of Test

: March 11, 2019 to March 28, 2019

Date of Report

: March 29, 2019

This Test Report is Issued Under the Authority of:

Prepared by

Approve

Iori Fan /

Alina Guo / Engineer

This test report is for the customer shown above and their specific product only. This report applies to above tested sample only and shall not be reproduced in part without written approval of Dongguan Nore Testing Center Co., Ltd.



# **Table of Contents**

1. GENERAL INFORMATION	5
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST	5
1.2 RELATED SUBMITTAL(S) / GRANT (S)	7
1.3 TEST METHODOLOGY	7
1.4 EQUIPMENT MODIFICATIONS	7
1.5 SUPPORT DEVICE	
1.6 TEST FACILITY AND LOCATION	8
1.7 SUMMARY OF TEST RESULTS	g
2. SYSTEM TEST CONFIGURATION	10
2.1 EUT CONFIGURATION	10
2.2 SPECIAL ACCESSORIES	10
2.3 DESCRIPTION OF TEST MODES	
2.4 EUT EXERCISE	10
3. CONDUCTED EMISSIONS TEST	11
3.1 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	
3.2 TEST CONDITION	11
3.3 MEASUREMENT RESULTS	11
4. RADIATED EMISSION TEST	12
4.1 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	12
4.2 MEASUREMENT PROCEDURE	13
4.3 LIMIT	
4.4 MEASUREMENT RESULTS	14
5. CHANNEL SEPARATION TEST	18
5.1 MEASUREMENT PROCEDURE	18
5.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	18
5.3 MEASUREMENT RESULTS	18
6. 20DB BANDWIDTH	24
6.1 MEASUREMENT PROCEDURE	24
6.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	24
6.3 MEASUREMENT RESULTS	24
7. HOPPING CHANNEL NUMBER	30
7.1 MEASUREMENT PROCEDURE	30
7.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	30
7.3 MEASUREMENT RESULTS	30



8. TIME OF OCCUPANCY (DWELL TIME)	32
8.1 MEASUREMENT PROCEDURE	32
8.2 MEASUREMENT RESULTS	32
9. MAXIMUM PEAK OUTPUT POWER	38
9.1 MEASUREMENT PROCEDURE	38
9.2 MEASUREMENT RESULTS	38
10. BAND EDGE	44
10.1 MEASUREMENT PROCEDURE	44
10.2 LIMIT	44
10.3 MEASUREMENT RESULTS	44
11. ANTENNA APPLICATION	51
11.1 ANTENNA REQUIREMENT	51
11.2 MEASUREMENT RESULTS	51
12. CONDUCTED SPURIOUS EMISSIONS	52
12.1 MEASUREMENT PROCEDURE	52
12.2. MEASUREMENT RESULTS	52
13. TEST EQUIPMENT LIST	56

Dongguan Nore Testing Center Co., Ltd. Report No.: NTC1903078FV00 FCC ID: 2AHU2JWM20



# **Revision History of This Test Report**

Report Number	Description	Issued Date
NTC1903078FV00	Initial Issue	2019-03-29

Report No.: NTC1903078FV00

FCC ID: 2AHU2JWM20



## 1. GENERAL INFORMATION

## 1.1 Product Description for Equipment under Test

Product Name : JENSEN 2-ZONE WALL STEREO

Main Model Name : JWM20

Additional Model Name : N/A

Model difference : N/A

Brand Name : JENSEN

Power Supply : DC 12V

Adapter : N/A

Test voltage : DC 12V battery

Hardware version : V1.0

Software version : V1.0

Serial number : N/A

Note : N/A

**Technical parameters** 

Bluetooth Version : BT 2.1+EDR Frequency Range : 2402-2480MHz

Modulation : GFSK,  $\pi/4$ -DQPSK, 8DPSK

Number of Channel : 79 Channel space : 1MHz

Date Rate : 1Mbps for GFSK

2Mbps for  $\pi 4$ /-DQPSK

3Mbps for 8DPSK

Antenna Type : PCB antenna

Antenna Gain : 0 dBi

FCC ID: 2AHU2JWM20



#### **BDR+EDR Channel List**

Channel	Frequency MHz	Channel	Frequency MHz	Channel	Frequency MHz	Channel	Frequency MHz
1	2402	21	2422	41	2442	61	2462
2	2403	22	2423	42	2443	62	2463
3	2404	23	2424	43	2444	63	2464
4	2405	24	2425	44	2445	64	2465
5	2406	25	2426	45	2446	65	2466
6	2407	26	2427	46	2447	66	2467
7	2408	27	2428	47	2448	67	2468
8	2409	28	2429	48	2449	68	2469
9	2410	29	2430	49	2450	69	2470
10	2411	30	2431	50	2451	70	2471
11	2412	31	2432	51	2452	71	2472
12	2413	32	2433	52	2453	72	2473
13	2414	33	2434	53	2454	73	2474
14	2415	34	2435	54	2455	74	2475
15	2416	35	2436	55	2456	75	2476
16	2417	36	2437	56	2457	76	2477
17	2418	37	2438	57	2458	77	2478
18 2419 38		38	2439	58	2459	78	2479
19	2420	39	2440	59	2460	79	2480
20	2421	40	2441	60	2461		

Note: According to section 15.31(m), regards to the operating frequency range over 10MHz, the Lowest, middle, and the Highest frequency of channel were selected to perform the test. The selected frequency and test software see below:

Channel	Frequency MHz
1	2402
40	2441
79	2480

Test SW version	BK3256 RF Test_V1.3
-----------------	---------------------

Report No.: NTC1903078FV00

FCC ID: 2AHU2JWM20



## 1.2 Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended for FCC ID: 2AHU2JWM20 filing to comply with Section 15.247 of the FCC Part 15 (2016), Subpart C Rule.

## 1.3 Test Methodology

Radiated emission measurements were performed according to the procedures in ANSI C63.10 (2013). Radiated emission measurement was performed in semi-anechoic chamber. For radiated emission measurement, preliminary scans were performed in the semi-anechoic chamber only to determine the worst case modes. All radiated tests were performed at an antenna to EUT distance of 3 meters.

## 1.4 Equipment Modifications

Not available for this EUT intended for grant.

#### 1.5 Support Device

lead-acidBattery : DC 12V provided by NTC lab.

Report No.: NTC1903078FV00 FCC ID: 2AHU2JWM20



## 1.6 Test Facility and Location

Site Description

EMC Lab : Listed by CNAS, August 13, 2018

The Certificate is valid until August 13, 2024

The Laboratory has been assessed and proved to

be in compliance with CNAS/CL01

The Certificate Registration Number is L5795.

Listed by A2LA, November 01, 2017

The certificate is valid until December 31, 2019 The Laboratory has been assessed and proved to

be in compliance with ISO17025

The Certificate Registration Number is 4429.01

Listed by FCC, November 06, 2017 The Designation Number is CN1214 Test Firm Registration Number: 907417

Listed by Industry Canada, June 08, 2017

The Certificate Registration Number. Is 46405-9743

Name of Firm : Dongguan Nore Testing Center Co., Ltd.

(Dongguan NTC Co., Ltd.)

Site Location : Building D, Gaosheng Science and Technology

park, Hongtu road, Nancheng district, Dongguan

city, Guangdong province, China

Dongguan Nore Testing Center Co., Ltd. Report No.: NTC1903078FV00 FCC ID: 2AHU2JWM20

## 1.7 Summary of Test Results

FCC Rules	Description Of Test	Uncertainty	Result
§15.247(a)(1)	Channel Separation test	±1.42 x10 <sup>-4</sup> %	Compliant
§15.247(a)(1)	20dB Bandwidth	±1.42 x10 <sup>-4</sup> %	Compliant
§15.247(a)(1)(iii)	Hopping Channel Number	±1.42 x10 <sup>-4</sup> %	Compliant
§15.247(a)(1)(iii)	Time of Occupancy (Dwell Time)	±5%	Compliant
§15.247(b)	Max Peak output Power test	±1.06dB	Compliant
§15.247(d)	Band edge test	±1.70dB	Compliant
§15.207 (a)	AC Power Conducted Emission	±1.06dB	Not applicable
§15.247(d),§15.209, §15.205	Radiated Emission	±3.70dB	Compliant
§15.203	Antenna Requirement	N/A	Compliant
§15.247(d)	Conducted Spurious Emission	±1.70dB	Compliant

Note: Due to this EUT is powered by automotive battery only, so the AC Power Conducted Emission is not applicable.

Report No.: NTC1903078FV00 FCC ID: 2AHU2JWM20



## 2. System Test Configuration

## 2.1 EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

#### 2.2 Special Accessories

Not available for this EUT intended for grant.

## 2.3 Description of test modes

The EUT has been tested under operating condition. Test program used to control the EUT for staying in continuous transmitting and normal mode is programmed. The Lowest, middle and highest channel were chosen for testing, and all packets DH1, DH3 and DH5 mode in all modulation type GFSK,  $\pi/4$ -DQPSK, 8DPSK were tested.

#### 2.4 EUT Exercise


The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements.

FCC ID: 2AHU2JWM20



## 3. Conducted Emissions Test

## 3.1 Test SET-UP (Block Diagram of Configuration)



#### 3.2 Test Condition

Test Requirement: FCC Part 15.207

Frequency Range: 150KHz ~ 30MHz

**Detector: RBW 9KHz, VBW 30KHz** 

**Operation Mode: BT** 

#### 3.3 Measurement Results


Not applicable.


**Testing Center** 

## 4. Radiated Emission Test

## **4.1 Test SET-UP (Block Diagram of Configuration)**

## 4.1.1 Radiated Emission Test Set-Up, Frequency Below 30MHz






Report No.: NTC1903078FV00 FCC ID: 2AHU2JWM20



## 4.1.2 Radiated Emission Test Set-Up, Frequency above 1GHz



#### 4.2 Measurement Procedure

- a. Blow 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi- anechoic chamber room.
- b. For the radiated emission test above 1GHz:
  - The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter full anechoic chamber room. The table was rotated 360 degrees to determine the position of the highest radiation. Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- c. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. The test-receiver system was set to peak detect function and specified bandwidth with maximum hold mode.
- f. A Quasi-peak measurement was then made for that frequency point for below 1GHz test. PK and AV for above 1GHz emission test.

Report No.: NTC1903078FV00

FCC ID: 2AHU2JWM20



During the radiated emission test, the spectrum analyzer was set with the following

configurations:

Frequency Band (MHz)	Level	Resolution Bandwidth	Video Bandwidth
30 to 1000	QP	120 kHz	300 kHz
Above 1000	Peak	1 MHz	3 MHz
Above 1000	Average	1 MHz	10 Hz

#### 4.3 Limit

Frequency range	Distance Meters	Field Strengths Limit (15.209)
MHz		μV/m
0.009 ~ 0.490	300	2400/F(kHz)
0.490 ~ 1.705	30	24000/F(kHz)
1.705 ~ 30	30	30
30 ~ 88	3	100
88 ~ 216	3	150
216 ~ 960	3	200
Above 960	3	500

Remark: (1) Emission level (dB) $\mu$ V = 20 log Emission level  $\mu$ V/m

- (2) The smaller limit shall apply at the cross point between two frequency bands.
- (3) As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.
- (4) The frequency range scanned is from the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or 40 GHz, whichever is lower.

## 4.4 Measurement Results

Please refer to following plots of the worst case: GFSK Low channel.

Report No.: NTC1903078FV00 FCC ID: 2AHU2JWM20





Dongguan NTC Co., Ltd. Tel:+86-769-22022444 Fax:+86-769-22022799 Web: Http://www.ntc-c.com

#### **Radiated Emission Measurement** File :JWM20 Data :#2 Date: 2019/3/13 Time: 9:25:13 80.0 dBuV/m 70 60 FCC Part 15\_ClassB\_3M Margin -6 dB 50 40 30 20 10 0.0 418.00 127.00 224.00 321.00 612.00 1000.00 MHz 515.00 709.00 30.000 806.00

Site: 3m Chamber Limit: FCC Part 15\_ClassB\_3M

EUT: JENSEN 2-ZONE WALL STEREO

M/N: JWM20 Mode: TX Note:

Polarizati	on:	Horizontal	Temperature:	26
Dower	DC	12\/	Humidity	<b>17</b> %

Distance: 3m

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		288.0200	46.20	-10.80	35.40	46.00	-10.60	QP			
2		339.4300	33.51	-9.31	24.20	46.00	-21.80	QP			
3		384.0500	39.29	-9.19	30.10	46.00	-15.90	QP			
4	*	480.0800	49.51	-7.21	42.30	46.00	-3.70	QP			
5		673.1100	43.53	-4.53	39.00	46.00	-7.00	QP			
6	İ	865.1700	42.72	-1.12	41.60	46.00	-4.40	QP			


<sup>\*:</sup>Maximum data x:Over limit !:over margin Reference Only

Report No.: NTC1903078FV00 FCC ID: 2AHU2JWM20





Dongguan NTC Co., Ltd. Tel:+86-769-22022444 Fax:+86-769-22022799 Web: Http://www.ntc-c.com



Site: 3m Chamber Limit: FCC Part 15\_ClassB\_3M

EUT: JENSEN 2-ZONE WALL STEREO

M/N: JWM20 Mode: TX Note:

Polarization: Vertical DC12V Power:

Temperature: Humidity: 47 %

Distance: 3m

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBu∀	dB/m	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		288.0200	36.70	-12.80	23.90	46.00	-22.10	QP			
2	*	480.0800	45.41	-9.21	36.20	46.00	-9.80	QP			
3		576.1100	36.00	-7.70	28.30	46.00	-17.70	QP			
4		673.1100	40.03	-4.53	35.50	46.00	-10.50	QP			
5		864.2000	34.21	-1.11	33.10	46.00	-12.90	QP			
6		960.2300	29.33	-0.23	29.10	54.00	-24.90	QP			

Report No.: NTC1903078FV00 FCC ID: 2AHU2JWM20



Modulation: GFSK (the worst case)

Frequency Range: 1-25GHz Test Date: March 28, 2019

Test Result: PASS Temperature : 24  $^{\circ}$ C Measured Distance: 3m Humidity : 47  $^{\circ}$ 

Test By: Sance

Freq.	Ant.Pol. (H/V)	Reading Level(dBuV)		Factor	Emission Level (dBuV)		Limit 3m (dBuV/m)		Margin (dB)	
(MHz)		PK	AV	(dB/m)	PK	AV	PK	AV	PK	AV
			Oper	ation Mo	de: TX N	lode (Lo	w)			
4804	V	46.94	32.39	6.30	53.24	38.69	74.00	54.00	-20.76	-15.31
7206	V	52.40	42.88	10.44	62.84	53.32	74.00	54.00	-11.16	-0.68
4804	Н	47.12	32.16	6.30	53.42	38.46	74.00	54.00	-20.58	-15.54
7206	Н	49.14	40.83	10.44	59.58	51.27	74.00	54.00	-14.42	-2.73
			Ope	ration Mo	ode: TX N	ode (Mi	d)			
4882	V	47.52	31.83	6.60	54.12	38.43	74.00	54.00	-19.88	-15.57
7323	V	48.47	39.01	10.55	59.02	49.56	74.00	54.00	-14.98	-4.44
4882	Н	47.09	31.80	6.60	53.69	38.40	74.00	54.00	-20.31	-15.60
7323	Н	47.84	34.85	10.55	58.39	45.40	74.00	54.00	-15.61	-8.60
	Operation Mode: TX Mode (High)									
4960	V	46.40	32.99	6.89	53.29	39.88	74.00	54.00	-20.71	-14.12
7440	V	46.47	31.39	10.60	57.07	41.99	74.00	54.00	-16.93	-12.01
4960	Н	46.43	33.56	6.89	53.32	40.45	74.00	54.00	-20.68	-13.55
7440	Н	46.42	33.09	10.60	57.02	43.69	74.00	54.00	-16.98	-10.31
	_									

**Note:** (1) All Readings are Peak Value and AV.

- (2) Emission Level= Reading Level + Factor
- (3) Factor= Antenna Gain + Cable Loss Amplifier Gain
- (4) Data of measurement within this frequency range shown "---" in the table above means the reading of emissions are attenuated more than 10dB below the permissible limits.
- (5) Measurement uncertainty: ±3.7dB.
- (6) Horn antenna used for the emission over 1000MHz.




## 5. Channel Separation test

## **5.1 Measurement Procedure**

Minimum Hopping Channel Carrier Frequency Separation, FCC Rule 15.247(a)(1):

Connect EUT antenna terminal to the spectrum analyzer with a low loss cable, and using the MARKER and Max-Hold function to record the separation of two adjacent channels.

## 5.2 Test SET-UP (Block Diagram of Configuration)



#### 5.3 Measurement Results

Modulation: GFSK, π/4-DQPSK, 8DPSK

RBW: 100KHz VBW: 300KHz

Packet: Spectrum Detector: PK DH5

Test Bv: Test Date: March 25, 2019 Sance

Temperature: **22** ℃ Humidity: 53 %


Test Result: **PASS** 

Channel number	Channel	Separation Read	Separation Limit		
	frequency (MHz)	Value (KHz)	2/3 20dB Bandwidth		
			(KHz)		
GFSK					
Lowest	2402	1000	>708.7		
Middle	2441	1000	>682.7		
Highest	2480	1000	>657.3		
π/4-DQPSK					
Lowest	2402	1000	>875.3		
Middle	2441	1000	>865.3		
Highest	2480	1000	>862.0		
8DPSK					
Lowest	2402	1000	>868.7		
Middle	2441	1000	>868.7		
Highest	2480	1000	>865.3		

FCC ID: 2AHU2JWM20




## **GFSK Lowest Channel**



Date: 25.MAR.2019 16:32:09

## **GFSK Middle Channel**




Date: 25.MAR.2019 16:34:23

FCC ID: 2AHU2JWM20




# **GFSK Highest Channel**



Date: 25.MAR.2019 16:36:06

## π/4-DQPSK Lowest Channel




Date: 25.MAR.2019 16:38:10

FCC ID: 2AHU2JWM20




## π/4-DQPSK Middle Channel



Date: 25.MAR.2019 16:41:12

# $\pi/4$ -DQPSK Highest Channel




Date: 25.MAR.2019 16:43:12

FCC ID: 2AHU2JWM20




## **8DPSK Lowest Channel**



Date: 25.MAR.2019 16:44:59

## **8DPSK Middle Channel**




Date: 25.MAR.2019 16:48:06

FCC ID: 2AHU2JWM20



# **8DPSK Highest Channel**



Date: 25.MAR.2019 16:43:12

Report No.: NTC1903078FV00 FCC ID: 2AHU2JWM20



#### 6. 20dB Bandwidth

#### **6.1 Measurement Procedure**

Maximum 20dB RF Bandwidth, FCC Rule 15.247(a)(1):

The antenna port of the EUT was connected to the input of a spectrum analyzer. Analyzer RBW was chosen so that the display was a result of the hopping channel modulation. For each RF output channel investigated, the spectrum analyzer center frequency was set to the channel carrier. Use the spectrum 20dB down delta function to measure the bandwidth.

#### **6.2 Test SET-UP (Block Diagram of Configuration)**



#### 6.3 Measurement Results

Refer to attached data chart.

Modulation: GFSK,  $\pi/4$ -DQPSK, 8DPSK

RBW: 30KHz VBW: 100KHz Packet: DH5 Spectrum Detector: PK

Test By: Sance Test Date: March 25, 2019

Temperature : 22  $^{\circ}$  Humidity : 53  $^{\circ}$ 


Test Result: PASS

Channel frequency (MHz)	20dB Down BW(kHz)				
GFSK					
2402	1063				
2441	1024				
2480	986				
π/4-DQPSK					
2402	1313				
2441	1298				
2480	1293				
8DPSK					
2402	1303				
2441	1303				
2480	1298				

FCC ID: 2AHU2JWM20




## **GFSK Lowest Channel**



Date: 25.MAR.2019 16:21:44

## **GFSK Middle Channel**




Date: 25.MAR.2019 16:22:40

FCC ID: 2AHU2JWM20




# **GFSK Highest Channel**



Date: 25.MAR.2019 16:23:34

## π/4-DQPSK Lowest Channel




Date: 25.MAR.2019 16:24:25

FCC ID: 2AHU2JWM20




## π/4-DQPSK Middle Channel



Date: 25.MAR.2019 16:25:17

# $\pi/4$ -DQPSK Highest Channel




Date: 25.MAR.2019 16:26:05

FCC ID: 2AHU2JWM20




## **8DPSK Lowest Channel**



Date: 25.MAR.2019 16:27:11


## **8DPSK Middle Channel**



Date: 25.MAR.2019 16:28:07

FCC ID: 2AHU2JWM20





Date: 25.MAR.2019 16:29:18

Report No.: NTC1903078FV00 FCC ID: 2AHU2JWM20



## 7. Hopping Channel Number

#### 7.1 Measurement Procedure

Minimum Number of Hopping Frequencies, FCC Rule 15.247(a)(1)(iii):

Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum, and the spectrum analyzer set to MAX HOLD readings were taken for 3-5 minutes. The channel peaks so recorded were added together, and the total number compared to the minimum number of channels required in the regulation.

## 7.2 Test SET-UP (Block Diagram of Configuration)

EUT Spectrum Analyzer

#### 7.3 Measurement Results

Modulation GFSK,  $\pi/4$ -DQPSK, 8DPSK

RBW: 100KHz VBW: 300KHz

Packet: DH5 Spectrum Detector: PK

Test By: Sance Test Date: March 25, 2019

Temperature :  $22 \,^{\circ}$ C Humidity :  $53 \,^{\circ}$ 


Test Result: PASS

Hopping Channel Frequency Range	Number of Hopping Channels	Limit
2402-2480	79	≥15

The worst case: GFSK

FCC ID: 2AHU2JWM20





Date: 25.MAR.2019 17:06:53

Report No.: NTC1903078FV00 FCC ID: 2AHU2JWM20



## 8. Time of Occupancy (Dwell Time)

#### 8.1 Measurement Procedure

Average Channel Occupancy Time, FCC Ref:15.247(a)(1)(iii):

Connect EUT antenna terminal to the spectrum analyzer with a low loss cable. The spectrum analyzer center frequency was set to one of the known hopping channels. The Sweep was set to 10 ms, the SPAN was set to Zero SPAN. The time duration of the transmissions so captured was measured with the Marker Delta function

#### 8.2 Measurement Results

The maximum number of hopping channels in 31.6s (0.4s/Channel x 79 Channel)

Refer to attached data chart.

Modulation : GFSK,  $\pi/4$ -DQPSK, 8DPSK


RBW: 1MHz VBW: 1MHz Spectrum Detector: PK Test By: Sance Test Date: March 25, 2019 Temperature:  $22^{\circ}$ C Test Result: PASS Humidity: 53 %

Packet	Frequency	Result			Limit		
	(MHz)		(msec)		(msec)		
GFSK							
DH1	2441	0.405	(ms)*(1600/(2*79))*31.6=	129.60	400		
DH3	2441	1.663	(ms)*(1600/(4*79))*31.6=	266.08	400		
DH5	2441	2.917	(ms)*(1600/(6*79))*31.6=	311.15	400		
	π/4-DQPSK						
2-DH1	2441	0.401	(ms)*(1600/(2*79))*31.6=	128.32	400		
2-DH3	2441	1.659	(ms)*(1600/(4*79))*31.6=	265.44	400		
2-DH5	2441	2.909	(ms)*(1600/(6*79))*31.6=	310.29	400		
8DPSK							
3-DH1	2441	0.405	(ms)*(1600/(2*79))*31.6=	129.60	400		
3-DH3	2441	1.659	(ms)*(1600/(4*79))*31.6=	265.44	400		
3-DH5	2441	2.885	(ms)*(1600/(6*79))*31.6=	307.73	400		

FCC ID: 2AHU2JWM20








Date: 25.MAR.2019 17:22:10

## **GFSK DH3**




Date: 25.MAR.2019 17:22:47

FCC ID: 2AHU2JWM20








Date: 25.MAR.2019 17:23:25

## π/4-DQPSK 2-DH1




Date: 25.MAR.2019 17:23:58

FCC ID: 2AHU2JWM20




## $\pi/4$ -DQPSK 2-DH3



Date: 25.MAR.2019 17:24:50

## π/4-DQPSK 2-DH5




Date: 25.MAR.2019 17:25:29

FCC ID: 2AHU2JWM20




## **8DPSK 3-DH1**



Date: 25.MAR.2019 17:26:01

## **8DPSK 3-DH3**




Date: 25.MAR.2019 17:26:34

FCC ID: 2AHU2JWM20



# **8DPSK 3-DH5**



Date: 25.MAR.2019 17:27:09

Report No.: NTC1903078FV00

FCC ID: 2AHU2JWM20



#### 9. MAXIMUM PEAK OUTPUT POWER

#### 9.1 Measurement Procedure

Maximum Conducted Output Power at Antenna Terminals, FCC Rules 15.247(b)(1):

Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum. The analyzer was set for RBW > 20dB bandwidth and power was read directly in dBm. Cable loss was considered during this measurement.

#### 9.2 Measurement Results

Refer to attached data chart.

Modulation : GFSK,  $\pi/4$ -DQPSK, 8DPSK

RBW: 3MHz VBW: 3MHz

Spectrum Detector: PK Test Date: March 25, 2019


Test By: Sance Temperature : 22  $^{\circ}$ C Test Result: PASS Humidity : 53  $^{\circ}$ 

Channel Frequency	Cable Loss	Peak Power output(dBm)	Peak Power output(mW)	Peak Power Limit(dBm)	Pass/Fail				
(MHz)			Output(IIIVV)	Limit(dDin)					
GFSK									
2402.00	2402.00 1.5 4		2.70	21	PASS				
2441.00	2441.00 1.5		2.83	21	PASS				
2480.00	2480.00 1.5		2.86	21	PASS				
π/4-DQPSK									
2402.00	1.5	21	PASS						
2441.00	1.5	4.18	2.62	21	PASS				
2480.00 1.5		4.23	2.65	21	PASS				
8DPSK									
2402.00	2402.00 1.5 4.09		2.56	21	PASS				
2441.00	1.5	4.29	2.69	21	PASS				
2480.00	1.5	4.45	2.79	21	PASS				

FCC ID: 2AHU2JWM20




# **GFSK Lowest Channel**



Date: 25.MAR.2019 16:07:59

# **GFSK Middle Channel**




Date: 25.MAR.2019 16:10:40

FCC ID: 2AHU2JWM20




# **GFSK Highest Channel**



Date: 25.MAR.2019 16:13:05

# π/4-DQPSK Lowest Channel




Date: 25.MAR.2019 16:15:28


FCC ID: 2AHU2JWM20



## π/4-DQPSK Middle Channel



Date: 25.MAR.2019 16:17:46




Date: 25.MAR.2019 16:19:13

FCC ID: 2AHU2JWM20




## **8DPSK Lowest Channel**



Date: 25.MAR.2019 16:19:38

## **8DPSK Middle Channel**



Date: 25.MAR.2019 16:19:57

FCC ID: 2AHU2JWM20





Date: 25.MAR.2019 16:20:16

Report No.: NTC1903078FV00 FCC ID: 2AHU2JWM20



## 10. Band Edge

#### 10.1 Measurement Procedure

Out of Band Conducted Emissions, FCC Rule 15.247(d):

The transmitter output is connected to spectrum analyzer. The resolution bandwidth is set to 100KHz, and the video bandwidth set to 300KHz.

#### **10.2** Limit

15.247(d)In any 100KHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100KHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

#### 10.3 Measurement Results

Please see below test table and plots.

For Radiated Emission
The worst case: **GFSK** 

Hopping-on mode

i lopping (	on mode									
Freq. (MHz)	Ant.Pol. (H/V)	Reading Level(dBuV)		Factor (dB/m)	Emission Level (dBuV)		Limit 3m (dBuV/m)		Margin (dB)	
		PK	AV	(ub/III)	PK	AV	PK	AV	PK	AV
2390.000	Η	68.74	44.70	0.13	68.87	44.83	74.00	54.00	-5.13	-9.17
2390.000	<b>V</b>	66.69	44.17	0.13	66.82	44.30	74.00	54.00	-7.18	-9.70
2483.500	Ι	62.52	39.51	0.35	62.87	39.86	74.00	54.00	-11.13	-14.14
2483.500	V	62.24	39.03	0.35	62.59	39.38	74.00	54.00	-11.41	-14.62

**Note:** (1) Emission Level= Reading Level + Factor


(2) Factor= Antenna Gain + Cable Loss – Amplifier Gain


(3) Horn antenna used for the emission over 1000MHz.



#### For RF Conducted

# **GFSK Lowest Channel**







Date: 25.MAR.2019 16:51:42



# **GFSK Highest Channel**








Date: 25.MAR.2019 16:53:38


FCC ID: 2AHU2JWM20



# π/4-DQPSK Lowest Channel








Date: 25.MAR.2019 16:56:21


FCC ID: 2AHU2JWM20



# $\pi/4\text{-DQPSK}$ Highest Channel









Date: 25.MAR.2019 16:58:38



# **8DPSK Lowest Channel**









Date: 25.MAR.2019 17:02:50



# **8DPSK Highest Channel**







Date: 25.MAR.2019 17:04:35

Report No.: NTC1903078FV00 FCC ID: 2AHU2JWM20



## 11. Antenna Application

#### 11.1 Antenna requirement

According to of FCC part 15C section 15.203 and 15.240:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Systems operating in the 2400-2483.5MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum peak output power of the intentional radiator is reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

#### 11.2 Measurement Results

The antenna is PCB antenna and no consideration of replacement, and the best case gain of the antenna is 0 dBi. So, the antenna is consider meet the requirement.

Report No.: NTC1903078FV00

FCC ID: 2AHU2JWM20



# 12. Conducted Spurious Emissions

#### 12.1 Measurement Procedure

Out of Band Conducted Spurious Emissions, FCC Rule 15.247(d):

The transmitter output is connected to spectrum analyzer. All spurious emission and up to the tenth harmonic was measured and they were found to be at least 20dB below the highest level of the desired power in the passband.


#### 12.2. Measurement Results

Please refer to following plots, the worst case (**GFSK**) was shown.


FCC ID: 2AHU2JWM20



## **Lowest Channel**



Date: 25.MAR.2019 17:16:27




Date: 25.MAR.2019 17:15:39


FCC ID: 2AHU2JWM20



## **Middle Channel**



Date: 25.MAR.2019 17:18:23




Date: 25.MAR.2019 17:17:47


FCC ID: 2AHU2JWM20



# **Highest Channel**



Date: 25.MAR.2019 17:20:37



Date: 25.MAR.2019 17:20:03

Note: Sweep points=30001pts

FCC ID: 2AHU2JWM20



# 13. Test Equipment List

Description	Manufacturer	Model Number	Serial Characteristics Number		Calibration Date	Calibration Due Date
Test Receiver	Rohde & Schwarz	ESCI7	100837	9KHz~7GHz	Mar. 13, 2019	Mar. 12, 2020
Antenna	Schwarzbeck	VULB9162	9162-010	30MHz~7GHz	Mar. 14, 2019	Mar. 13, 2020
Cable	Huber+Suhner	CBL2-NN-1M	22390001	9KHz~7GHz	Mar. 13, 2019	Mar. 12, 2020
Cable	Huber+Suhner	CIL02	N/A	9KHz~7GHz	Mar. 13, 2019	Mar. 12, 2019
RF Cable Huber+Suhner		SF-104	MY16559/4	9KHz~25GHz	Apr. 25, 2018	Apr. 25, 2019
Power Amplifier	HP	HP 8447D	1145A00203	100KHz~1.3GHz	Mar. 13, 2019	Mar. 12, 2020
Horn Antenna	Schwarzbeck	BBHA9170	9170-242	15GHz~40GHz	Mar. 13, 2019	Mar. 12, 2020
Horn Antenna	Com-Power	AH-118	071078	1GHz~18GHz	Mar. 14, 2019	Mar. 13, 2020
RF Cable	Huber+Suhner	SF-104	N/A	9KHz~40GHz	Apr. 25, 2018	Apr. 25, 2019
Loop antenna	Daze	ZA30900A	0708	9KHz~30MHz	Apr. 25, 2018	Apr. 25, 2019
Spectrum Analyzer	Rohde & Schwarz	FSU26	200409/026	20Hz~26.5GHz	Apr. 25, 2018	Apr. 25, 2019
Spectrum Analyzer	Rohde & Schwarz	FSV40	101003	10Hz~40GHz	Apr. 06, 2018	Apr. 05, 2019
Pre-Amplifier EMCI		EMC 184045	980102	18GHz~40GHz	Nov. 02, 2018	Nov. 01, 2019
Pre-Amplifier	Agilent	8449B	3008A02964	1GHz~26.5GHz	Apr. 25, 2018	Apr. 25, 2019
L.I.S.N.	Rohde & Schwarz	ENV 216	101317	9KHz~30MHz	Mar. 13, 2019	Mar. 12, 2020
Temporary antenna connector	TESCOM	SS402	N/A	9KHz-25GHz	N/A	N/A
Power Meter	Anritsu	ML2495A	1139001	100k-65GHz	Nov. 02, 2018	Nov. 01, 2019
Power Sensor	Anritsu	MA2411B	100345	300M-40GHz	Nov. 02, 2018	Nov. 01, 2019

Note: The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna coSnnector is listed in the equipment list.