

October 10, 2017

TUV SUD BABT FCB Octagon House, Segensworth Road, Fareham, Hampshire, PO15 5RL

Attention: Director of Certification

RE: Analysis of RF Exposure for Portable and Mobile use per KDB 447498 D01 RF Exposure Procedures and Equipment Authorization Policies for Mobile and Portable Devices v06 and RSS-102 Issue 5 March 2015

IC: 21382-9990005001 FCC ID: 2AHYU-9990005001

Portable exposure SAR Exemption Calculation using a 6mm separation distance:

As per Clause 4.3.1 (a) of KDB 447498 D01 v06:

$$\left(\frac{\text{max.power of channel,including tune-up tolerance,mW}}{\text{min.test separation distance,mm}}\right) \times \left(\sqrt{f(GHz)}\right) \le 3.0$$

$$\left(\frac{0.99 \text{ mW}}{6 \text{ mm}}\right) \times \left(\sqrt{2.480 (GHz)}\right) \le 3.0$$

 $0.0.26 \le 3.0$ (complies)

The EUT complies with the exemption limits for routine evaluation based on frequency and separation distance as per Table 1 of RSS-102 Issue 5 March 2015 with an EIRP of 0.99mW. See separate RSS-102 Annex A exhibit for more details.

All calculations were based on peak power (worst case than source-based time-averaged maximum conducted output power).

Sincerely.

Name

Authorized Signatory

Title: EMC/Wireless Test Engineer