

RC-032-PTE-15-105080-1-A

E.M.C Test Report

According to the standards:
FCC 47 CFR PART 15 : 2015 (§15.247)

Equipment under test:

Hand pendant
with BLE 2.4 GHz
FCC ID: 2AHZSHP-MOB

Company:


IBA

FCC accredited: FR0004

DISTRIBUTION: Mr. AGRAM

(Company: IBA)

Number of pages: 58 with 6 annexes

Ed.	Date	Modified page(s)	Written by		Technical Verification and Quality Approval	
			Name	Visa	Name	Visa
0	18/04/16	Creation	F. LHEUREUX	FL	B. Pellexin	

*Duplication of this report is only permitted for an integral photographic facsimile. It includes the number of pages referenced above.
This document is the result of testing a specimen or a sample of the product submitted. It does not imply an assessment of the conformity of the whole
production of the item tested.*



Siège Social : Emitech - 3, rue des Coudriers - Z.A. de l'Observatoire - 78180 MONTIGNY LE BX - France
Siret : 344 545 645 00022 - Tél. : 33 (0)1 30 57 55 55 - Fax : 33 (0)1 30 43 74 48 - E-mail : contact@emitech.fr - URL : www.emitech.fr
S.A. au capital de 1 560 000 € - R.C.S. VERSAILLES 344 545 645 - APE 7112B

TEST CERTIFICATION FOR: FCC Certification

NAME OF THE EQUIPMENT UNDER TEST: Hand pendant with BLE 2.4 GHz

Serial number: 5651-0001

Reference / model (P/N): P4000021

Software version: WMEB - 1.0.0 – Radio Tests

NAME OF THE MANUFACTURER: IBA

ADDRESS OF THE APPLICANT:

Company: IBA

Address: Chemin du Cyclotron 3
1348 LOUVAIN-LA-NEUVE
BELGIUM

Person in charge: Mr. AGRAM

Person present during the tests Mr. BOURMORCK

DATES OF TESTS: 05 and 06/04/2016

TESTS LOCATION: EMITECH laboratory in Montigny Le Bretonneux (78)
FRANCE.

TESTS OPERATORS: F. LHEUREUX / C. FOURCADE

TESTS TUTOR: B. PELLERIN

TABLE OF CONTENTS

1. INTRODUCTION	4
2. REFERENCE DOCUMENTS	4
3. PRODUCT DESCRIPTION	5
4. TESTS AND CONCLUSION	6
5. DIGITAL MODULATION SYSTEMS	8
6. TRANSMITTER OUTPUT POWER	10
7. PEAK POWER SPECTRAL DENSITY	12
8. ADDITIONAL PROVISIONS TO THE GENERAL RADIATED EMISSIONS LIMITATION	15
9. UNINTENTIONAL RADIATED EMISSIONS AND TRANSMITTER UNWANTED EMISSION IN THE BAND 9 KHZ – 25 GHZ	17
10. CONDUCTED EMISSION	22

ANNEX 1: ANTENNA FACTORS, INSERTION LOSSES AND AMPLIFIER VALUES

ANNEX 2: EXTERNAL PHOTOGRAPHIES

ANNEX 3: TEST SETUP PHOTOGRAPHIES

ANNEX 4: 6 dB BANDWIDTH, 20 dB BANDWIDTH

ANNEX 5: BAND EDGE

ANNEX 6: CALIBRATION DATES

1. INTRODUCTION

This document presents the results of Electromagnetic Compatibility tests performed on the equipment «Hand pendant with BLE 2.4 GHz» according to reference documents listed below.

2. REFERENCE DOCUMENTS

FCC 47 CFR Part 15: 2015

Code of Federal Regulations. Title 47- Telecommunication
Chapter 1- Federal Communication Commission
Part 15- Radio frequency devices

ANSI C63.4: 2014

Methods of Measurement of Radio-Noise Emissions from Low Voltage Electrical and Electronics Equipment in the range of 9 kHz to 40 GHz.


KDB 558074 D01 DTS Meas Guidance V03r04

Guidance for performing compliance measurement on Digital Transmission Systems (DTS) operating under § 15.247

3. PRODUCT DESCRIPTION

Class:	B (Medical environment)
Antenna type and gain:	Integral antenna: Not communicated
Operating frequency range:	from 2402 MHz to 2480 MHz
Number of channels:	40
Channel spacing:	2 MHz
Modulation:	-
Power source:	3 Vdc (battery)
Software power setting:	WMEB – 1.0.0 – Radio Tests
Modification of the equipment during the tests:	No.

The equipment under test is presented in a plastic housing, intended for use portable in a medical environment, it is tested in horizontal position and vertical position. That used for all measurements in a horizontal position.
The equipment under test is recharged via a charging station supplied with 230 Vac / 50 Hz.
The equipment under test is provided for use of +15°C to +30°C.



E.U.T.



E.U.T. + charging station

4. TESTS AND CONCLUSION

The following table summarizes test results of the EUT.

Subpart B of the standard FCC part 15 – Unintentional radiators

Test procedure	Designation of test	Test results				Comments
		Pass	Fail	N.A.	N.P.	
15.107	Measurement of conducted emission on AC mains ports	X				
15.109	Radiated emission limits	X				

Subpart C of the standard FCC part 15 – Intentional radiators

Test procedure	Designation of test	Test results				Comments
		Pass	Fail	N.A.	N.P.	
15.205	Restricted bands of operation	X				
15.207	Measurement of conducted emission on AC mains ports	X				
15.209	Radiated emission limits; general requirements	X				
15.215	Additional provisions to the general radiated emission limitations					
	(a) Alternative to general radiated emission limits	X				
	(b) Unwanted emissions outside of § 15.247 frequency bands	X				
	(c) 20 dB bandwidth and band-edge compliance	X				
15.247	Intentional radiated emissions					
	a) frequency hopping and digitally modulated					
	a) (1) hopping mode			X		
	a) (1) (i) frequency hopping in the band 902-928 MHz			X		
	a) (1) (ii) frequency hopping in the band 5725-5850 MHz			X		
	a) (1) (iii) frequency hopping in the band 2400-2483.5 MHz			X		
	a) (2) systems using digital modulation in the bands 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz (6 dB bandwidth)	X				
	b) maximum peak conducted					
	b) (1) frequency hopping in the bands 2400-2483.5 MHz or 5725-5850 MHz			X		
	b) (2) frequency hopping in the band 902-928 MHz			X		

Test procedure	Designation of test	Test results				Comments
		Pass	Fail	N.A.	N.P.	
	b) (3) systems using digital modulation in the bands 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz	X				
	b) (4) maximum peak conducted > 6 dBi					
	b) (4) (i) frequency hopping in the band 2400–2483.5 MHz			X		
	b) (4) (ii) frequency hopping in the band 5725–5850 MHz			X		
	b) (4) (iii) fixed, point-to-point			X		
	c) directional antenna > 6 dBi					
	c) (1) fixed, point-to-point operation			X		
	c) (1) (i) in the band 2400–2483.5 MHz			X		
	c) (1) (ii) in the band 5725–5850 MHz			X		
	c) (1) (iii) fixed, point-to-point			X		
	c) (2) multiple directional beams in the band 2400–2483.5 MHz			X		
	c) (2) (i) information			X		
	c) (2) (ii) sum of the power supplied to all antennas			X		
	c) (2) (iii) one antenna for multiple directional beams			X		
	c) (2) (iv) single directional beam			X		
	d) intentional radiator	X				
	e) peak power spectral density	X				
	f) hybrid system			X		
	g) continuous data stream during the test			X		
	h) to avoid hopping on occupied channels			X		
	i) RF exposure compliance			X		P < 500 mW

N.A.: Not Applicable

N.P.: Not Performed

Conclusion:

The tested sample «**Hand pendant with 2.4 GHz**» submitted to the tests complies with the requirements of the standard:

- FCC 47 CFR PART 15 : 2015

According to the limits specified in this report.

5. DIGITAL MODULATION SYSTEMS

Standard: FCC 47 CFR PART 15 : 2015

Section: §15.247 a) (2)

Test configuration:

The system is tested in normalized test site.

The test unit is placed on a rotating table, 0.8 m from a ground plane. Zero degree azimuth corresponds to the front of the equipment under test.

The level was maximised in antenna height, azimuth and polarization. The maximum level measured on the spectrum analyser was recorded.

Distance of antenna: 3 meters

Instrumentation test list:

CATEGORY	BRAND	TYPE	N° EMITECH
Antenna	Emco	Emco	3374
Antenna mast	Maturo	MCU	8410
Antenna mast	Maturo	AM 4.0	8411
Cable	C&C	C&C	11136
Cable	C&C	C&C	11172
Cable	C&C	N-2m	11177
Shielded enclosure	SIDT	SIDT	0549
Spectrum analyzer	Rohde & Schwarz	FSP40 (V 4.00SP1-V3.0-10-2)	5175

Equipment under test operating condition:

EUT is in continuous transmission mode.

Measure conditions:

Ambient temperature (°C): 21

Relative humidity (%): 39

Resolution bandwidth: 100 kHz

Results:

Power source: 3 Vdc

6 dB bandwidth

Frequency	Mode	Results	Comments
2402 MHz	advertising	0.690 MHz	See annex n°4
2426 MHz		0.670 MHz	See annex n°4
2480 MHz		0.650 MHz	See annex n°4

20 dB bandwidth

Frequency	Mode	Results	Comments
2402 MHz	advertising	1.220 MHz	See annex n°4
2426 MHz		1.240 MHz	See annex n°4
2480 MHz		1.210 MHz	See annex n°4

Test conclusion: Complies with the requirements of the standard.

6. TRANSMITTER OUTPUT POWER

Standard: FCC 47 CFR PART 15 : 2015

Section: §15.247 b) (3)

Test configuration:

The system is tested in normalized test site.

The test unit is placed on a rotating table, 0.8 m from a ground plane. Zero degree azimuth corresponds to the front of the equipment under test.

The level was maximised in antenna height, azimuth and polarization. The maximum level measured on the spectrum analyser was recorded.

Distance of antenna: 3 meters

Instrumentation test list:

CATEGORY	BRAND	TYPE	N° EMITECH
Antenna	Emco	Cornet 3115	3374
Antenna mast	Maturo	MCU	8410
Antenna mast	Maturo	AM 4.0	8411
Cable	C&C	N-6m	11136
Cable	C&C	N-2m	11172
Cable	C&C	N-2m	11177
Shielded enclosure	SIDT	C.4	0549
Spectrum analyzer	Rohde & Schwarz	FSP40 (V 4.00SP1-V3.0-10-2)	5175

Equipment under test operating condition:

EUT is in continuous transmission mode.

Measure conditions:

Ambient temperature (°C): 21

Relative humidity (%): 39

Resolution bandwidth: 2 MHz

Results:

Power source: 3 Vdc

Frequency	Mode	Electro-magnetic field (dB μ V/m)	TP* (dBm)	Limit (dBm)
2402 MHz	advertising	86.10	- 11.28	+ 30
2426 MHz		86.30	- 11.08	+ 30
2480 MHz		85.38	- 12.00	+ 30

* TP = $(E \times d)^2 / (30 \times 1.64)$ for d = 3 m**Test conclusion:** Complies with the requirements of the standard.

7. PEAK POWER SPECTRAL DENSITY

Standard: FCC 47 CFR PART 15 : 2015

Section: §15.247 e)

Test configuration:

The system is tested in normalized test site.

The test unit is placed on a rotating table, 0.8 m from a ground plane. Zero degree azimuth corresponds to the front of the equipment under test.

The level was maximised in antenna height, azimuth and polarization. The maximum level measured on the spectrum analyser was recorded.

Distance of antenna: 3 meters

Instrumentation test list:

CATEGORY	BRAND	TYPE	N° EMITECH
Antenna	Emco	Cornet 3115	3374
Antenna mast	Maturo	MCU	8410
Antenna mast	Maturo	AM 4.0	8411
Cable	C&C	N-6m	11136
Cable	C&C	N-2m	11172
Cable	C&C	N-2m	11177
Shielded enclosure	SIDT	C.4	0549
Spectrum analyzer	Rohde & Schwarz	FSP40 (V 4.00SP1-V3.0-10-2)	5175

Equipment under test operating condition:

EUT is in continuous transmission mode.

Measure conditions:

Ambient temperature (°C): 21

Relative humidity (%): 39

Resolution bandwidth: 30 kHz


Video bandwidth: 100 kHz

Results:


Power source: 3 Vdc

Frequency	Mode	Electro-magnetic field (dB μ V/m)	PPSD* (dBm)	Limit (dBm)
2402 MHz	Advertising	84.73	- 12.65	+ 8.0
2426 MHz		84.99	- 12.39	
2480 MHz		84.56	- 12.82	


* PPST = $(E \times d)^2 / (30 \times 1.64)$ for $d = 3$ m



Date: 5.APR.2016 14:45:58



Date: 5.APR.2016 15:32:15



Date: 5.APR.2016 15:59:12

Test conclusion: Complies with the requirements of the standard.

8. ADDITIONAL PROVISIONS TO THE GENERAL RADIATED EMISSIONS LIMITATION

Standard: FCC 47 CFR PART 15 : 2015

Sections: §15.215 (b) and §15.247 (d)

Instrumentation test list:

CATEGORY	BRAND	TYPE	N° EMITECH
Antenna	Emco	Cornet 3115	3374
Antenna mast	Maturo	MCU	8410
Antenna mast	Maturo	AM 4.0	8411
Cable	C&C	N-6m	11136
Cable	C&C	N-2m	11172
Cable	C&C	N-2m	11177
Shielded enclosure	SIDT	C.4	0549
Spectrum analyzer	Rohde & Schwarz	FSP40 (V 4.00SP1-V3.0-10-2)	5175

Equipment under test arrangement:

The system is tested in normalized test site.

The test unit is placed on a rotating table, 0.8 m from a ground plane. Zero degree azimuth corresponds to the front of the equipment under test.

The level was maximised in antenna height, azimuth and polarization. The maximum level measured on the spectrum analyser was recorded.

Results:

Ambient temperature (°C): 21

Relative humidity (%): 39

Lower Band Edge: from 2310 MHz to 2390 MHz
Upper Band Edge: from 2483.5 MHz to 2500 MHz

Polarization of test antenna: Horizontal (height = 142 cm) } For 2402 MHz
Position of equipment: azimuth = 0° }

Polarization of test antenna: Horizontal (height = 110 cm) } For 2480 MHz
Position of equipment: azimuth = 0° }

- Advertising Mode

Fundamental frequency (MHz)	Field Strength Level of fundamental (dBμV/m)	Detector (Peak or Average)	Frequency of maximum Band-edges Emission (MHz)	Delta Marker (dB) *	Calculated Max Out of Band Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)
2401.99	85.49	Average	2356.16	35.9	49.6	54.0	4.4
2479.99	84.54	Average	2486.07	39.9	48.6	54.0	5.4

* According to step 2 of Marker-Delta Method DA 00-705.

Band-edge curves are given in annex 5.

9. UNINTENTIONAL RADIATED EMISSIONS AND TRANSMITTER UNWANTED EMISSION IN THE BAND 9 kHz – 25 GHz

Standard: FCC 47 CFR PART 15 : 2015

Section: §15.205; 15.209 and §15.247

Equipment under test arrangement:

The equipment under test (EUT) is placed on a non-conductive test table at 0.8 m above the horizontal metal ground plane.

For maximum meter reading at each frequency, the antenna height is adjusted between 1 m and 4 m above the ground plane. A 360 degrees rotation of the EUT is performed in vertical and horizontal polarization. The frequency azimuth and antenna height are presented in the table on the next pages.

The E.U.T. is blocked in continuous transmission.

Frequencies range: 9 kHz – 30 MHz
30 MHz - 1 GHz
1 GHz – 25 GHz

Detection mode: Quasi-peak for 9 kHz – 30 MHz
Quasi-peak for 30 MHz - 1 GHz
Average for 1 GHz – 25 GHz

Resolution bandwidth: 200 Hz for 9 kHz – 150 kHz
9 kHz for 150 kHz – 30 MHz
120 kHz for 30 MHz - 1 GHz
1 MHz for 1 GHz – 25 GHz

Measurement distance: 3 meters from 9 kHz to 30 MHz
3 meters from 30 MHz to 25 GHz

- Limit for emission radiated outside the frequency band, except the harmonics, shall be attenuated by at least 20 dB below the level of fundamental or the general radiated emission limits.

From 9 kHz to 30 MHz

Frequencies range	Limit ($\mu\text{V/m}$)
9 – 490 kHz	2400/F (F in kHz) *
490 – 1705 kHz	24000/F (F in kHz) **
1.705 – 30 MHz	30 **

* Limits in $\mu\text{V/m}$ can be extrapolated to 3 m using 40 dB / decade.

** Limits in $\mu\text{V/m}$ can be extrapolated to 3 m using 20 dB / decade.

From 30 MHz to 25 GHz

Frequencies range (MHz)	Limit (dB $\mu\text{V/m}$)	Limit ($\mu\text{V/m}$)
30 to 88	40.0	100
88 to 216	43.5	150
216 to 960	46.0	200
Above 960	54.0	500

Instrumentation test list:



CATEGORY	BRAND	TYPE	N° EMITECH
Amplifier	Mini-circuit	ZFL-1000LN	6367
Amplifier	Miteq	AFS42-00102650-42-10P-42	3229
Antenna	Schaffner	CBL 6143A	5647
Antenna	Emco	3115	3374
Antenna	Oritel	CM 42/25	1045
Antenna	Emco	6502	9579
Antenna mast	Maturo	MCU	8410
Antenna mast	Maturo	AM 4.0	8411
Cable	C&C	N-2m	11181
Cable	C&C	N-10m	11136
Cable	C&C	N-2m	11182
Cable	C&C	N-6m	11172
Cable	C&C	K-2m	11132
Cable	C&C	K-2m	11133
Filter	Micro-Tronics	HPM 14758	4691
Receiver	Rohde & Schwarz	ESRP7	10517
Shielded enclosure	SIDT	C.4	0549
Spectrum analyzer	Rohde & Schwarz	FSP40 (V 4.00SP1-V3.0-10-2)	5175

Results:

Ambient temperature (°C): 21
Relative humidity (%): 39
Power source: 3 Vdc

Curves 1 and 2



Frequency 2402 MHz



No significant frequency has been found other than those given above between 9 kHz to 30 MHz and 1 GHz to 25 GHz.

Curves 3 and 4



Frequency 2480 MHz



No significant frequency has been found other than those given above between 9 kHz to 30 MHz and 1 GHz to 25 GHz.

Curves 5 and 6

Transmission mode



No significant frequency has been found other than those given above between 9 kHz to 30 MHz and 1 GHz to 25 GHz.

Test conclusion:

The equipment complies with the requirements of the standard.

10. CONDUCTED EMISSION

Standard: FCC 47 CFR PART 15 : 2015

Test method: Part 15.107 and 15.207

Test configuration:

Tested cable	Measure with	E.U.T. height
Power supply 120 Vac / 60 Hz (Nominal configuration)	L.I.S.N.	80 cm
Power supply 120 Vac / 60 Hz (In charging on a PC)	L.I.S.N.	80 cm
Power supply 120 Vac / 60 Hz (Travel charger configuration)	L.I.S.N.	80 cm

Frequencies band	Tested cable	Resolution bandwidth	Video bandwidth
150 kHz - 30 MHz	Power supply 120 Vac / 60 Hz (Nominal configuration)	10 kHz	30 kHz
150 kHz - 30 MHz	Power supply 120 Vac / 60 Hz (Nominal configuration)	9 kHz	Auto
150 kHz - 30 MHz	Power supply 120 Vac / 60 Hz (In charging on a PC)	10 kHz	30 kHz
150 kHz - 30 MHz	Power supply 120 Vac / 60 Hz (In charging on a PC)	9 kHz	Auto
150 kHz - 30 MHz	Power supply 120 Vac / 60 Hz (Travel charger configuration)	10 kHz	30 kHz
150 kHz - 30 MHz	Power supply 120 Vac / 60 Hz (Travel charger configuration)	9 kHz	Auto

Test method deviation: No

Test equipment list:

CATEGORY	BRAND	TYPE	N° EMITECH
Bobine PE	Emitech	CISPR 16-2-1 : 2008	10063
Cable	-	N-2m	2873
Cable	-	N-2m	2814
Cable	C&C	BNC-0.3m	9953
LISN	Rohde & Schwarz	ESH3-Z5	6602
Multimeter	Emitech	Absorbeur courant de gaine	12366
Receiver	Rohde & Schwarz	ESRP7	10517
Surges Suppressor	Hewlett Packard	11947A	0237
Test enclosure	Emitech	JD1	1804

Results:



See curves below including detections and limits in peak (red), average (green) and quasi-peak (blue).

Curves 7 and 8

Hand pendant with BLE 2.4 GHz

Conducted voltage emission (measurement): Power supply 120 Vac / 60 Hz
(Nominal configuration) in peak detection

06/04/2016





Class: B of the standard

Curves 9 and 10

Hand pendant with BLE 2.4 GHz

Conducted voltage emission (measurement): Power supply 120 Vac / 60 Hz
(Nominal configuration) in average value detection

06/04/2016





Class: B of the standard

Curves 11 and 12

Hand pendant with BLE 2.4 GHz

Conducted voltage emission (measurement): Power supply 120 Vac / 60 Hz
(In charging on a PC) in peak detection

06/04/2016





Class: B of the standard

Curves 13 and 14

Hand pendant with BLE 2.4 GHz

Conducted voltage emission (measurement): Power supply 120 Vac / 60 Hz
(In charging on a PC) in average value detection

06/04/2016





Class: B of the standard

Curves 15 and 16

Hand pendant with BLE 2.4 GHz

Conducted voltage emission (measurement): Power supply 120 Vac / 60 Hz
(Travel charger configuration) in peak detection

06/04/2016





Class: B of the standard

Curves 17 and 18

Hand pendant with BLE 2.4 GHz

Conducted voltage emission (measurement): Power supply 120 Vac / 60 Hz
(Travel charger configuration) in average value detection

06/04/2016



Class: B of the standard

« □□□ End of report, 6 annexes to be forwarded □□□ »

ANNEX 1:

ANTENNA FACTORS, INSERTION LOSSES AND AMPLIFIER VALUES

BILL OF MATERIAL

The test antenna used for the radiated emission between 9 kHz and 30 MHz is the active loop antenna n°9579. Antenna factors are given in table 1.

The test antenna used for the radiated emission between 30 MHz and 1 GHz is the bilog n°5647. Antenna factors are given in table 2.

The measuring receiver n°10517 used in the frequency range 9 kHz to 1 GHz has an integrated preamplifier.

The spectrum analyzer n°5175 is used in the frequency range 1 GHz to 25 GHz.

The test cable used between 9 kHz and 30 MHz to connect the antennas to the receiver for measurements at a distance of 3 meters has losses given in table 3.

The test cable used between 30 MHz and 1 GHz to connect the antennas to the receiver for measurements at a distance of 3 meters has losses given in table 4a, 4b and 4c.

The test antenna used for the radiated emission between 1 GHz and 18 GHz is the horn antenna n°3374. Factors are given in table 5.

The test antenna used for the radiated emission between 18 GHz and 25 GHz is the horn antenna n°1045. Factors are given in table 6.

The amplifier n°3229 used to connect the spectrum analyzer to the test cable has gain values given in the table 7.

The test cable used between 1 GHz and 18 GHz to connect the horn antenna to the amplifier for measurements at distance of 3 meters has losses given in table 8.

The test cable used between 18 GHz and 26 GHz to connect the horn antenna to the amplifier for measurements at distance of 3 meters has losses given in table 9a and 9b.

Frequency (MHz)	Antenna factor (dB/m)	Frequency (MHz)	Antenna factor (dB/m)
0.009	20.9	0.8	11.2
0.01	20.2	1	11.2
0.015	16.6	1.5	11.1
0.02	15.1	2	11.0
0.03	13.8	3	10.9
0.05	12.4	5	10.7
0.08	11.9	8	10.3
0.1	11.8	10	10.0
0.15	11.7	15	9.3
0.2	11.6	20	8.4
0.3	11.5	25	6.3
0.5	11.4	30	5.7

TABLE 1 : ACTIVE LOOP ANTENNA

Frequency (MHz)	Antenna factor (dB/m)	Frequency (MHz)	Antenna factor (dB/m)
30	23.5	160	10.8
35	20.5	180	10.3
40	17.9	200	11.6
45	15.4	250	13.4
50	13.0	300	14.1
60	10.7	400	16.4
70	8.9	500	17.2
80	7.4	600	18.5
90	8.3	700	19.1
100	10.9	800	19.9
120	13.8	900	20.1
140	12.4	1000	20.6

TABLE 2 : BILOG ANTENNA

Frequency (MHz)	Loss (dB)	Frequency (MHz)	Loss (dB)
0.009	0.0	6.000	0.5
0.020	0.0	7.000	0.5
0.050	0.0	8.000	0.5
0.100	0.1	9.000	0.6
0.500	0.1	10.00	0.6
1.000	0.2	15.00	0.8
2.000	0.3	20.00	0.9
3.000	0.3	25.00	1.0
4.000	0.4	30.00	1.1
5.000	0.4	-	-

**TABLE 3 : TEST CABLE FOR 3M MEASUREMENT INTO 9 kHz
AND 30 MHz**

Frequency (MHz)	Loss (dB)	Frequency (MHz)	Loss (dB)
30	0.1	250	0.2
40	0.1	300	0.3
50	0.1	400	0.3
60	0.1	500	0.4
70	0.1	600	0.4
80	0.1	700	0.5
90	0.1	800	0.5
100	0.1	900	0.6
150	0.2	1000	0.6
200	0.2	-	-

**TABLE 4a : TEST CABLE FOR 3M MEASUREMENT INTO 30 MHz
AND 1 GHz**

Frequency (MHz)	Loss (dB)	Frequency (MHz)	Loss (dB)
30	0.3	250	0.8
40	0.3	300	0.8
50	0.4	400	1.0
60	0.4	500	1.1
70	0.4	600	1.2
80	0.4	700	1.3
90	0.5	800	1.4
100	0.5	900	1.5
150	0.6	1000	1.5
200	0.7	-	-

TABLE 4b : TEST CABLE FOR 3M MEASUREMENT INTO 30 MHz
AND 1 GHz

Frequency (MHz)	Loss (dB)	Frequency (MHz)	Loss (dB)
30	0.3	250	1.1
40	0.4	300	1.2
50	0.5	400	1.4
60	0.5	500	1.7
70	0.5	600	1.8
80	0.6	700	2.0
90	0.6	800	2.1
100	0.7	900	2.3
150	0.8	1000	2.4
200	1.0	-	-

TABLE 4c : TEST CABLE FOR 3M MEASUREMENT INTO 30 MHz
AND 1 GHz

Frequency (GHz)	Antenna factor (dB/m)	Frequency (GHz)	Antenna factor (dB/m)
1.0	23.7	10.0	37.6
1.5	25.0	10.5	37.8
2.0	27.5	11.0	38.1
2.5	28.8	11.5	38.3
3.0	29.8	12.0	38.8
3.5	31.2	12.5	38.8
4.0	32.5	13.0	39.4
4.5	32.5	13.5	40.0
5.0	33.5	14.0	40.1
5.5	34.1	14.5	40.6
6.0	34.1	15.0	40.6
6.5	34.4	15.5	39.7
7.0	35.4	16.0	39.3
7.5	36.6	16.5	39.9
8.0	36.6	17.0	41.4
8.5	37.0	17.5	45.1
9.0	37.1	18.0	46.3
9.5	37.2	-	-

TABLE 5 : HORN ANTENNA

Frequency (GHz)	Antenna factor (dB/m)	Frequency (GHz)	Antenna factor (dB/m)
18.0	30.7	22.5	30.9
18.5	30.7	23.0	31.2
19.0	30.5	23.5	31.1
19.5	30.7	24.0	31.3
20.0	30.7	24.5	31.5
20.5	30.8	25.0	31.0
21.0	30.9	25.5	31.0
21.5	30.5	26.0	31.4
22.0	30.6	-	-

TABLE 6 : HORN ANTENNA

Frequency (GHz)	Gain value (dB)	Frequency (GHz)	Gain value (dB)
1.0	33.4	12.0	32.4
1.5	33.7	13.0	32.5
2.0	33.9	14.0	31.6
2.5	34.0	15.0	33.0
3.0	33.9	16.0	33.5
4.0	34.3	17.0	33.9
5.0	35.2	18.0	34.3
6.0	34.7	19.0	34.4
7.0	34.0	20.0	32.9
8.0	33.7	21.0	33.2
9.0	31.8	22.0	34.3
9.5	31.1	23.0	34.6
10.0	30.5	24.0	34.4
10.5	30.7	25.0	34.5
11.0	31.1	26.0	32.5

TABLE 7 : AMPLIFIER GAIN VALUE

Frequency (GHz)	Gain value (dB)	Frequency (GHz)	Gain value (dB)
1.0	1.6	9.5	5.6
1.5	2.0	10.0	5.7
2.0	2.4	10.5	5.8
2.5	2.7	11.0	5.9
3.0	3.0	12.0	6.2
4.0	3.4	13.0	6.4
5.0	3.8	14.0	6.6
6.0	4.1	15.0	7.1
7.0	4.6	16.0	7.3
8.0	5.1	17.0	7.6
9.0	5.5	18.0	7.8

TABLE 8 : TEST CABLE FOR 3M MEASUREMENT INTO 1 TO 18 GHz

Frequency (GHz)	Loss (dB)
18.0	3.8
19.0	3.8
20.0	3.9
21.0	4.0
22.0	4.1
23.0	4.2
24.0	4.3
25.0	4.4
26.0	4.5

**TABLE 9a: TEST CABLE FOR 3M
MEASUREMENT INTO 18 TO 26 GHz**

Frequency (GHz)	Loss (dB)
18.0	3.8
19.0	3.8
20.0	3.9
21.0	4.0
22.0	4.1
23.0	4.2
24.0	4.3
25.0	4.4
26.0	4.5

**TABLE 9b: TEST CABLE FOR 3M
MEASUREMENT INTO 18 TO 26 GHz**

ANNEX 2:

EXTERNAL PHOTOGRAPHS






ANNEX 3:

TEST SETUP PHOTOGRAPHS








Power supply 120 Vac / 60 Hz (Nominal configuration)



Power supply 120 Vac / 60 Hz (In charging on a PC)




Power supply 120 Vac / 60 Hz (Travel charger configuration)

ANNEX 4:

6 dB BANDWIDTH
20 dB BANDWIDTH


6 dB BANDWIDTH

Frequency 2402 MHz




Date: 5.APR.2016 14:41:18

Frequency 2426 MHz



Date: 5.APR.2016 15:25:09


Frequency 2480 MHz



Date: 5.APR.2016 15:54:40


20 dB BANDWIDTH

Frequency 2402 MHz




Date: 5.APR.2016 14:50:30

Frequency 2426 MHz



Date: 5.APR.2016 15:27:24


Frequency 2480 MHz




Date: 5.APR.2016 15:56:04

ANNEX 5:

BAND EDGE



Date: 5.APR.2016 14:58:26



Date: 5.APR.2016 16:04:41

ANNEX 6:

CALIBRATION DATES

N° EMITECH	LAST CALIBRATION	CALIBRATION DUE DATE
10517	18/09/2014	18/09/2016
5175	01/04/2016	01/04/2018
0549	16/02/2015	16/02/2018
0317	18/02/2015	18/02/2019
3106	05/06/2014	05/06/2016
11136	10/03/2014	10/05/2016
11172	28/03/2014	28/05/2016
11181	28/03/2014	28/05/2016
11182	28/03/2014	28/05/2016
1045	21/03/2015	21/03/2019
11132	10/03/2014	10/05/2016
11133	10/03/2014	10/05/2016
3374	28/10/2015	28/10/2018
9579	21/08/2015	21/08/2017
3229	02/04/2015	02/06/2016
6367	16/07/2015	16/07/2016