

---

# FCC Test Report

---

Report No.: AGC07091160701FE03

**FCC ID** : 2A14ZS6

**APPLICATION PURPOSE** : Original Equipment

**PRODUCT DESIGNATION** : Bluetooth headset

**BRAND NAME** : N/A

**MODEL NAME** : S6

**CLIENT** : Shenzhen Dilante Electronic Co.,Ltd.

**DATE OF ISSUE** : Aug.04, 2016

**STANDARD(S)** : FCC Part 15 Rules

**TEST PROCEDURE(S)**

**REPORT VERSION** : V1.0

Attestation of Global Compliance (Shenzhen) Co., Ltd



**CAUTION:**

This report shall not be reproduced except in full without the written permission of the test laboratory and shall not be quoted out of context.



### Report Revise Record

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	Aug.04, 2016	Valid	Original Report

TABLE OF CONTENTS

1. VERIFICATION OF CONFORMITY ..... 4

2. GENERAL INFORMATION ..... 5

    2.1. PRODUCT DESCRIPTION.....5

    2.2. TABLE OF CARRIER FREQUENCYS.....5

3. MEASUREMENT UNCERTAINTY..... 7

4. DESCRIPTION OF TEST MODES..... 7

5. SYSTEM TEST CONFIGURATION ..... 9

    5.1. CONFIGURATION OF EUT SYSTEM .....9

    5.2. EQUIPMENT USED IN EUT SYSTEM .....9

    5.3. SUMMARY OF TEST RESULTS .....9

6. TEST FACILITY ..... 10

7. ALL TEST EQUIPMENT LIST ..... 10

8. RADIATED EMISSION ..... 12

    8.1TEST LIMIT.....12

    8.2. MEASUREMENT PROCEDURE .....13

    8.3. TEST SETUP.....15

    8.4. TEST RESULT .....17

9. BAND EDGE EMISSION ..... 45

    9.1. MEASUREMENT PROCEDURE .....45

    9.2 TEST SETUP.....45

    9.3 RADIATED TEST RESULT .....46

10. 20DB BANDWIDTH..... 54

    10.1. MEASUREMENT PROCEDURE .....54

    10.2. TEST SET-UP.....54

    10.3. LIMITS AND MEASUREMENT RESULTS.....54

11. FCC LINE CONDUCTED EMISSION TEST ..... 63

    11.1. LIMITS OF LINE CONDUCTED EMISSION TEST .....63

    11.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST.....63

    11.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST .....64

    11.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST.....64

    11.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST.....65

APPENDIX A: PHOTOGRAPHS OF TEST SETUP ..... 69

APPENDIX B: PHOTOGRAPHS OF EUT ..... 72


APPENDIX B: PHOTOGRAPHS OF EUT ..... 72

## 1. VERIFICATION OF CONFORMITY

<b>Applicant</b>	Shenzhen Dilante Electronic Co.,Ltd.
<b>Address</b>	Chunxing Industry Zone,Dalang Street,LongHua District,Shenzhen.China
<b>Manufacturer</b>	Shenzhen Dilante Electronic Co.,Ltd.
<b>Address</b>	Chunxing Industry Zone,Dalang Street,LongHua District,Shenzhen.China
<b>Product Designation</b>	Bluetooth headset
<b>Brand Name</b>	N/A
<b>Test Model</b>	S6
<b>Date of test</b>	July 13, 2016 to July 18, 2016
<b>Deviation</b>	None
<b>Condition of Test Sample</b>	Normal
<b>Report Template</b>	AGCRT-US-BR/RF

We hereby certify that:

The above equipment was tested by Dongguan Precise Testing Service Co., Ltd. The test data, the energy emitted by the sample tested as described in this report is in compliance with the requirements of FCC Rules Part 15.249.

Tested By   
Time Huang(Huang Nanhui) Aug.04, 2016

Reviewed By   
Forrest Lei(Lei Yonggang) Aug.04, 2016

Approved By   
Solger Zhang(Zhang Hongyi)  
Authorized Officer Aug.04, 2016

## 2. GENERAL INFORMATION

### 2.1. PRODUCT DESCRIPTION

A major technical description of EUT is described as following

<b>Operation Frequency</b>	2.402 GHz to 2.480GHz
<b>RF Output Power</b>	3.53dBm(Max EIRP Power=Max radiation field-95.2)
<b>Bluetooth Version</b>	V4.0
<b>Modulation</b>	GFSK, $\pi/4$ -DQPSK, 8DPSK for BR/EDR, GFSK for BLE
<b>Number of channels</b>	79 for BR/EDR, 40 for BLE
<b>Hardware Version</b>	V1
<b>Software Version</b>	V1
<b>Antenna Designation</b>	Ceramic Antenna
<b>Antenna Gain</b>	0dBi
<b>Power Supply</b>	DC 3.7V

Note: The USB port only used for charging and can't be used to transfer data with PC.

### 2.2. TABLE OF CARRIER FREQUENCIES

BR/EDR channel List

Frequency Band	Channel Number	Frequency
2400~2483.5MHZ	0	2402MHz
	1	2403MHz
	:	:
	38	2440 MHz
	39	2441 MHz
	40	2442 MHz
	:	:
	77	2479 MHz
	78	2480 MHz

BLE Channel List

Frequency Band	Channel Number	Frequency
2400~2483.5MHZ	0	2402MHz
	1	2404MHz
	:	:
	38	2478 MHz
	39	2480 MHz

### 3. MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement  $y \pm U$ , where expanded uncertainty  $U$  is based on a standard uncertainty multiplied by a coverage factor of  $k=2$ , providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	Conducted Emission Test	$\pm 3.18\text{dB}$
2	All emissions, radiated	$\pm 3.91\text{dB}$
3	Temperature	$\pm 0.5^\circ\text{C}$
4	Humidity	$\pm 2\%$

### 4. DESCRIPTION OF TEST MODES

NO.	TEST MODE DESCRIPTION
1	Low channel GFSK
2	Middle channel GFSK
3	High channel GFSK
4	Low channel $\pi/4$ -DQPSK
5	Middle channel $\pi/4$ -DQPSK
6	High channel $\pi/4$ -DQPSK
7	Low channel 8DPSK
8	Middle channel 8DPSK
9	High channel 8DPSK
10	BT Link with charging
11	BT Link

Note:

1. All the test modes can be supply by battery, only the result of the worst case was recorded in the report, if no other cases.
2. For Radiated Emission, 3axis were chosen for testing for each applicable mode.
3. The EUT used fully-charged battery when tested.

Software Setting

BlueTest3

Test Mode

PAUSE  
RADIO STATUS  
RADIO STATUS FULL  
-----  
TXSTART  
TXDATA1  
TXDATA2  
TXDATA3  
TXDATA4  
-----  
RXSTART1  
RXSTART2  
RXDATA1

Test Arguments

LO Freq. (MHz)2402  
  
Power (Ext, Int)25550

Close

Execute

Cold Reset

Warm Reset

Test Results

☐ Save to file

Browse for file

Display :

☒ Standard

☐ Bit Error

. \logfile.txt


Opening USB SPI (602250).  
Transport active.  
dal (Hardware ID 0x332) firmware version 8648.  
Sent Command Varid 5004, parameters: 0004 0962 FF32 0000 0000 0000  
Radio Test TXDATA1 successful



## 5. SYSTEM TEST CONFIGURATION


### 5.1. CONFIGURATION OF EUT SYSTEM

Configure 1: (Normal hopping)



**Note:** Owing to the EUT has own battery, Testing will be performed while PC or adapter remove.

Configure 2: (Control continuous TX)



### 5.2. EQUIPMENT USED IN EUT SYSTEM

Item	Equipment	Mfr/Brand	Model/Type No.	Remark
1	Bluetooth Headset	Dilante	S6	EUT
2	Battery	BYT	371025	Accessory
3	PC	ASUS	Y481C	A.E
4	Control box	CSR	USB_SPI_TOOLS	A.E
5	Adapter	N/A	FY0502000	A.E

### 5.3. SUMMARY OF TEST RESULTS

FCC RULES	DESCRIPTION OF TEST	RESULT
§15.249	Radiated Emission	Compliant
§15.249	Band Edges	Compliant
§15.207	Conduction Emission	Compliant
§15.215	Bandwidth	Compliant

## 6. TEST FACILITY

<b>Site</b>	Dongguan Precise Testing Service Co., Ltd.
<b>Location</b>	Building D,Baoding Technology Park,Guangming Road2,Dongcheng District, Dongguan, Guangdong, China,
<b>FCC Registration No.</b>	371540
<b>Description</b>	The test site is constructed and calibrated to meet the FCC requirements in documents ANSI C63.4:2014.

## TEST METHODOLOGY

All measurements contained in this report were conducted with ANSI C63.10-2013

## 7. ALL TEST EQUIPMENT LIST

FOR RADIATED EMISSION TEST (BELOW 1GHZ)

Radiated Emission Test Site					
Name of Equipment	Manufacturer	Model Number	Serial Number	Last Calibration	Due Calibration
EMI Test Receiver	Rohde & Schwarz	ESCI	101417	July 4, 2016	July 3, 2017
Trilog Broadband Antenna (25M-1GHz)	SCHWARZBECK	VULB9160	9160-3355	July 4, 2016	July 3, 2017
Signal Amplifier	SCHWARZBECK	BBV 9475	9745-0013	July 4, 2016	July 3, 2017
RF Cable	SCHWARZBECK	AK9515E	96221	July 4, 2016	July 3, 2017
3m Anechoic Chamber	CHENGYU	966	PTS-001	June 6, 2016	June 5, 2017
MULTI-DEVICE Positioning Controller	Max-Full	MF-7802	MF780208339	N/A	N/A
Active loop antenna (9K-30MHz)	Schwarzbeck	FMZB1519	1519-038	June 6, 2016	June 5, 2017
Spectrum analyzer	Agilent	E4407B	MY46185649	June 6, 2016	June 5, 2017
Radiation Cable 1	MXT	RS1	R005	June 6, 2016	June 5, 2017
Radiation Cable 2	MXT	RS1	R006	June 6, 2016	June 5, 2017

FOR RADIATED EMISSION TEST (1GHZ ABOVE)

Radiated Emission Test Site					
Name of Equipment	Manufacturer	Model Number	Serial Number	Last Calibration	Due Calibration
EMI Test Receiver	Rohde & Schwarz	ESCI	101417	July 4, 2016	July 3, 2017
Horn Antenna (1G-18GHz)	SCHWARZBECK	BBHA9120D	9120D-1246	July 11, 2016	July 10, 2017
Spectrum Analyzer	Agilent	E4411B	MY4511453	July 4, 2016	July 3, 2017
Signal Amplifier	SCHWARZBECK	BBV 9718	9718-269	July 7, 2016	July 6, 2017
RF Cable	SCHWARZBECK	AK9515H	96220	July 8, 2016	July 7, 2017
3m Anechoic Chamber	CHENGYU	966	PTS-001	June 6, 2016	June 5, 2017
MULTI-DEVICE Positioning Controller	Max-Full	MF-7802	MF780208339	N/A	N/A
Horn Ant (18G-40GHz)	Schwarzbeck	BBHA 9170	9170-181	June 6, 2016	June 5, 2017
Radiation Cable 1	MXT	RS1	R005	June 6, 2016	June 5, 2017
Radiation Cable 2	MXT	RS1	R006	June 6, 2016	June 5, 2017

Conducted Emission Test Site					
Name of Equipment	Manufacturer	Model Number	Serial Number	Last Calibration	Due Calibration
EMI Test Receiver	- Rohde & Schwarz	ESCI	101417	July 4, 2016	July 3, 2017
Artificial Mains Network	Narda	L2-16B	000WX31025	July 8, 2016	July 7, 2017
Artificial Mains Network (AUX)	Narda	L2-16B	000WX31026	July 8, 2016	July 7, 2017
RF Cable	SCHWARZBECK	AK9515E	96222	July 4, 2016	July 3, 2017
Shielded Room	CHENGYU	843	PTS-002	June 6, 2016	June 5, 2017
Conduction Cable	MXT	SE1	S003	June 6, 2016	June 5, 2017

## 8. RADIATED EMISSION

### 8.1 TEST LIMIT

#### Standard FCC15.249

Fundamental Frequency	Field Strength of Fundamental (millivolts/meter)	Field Strength of Harmonics (microvolts/meter)
900-928MHz	50	500
2400-2483.5MHz	50	500
5725-5875MHz	50	500
24.0-24.25GHz	250	2500

#### Standard FCC 15.209

Frequency (MHz)	Distance Meters	Field Strengths Limit	
		$\mu$ V/m	dB( $\mu$ V)/m
0.009 ~ 0.490	300	2400/F(kHz)	---
0.490 ~ 1.705	30	24000/F(kHz)	---
1.705 ~ 30	30	30	---
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
960 ~ 1000	3	500	54.0
Above 1000	3	Other:74.0 dB( $\mu$ V)/m (Peak) 54.0 dB( $\mu$ V)/m (Average)	

Remark: (1) Emission level  $\text{dB}\mu\text{V} = 20 \log \text{Emission level } \mu\text{V/m}$   
 (2) The smaller limit shall apply at the cross point between two frequency bands.  
 (3) Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.

## 8.2. MEASUREMENT PROCEDURE


1. The measuring distance of 3m shall be used for measurements. The EUT was placed on the top of a rotating table 0.8 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation(Below 1GHz)
2. The measuring distance of 3m shall used for measurements. The EUT was placed on the top of a rotating table 1.5 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation(Above 1GHz)
3. The height of the test antenna shall vary between 1m to 4m.Both horizontal and vertical polarization Of the antenna are set to make the measurement.
4. The initial step in collecting radiated emission data is a receive peak detector mode. Pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
5. All readings are peak unless otherwise stated QP in column of Note. Peak denoted that the Peak reading compliance with the QP limits and then QP Mode measurement didn't perform(Below 1GHz)
6. All readings are Peak mode value unless otherwise stated AVG in column of Note. If the Peak mode measured value compliance with the Peak limits and lower than AVG Limits, the EUT shall be deemed to meet Peak&AVG limits and then only Peak mode was measured, but AVG mode didn't perform.(Above 1GHz)

The following table is the setting of spectrum analyzer and receiver.


<b>Spectrum Parameter</b>	<b>Setting</b>
Start ~Stop Frequency	9KHz~150KHz/RB 200Hz for QP
Start ~Stop Frequency	150KHz~30MHz/RB 9KHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RB 120KHz for QP
Start ~Stop Frequency	1GHz~26.5GHz 1MHz/3MHz for Peak, 1MHz/10Hz for Average
<b>Receiver Parameter</b>	<b>Setting</b>
Start ~Stop Frequency	9KHz~150KHz/RB 200Hz for QP
Start ~Stop Frequency	150KHz~30MHz/RB 9KHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RB 120KHz for QP

8.3. TEST SETUP


Radiated Emission Test-Setup Frequency Below 30MHz



RADIATED EMISSION TEST SETUP 30MHz-1000MHz



### RADIATED EMISSION TEST SETUP ABOVE 1000MHz





## 8.4. TEST RESULT

(Worst modulation:GFSK)

FOR BR/EDR

### RADIATED EMISSION BELOW 30MHZ

No emission found between lowest internal used/generated frequencies to 30MHz.

### RADIATED EMISSION BELOW 1GHZ

RADIATED EMISSION TEST- (30MHZ-1GHZ)-LOW CHANNEL-HORIZONTAL



Site: site #1  
Limit: FCC Class B 3M Radiation  
EUT: Bluetooth Headset  
M/N: S6  
Mode: Low Channel TX  
Note:

Polarization: **Horizontal**  
Power:  
Distance:

Temperature: 22.8  
Humidity: 53.8 %

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		104.3667	8.46	9.47	17.93	43.50	-25.57	peak			
2		351.7167	7.21	18.75	25.96	46.00	-20.04	peak			
3		416.3833	11.15	19.57	30.72	46.00	-15.28	peak			
4		668.5833	4.05	24.35	28.40	46.00	-17.60	peak			
5	*	786.6000	4.82	27.14	31.96	46.00	-14.04	peak			
6		970.9000	3.07	29.80	32.87	54.00	-21.13	peak			

RESULT: PASS

# RADIATED EMISSION TEST- (30MHZ-1GHZ)-LOW CHANNEL -VERTICAL



Site: site #1  
Limit: FCC Class B 3M Radiation  
EUT: Bluetooth Headset  
M/N: S6  
Mode: Low Channel TX  
Note:

Polarization: **Vertical**  
Power:  
Distance:

Temperature: 22.8  
Humidity: 53.8 %

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		80.1167	12.98	1.84	14.82	40.00	-25.18	peak			
2		138.3167	2.41	14.50	16.91	43.50	-26.59	peak			
3		427.7000	5.49	19.91	25.40	46.00	-20.60	peak			
4		759.1167	4.32	26.76	31.08	46.00	-14.92	peak			
5		799.5333	4.43	27.31	31.74	46.00	-14.26	peak			
6	*	948.2667	2.88	29.95	32.83	46.00	-13.17	peak			

**RESULT: PASS**

**Note:** 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.

2. The "Factor" value can be calculated automatically by software of measurement system.

# RADIATED EMISSION TEST- (30MHZ-1GHZ)-MIDDLE CHANNEL-HORIZONTAL




Site: site #1 Polarization: **Horizontal** Temperature: 22.8  
Limit: FCC Class B 3M Radiation Power: Humidity: 53.8 %  
EUT: Bluetooth Headset Distance:  
M/N: S6  
Mode: Middle Channel TX  
Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		96.2833	10.99	6.77	17.76	43.50	-25.74	peak			
2		202.9832	5.53	11.70	17.23	43.50	-26.27	peak			
3		351.7167	5.72	18.75	24.47	46.00	-21.53	peak			
4		416.3833	10.02	19.57	29.59	46.00	-16.41	peak			
5		783.3667	4.06	27.09	31.15	46.00	-14.85	peak			
6	*	907.8500	3.85	28.83	32.68	46.00	-13.32	peak			

**RESULT: PASS**

# RADIATED EMISSION TEST- (30MHZ-1GHZ)- MIDDLE CHANNEL -VERTICAL



Site: site #1  
Limit: FCC Class B 3M Radiation  
EUT: Bluetooth Headset  
M/N: S6  
Mode: Middle Channel TX  
Note:

Polarization: **Vertical**  
Power:  
Distance:

Temperature: 22.8  
Humidity: 53.8 %

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		80.1167	12.73	1.84	14.57	40.00	-25.43	peak			
2		154.4832	1.16	15.29	16.45	43.50	-27.05	peak			
3		249.8667	5.26	13.89	19.15	46.00	-26.85	peak			
4		427.7000	4.96	19.91	24.87	46.00	-21.13	peak			
5		815.7000	4.61	27.32	31.93	46.00	-14.07	peak			
6	*	932.1000	3.99	29.50	33.49	46.00	-12.51	peak			

**RESULT: PASS**

**Note:** 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.

2. The "Factor" value can be calculated automatically by software of measurement system.

# RADIATED EMISSION TEST- (30MHZ-1GHZ)-HIGH CHANNEL-HORIZONTAL



Site: site #1  
Limit: FCC Class B 3M Radiation  
EUT: Bluetooth Headset  
M/N: S6  
Mode: High Channel TX  
Note:

Polarization: **Horizontal**  
Power:  
Distance:

Temperature: 22.8  
Humidity: 53.8 %

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		125.3833	18.55	8.37	26.92	43.50	-16.58	peak			
2		201.3667	10.39	11.86	22.25	43.50	-21.25	peak			
3		416.3833	10.06	19.57	29.63	46.00	-16.37	peak			
4		628.1667	4.21	23.80	28.01	46.00	-17.99	peak			
5	*	768.8167	7.42	26.89	34.31	46.00	-11.69	peak			
6		948.2667	3.41	29.95	33.36	46.00	-12.64	peak			

**RESULT: PASS**

# RADIATED EMISSION TEST- (30MHZ-1GHZ)-HIGH CHANNEL -VERTICAL



Site: site #1  
Limit: FCC Class B 3M Radiation  
EUT: Bluetooth Headset  
M/N: S6  
Mode: High Channel TX  
Note:

Polarization: **Vertical**  
Power:  
Distance:

Temperature: 22.8  
Humidity: 53.8 %

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		80.1167	16.77	1.84	18.61	40.00	-21.39	peak			
2		133.4667	9.29	12.48	21.77	43.50	-21.73	peak			
3		253.1000	11.55	13.99	25.54	46.00	-20.46	peak			
4		427.7000	5.66	19.91	25.57	46.00	-20.43	peak			
5		773.6667	6.25	26.96	33.21	46.00	-12.79	peak			
6	*	948.2667	3.95	29.95	33.90	46.00	-12.10	peak			

## RESULT: PASS

**Note:** 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.

2. The "Factor" value can be calculated automatically by software of measurement system.

FOR BLE

### RADIATED EMISSION BELOW 30MHZ

No emission found between lowest internal used/generated frequencies to 30MHz.

### RADIATED EMISSION BELOW 1GHZ

RADIATED EMISSION TEST- (30MHZ-1GHZ)-LOW CHANNEL-HORIZONTAL



Site: site #1  
Limit: FCC Class B 3M Radiation  
EUT: Bluetooth Headset  
M/N: S6  
Mode: Low Channel TX  
Note:


Polarization: *Horizontal*  
Power:  
Distance:

Temperature: 22.8  
Humidity: 53.8 %

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		131.8498	8.57	11.39	19.96	43.50	-23.54	peak			
2		371.1166	8.50	18.88	27.38	46.00	-18.62	peak			
3		427.6999	9.99	19.91	29.90	46.00	-16.10	peak			
4		668.5833	4.05	24.35	28.40	46.00	-17.60	peak			
5		760.7332	4.34	26.78	31.12	46.00	-14.88	peak			
6	*	935.3333	2.74	29.59	32.33	46.00	-13.67	peak			

RESULT: PASS

# RADIATED EMISSION TEST- (30MHZ-1GHZ)-LOW CHANNEL -VERTICAL



Site: site #1  
Limit: FCC Class B 3M Radiation  
EUT: Bluetooth Headset  
M/N: S6  
Mode: Low Channel TX  
Note:

Polarization: **Vertical**  
Power:  
Distance:

Temperature: 22.8  
Humidity: 53.8 %

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		152.8667	7.71	15.28	22.99	43.50	-20.51	peak			
2		317.7667	2.97	16.59	19.56	46.00	-26.44	peak			
3		427.6999	3.49	19.91	23.40	46.00	-22.60	peak			
4		759.1167	2.82	26.76	29.58	46.00	-16.42	peak			
5		799.5333	2.92	27.31	30.23	46.00	-15.77	peak			
6	*	945.0333	1.13	29.86	30.99	46.00	-15.01	peak			

**RESULT: PASS**

**Note:** 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.

2. The "Factor" value can be calculated automatically by software of measurement system.



# RADIATED EMISSION TEST- (30MHZ-1GHZ)-MIDDLE CHANNEL-HORIZONTAL



Site: site #1

Limit: FCC Class B 3M Radiation

EUT: Bluetooth Headset

M/N: S6

Mode: Middle Channel TX

Note:

Polarization: *Horizontal*

Power:

Distance:


Temperature: 22.8

Humidity: 53.8 %

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		99.5167	11.16	10.00	21.16	43.50	-22.34	peak			
2		351.7167	5.72	18.75	24.47	46.00	-21.53	peak			
3		419.6166	8.84	19.67	28.51	46.00	-17.49	peak			
4		589.3667	3.70	23.46	27.16	46.00	-18.84	peak			
5		760.7332	3.73	26.78	30.51	46.00	-15.49	peak			
6	*	954.7332	1.65	29.95	31.60	46.00	-14.40	peak			

**RESULT: PASS**

## RADIATED EMISSION TEST- (30MHZ-1GHZ)- MIDDLE CHANNEL -VERTICAL



Site: site #1

Polarization: **Vertical**

Temperature: 22.8

Limit: FCC Class B 3M Radiation

Power:

Humidity: 53.8 %

EUT: Bluetooth Headset

Distance:

M/N: S6

Mode: Middle Channel TX


Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		123.7667	11.24	8.43	19.67	43.50	-23.83	peak			
2		249.8667	6.26	13.89	20.15	46.00	-25.85	peak			
3		427.6999	5.96	19.91	25.87	46.00	-20.13	peak			
4		728.3999	1.46	26.01	27.47	46.00	-18.53	peak			
5		783.3667	2.42	27.09	29.51	46.00	-16.49	peak			
6	*	815.7000	3.61	27.32	30.93	46.00	-15.07	peak			

**RESULT: PASS****Note:** 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.

2. The "Factor" value can be calculated automatically by software of measurement system.

# RADIATED EMISSION TEST- (30MHZ-1GHZ)-HIGH CHANNEL-HORIZONTAL




Site: site #1 Polarization: **Horizontal** Temperature: 22.8  
Limit: FCC Class B 3M Radiation Power: Humidity: 53.8 %  
EUT: Bluetooth Headset Distance:  
M/N: S6  
Mode: High Channel TX  
Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		112.4500	13.26	7.60	20.86	43.50	-22.64	peak			
2		125.3833	15.05	8.37	23.42	43.50	-20.08	peak			
3		199.7500	11.56	11.99	23.55	43.50	-19.95	peak			
4		351.7167	8.93	18.75	27.68	46.00	-18.32	peak			
5		416.3833	8.56	19.57	28.13	46.00	-17.87	peak			
6	*	768.8165	4.92	26.89	31.81	46.00	-14.19	peak			

**RESULT: PASS**

# RADIATED EMISSION TEST- (30MHZ-1GHZ)-HIGH CHANNEL -VERTICAL



Site: site #1  
Limit: FCC Class B 3M Radiation  
EUT: Bluetooth Headset  
M/N: S6  
Mode: High Channel TX  
Note:

Polarization: **Vertical**  
Power:  
Distance:

Temperature: 22.8  
Humidity: 53.8 %

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		83.3499	18.90	3.00	21.90	40.00	-18.10	peak			
2		162.5665	6.90	15.17	22.07	43.50	-21.43	peak			
3		253.0998	11.55	13.99	25.54	46.00	-20.46	peak			
4		351.7167	4.93	18.75	23.68	46.00	-22.32	peak			
5		539.2500	2.77	22.19	24.96	46.00	-21.04	peak			
6	*	773.6666	5.25	26.96	32.21	46.00	-13.79	peak			

**RESULT: PASS**

**Note:** 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.


2. The "Factor" value can be calculated automatically by software of measurement system.

# RADIATED EMISSION ABOVE 1GHZ

(Worst modulation: GFSK)

FOR BR/EDR

RADIATED EMISSION TEST- (ABOVE 1GHZ)-LOW CHANNEL-HORIZONTAL




Site: site #1 Polarization: *Horizontal* Temperature: 26  
Limit: FCC Class B 3M Radiation above 1GHZ(PK)- Power: Humidity: 60 %  
EUT: Bluetooth Headset Distance: 3m  
M/N: S6  
Mode: Low Channel TX  
Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2402.000	106.78	-9.68	97.10	114.00	-16.90	peak			
2	*	2402.000	93.65	-9.68	83.97	94.00	-10.03	AVG	100	87	
3		3608.333	52.94	-7.22	45.72	74.00	-28.28	peak			
4		5366.667	47.61	-1.81	45.80	74.00	-28.20	peak			

RESULT: PASS

# RADIATED EMISSION TEST- (ABOVE 1GHZ)-LOW CHANNEL- VERTICAL




Site: site #1 Polarization: **Vertical** Temperature: 26  
Limit: FCC Class B 3M Radiation above 1GHZ(PK)- Power: Humidity: 60 %  
EUT: Bluetooth Headset Distance: 3m  
M/N: S6  
Mode: Low Channel TX  
Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2402.000	107.18	-9.68	97.50	114.00	-16.50	peak			
2	*	2402.000	94.09	-9.68	84.41	94.00	-9.59	AVG	100	165	
3		3041.667	54.60	-8.32	46.28	74.00	-27.72	peak			
4		4583.333	48.82	-2.89	45.93	74.00	-28.07	peak			

**RESULT: PASS**

# RADIATED EMISSION TEST- (ABOVE 1GHZ)-MIDDLE CHANNEL-HORIZONTAL




Site: site #1 Polarization: *Horizontal* Temperature: 26  
Limit: FCC Class B 3M Radiation above 1GHZ(PK)- Power: Humidity: 60 %  
EUT: Bluetooth Headset Distance: 3m  
M/N: S6  
Mode: Middle Channel TX  
Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2441.000	107.84	-9.63	98.21	114.00	-15.79	peak			
2	*	2441.000	93.06	-9.63	83.43	94.00	-10.57	AVG	100	88	
3		2833.333	54.84	-8.76	46.08	74.00	-27.92	peak			
4		5533.333	47.57	-1.79	45.78	74.00	-28.22	peak			

**RESULT: PASS**

# RADIATED EMISSION TEST- (ABOVE 1GHZ)-MIDDLE CHANNEL- VERTICAL




Site: site #1 Polarization: **Vertical** Temperature: 26  
Limit: FCC Class B 3M Radiation above 1GHZ(PK)- Power: Humidity: 60 %  
EUT: Bluetooth Headset Distance: 3m  
M/N: S6  
Mode: Middle Channel TX  
Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2441.000	108.19	-9.63	98.56	114.00	-15.44	peak			
2	*	2441.000	93.64	-9.63	84.01	94.00	-9.99	AVG	100	53	
3		3833.333	51.87	-5.84	46.03	74.00	-27.97	peak			
4		5475.000	48.56	-1.81	46.75	74.00	-27.25	peak			

**RESULT: PASS**



# RADIATED EMISSION TEST- (ABOVE 1GHZ)-HIGH CHANNEL-HORIZONTAL




Site: site #1 Polarization: *Horizontal* Temperature: 26  
Limit: FCC Class B 3M Radiation above 1GHZ(PK)- Power: Humidity: 60 %  
EUT: Bluetooth Headset Distance: 3m  
M/N: S6  
Mode: High Channel TX  
Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2480.000	107.83	-9.59	98.24	114.00	-15.76	peak			
2	*	2480.000	94.26	-9.59	84.67	94.00	-9.33	AVG	100	89	
3		2700.000	54.88	-9.09	45.79	74.00	-28.21	peak			
4		4175.000	49.77	-4.21	45.56	74.00	-28.44	peak			

**RESULT: PASS**

# RADIATED EMISSION TEST- (ABOVE 1GHZ)-HIGH CHANNEL- VERTICAL



Site: site #1 Polarization: **Vertical** Temperature: 26  
Limit: FCC Class B 3M Radiation above 1GHZ(PK)- Power: Humidity: 60 %  
EUT: Bluetooth Headset Distance: 3m  
M/N: S6  
Mode: High Channel TX  
Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2480.000	107.92	-9.59	98.33	114.00	-15.67	peak			
2	*	2480.000	95.31	-9.59	85.72	94.00	-8.28	AVG	100	152	
3		2858.333	54.38	-8.70	45.68	74.00	-28.32	peak			
4		4733.333	48.89	-2.50	46.39	74.00	-27.61	peak			

## RESULT: PASS

**Note:** 6~25GHz at least have 20dB margin. No recording in the test report.

Factor=Antenna Factor + Cable loss - Amplifier gain, Margin=Measurement-Limit.

The "Factor" value can be calculated automatically by software of measurement system.

# **Field strength of the fundamental signal**

## **1Mbps Result:**

### **Peak value**

Frequency	Reading Level	Factor	Measurement	Limit	Over	Antenna
(MHz)	(dBuv)	(dB/m)	(dBuv/m)	(dBuv/m)	(dB)	Polarization
2402	106.78	-9.68	97.10	114	-16.90	Horizontal
2402	107.18	-9.68	97.50	114	-16.50	Vertical
2441	107.84	-9.63	98.21	114	-15.79	Horizontal
2441	108.19	-9.63	98.56	114	-15.44	Vertical
2480	107.83	-9.59	98.24	114	-15.76	Horizontal
2480	107.92	-9.59	98.33	114	-15.67	Vertical

### **Average value**

Frequency	Reading Level	Factor	Measurement	Limit	Over	Antenna
(MHz)	(dBuv)	(dB/m)	(dBuv/m)	(dBuv/m)	(dB)	Polarization
2402	93.65	-9.68	83.97	94	-10.03	Horizontal
2402	94.09	-9.68	84.41	94	-9.59	Vertical
2441	93.06	-9.63	83.43	94	-10.57	Horizontal
2441	93.64	-9.63	84.01	94	-9.99	Vertical
2480	94.26	-9.59	84.67	94	-9.33	Horizontal
2480	95.31	-9.59	85.72	94	-8.28	Vertical

**2Mbps Result:**

**Peak value**

Frequency	Reading Level	Factor	Measurement	Limit	Over	Antenna
(MHz)	(dBuv)	(dB/m)	(dBuv/m)	(dBuv/m)	(dB)	Polarization
2402	106.81	-9.68	97.13	114	-16.87	Horizontal
2402	106.73	-9.68	97.05	114	-16.95	Vertical
2441	107.89	-9.68	98.21	114	-15.79	Horizontal
2441	107.79	-9.68	98.11	114	-15.89	Vertical
2480	107.61	-9.63	97.98	114	-16.02	Horizontal
2480	107.51	-9.63	97.88	114	-16.12	Vertical

**Average value**

Frequency	Reading Level	Factor	Measurement	Limit	Over	Antenna
(MHz)	(dBuv)	(dB/m)	(dBuv/m)	(dBuv/m)	(dB)	Polarization
2402	93.70	-9.63	84.07	94	-9.93	Horizontal
2402	93.64	-9.63	84.01	94	-9.99	Vertical
2441	93.48	-9.59	83.89	94	-10.11	Horizontal
2441	93.37	-9.59	83.78	94	-10.22	Vertical
2480	95.01	-9.59	85.42	94	-8.58	Horizontal
2480	94.88	-9.59	85.29	94	-8.71	Vertical

### 3Mbps Result:

#### Peak value


Frequency	Reading Level	Factor	Measurement	Limit	Over	Antenna
(MHz)	(dBuv)	(dB/m)	(dBuv/m)	(dBuv/m)	(dB)	Polarization
2402	106.59	-9.68	96.91	114	-17.09	Horizontal
2402	106.52	-9.68	96.84	114	-17.16	Vertical
2441	107.66	-9.68	97.98	114	-16.02	Horizontal
2441	107.6	-9.68	97.92	114	-16.08	Vertical
2480	107.39	-9.63	97.76	114	-16.24	Horizontal
2480	107.31	-9.63	97.68	114	-16.32	Vertical

#### Average value

Frequency	Reading Level	Factor	Measurement	Limit	Over	Antenna
(MHz)	(dBuv)	(dB/m)	(dBuv/m)	(dBuv/m)	(dB)	Polarization
2402	93.50	-9.63	83.87	94	-10.13	Horizontal
2402	93.39	-9.63	83.76	94	-10.24	Vertical
2441	93.24	-9.59	83.65	94	-10.35	Horizontal
2441	96.13	-9.59	86.54	94	-7.46	Vertical
2480	94.70	-9.59	85.11	94	-8.89	Horizontal
2480	94.58	-9.59	84.99	94	-9.01	Vertical

FOR BLE

RADIATED EMISSION TEST- (ABOVE 1GHZ)-LOW CHANNEL-HORIZONTAL




Site: site #1	Polarization: <i>Horizontal</i>	Temperature: 26
Limit: FCC Class B 3M Radiation above 1GHZ(PK)-	Power:	Humidity: 60 %
EUT: Bluetooth Headset	Distance: 3m	
M/N: S6		
Mode: Low Channel TX		
Note:		

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2402.000	107.69	-9.68	98.01	114.00	-15.99	peak			
2	*	2402.000	92.80	-9.68	83.12	94.00	-10.88	AVG	100	55	
3		3500.000	53.41	-7.89	45.52	74.00	-28.48	peak			
4		4175.000	49.61	-4.21	45.40	74.00	-28.60	peak			

RESULT: PASS

# RADIATED EMISSION TEST- (ABOVE 1GHZ)-LOW CHANNEL- VERTICAL




Site: site #1 Polarization: **Vertical** Temperature: 26  
Limit: FCC Class B 3M Radiation above 1GHZ(PK)- Power: Humidity: 60 %  
EUT: Bluetooth Headset Distance: 3m  
M/N: S6  
Mode: Low Channel TX  
Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2402.000	107.77	-9.68	98.09	114.00	-15.91	peak			
2	*	2402.000	94.19	-9.68	84.51	94.00	-9.49	AVG	100	182	
3		3533.333	53.31	-7.68	45.63	74.00	-28.37	peak			
4		5016.667	46.99	-1.80	45.19	74.00	-28.81	peak			

**RESULT: PASS**

# RADIATED EMISSION TEST- (ABOVE 1GHZ)-MIDDLE CHANNEL-HORIZONTAL




Site: site #1 Polarization: *Horizontal* Temperature: 26  
Limit: FCC Class B 3M Radiation above 1GHZ(PK)- Power: Humidity: 60 %  
EUT: Bluetooth Headset Distance: 3m  
M/N: S6  
Mode: Middle Channel TX  
Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2440.000	108.26	-9.64	98.62	114.00	-15.38	peak			
2	*	2440.000	94.96	-9.64	85.32	94.00	-8.68	AVG	100	69	
3		3558.333	53.39	-7.53	45.86	74.00	-28.14	peak			
4		4583.333	48.19	-2.89	45.30	74.00	-28.70	peak			

**RESULT: PASS**



## RADIATED EMISSION TEST- (ABOVE 1GHZ)-MIDDLE CHANNEL- VERTICAL



Site: site #1

Polarization: *Vertical*

Temperature: 26

Limit: FCC Class B 3M Radiation above 1GHZ(PK)-

Power:

Humidity: 60 %

EUT: Bluetooth Headset

Distance: 3m

M/N: S6


Mode: Middle Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2440.000	108.29	-9.64	98.65	114.00	-15.35	peak			
2	*	2440.000	96.97	-9.64	87.33	94.00	-6.67	AVG	100	176	
3		3183.333	54.81	-8.19	46.62	74.00	-27.38	peak			
4		4958.333	47.58	-1.91	45.67	74.00	-28.33	peak			

**RESULT: PASS**

# RADIATED EMISSION TEST- (ABOVE 1GHZ)-HIGH CHANNEL-HORIZONTAL




Site: site #1 Polarization: *Horizontal* Temperature: 26  
Limit: FCC Class B 3M Radiation above 1GHZ(PK)- Power: Humidity: 60 %  
EUT: Bluetooth Headset Distance: 3m  
M/N: S6  
Mode: High Channel TX  
Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		1291.667	60.62	-15.47	45.15	74.00	-28.85	peak			
2		2480.000	108.32	-9.59	98.73	114.00	-15.27	peak			
3	*	2480.000	95.25	-9.59	85.66	94.00	-8.34	AVG	100	70	
4		3941.667	51.60	-5.17	46.43	74.00	-27.57	peak			

**RESULT: PASS**

# RADIATED EMISSION TEST- (ABOVE 1GHZ)-HIGH CHANNEL- VERTICAL



Site: site #1 Polarization: **Vertical** Temperature: 26  
Limit: FCC Class B 3M Radiation above 1GHZ(PK)- Power: Humidity: 60 %  
EUT: Bluetooth Headset Distance: 3m  
M/N: S6  
Mode: High Channel TX  
Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2480.000	107.40	-9.59	97.81	114.00	-16.19	peak			
2	*	2480.000	95.15	-9.59	85.56	94.00	-8.44	AVG	100	181	
3		3016.667	54.95	-8.34	46.61	74.00	-27.39	peak			
4		5450.000	48.46	-1.81	46.65	74.00	-27.35	peak			

## RESULT: PASS

**Note:** 6~25GHz at least have 20dB margin. No recording in the test report.

Factor=Antenna Factor + Cable loss - Amplifier gain, Margin=Measurement-Limit.

The "Factor" value can be calculated automatically by software of measurement system.

# **Field strength of the fundamental signal**

## **Peak value**

Frequency	Reading Level	Factor	Measurement	Limit	Over	Antenna
(MHz)	(dBuv)	(dB/m)	(dBuv/m)	(dBuv/m)	(dB)	Polarization
2402	107.69	-9.68	98.01	114	-15.99	Horizontal
2402	107.77	-9.68	98.07	114	-15.91	Vertical
2440	108.26	-9.64	98.62	114	-15.38	Horizontal
2440	108.29	-9.64	98.65	114	-15.35	Vertical
2480	108.32	-9.59	98.73	114	-15.27	Horizontal
2480	107.40	-9.59	97.81	114	-16.19	Vertical

## **Average value**

Frequency	Reading Level	Factor	Measurement	Limit	Over	Antenna
(MHz)	(dBuv)	(dB/m)	(dBuv/m)	(dBuv/m)	(dB)	Polarization
2402	92.80	-9.68	83.12	94	-10.88	Horizontal
2402	94.19	-9.68	84.51	94	-9.49	Vertical
2440	94.96	-9.64	85.32	94	-8.68	Horizontal
2440	96.97	-9.64	87.33	94	-6.67	Vertical
2480	95.25	-9.59	85.66	94	-8.34	Horizontal
2480	95.15	-9.59	85.56	94	-8.44	Vertical


## 9. BAND EDGE EMISSION

### 9.1. MEASUREMENT PROCEDURE

- 1The EUT operates at hopping-off test mode. The lowest or highest channels are tested to verify the largest transmission and spurious emissions power at the continuous transmission mode.
- 2Max hold the trace of the setup 1, and the EUT operates at hopping-on test mode to verify the largest spurious emissions power.
- 3Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of the emission

### 9.2 TEST SETUP

RADIATED EMISSION TEST SETUP




### 9.3 RADIATED TEST RESULT

(Worst modulation: GFSK)

FOR BR/EDR


TEST PLOT OF BAND EDGE FOR LOW CHANNEL-Horizontal



Site: site #1	Polarization: <i>Horizontal</i>	Temperature: 26
Limit: FCC Class B 3M Radiation above 1GHZ(PK)	Power:	Humidity: 60 %
EUT: Bluetooth Headset	Distance:	
M/N: S6		
Mode: Low Channel TX		
Note:		

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2354.092	32.23	10.27	42.50	74.00	-31.50	peak			
2		2390.000	33.12	10.31	43.43	74.00	-30.57	peak			
3	*	2402.000	86.91	10.32	97.23	74.00	23.23	peak			

# TEST PLOT OF BAND EDGE FOR LOW CHANNEL -Vertical



Site: site #1

Polarization: **Vertical**

Temperature: 26

Limit: FCC Class B 3M Radiation above 1GHZ(PK)

Power:

Humidity: 60 %

EUT: Bluetooth Headset

Distance:


M/N: S6

Mode: Low Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2257.400	32.00	10.16	42.16	74.00	-31.84	peak			
2		2390.000	32.84	10.31	43.15	74.00	-30.85	peak			
3	*	2402.000	87.26	10.32	97.58	74.00	23.58	peak			

# TEST PLOT OF BAND EDGE FOR HIGH CHANNEL -Horizontal




Site: site #1	Polarization: <b>Horizontal</b>	Temperature: 26
Limit: FCC Class B 3M Radiation above 1GHZ(PK)	Power:	Humidity: 60 %
EUT: Bluetooth Headset	Distance:	
M/N: S6		
Mode: High Channel TX		
Note:		

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	2480.000	87.96	10.41	98.37	74.00	24.37	peak			
2		2483.500	29.75	10.41	40.16	74.00	-33.84	peak			
3		2495.013	31.28	10.42	41.70	74.00	-32.30	peak			



# TEST PLOT OF BAND EDGE FOR HIGH CHANNEL-Vertical



Site: site #1 Polarization: **Vertical** Temperature: 26  
Limit: FCC Class B 3M Radiation above 1GHZ(PK) Power: Humidity: 60 %  
EUT: Bluetooth Headset Distance:  
M/N: S6  
Mode: High Channel TX  
Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	2480.000	87.85	10.41	98.26	74.00	24.26	peak			
2		2483.500	29.87	10.41	40.28	74.00	-33.72	peak			
3		2487.570	30.94	10.42	41.36	74.00	-32.64	peak			

## RESULT: PASS

**Note:** The other modes radiation emission have enough 20dB margin.


Factor=Antenna Factor + Cable loss - Amplifier gain, Over=Measure-Limit.

The "Factor" value can be calculated automatically by software of measurement system.

Hopping on mode and Hopping off mode have been tested, but only worst case reported.

FOR BLE


TEST PLOT OF BAND EDGE FOR LOW CHANNEL-Horizontal



Site: site #1 Polarization: **Horizontal** Temperature: 26  
Limit: FCC Class B 3M Radiation above 1GHZ(PK) Power: Humidity: 60 %  
EUT: Bluetooth Headset Distance:  
M/N: S6  
Mode: Low Channel TX  
Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2309.675	32.38	10.22	42.60	74.00	-31.40	peak			
2		2390.000	34.12	10.31	44.43	74.00	-29.57	peak			
3	*	2402.000	87.91	10.32	98.23	74.00	24.23	peak			


# TEST PLOT OF BAND EDGE FOR LOW CHANNEL -Vertical



Site: site #1 Polarization: **Vertical** Temperature: 26  
Limit: FCC Class B 3M Radiation above 1GHZ(PK) Power: Humidity: 60 %  
EUT: Bluetooth Headset Distance:  
M/N: S6  
Mode: Low Channel TX  
Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2257.400	32.50	10.16	42.66	74.00	-31.34	peak			
2		2390.000	31.34	10.31	41.65	74.00	-32.35	peak			
3	*	2402.000	87.76	10.32	98.08	74.00	24.08	peak			


# TEST PLOT OF BAND EDGE FOR HIGH CHANNEL -Horizontal



Site: site #1 Polarization: *Horizontal* Temperature: 26  
Limit: FCC Class B 3M Radiation above 1GHZ(PK) Power: Humidity: 60 %  
EUT: Bluetooth Headset Distance:  
M/N: S6  
Mode: High Channel TX  
Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	2480.000	87.96	10.41	98.37	74.00	24.37	peak			
2		2483.500	31.75	10.41	42.16	74.00	-31.84	peak			
3		2488.487	30.64	10.42	41.06	74.00	-32.94	peak			

# TEST PLOT OF BAND EDGE FOR HIGH CHANNEL-Vertical



Site: site #1 Polarization: **Vertical** Temperature: 26  
Limit: FCC Class B 3M Radiation above 1GHZ(PK) Power: Humidity: 60 %  
EUT: Bluetooth Headset Distance:  
M/N: S6  
Mode: High Channel TX  
Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	2480.000	87.85	10.41	98.26	74.00	24.26	peak			
2		2483.500	30.37	10.41	40.78	74.00	-33.22	peak			
3		2492.483	30.99	10.42	41.41	74.00	-32.59	peak			

## RESULT: PASS

**Note:** The other modes radiation emission have enough 20dB margin.

Factor=Antenna Factor + Cable loss - Amplifier gain, Over=Measure-Limit.

The "Factor" value can be calculated automatically by software of measurement system.


## 10. 20DB BANDWIDTH

### 10.1. MEASUREMENT PROCEDURE

1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
2. Set the EUT Work on the top, the middle and the bottom operation frequency individually.
3. Set Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hoping channel  
RBW  $\geq$  1% of the 20 dB bandwidth, VBW  $\geq$  RBW; Sweep = auto; Detector function = peak
4. Set SPA Trace 1 Max hold, then View.

### 10.2. TEST SET-UP

(BLOCK DIAGRAM OF CONFIGURATION)




Note: The EUT has been used temporary antenna connector for testing.

### 10.3. LIMITS AND MEASUREMENT RESULTS


FOR BR/EDR

BLUETOOTH 1MBPS LIMITS AND MEASUREMENT RESULT				
Applicable Limits	Measurement Result			
	Test Data (MHz)			Result
		99%OBW (MHz)	-20dB BW(MHz)	
N/A	Low Channel	0.927	1.095	PASS
	Middle Channel	0.924	1.091	PASS
	High Channel	0.930	1.092	PASS


TEST PLOT OF BANDWIDTH FOR LOW CHANNEL



TEST PLOT OF BANDWIDTH FOR MIDDLE CHANNEL




TEST PLOT OF BANDWIDTH FOR HIGH CHANNEL






BLUETOOTH 2MBPS LIMITS AND MEASUREMENT RESULT				
Applicable Limits	Measurement Result			
	Test Data (MHz)			Result
		99%OBW (MHz)	-20dB BW(MHz)	
N/A	Low Channel	1.200	1.368	PASS
	Middle Channel	1.219	1.374	PASS
	High Channel	1.235	1.379	PASS


TEST PLOT OF BANDWIDTH FOR LOW CHANNEL



### TEST PLOT OF BANDWIDTH FOR MIDDLE CHANNEL




### TEST PLOT OF BANDWIDTH FOR HIGH CHANNEL




BLUETOOTH 3MBPS LIMITS AND MEASUREMENT RESULT				
Applicable Limits	Measurement Result			
	Test Data (MHz)			Result
		99%OBW (MHz)	-20dB BW(MHz)	
N/A	Low Channel	1.228	1.374	PASS
	Middle Channel	1.233	1.380	PASS
	High Channel	1.241	1.384	PASS


TEST PLOT OF BANDWIDTH FOR LOW CHANNEL



TEST PLOT OF BANDWIDTH FOR MIDDLE CHANNEL




TEST PLOT OF BANDWIDTH FOR HIGH CHANNEL




FOR BLE

BLUETOOTH 1MBPS LIMITS AND MEASUREMENT RESULT				
Applicable Limits	Measurement Result			
	Test Data (MHz)			Result
		99%OBW (MHz)	-20dB BW(MHz)	
N/A	Low Channel	1.058	1.208	PASS
	Middle Channel	1.051	1.210	PASS
	High Channel	1.057	1.210	PASS


TEST PLOT OF BANDWIDTH FOR LOW CHANNEL



### TEST PLOT OF BANDWIDTH FOR MIDDLE CHANNEL



### TEST PLOT OF BANDWIDTH FOR HIGH CHANNEL



## 11. FCC LINE CONDUCTED EMISSION TEST


### 11.1. LIMITS OF LINE CONDUCTED EMISSION TEST

Frequency	Maximum RF Line Voltage	
	Q.P.( dBuV)	Average( dBuV)
150kHz~500kHz	66-56	56-46
500kHz~5MHz	56	46
5MHz~30MHz	60	50

Note:

1. The lower limit shall apply at the transition frequency.
2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.

### 11.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST



### **11.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST**

1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
2. Support equipment, if needed, was placed as per ANSI C63.10.
3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10.
4. All support equipments received AC120V/60Hz power from a LISN, if any.
5. The EUT received DC charging voltage by adapter or PC which received 120V/60Hz power by a LISN.
6. The test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
7. Analyzer / Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.
8. During the above scans, the emissions were maximized by cable manipulation.
9. The test mode(s) were scanned during the preliminary test.

Then, the EUT configuration and cable configuration of the above highest emission level were recorded for reference of final testing.

### **11.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST**


1. EUT and support equipment was set up on the test bench as per step 2 of the preliminary test.
2. A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. If EUT emission level was less -2dB to the A.V. limit in Peak mode, then the emission signal was re-checked using Q.P and Average detector.
3. The test data of the worst case condition(s) was reported on the Summary Data page.



11.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST

By adapter(worst case)  
FOR BR/EDR


Line Conducted Emission Test Line 1-L



Site: Conduction	Phase: L1	Temperature: 22.9
Limit: FCC Class B Conduction(QP)	Power:	Humidity: 56.3 %
EUT: Bluetooth Headset		
M/N: S6		
Mode: BT Link with chharging		
Note:		

No.	Freq. (MHz)	Reading_Level (dBuV)			Correct Factor (dB)	Measurement (dBuV)			Limit (dBuV)		Margin (dB)		P/F	Comment
		Peak	QP	AVG		Peak	QP	AVG	QP	AVG	QP	AVG		
1	0.5100	30.49		15.92	10.39	40.88		26.31	56.00	46.00	-15.12	-19.69	P	
2	0.8300	33.71		19.20	10.32	44.03		29.52	56.00	46.00	-11.97	-16.48	P	
3	1.7860	32.33		20.33	10.29	42.62		30.62	56.00	46.00	-13.38	-15.38	P	
4	2.6820	31.78		18.65	10.47	42.25		29.12	56.00	46.00	-13.75	-16.88	P	
5	6.3819	35.19		19.45	10.30	45.49		29.75	60.00	50.00	-14.51	-20.25	P	
6	16.3739	32.06		18.01	10.12	42.18		28.13	60.00	50.00	-17.82	-21.87	P	

Line Conducted Emission Test Line 2-N



Site: Conduction  
Limit: FCC Class B Conduction(QP)  
EUT: Bluetooth Headset  
M/N: S6  
Mode: BT Link with charging  
Note:


Phase: N  
Power:

Temperature: 22.9  
Humidity: 56.3 %

No.	Freq. (MHz)	Reading_Level (dBuV)			Correct Factor	Measurement (dBuV)			Limit (dBuV)		Margin (dB)		P/F	Comment
		Peak	QP	AVG		Peak	QP	AVG	QP	AVG	QP	AVG		
1	0.2540	29.03		12.49	10.27	39.30		22.76	61.62	51.62	-22.32	-28.86	P	
2	0.5740	29.53		20.36	10.33	39.86		30.69	56.00	46.00	-16.14	-15.31	P	
3	2.6099	26.67		15.08	10.46	37.13		25.54	56.00	46.00	-18.87	-20.46	P	
4	2.9140	28.07		9.77	10.53	38.60		20.30	56.00	46.00	-17.40	-25.70	P	
5	6.1099	32.27		19.91	10.28	42.55		30.19	60.00	50.00	-17.45	-19.81	P	
6	15.9179	32.26		13.39	10.11	42.37		23.50	60.00	50.00	-17.63	-26.50	P	

FOR BLE


Line Conducted Emission Test Line 1-L



Site: Conduction	Phase: L1	Temperature: 22.9
Limit: FCC Class B Conduction(QP)	Power:	Humidity: 56.3 %
EUT: Bluetooth Headset		
M/N: S6		
Mode: BT Link with charging		
Note:		

No.	Freq. (MHz)	Reading_Level (dBuV)			Correct Factor (dB)	Measurement (dBuV)			Limit (dBuV)		Margin (dB)		P/F	Comment
		Peak	QP	AVG		Peak	QP	AVG	QP	AVG	QP	AVG		
1	0.4420	26.51		12.04	10.36	36.87		22.40	57.02	47.02	-20.15	-24.62	P	
2	0.9540	30.78		19.57	10.39	41.17		29.96	56.00	46.00	-14.83	-16.04	P	
3	2.9180	32.84		17.18	10.53	43.37		27.71	56.00	46.00	-12.63	-18.29	P	
4	3.7980	33.64		16.19	10.46	44.10		26.65	56.00	46.00	-11.90	-19.35	P	
5	5.8859	34.72		19.18	10.27	44.99		29.45	60.00	50.00	-15.01	-20.55	P	
6	16.3699	30.36		17.16	10.12	40.48		27.28	60.00	50.00	-19.52	-22.72	P	

# Line Conducted Emission Test Line 2-N



Site: Conduction

Phase: N

Temperature: 22.9

Limit: FCC Class B Conduction(QP)

Power:

Humidity: 56.3 %

EUT: Bluetooth Headset

M/N: S6

Mode: BT Link with charging

Note:


No.	Freq. (MHz)	Reading_Level (dBuV)			Correct Factor dB	Measurement (dBuV)			Limit (dBuV)		Margin (dB)		P/F	Comment
		Peak	QP	AVG		Peak	QP	AVG	QP	AVG	QP	AVG		
1	0.2540	27.42		13.20	10.27	37.69		23.47	61.62	51.62	-23.93	-28.15	P	
2	0.5740	27.25		19.45	10.33	37.58		29.78	56.00	46.00	-18.42	-16.22	P	
3	0.8260	27.04		17.08	10.31	37.35		27.39	56.00	46.00	-18.65	-18.61	P	
4	1.6500	27.25		10.83	10.33	37.58		21.16	56.00	46.00	-18.42	-24.84	P	
5	6.6139	31.80		20.64	10.31	42.11		30.95	60.00	50.00	-17.89	-19.05	P	
6	15.5779	30.42		11.66	10.11	40.53		21.77	60.00	50.00	-19.47	-28.23	P	



## APPENDIX A: PHOTOGRAPHS OF TEST SETUP

### FCC LINE CONDUCTED EMISSION TEST SETUP




### FCC RADIATED EMISSION TEST SETUP










## APPENDIX B: PHOTOGRAPHS OF EUT

TOP VIEW OF EUT



BOTTOM VIEW OF EUT






FRONT VIEW OF EUT




BACK VIEW OF EUT



LEFT VIEW OF EUT



RIGHT VIEW OF EUT





VIEW OF EUT (PORT)




VIEW OF EUT (LOCAL)-1



VIEW OF EUT (LOCAL)-2




OPEN VIEW OF EUT







INTERNAL VIEW OF EUT-1



INTERNAL VIEW OF EUT-2



INTERNAL VIEW OF EUT-3



VIEW OF ADAPTER(AE)



THE ADAPTER SUPPLIED BY AGC

----END OF REPORT----