

FCC PART 15.249

TEST REPORT

For

Shenzhen Merrytek Technology Co.,LTD

NO.3 Building,380 Xiangshan Avenue,Luotian,Songgang Town,Bao'an
District,Shenzhen,Guangdong,China

FCC ID: 2AI53-MC602S

Report Type: Original Report		Product Type: Lighting Control Switch	
Test Engineer:	Rocky Xiao	<i>Rocky Xiao</i>	
Report Number:	RDG160616052-00		
Report Date:	2016-09-19		
Reviewed By:	Jerry Zhang EMC Manager	<i>Jerry Zhang</i>	
Test Laboratory:	Bay Area Compliance Laboratories Corp. (Dongguan) No.69 Pulongcun, Puxinhu Industrial Zone, Tangxia, Dongguan, Guangdong, China Tel: +86-769-86858888 Fax: +86-769-86858891 www.baclcorp.com.cn		

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Dongguan).

TABLE OF CONTENTS

GENERAL INFORMATION.....	3
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	3
OBJECTIVE	3
RELATED SUBMITTAL(S)/GRANT(S).....	3
TEST METHODOLOGY	3
TEST FACILITY	3
SYSTEM TEST CONFIGURATION.....	4
JUSTIFICATION	4
EUT EXERCISE SOFTWARE	4
EQUIPMENT MODIFICATIONS	4
SUPPORT EQUIPMENT LIST AND DETAILS	4
EXTERNAL I/O CABLE.....	4
BLOCK DIAGRAM OF TEST SETUP	5
SUMMARY OF TEST RESULTS	6
FCC§15.203 - ANTENNA REQUIREMENT.....	7
APPLICABLE STANDARD	7
ANTENNA CONNECTOR CONSTRUCTION	7
FCC §15.207 (A) – AC LINE CONDUCTED EMISSIONS	8
APPLICABLE STANDARD	8
MEASUREMENT UNCERTAINTY.....	8
EUT SETUP	8
EMI TEST RECEIVER SETUP.....	9
TEST PROCEDURE	9
CORRECTED AMPLITUDE & MARGIN CALCULATION	9
TEST EQUIPMENT LIST AND DETAILS.....	10
TEST RESULTS SUMMARY	10
TEST DATA	10
FCC§15.205, §15.209&§15.249- RADIATED EMISSIONS	19
APPLICABLE STANDARD	19
MEASUREMENT UNCERTAINTY	19
EUT SETUP	20
TEST EQUIPMENT SETUP	21
TEST PROCEDURE	21
CORRECTED AMPLITUDE & MARGIN CALCULATION	21
TEST EQUIPMENT LIST AND DETAILS.....	22
TEST DATA	22
FCC §15.215(C) – 20 DB BANDWIDTH TESTING.....	26
APPLICABLE STANDARD	26
TEST PROCEDURE	26
TEST EQUIPMENT LIST AND DETAILS.....	26
TEST DATA	26

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The *Shenzhen Merrytek Technology Co.,LTD*'s product, model number: *MC602S (FCC ID:2AI53-MC602S)* (the "EUT") in this report was a *Lighting Control Switch*, which was measured approximately:9.8 cm (L) x 4.3 cm (W) x 2.9 cm (H), rated input voltage: AC120.0V or AC277V.

All measurement and test data in this report was gathered from production sample serial number: 160616052 (Assigned by BACL, Dongguan). The EUT was received on 2016-06-22.

Objective

This type approval report is prepared on behalf of *Shenzhen Merrytek Technology Co.,LTD*. in accordance with Part 2-Subpart J, and Part 15-Subparts A, B and C of the Federal Communication Commissions rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205,15.207, 15.209 and 15.249 rules.

Related Submittal(s)/Grant(s)

No related submittal.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Dongguan).

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.69 Pulongcun, Puxinhu Industrial Zone, Tangxia, Dongguan, Guangdong, China

Test site at Bay Area Compliance Laboratories Corp. (Dongguan) has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on February 06, 2015.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 273710. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

SYSTEM TEST CONFIGURATION

Justification

The system was configured for testing in engineering mode with maximum power output. The device operating at 5772MHz.

EUT Exercise Software

No software was used in testing.

Equipment Modifications

No modifications were made to the EUT.

Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
Supersun	LED LAMP(400W)	SPSA191227	N/A
Supersun	LED LAMP(800W)	SPSA192884	N/A
Supersun	Ballast	BA0599252	N/A
Supersun	Fluorescent LAMP(200W)	FL0638	N/A
Supersun	Fluorescent LAMP(400W)	FL0647	N/A

External I/O Cable


Cable Description	Shielding Type	Ferrite Core	Length (m)	From	To
Power Line	No	No	2.0	EUT	Lamp
Power Line	No	No	2.0	EUT	Ballast
Power Line	No	No	1.0	Ballast	LAMP

Block Diagram of Test Setup

Resistive Load:



Ballast Load



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§15.203	Antenna Requirement	Compliance
§15.207(a)	Conduction Emissions	Compliance
15.205, §15.209, §15.249	Radiated Emissions	Compliance
§15.215 (c)	20 dB Bandwidth	Compliance

FCC§15.203 - ANTENNA REQUIREMENT

Applicable Standard

For intentional device, according to §15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used.

Antenna Connector Construction

The EUT has an internal antenna, the antenna gain is 0dBi, fulfill the requirement of this section. Please refer to the EUT photos.

Result: Compliant.

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC§15.207

Measurement Uncertainty

Compliance or non-compliance with a disturbance limit shall be determined in the following manner:

If U_{lab} is less than or equal to U_{cisp} of Table 1, then:

- compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.

If U_{lab} is greater than U_{cisp} of Table 1, then:


- compliance is deemed to occur if no measured disturbance level, increased by $(U_{lab} - U_{cisp})$, exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level, increased by $(U_{lab} - U_{cisp})$, exceeds the disturbance limit.

Based on CISPR 16-4-2-2011, measurement uncertainty of conducted disturbance at mains port using AMN at Bay Area Compliance Laboratories Corp. (Dongguan) is 3.12 dB (150 kHz to 30 MHz).

Table 1 – Values of U_{cisp}

Measurement	U_{cisp}
Conducted disturbance at mains port using AMN (150 kHz to 30 MHz)	3.4 dB

EUT Setup



- Note: 1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

The EUT was connected to a 120 VAC/60 Hz or 277VAC/60Hz power source.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the adapter of laptop was connected to the first LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

Corrected Amplitude & Margin Calculation

The basic equation is as follows:

$$V_C = V_R + A_C + VDF$$

$$C_f = A_C + VDF$$

Herein,

V_C (cord. Reading): corrected voltage amplitude

V_R : reading voltage amplitude

A_C : attenuation caused by cable loss

VDF: voltage division factor of AMN

C_f : Correction Factor

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. For example, a margin of 7dB means the emission is 7dB below the maximum limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESCS 30	830245/006	2015-12-10	2016-12-09
R&S	L.I.S.N	ESH3-Z5	892107/021	2016-07-16	2017-07-15
R&S	Two-line V-network	ENV 216	3560.6550.12	2015-11-26	2016-11-25
R&S	Test Software	EMC32	Version8.53.0	N/A	N/A

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.207.


Test Data**Environmental Conditions**

Temperature:	28.6°C
Relative Humidity:	60 %
ATM Pressure:	99.8 kPa

The testing was performed by Rocky Xiao on 2016-09-06.


Test Mode: Transmitting / Ballast

AC120 V, 60 Hz, Line:




Frequency (MHz)	Quasi Peak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.304845	35.0	9.000	L1	0.2	25.1	60.1	Compliance
0.609741	31.3	9.000	L1	0.2	24.7	56.0	Compliance
0.665597	31.3	9.000	L1	0.2	24.7	56.0	Compliance
0.732382	31.5	9.000	L1	0.2	24.5	56.0	Compliance
0.786832	30.6	9.000	L1	0.2	25.4	56.0	Compliance
0.852094	32.1	9.000	L1	0.2	23.9	56.0	Compliance

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.183065	37.3	9.000	L1	0.2	17.0	54.3	Compliance
0.243884	36.4	9.000	L1	0.2	15.6	52.0	Compliance
0.304845	34.2	9.000	L1	0.2	15.9	50.1	Compliance
0.366160	31.7	9.000	L1	0.4	16.9	48.6	Compliance
0.609741	28.9	9.000	L1	0.2	17.1	46.0	Compliance
0.670921	28.8	9.000	L1	0.2	17.2	46.0	Compliance

AC120 V, 60 Hz, Neutral:


Frequency (MHz)	Quasi Peak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.670921	38.5	9.000	N	0.4	17.5	56.0	Compliance
0.732382	38.5	9.000	N	0.4	17.5	56.0	Compliance
0.793127	38.2	9.000	N	0.4	17.8	56.0	Compliance
0.852094	39.0	9.000	N	0.4	17.0	56.0	Compliance
2.130339	37.6	9.000	N	0.4	18.4	56.0	Compliance
2.252540	38.1	9.000	N	0.5	17.9	56.0	Compliance

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.609741	33.8	9.000	N	0.4	12.2	46.0	Compliance
0.670921	36.6	9.000	N	0.4	9.4	46.0	Compliance
0.732382	36.4	9.000	N	0.4	9.6	46.0	Compliance
0.793127	35.7	9.000	N	0.4	10.3	46.0	Compliance
0.852094	35.5	9.000	N	0.4	10.5	46.0	Compliance
2.252540	35.5	9.000	N	0.5	10.5	46.0	Compliance

AC277 V, 60 Hz, Line:

Frequency (MHz)	Quasi Peak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.366160	37.3	9.000	L1	0.4	21.3	58.6	Compliance
0.396530	37.1	9.000	L1	0.6	20.8	57.9	Compliance
0.426011	36.8	9.000	L1	0.6	20.5	57.3	Compliance
0.457684	36.3	9.000	L1	0.4	20.5	56.7	Compliance
0.487810	35.4	9.000	L1	0.3	20.8	56.2	Compliance
0.519918	33.2	9.000	L1	0.2	22.8	56.0	Compliance

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.243884	37.3	9.000	L1	0.2	14.6	52.0	Compliance
0.304845	37.4	9.000	L1	0.2	12.7	50.1	Compliance
0.366160	36.4	9.000	L1	0.4	12.2	48.6	Compliance
0.426011	35.7	9.000	L1	0.6	11.6	47.3	Compliance
0.487810	34.2	9.000	L1	0.3	12.0	46.2	Compliance
0.549741	32.5	9.000	L1	0.2	13.5	46.0	Compliance


AC277V, 60 Hz, Neutral:

Frequency (MHz)	Quasi Peak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.426011	40.6	9.000	N	0.4	16.8	57.3	Compliance
0.457684	40.3	9.000	N	0.4	16.4	56.7	Compliance
0.487810	40.1	9.000	N	0.4	16.1	56.2	Compliance
1.219583	39.1	9.000	N	0.4	16.9	56.0	Compliance
1.249088	39.2	9.000	N	0.4	16.8	56.0	Compliance
1.279307	39.0	9.000	N	0.4	17.0	56.0	Compliance

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.426011	36.8	9.000	N	0.4	10.6	47.3	Compliance
0.487810	36.3	9.000	N	0.4	9.9	46.2	Compliance
0.549741	35.5	9.000	N	0.4	10.5	46.0	Compliance
1.219583	36.3	9.000	N	0.4	9.7	46.0	Compliance
1.249088	35.1	9.000	N	0.4	10.9	46.0	Compliance
1.279307	35.8	9.000	N	0.4	10.2	46.0	Compliance


Test Mode: Transmitting / Resistive

AC120 V, 60 Hz, Line:




Frequency (MHz)	Quasi Peak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.178741	39.2	9.000	L1	0.2	25.3	64.5	Compliance
0.240029	38.5	9.000	L1	0.2	23.6	62.1	Compliance
0.300025	36.8	9.000	L1	0.1	23.4	60.2	Compliance
0.360371	34.4	9.000	L1	0.3	24.3	58.7	Compliance
0.660314	30.3	9.000	L1	0.1	25.7	56.0	Compliance
0.780588	30.2	9.000	L1	0.1	25.8	56.0	Compliance

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.180171	37.7	9.000	L1	0.2	16.8	54.5	Compliance
0.240029	36.1	9.000	L1	0.2	16.0	52.1	Compliance
0.300025	33.1	9.000	L1	0.1	17.1	50.2	Compliance
0.360371	30.4	9.000	L1	0.3	18.3	48.7	Compliance
0.422630	28.6	9.000	L1	0.7	18.8	47.4	Compliance
0.541050	27.6	9.000	L1	0.1	18.4	46.0	Compliance

AC120 V, 60 Hz, Neutral:


Frequency (MHz)	Quasi Peak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.660314	34.6	9.000	N	0.1	21.4	56.0	Compliance
0.720803	35.5	9.000	N	0.1	20.5	56.0	Compliance
0.780588	35.5	9.000	N	0.1	20.5	56.0	Compliance
1.745563	34.8	9.000	N	0.2	21.2	56.0	Compliance
1.802095	33.0	9.000	N	0.2	23.0	56.0	Compliance
2.558827	31.2	9.000	N	0.2	24.8	56.0	Compliance

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.541050	29.0	9.000	N	0.1	17.0	46.0	Compliance
0.600101	29.4	9.000	N	0.1	16.6	46.0	Compliance
0.660314	29.7	9.000	N	0.1	16.3	46.0	Compliance
0.720803	30.8	9.000	N	0.1	15.2	46.0	Compliance
0.780588	30.3	9.000	N	0.1	15.7	46.0	Compliance
1.745563	28.8	9.000	N	0.2	17.2	46.0	Compliance

AC277 V, 60 Hz, Line:

Frequency (MHz)	Quasi Peak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.332770	40.5	9.000	L1	0.1	18.9	59.4	Compliance
0.363254	40.6	9.000	L1	0.3	18.1	58.7	Compliance
0.396530	43.5	9.000	L1	0.8	14.5	58.0	Compliance
0.419276	38.6	9.000	L1	0.7	18.9	57.5	Compliance
0.450448	38.2	9.000	L1	0.5	18.7	56.9	Compliance
0.480097	36.4	9.000	L1	0.3	19.9	56.3	Compliance

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.363254	38.0	9.000	L1	0.3	10.7	48.7	Compliance
0.390261	39.0	9.000	L1	0.7	9.1	48.1	Compliance
0.422630	38.6	9.000	L1	0.7	8.8	47.4	Compliance
0.450448	37.1	9.000	L1	0.5	9.8	46.9	Compliance
0.480097	35.7	9.000	L1	0.3	10.6	46.3	Compliance
0.511698	34.3	9.000	L1	0.1	11.7	46.0	Compliance

AC277V, 60 Hz, Neutral:

Frequency (MHz)	Quasi Peak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
1.352690	38.2	9.000	N	0.2	17.8	56.0	Compliance
1.385415	38.7	9.000	N	0.2	17.3	56.0	Compliance
1.441726	38.1	9.000	N	0.2	17.9	56.0	Compliance
1.476605	37.5	9.000	N	0.2	18.5	56.0	Compliance
1.500325	37.3	9.000	N	0.2	18.7	56.0	Compliance
1.536622	37.2	9.000	N	0.2	18.8	56.0	Compliance

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.390261	38.8	9.000	N	0.1	9.3	48.1	Compliance
0.422630	37.1	9.000	N	0.1	10.3	47.4	Compliance
0.450448	35.9	9.000	N	0.1	11.0	46.9	Compliance
0.572086	35.2	9.000	N	0.1	10.8	46.0	Compliance
1.352690	35.5	9.000	N	0.2	10.5	46.0	Compliance
1.385415	34.0	9.000	N	0.2	12.0	46.0	Compliance

FCC§15.205, §15.209&§15.249- RADIATED EMISSIONS

Applicable Standard

As per FCC§15.249 (a), except as provided in paragraph (b) of this section, the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

Fundamental frequency	Field strength of fundamental (millivolts/meter)	Field strength of harmonics (microvolts/meter)
902–928 MHz	50	500
2400–2483.5 MHz	50	500
5725–5875 MHz	50	500
24.0–24.25 GHz	250	2500

As per FCC§15.249 (c), Field strength limits are specified at a distance of 3 meters.

(d) Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.

Measurement Uncertainty

Compliance or non- compliance with a disturbance limit shall be determined in the following manner:

If U_{lab} is less than or equal to U_{cisprr} of Table 1, then:

- compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- non - compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.

If U_{lab} is greater than U_{cisprr} of Table 1, then:

- compliance is deemed to occur if no measured disturbance level, increased by $(U_{lab} - U_{cisprr})$, exceeds the disturbance limit;
- non - compliance is deemed to occur if any measured disturbance level, increased by $(U_{lab} - U_{cisprr})$, exceeds the disturbance limit.


Based on CISPR 16-4-2: 2011, measurement uncertainty of radiated emission at a distance of 3m at Bay Area Compliance Laboratories Corp. (Dongguan) is: 30M~200MHz: 4.58 dB for Horizontal, 4.59 dB for Vertical; 200M~1GHz: 4.83 dB for Horizontal, 5.85 dB for Vertical; 1G~6GHz: 4.45 dB, 6G~18GHz: 5.23 dB

Table 1 – Values of U_{cispr}


Measurement	U_{cispr}
Radiated disturbance (electric field strength at an OATS or in a SAC) (30 MHz to 1000 MHz)	6.3 dB
Radiated disturbance (electric field strength in a FAR) (1 GHz to 6 GHz)	5.2 dB
Radiated disturbance (electric field strength in a FAR) (6 GHz to 18 GHz)	5.5 dB

EUT Setup

Below 1 GHz:



Above 1 GHz:



The radiated emission and out of band emission tests were performed in the 3 meters chamber test site, using the setup accordance with the ANSI C63.10-2013 The specification used was the FCC 15.209/15.205 and FCC 15.249 limits.

Test Equipment Setup

The system was investigated from 30 MHz to 40 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
30 MHz – 1000 MHz	120 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1MHz	3 MHz	/	PK
	1MHz	10 Hz	/	Ave.

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

All data was recorded in the Quasi-peak detection mode from 30 MHz to 1GHz, peak and average detection mode above 1 GHz.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESCI	100224	2015-08-03	2016-08-02
Sunol Sciences	Antenna	JB3	A060611-3	2014-11-06	2017-11-05
HP	Amplifier	8447E	2434A02181	2015-09-01	2016-09-01
Agilent	Spectrum Analyzer	E4440A	SG43360054	2015-11-23	2016-11-22
ETS-Lindgren	Horn Antenna	3115	9808-5557	2015-09-06	2018-09-06
Mini-Circuit	Amplifier	ZVA-213-S+	054201245	2016-02-19	2017-02-19
R&S	Spectrum Analyzer	FSP 38	100478	2016-05-09	2017-05-09
Ducommun Technologies	Horn Antenna	ARH-4223-02	1007726-01 1304	2014-06-16	2017-06-15
Quinstar	Amplifier	QLW-18405536-JO	15964001001	2015-09-06	2016-09-06
N/A	Coaxial Cable	14m	N/A	2016-05-06	2017-05-06
N/A	Coaxial Cable	8m	N/A	2016-05-06	2017-05-06
Ducommun Technologies	Horn Antenna	ARH-2823-02	1007726-01 1302	2014-06-16	2017-06-15

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data**Environmental Conditions**

Temperature:	27.1 °C
Relative Humidity:	48 %
ATM Pressure:	100.1 kPa


The testing was performed by Rocky Xiao on 2016-06-27.

Test Mode: Transmitting


Test Mode: Transmitting

30MHz-1GHz:

Horizontal



Frequency (MHz)	Receiver Reading (dBμV)	Detector	Correction Factor (dB/m)	Cord. Amp. (dBμV/m)	Limit (dBμV/m)	Margin (dB)
30.0000	26.65	QP	0.95	27.60	40.00	12.40
69.7700	28.21	QP	-12.01	16.20	40.00	23.80
103.7200	26.50	QP	-8.60	17.90	43.50	25.60
205.5700	36.89	QP	-8.39	28.50	43.50	15.00
312.2700	29.45	QP	-5.55	23.90	46.00	22.10
352.0400	28.74	QP	-4.64	24.10	46.00	21.90

Vertical

Frequency (MHz)	Receiver Reading (dBuV)	Detector	Correction Factor (dB/m)	Cord. Amp. (dBuV/m)	Limit (dBuV/m)	Margin (dB)
33.8800	37.17	QP	-1.97	35.20	40.00	4.80
41.6400	41.15	QP	-7.65	33.50	40.00	6.50
76.5600	34.04	QP	-11.94	22.10	40.00	17.90
127.9700	29.22	QP	-5.62	23.60	43.50	19.90
200.7200	30.69	QP	-7.29	23.40	43.50	20.10
507.2400	26.45	QP	-1.55	24.90	46.00	21.10

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector	Polar (H/V)	Factor (dB(1/m))					
5772	74.37	PK	H	32.16	5.48	26.57	85.44	114.00	28.56
5772	60.32	AV	H	32.16	5.48	26.57	71.39	94.00	22.61
5772	88.33	PK	V	32.16	5.48	26.57	99.40	114.00	14.60
5772	74.28	AV	V	32.16	5.48	26.57	85.35	94.00	8.65
5725	31.33	PK	V	32.15	5.60	26.63	42.45	74.00	31.55
5725	22.26	PK	V	32.15	5.60	26.63	33.38	54.00	20.62
11550	38.78	PK	V	37.90	8.93	26.09	59.52	74.00	14.48
11550	24.73	AV	V	37.90	8.93	26.09	45.47	54.00	8.53
17325	35.92	PK	V	41.45	13.17	25.63	64.91	74.00	9.09
17325	21.87	AV	V	41.45	13.17	25.63	50.86	54.00	3.14
6964	34.18	PK	V	33.51	6.35	26.32	47.72	74.00	26.28
6964	21.89	AV	V	33.51	6.35	26.32	35.43	54.00	18.57
10405	33.53	PK	V	36.98	8.31	25.53	53.29	74.00	20.71
10405	21.14	AV	V	36.98	8.31	25.53	40.90	54.00	13.10

FCC §15.215(c) – 20 dB BANDWIDTH TESTING**Applicable Standard**

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§ 15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

Test Procedure

1. Position the EUT on the test table without connection to measurement instrument. Turn on the EUT. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
2. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
3. Repeat above procedures until all frequencies measured were complete.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSP 38	100478	2015-11-23	2016-11-22
E-Microwave	DC Blocking	EMDCB-00036	0E01201047	2016-05-06	2017-05-06
N/A	Coaxial Cable	0.1m	N/A	2016-05-06	2017-05-06

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data**Environmental Conditions**

Temperature:	31.2 °C
Relative Humidity:	49%
ATM Pressure:	100.1kPa

* The testing was performed by Rocky Xiao on 2016-07-05.


Test Result: Compliant.

Please refer to following tables and plots

Test Mode: Transmitting

Channel	Frequency (MHz)	20 dB Bandwidth (MHz)
Middle	5772	8.437

Middle Channel



***** END OF REPORT *****