

Report No. : FA681620

Project No: CB10603276

RF Exposure Evaluation Report

Equipment : Norton Core Secure WiFi Router

Brand Name : Norton Core

Model No. : 517

FCC ID : 2AI6F-517

Standard : 47 CFR Part 2.1091

Applicant : Symantec Corporation

350 Ellis Street Mountain View, CA 94043 United

States

Manufacturer : CyberTAN Technology Inc.

No. 99, Park Avenue III, Science-based Industrial

Park, Hsinchu, 308 Taiwan

The product sample received on Aug. 16, 2017 and completely tested on Mar. 14, 2017. We, SPORTON, would like to declare that the tested sample has been evaluated in accordance with 47 CFR Part 2.1091, and pass the limit.

Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

Cliff Chang

SPORTON INTERNATIONAL INC.



Page No.

Report Version

Issued Date



: 1 of 6

: Rev. 01

: Mar. 31, 2017



RF Exposure Evaluation Report

TABLE OF CONTENTS

1	GENERAL DESCRIPTION
	EUT General Information
1.2	Table for Multiple Listing
1.3	Table for Class II Change
1.4	Testing Location
2	MAXIMUM PERMISSIBLE EXPOSURE
	Limit of Maximum Permissible Exposure
2.2	MPE Calculation Method
2.3	Calculated Result and Limit
	OGRAPHS OF EUT V01

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-327-0973 FCC ID: 2AI6F-517 Page No. : 2 of 6
Report Version : Rev. 01

Report Version Issued Date

: Mar. 31, 2017



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FA681620	Rev. 01	Initial issue of report	Mar. 31, 2017

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-327-0973 FCC ID: 2Al6F-517 Page No. : 3 of 6
Report Version : Rev. 01

Report No.: FA681620

Issued Date : Mar. 31, 2017



1 General Description

1.1 EUT General Information

	RF General Information							
Evaluation Mode	Frequency Range (MHz)	Operating Frequency (MHz)	Modulation Type					
2.4GHz WLAN	2400-2483.5 2412-2462		802.11b: DSSS (DBPSK, DQPSK, CCK) 802.11g/n: OFDM (BPSK, QPSK, 16QAM, 64QAM) 802.11ac: OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM)					
5GHz WLAN	5150-5250 5725-5850	5180-5240 5745-5825	802.11a/n: OFDM (BPSK, QPSK, 16QAM, 64QAM) 802.11ac: OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM)					
Bluetooth	2400-2483.5	2402-2480	BR / EDR: FHSS (GFSK / π/4-DQPSK / 8DPSK) LE: DSSS (GFSK)					

1.2 Table for Multiple Listing

The EUT has two exterior which are identical to each other in all aspects except for the following table:

Brand Name	Model Name	EUT	Color		
Norton Core	Core 517	1	Granite Gray		
		2	Titanium Gold		

1.3 Testing Location

	Testing Location								
	HWA YA ADD: No. 52, Hwa Ya 1st Rd., Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.								
		TEL	:	886-3-327-3456 FAX : 886-3-327-0973					
\boxtimes	JHUBEI	ADD	:	No.8, Lane 724, Bo-ai St., Jhubei City, HsinChu County 302, Taiwan, R.O.C.					
		TEL	:	886-3-656-9065 FAX : 886-3-656-9085					

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-327-0973 FCC ID: 2Al6F-517 Page No. : 4 of 6
Report Version : Rev. 01

: Mar. 31, 2017

Issued Date



2 Maximum Permissible Exposure

2.1 Limit of Maximum Permissible Exposure

(A) Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Power Density (Strength (H) (A/m) (mW/ cm²)		Averaging Time E ², H ² or S (minutes)
0.3-3.0	614	1.63 (100)*		6
3.0-30	1842 / f	4.89 / f (900 / f)*		6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-100,000			5	6

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Power Density (mW/ cm²)		Averaging Time E ², H ² or S (minutes)
0.3-1.34	614	1.63 (100)*		30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: f = frequency in MHz; *Plane-wave equivalent power density

2.2 MPE Calculation Method

The MPE was calculated at 26 cm to show compliance with the power density limit.

The following formula was used to calculate the Power Density:

E (V/m) =
$$\frac{\sqrt{30 \times P \times G}}{d}$$
 Power Density: Pd (W/m²) = $\frac{E^2}{377}$

E = Electric field (V/m)

P = RF output power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-327-0973 FCC ID: 2Al6F-517 Page No. : 5 of 6
Report Version : Rev. 01

: Mar. 31, 2017

Issued Date



RF Exposure Evaluation Report

2.3 Calculated Result and Limit

Exposure Environment: General Population / Uncontrolled Exposure

Simultaneous Transmission Analysis Mode: Bluetooth+WLAN 2.4GHz +WLAN 5GHz

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	EIRP (W)	Distance (cm)	S (mW/cm²)	S Limit (mW/cm²)	Ratio (S/Limit)
2.4G;D1D	7.52	28.41	35.93	3.91742	26	0.46115	1.00000	0.46115
5.2G;D1D	8.32	27.66	35.99	3.97192	26	0.46757	1.00000	0.46757
2.4G;BT-EDR	2.54	7.35	9.89	0.00975	26	0.00115	1.00000	0.00115
							Sum Ratio	0.92987
							Ratio Limit	1

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-327-0973 FCC ID: 2Al6F-517 Page No. : 6 of 6
Report Version : Rev. 01
Issued Date : Mar. 31, 2017