



RF Test Report

Applicant : Shenzhen Tuge Information Limited Inc

Product Type : TGT WiFi

Trade Name : TGT WiFi

Model Number : T2C

Applicable Standard : FCC 47 CFR PART 22H

FCC 47 CFR PART 24E

ANSI/TIA-603-D

Receive Date : May 04, 2016

Test Period : May 13 ~ Jun. 07, 2016

Issue Date : Jul. 06, 2016

Issue by

A Test Lab Techno Corp.

No. 140-1, Changan Street, Bade District,

Taoyuan City 33465, Taiwan (R.O.C)


Tel: +886-3-2710188 / Fax: +886-3-2710190





<u>Taiwan Accreditation Foundation accreditation number: 1330</u>


Note: This report shall not be reproduced except in full, without the written approval of A Test Lab Techno Corp. This document may be altered or revised by A Test Lab Techno Corp. personnel only, and shall be noted in the revision section of the document. The client should not use it to claim product endorsement by TAF, or any government agencies. The test results in the report only apply to the tested sample.





Revision History

Rev.	Issue Date	Revisions	Revised By
00	Jun. 17, 2016	Initial Issue	Snow Wang
01	Jun. 24, 2016	Revised report information.	Snow Wang
02	Jul. 06, 2016	Revised report information.	Peggy Chang





Verification of Compliance

Issued Date: Jul. 06, 2016

Applicant : Shenzhen Tuge Information Limited Inc

Product Type : TGT WiFi

Trade Name : TGT WiFi

Model Number : T2C

FCC ID : 2AIC4-T2C

EUT Rated Voltage : DC 5V, 1A

Test Voltage : 120 Vac / 60 Hz

Applicable Standard: FCC 47 CFR PART 22H

FCC 47 CFR PART 24E

ANSI/TIA-603-D

Test Result : Complied

Performing Lab. : A Test Lab Techno Corp.

No. 140-1, Changan Street, Bade District,

Taoyuan City 33465, Taiwan (R.O.C)

Tel: +886-3-2710188 / Fax: +886-3-2710190

Taiwan Accreditation Foundation accreditation number: 1330

http://www.atl-lab.com.tw/e-index.htm

A Test Lab Techno Corp. tested the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by A Test Lab Techno Corp. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

(Manager) (Fly Lu) (Testing Engineer) (Eric Ou Yang)






TABLE OF CONTENTS

1	Gen	eral Information	5
	1.1.	Summary of Test Result	5
	1.2.	Testing Location	5
	1.3.	Measurement Uncertainty	6
	1.4.	Test Site Environment	6
2	EUT	Description	7
3	Test	t Methodology	8
	3.1.	Mode of Operation	8
	3.2.	EUT Exercise Software	8
	3.3.	Configuration of Test System Details	9
	3.4.	Test Instruments	10
	3.5.	Reference Testing Standards	11
4	Test	t Results	12
	4.1.	RF Output Power	12
	4.2.	Effective Radiated Power / Equivalent Isotropic Radiated Power	14
	4.3.	Peak to Average Ratio	22
	4.4.	Emission Bandwidth & Occupied Bandwidth	37
	4.5.	Frequency Stability	90
	4.6.	Band Edge	97
	4.7.	Radiated Spurious Emissions	112
		Conducted Spurious Emission	



Report Number: 1605FR21-02

1 General Information

1.1. Summary of Test Result

FCC Rules	Description	Verdict	Remark
§2.1046	RF Output Power	Pass	
§22.913(a)(2)	Effective Radiated Power	Pass	
§24.232(c)	Equivalent Isotropic Radiated Power	Pass	
§24.232(d)	Peak to average ratio	Pass	
§2.1049(h)(i) §22.917(b) §24.238(b)	Emission Bandwidth & Occupied Bandwidth	Pass	
§2.1055 §22.355 §24.235	Frequency Stability for Temperature & Voltage	Pass	
§2.1051 §22.917(a) §24.238(a)	Band Edge Measurement	Pass	
§2.1053 §22.917(a) §24.238(a)	Radiated Spurious Emissions	Pass	
§2.1051 §22.917(a) §24.238(a)	Conducted Spurious Emission	Pass	

The test results of this report relate only to the tested sample(s) identified in this report. Manufacturer or whom it may concern should recognize the pass or fail of the test result.


1.2. Testing Location

Site Name: A Test Lab Techno Corp.

http://www.atl-lab.com.tw/e-index.htm

Site Address: No. 140-1, Changan Street, Bade District, Taoyuan City 33465, Taiwan (R.O.C)

Tel: +886-3-2710188 Fax: +886-3-2710190






1.3. Measurement Uncertainty

Test Item			Uncertainty
Peak Output Power (Conducted)			+0.27 dB/-0.28 dB
Occupied Bandwidth (Conducte	ed)		4.96%
Emission Bandwidth (Conducte	d)		4.96%
Frequency Stability			+ 2.212 x 10 ⁻⁷ % / - 2.170 x 10 ⁻⁷
orn /oirn	Horizontal		±4.898 dB
e.r.p. / e.i.r.p.	Vertical		±4.867 dB
_		30 ~ 167 MHz	4.22 dB
		167 ~ 500 MHz	3.44 dB
	Horizontal	500 ~ 1000 Hz	3.39 dB
		1 ~ 18 GHz	4.05 dB
Dadiated Caurious Emission		18 ~ 40 GHz	4.05 dB
Radiated Spurious Emission	Vertical	30 ~ 167 MHz	3.37 dB
		167 ~ 500 MHz	3.19 dB
		500 ~ 1000 Hz	3.19 dB
		1 ~ 18 GHz	4.08 dB
		18 ~ 40 GHz	4.04 dB
	Horizontal	30MHz~1000MHz	5.442 dB
	Vertical	30MHz~1000MHz	5.478 dB
Radiated Emission	1GHz~18GH	lz	5.474 dB
	18GHz~26.5GHz		5.630 dB
	26.5GHz~40GHz		5.054 dB

Note: The Vertical and Horizontal measurement uncertainty of 1GHz to 4GHz is evaluated and choose which polarity is worst value.

1.4. Test Site Environment

Items	Required (IEC 60068-1)	Actual
Temperature (°C)	15-35	26
Humidity (%RH)	25-75	60
Barometric pressure (mbar)	860-1060	950





2 **EUT Description**

Applicant		Shenzhen Tuge Information Limited Inc Room 406,25 Building ,Nanshan Science Park west industrial area, Shenzhen City, Guangdong Province, China				
Manufacturer		Shenzhen Tuge Information Limited Inc Room 406,25 Building ,Nanshan Science Park west industrial area, Shenzhen City, Guangdong Province, China				
Product T	·уре	TGT WiFi				
Trade Na	me	TGT WiFi				
Model Nu	mber	T2C				
IMEI No.		IMEI1 :8696	666020000012, IMEI2:869	9666020000020		
FCC ID		2AIC4-T2C				
Hardware	Version	P613-V00				
Software	Version	T2_M2_P6	13GT-V00_02			
Radio Ha	rdware Version	P613-V00				
Radio Sol	ftware Version	T2_M2_P613GT-V00_02				
	GPRS/EGPRS	Band	UL Frequency (MHz)	DL Frequency (MHz)	Modulation	
		850	824.2 ~ 848.8	869.2 ~ 893.8	GMSK/8PSK	
		1900	1850.2 ~ 1909.8	1930.2 ~ 1989.8	GMSK/8PSK	
Operate Band		*GPRS/EGPRS Multi Class 12.				
Dana	WCDMA	Band	UL Frequency (MHz)	DL Frequency (MHz)	Modulation	
	(RMC12.2K)/ HSDPA/	II	1852.4 ~ 1907.6	1932.4 ~ 1987.6	QPSK	
	HSUPA	V	826.4 ~ 846.6	871.4 ~ 891.6	QPSK	
Channel (Control	Auto				
Antenna 7	Гуре	Internal Antenna				
Antenna Gain (dBi)		GPRS/EGPRS 850 : 1			: 1.0 dBi	
			PRS 1900		: 1.2 dBi	
			ISDPA/ HSUPA Band II		: 1.1 dBi	
			ISDPA/ HSUPA Band V		: 1.0 dBi	
Extreme t	emp. Tolerance	0°C to 40°C				

Operate Band	Max. RF Output power (W)	Max. ERP/EIRP (W)	Emission Designator
GPRS 850	1.476	1.21	248KG1W
EGPRS 850	0.617	0.37	247KG1W
GPRS 1900	0.984	0.94	246KG1W
EGPRS 1900	0.466	0.31	249KG1W
WCDMA/ HSDPA/ HSUPA Band II	0.200	0.19	4M17F1W
WCDMA/ HSDPA/ HSUPA Band V	0.238	0.20	4M18F1W



Report Number: 1605FR21-02

3 Test Methodology

3.1. Mode of Operation

ATL has verified the construction and function in typical operation. All the test modes were carried out with the EUT in normal operation, which was shown in this test report and defined as:

- GPRS 850 link mode
- GPRS 1900 link mode
- EGPRS 850 link mode
- EGPRS 1900 link mode
- WCDMA Band II link mode
- WCDMA Band V link mode

By preliminary testing and verifying three axis (X, Y and Z) position of EUT transmitted status, it was found that "X axis" position was the worst, then the final test was executed the worst condition and test data were recorded in this report.


Regards to the frequency band operation: the lowest, middle and highest frequency of channel were selected to perform the test, then shown on this report.

Software used to control the EUT for staying in continuous transmitting mode was programmed.

3.2. EUT Exercise Software


1	Setup the EUT and Base Station (CMU200) as shown on 3.3.
2	Turn on the power of all equipment.


Mea	Measurement Software		
1	EZ-EMC Ver. ATL-03A1-1		





3.3. Configuration of Test System Details







3.4. Test Instruments

Conducted test system					
Equipment	Manufacturer	Model Number	Serial Number	Cal. Date	Cal. Period
Universal Radio Communication Tester	R&S	CMU200	112387	02/25/2016	1 year
Spectrum Analyzer	R&S	FSU26	201118	11/02/2015	1 year
Temperature & Humidity Chamber	TAICHY	MHU-225LA	980729	04/18/2016	1 year
Conducted Test Site	ATL	TE05	TE05	N.C.R.	

Radiated Emission test system					
Equipment	Manufacturer	Model Number	Serial Number	Cal. Date	Cal. Period
RF Pre-selector	Agilent	N9039A	MY46520256	01/08/2016	1 year
Spectrum Analyzer	Agilent	E4446A	MY46180578	01/08/2016	1 year
Signal Generator	Signal Generator	E8257D	MY44320425	02/26/2016	1 year
Pre Amplifier	Agilent	8449B	3008A02237	10/07/2015	1 year
Pre Amplifier	Agilent	8447D	2944A11119	01/11/2016	1 year
Pre Amplifier	EMCI	EMC012645SE	980289	01/14/2016	1 year
Trilog-Broadband Antenna	SCHWARZBECK MESS-ELEKTRONIK	VULB 9168	419	10/28/2015	1 year
Broadband Antenna (30MHz~1GHz)	SCHWARZBECK MESS-ELEKTRONIK	VULB9163	9163-270	08/11/2015	1 year
Horn Antenna (1~18GHz)	SCHWARZBECK MESS-ELEKTRONIK	BBHA9120D	9120D-550	06/12/2015	1 year
Horn Antenna (1~18GHz)	ETS	3117	00152321	08/14/2015	1 year
Horn Antenna (18~40GHz)	SCHWARZBECK MESS-ELEKTRONIK	BBHA9170	9170-320	07/06/2015	1 year
Horn Antenna (18~40GHz)	ETS	3116	00086467	09/01/2015	1 year
Sleeve Dipole(CF880) (780-980MHz)	ETS	3126-880	00064344	10/06/2014	2 years
Sleeve Dipole(CF1845) (1695-1995MHz)	ETS	3126-1845	00083335	10/06/2014	2 years
3 Meter Chamber Test Site	ATL	TE01	888001	08/27/2015	1 year


Note: N.C.R. = No Calibration Request.





3.5. Reference Testing Standards

Standard	Description	Version
FCC 47 CFR PART 22H	Public Mobile Services	Oct. 2015
FCC 47 CFR PART 24E Personal Communications Services		Oct. 2015
ANSI/TIA-603-D	Land Mobile FM or PM Communications Equipment Measurement and Performance Standards	2010
FCC KDB 971168 D01	Power Meas License Digital Systems	v02r02






4 Test Results

4.1. RF Output Power

■ Test Setup




■ Test Procedure

The EUT was set up for the maximum power with simulator.

Set the EUT to transmit under low, middle and high channel and record the power level shown on simulator.

The measurement is made according to FCC KDB 971168 D01 as below:

- 1. The transmitter output was connected to power meter and base station through Power Divider.
- 2. The EUT was set up for the max output power with pseudo random data modulation.
 - -Set base station for EUT at GSM 850: PCL=5 and PCS 1900: PCL=0.
 - -Set base station for EUT at WCDMA Band V and WCDMA Band II, power level was set to maximum.
- 3. Select lowest, middle, and highest channels for each band.
- 4. In all cases, output power is within the specified limits.





■ Test Results


RF Power setting in Test Software	Test Software Version
Default	T2_M2_P613GT-V00_02

Operate Band	Power Step	Nominal Peak Output Power (dBm)
GPRS 850	3	33dBm(2W)
EGPRS 850	6	27dBm(0.5W)
GPRS 1900	3	30dBm(1W)
EGPRS 1900	5	26dBm(0.4W)

Operate Band	Modulation	Power Step	Time Slots	Frequency (MHz)	Output Power (dBm)		
	Туре			(IVII IZ)	SIM 1	SIM 2	
	GMSK	3	1Slot	824.2	31.61	31.59	
GPRS 850				836.6	31.67	31.59	
				848.8	31.69	31.56	
				824.2	27.84	27.44	
EGPRS 850	8PSK	6	1Slot	836.6	27.85	27.40	
				848.8	27.90	27.43	

Operate Band	Modulation Type	Power Step	Time Slots	Frequency (MHz)	Output Power (dBm)	
	туре			(IVII IZ)	SIM 1	SIM 2
GPRS 1900	GMSK	3	1Slot	1850.20	29.45	28.76
				1880.00	29.93	29.23
				1909.80	29.86	29.25
			1Slot	1850.20	26.00	25.53
EGPRS 1900	8PSK	5		1880.00	26.68	26.30
				1909.80	26.67	26.45

Operate Band	Modulation Type	Frequency (MHz)	Output Power (dBm)		
		(1711 12)	SIM 1	SIM 2	
		1852.4	22.85	22.66	
WCDMA Band II	QPSK	1880.0	22.66	22.54	
		1907.6	23.00	22.60	
		826.4	23.56	23.42	
WCDMA Band V	QPSK	836.6	23.64	23.54	
		846.6	23.77	23.66	






4.2. Effective Radiated Power / Equivalent Isotropic Radiated Power

■ Limit


For FCC Part 22.913(a)(2): The ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 Watts . For FCC Part 24.232(c): The EIRP of mobile transmitters and auxiliary test transmitters must not exceed 2 Watts.


■ Test Setup

Below 1 GHz




Above 1 GHz







For Substituted Method Test Set-UP




Ground plane

■ Test Procedure

- 1. The EUT was set up for the maximum power. The power was measured with Spectrum Analyzer. All measurements were done at 3 channels (low, middle and high operational frequency range).
- 2. Radiation Emission measurement. In the semi-anechoic chamber, EUT placed on the 1.5m height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization to find the maximum polar radiated power. The "Read Value" is the spectrum reading the maximum power value.
- 3. The substitution antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a TX cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to "previously recorded (Pr)" of step a. Record the power level of S.G.
 - Below 1 GHz substituted method test used sleeve dipole antenna to Bi-Log antenna
 - Above 1 GHz substituted method test used horn antenna to horn antenna
 - E.I.R.P. = Output power level of S.G (P_{Mea}) + Amplifier Gain (P_{Ag}) TX cable loss (P_{Cl}) + Antenna gain of substitution horn (G_{a})

E.R.P. = E.I.R.P- 2.15 dB






■ Test Result

Both of Vertical and Horizontal polarizations are evaluated, but only the worst case is recorded in this report. Peak EIRP (dBm) = PM_{ea} - P_{cl} + P_{Ag} + G_a

Peak ERP(dBm) = $PM_{ea} - P_{cl} + P_{Ag} + G_{a} - 2.15dB$

SIM 1											
Operate Band: GPRS 850 Modulation Type: GMSK											
Frequency	Ant.	P _{Mea}	P _{cl}	P_{Ag}	G _a Antenna Gain	Correction	EF	RP	Limit		
(MHz)	Polar.	(dBm)	(dB)	(dB)	(dB)	(dB)	(dBm)	(W)	LIIIIII		
024.2	Н	-14.95	2.77	48	1.02	2.15	29.15	0.82	< 7		
824.2	V	-13.58	2.77	48	1.02	2.15	30.52	1.13	< 7		
836.6	Н	-14.84	2.78	48.04	1.06	2.15	29.33	0.86	< 7		
0.00.0	V	-13.47	2.78	48.04	1.06	2.15	30.70	1.17	< 7		
040.0	Н	-15.32	2.79	48.08	1.10	2.15	28.92	0.78	< 7		
848.8	V	-14.13	2.79	48.08	1.10	2.15	30.11	1.03	< 7		


SIM 1										
Operate Band: EGPRS 850 Modulation Type: 8PSK										
Frequency	Ant.	P _{Mea}	P _{cl}	P_{Ag}	G _a Antenna Gain	Correction	EF	RP	Limeia	
(MHz)	Polar.	(dBm)	(dB)	(dB)	(dB)	(dB)	(dBm)	(W)	Limit	
024.0	Н	-21.48	2.77	48	1.02	2.15	22.62	0.18	< 7	
824.2	V	-18.70	2.77	48	1.02	2.15	25.40	0.35	< 7	
926.6	Н	-20.25	2.78	48.04	1.06	2.15	23.92	0.25	< 7	
836.6	V	-18.71	2.78	48.04	1.06	2.15	25.46	0.35	< 7	
848.8	Н	-20.49	2.79	48.08	1.10	2.15	23.75	0.24	< 7	
040.0	V	-18.70	2.79	48.08	1.10	2.15	25.54	0.36	< 7	





SIM 1											
Operate Band	l: GPR	S 1900		Modu	lation Type: GMSK						
Frequency	Ant.	P _{Mea}	P _{cl}	P_{Ag}	G _a Antenna Gain	EII	RP	Limit			
(MHz)	Polar.	(dBm)	(dB)	(dB)	(dB)	(dBm)	(W)	(W)			
1850.2	Н	-18.51	4.02	46.49	4.89	28.85	0.77	< 2			
1650.2	V	-17.65	4.02	46.49	4.89	29.71	0.94	< 2			
1000.0	Н	-18.78	4.05	46.52	4.81	28.50	0.71	< 2			
1880.0	V	-18.23	4.05	46.52	4.81	29.05	0.80	< 2			
1909.8	Н	-18.77	4.09	46.56	4.73	28.43	0.70	< 2			
1909.6	V	-17.72	4.09	46.56	4.73	29.48	0.89	< 2			


SIM 1											
Operate Band: EGPRS 1900 Modulation Type: 8PSK											
Frequency	Ant.					Limit					
(MHz)	Polar.	(dBm)	(dB)	(dB)	(dB)	(dBm)	(W)	(W)			
4050.0	Н	-24.56	4.02	46.49	4.89	22.80	0.19	< 2			
1850.2	V	-22.43	4.02	46.49	4.89	24.93	0.31	< 2			
1000.0	Н	-24.57	4.05	46.52	4.81	22.71	0.19	< 2			
1880.0	V	-22.42	4.05	46.52	4.81	24.86	0.31	< 2			
4000.0	Н	-25.01	4.09	46.56	4.73	22.19	0.17	< 2			
1909.8	V	-23.22	4.09	46.56	4.73	23.98	0.25	< 2			





SIM 1										
Operate Band: WCDMA Band II Modulation Type: QPSK										
Frequency	Ant.	P _{Mea}	P _{cl} P _{Aq} G _a Antenna Gain EIRP					Limit		
(MHz)	Polar.	(dBm)	(dB)	(dB)	(dB)	(dBm)	(W)	(W)		
1852.4	Н	-27.09	4.02	46.49	4.89	20.27	0.11	< 2		
1652.4	V	-25.21	4.02	46.49	4.89	22.15	0.16	< 2		
1000.0	Н	-25.11	4.05	46.52	4.81	22.17	0.16	< 2		
1880.0	V	-24.50	4.05	46.52	4.81	22.78	0.19	< 2		
1907.6	Н	-25.48	4.09	46.56	4.73	21.72	0.15	< 2		
1907.6	V	-24.60	4.09	46.56	4.73	22.60	0.18	< 2		


					SIM 1				
Operate Band	: WCE	MA Band	V		Modulation Typ	e: QPSK			
Frequency	Ant.	P _{Mea}	P _{cl}	P _{Ag}	Ga Antenna Gain	Correction	EF	RP	Limit
(MHz)	Polar.	(dBm)	(dB)	(dB)	(dB)	(dB)	(dBm)	(W)	(W)
000.4	Н	-23.96	2.78	48.01	1.03	2.15	20.15	0.10	< 7
826.4	V	-22.05	2.78	48.01	1.03	2.15	22.06	0.16	< 7
020.0	Н	-23.45	2.78	48.04	1.06	2.15	20.72	0.12	< 7
836.6	V	-21.21	2.78	48.04	1.06	2.15	22.96	0.20	< 7
946.6	Н	-23.84	2.79	48.07	1.09	2.15	20.38	0.11	< 7
846.6	V	-21.84	2.79	48.07	1.09	2.15	22.38	0.17	< 7





					SIM 2						
Operate Band	l: GPR	S 850			Modulation Typ	e: GMSK					
Frequency	Ant.	P _{Mea}	P _{cl}	P _{Ag}	G _a Antenna Gain	Correction	EF	RP	Limit		
(MHz)	Polar.	(dBm)	(dB)	(dB)	(dB)	(dB)	(dBm)	(W)	LITTIIL		
824.2	Н	-15.31	2.77	48	1.02	2.15	28.79	0.76	< 7		
024.2	V	-14.01	2.77	48	1.02	2.15	30.09	1.02	< 7		
836.6	Η	-15.02	2.78	48.04	1.06	2.15	29.15	0.82	< 7		
030.0	V	-13.36	2.78	48.04	1.06	2.15	30.81	1.21	< 7		
848.8	Н	-15.58	2.79	48.08	1.10	2.15	28.66	0.73	< 7		
040.0	V	-14.30	2.79	48.08	1.10	2.15	29.94	0.99	< 7		


	SIM 2								
Operate Band	l: EGP	RS 850			Modulation Typ	e: 8PSK			
Frequency	Ant.	P _{Mea}	P _{cl}	P _{Ag}	Ga Antenna Gain	Correction	EF	RP	l imais
(MHz)	Polar.	(dBm)	(dB)	(dB)	(dB)	(dB)	(dBm)	(W)	Limit
924.2	Н	-21.68	2.77	48	1.02	2.15	22.42	0.17	< 7
824.2	V	-18.39	2.77	48	1.02	2.15	25.71	0.37	< 7
926.6	Н	-20.49	2.78	48.04	1.06	2.15	23.68	0.23	< 7
836.6	V	-18.67	2.78	48.04	1.06	2.15	25.50	0.35	< 7
040.0	Н	-20.99	2.79	48.08	1.10	2.15	23.25	0.21	< 7
848.8	V	-19.01	2.79	48.08	1.10	2.15	25.23	0.33	< 7





				OIMA				
				SIM 2				
Operate Band	l: GPR	S 1900		Modu	lation Type: GMSK			
Frequency	Ant.	P _{Mea}	P _{cl}	P_{Ag}	G _a Antenna Gain	EI	RP	Limit
(MHz)	Polar.	(dBm)	(dB)	(dB)	(dB)	(dBm)	(W)	(W)
1850.2	Н	-19.39	4.02	46.49	4.89	27.97	0.63	< 2
1650.2	V	-17.93	4.02	46.49	4.89	29.43	0.88	< 2
1880.0	Н	-18.51	4.05	46.52	4.81	28.77	0.75	< 2
1000.0	V	-17.62	4.05	46.52	4.81	29.66	0.92	< 2
1909.8	Н	-19.22	4.09	46.56	4.73	27.98	0.63	< 2
1909.6	V	-19.22	4.09	46.56	4.73	27.98	0.63	< 2


	SIM 2							
Operate Band	l: EGP	RS 1900		Modu	lation Type: 8PSK			
Frequency	Ant.	P _{Mea}	P _{cl}	P _{Ag}	G _a Antenna Gain	EII	RP	Limit
(MHz)	Polar.	(dBm)	(dB)	(dB)	(dB)	(dBm)	(W)	(W)
1050.0	Н	-24.78	4.02	46.49	4.89	22.58	0.18	< 2
1850.2	V	-22.81	4.02	46.49	4.89	24.55	0.29	< 2
1880.0	Н	-24.82	4.05	46.52	4.81	22.46	0.18	< 2
1000.0	V	-23.81	4.05	46.52	4.81	23.47	0.22	< 2
1000.0	Н	-25.15	4.09	46.56	4.73	22.05	0.16	< 2
1909.8	V	-23.64	4.09	46.56	4.73	23.56	0.23	< 2





				SIM 2				
Operate Band	Operate Band: WCDMA Band II Modulation Type: QPSK							
Frequency	Ant.	P _{Mea}	P _{cl}	P_{Ag}	G _a Antenna Gain	EII	RP	Limit
(MHz)	Polar.	(dBm)	(dB)	(dB)	(dB)	(dBm)	(W)	(W)
1050.4	Н	-27.23	4.02	46.49	4.89	20.13	0.10	< 2
1852.4	V	-25.08	4.02	46.49	4.89	22.28	0.17	< 2
4000.0	Н	-26.50	4.05	46.52	4.81	20.78	0.12	< 2
1880.0	V	-24.39	4.05	46.52	4.81	22.89	0.19	< 2
1007.6	Н	-24.98	4.09	46.56	4.73	22.22	0.17	< 2
1907.6	V	-24.79	4.09	46.56	4.73	22.41	0.17	< 2

					SIM 2				
Operate Band: WCDMA Band V Modulation Type: QPSK									
Frequency	Ant.	P _{Mea}	P _{cl}	P _{Ag}	Ga Antenna Gain	Correction	EF	RP	Limit
(MHz)	Polar.	(dBm)	(dB)	(dB)	(dB)	(dB)	(dBm)	(W)	(W)
000.4	Н	-24.19	2.78	48.01	1.03	2.15	19.92	0.10	< 7
826.4	V	-22.40	2.78	48.01	1.03	2.15	21.71	0.15	< 7
000.0	Н	-23.72	2.78	48.04	1.06	2.15	20.45	0.11	< 7
836.6	V	-21.21	2.78	48.04	1.06	2.15	22.96	0.20	< 7
946.6	Н	-24.03	2.79	48.07	1.09	2.15	20.19	0.10	< 7
846.6	V	-21.84	2.79	48.07	1.09	2.15	22.38	0.17	< 7






4.3. Peak to Average Ratio

■ Limit


In measuring transmissions in this band using an average power technique, the peak to-average ratio (PAR) of the transmission may not exceed 13 dB.

■ Setup



■ Test Procedure

- a. Set resolution/measurement bandwidth signal's occupied bandwidth;
- b. Set the number of counts to a value that stabilizes the measured CCDF curve;
- c. Record the maximum PAPR level associated with a probability of 0.1%.





■ Test Result

	SIM1	
Operate Band:	GPRS 850	Modulation Type: GMSK
Frequency (MHz)	Peak to Average Ratio (dB)	Limit (dB)
824.2	7.660	< 13
836.6	7.660	< 13
848.8	7.660	< 13

	SIM1	
Operate Band:	EGPRS 850	Modulation Type: 8PSK
Frequency (MHz)	Peak to Average Ratio (dB)	Limit (dB)
824.2	7.596	< 13
836.6	7.596	< 13
848.8	7.628	< 13

	SIM1	
Operate Band:	GPRS 1900	Modulation Type: GMSK
Frequency	Peak to Average Ratio	Limit
(MHz)	(dB)	(dB)
1850.20	7.660	< 13
1880.00	7.628	< 13
1909.80	7.660	< 13

	SIM1	
Operate Band:	EGPRS 1900	Modulation Type: 8PSK
Frequency (MHz)	Peak to Average Ratio (dB)	Limit (dB)
1850.20	7.628	< 13
1880.00	7.628	< 13
1909.80	7.628	< 13

SIM1							
Operate Band:	WCDMA Band II	Modulation Type: QPSK					
Frequency	Peak to Average Ratio	Limit					
(MHz)	(dB)	(dB)					
1852.4	3.429	< 13					
1880.0	3.526	< 13					
1907.6	3.526	< 13					

	SIM1	
Operate Band:	WCDMA Band V	Modulation Type: QPSK
Frequency (MHz)	Peak to Average Ratio (dB)	Limit (dB)
826.4	3.494	< 13
836.6	3.205	< 13
846.6	3.462	< 13



	SIM2	
Operate Band:	GPRS 850	Modulation Type: GMSK
Frequency (MHz)	Peak to Average Ratio (dB)	Limit (dB)
824.2	7.628	< 13
836.6	7.660	< 13
848.8	7.660	< 13

SIM2			
Operate Band:	EGPRS 850	Modulation Type: 8PSK	
Frequency (MHz)	Peak to Average Ratio (dB)	Limit (dB)	
824.2	7.596	< 13	
836.6	7.628	< 13	
848.8	7.628	< 13	


SIM2			
Operate Band:	GPRS 1900	Modulation Type: GMSK	
Frequency (MHz)	Peak to Average Ratio (dB)	Limit (dB)	
1850.20	7.660	< 13	
1880.00	7.660	< 13	
1909.80	7.660	< 13	

SIM2			
Operate Band:	EGPRS 1900	Modulation Type: 8PSK	
Frequency (MHz)	Peak to Average Ratio (dB)	Limit (dB)	
1850.20	7.628	< 13	
1880.00	7.660	< 13	
1909.80	7.628	< 13	


SIM2				
Operate Band:	WCDMA Band II	Modulation Type: 0	QPSK	
Frequency (MHz)	Peak to Average Ratio (dB)	Limit (dB)		
1852.4	3.333	< 13		
1880.0	3.301	< 13		
1907.6	3.301	< 13		

SIM2			
Operate Band:	WCDMA Band V	Modulation Type: QPSK	
Frequency (MHz)	Peak to Average Ratio (dB)	Limit (dB)	
826.4	3.494	< 13	
836.6	3.333	< 13	
846.6	3.494	< 13	

































































4.4. Emission Bandwidth & Occupied Bandwidth


■ Setup



■ Test Procedure

The measurement is made according to FCC rules part 22 and 24:

- 1. The EUT was connected to Spectrum Analyzer and Base Station via Power Divider.
- 2. The occupied bandwidth of Low \cdot middle and High channel for the highest RF powers was measured.





■ Test Result

SIM 1		
Operate Band:	GPRS 850	Modulation Type: GMSK
Frequency (MHz)	Emission Bandwidth (100%) (kHz)	99% Bandwidth (kHz)
824.2	309.295	244.391
836.6	306.891	245.994
848.8	308.494	242.788


SIM 1		
Operate Band:	EGPRS 850	Modulation Type: 8PSK
Frequency (MHz)	Emission Bandwidth (100%) (kHz)	99% Bandwidth (kHz)
824.2	307.692	246.795
836.6	307.692	246.795
848.8	307.692	243.590

The cell band analyzer settings: RBW =5 kHz; VBW = 20 kHz.

	SIM 1	
Operate Band:	GPRS 1900	Modulation Type: GMSK
Frequency (MHz)	Emission Bandwidth (100%) (kHz)	99% Bandwidth (kHz)
1850.20	307.692	244.391
1880.00	306.891	244.391
1909.80	306.090	244.391

	SIM 1	
Operate Band:	EGPRS 1900	Modulation Type: 8PSK
Frequency (MHz)	Emission Bandwidth (100%) (kHz)	99% Bandwidth (kHz)
1850.20	307.692	245.192
1880.00	306.891	244.391
1909.80	307.692	245.994

The pcs band analyzer settings: RBW =5 kHz; VBW = 20 kHz.






	SIM 1	
Operate Band:	WCDMA Band II	Modulation Type: QPSK
Frequency (MHz)	Emission Bandwidth (100%) (MHz)	99% Bandwidth (MHz)
1852.4	4.503	4.167
1880.0	4.519	4.167
1907.6	4.503	4.167

The WCDMA Band II analyzer settings: RBW =50 kHz; VBW = 200 kHz

	SIM 1	
Operate Band:	WCDMA Band V	Modulation Type: QPSK
Frequency (MHz)	Emission Bandwidth (100%) (MHz)	99% Bandwidth (MHz)
826.4	4.487	4.183
836.6	4.471	4.151
846.6	4.487	4.167

The WCDMA Band V analyzer settings: RBW =50 kHz; VBW = 200 kHz





	SIM 2	
Operate Band:	GPRS 850	Modulation Type: GMSK
Frequency (MHz)	Emission Bandwidth (100%) (kHz)	99% Bandwidth (kHz)
824.2	306.090	247.596
836.6	306.891	246.795
848.8	305.288	245.192


SIM 2		
Operate Band:	EGPRS 850	Modulation Type: 8PSK
Frequency (MHz)	Emission Bandwidth (100%) (kHz)	99% Bandwidth (kHz)
824.2	306.891	244.391
836.6	307.692	242.788
848.8	306.891	245.994

The cell band analyzer settings: RBW =5 kHz; VBW = 20 kHz.

SIM 2		
Operate Band:	GPRS 1900	Modulation Type: GMSK
Frequency (MHz)	Emission Bandwidth (100%) (kHz)	99% Bandwidth (kHz)
1850.20	306.891	245.994
1880.00	306.891	244.391
1909.80	306.891	245.994

SIM 2		
Operate Band:	EGPRS 1900	Modulation Type: 8PSK
Frequency (MHz)	Emission Bandwidth (100%) (kHz)	99% Bandwidth (kHz)
1850.20	306.090	249.199
1880.00	308.494	241.987
1909.80	307.692	245.192

The pcs band analyzer settings: RBW =5 kHz; VBW = 20 kHz.






	SIM 2	
Operate Band:	WCDMA Band II	Modulation Type: QPSK
Frequency (MHz)	Emission Bandwidth (100%) (MHz)	99% Bandwidth (MHz)
1852.4	4.471	4.151
1880.0	4.487	4.151
1907.6	4.487	4.151

The WCDMA Band II analyzer settings: RBW =50 kHz; VBW = 200 kHz


	SIM 2	
Operate Band:	WCDMA Band V	Modulation Type: QPSK
Frequency (MHz)	Emission Bandwidth (100%) (MHz)	99% Bandwidth (MHz)
826.4	4.487	4.167
836.6	4.471	4.151
846.6	4.471	4.167


The WCDMA Band V analyzer settings: RBW =50 kHz; VBW = 200 kHz






■ Emission Bandwidth (100%) Test Graphs









































































































































































■ 99% Bandwidth Test Graphs

































































































































































4.5. Frequency Stability

■ Limit

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within ±0.00025% (±2.5ppm) of the center frequency.


■ Setup



■ Test Procedure

The measurement is made according to FCC rules part 22 and 24:

- 1. The EUT and test equipment were set up as shown on the following section.
- 2. With all power removed, the temperature was decreased to -30°C and permitted to stabilize for three hours. Power was applied and the maximum change in frequency was note within one minute.
- 3. With power OFF, the temperature was raised in 10℃ steps. The sample was permitted to stabilize at each step for at least one-half hour. Power was applied and the maximum frequency change was noted within one minute.
- 4. The EUT was placed in a temperature chamber at 25 ± 5 °C and connected as the following section.
- 5. The power supply voltage to the EUT was varied from BEP to 115% of the nominal value measured at the input to the EUT.
- 6. The temperature tests were performed for the worst case.
- 7. Test data was recorded.






■ Test Result

SIM 1							
Operate Band: GPRS 850 Modulation Type: GMSK							
		Voltage					
Frequency	Voltage	Temperature	Frequen	cy Error	Limit		
(MHz)	[Vdc]	(℃)	(Hz)	(ppm)	(ppm)		
	4.20	20	-11	0.013	± 2.5		
836.6	3.80	20	-17	0.020	± 2.5		
	3.50	20	-8	0.010	± 2.5		
		Temperat	ture				
Frequency (MHz)	Voltage [Vdc]	Temperature (°C)	Deviation (Hz)	Deviation (ppm)	Limit (ppm)		
	3.80	0	-11	0.013	± 2.5		
	3.80	10	-9	0.011	± 2.5		
836.6	3.80	20	-19	0.023	± 2.5		
	3.80	30	-10	0.012	± 2.5		
	3.80	40	-14	0.017	± 2.5		


SIM 1								
Operate Band: EGPRS 850 Modulation Type: 8PSK								
		Voltage	е					
Frequency	Voltage	Temperature	Frequen	cy Error	Limit			
(MHz)	[Vdc]	(℃)	(Hz)	(ppm)	(ppm)			
	4.20	20	-49	0.059	± 2.5			
836.6	3.80	20	-50	0.060	± 2.5			
	3.50	20	-47	0.057	± 2.5			
		Temperat	ture					
Frequency (MHz)	Voltage [Vdc]	Temperature (°C)	Deviation (Hz)	Deviation (ppm)	Limit (ppm)			
	3.80	0	-52	0.062	± 2.5			
	3.80	10	-45	0.054	± 2.5			
836.6	3.80	20	-67	0.080	± 2.5			
	3.80	30	-46	0.055	± 2.5			
	3.80	40	-50	0.060	± 2.5			





	SIM 1							
Operate Band: C	SPRS 1900	Modulation ²	Type: GMSK					
		Voltage	9					
Frequency	Voltage	Temperature	Frequen	cy Error	Limit			
(MHz)	[Vdc]	(℃)	(Hz)	(ppm)	(ppm)			
	4.20	20	-24	0.013	± 2.5			
1880.0	3.80	20	-15	0.008	± 2.5			
	3.50	20	-19	0.010	± 2.5			
		Temperat	ture					
Frequency (MHz)	Voltage [Vdc]	Temperature (°C)	Deviation (Hz)	Deviation (ppm)	Limit (ppm)			
	3.80	0	-19	0.010	± 2.5			
	3.80	10	-22	0.012	± 2.5			
1880.0	3.80	20	-8	0.004	± 2.5			
	3.80	30	-3	0.002	± 2.5			
	3.80	40	-21	0.011	± 2.5			


	SIM 1							
Operate Band: E	EGPRS 1900	Modulation ³	Type: 8PSK					
		Voltage	9					
Frequency	Voltage	Temperature	Frequen	cy Error	Limit			
(MHz)	[Vdc]	(℃)	(Hz)	(ppm)	(ppm)			
	4.20	20	-47.41	0.025	± 2.5			
1880.0	3.80	20	-46.24	0.025	± 2.5			
	3.50	20	-47.22	0.025	± 2.5			
		Temperat	ture					
Frequency (MHz)	Voltage [Vdc]	Temperature (°C)	Deviation (Hz)	Deviation (ppm)	Limit (ppm)			
	3.80	0	-51.4	0.027	± 2.5			
	3.80	10	-47.80	0.025	± 2.5			
1880.0	3.80	20	-50.62	0.027	± 2.5			
	3.80	30	-58.81	0.031	± 2.5			
	3.80	40	-56.02	0.030	± 2.5			





SIM 1								
Operate Band: \	NCDMA Band II	Modulation ³	Type: QPSK					
		Voltage	е					
Frequency	Voltage	Temperature	Frequen	cy Error	Limit			
(MHz)	[Vdc]	(℃)	(Hz)	(ppm)	(ppm)			
	4.20	20	-6	0.003	± 2.5			
1880.0	3.80	20	-6	0.003	± 2.5			
	3.50	20	-5	0.003	± 2.5			
		Temperat	ture					
Frequency (MHz)	Voltage [Vdc]	Temperature (°C)	Deviation (Hz)	Deviation (ppm)	Limit (ppm)			
	3.80	0	8	0.004	± 2.5			
	3.80	10	5	0.003	± 2.5			
1880.0	3.80	20	-2	0.001	± 2.5			
	3.80	30	8	0.004	± 2.5			
	3.80	40	5	0.002	± 2.5			


		011.4							
	SIM 1								
Operate Band:	WCDMA Band V	Modulation ³	Type: QPSK						
		Voltage	Э						
Frequency	Voltage	Temperature	Frequen	cy Error	Limit				
(MHz)	[Vdc]	(℃)	(Hz)	(ppm)	(ppm)				
	4.20	20	-10	0.012	± 2.5				
836.6	3.80	20	-9	0.010	± 2.5				
	3.50	20	-6	0.007	± 2.5				
		Temperat	ture						
Frequency (MHz)	Voltage [Vdc]	Temperature (°C)	Deviation (Hz)	Deviation (ppm)	Limit (ppm)				
	3.80	0	-5	0.006	± 2.5				
	3.80	10	-4	0.005	± 2.5				
836.6	3.80	20	-5	0.006	± 2.5				
	3.80	30	-5	0.006	± 2.5				
	3.80	40	-6	0.008	± 2.5				





SIM 2								
Operate Band: GPRS 850 Modulation Type: GMSK								
		Voltage	Э					
Frequency	Voltage	Temperature	Frequen	cy Error	Limit			
(MHz)	[Vdc]	(℃)	(Hz)	(ppm)	(ppm)			
	4.20	20	-3	0.004	± 2.5			
836.6	3.80	20	-7	0.008	± 2.5			
	3.50	20	-16	0.019	± 2.5			
		Temperat	ture					
Frequency (MHz)	Voltage [Vdc]	Temperature (°C)	Deviation (Hz)	Deviation (ppm)	Limit (ppm)			
	3.80	0	-17	0.020	± 2.5			
	3.80	10	-5	0.006	± 2.5			
836.6	3.80	20	-10	0.012	± 2.5			
	3.80	30	-7	0.008	± 2.5			
	3.80	40	-18	0.022	± 2.5			


OIM O								
	SIM 2							
Operate Band: E	GPRS 850	Modulation [*]	Type: 8PSK					
		Voltage	е					
Frequency	Voltage	Temperature	Frequen	cy Error	Limit			
(MHz)	[Vdc]	(℃)	(Hz)	(ppm)	(ppm)			
	4.20	20	-46	0.055	± 2.5			
836.6	3.80	20	-51	0.061	± 2.5			
	3.50	20	-43	0.051	± 2.5			
		Temperat	ture					
Frequency (MHz)	Voltage [Vdc]	Temperature (°C)	Deviation (Hz)	Deviation (ppm)	Limit (ppm)			
	3.80	0	-50	0.060	± 2.5			
	3.80	10	-42	0.050	± 2.5			
836.6	3.80	20	-53	0.063	± 2.5			
	3.80	30	-61	0.073	± 2.5			
	3.80	40	-58	0.069	± 2.5			





SIM 2								
Operate Band: 0								
·		Voltage	Э					
Frequency	Voltage	Temperature	Frequen	cy Error	Limit			
(MHz)	[Vdc]	(℃)	(Hz)	(ppm)	(ppm)			
	4.20	20	-21	0.011	± 2.5			
1880.0	3.80	20	-16	0.009	± 2.5			
	3.50	20	-11	0.006	± 2.5			
		Temperat	ture					
Frequency (MHz)	Voltage [Vdc]	Temperature (°C)	Deviation (Hz)	Deviation (ppm)	Limit (ppm)			
	3.80	0	-25	0.013	± 2.5			
	3.80	10	-7	0.004	± 2.5			
1880.0	3.80	20	-18	0.010	± 2.5			
	3.80	30	-14	0.007	± 2.5			
	3.80	40	-27	0.014	± 2.5			


		SIM 2					
Operate Band: E	GPRS 1900		* *				
		Voltage	е				
Frequency	Voltage	Temperature	Frequen	cy Error	Limit		
(MHz)	[Vdc]	(℃)	(Hz)	(ppm)	(ppm)		
	4.20	20	-48	0.026	± 2.5		
1880.0	3.80	20	-43	0.023	± 2.5		
	3.50	20	-48	0.026	± 2.5		
		Temperat	ture				
Frequency (MHz)	Voltage [Vdc]	Temperature (°C)	Deviation (Hz)	Deviation (ppm)	Limit (ppm)		
	3.80	0	-48	0.026	± 2.5		
	3.80	10	-52	0.028	± 2.5		
1880.0	3.80	20	-50	0.027	± 2.5		
	3.80	30	-52	0.028	± 2.5		
	3.80	40	-54	0.029	± 2.5		





SIM 2								
Operate Band: \	NCDMA Band II	Modulation ⁷	Type: QPSK					
		Voltage	е					
Frequency	Voltage	Temperature	Frequen	cy Error	Limit			
(MHz)	[Vdc]	(℃)	(Hz)	(ppm)	(ppm)			
	4.20	20	-6	0.003	± 2.5			
1880.0	3.80	20	6	0.003	± 2.5			
	3.50	20	-8	0.004	± 2.5			
		Temperat	ture					
Frequency (MHz)	Voltage [Vdc]	Temperature (°C)	Deviation (Hz)	Deviation (ppm)	Limit (ppm)			
	3.80	0	-4	0.002	± 2.5			
	3.80	10	-6	0.003	± 2.5			
1880.0	3.80	20	-4	0.002	± 2.5			
	3.80	30	-3	0.002	± 2.5			
	3.80	40	-6	0.003	± 2.5			

SIM 2								
Operate Band:	WCDMA Band V	Modulation ¹	Type: QPSK					
		Voltage	Э					
Frequency	Voltage	Temperature	Frequen	cy Error	Limit			
(MHz)	[Vdc]	(℃)	(Hz)	(ppm)	(ppm)			
	4.20	20	-2	0.003	± 2.5			
836.6	3.80	20	-3	0.004	± 2.5			
	3.50	20	-4	0.004	± 2.5			
		Temperat	ture					
Frequency (MHz)	Voltage [Vdc]	Temperature (°C)	Deviation (Hz)	Deviation (ppm)	Limit (ppm)			
	3.80	0	3	0.004	± 2.5			
	3.80	10	-2	0.003	± 2.5			
836.6	3.80	20	3	0.004	± 2.5			
	3.80	30	-3	0.003	± 2.5			
	3.80	40	-3	0.004	± 2.5			






4.6. Band Edge

■ Limit

On any frequency outside frequency band of the US Cellular/PCS spectrum, the power of any emission shall be attenuated below the transmitter power (P, in Watts) by at least 43+10Log (P) dB.

■ Setup



■ Test Procedure

The measurement is made according to FCC rules part 22 and 24:

- 1. The EUT was connected to Spectrum Analyzer and Base Station via Power Divider.
- 2. The band edge of low and high channels for the highest RF powers within the transmitting frequency band were measured. Setting RBW as roughly BW/100.
- 3. The band edge setting:

For GSM 850 and PCS 1900, RB=5 kHz; VB=20 kHz.

For WCDMA Band V and WCDMA Band II, RB=50 kHz; VB=200 kHz.



■ Test Result

SIM 1			
Operate Band: GPRS 850			
Band Edge	Channel	Results (dBm)	Limit (dBm)
Lower Band Edge	128	-15.17	< -13
Higher Band Edge	251	-13.77	< -13

SIM 1			
Operate Band: EGPRS 850			
Band Edge	Channel	Results (dBm)	Limit (dBm)
Lower Band Edge	128	-21.1	< -13
Higher Band Edge	251	-18.28	< -13

SIM 1			
Operate Band: GPRS 1900			
Band Edge	Channel	Results (dBm)	Limit (dBm)
Lower Band Edge	512	-18.73	< -13
Higher Band Edge	810	-17.17	< -13

SIM 1			
Operate Band: EGPRS 1900			
Band Edge	Channel	Results (dBm)	Limit (dBm)
Lower Band Edge	512	-21.96	< -13
Higher Band Edge	810	-19.65	< -13

SIM 1				
Operate Band: WCDMA Band II				
Band Edge Channel Results Limit (dBm) (dBm)				
Lower Band Edge	9262	-32.10	< -13	
Higher Band Edge	9538	-30.95	< -13	

SIM 1			
Operate Band: WCDMA Band V			
Band Edge Channel Results Limit (dBm) (dBm)			
Lower Band Edge	4132	-29.49	< -13
Higher Band Edge	4233	-28.91	< -13



SIM 2				
Operate Band: GPRS 850				
Band Edge Channel Results Limit (dBm) (dBm)				
Lower Band Edge 128 -14.40 < -13				
Higher Band Edge	251	-13.09	< -13	


SIM 2				
Operate Band: EGPRS 850				
Band Edge Channel Results (dBm) Limit (dBm)				
Lower Band Edge 128 -20.96 < -13				
Higher Band Edge	251	-18.41	< -13	

SIM 2				
Operate Band: GPRS 1900				
Band Edge Channel Results Limit (dBm) (dBm)				
Lower Band Edge	512	-18.82	< -13	
Higher Band Edge	810	-17.3	< -13	

SIM 2			
Operate Band: EGPRS 1900			
Band Edge	Channel	Results (dBm)	Limit (dBm)
Lower Band Edge	512	-20.63	< -13
Higher Band Edge	810	-20.37	< -13


SIM 2				
Operate Band: WCDMA Band II				
Band Edge Channel Results (dBm) Limit (dBm)				
Lower Band Edge	9262	-31.55	< -13	
Higher Band Edge	9538	-29.67	< -13	

SIM 2				
Operate Band: WCDMA Band V				
Band Edge Channel Results Limit (dBm) (dBm)				
Lower Band Edge	4132	-30.55	< -13	
Higher Band Edge	4233	-30.11	< -13	






■ Test Graphs


































































4.7. Radiated Spurious Emissions

■ Limit


The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10log(P) dB.


It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10th harmonic.

■ Setup

Below 1GHz


Below 1 GHz









Above 1GHz



For Substituted Method Test Set-UP



Ground plane





■ Test Procedure


- 1. The EUT was set up for the maximum power. The power was measured with Spectrum Analyzer. All measurements were done at 3 channels (low, middle and high operational frequency range).
- 2. Radiation Emission measurement. In the semi-anechoic chamber, EUT placed on the 1.5m height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization to find the maximum polar radiated power. The "Read Value" is the spectrum reading the maximum power value.
- 3. The substitution antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a TX cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to "previously recorded (Pr)" of step a. Record the power level of S.G.

Below 1 GHz substituted method test used sleeve dipole antenna to Bi-Log antenna

Above 1 GHz substituted method test used horn antenna to horn antenna

E.I.R.P. = Output power level of S.G (PMea) - TX cable loss (PcI) + Antenna gain of substitution horn (Ga)

E.R.P. = E.I.R.P- 2.15 dB






■ Test Result

	SIM 1									
Operate Band	Operate Band: GPRS 850 Modulation Type: GMSK									
Frequency: 824.2 MHz										
Frequency	Ant.	P _{Mea}	P _{cl}	G _a Antenna Gain	Correction	ERP	Limit			
(MHz)	Polar.	(dBm)	(dB)	(dB)	(dB)	(dBm)	(dBm)			
1648.4	Н	-57.64	3.78	5.41	2.15	-58.16	< -13			
1648.4	V	-59.07	3.78 5.41 2.15 -59.59 < -13							

	SIM 1									
Operate Band: GPRS 850 Modulation Type: GMSK										
Frequency:	requency: 836.6 MHz									
Frequency	Ant.	P_{Mea}	P _{cl}	G _a Antenna Gain	Correction	ERP	Limit			
(MHz)	Polar.	(dBm)	(dB)	(dB)	(dB)	(dBm)	(dBm)			
1672.0	Н	-59.23	3.81 5.36 2.15 -59.83 < -13							
1673.2	V	-59.55	3.81	5.36	2.15	-60.15	< -13			

SIM 1									
Operate Band: GPRS 850 Modulation Type: GMSK									
Frequency:	ency: 848.8 MHz								
Frequency	Ant.	P _{Mea}	P _{cl}	G _a Antenna Gain	Correction	ERP	Limit		
(MHz)	Polar.	(dBm)	(dB)	(dB)	(dB)	(dBm)	(dBm)		
1697.6	Н	-58.5	3.84	5.28	2.15	-59.21	< -13		
1697.6	V	-57.42	3.84	5.28	2.15	-58.13	< -13		






SIM 1										
Operate Band: GPRS 1900 Modulation Type: GMSK										
Frequency: 1850.2 MHz										
Frequency	Ant.	P _{Mea}	P _{cl} G _a Antenna Gain EIRP Limit							
(MHz)	Polar.	(dBm)	(dB)	(dB)	(dBm)	(dBm)				
3700.4	Н	-50.19	5.85 8.6 -47.44 < -13							
3700.4	V	-48.1	5.85	8.6	-45.35	< -13				

	SIM 1										
Operate Band	l: GPR	S 1900		Modulation Type: GMSK							
Frequency:	requency: 1880.0 MHz										
Frequency	Ant.	P _{Mea}	P _{cl} G _a Antenna Gain EIRP Limit								
(MHz)	Polar.	(dBm)	(dB)	(dB)	(dBm)	(dBm)					
3760.0	Н	-51.67	5.91 8.66 -48.92 < -13								
3760.0	V	-47.93	5.91 8.66 -45.18 < -13								

	SIM 1										
Operate Band	Operate Band: GPRS 1900 Modulation Type: GMSK										
Frequency: 1909.8 MHz											
Frequency	Ant.	P _{Mea}	P _{cl} G _a Antenna Gain EIRP Limit								
(MHz)	Polar.	(dBm)	(dB)	(dB)	(dBm)	(dBm)					
3819.6	Η	-50.44	5.95 8.72 -47.67 < -13								
3819.6	V	-46.8	5.95 8.72 -44.03 < -13								





	SIM 1										
Operate Band	Operate Band: WCDMA Band II Modulation Type: QPSK										
Frequency: 1852.4 MHz											
Frequency	Ant.	P _{Mea}	P _{cl} G _a Antenna Gain EIRP Limit								
(MHz)	Polar.	(dBm)	(dB)	(dB)	(dBm)	(dBm)					
3700.0	Н	-51.86	5.85 8.6 -49.11 < -13								
3704.8	V	-51.03	5.86 8.61 -48.28 < -13								

	SIM 1										
Operate Band	Operate Band: WCDMA Band II Modulation Type: QPSK										
Frequency:	1880	30.0 MHz									
Frequency	Ant.	P _{Mea}	P _{cl} G _a Antenna Gain EIRP Limit								
(MHz)	Polar.	(dBm)	(dB)	(dB)	(dBm)	(dBm)					
3760.0	Н	-53.7	5.9 8.66 -50.94 < -13								
3760.0	V	-50.86	5.9 8.66 -48.1 < -13								

SIM 1										
Operate Band	Operate Band: WCDMA Band II Modulation Type: QPSK									
Frequency: 1907.6 MHz										
Frequency	Ant.	P _{Mea}	P _{cl} G _a Antenna Gain EIRP Limit							
(MHz)	Polar.	(dBm)	(dB)	(dB)	(dBm)	(dBm)				
3815.2	Н	-52.53	5.95 8.72 -49.76 < -13							
3815.2	V	-50.20	5.95	8.72	-47.43	< -13				






SIM 1										
Operate Band: WCDMA Band V Modulation Type: QPSK										
Frequency: 826.4 MHz										
Frequency	Ant.	P _{Mea}	P _{cl}	G _a Antenna Gain	Correction	ERP	Limit			
(MHz)	Polar.	(dBm)	(dB)	(dB)	(dB)	(dBm)	(dBm)			
1652.8	Н	-59.66	3.78	5.41	2.15	-60.18	< -13			
1652.8	V	-59.8	3.78	5.41	2.15	-60.32	< -13			

	SIM 1									
Operate Band	Operate Band: WCDMA Band V Modulation Type: QPSK									
Frequency: 836.6 MHz										
Frequency	Ant.	P _{Mea}	P _{cl} G _a Antenna Gain Correction ERP Limit							
(MHz)	Polar.	(dBm)	(dB)	(dB)	(dB)	(dBm)	(dBm)			
1673.2	Н	-59.45	3.81 5.36 2.15 -60.05 < -13							
1673.2	V	-58.18	3.81 5.36 2.15 -58.78 < -13							

SIM 1										
Operate Band	Operate Band: WCDMA Band V Modulation Type: QPSK									
Frequency: 846.6 MHz										
Frequency	Ant.	P _{Mea}	P _{cl}	G _a Antenna Gain	Correction	ERP	Limit			
(MHz)	Polar.	(dBm)	(dB)	(dB)	(dB)	(dBm)	(dBm)			
1692.8	Н	-58.91	3.84	5.28	2.15	-59.62	< -13			
1692.8	V	-60.15	3.84	5.28	2.15	-60.86	< -13			






	SIM 2										
Operate Band: GPRS 850 Modulation Type: GMSK											
Frequency: 824.2 MHz											
Frequency	Ant.	P _{Mea}	P _{cl} G _a Antenna Gain Correction ERP Limit								
(MHz)	Polar.	(dBm)	(dB)	(dB)	(dB)	(dBm)	(dBm)				
1648.4	Н	-58.58	3.78 5.41 2.15 -59.1 < -13								
1648.4	V	-58.55	3.78	5.41	2.15	-59.07	< -13				

	SIM 2									
Operate Band: GPRS 850 Modulation Type: GMSK										
Frequency:	836.6	6 MHz								
Frequency	Ant.	P _{Mea}	P _{cl}	P _{cl} G _a Antenna Gain Correction ERP Limit						
(MHz)	Polar.	(dBm)	(dB)	(dB)	(dB)	(dBm)	(dBm)			
1672.0	Н	-59.61	3.81 5.36 2.15 -60.21 < -13							
1673.2	V	-59.73	3.81	5.35	2.15	-60.34	< -13			

	SIM 2										
Operate Band	Operate Band: GPRS 850 Modulation Type: GMSK										
Frequency: 848.8 MHz											
Frequency	Ant.	P _{Mea}	P _{cl} G _a Antenna Gain Correction ERP Limit								
(MHz)	Polar.	(dBm)	(dB)	(dB)	(dB)	(dBm)	(dBm)				
1697.6	Н	-59.34	3.84	5.28	2.15	-60.05	< -13				
1697.6	V	-58.85	3.84	5.28	2.15	-59.56	< -13				






SIM 2										
Operate Band: GPRS 1900 Modulation Type: GMSK										
Frequency: 1850.2 MHz										
Frequency	Ant.	P _{Mea}	P _{cl} G _a Antenna Gain EIRP Limit							
(MHz)	Polar.	(dBm)	(dB)	(dB)	(dBm)	(dBm)				
3700.4	Н	-48.77	5.85 8.6 -46.02 < -1							
3700.4	V	-47.69	5.85	8.6	-44.94	< -13				

	SIM 2										
Operate Band	Operate Band: GPRS 1900 Modulation Type: GMSK										
Frequency:	1880	.0 MHz									
Frequency	Ant.	P _{Mea}	P _{cl} G _a Antenna Gain EIRP Limit								
(MHz)	Polar.	(dBm)	(dB)	(dB)	(dBm)	(dBm)					
3760.0	Н	-52.14	5.91 8.66 -49.39 < -13								
3760.0	V	-48.66	5.91 8.66 -45.91 < -13								

	SIM 2										
Operate Band	Operate Band: GPRS 1900 Modulation Type: GMSK										
Frequency:	1909	.8 MHz									
Frequency	Ant.	P _{Mea}	P _{cl} G _a Antenna Gain EIRP Limit								
(MHz)	Polar.	(dBm)	(dB)	(dB)	(dBm)	(dBm)					
3819.6	Н	-50.93	5.95 8.72 -48.16 < -13								
3819.6	V	-47.64	5.95 8.72 -44.87 < -13								






SIM 2										
Operate Band: WCDMA Band II Modulation Type: QPSK										
Frequency: 1852.4 MHz										
Frequency	Ant.	P _{Mea}	P _{cl} G _a Antenna Gain EIRP Limit							
(MHz)	Polar.	(dBm)	(dB)	(dB)	(dBm)	(dBm)				
3704.8	Н	-53.42	5.85 8.6 -50.67 < -13							
3704.8	V	-51.71	5.86	8.61	-48.96	< -13				

	SIM 2										
Operate Band	Operate Band: WCDMA Band II Modulation Type: QPSK										
Frequency:	1880	.0 MHz									
Frequency	Ant.	P _{Mea}	P _{cl} G _a Antenna Gain EIRP Limit								
(MHz)	Polar.	(dBm)	(dB)	(dB)	(dBm)	(dBm)					
3760.0	Н	-54.09	5.9 8.66 -51.33 < -13								
3760.0	V	-51.5	5.9 8.66 -48.74 < -13								

	SIM 2										
Operate Band: WCDMA Band II Modulation Type: QPSK											
Frequency:	1907	.6 MHz									
Frequency	Ant.	P _{Mea}	P _{cl} G _a Antenna Gain EIRP Limit								
(MHz)	Polar.	(dBm)	(dB)	(dB)	(dBm)	(dBm)					
3815.2	Н	-53.75	5.95 8.72 -50.98 < -13								
3815.2	V	-50.89	5.95 8.72 -48.12 < -13								






SIM 2										
Operate Band: WCDMA Band V Modulation Type: QPSK										
Frequency: 826.4 MHz										
Frequency	Ant.	P _{Mea}	P _{cl} G _a Antenna Gain Correction ERP Limit							
(MHz)	Polar.	(dBm)	(dB)	(dB)	(dB)	(dBm)	(dBm)			
1652.8	Н	-60.12	3.78	5.41	2.15	-60.64	< -13			
1652.8	V	-58.78	3.78	5.41	2.15	-59.3	< -13			

	SIM 2										
Operate Band	Operate Band: WCDMA Band V Modulation Type: QPSK										
Frequency:	836.6	6 MHz									
Frequency	Ant.	P _{Mea}	P _{cl} G _a Antenna Gain Correction ERP Limit								
(MHz)	Polar.	(dBm)	(dB)	(dB)	(dB)	(dBm)	(dBm)				
1673.2	Н	-59.97	3.81 5.36 2.15 -60.57 < -13								
1673.2	V	-58.59	3.81	5.36	2.15	-59.19	< -13				

SIM 2										
Operate Band	Operate Band: WCDMA Band V Modulation Type: QPSK									
Frequency: 846.6 MHz										
Frequency	Ant.	P _{Mea}	P _{cl}	G _a Antenna Gain	Correction	ERP	Limit			
(MHz)	Polar.	(dBm)	(dB)	(dB)	(dB)	(dBm)	(dBm)			
1692.8	Н	-59.37	3.84	5.28	2.15	-60.08	< -13			
1692.8	V	-59.6	3.84	5.28	2.15	-60.31	< -13			







4.8. Conducted Spurious Emission


■ Limit

Part 24.238 and Part 22.917 specify that the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10 log(P) dB.

■ Setup










■ Test Procedure

- 1. The EUT was connected to Spectrum Analyzer and Base Station via Power Divider.
- 2. The middle channel for the highest RF power within the transmitting frequency was measured.
- 3. The conducted spurious emission for the whole frequency range was taken.





■ Test Graphs

