

FCC Radio Test Report

FCC ID: 2AIIJ-U9

Original Grant

Report No. : TB-FCC148059
Applicant : Shenzhen SAME SONG Electronics Co.,Ltd.
Equipment Under Test (EUT)
EUT Name : Second-generation Smart Watch
Model No. : U9
Series Model No. : U8
Brand Name : N/A
Receipt Date : 2016-05-10
Test Date : 2016-05-11 to 2016-05-25
Issue Date : 2016-05-26
Standards : FCC Part 15: 2015, Subpart C(15.247)
Test Method : ANSI C63.10: 2013
Conclusions : **PASS**

In the configuration tested, the EUT complied with the standards specified above,
The EUT technically complies with the FCC requirements

Test/Witness Engineer :

WANG SU

Approved& Authorized :

Longhai



This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in the report.

Contents

CONTENTS.....	2
1. GENERAL INFORMATION ABOUT EUT	4
1.1 Client Information.....	4
1.2 General Description of EUT (Equipment Under Test)	4
1.3 Block Diagram Showing the Configuration of System Tested.....	5
1.4 Description of Support Units	6
1.5 Description of Test Mode.....	6
1.6 Description of Test Software Setting	7
1.7 Measurement Uncertainty	7
1.8 Test Facility.....	8
2. TEST SUMMARY.....	9
3. TEST EQUIPMENT.....	10
4. CONDUCTED EMISSION TEST	11
4.1 Test Standard and Limit.....	11
4.2 Test Setup.....	11
4.3 Test Procedure.....	11
4.4 EUT Operating Mode	12
4.5 Test Data.....	12
5. RADIATED EMISSION TEST	17
5.1 Test Standard and Limit.....	17
5.2 Test Setup.....	18
5.3 Test Procedure.....	19
5.4 EUT Operating Condition	19
6. RESTRICTED BANDS REQUIREMENT	38
6.1 Test Standard and Limit.....	38
6.2 Test Setup.....	38
6.3 Test Procedure.....	38
6.4 EUT Operating Condition	39
6.4 Test Data.....	39
7. NUMBER OF HOPPING CHANNEL	52
7.1 Test Standard and Limit.....	52
7.2 Test Setup.....	52
7.3 Test Procedure.....	52
7.4 EUT Operating Condition	52
7.5 Test Data.....	52
8. AVERAGE TIME OF OCCUPANCY.....	54
8.1 Test Standard and Limit.....	54
8.2 Test Setup.....	54
8.3 Test Procedure.....	54

8.4 EUT Operating Condition	54
8.5 Test Data.....	55
9. CHANNEL SEPARATION AND BANDWIDTH TEST	73
9.1 Test Standard and Limit.....	73
9.2 Test Setup.....	73
9.3 Test Procedure.....	73
9.4 EUT Operating Condition	73
9.5 Test Data.....	74
10. PEAK OUTPUT POWER TEST.....	86
10.1 Test Standard and Limit	86
10.2 Test Setup.....	86
10.3 Test Procedure.....	86
10.4 EUT Operating Condition	86
10.5 Test Data.....	87
11. ANTENNA REQUIREMENT.....	93
11.1 Standard Requirement.....	93
11.2 Antenna Connected Construction	93

1. General Information about EUT

1.1 Client Information

Applicant : Shenzhen SAME SONG Electronics Co.,Ltd.
Address : 13F, Nantongbang High-Tech Industrial Park Building B, Dabutou Road, Guanlan Street,Longhua New District, Shenzhen, China
Manufacturer : Shenzhen SAME SONG Electronics Co.,Ltd.
Address : 13F, Nantongbang High-Tech Industrial Park Building B, Dabutou Road, Guanlan Street,Longhua New District, Shenzhen, China

1.2 General Description of EUT (Equipment Under Test)

EUT Name	:	Second-generation Smart Watch	
Models No.	:	U9 ,U8	
Model Difference	:	All these models are identical in the same PCB, layout and electrical circuit, the only difference is model name for commercial.	
Product Description	:	Operation Frequency: Bluetooth : 2402~2480MHz GSM 850: 824.20MHz-848.80MHz See Note 1 PCS1900: 1850.20MHz-1909.80MHz See Note 1	
		Number of Channel:	Bluetooth:79 Channels See Note 2
		Max Peak Output Power:	Bluetooth: 7.978 dBm(GFSK)
		Antenna Gain:	0 dBi Integral Antenna
		Modulation Type:	GFSK 1Mbps(1 Mbps) π /4-DQPSK(2 Mbps) 8-DPSK(3 Mbps)
Power Supply	:	DC Voltage supplied from Host System by USB cable. DC power by Li-ion Battery.	
Power Rating	:	DC 5.0V by USB cable. DC 3.7V by 230mAh Li-ion Battery.	
Connecting I/O Port(S)	:	Please refer to the User's Manual	

Note:

- (1) For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual. The EUT has also been tested and complied the FCC 2&22&24 for GSM850, PCS1900 , and recorded in the separate test report.
- (2) Channel List:


Bluetooth Channel List					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)

00	2402	27	2429	54	2456
01	2403	28	2430	55	2457
02	2404	29	2431	56	2458
03	2405	30	2432	57	2459
04	2406	31	2433	58	2460
05	2407	32	2434	59	2461
06	2408	33	2435	60	2462
07	2409	34	2436	61	2463
08	2410	35	2437	62	2464
09	2411	36	2438	63	2465
10	2412	37	2439	64	2466
11	2413	38	2440	65	2467
12	2414	39	2441	66	2468
13	2415	40	2442	67	2469
14	2416	41	2443	68	2470
15	2417	42	2444	69	2471
16	2418	43	2445	70	2472
17	2419	44	2446	71	2473
18	2420	45	2447	72	2474
19	2421	46	2448	73	2475
20	2422	47	2449	74	2476
21	2423	48	2450	75	2477
22	2424	49	2451	76	2478
23	2425	50	2452	77	2479
24	2426	51	2453	78	2480
25	2427	52	2454		
26	2428	53	2455		

(3) The Antenna information about the equipment is provided by the applicant.

1.3 Block Diagram Showing the Configuration of System Tested

TX Mode



1.4 Description of Support Units

The EUT has been test as an independent unit.

1.5 Description of Test Mode

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned follow was evaluated respectively.

For Conducted Test	
Final Test Mode	Description
Mode 1	USB Charging with TX GFSK Mode

For Radiated Test	
Final Test Mode	Description
Mode 1	USB Charging with TX GFSK Mode
Mode 2	TX Mode(GFSK) Channel 00/39/78
Mode 3	TX Mode($\pi/4$ -DQPSK) Channel 00/39/78
Mode 4	TX Mode(8-DPSK) Channel 00/39/78
Mode 5	Hopping Mode(GFSK)
Mode 6	Hopping Mode($\pi/4$ -DQPSK)
Mode 7	Hopping Mode(8-DPSK)

Note:

- (1) For all test, we have verified the construction and function in typical operation. And all the test modes were carried out with the EUT in transmitting operation in maximum power with all kinds of data rate. We have pretested all the test mode above.
According to ANSI C63.10 standards, the measurements are performed at the highest, middle, lowest available channels, and the worst case data rate as follows:
TX Mode: GFSK (1 Mbps)
TX Mode: $\pi/4$ -DQPSK (2 Mbps)
TX Mode: 8-DPSK (3Mbps)
- (2) The EUT is considered a portable unit; it was pre-tested on the positioned of each 3 axis, X-plane, Y-plane and Z-plane. The worst case was found positioned on X-plane as the normal use. Therefore only the test data of this X-plane was used for radiated emission measurement test.

1.6 Description of Test Software Setting

During testing channel& Power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters of Bluetooth mode.

Test Software Version	*#83646633#		
Frequency	2402 MHz	2441MHz	2480 MHz
GFSK	DEF	DEF	DEF
$\pi/4$ -DQPSK	DEF	DEF	DEF
8-DPSK	DEF	DEF	DEF

1.7 Measurement Uncertainty

The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

Test Item	Parameters	Expanded Uncertainty (U_{Lab})
Conducted Emission	Level Accuracy: 9kHz~150kHz 150kHz to 30MHz	± 3.42 dB ± 3.42 dB
Radiated Emission	Level Accuracy: 9kHz to 30 MHz	± 4.60 dB
Radiated Emission	Level Accuracy: 30MHz to 1000 MHz	± 4.40 dB
Radiated Emission	Level Accuracy: Above 1000MHz	± 4.20 dB

1.8 Test Facility

The testing report were performed by the Shenzhen Toby Technology Co., Ltd., in their facilities located at 1A/F., Bldg.6, Yusheng Industrial Zone, The National Road No.107 Xixiang Section 467, Xixiang, Bao'an, Shenzhen, Guangdong, China. At the time of testing, the following bodies accredited the Laboratory:

CNAS (L5813)

The Laboratory has been accredited by CNAS to ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories for the competence in the field of testing. And the Registration No.: CNAS L5813.

FCC List No.: (811562)

The Laboratory is listed in the United States of American Federal Communications Commission (FCC), and the registration number is 811562.

IC Registration No.: (11950A-1)

The Laboratory has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing. The site registration: Site# 11950A-1.

2. Test Summary

FCC Part 15 Subpart C(15.247)/ RSS 247 Issue 1				
Standard Section		Test Item	Judgment	Remark
FCC	IC			
15.203		Antenna Requirement	PASS	N/A
15.207	RSS-GEN 7.2.2	Conducted Emission	PASS	N/A
15.205	RSS-Gen 7.2.3	Restricted Bands	PASS	N/A
15.247(a)(1)	RSS 247 5.1 (2)	Hopping Channel Separation	PASS	N/A
15.247(a)(1)	RSS 247 5.1 (4)	Dwell Time	PASS	N/A
15.247(b)(1)	RSS 247 5.4 (2)	Peak Output Power	PASS	N/A
15.247(b)(1)	RSS 247 5.1 (4)	Number of Hopping Frequency	PASS	N/A
15.247(c)	RSS 247 5.5	Radiated Spurious Emission	PASS	N/A
15.247(a)	RSS 247 5.1 (1)	99% Occupied Bandwidth & 20dB Bandwidth	PASS	99%OBW GFSK:862.3342kHz π /4-DQPSK: 1075.90kHz 8-DPSK: 1104.80KHz
Note: N/A is an abbreviation for Not Applicable.				

3. Test Equipment

Conducted Emission Test					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Due Date
EMI Test Receiver	Rohde & Schwarz	ESCI	100321	Aug. 07, 2015	Aug. 06, 2016
RF Switching Unit	Compliance Direction Systems Inc	RSU-A4	34403	Aug. 07, 2015	Aug. 06, 2016
AMN	SCHWARZBECK	NNBL 8226-2	8226-2/164	Aug. 07, 2015	Aug. 06, 2016
LISN	Rohde & Schwarz	ENV216	101131	Aug. 08, 2015	Aug. 07, 2016
Radiation Emission Test					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Due Date
Spectrum Analyzer	Agilent	E4407B	MY45106456	Aug. 29, 2015	Aug. 28, 2016
EMI Test Receiver	Rohde & Schwarz	ESCI	100010/007	Aug. 07, 2015	Aug. 06, 2016
Bilog Antenna	ETS-LINDGREN	3142E	00117537	Mar. 26, 2016	Mar. 25, 2017
Bilog Antenna	ETS-LINDGREN	3142E	00117542	Mar. 26, 2016	Mar. 25, 2017
Horn Antenna	ETS-LINDGREN	3117	00143207	Mar. 26, 2016	Mar. 25, 2017
Horn Antenna	ETS-LINDGREN	3117	00143209	Mar. 26, 2016	Mar. 25, 2017
Pre-amplifier	Sonoma	310N	185903	Mar. 26, 2016	Mar. 25, 2017
Pre-amplifier	HP	8447B	3008A00849	Mar. 26, 2016	Mar. 25, 2017
Cable	HUBER+SUHNER	100	SUCOFLEX	Mar. 26, 2016	Mar. 25, 2017
Positioning Controller	ETS-LINDGREN	2090	N/A	N/A	N/A

4. Conducted Emission Test

4.1 Test Standard and Limit

4.1.1 Test Standard
FCC Part 15.207

4.1.2 Test Limit


Conducted Emission Test Limit

Frequency	Maximum RF Line Voltage (dB μ V)	
	Quasi-peak Level	Average Level
150kHz~500kHz	66 ~ 56 *	56 ~ 46 *
500kHz~5MHz	56	46
5MHz~30MHz	60	50

Notes:

- (1) *Decreasing linearly with logarithm of the frequency.
- (2) The lower limit shall apply at the transition frequencies.
- (3) The limit decrease in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

4.2 Test Setup



4.3 Test Procedure

The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.

Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.

I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.

LISN at least 80 cm from nearest part of EUT chassis

The bandwidth of EMI test receiver is set at 9kHz, and the test frequency band is from 0.15MHz to 30MHz.


4.4 EUT Operating Mode

Please refer to the description of test mode.

4.5 Test Data

Test data please refer the following pages.


EUT:	Second-generation Smart Watch	Model Name :	U9
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60 Hz		
Terminal:	Line		
Test Mode:	USB Charging with TX GFSK Mode 2402 MHz		
Remark:	Only worse case is reported		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector
1		0.1740	37.95	9.97	47.92	64.76	-16.84	QP
2	*	0.1740	37.47	9.97	47.44	54.76	-7.32	AVG
3		0.2128	37.71	10.02	47.73	63.09	-15.36	QP
4		0.2128	34.37	10.02	44.39	53.09	-8.70	AVG
5		0.2779	33.30	10.02	43.32	60.88	-17.56	QP
6		0.2779	27.54	10.02	37.56	50.88	-13.32	AVG
7		0.5540	35.14	10.05	45.19	56.00	-10.81	QP
8		0.5540	27.45	10.05	37.50	46.00	-8.50	AVG
9		0.9580	29.97	10.07	40.04	56.00	-15.96	QP
10		0.9580	20.42	10.07	30.49	46.00	-15.51	AVG
11		8.3180	14.41	10.10	24.51	60.00	-35.49	QP
12		8.3180	9.44	10.10	19.54	50.00	-30.46	AVG

Emission Level= Read Level+ Correct Factor

EUT:	Second-generation Smart Watch	Model Name :	U9
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60 Hz		
Terminal:	Neutral		
Test Mode:	USB Charging with TX GFSK Mode 2402 MHz		
Remark:	Only worse case is reported		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector
1		0.1740	34.50	10.12	44.62	64.76	-20.14	QP
2		0.1740	33.87	10.12	43.99	54.76	-10.77	AVG
3		0.4220	23.78	10.05	33.83	57.41	-23.58	QP
4		0.4220	19.01	10.05	29.06	47.41	-18.35	AVG
5		0.5540	36.11	10.02	46.13	56.00	-9.87	QP
6	*	0.5540	28.41	10.02	38.43	46.00	-7.57	AVG
7		2.1940	27.76	10.06	37.82	56.00	-18.18	QP
8		2.1940	22.39	10.06	32.45	46.00	-13.55	AVG
9		4.7980	25.09	10.06	35.15	56.00	-20.85	QP
10		4.7980	21.34	10.06	31.40	46.00	-14.60	AVG
11		22.8700	24.81	10.06	34.87	60.00	-25.13	QP
12		22.8700	21.26	10.06	31.32	50.00	-18.68	AVG


Emission Level= Read Level+ Correct Factor

EUT:	Second-generation Smart Watch	Model Name :	U9
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 240V/60 Hz		
Terminal:	Line		
Test Mode:	USB Charging with TX GFSK Mode 2402 MHz		
Remark:	Only worse case is reported		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector
		MHz	dBuV	dB	dBuV	dBuV	dB	
1		0.2100	33.78	10.12	43.90	63.20	-19.30	QP
2		0.2100	32.07	10.12	42.19	53.20	-11.01	AVG
3		0.5540	35.97	10.02	45.99	56.00	-10.01	QP
4	*	0.5540	28.39	10.02	38.41	46.00	-7.59	AVG
5		1.5339	28.61	10.11	38.72	56.00	-17.28	QP
6		1.5339	22.43	10.11	32.54	46.00	-13.46	AVG
7		4.1579	27.76	10.06	37.82	56.00	-18.18	QP
8		4.1579	23.07	10.06	33.13	46.00	-12.87	AVG
9		6.5260	29.84	10.06	39.90	60.00	-20.10	QP
10		6.5260	22.08	10.06	32.14	50.00	-17.86	AVG
11		15.8660	31.48	10.06	41.54	60.00	-18.46	QP
12		15.8660	30.62	10.06	40.68	50.00	-9.32	AVG

Emission Level= Read Level+ Correct Factor

EUT:	Second-generation Smart Watch	Model Name :	U9
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 240V/60 Hz		
Terminal:	Neutral		
Test Mode:	USB Charging with TX GFSK Mode 2402 MHz		
Remark:	Only worse case is reported		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector
1		0.1740	37.50	9.97	47.47	64.76	-17.29	QP
2	*	0.1740	36.97	9.97	46.94	54.76	-7.82	AVG
3		0.2100	37.37	10.02	47.39	63.20	-15.81	QP
4		0.2100	34.06	10.02	44.08	53.20	-9.12	AVG
5		0.5540	35.23	10.05	45.28	56.00	-10.72	QP
6		0.5540	27.70	10.05	37.75	46.00	-8.25	AVG
7		2.1700	27.25	10.05	37.30	56.00	-18.70	QP
8		2.1700	21.97	10.05	32.02	46.00	-13.98	AVG
9		5.1820	26.78	9.97	36.75	60.00	-23.25	QP
10		5.1820	21.97	9.97	31.94	50.00	-18.06	AVG
11		15.9940	31.00	10.24	41.24	60.00	-18.76	QP
12		15.9940	28.87	10.24	39.11	50.00	-10.89	AVG

Emission Level= Read Level+ Correct Factor

5. Radiated Emission Test

5.1 Test Standard and Limit

5.1.1 Test Standard

FCC Part 15.209

5.1.2 Test Limit

Radiated Emission Limit (9 kHz~1000MHz)

Frequency (MHz)	Field Strength (microvolt/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3


Radiated Emission Limit (Above 1000MHz)

Frequency (MHz)	Class B (dBuV/m)(at 3m)	
	Peak	Average
Above 1000	74	54


Note:

- (1) The tighter limit applies at the band edges.
- (2) Emission Level (dBuV/m)=20log Emission Level (uV/m)


5.2 Test Setup



Bellow 30MHz Test Setup



Bellow 1000MHz Test Setup



Above 1GHz Test Setup

5.3 Test Procedure

- (1) The measuring distance of 3m shall be used for measurements at frequency up to 1GHz and above 1 GHz. The EUT was placed on a rotating 0.8m high above ground, the table was rotated 360 degrees to determine the position of the highest radiation.
- (2) Measurements at frequency above 1GHz. The EUT was placed on a rotating 1.5m high above the ground. RF absorbers covered the ground plane with a minimum area of 3.0m by 3.0m between the EUT and measurement receiver antenna. The RF absorber shall not exceed 30cm in high above the conducting floor. The table was rotated 360 degrees to determine the position of the highest radiation.
- (3) The Test antenna shall vary between 1m and 4m, Both Horizontal and Vertical antenna are set to make measurement.
- (4) The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- (5) If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit Bellow 1 GHz, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed. But the Peak Value and average value both need to comply with applicable limit above 1 GHz.
- (6) Testing frequency range below 1GHz the measuring instrument use VBW=120 kHz with Quasi-peak detection.
- (7) Testing frequency range above 1GHz the measuring instrument use RBW=1 MHz and VBW=3 MHz with Peak Detector for Peak Values, and use RBW=1 MHz and VBW=10 Hz with Peak Detector for Average Values.
- (8) For the actual test configuration, please see the test setup photo.

5.4 EUT Operating Condition


The Equipment Under Test was set to Continual Transmitting in maximum power in TX mode.

5.5 Test Data

Remark: During testing above 1GHz the measuring instrument use RBW=1 MHz and VBW=3 MHz with Peak Detector for Peak Values, and use RBW=1 MHz and VBW=1 kHz with Peak Detector for Average Values.

Test data please refer the following pages.

EUT:	Second-generation Smart Watch	Model Name :	U9
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Ant. Pol.	Horizontal		
Test Mode:	TX GFSK Mode 2402MHz		
Remark:	Only worse case is reported		




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	*	83.8156	59.55	-23.06	36.49	40.00	-3.51	peak
2	!	233.3487	60.01	-18.91	41.10	46.00	-4.90	peak
3		360.4476	50.07	-14.55	35.52	46.00	-10.48	peak
4		492.4685	44.27	-11.67	32.60	46.00	-13.40	peak
5		699.3046	41.79	-6.89	34.90	46.00	-11.10	peak
6		798.9796	37.67	-6.52	31.15	46.00	-14.85	peak

*:Maximum data x:Over limit !:over margin

Emission Level= Read Level+ Correct Factor

EUT:	Second-generation Smart Watch	Model Name :	U9
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Ant. Pol.	Vertical		
Test Mode:	TX GFSK Mode 2402MHz		
Remark:	Only worse case is reported		




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	*	84.1099	59.95	-23.03	36.92	40.00	-3.08	peak
2	!	191.7450	58.97	-20.81	38.16	43.50	-5.34	peak
3	!	234.1683	59.63	-18.87	40.76	46.00	-5.24	peak
4		360.4476	52.09	-14.55	37.54	46.00	-8.46	peak
5		468.8761	43.99	-11.81	32.18	46.00	-13.82	peak
6		801.7862	38.62	-6.49	32.13	46.00	-13.87	peak

*:Maximum data x:Over limit !:over margin

Emission Level= Read Level+ Correct Factor


EUT:	Second-generation Smart Watch	Model Name :	U9
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Ant. Pol.	Horizontal		
Test Mode:	TX π /4-DQPSK Mode 2402MHz		
Remark:	Only worse case is reported		




No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		71.8319	54.59	-23.56	31.03	40.00	-8.97	peak
2		143.8292	51.78	-21.67	30.11	43.50	-13.39	peak
3	*	222.1698	58.50	-19.43	39.07	46.00	-6.93	peak
4		348.0274	50.52	-14.72	35.80	46.00	-10.20	peak
5		492.4685	44.27	-11.67	32.60	46.00	-13.40	peak
6		699.3046	40.79	-6.89	33.90	46.00	-12.10	peak

*:Maximum data x:Over limit !:over margin

Emission Level= Read Level+ Correct Factor



EUT:	Second-generation Smart Watch	Model Name :	U9
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Ant. Pol.	Horizontal		
Test Mode:	TX 8-DPSK Mode 2402MHz		
Remark:	Only worse case is reported		




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		83.8156	55.05	-23.06	31.99	40.00	-8.01	peak
2	*	233.3487	58.01	-18.91	39.10	46.00	-6.90	peak
3		348.0274	50.52	-14.72	35.80	46.00	-10.20	peak
4		455.9057	45.42	-12.26	33.16	46.00	-12.84	peak
5		699.3046	39.79	-6.89	32.90	46.00	-13.10	peak
6		798.9796	37.67	-6.52	31.15	46.00	-14.85	peak

*:Maximum data x:Over limit !:over margin

Emission Level= Read Level+ Correct Factor

EUT:	Second-generation Smart Watch	Model Name :	U9
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Ant. Pol.	Vertical		
Test Mode:	TX 8-DPSK Mode 2402MHz		
Remark:	Only worse case is reported		




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	*	78.4133	58.21	-23.34	34.87	40.00	-5.13	peak
2		143.8292	49.38	-21.67	27.71	43.50	-15.79	peak
3		167.8240	53.26	-21.04	32.22	43.50	-11.28	peak
4		234.1682	57.13	-18.87	38.26	46.00	-7.74	peak
5		336.0350	51.31	-15.46	35.85	46.00	-10.15	peak
6		744.8659	38.02	-7.09	30.93	46.00	-15.07	peak

*:Maximum data x:Over limit !:over margin

Emission Level= Read Level+ Correct Factor


EUT:	Second-generation Smart Watch	Model Name :	U9
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Ant. Pol.	Horizontal		
Test Mode:	TX GFSK Mode 2402MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	*	4803.678	35.23	13.44	48.67	54.00	-5.33	AVG
2		4804.064	43.92	13.44	57.36	74.00	-16.64	peak

Emission Level= Read Level+ Correct Factor


EUT:	Second-generation Smart Watch	Model Name :	U9
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Ant. Pol.	Vertical		
Test Mode:	TX GFSK Mode 2402MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	*	4804.191	33.99	13.44	47.43	54.00	-6.57	AVG
2		4804.238	43.94	13.44	57.38	74.00	-16.62	peak

Emission Level= Read Level+ Correct Factor


EUT:	Second-generation Smart Watch	Model Name :	U9
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Ant. Pol.	Horizontal		
Test Mode:	TX GFSK Mode 2441MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	*	4882.330	34.08	13.90	47.98	54.00	-6.02	AVG
2		4882.418	42.69	13.90	56.59	74.00	-17.41	peak

Emission Level= Read Level+ Correct Factor


EUT:	Second-generation Smart Watch	Model Name :	U9
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Ant. Pol.	Vertical		
Test Mode:	TX GFSK Mode 2441MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		4881.585	42.49	13.90	56.39	74.00	-17.61	peak
2	*	4882.020	33.97	13.90	47.87	54.00	-6.13	AVG

Emission Level= Read Level+ Correct Factor


EUT:	Second-generation Smart Watch	Model Name :	U9
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Ant. Pol.	Horizontal		
Test Mode:	TX GFSK Mode 2480MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		4960.314	43.34	14.36	57.70	74.00	-16.30	peak
2	*	4960.357	34.27	14.36	48.63	54.00	-5.37	AVG

Emission Level= Read Level+ Correct Factor


EUT:	Second-generation Smart Watch	Model Name :	U9
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Ant. Pol.	Vertical		
Test Mode:	TX GFSK Mode 2480MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	*	4960.129	33.85	14.36	48.21	54.00	-5.79	AVG
2		4960.295	43.33	14.36	57.69	74.00	-16.31	peak

Emission Level= Read Level+ Correct Factor


EUT:	Second-generation Smart Watch	Model Name :	U9
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Ant. Pol.	Horizontal		
Test Mode:	TX 8-DPSK Mode 2402MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	*	4803.551	33.55	13.44	46.99	54.00	-7.01	AVG
2		4804.269	43.29	13.44	56.73	74.00	-17.27	peak

Emission Level= Read Level+ Correct Factor


EUT:	Second-generation Smart Watch	Model Name :	U9
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Ant. Pol.	Vertical		
Test Mode:	TX 8-DPSK Mode 2402MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	*	4804.012	34.15	13.44	47.59	54.00	-6.41	AVG
2		4804.468	43.43	13.44	56.87	74.00	-17.13	peak

Emission Level= Read Level+ Correct Factor


EUT:	Second-generation Smart Watch	Model Name :	U9
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Ant. Pol.	Horizontal		
Test Mode:	TX 8-DPSK Mode 2441MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	*	4882.041	33.13	13.90	47.03	54.00	-6.97	AVG
2		4882.458	42.92	13.90	56.82	74.00	-17.18	peak

Emission Level= Read Level+ Correct Factor


EUT:	Second-generation Smart Watch	Model Name :	U9
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Ant. Pol.	Vertical		
Test Mode:	TX 8-DPSK Mode 2441MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		4881.521	44.44	13.90	58.34	74.00	-15.66	peak
2	*	4882.061	33.64	13.90	47.54	54.00	-6.46	AVG

Emission Level= Read Level+ Correct Factor


EUT:	Second-generation Smart Watch	Model Name :	U9
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Ant. Pol.	Horizontal		
Test Mode:	TX 8-DPSK Mode 2480MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	*	4959.906	33.68	14.36	48.04	54.00	-5.96	AVG
2		4960.265	43.50	14.36	57.86	74.00	-16.14	peak

Emission Level= Read Level+ Correct Factor

EUT:	Second-generation Smart Watch	Model Name :	U9
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Ant. Pol.	Vertical		
Test Mode:	TX 8-DPSK Mode 2480MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	*	4959.831	33.50	14.36	47.86	54.00	-6.14	AVG
2		4960.359	43.57	14.36	57.93	74.00	-16.07	peak

Emission Level= Read Level+ Correct Factor

6. Restricted Bands Requirement

6.1 Test Standard and Limit

6.1.1 Test Standard

FCC Part 15.209


FCC Part 15.205

6.1.2 Test Limit

Restricted Frequency Band (MHz)	Class B (dBUV/m)(at 3m)	
	Peak	Average
2310 ~2390	74	54
2483.5 ~2500	74	54

Note: All restriction bands have been tested, only the worst case is reported.

6.2 Test Setup



6.3 Test Procedure

- (1) The measuring distance of 3m shall be used for measurements at frequency up to 1GHz and above 1 GHz. The EUT was placed on a rotating 0.8m high above ground, the table was rotated 360 degrees to determine the position of the highest radiation.
- (2) Measurements at frequency above 1GHz. The EUT was placed on a rotating 1.5m high above the ground. RF absorbers covered the ground plane with a minimum area of 3.0m by 3.0m between the EUT and measurement receiver antenna. The RF absorber shall not exceed 30cm in high above the conducting floor. The table was rotated 360 degrees to determine the position of the highest radiation.

-
- (3) The Test antenna shall vary between 1m and 4m, Both Horizontal and Vertical antenna are set to make measurement.
 - (4) The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
 - (5) If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit Bellow 1 GHz, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed. But the Peak Value and average value both need to comply with applicable limit above 1 GHz.
 - (6) Testing frequency range below 1GHz the measuring instrument use VBW=120 kHz with Quasi-peak detection.
 - (7) Testing frequency range above 1GHz the measuring instrument use RBW=1 MHz and VBW=3 MHz with Peak Detector for Peak Values, and use RBW=1 MHz and VBW=10 Hz with Peak Detector for Average Values.
 - (8) For the actual test configuration, please see the test setup photo.

6.4 EUT Operating Condition

The Equipment Under Test was set to Continual Transmitting in maximum power.


6.4 Test Data

Remark: During testing above 1GHz the measuring instrument use RBW=1 MHz and VBW=3 MHz with Peak Detector for Peak Values, and use RBW=1 MHz and VBW=1 KHz with Peak Detector for Average Values.

All restriction bands have been tested, only the worst case is reported.

(1) Radiation Test


EUT:	Second-generation Smart Watch	Model Name :	U9
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Ant. Pol.	Horizontal		
Test Mode:	TX GFSK Mode 2402MHz		
Remark:	N/A		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		2390.000	45.36	0.77	46.13	74.00	-27.87	peak
2		2390.000	33.58	0.77	34.35	54.00	-19.65	AVG
3	X	2402.000	88.74	0.82	89.56	Fundamental Frequency		peak
4	*	2402.100	84.19	0.82	85.01	Fundamental Frequency		AVG

Emission Level= Read Level+ Correct Factor


EUT:	Second-generation Smart Watch	Model Name :	U9
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Ant. Pol.	Vertical		
Test Mode:	TX GFSK Mode 2402MHz		
Remark:	N/A		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		2390.000	45.21	0.77	45.98	74.00	-28.02	peak
2		2390.000	33.39	0.77	34.16	54.00	-19.84	AVG
3	X	2402.100	88.52	0.82	89.34	Fundamental Frequency		peak
4	*	2402.100	84.36	0.82	85.18	Fundamental Frequency		AVG

Emission Level= Read Level+ Correct Factor


EUT:	Second-generation Smart Watch	Model Name :	U9
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Ant. Pol.	Horizontal		
Test Mode:	TX GFSK Mode 2480 MHz		
Remark:	N/A		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1	*	2480.000	87.28	1.15	88.43	Fundamental Frequency		AVG
2	X	2480.200	92.09	1.15	93.24	Fundamental Frequency		peak
3		2483.500	62.46	1.17	63.63	74.00	-10.37	peak
4		2483.500	46.45	1.17	47.62	54.00	-6.38	AVG

Emission Level= Read Level+ Correct Factor


EUT:	Second-generation Smart Watch	Model Name :	U9
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Ant. Pol.	Vertical		
Test Mode:	TX GFSK Mode 2480 MHz		
Remark:	N/A		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1	X	2480.000	89.22	1.15	90.37	Fundamental Frequency		peak
2	*	2480.100	84.56	1.15	85.71	Fundamental Frequency		AVG
3		2483.500	59.30	1.17	60.47	74.00	-13.53	peak
4		2483.500	43.92	1.17	45.09	54.00	-8.91	AVG

Emission Level= Read Level+ Correct Factor


EUT:	Second-generation Smart Watch	Model Name :	U9
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Ant. Pol.	Horizontal		
Test Mode:	TX 8-DPSK Mode 2402MHz		
Remark:	N/A		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB Detector
1		2390.000	45.14	0.77	45.91	74.00	-28.09 peak
2		2390.000	33.70	0.77	34.47	54.00	-19.53 AVG
3	X	2401.900	88.31	0.82	89.13	Fundamental Frequency peak	
4	*	2402.000	83.30	0.82	84.12	Fundamental Frequency AVG	

Emission Level= Read Level+ Correct Factor


EUT:	Second-generation Smart Watch	Model Name :	U9
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Ant. Pol.	Vertical		
Test Mode:	TX 8-DPSK Mode 2402MHz		
Remark:	N/A		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		2390.000	43.06	0.77	43.83	74.00	-30.17	peak
2		2390.000	33.38	0.77	34.15	54.00	-19.85	AVG
3	*	2402.200	84.63	0.82	85.45	Fundamental Frequency		AVG
4	X	2402.300	89.52	0.82	90.34	Fundamental Frequency		peak

Emission Level= Read Level+ Correct Factor


EUT:	Second-generation Smart Watch	Model Name :	U9
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Ant. Pol.	Horizontal		
Test Mode:	TX 8-DPSK Mode 2480MHz		
Remark:	N/A		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1	X	2479.900	89.06	1.15	90.21	Fundamental Frequency		peak
2	*	2479.900	84.87	1.15	86.02	Fundamental Frequency		AVG
3		2483.500	59.74	1.17	60.91	74.00	-13.09	peak
4		2483.500	44.41	1.17	45.58	54.00	-8.42	AVG

Emission Level= Read Level+ Correct Factor

EUT:	Second-generation Smart Watch	Model Name :	U9
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Ant. Pol.	Vertical		
Test Mode:	TX 8-DPSK Mode 2480MHz		
Remark:	N/A		





No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	X	2479.900	90.19	1.15	91.34	Fundamental Frequency		peak
2	*	2480.000	86.09	1.15	87.24	Fundamental Frequency		AVG
3		2483.500	61.06	1.17	62.23	74.00	-11.77	peak
4		2483.500	45.39	1.17	46.56	54.00	-7.44	AVG



Emission Level= Read Level+ Correct Factor

(2) Conducted Test



EUT:	Second-generation Smart Watch	Model Name :	U9
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Test Mode:	TX GFSK Mode 2402MHz / 2480 MHz		
Remark:	N/A		





EUT:	Second-generation Smart Watch	Model Name :	U9
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Test Mode:	GFSK Hopping Mode		
Remark:	N/A		



EUT:	Second-generation Smart Watch	Model Name :	U9
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Test Mode:	TX 8-DPSK Mode 2402MHz / 2480 MHz		
Remark:	N/A		



EUT:	Second-generation Smart Watch	Model Name :	U9
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Test Mode:	8-DPSK Hopping Mode		
Remark:	N/A		



7. Number of Hopping Channel

7.1 Test Standard and Limit


6.1.1 Test Standard

FCC Part 15.247 (a)(1)

6.1.2 Test Limit

Section	Test Item	Limit
15.247	Number of Hopping Channel	>15

7.2 Test Setup



7.3 Test Procedure

- (1) The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
- (2) Spectrum Setting: RBW=100 KHz, VBW=100 KHz, Sweep time= Auto.

7.4 EUT Operating Condition

The EUT was set to the Hopping Mode by the Customer.

7.5 Test Data

EUT:	Second-generation Smart Watch	Model Name :	U9
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Test Mode:	Hopping Mode (GFSK/8-DPSK)		
Frequency Range	Quantity of Hopping Channel	Limit	
2402MHz~2480MHz	79	>15	
	79		

GFSK Mode

Start 2.4 GHz		#Res BW 100 kHz		#VBW 100 kHz	Stop 2.483 GHz	Sweep 10.76 ms (401 pts)
Marker	Trace	Type	X Axis	Amplitude		
1	(1)	Freq	2.40188 GHz	7.621 dBm		
2	(1)	Freq	2.47995 GHz	6.625 dBm		

8-DPSK Mode

Start 2.4 GHz		#Res BW 100 kHz		#VBW 100 kHz	Stop 2.483 GHz	Sweep 10.76 ms (401 pts)
Marker	Trace	Type	X Axis	Amplitude		
1	(1)	Freq	2.40188 GHz	4.29 dBm		
2	(1)	Freq	2.48016 GHz	4.404 dBm		

8. Average Time of Occupancy

8.1 Test Standard and Limit


8.1.1 Test Standard

FCC Part 15.247 (a)(1)

8.1.2 Test Limit

Section	Test Item	Limit
15.247(a)(1)/ RSS-210 Annex 8(A8.1d)	Average Time of Occupancy	0.4 sec

8.2 Test Setup



8.3 Test Procedure

- (1) The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
- (2) Spectrum Setting: RBW=1MHz, VBW=1MHz.
- (3) Use video trigger with the trigger level set to enable triggering only on full pulses.
- (4) Sweep Time is more than once pulse time.
- (5) Set the center frequency on any frequency would be measure and set the frequency span to zero.
- (6) Measure the maximum time duration of one single pulse.
- (7) Set the EUT for packet transmitting.
- (8) Measure the maximum time duration of one single pulse.

8.4 EUT Operating Condition

The EUT was set to the Hopping Mode by the Customer.

8.5 Test Data

EUT:	Second-generation Smart Watch		Model Name :	U9	
Temperature:	25 °C		Relative Humidity:	55%	
Test Voltage:	DC 3.7V				
Test Mode:	Hopping Mode (GFSK DH1)				
Channel (MHz)	Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result
2402	0.410	131.20	31.60	400	PASS
2441	0.410	131.20			
2480	0.410	131.20			
GFSK Hopping Mode DH1					
2402 MHz					

Agilent

Ref 15 dBm

#Atten 25 dB

Mkr1 Δ 410 μs
-2.853 dB

Peak

Log

10

dB/

Marker Δ

410.000000 μs

-2.853 dB

W1 S2

S3 FS

AA

Center 2.402 GHz


Res BW 1 MHz

#VBW 1 MHz


Sweep 4 ms (401 pts)

Span 0 Hz

GFSK Hopping Mode DH1
2441 MHz



GFSK Hopping Mode DH1
2480 MHz



EUT:	Second-generation Smart Watch		Model Name :	U9	
Temperature:	25 °C		Relative Humidity:	55%	
Test Voltage:	DC 3.7V				
Test Mode:	Hopping Mode (GFSK DH3)				
Channel (MHz)	Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result
2402	1.700	272.00	31.60	400	PASS
2441	1.700	272.00			
2480	1.700	272.00			

GFSK Hopping Mode DH3

2402 MHz

Agilent

Ref 15 dBm

Peak Log 10 dB/

Marker Δ 1.70000000 ms -0.784 dB

W1 S2 S3 FS AA

Center 2.402 GHz Res BW 1 MHz

#Atten 25 dB


Mkr1 Δ 1.7 ms -0.784 dB

#VBW 1 MHz


Sweep 8 ms (401 pts)

Span 0 Hz

GFSK Hopping Mode DH3
 2441 MHz




GFSK Hopping Mode DH3
 2480 MHz




EUT:	Second-generation Smart Watch		Model Name :	U9	
Temperature:	25 °C		Relative Humidity:	55%	
Test Voltage:	DC 3.7V				
Test Mode:	Hopping Mode (GFSK DH5)				
Channel (MHz)	Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result
2402	3.000	320.00	31.60	400	PASS
2441	3.000	320.00			
2480	3.000	320.00			
GFSK Hopping Mode DH5					
2402 MHz					
<div><div><div><div><div>Agilent</div><div>Ref 15 dBm</div><div>Peak</div><div>Log</div><div>10 dB/</div></div><div><div>#Atten 25 dB</div><div>Marker Δ</div><div>3.000000000 ms</div><div>0.835 dB</div></div><div><div>Mkr1 Δ</div><div>3 ms</div><div>0.835 dB</div></div></div><div><div>W1 S2</div><div>S3 FS</div><div>AA</div></div><div><div>Center 2.402 GHz</div><div>Res BW 1 MHz</div><div>#VBW 1 MHz</div><div>Span 0 Hz</div><div>Sweep 12 ms (401 pts)</div></div></div></div>					


GFSK Hopping Mode DH5
 2441 MHz




GFSK Hopping Mode DH5
 2480 MHz



π /4-DQPSK Hopping Mode DH1
 2441 MHz



π /4-DQPSK Hopping Mode DH1
 2480 MHz



EUT:	Second-generation Smart Watch		Model Name :	U9	
Temperature:	25 °C		Relative Humidity:	55%	
Test Voltage:	DC 3.7V				
Test Mode:	Hopping Mode (π /4-DQPSK DH3)				
Channel (MHz)	Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result
2402	1.700	272.00	31.60	400	PASS
2441	1.700	272.00			
2480	1.700	272.00			
π /4-DQPSK Hopping Mode DH3					
2402 MHz					

Agilent

Ref 15 dBm

#Atten 25 dB

Mkr1 Δ 1.7 ms
0.155 dB

Peak Log 10 dB/

Marker Δ
1.700000000 ms
0.155 dB

W1 S2
S3 FS
AA


Center 2.402 GHz
Res BW 1 MHz

#VBW 1 MHz


Sweep 8 ms (401 pts)

Span 0 Hz

π /4-DQPSK Hopping Mode DH3
 2441 MHz



π /4-DQPSK Hopping Mode DH3
 2480 MHz



EUT:	Second-generation Smart Watch		Model Name :	U9	
Temperature:	25 °C		Relative Humidity:	55%	
Test Voltage:	DC 3.7V				
Test Mode:	Hopping Mode (π /4-DQPSK DH5)				
Channel (MHz)	Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result
2402	3.000	320.00	31.60	400	PASS
2441	3.000	320.00			
2480	3.000	320.00			
π /4-DQPSK Hopping Mode DH5					
2402 MHz					

Agilent

Ref 15 dBm

#Atten 25 dB

Mkr1 Δ 3 ms
-1.021 dB

Peak

Log

10

dB/

Marker Δ

3.000000000 ms

-1.021 dB

W1 S2

S3 FS

AA

Center 2.402 GHz


Res BW 1 MHz

#VBW 1 MHz


Span 0 Hz

Sweep 12 ms (401 pts)

$\pi/4$ -DQPSK Hopping Mode DH5
 2441 MHz



$\pi/4$ -DQPSK Hopping Mode DH5
 2480 MHz



EUT:	Second-generation Smart Watch		Model Name :	U9	
Temperature:	25 °C		Relative Humidity:	55%	
Test Voltage:	DC 3.7V				
Test Mode:	Hopping Mode (8-DPSK DH1)				
Channel (MHz)	Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result
2402	0.410	131.20	31.60	400	PASS
2441	0.410	131.20			
2480	0.410	131.20			
8-DPSK Hopping Mode DH1					
2402 MHz					

Agilent

Ref 15 dBm

Peak

Log

10

dB/

Marker Δ

410.0000000 μs

0.055 dB

W1 S2

S3 FS

AA

Center 2.402 GHz


Res BW 1 MHz

#VBW 1 MHz


Span 0 Hz

Sweep 4 ms (401 pts)

8-DPSK Hopping Mode DH1
 2441 MHz



8-DPSK Hopping Mode DH1
 2480 MHz



EUT:	Second-generation Smart Watch		Model Name :	U9	
Temperature:	25 °C		Relative Humidity:	55%	
Test Voltage:	DC 3.7V				
Test Mode:	Hopping Mode (8-DPSK DH3)				
Channel (MHz)	Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result
2402	1.700	272.00	31.60	400	PASS
2441	1.700	272.00			
2480	1.700	272.00			
8-DPSK Hopping Mode DH3					
2402 MHz					

Agilent

Ref 15 dBm

#Atten 25 dB

Mkr1 Δ 1.7 ms
-0.05 dB

Peak

Log

10

dB/

Marker Δ

1.700000000 ms

-0.05 dB

W1 S2

S3 FS

AA

Center 2.402 GHz


Res BW 1 MHz

#VBW 1 MHz


Sweep 8 ms (401 pts)

Span 0 Hz

8-DPSK Hopping Mode DH3
 2441 MHz



8-DPSK Hopping Mode DH3
 2480 MHz



EUT:	Second-generation Smart Watch		Model Name :	U9	
Temperature:	25 °C		Relative Humidity:	55%	
Test Voltage:	DC 3.7V				
Test Mode:	Hopping Mode (8-DPSK DH5)				
Channel (MHz)	Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result
2402	3.000	320.00	31.60	400	PASS
2441	3.000	320.00			
2480	3.000	320.00			
8-DPSK Hopping Mode DH5					
2402 MHz					

Agilent

Ref 15 dBm

#Atten 25 dB

Mkr1 Δ 3 ms
-0.558 dB

Peak

Log

10

dB/

Marker Δ

3.000000000 ms

-0.558 dB

W1 S2

S3 FS

AA

Center 2.402 GHz


Res BW 1 MHz

#VBW 1 MHz


Sweep 12 ms (401 pts)

Span 0 Hz

8-DPSK Hopping Mode DH5
 2441 MHz



8-DPSK Hopping Mode DH5
 2480 MHz



9. Channel Separation and Bandwidth Test


9.1 Test Standard and Limit

9.1.1 Test Standard
FCC Part 15.247

9.1.2 Test Limit

Test Item	Limit	Frequency Range(MHz)
Bandwidth	≤ 1 MHz (20dB bandwidth)	2400~2483.5
Channel Separation	>25 KHz or $>$ two-thirds of the 20 dB bandwidth Which is greater	2400~2483.5

9.2 Test Setup



9.3 Test Procedure

- (1) The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
- (2) Spectrum Setting:
Channel Separation: RBW=30 kHz, VBW=100 kHz.
Bandwidth: RBW=30 kHz, VBW=100 kHz.
- (3) The bandwidth is measured at an amplitude level reduced 20dB from the reference level. The reference level is the level of the highest amplitude signal observed from the transmitter at the fundamental frequency. Once the reference level is established, the equipment is conditioned with typical modulating signal to produce the worst –case (i.e the widest) bandwidth.
- (4) Measure the channel separation the spectrum analyzer was set to Resolution Bandwidth:30 kHz, and Video Bandwidth:100 kHz. Sweep Time set auto.


9.4 EUT Operating Condition

The EUT was set to the Hopping Mode for Channel Separation Test and continuously transmitting for the Bandwidth Test.


9.5 Test Data

EUT:	Second-generation Smart Watch	Model Name :	U9
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Test Mode:	TX Mode (GFSK)		
Channel frequency (MHz)	99% OBW (kHz)	20dB Bandwidth (kHz)	20dB Bandwidth *2/3 (kHz)
2402	856.5948	838.814	
2441	859.0334	843.202	
2480	862.3342	852.587	
GFSK TX Mode			
2402 MHz			
<div> <div> <div>Agilent</div> <div> <div>Ref 15 dBm</div> <div>#Peak</div> <div>Log</div> <div>10</div> <div>dB/</div> </div> <div> <div>#Atten 25 dB</div> <div>Center</div> <div>2.402000000 GHz</div> </div> </div> <div> <div>Center 2.402 GHz</div> <div>#Res BW 30 kHz</div> <div>#VBW 100 kHz</div> <div>Sweep 5 ms (401 pts)</div> <div>Span 3 MHz</div> </div> <div> <div>Occupied Bandwidth</div> <div>856.5948 kHz</div> <div>Occ BW % Pwr</div> <div>99.00 %</div> <div>x dB</div> <div>-20.00 dB</div> </div> <div> <div>Transmit Freq Error</div> <div>-4.436 kHz</div> <div>x dB Bandwidth</div> <div>838.814 kHz</div> </div> </div>			

GFSK TX Mode
2441 MHz




GFSK TX Mode
2480 MHz




EUT:	Second-generation Smart Watch	Model Name :	U9
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Test Mode:	TX Mode (π /4-DQPSK)		
Channel frequency (MHz)	99% OBW (kHz)	20dB Bandwidth (kHz)	20dB Bandwidth *2/3 (kHz)
2402	1075.10	1133.00	755.33
2441	1075.90	1135.00	756.67
2480	1018.15	1141.00	760.67
π /4-DQPSK TX Mode			
2402 MHz			
<div> <div> <div>Agilent</div> <div> <div>Ref 15 dBm</div> <div>#Peak</div> <div>Log 10 dB/</div> </div> <div> <div>#Atten 25 dB</div> <div>Center 2.402000000 GHz</div> </div> </div> <div> <div>Center 2.402 GHz</div> <div>#Res BW 30 kHz</div> <div>#VBW 100 kHz</div> <div>Span 3 MHz</div> <div>Sweep 5 ms (401 pts)</div> <div>Occupied Bandwidth</div> <div>1.0751 MHz</div> <div>Occ BW % Pwr</div> <div>99.00 %</div> <div>x dB</div> <div>-20.00 dB</div> <div>Transmit Freq Error</div> <div>-7.742 kHz</div> <div>x dB Bandwidth</div> <div>1.133 MHz</div> </div> </div>			

2441 MHz




2480 MHz





EUT:	Second-generation Smart Watch	Model Name :	U9
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Test Mode:	TX Mode (8-DPSK)		
Channel frequency (MHz)	99% OBW (kHz)	20dB Bandwidth (kHz)	20dB Bandwidth *2/3 (kHz)
2402	1104.80	1171.00	780.67
2441	1104.10	1173.00	782.00
2480	1079.20	1136.00	757.33
8-DPSK TX Mode			
2402 MHz			
<div> <div> <div>Agilent</div> <div> <div>Ref 15 dBm</div> <div>#Peak</div> <div>Log</div> <div>10</div> <div>dB/</div> <div>Offst</div> <div>1</div> <div>dB</div> </div> <div> <div>Center</div> <div>2.402000000 GHz</div> </div> </div> <div> <div>#Atten 25 dB</div> </div> </div> <div> <div>Center 2.402 GHz</div> <div>#Res BW 30 kHz</div> <div>#VBW 100 kHz</div> <div>Span 3 MHz</div> <div>Sweep 5 ms (401 pts)</div> <div>Occupied Bandwidth</div> <div>1.1048 MHz</div> <div>Occ BW % Pwr</div> <div>99.00 %</div> <div>x dB</div> <div>-20.00 dB</div> <div>Transmit Freq Error</div> <div>-8.296 kHz</div> <div>x dB Bandwidth</div> <div>1.171 MHz</div> </div>			

8-DPSK TX Mode
 2441 MHz




8-DPSK TX Mode
 2480 MHz







GFSK Hopping Mode
2441 MHz




GFSK Hopping Mode
2480 MHz







π /4-DQPSK Hopping Mode
 2441 MHz




π /4-DQPSK Hopping Mode
 2480 MHz






8-DPSK Hopping Mode

2441 MHz



8-DPSK Hopping Mode

2480 MHz



10. Peak Output Power Test

10.1 Test Standard and Limit


10.1.1 Test Standard

FCC Part 15.247 (b) (1)

10.1.2 Test Limit

Test Item	Limit	Frequency Range(MHz)
Peak Output Power	Hopping Channels>75 Power<1W(30dBm) Other <125 mW(21dBm)	2400~2483.5

10.2 Test Setup



10.3 Test Procedure

- (1) The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
- (2) Spectrum Setting:
Peak Detector: RBW=1 MHz, VBW=3 MHz for bandwidth less than 1MHz.
RBW=3 MHz, VBW=3 MHz for bandwidth more than 1MHz.

10.4 EUT Operating Condition

The EUT was set to continuously transmitting in the max power during the test.

10.5 Test Data

EUT:	Second-generation Smart Watch	Model Name :	U9
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Test Mode:	TX Mode (GFSK)		
Channel frequency (MHz)	Test Result (dBm)	Limit (dBm)	
2402	7.978	30	
2441	7.749		
2480	7.458		
GFSK TX Mode			
2402 MHz			

Agilent

Ref 15 dBm

#Atten 25 dB

Mkr1 2.4020300 GHz
7.978 dBm

Peak Log 10 dB/

Marker
2.40203000 GHz
7.978 dBm

M1 S2
S3 FC
AA


Center 2.402 GHz

#Res BW 1 MHz


#VBW 3 MHz

Span 3 MHz
Sweep 5 ms (401 pts)

GFSK TX Mode
2441 MHz



GFSK TX Mode
2480 MHz



EUT:	Second-generation Smart Watch	Model Name :	U9
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Test Mode:	TX Mode (π /4-DQPSK)		
Channel frequency (MHz)	Test Result (dBm)	Limit (dBm)	
2402	6.715	21	
2441	6.506		
2480	6.245		
π /4-DQPSK TX Mode			
2402 MHz			

Agilent

Ref 15 dBm

Peak

Log

10

dB/

Mkr1 2.4019750 GHz

6.715 dBm

Marker

2.401975000 GHz

6.715 dBm

M1 S2

S3 FC

AA

Center 2.402 GHz


#Res BW 3 MHz

#VBW 3 MHz


Span 5 MHz

Sweep 5 ms (401 pts)

π /4-DQPSK TX Mode
2441 MHz



π /4-DQPSK TX Mode
2480 MHz



EUT:	Second-generation Smart Watch	Model Name :	U9
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Test Mode:	TX Mode (8-DPSK)		
Channel frequency (MHz)	Test Result (dBm)	Limit (dBm)	
2402	6.715	21	
2441	6.518		
2480	6.242		
8-DPSK TX Mode			
2402 MHz			

Agilent

Ref 15 dBm

Peak

Log

10

dB/

Mkr1 2.4021250 GHz

6.715 dBm

#Atten 25 dB

Marker

2.402125000 GHz

6.715 dBm

M1 S2

S3 FC

AA

Center 2.402 GHz


#Res BW 3 MHz

#VBW 3 MHz


Span 5 MHz

Sweep 5 ms (401 pts)

8-DPSK TX Mode
2441 MHz



8-DPSK TX Mode
2480 MHz



11. Antenna Requirement

11.1 Standard Requirement

11.1.1 Standard

FCC Part 15.203

11.1.2 Requirement

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

11.2 Antenna Connected Construction

The directional gains of the antenna used for transmitting is 0 dBi, and the antenna connector is de-signed with permanent attachment and no consideration of replacement. Please see the EUT photo for details.

The EUT antenna is a Integral antenna. It complies with the standard requirement.

Antenna Type
<input checked="" type="checkbox"/> Permanent attached antenna
<input type="checkbox"/> Unique connector antenna
<input type="checkbox"/> Professional installation antenna