



Shenzhen CTL Testing Technology Co., Ltd.  
Tel: +86-755-89486194 Fax: +86-755-26636041

# TEST REPORT

## FCC PART 15.249

Report Reference No. ....: CTL1605041550-WF

Compiled by:  
( position+printed name+signature)

Jacky Chen  
(File administrators)

*Jacky Chen*

Tested by:  
( position+printed name+signature)

Allen Wang  
(Test Engineer)

*Allen Wang*

Approved by:  
( position+printed name+signature)

Tracy Qi  
(Manager)

*Tracy Qi*

Product Name.....: iWiton navigator for gloves

Model/Type reference .....: ZYXJ.1.1.1

List Model(s).....: N/A

Trade Mark.....: iWiton

FCC ID.....: 2AIM4-ZYX

Applicant's name.....: Gamut(Guangzhou)System Service Co.,LTD

Address of applicant.....: Room 608, Jinda Building, No.12, Dadao Road, Yuexiu District, Guangzhou, China

Test Firm.....: Shenzhen CTL Testing Technology Co., Ltd.

Address of Test Firm.....: Floor 1-A, Baisha Technology Park, No.3011, Shahe Xi Road, Nanshan District, Shenzhen, China 518055

Test specification.....:

Standard.....: FCC Part 15.249: Operation within the bands 920-928 MHz, 2400-2483.5 MHz, 5725-5850 MHz and 24.0 - 24.25 GHz.

TRF Originator.....: Shenzhen CTL Testing Technology Co., Ltd.

Master TRF.....: Dated 2011-01

Date of Receipt.....: May 05, 2016

Date of Test Date.....: May 06, 2016 –May 29, 2016

Data of Issue.....: May 30, 2016

Result.....: Pass

**Shenzhen CTL Testing Technology Co., Ltd. All rights reserved.**

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen CTL Testing Technology Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen CTL Testing Technology Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

# TEST REPORT

<b>Test Report No. :</b> CTL1605041550-WF	May 30, 2016 Date of issue
---	-------------------------------

Equipment under Test : iWiton navigator for gloves

Model /Type : ZYXJ.1.1.1

Listed Models : N/A

**Applicant** : Gamut(Guangzhou)System Service Co.,LTD

Address : Room 608, Jinda Building, No.12, Dadao Road, Yuexiu District, Guangzhou, China

**Manufacturer** : Gamut(Guangzhou)System Service Co.,LTD

Address : Room 608, Jinda Building, No.12, Dadao Road, Yuexiu District, Guangzhou, China

<b>Test result</b>	<b>Pass *</b>
--------------------	---------------

\* In the configuration tested, the EUT complied with the standards specified page 5.

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.


**\*\* Modified History \*\***

Revision	Description	Issued Data	Report No.	Remark
Version 1.0	Initial Test Report Release	2016-05-30	CTL1605041550-WF	Tracy Qi



**Table of Contents****Page**

<b>1. SUMMARY.....</b>	<b>5</b>
1.1. TEST STANDARDS.....	5
1.2. TEST DESCRIPTION.....	5
1.3. TEST FACILITY .....	6
1.4. STATEMENT OF THE MEASUREMENT UNCERTAINTY.....	6
<b>2. GENERAL INFORMATION.....</b>	<b>7</b>
2.1. ENVIRONMENTAL CONDITIONS .....	7
2.2. GENERAL DESCRIPTION OF EUT .....	7
2.3. DESCRIPTION OF TEST MODES AND TEST FREQUENCY.....	8
2.4. EQUIPMENTS USED DURING THE TEST .....	9
2.5. RELATED SUBMITTAL(S) / GRANT(S).....	9
2.6. MODIFICATIONS.....	9
<b>3. TEST CONDITIONS AND RESULTS .....</b>	<b>10</b>
3.1. CONDUCTED EMISSIONS TEST .....	10
3.2. RADIATED EMISSIONS AND BAND EDGE .....	13
3.3. OCCUPIED BANDWIDTH MEASUREMENT.....	19
3.4. ANTENNA REQUIREMENT.....	23
<b>4. TEST SETUP PHOTOS OF THE EUT .....</b>	<b>25</b>
<b>5. EXTERNAL AND INTERNAL PHOTOS OF THE EUT .....</b>	<b>26</b>



# 1. SUMMARY

## 1.1. TEST STANDARDS

The tests were performed according to following standards:

**FCC Rules Part 15.249:** Operation within the bands 902 - 928 MHz, 2400 - 2483.5 MHz, 5725 - 5875 MHz, and 24.0 - 24.25 GHz.

**ANSI C63.10:2013 :** American National Standard for Testing Unlicensed Wireless Devices

**ANSI C63.4: 2014:** –American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40GHz  
Range of 9 kHz to 40GHz

## 1.2. Test Description

FCC PART 15.249		
FCC Part 15.249(a)	Field Strength of Fundamental	PASS
FCC Part 15.209	Spurious Emission	PASS
FCC Part 15.209	Band edge	PASS
FCC Part 15.215(c)	20dB bandwidth	PASS
FCC Part 15.207	Conducted Emission	PASS
FCC Part 15.203	Antenna Requirement	PASS



### 1.3. Test Facility

#### 1.3.1 Address of the test laboratory

Shenzhen CTL Testing Technology Co., Ltd.

Floor 1-A, Baisha Technology Park, No. 3011, Shahexi Road, Nanshan, Shenzhen 518055 China

There is one 3m semi-anechoic chamber and two line conducted labs for final test. The Test Sites meet the requirements in documents ANSI C63.4 and CISPR 22/EN 55022 requirements.

#### 1.3.2 Laboratory accreditation

The test facility is recognized, certified, or accredited by the following organizations:

##### IC Registration No.: 9618B

The 3m alternate test site of Shenzhen CTL Testing Technology Co., Ltd. EMC Laboratory has been registered by Certification and Engineer Bureau of Industry Canada for the performance of with Registration No.: 9618B on November 13, 2013.

##### FCC-Registration No.: 970318

Shenzhen CTL Testing Technology Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 970318, December 19, 2013.

### 1.4. Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 „Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements“ and is documented in the Shenzhen CTL Testing Technology Co., Ltd. quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for CTL laboratory is reported:

Test	Range	Measurement Uncertainty	Notes
Radiated Emission	30~1000MHz	4.10dB	(1)
Radiated Emission	Above 1GHz	4.32dB	(1)
Conducted Disturbance	0.15~30MHz	3.20dB	(1)

- (1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

## 2. GENERAL INFORMATION

### 2.1. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Normal Temperature:	25°C
Relative Humidity:	55 %
Air Pressure:	101 kPa

### 2.2. General Description of EUT

Product Name:	iWiton navigator for gloves
Model/Type reference:	ZYXJ.1.1.1
Power supply:	DC 3.7V from battery
<b>Bluetooth BLE</b>	
Supported type:	Version 4.0 for low Energy
Modulation:	GFSK
Operation frequency:	2402MHz to 2480MHz
Channel number:	40
Channel separation:	2 MHz
Antenna type:	PCB Antenna
Antenna gain:	0dBi
<b>2.4GHz wireless</b>	
Modulation:	GFSK
Operation frequency:	2452MHz
Channel number:	1
Antenna type:	Ceramic antenna
Antenna gain:	0dBi

Note: For more details, please refer to the user's manual of the EUT.

## 2.3. Description of Test Modes and Test Frequency


### Operation Frequency List BT4.0 :

Channel	Frequency (MHz)
<b>00</b>	<b>2402</b>
01	2404
02	2406
:	:
<b>19</b>	<b>2440</b>
:	:
37	2476
38	2478
39	2480

### Operation Frequency List 2.4GHz

Channel	Frequency(MHz)
<b>01</b>	<b>2452</b>

Note: The line display in grey is the channel selected to perform test.





## 2.4. Equipments Used during the Test

Test Equipment	Manufacturer	Model No.	Serial No.	Calibration Date last time	Calibration Date recent	Calibration Due Date
LISN	R&S	ENV216	3560.6550.12	2015/06/02	--	2016/06/01
LISN	R&S	ESH2-Z5	860014/010	2015/06/02	--	2016/06/01
Bilog Antenna	Sunol Sciences Corp.	JB1	A061713	2015/06/02	--	2016/06/01
EMI Test Receiver	R&S	ESCI	103710	2015/06/02	--	2016/06/01
Spectrum Analyzer	Agilent	E4407B	MY41440676	2015/05/21	2016/05/21	2017/05/20
Spectrum Analyzer	Agilent	N9020	US46220290	2016/01/17	--	2017/01/16
Controller	EM Electronics	Controller EM 1000	N/A	2015/05/21	2016/05/21	2017/05/20
Horn Antenna	Sunol Sciences Corp.	DRH-118	A062013	2015/05/19	2016/05/19	2017/05/18
Active Loop Antenna	SCHWARZBEC K	FMZB1519	1519-037	2015/05/19	2016/05/19	2017/05/18
Amplifier	Agilent	8349B	3008A02306	2015/05/19	2016/05/19	2017/05/18
Amplifier	Agilent	8447D	2944A10176	2015/05/19	2016/05/19	2017/05/18
Temperature/Humidity Meter	Gangxing	CTH-608	02	2015/05/20	2016/05/20	2017/05/19
High-Pass Filter	K&L	9SH10-2700/X 12750-O/O	N/A	2015/05/20	2016/05/20	2017/05/19
High-Pass Filter	K&L	41H10-1375/U1 2750-O/O	N/A	2015/05/20	2016/05/20	2017/05/19
Coaxial Cables	HUBER+SUHNER	SUCOFLEX 104PEA-10M	10m	2015/06/02	--	2016/06/01
Coaxial Cables	HUBER+SUHNER	SUCOFLEX 104PEA-3M	3m	2015/06/02	--	2016/06/01
Coaxial Cables	HUBER+SUHNER	SUCOFLEX 104PEA-3M	3m	2015/06/02	--	2016/06/01
RF Cable	Megalon	RF-A303	N/A	2015/06/02	--	2016/06/01

The calibration interval was one year

## 2.5. Related Submittal(s) / Grant(s)

This submittal(s) (test report) is intended to comply with Section 15.249 of the FCC Part 15, Subpart C Rules.

## 2.6. Modifications

No modifications were implemented to meet testing criteria.

### 3. TEST CONDITIONS AND RESULTS

#### 3.1. Conducted Emissions Test


##### LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.207

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\* Decreases with the logarithm of the frequency.

##### TEST CONFIGURATION



##### TEST PROCEDURE


1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. The EUT is a tabletop system; a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10:2013.
2. Support equipment, if needed, was placed as per ANSI C63.10:2013.
3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10:2013.
4. If a EUT received DC power from the USB Port of Notebook PC, the PC's adapter received AC120V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
5. All support equipments received AC power from a second LISN, if any.
6. The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
7. Analyzer / Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes.
8. During the above scans, the emissions were maximized by cable manipulation.

## TEST RESULTS

Remark: Both BLE and 2.4GHz wireless mode were tested, only the worst result of BLE High Channel was reported as below:

### SCAN TABLE: "Voltage (9K-30M) FIN"

Short Description: 150K-30M Voltage



### MEASUREMENT RESULT: "CTL160517104\_fin"

5/17/2016 11:44AM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.150001	46.20	10.2	66	19.8	QP	L1	GND
0.591001	42.00	10.2	56	14.0	QP	L1	GND
0.910501	35.40	10.2	56	20.6	QP	L1	GND
1.491001	33.90	10.3	56	22.1	QP	L1	GND
1.531501	33.90	10.3	56	22.1	QP	L1	GND
2.107501	33.80	10.4	56	22.2	QP	L1	GND


### MEASUREMENT RESULT: "CTL160517104\_fin2"

5/17/2016 11:44AM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.595501	31.80	10.2	46	14.2	AV	L1	GND
0.865501	25.10	10.2	46	20.9	AV	L1	GND
0.910501	25.40	10.2	46	20.6	AV	L1	GND
1.446001	23.50	10.3	46	22.5	AV	L1	GND
2.094001	23.30	10.4	46	22.7	AV	L1	GND
2.121001	23.50	10.4	46	22.5	AV	L1	GND

**SCAN TABLE: "Voltage (9K-30M) FIN"**

Short Description: 150K-30M Voltage

**MEASUREMENT RESULT: "CTL160517105\_fin"**

5/17/2016 11:47AM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.154501	45.80	10.2	66	20.0	QP	N	GND
0.447001	31.70	10.2	57	25.2	QP	N	GND
0.595501	36.30	10.2	56	19.7	QP	N	GND
0.856501	30.80	10.2	56	25.2	QP	N	GND
1.459501	29.00	10.3	56	27.0	QP	N	GND
28.036501	27.70	11.2	60	32.3	QP	N	GND

**MEASUREMENT RESULT: "CTL160517105\_fin2"**

5/17/2016 11:47AM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.280501	22.60	10.2	51	28.2	AV	N	GND
0.600001	25.30	10.2	46	20.7	AV	N	GND
0.901501	19.60	10.2	46	26.4	AV	N	GND
25.993501	22.90	11.2	50	27.1	AV	N	GND
26.713501	22.50	11.2	50	27.5	AV	N	GND
26.772001	23.40	11.2	50	26.6	AV	N	GND

### 3.2. Radiated Emissions and Band Edge

#### Limit

According 15.249, the field strength of emissions from intentional radiators operated within 2400MHz-2483.5 MHz shall not exceed 94dB $\mu$ V/m (50mV/m):

FCC PART 15.249(d) Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.


In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a)

Radiated emission limits


Frequency (MHz)	Distance (Meters)	Radiated (dB $\mu$ V/m)	Radiated ( $\mu$ V/m)
0.009-0.49	3	$20\log(2400/F(\text{KHz}))+40\log(300/3)$	$2400/F(\text{KHz})$
0.49-1.705	3	$20\log(24000/F(\text{KHz}))+40\log(30/3)$	$24000/F(\text{KHz})$
1.705-30	3	$20\log(30)+40\log(30/3)$	30
30-88	3	40.0	100
88-216	3	43.5	150
216-960	3	46.0	200
Above 960	3	54.0	500

#### TEST CONFIGURATION

(A) Radiated Emission Test Set-Up, Frequency Below 30MHz




(B) Radiated Emission Test Set-Up, Frequency below 1000MHz





## (C) Radiated Emission Test Set-Up, Frequency above 1000MHz

**Test Procedure**

1. Below 1GHz measurement the EUT is placed on a turntable which is 0.8m above ground plane, and above 1GHz measurement EUT was placed on a low permittivity and low loss tangent turn table which is 1.5m above ground plane.
2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
3. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
4. The test-receiver system was set to peak and average detects function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.
5. Maximum procedure was performed by raising the receiving antenna from 1m to 4m and rotating the turn table from 0° to 360° to acquire the highest emissions from EUT
6. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
7. Repeat above procedures until all frequency measurements have been completed.

**TEST RESULTS****Remark:**

1. By preliminary testing and verifying three axis (X, Y and Z) position of EUT transmitted status, it was found that "Z axis" position was the worst, and test data recorded in this report.
2. Radiated emission test from 9 KHz to 10th harmonic of fundamental was verified, and no emission found except system noise floor in 9 KHz to 30MHz and not recorded in this report.
3. For Below 1GHz test, Both BLE and 2.4GHz wireless mode were tested, only the worst result of BLE High Channel was reported




## For 30MHz-1GHz

## Horizontal

**SWEEP TABLE: "test (30M-1G)"**

Short Description:		Field Strength			
Start	Stop	Detector	Meas. Time	IF Bandw.	Transducer
30.0 MHz	1.0 GHz	MaxPeak	300.0 ms	120 kHz	JB1

**MEASUREMENT RESULT: "CTL160511731\_red"**


5/12/2016 2:37PM

Frequency MHz	Level dBµV/m	Transd dB	Limit dBµV/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
30.000000	23.00	20.8	40.0	17.0	---	0.0	0.00	HORIZONTAL
74.620000	12.30	8.3	40.0	27.7	---	0.0	0.00	HORIZONTAL
159.980000	17.20	13.6	43.5	26.3	---	0.0	0.00	HORIZONTAL
214.300000	16.90	14.0	43.5	26.6	---	0.0	0.00	HORIZONTAL
538.280000	24.10	20.6	46.0	21.9	---	0.0	0.00	HORIZONTAL
945.680000	30.00	26.5	46.0	16.0	---	0.0	0.00	HORIZONTAL

## Vertical

**SWEEP TABLE: "test (30M-1G)"**

Short Description:		Field Strength			
Start	Stop	Detector	Meas. Time	IF Bandw.	Transducer
30.0 MHz	1.0 GHz	MaxPeak	300.0 ms	120 kHz	JB1

**MEASUREMENT RESULT: "CTL160511730\_red"**

5/12/2016 2:36PM

Frequency MHz	Level dBµV/m	Transd dB	Limit dBµV/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
30.000000	23.10	20.8	40.0	16.9	---	0.0	0.00	VERTICAL
74.620000	13.10	8.3	40.0	26.9	---	0.0	0.00	VERTICAL
134.760000	18.80	14.4	43.5	24.7	---	0.0	0.00	VERTICAL
200.720000	18.20	14.1	43.5	25.3	---	0.0	0.00	VERTICAL
555.740000	25.70	21.1	46.0	20.3	---	0.0	0.00	VERTICAL
943.740000	32.10	26.4	46.0	13.9	---	0.0	0.00	VERTICAL

**For 1GHz to 25GHz****BT4.0 GFSK Mode (above 1GHz)**

Frequency(MHz):				2402		Polarity:			HORIZONTAL	
No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
1	2402.00	89.98	PK	114	24.02	56.58	28.78	4.61	0.00	33.40
1	2402.00	81.55	AV	94	12.45	48.15	28.78	4.61	0.00	33.40
2	2390.00	43.44	PK	74	30.56	10.12	28.72	4.60	0.00	33.32
2	2390.00	--	AV	54	--	--	--	--	--	--
3	2400.00	38.45	PK	74	35.55	5.06	28.78	4.61	0.00	33.39
3	2400.00	--	AV	54	--	--	--	--	--	--
4	4804.00	49.25	PK	74	24.75	44.74	33.49	6.91	35.89	4.51
4	4804.00	--	AV	54	--	--	--	--	--	--
5	5125.75	40.15	PK	74	33.85	32.94	34.38	7.10	34.28	7.21
5	5125.75	--	AV	54	--	--	--	--	--	--
6	7206.00	47.21	PK	74	26.79	36.10	36.95	9.18	35.03	11.11
6	7206.00	--	AV	54	--	--	--	--	--	--

Frequency(MHz):				2402		Polarity:			VERTICAL	
No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
1	2402.00	88.41	PK	114	25.59	55.01	28.78	4.61	0.00	33.40
1	2402.00	81.26	AV	94	12.74	47.86	28.78	4.61	0.00	33.40
2	2390.00	42.55	PK	74	31.45	9.23	28.72	4.60	0.00	33.32
2	2390.00	--	AV	54	--	--	--	--	--	--
3	2400.00	38.54	PK	74	35.46	5.15	28.78	4.61	0.00	33.39
3	2400.00	--	AV	54	--	--	--	--	--	--
4	4804.00	49.31	PK	74	24.69	44.80	33.49	6.91	35.89	4.51
4	4804.00	--	AV	54	--	--	--	--	--	--
5	5011.25	40.20	PK	74	33.8	33.38	34.02	7.04	34.23	6.82
5	5011.25	--	AV	54	--	--	--	--	--	--
6	7206.00	46.48	PK	74	27.52	35.37	36.95	9.18	35.03	11.11
6	7206.00	--	AV	54	--	--	--	--	--	--

**REMARKS:**

1. Emission level (dBuV/m) =Raw Value (dBuV)+Correction Factor (dB/m)
2. Correction Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor
3. Margin value = Limit value- Emission level.
4. -- Mean the PK detector measured value is below average limit.
5. The other emission levels were very low against the limit.
6. RBW1MHz VBW3MHz Peak detector is for PK value; RBW 1MHz VBW10Hz Peak detector is for AV value.

Frequency(MHz):				2440		Polarity:			HORIZONTAL	
No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
1	2440.00	89.14	PK	114	24.86	55.63	28.85	4.65	0.00	33.51
1	2440.00	81.25	AV	94	12.75	47.74	28.85	4.65	0.00	33.51
2	3956.75	38.29	PK	74	35.71	33.58	33.19	6.35	34.83	4.71
2	3956.75	--	AV	54	--	--	--	--	--	--
3	4880.00	48.22	PK	74	25.78	41.86	33.60	6.95	34.19	6.36
3	4880.00	--	AV	54	--	--	--	--	--	--
4	5235.50	40.51	PK	74	33.49	32.87	34.58	7.16	34.10	7.64
4	5235.50	--	AV	54	--	--	--	--	--	--
5	7320.00	41.86	PK	74	32.14	30.17	37.46	9.23	35.00	11.69
5	7320.00	--	AV	54	--	--	--	--	--	--

Frequency(MHz):				2440		Polarity:			VERTICAL	
No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
1	2440.00	89.21	PK	114	24.79	55.70	28.85	4.65	0.00	33.51
1	2440.00	81.55	AV	94	12.45	48.04	28.85	4.65	0.00	33.51
2	3525.50	38.40	PK	74	35.60	35.72	31.95	5.86	35.13	2.68
2	3525.50	--	AV	54	--	--	--	--	--	--
3	4880.00	48.29	PK	74	25.71	41.93	33.60	6.95	34.19	6.36
3	4880.00	--	AV	54	--	--	--	--	--	--
4	5225.50	40.54	PK	74	33.46	32.92	34.57	7.16	34.10	7.62
4	5225.50	--	AV	54	--	--	--	--	--	--
5	7320.00	42.45	PK	74	31.55	30.76	37.46	9.23	35.00	11.69
5	7320.00	--	AV	54	--	--	--	--	--	--

## REMARKS:

1. Emission level (dBuV/m) =Raw Value (dBuV)+Correction Factor (dB/m)
2. Correction Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor
3. Margin value = Limit value- Emission level.
4. -- Mean the PK detector measured value is below average limit.
5. The other emission levels were very low against the limit.
6. RBW1MHz VBW3MHz Peak detector is for PK value; RBW 1MHz VBW10Hz Peak detector is for AV value.

Frequency(MHz):				2480		Polarity:			HORIZONTAL	
No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
1	2480.00	88.41	PK	114	25.59	54.79	28.92	4.70	0.00	33.62
1	2480.00	81.26	AV	94	12.74	47.64	28.92	4.70	0.00	33.62
2	2483.50	40.12	PK	74	33.88	6.49	28.93	4.70	0.00	33.63
2	2483.50	--	AV	54	--	--	--	--	--	--
3	2500.00	37.52	PK	74	36.48	3.84	28.96	4.72	0.00	33.68
3	2500.00	--	AV	54	--	--	--	--	--	--
4	4960.00	48.26	PK	74	25.74	43.34	33.84	7.00	35.92	4.92
4	4960.00	--	AV	54	--	--	--	--	--	--
5	5145.75	40.14	PK	74	33.86	32.88	34.43	7.11	34.28	7.26
5	5145.75	--	AV	54	--	--	--	--	--	--
6	7440.00	43.12	PK	74	30.88	31.17	37.64	9.28	34.97	11.95
6	7440.00	--	AV	54	--	--	--	--	--	--

Frequency(MHz):				2480		Polarity:			VERTICAL	
No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
1	2480.00	87.85	PK	114	26.15	54.23	28.92	4.70	0.00	33.62
1	2480.00	81.33	AV	94	12.67	47.71	28.92	4.70	0.00	33.62
2	2483.50	40.41	PK	74	33.59	6.78	28.93	4.70	0.00	33.63
2	2483.50	--	AV	54	--	--	--	--	--	--
3	2500.00	37.21	PK	74	36.79	3.53	28.96	4.72	0.00	33.68
3	2500.00	--	AV	54	--	--	--	--	--	--
4	4960.00	48.39	PK	74	25.61	43.47	33.84	7.00	35.92	4.92
4	4960.00	--	AV	54	--	--	--	--	--	--
5	5210.50	41.74	PK	74	32.26	34.35	34.55	7.15	34.31	7.39
5	5210.50	--	AV	54	--	--	--	--	--	--
6	7440.00	43.55	PK	74	30.45	31.60	37.64	9.28	34.97	11.95
6	7440.00	--	AV	54	--	--	--	--	--	--

## REMARKS:

1. Emission level (dBuV/m) =Raw Value (dBuV)+Correction Factor (dB/m)
2. Correction Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor
3. Margin value = Limit value- Emission level.
4. -- Mean the PK detector measured value is below average limit.
5. The other emission levels were very low against the limit.
6. RBW1MHz VBW3MHz Peak detector is for PK value; RBW 1MHz VBW10Hz Peak detector is for AV value.



**2.4GHz wireless GFSK Mode (above 1GHz)**

Frequency(MHz):				2452		Polarity:			HORIZONTAL	
No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
1	2452.00	86.52	PK	114	27.48	52.98	28.87	4.67	0.00	33.54
1	2452.00	80.14	AV	94	13.86	46.60	28.87	4.67	0.00	33.54
2	2390.00	37.26	PK	74	36.74	3.94	28.72	4.60	0.00	33.32
2	2390.00	--	AV	54	--	--	--	--	--	--
3	2400.00	38.52	PK	74	35.48	5.13	28.78	4.61	0.00	33.39
3	2400.00	--	AV	54	--	--	--	--	--	--
4	2483.50	39.68	PK	74	34.32	6.05	28.93	4.70	0.00	33.63
4	2483.50	--	AV	54	--	--	--	--	--	--
5	2500.00	39.66	PK	74	34.34	5.98	28.96	4.72	0.00	33.68
5	2500.00	--	AV	54	--	--	--	--	--	--
6	4904.00	55.24	PK	74	18.76	48.92	33.64	6.96	34.28	6.32
6	4904.00	47.36	AV	54	6.64	41.04	33.64	6.96	34.28	6.32
7	5025.75	50.15	PK	74	23.85	43.27	34.07	7.05	34.24	6.88
7	5025.75	--	AV	54	--	--	--	--	--	--
8	7356.00	49.63	PK	74	24.37	37.84	37.54	9.24	34.99	11.79
8	7356.00	--	AV	54	--	--	--	--	--	--

Frequency(MHz):				2452		Polarity:			VERTICAL	
No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
1	2452.00	86.69	PK	114	27.31	53.15	28.87	4.67	0.00	33.54
1	2452.00	81.52	AV	94	12.48	47.98	28.87	4.67	0.00	33.54
2	2390.00	39.65	PK	74	34.35	6.33	28.72	4.60	0.00	33.32
2	2390.00	--	AV	54	--	--	--	--	--	--
3	2400.00	38.45	PK	74	35.55	5.06	28.78	4.61	0.00	33.39
3	2400.00	--	AV	54	--	--	--	--	--	--
4	2483.50	38.21	PK	74	35.79	4.58	28.93	4.70	0.00	33.63
4	2483.50	--	AV	54	--	--	--	--	--	--
5	2500.00	37.66	PK	74	36.34	3.98	28.96	4.72	0.00	33.68
5	2500.00	--	AV	54	--	--	--	--	--	--
6	4904.00	54.89	PK	74	19.11	48.57	33.64	6.96	34.28	6.32
6	4904.00	48.23	AV	54	5.77	41.91	33.64	6.96	34.28	6.32
7	5133.50	51.23	PK	74	22.77	44.00	34.40	7.11	34.28	7.23
7	5133.50	--	AV	54	--	--	--	--	--	--
8	7356.00	49.30	PK	74	24.7	37.51	37.54	9.24	34.99	11.79
8	7356.00	--	AV	54	--	--	--	--	--	--

**REMARKS:**

1. Emission level (dBuV/m) =Raw Value (dBuV)+Correction Factor (dB/m)
2. Correction Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor
3. Margin value = Limit value- Emission level.
4. -- Mean the PK detector measured value is below average limit.

5. The other emission levels were very low against the limit.
6. RBW1MHz VBW3MHz Peak detector is for PK value; RBW 1MHz VBW10Hz Peak detector is for AV value.






### 3.3. Occupied Bandwidth Measurement

#### Limit

N/A

#### Test Configuration



#### Test Procedure

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 30 KHz RBW and 100 KHz VBW.

The 20dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20dB.

#### Test Results

##### **BT4.0**

Modulation	Channel	99% OBW (MHz)	20dB bandwidth (MHz)	Result
GFSK	CH00	1.067	1.175	Pass
	CH19	1.069	1.214	
	CH39	1.094	1.190	


##### **2.4GHz wireless**

Modulation	Frequency (MHz)	99% OBW (MHz)	20dB bandwidth (MHz)	Result
GFSK	2452	0.835	0.885	Pass


Test plot as follows:

BT4.0


GFSK Modulation



CH00




CH19



CH39

2.4GHz wireless  
GFSK Modulation



### 3.4. Antenna Requirement

#### Standard Applicable


For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

#### **Refer to statement below for compliance.**

The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.

#### Antenna Connected Construction

The antenna used in this product is an internal Antenna, The directional gains of antenna used for transmitting is 0 dBi.





#### 4. Test Setup Photos of the EUT








## 5. External and Internal Photos of the EUT

### External Photos of EUT














Internal Photos of EUT

\*\*\*\*\* End of Report \*\*\*\*\*